

Web Services API Specification

RemitONE Money Transfer Management Solution

Version 1.10
February 2016

Table of Contents

1.Introduction....6
Connection Parameters....6
Response Format....7
Listing of provided Web Services....8
Admin API....8
Sending Agent API....8
Receiving Bank/Agent API....9
2.Web Service Method Details....10
Admin API....10
getSourceCountries....10
getDestinationCountries....10
getSellRates....11
getAgents....12
getAgentRates....13
getAgentCharges....14
getCountryCharges....15
getTransactionStatus....16
getTransactionStatusByAgentTransRef....17
getDeliveryBanks....17
getDeliveryBankBranches....18
createDeliveryBankBranch....19
updateDeliveryBankBranch....20
getCollectionPoints....21
createCollectionPoint....22
updateCollectionPoint....23
getTransactions....25
assignTransactions....26
getErrorTransactions....27
processCashCollectionTransactionByBank....28
requestCancellation....28
getMobileNetworkOperators....29
createMobileNetworkCreditType....30
updateMobileNetworkCreditType....31
uploadCSVData....32
Sending Agent API....34
getAgentDetails....34
getDestinationCountries....34
getRates....35
getCurrentCredit....36
createRemitter....36
searchRemitter....38

updateRemitter....39
createBeneficiary....41
searchBeneficiary....43
getRemitterBeneficiaries....44
updateBeneficiary....45
assignBeneficiary....47
createTransaction....47
confirmTransaction....50
insertTransaction....50
getTransactionDetails....53
getRemitterTransactions....56
getTransactionStatus....57
getTransactionStatusByAgentTransRef....58
getCharges....59
getDeliveryBanks....60
getDeliveryBankBranches....61
getCollectionPoints....61
transactionPaymentCleared....62
getCashCollectionTransactionDetails....63
processCashCollectionTransaction....65
getErrorTransactions....66
requestCancellation....67
Receiving Bank/Agent API....69
getPayoutTransactions....69
getPayoutTransactionDetails....72
acceptPayoutTransactions....74
getPendingPayoutTransactions....78
processPayoutTransaction....81
errorPayoutTransaction....82
getErrorTransactions....83
3.Testing Web Services Functionality....85
Using Web Services in a Live Environment: Some suggestions....85
Appendix A : Destination Country ISO Codes....87
Appendix B : Remitter ID Type Codes....94
Appendix C : Beneficiary ID Type Codes....94
Appendix D : Payment Method Codes....94
Appendix E : Service Level (Delivery Speed) Codes....95
Appendix F : Source of Income Codes....95
Appendix G : Remittance Purpose Codes....95
Appendix H : Transaction Statuses....96

1.Introduction

The RemitONE WebServices Infrastructure uses the REST protocol. Our services use the POST method for invoking the service, and hence all data must be provided as POST variables. The response is provided as structured XML.

This document outlines the input and output parameters for each of the RemitONE WebServices.

Connection Parameters

The BASE_URL is the URL at which the WebServices are hosted. This BASE_URL is then followed by the required GROUP name, and then the required METHOD name.

For example,
BASE_URL = https://www.remitone.com/ws/

GROUP = transaction
METHOD = createTransaction

This would give a complete URL of :
https://www.remitone.com/ws/transaction/createTransaction

The client application would need to make a POST to this URL to invoke this particular WebService. *In the specification below, a * indicates a required input parameter.*

Every invocation must contain the following parameters (as POST variables) :

Name	Type	Notes
username *	Text	
password *	Text	
pin *	Text	

These will be provided to you when your WebService Account is activated.

All other parameters will depend on the particular WebService being invoked.

Response Format

A Successful Response will always contain the following XML structure :

```
<?xml version="1.0" encoding="utf-8"?>
<response>
    <status>SUCCESS</status>
    <result>
        [Specific response for the particular Web Service]
    </result>
</response>
```

An Error Response is as follows :

```
<?xml version="1.0" encoding="utf-8"?>
<response>
    <status>FAIL</status>
    <result>
        <message>[Error message]</message>
    </result>
</response>
```

An Error Response with Validation errors is as follows :

```
<?xml version="1.0" encoding="utf-8"?>
<response>
    <status>FAIL</status>
    <result>
        <message>VALIDATION FAILED</message>
        <errors>
            <error>[Validation error message]</error>
            <error>[Validation error message]</error>
            <error>[Validation error message]</error>
        </errors>
    </result>
</response>
```

Listing of provided Web Services

Admin API

1. getSourceCountries
2. getDestinationCountries
3. getSellRates
4. getAgents
5. getAgentRates
6. getAgentCharges
7. getCountryCharges
8. getTransactionStatus
9. getTransactionStatusByAgentTransRef
10. getDeliveryBanks
11. getDeliveryBankBranches
12. getCollectionPoints

Sending Agent API

1. getAgentDetails
2. getDestinationCountries
3. getRates

4.getCurrentCredit

5. createRemitter
6. searchRemitter

7.updateRemitter

8. createBeneficiary
9. searchBeneficiary
10. updateBeneficiary
11. assignBeneficiary
12. createTransaction
13. confirmTransaction
14. insertTransaction
15. getTransactionStatus
16. getTransactionStatusByAgentTransRef
17. getCharges
18. getDeliveryBanks
19. getDeliveryBankBranches
20. getCollectionPoints

21. transactionPaymentCleared
22. getCashCollectionTransactionDetails
23. processCashCollectionTransaction

Receiving Bank/Agent API

---

1. getPayoutTransactions
2. getPayoutTransactionDetails
3. acceptPayoutTransactions
4. getPendingPayoutTransactions
5. processPayoutTransaction
6. errorPayoutTransaction

2.Web Service Method Details

Admin API

getSourceCountries

Group : **admin**
Method : **getSourceCountries**
This method provides a list of available source countries on the system.

Input fields :

none (apart from username, password and pin which are required in every invocation).

Example Output XML :

```
<?xml version="1.0" encoding="utf-8"?>
<response>
    <status>SUCCESS</status>
    <result>
        <countries>
            <country>
                <id>001</id>
                <name>United Kingdom</name>
                <iso_code>UK</iso_code>
                <currency>GBP</currency>
                <allowed_currencies>
                    <currency>GBP</currency>
                </allowed_currencies>
            </country>
            <country>
                <id>002</id>
                <name>United States</name>
                <iso_code>US</iso_code>
                <currency>USD</currency>
                <allowed_currencies>
                    <currency>USD</currency>
                </allowed_currencies>
            </country>
        </countries>
    </result>
</response>
```

---

getDestinationCountries

Group : **country**
Method : **getDestinationCountries**
This method provides a list of available destination countries on the system.

Input fields :
none (apart from username, password and pin which are required in every invocation).

Example Output XML :

```
<?xml version="1.0" encoding="utf-8"?>
<response>
    <status>SUCCESS</status>
    <result>
        <countries>
            <country>
                <id>998</id>
                <name>Bangladesh</name>
                <iso_code>BD</iso_code>
                <currency>BDT</currency>
                <allowed_currencies>
                    <currency>BDT</currency>
                </allowed_currencies>
            </country>
            <country>
                <id>999</id>
                <name>Philippines</name>
                <iso_code>PH</iso_code>
                <currency>PHP</currency>
                <allowed_currencies>
                    <currency>PHP</currency>
                </allowed_currencies>
            </country>
        </countries>
    </result>
</response>
```

---

getSellRates

Group : **admin**
Method : **getSellRates**
This method provides current rates from the system for the source and destination countries provided.

Input fields:

Name	Type	Notes
source_country *	Text	The name of the Source Country, as per the output of **getSourceCountries**.
destination_country *	Text	The name of the Destination Country, as per the output of **getDestinationCountries**.

source_currency	Text	The 3 letters ISO currency code, as listed in **Appendix A**
destination_currency	Text	The 3 letters ISO currency code, as listed in **Appendix A**
delivery_bank	Text	The name of the delivery bank, as per the output of **getDeliveryBanks**.

Example Output XML :

```
<?xml version="1.0" encoding="utf-8"?>
<response>
    <status>SUCCESS</status>
    <result>
        <rate>
            <account>39.5000</account>
            <cash_collection>39.0000</cash_collection>
            <card>39.5000</card>
            <home_delivery>38.0000</home_delivery>
            <utility_bill>39.6000</utility_bill>
            <mobile_transfer>36.0000</mobile_transfer>
        </rate>
    </result>
</response>
```

---

getAgents

Group : **admin**
Method : **getAgents**
This method provides a list of available agents on the system.

Input fields :
none (apart from username, password and pin which are required in every invocation).

Example Output XML :

```
<?xml version="1.0" encoding="utf-8"?>
<response>
      <responseId>4</responseId>
      <status>SUCCESS</status>
      <result>
            <agents>
                  <agent>
                        <name>Test Agent</name>
                        <username>testagent</username>
                        <code>2000</code>
                        <country>Singapore</country>
                  </agent>
```

```
                    <agent>
                          <name>PRIME EXCHANGE CO PTE LTD</name>
                          <username>primex</username>
                          <code>2007</code>
                          <country>Singapore</country>
                    </agent>
              </agents>
      </result>
</response>
```

---

getAgentRates

Group : **admin**
Method : **getAgentRates**
This method provides the current rates for an agent on the system.

Input fields:

Name	Type	Notes
agent_code *	Code	The Agent code, as per the output of **getAgents**.
dest_country *	Text	The name of the Destination Country, as per the output of **getDestinationCountries**.
source_currency	Text	The 3 letters ISO currency code, as listed in **Appendix A**
destination_currency	Text	The 3 letters ISO currency code, as listed in **Appendix A**
delivery_bank	Text	The name of the delivery bank, as per the output of **getDeliveryBanks**.

Example Output XML :

```
<?xml version="1.0" encoding="utf-8"?>
<response>
    <status>SUCCESS</status>
    <result>
        <rate>
            <account>39.5000</account>
            <cash_collection>39.0000</cash_collection>
            <card>39.5000</card>
            <home_delivery>38.0000</home_delivery>
            <utility_bill>39.6000</utility_bill>
            <mobile_transfer>36.0000</mobile_transfer>
        </rate>
    </result>
```

```
</response>
```

getAgentCharges

Group: **admin**
Method: **getAgentCharges**

Input fields:

Name	Type	Notes
agent_code *	Code	The Agent code, as per the output of **getAgents**.
destination_country *	Text	Name of country retrieved from calling **getDestinationCountries**
source_currency	Text	The 3 letters ISO currency code, as listed in **Appendix A**
destination_currency	Text	The 3 letters ISO currency code, as listed in **Appendix A**
trans_type *	Text	Account / Cash Collection / Card Transfer / Home Delivery / Mobile Transfer
payment_method *	Code	See Appendix D for codes.
service_level *	Code	See Appendix E for codes.
delivery_bank	Text	The name of the delivery bank, as per the output of **getDeliveryBanks**.
sms_confirmation *	Boolean	t / f
sms_notification *	Boolean	t / f
amount_type *		Whether the amount is specified in the source currency or the destination currency. Possible values : SOURCE / DESTINATION.
amount_to_send *	Numeric	

Example Output XML :

```
<?xml version="1.0" encoding="utf-8"?>
<response>
    <status>SUCCESS</status>
    <result>
        <source_currency>GBP</source_currency>
        <source_amount>100</source_amount>
```

```
        <rate>37.53</rate>
        <destination_currency>PHP</destination_currency>
        <destination_amount>3753.00</destination_amount>
        <commission>10.50</commission>
        <agent_fee>0.00</agent_fee>
        <hq_fee>0.50</hq_fee>
        <total_charges>11.00</total_charges>
        <tax>3.40</tax>
    </result>
</response>
```

---

getCountryCharges

Group: **admin**
Method: **getCountryCharges**

Input fields:

Name	Type	Notes
source_country *	Text	Name of country retrieved from calling **getSourceCountries**
destination_country *	Text	Name of country retrieved from calling **getDestinationCountries**
source_currency	Text	The 3 letters ISO currency code, as listed in **Appendix A**
destination_currency	Text	The 3 letters ISO currency code, as listed in **Appendix A**
trans_type *	Text	Account / Cash Collection / Card Transfer / Home Delivery / Mobile Transfer
payment_method *	Code	See Appendix D for codes.
service_level *	Code	See Appendix E for codes.
delivery_bank	Text	The name of the delivery bank, as per the output of **getDeliveryBanks**.
sms_confirmation *	Boolean	t / f
sms_notification *	Boolean	t / f
amount_type *		Whether the amount is specified in the source currency or the destination currency. Possible values : SOURCE / DESTINATION.
amount_to_send *	Numeric	

Example Output XML :

```
<?xml version="1.0" encoding="utf-8"?>
<response>
    <status>SUCCESS</status>
    <result>
        <source_currency>GBP</source_currency>
        <source_amount>100</source_amount>
        <rate>37.53</rate>
        <destination_currency>PHP</destination_currency>
        <destination_amount>3753.00</destination_amount>
        <commission>10.50</commission>
        <agent_fee>0.00</agent_fee>
        <hq_fee>0.50</hq_fee>
        <total_charges>11.00</total_charges>
        <tax>3.40</tax>
    </result>
</response>
```

---

getTransactionStatus

Group: **transaction**
Method: **getTransactionStatus**

Input fields:

Name	Type	Notes
trans_ref *	Text	

Example Output XML :

```
<?xml version="1.0" encoding="utf-8"?>
<response>
    <status>SUCCESS</status>
    <result>
        <trans_ref>RA0003101</trans_ref>
        <agent_trans_ref>ABC12345678</agent_trans_ref>
        <benef_trans_ref>ABC12345678</benef_trans_ref>
        <status>SENT_FOR_PAY</status>
        <compliance_check_required>f</compliance_check_required>
        <compliance_checked>f</compliance_checked>
    </result>
</response>
```

---

getTransactionStatusByAgentTransRef

Group: **transaction**
Method: **getTransactionStatusByAgentTransRef**

Input fields:

Name	Type	Notes
trans_ref *	Text	Agent's unique transaction reference (if provided at the time of creation). See getTransactionStatus above to request the transaction status using the RemitONE's transaction reference.

Example Output XML :

```
<?xml version="1.0" encoding="utf-8"?>
<response>
    <status>SUCCESS</status>
    <result>
        <trans_ref>RA0003101</trans_ref>
        <agent_trans_ref>ABC12345678</agent_trans_ref>
        <benef_trans_ref>ABC12345678</benef_trans_ref>
        <status>SENT_FOR_PAY</status>
        <compliance_check_required>f</compliance_check_required>
        <compliance_checked>f</compliance_checked>
    </result>
</response>
```

---

getDeliveryBanks

Group: **deliveryBank**
Method: **getDeliveryBanks**

Input fields:

Name	Type	Notes
dest_country	Text	The name of the Destination Country, as per the output of **getDestinationCountries**.

Example Output XML :

```
<?xml version="1.0" encoding="utf-8"?>
<response>
    <responseId>42</responseId>
    <status>SUCCESS</status>
    <result>
        <delivery_banks>
            <delivery_bank>
                <bank_id>14</bank_id>
                <name>delivery bank</name>
                <country_id>999</country_id>
                <bank_code>del123</bank_code>
                <swift_code>sw123</swift_code>
                <address>address 123</address>
                <city>city123</city>
                <state>state123</state>
                <telephone>123</telephone>
                <account_number_mask>123</account_number_mask>
                <enabled>t</enabled>
            </delivery_bank>
        </delivery_banks>
    </result>
</response>
```

---

getDeliveryBankBranches

Group: **deliveryBankBranch**
Method: **getDeliveryBankBranches**

Input fields:

Name	Type	Notes
delivery_bank	Text	The name of the delivery bank, as per the output of **getDeliveryBanks**.

```
<?xml version="1.0" encoding="utf-8"?>
<response>
    <responseId>44</responseId>
    <status>SUCCESS</status>
    <result>
        <delivery_bank_branches>
            <delivery_bank_branch>
                <id>1</id>
                <name>Branch123</name>
                <branch_code>BRANCH-123</branch_code>
                <enabled>t</enabled>
                <delivery_bank>1</delivery_bank>
```

```
                <city>city123</city>
                <state>state123</state>
                <telephone>012345678</telephone>
                <manager>manager123</manager>
            </delivery_bank_branch>
        </delivery_bank_branches>
    </result>
</response>
```

---

createDeliveryBankBranch

Group: **deliveryBankBranch**
Method: **createDeliveryBankBranch**

Input fields:

Name	Type	Notes
name	Text	The name of the delivery bank branch.
branch_code	Text	The code of the delivery bank branch.
enabled	Boolean	Enable/Disable this delivery bank branch.
bank	Text	The name of the delivery bank, as per the output of **getDeliveryBanks**.
address	Text	The address of the delivery bank branch.
city	Text	The city of the delivery bank branch.
state	Text	The state of the delivery bank branch.
telephone	Text	The telephone number of the delivery bank branch prefixed by + or 00 followed by the country code.
manager	Text	The manager's name of the delivery bank branch.
email	Text	The email of the delivery bank branch.
third_party_id	Text	An optional third party identifier.

```
<?xml version="1.0" encoding="utf-8"?>
<response>
    <responseId>44</responseId>
    <status>SUCCESS</status>
    <result>
```

```
        <id>1</id>
        <name>My Collection Point</name>
        <branch_code>CODE</branch_code>
        <enabled>t</enabled>
        <delivery_bank>1</delivery_bank>
        <address>123 Street</address>
        <city>London</city>
        <state>London</state>
        <telephone>004412356789</telephone>
        <manager>John Doe</manager>
        <email>delivery@bank.branch</email>
        <third_party_id>123</third_party_id>
    </result>
</response>
```

---

updateDeliveryBankBranch

Group: **deliveryBankBranch**
Method: **updateDeliveryBankBranch**

Input fields:

Name	Type	Notes
id	Integer	The id of the delivery bank branch.
name	Text	The name of the delivery bank branch.
branch_code	Text	The code of the delivery bank branch.
enabled	Boolean	Enable/Disable this delivery bank branch.
bank	Text	The name of the delivery bank, as per the output of **getDeliveryBanks**.
address	Text	The address of the delivery bank branch.
city	Text	The city of the delivery bank branch.
state	Text	The state of the delivery bank branch.
telephone	Text	The telephone number of the delivery bank branch prefixed by + or 00 followed by the country code.
manager	Text	The manager's name of the delivery bank branch.
email	Text	The email of the delivery bank branch.
third_party_id	Text	An optional third party identifier.

```
<?xml version="1.0" encoding="utf-8"?>
<response>
    <responseId>44</responseId>
    <status>SUCCESS</status>
    <result>
        <id>1</id>
        <name>My Collection Point</name>
        <branch_code>CODE</branch_code>
        <enabled>t</enabled>
        <delivery_bank>1</delivery_bank>
        <address>123 Street</address>
        <city>London</city>
        <state>London</state>
        <telephone>004412356789</telephone>
        <manager>John Doe</manager>
        <email>delivery@bank.branch</email>
        <third_party_id>123</third_party_id>
    </result>
</response>
```

---

getCollectionPoints

Group: **collectionPoint**
Method: **getCollectionPoints**

Input fields:

Name	Type	Notes
delivery_bank	Text	The name of the delivery bank, as per the output of **getDeliveryBanks**.

```
<?xml version="1.0" encoding="utf-8"?>
<response>
    <responseId>45</responseId>
    <status>SUCCESS</status>
    <result>
        <collection_points>
            <collection_point>
                <collection_id>1</collection_id>
                <name>colltion123</name>
                <bank>Bank 123</bank>
                <delivery_bank>1</delivery_bank>
                <address>address123</address>
                <city>city123</city>
                <state>state123</state>
                <country_id>123</country_id>
```

```
                <code>COLLECTION-123</code>
                <telephone>012345678</telephone>
                <fax>fax123</fax>
                <email>email123</email>
                <working_hours>1</working_hours>
                <contact_person>person123</contact_person>
                <default_in_country>t</default_in_country>
                <enabled>t</enabled>
                <collection_pin_prefix>123</collection_pin_prefix>
                <rate_markup>1</rate_markup>
            </collection_point>
        </collection_points>
    </result>
</response>
```

---

createCollectionPoint

Group: **collectionPoint**
Method: **createCollectionPoint**

Input fields:

Name	Type	Notes
name	Text	The name of the collection point.
bank	Text	The name of the delivery bank, as per the output of **getDeliveryBanks**.
country_id	Integer	The id of the Destination Country, as per the output of **getDestinationCountries**.
code	Text	The code of the collection point.
address	Text	The address of the collection point.
city	Text	The city of the collection point.
state	Text	The state of the collection point.
telephone	Text	The telephone number of the collection point prefixed by + or 00 followed by the country code.
fax	Text	The fax number of the collection point prefixed by + or 00 followed by the country code.
email	Text	The email of the collection point.

working_hours	Text	The working hours of the collection point.
contact_person	Text	The name of the person to contact in the collection point.
default_in_country	Boolean	Set this collection point as the default one for the specified country.
enabled	Boolean	Enable/Disable this collection point.

```
<?xml version="1.0" encoding="utf-8"?>
<response>
    <responseId>42</responseId>
    <status>SUCCESS</status>
    <result>
        <collection_id>1</collection_id>
        <name>My Collection Point</name>
        <bank>My delivery Bank</bank>
        <delivery_bank>1</delivery_bank>
        <address>123 Street</address>
        <city>London</city>
        <state>London</state>
        <country_id>999</country_id>
        <code>CODE</code>
        <telephone>0044123456789</telephone>
        <fax>0044123456789</fax>
        <email>collection@point.com</email>
        <working_hours>8am to 7pm</working_hours>
        <contact_person>John Doe</contact_person>
        <default_in_country>f</default_in_country>
        <enabled>t</enabled>
        <collection_pin_prefix>CP</collection_pin_prefix>
        <rate_markup></rate_markup>
    </result>
</response>
```

---

updateCollectionPoint

Group: **collectionPoint**
Method: upda**teCollectionPoint**

Input fields:

Name	**Type**	**Notes**
collection_id	Integer	The id of the collection point.
name	Text	The name of the collection point.

bank	Text	The name of the delivery bank, as per the output of **getDeliveryBanks**.
country_id	Integer	The id of the Destination Country, as per the output of **getDestinationCountries**.
code	Text	The code of the collection point.
address	Text	The address of the collection point.
city	Text	The city of the collection point.
state	Text	The state of the collection point.
telephone	Text	The telephone number of the collection point prefixed by + or 00 followed by the country code.
fax	Text	The fax number of the collection point prefixed by + or 00 followed by the country code.
email	Text	The email of the collection point.
working_hours	Text	The working hours of the collection point.
contact_person	Text	The name of the person to contact in the collection point.
default_in_country	Boolean	Set this collection point as the default one for the specified country.
enabled	Boolean	Enable/Disable this collection point.

```
<?xml version="1.0" encoding="utf-8"?>
<response>
    <responseId>42</responseId>
    <status>SUCCESS</status>
    <result>
        <collection_id>1</collection_id>
        <name>My Collection Point</name>
        <bank>My delivery Bank</bank>
        <delivery_bank>1</delivery_bank>
        <address>123 Street</address>
        <city>London</city>
        <state>London</state>
        <country_id>999</country_id>
        <code>CODE</code>
        <telephone>0044123456789</telephone>
        <fax>0044123456789</fax>
        <email>collection@point.com</email>
        <working_hours>8am to 7pm</working_hours>
        <contact_person>John Doe</contact_person>
        <default_in_country>f</default_in_country>
        <enabled>t</enabled>
        <collection_pin_prefix>CP</collection_pin_prefix>
        <rate_markup></rate_markup>
```

```
    </result>
</response>
```

---

getTransactions

Group : **transaction**
Method : **getTransactions**

Input fields :

Name	Type	Notes
from_date	Date	YYYY-MM-DD (Either this date is required or the processed_from_date)
to_date	Date	YYYY-MM-DD (Either this date is required or the processed_to_date)
processed_from_date	Date Time	YYYY-MM-DD HH:MM
processed_to_date	Date Time	YYYY-MM-DD HH:MM
country_code	Text	2 letter country ISO code. (Country code as set-up in the system)
country_type	Text	SOURCE / DESTINATION (Required if country_code is provided)
trans_corridor	Text	ALL / INTERNATIONAL / DOMESTIC (If not provided, will default to ALL)
compliance_needed	Boolean	t/f

Example Output XML :

```
<?xml version="1.0" encoding="utf-8"?>
<response>
      <status>SUCCESS</status>
      <result>
            <count>1</count>
            <transactions>
                  <transaction>
                        <trans_ref>RA20079112</trans_ref>
                        <trans_type>Account</trans_type>
                        <status>HQ_OK</status>
                        <creation_date>2010-05-07 16:25:12.26266</creation_date>
                        <processed_date>2010-05-09 16:25:12</processed_date>
                        <originating_country>SG</originating_country>
                        <destination_country>BD</destination_country>
```

```
                        <source_currency>SGD</source_currency>
                        <source_amount>85.00</source_amount>
                        <commission>5.00</commission>
                        <tax>5.00</tax>
                        <dest_currency>BDT</dest_currency>
                        <dest_amount>4188.80</dest_amount>
                        <rate>49.2800</rate>
                        <remitter_name>ALI IMAN</remitter_name>
                        <remitter_id>1210</remitter_id>
                        <payment_method>1</payment_method>
                        <benef_name>HASSAN SYFULLAH</benef_name>
                         <benef_mobile>07512457841</benef_mobile>
                        <source_agent_name>JOE BLOGGS</source_agent_name>
                        <source_agent_teller_name>JOHN
TELLER</source_agent_teller_name>
                        <bank_buy_rate>53.3200</rate>
                        <source_conv_rate>48.1400</source_conv_rate>
                        <dest_conv_rate>49.2800</dest_conv_rate>
                        <compliance_needed>f</compliance_needed>
                         <compliance_checked>f</compliance_checked>
                </transaction>
            </transactions>
      </result>
</response>
```

---

assignTransactions

Group : **transaction**
Method : **assignTransactions**

Input fields :

Name	Type	Notes
trans_refs	Text	Comma separated list of transaction references. I.e. **RA123451234** or **RA123451234, RA123451251, RA123453614**
proc_bank_name	Text	Name of the Processing Bank (Abbreviated Bank Name)

Example Output XML :

```
<?xml version="1.0" encoding="utf-8"?>
<response>
```

```
        <responseId>326</responseId>
        <status>SUCCESS</status>
        <result>
            <transactions>
                <transaction>
                    <trans_ref>RC000647000434</trans_ref>
                    <proc_bank_name>HSBC_UK</proc_bank_name>
                </transaction>
                <transaction>
                    <trans_ref>RA000606000286</trans_ref>
                    <proc_bank_name>HSBC_UK</proc_bank_name>
                </transaction>
            </transactions>
        </result>
    </response>
```

---

getErrorTransactions

Group : **transaction**
Method : **getErrorTransactions**

Input fields :

Name	Type	Notes
from_date	Date	YYYY-MM-DD
to_date	Date	YYYY-MM-DD

Example Output XML :

```
    <?xml version="1.0" encoding="utf-8"?>
    <response>
        <responseId>326</responseId>
        <status>SUCCESS</status>
        <result>
            <count>{$trans_count}</count>
            <transactions>
                <transaction>
                    <trans_ref>CC123456789</trans_ref>
                    <agent_trans_ref></agent_trans_ref>
                    <trans_type>CASH_COLLECTION</trans_type>
                    <status>ERROR</status>
                    <error_date>2016-02-26</error_date>
                    <error_reason>Invalid Beneficiary ID</error_reason>
<previous_status_before_error>SENT_FOR_PAY</previous_status_before_error>
                    <error_user_id>1</error_user_id>
                    <error_username>admin</error_username>
                    <error_agent_code>123</error_agent_code>
                    <error_agent_name>Admin</error_agent_name>
```

```
                    <remitter_id>10000</remitter_id>
                    <remitter_name>John Doe</remitter_name>
                    <beneficiary_id>1</beneficiary_id>
                    <beneficiary_name>Jane Doe</beneficiary_name>
                    <destination_country>China</destination_country>
                    <originating_country>France</originating_country>
                    <source_currency>EUR</source_currency>
                    <source_transfer_amount>42</source_transfer_amount>
                    <rate>13.37</rate>
                    <destination_currency>CNY</destination_currency>
                    <destination_amount>561.54</destination_amount>
                    <delivery_date></delivery_date>
                </transaction>
            </transactions>
        </result>
    </response>
```

---

processCashCollectionTransactionByBank

Group : **transaction**
Method : **processingCashCollectionTransactionByBank**

Input fields :

Name	Type	Notes
trans_refs	Text	text
bank_name	Text	Name of the Processing Bank (Abbreviated Bank Name)

Example Output XML :

```
<?xml version="1.0" encoding="utf-8"?>
<response>
      <status>SUCCESS</status>
      <result>
            <trans_ref>RA20079121</trans_ref>
            <process_result>SUCCESS</process_result>
            <message></message>
      </result>
</response>
```

---

requestCancellation

Group : **transaction**
Method : **requestCancellation**

Input fields :

Name	Type	Notes
trans_ref	Text	Transaction reference I.e. **RA123451234**

Example Output XML :

```
<?xml version="1.0" encoding="utf-8"?>
<response>
    <responseId>326</responseId>
    <status>SUCCESS</status>
    <result>
        <trans_ref>RA123451234</trans_ref>
        <message>Transaction successfully aborted</message>
    </result>
</response>
```

---

getMobileNetworkOperators

Group : **mobileNetworkOperator**
Method : **getMobileNetworkOperators**

Input fields :

Name	Type	Notes
country_id	Integer	The id of the Destination Country, as per the output of **getDestinationCountries**.

Example Output XML :

```
<?xml version="1.0" encoding="utf-8"?>
<response>
    <responseId>42</responseId>
    <status>SUCCESS</status>
    <result>
        <count>1</count>
        <mnos>
            <mno>
                <mobile_network_id>1</mobile_network_id>
                <name>AT&T</name>
                <code>ATT</code>
```

```
                <country_id>999</country_id>
                <number_pattern></number_pattern>
                <regex_pattern></regex_pattern>
                <enabled>t</enabled>
            </mno>
        </mnos>
    </result>
</response>
```

---

createMobileNetworkCreditType

Group : **mobileNetworkCreditType**
Method : **createMobileNetworkCreditType**

Input fields :

Name	Type	Notes
name	Text	The name of the mobile network credit type.
code	Text	The code of the mobile network credit type.
mobile_network_id	Integer	The id of the Mobile Network Operator, as per the output of **getMobileNetworkOperators**.
type	Text	The code of the mobile network credit type. I.e. Fixed Open
currency	Text	The currency ISO code of the mobile network credit type.
amount	Float	The amount of the mobile network credit type (used when the type is set to Fixed)
minimum	Float	The minimum amount of the mobile network credit type (used when the type is set to Open).
maximum	Float	The maximum amount of the mobile network credit type (used when the type is set to Open).
enabled	Boolean	Enable/Disable the mobile network credit type.

Example Output XML :

```
<?xml version="1.0" encoding="utf-8"?>
<response>
    <responseId>42</responseId>
    <status>SUCCESS</status>
```

```
        <result>
            <credit_type_id>1</credit_type_id>
            <mobile_network_id>1</mobile_network_id>
            <name>My Credit Type</name>
            <code>CODE</code>
            <country_id>999</country_id>
            <type>Fixed</type>
            <currency>GBP</currency>
            <minimum></minimum>
            <maximum></maximum>
            <amount>13.37</amount>
            <enabled>t</enabled>
        </result>
    </response>
```

---

updateMobileNetworkCreditType

Group : **mobileNetworkCreditType**
Method : **updateMobileNetworkCreditType**

Input fields :

Name	Type	Notes
credit_type_id	Integer	The id of the mobile network credit type.
name	Text	The name of the mobile network credit type.
code	Text	The code of the mobile network credit type.
mobile_network_id	Integer	The id of the Mobile Network Operator, as per the output of **getMobileNetworkOperators**.
type	Text	The code of the mobile network credit type. I.e. Fixed Open
currency	Text	The currency ISO code of the mobile network credit type.
amount	Float	The amount of the mobile network credit type (used when the type is set to Fixed)
minimum	Float	The minimum amount of the mobile network credit type (used when the type is set to Open).
maximum	Float	The maximum amount of the mobile network credit type (used when the type is set to Open).
enabled	Boolean	Enable/Disable the mobile network credit type.

Example Output XML :

```
<?xml version="1.0" encoding="utf-8"?>
<response>
    <responseId>42</responseId>
    <status>SUCCESS</status>
    <result>
        <credit_type_id>1</credit_type_id>
        <mobile_network_id>1</mobile_network_id>
        <name>My Credit Type</name>
        <code>CODE</code>
        <country_id>999</country_id>
        <type>Fixed</type>
        <currency>GBP</currency>
        <minimum></minimum>
        <maximum></maximum>
        <amount>13.37</amount>
        <enabled>t</enabled>
    </result>
</response>
```

---

uploadCSVData

Group : **CSV**
Method : **uploadCSVData**

Input fields :

Name	Type	Notes
csv_type	Text	The type of the CSV file that is being uploaded. At the moment, we support the following types: collection_point commission_slab delivery_bank delivery_bank_branch sell_rate
csv_file	File	The CSV file to upload.

Example Output XML for type=collection_point :

```
<?xml version="1.0" encoding="utf-8"?>
<response>
    <responseId>42</responseId>
    <status>SUCCESS</status>
    <results>
```

```
                <total>5</total>
                <success>
                    <total>1</total>
                    <messages>
                        <message>Line 3: My Collection Point inserted
successfully</message>
                    </messages>
                </success>
                <failure>
                    <total>1</total>
                    <messages>
                        <message>Line 5: Error performing operation, row not
inserted!</message>
                    </messages>
                </failure>
                <missing_name>
                    <total>1</total>
                    <messages>
                        <message>Line 2: Missing data in Name field, row not
inserted!</message>
                    </messages>
                </missing_name>
                <missing_value>
                    <total>1</total>
                    <messages>
                        <message>Line 4: The Bank XXX does not exist in
database, row not inserted!</message>
                    </messages>
                </missing_value>
                <duplicate>
                    <total>1</total>
                    <messages>
                        <message>Line 1: The Collection Point already exists in
the database, row not inserted!</message>
                    </messages>
                </duplicate>
            </results>
        </response>
```

getAgentDetails

Method **: getAgentDetails**
This method provides the agent credentials including the agent name, country, currency and the destination countries.

Input fields :
none (apart from username, password and pin which are required in every invocation).

Example output XML:

```
<?xml version="1.0" encoding="utf-8"?>
<response>
    <status>SUCCESS</status>
    <result>
        <agent>
            <id>13</id>
            <username>agent_bidi</username>
            <name>Agnets</name>
            <country>United Kingdom-USD</country>
            <currency>USD</currency>
            <destination_countries>
                <country>
                    <name>Lebanon</name>
                    <code>LB</code>
                    <currency>LBP</currency>
                </country>
                <country>
                    <name>United Kingdom-USD</name>
                    <code>UK-USD</code>
                    <currency>USD</currency>
                </country>
            </destination_countries>
        </agent>
    </result>
</response>
```

getDestinationCountries

Group : **country**
Method : **getDestinationCountries**

This method provides a list of available destination countries on the system.

Input fields :
none (apart from username, password and pin which are required in every invocation).

Example Output XML :

```
<?xml version="1.0" encoding="utf-8"?>
<response>
    <status>SUCCESS</status>
    <result>
        <countries>
            <country>
                <id>998</id>
                <name>Bangladesh</name>
                <iso_code>BD</iso_code>
                <currency>BDT</currency>
            </country>
            <country>
                <id>999</id>
                <name>Philippines</name>
                <iso_code>PH</iso_code>
                <currency>PHP</currency>
            </country>
        </countries>
    </result>
</response>
```

---

getRates

Group : **rates**
Method : **getRates**
This method provides current rates from the system.

Input fields:

Name	Type	Notes
source_currency	Text	Optional
dest_country *	Text	The name of the Destination Country, as per the output of **getDestinationCountries**.
dest_currency	Text	Optional
Delivery Bank Name	Text	Optional

Example Output XML :

```
<?xml version="1.0" encoding="utf-8"?>
<response>
    <status>SUCCESS</status>
    <result>
        <rate>
            <account>39.5000</account>
            <cash_collection>39.0000</cash_collection>
            <card>39.5000</card>
            <home_delivery>38.0000</home_delivery>
            <utility_bill>39.6000</utility_bill>
            <mobile_transfer>36.0000</mobile_transfer>
        </rate>
    </result>
</response>
```

---

getCurrentCredit

Group : **agent**
Method : **getCurrentCredit**

Input fields :

none

Example Output XML :

```
<?xml version="1.0" encoding="utf-8"?>
   <response>
       <status>SUCCESS</status>
       <result>
           <credit>
               <currency>CAD</currency>
               <available_credit>1952</available_credit>
               <date_last_updated>2009-06-19 17:03:15</date_last_updated>
           </credit>
       </result>
   </response>
```

---

createRemitter

Group : **remitter**
Method : **createRemitter**

Input fields :

Name	Type	Notes
firstname *	Text	

lastname *	Text	
type *	Text	registered / nonregistered
nationality	Text	2 letter country ISO code. Please refer to Appendix A.
gender	Text	Male / Female
status *	Text	valid / expired / blocked
comments	Text	
address1 *	Text	
address2	Text	
city *	Text	
state	Text	
postcode	Text	
email	Text	
telephone	Text	
mobile	Text	
dob	Date	YYYY-MM-DD. Required if type is 'registered'.
id_type	Code	See Appendix B for codes. Required if type is 'registered'.
id_details	Text	Required if type is 'registered'.
id_issued_by	Text	Required if type is 'registered'.
id_issue_place	Text	Required if type is 'registered'.
id_start	Date	YYYY-MM-DD. Required if type is 'registered'.
id_expiry	Date	YYYY-MM-DD. Required if type is 'registered'.
id2_type	Code	See Appendix B for codes.
id2_details	Text	
id2_issued_by	Text	
id2_issue_place	Text	
id2_start	Date	YYYY-MM-DD
id2_expiry	Date	YYYY-MM-DD
account_number	Text	
sort_code	Text	
groups	Text	Comma separate string e.g Default,Group2,Group3
credit_balance	Text	

credit_currency	Text	
Id1_scan	File	png, gif, jpg, jpeg, bmp and pdf
Id2_scan	File	png, gif, jpg, jpeg, bmp and pdf

Example Output XML :

```
<?xml version="1.0" encoding="utf-8"?>
<response>
    <status>SUCCESS</status>
    <new_remitter_id>10024</new_remitter_id>
</response>
```

---

searchRemitter

Group : **remitter**
Method : **searchRemitter**

Input fields :

Name	Type	Notes
remitter_id	Text	Required if the full name is not provided.
firstname	Text	Required if remitter_id is not provided.
lastname	Text	Required if remitter_id is not provided.
dob	Date	YYYY-MM-DD
address_line1	Text	
city	Text	
postcode	Text	
telephone	Text	
mobile	Text	
email	Text	
id1_type	Text	See Appendix C for codes
id1_details	Text	
remitter_type	Text	registered / nonregistered

Example Output XML :

```
<?xml version="1.0" encoding="utf-8"?>
<response>
    <status>SUCCESS</status>
    <result>
        <remitters>
            <remitter>
                <remitter_id>10001</remitter_id>
                <status>enabled</status>
                <firstname>James</firstname>
                <lastname>Smith</lastname>
                <address1>100 Rue Bleue</address1>
                <address2></address2>
                <city>Ottawa</city>
                <state></state>
                <postcode>OW878</postcode>
                <country>Canada</country>
                <telephone>54654675</telephone>
                <mobile></mobile>
                <email></email>
                <dob>23-07-1979</dob>
                <nationality>CA</nationality>
                <id_type>passport</id_type>
                <id_details>4395346</id_details>
                <id_issued_by>CAPA</id_issued_by>
                <id_issue_place>Ottawa</id_issue_place>
                <id_start>03-07-2005</id_start>
                <id_expiry>03-07-2015</id_expiry>
                <id2_type>driving_license</id2_type>
                <id2_details>12367598</id2_details>
                <id2_issued_by>CAPA</id2_issued_by>
                <id2_issue_place>Ottawa</id2_issue_place>
                <id2_start>06-09-2002</id2_start>
                <id2_expiry>06-09-2012</id2_expiry>
                <comments></comments>
                <groups>Default,Group2,Group3</groups>
                <credit_balance>100.00</credit_balance>
                <credit_currency>GBP</credit_currency>
            </remitter>
        </remitters>
    </result>
</response>
```

---

updateRemitter

Group : **remitter**
Method : **updateRemitter**

Input fields :

Name	Type	Notes
remitter_id *	Text	

firstname	Text	
lastname	Text	
type	Text	registered / nonregistered
nationality	Text	2 letter country ISO code. Please refer to Appendix A.
status	Text	valid / expired / blocked
comments	Text	
address1	Text	
address2	Text	
city	Text	
state	Text	
postcode	Text	
email	Text	
telephone	Text	
mobile	Text	
dob	Date	YYYY-MM-DD
id_type	Code	See Appendix B for codes
id_details	Text	
id_issued_by	Text	
id_issue_place	Text	
id_start	Date	YYYY-MM-DD
id_expiry	Date	YYYY-MM-DD
id2_type	Code	See Appendix B for codes
id2_details	Text	
id2_issued_by	Text	
id2_issue_place	Text	
id2_start	Date	YYYY-MM-DD
id2_expiry	Date	YYYY-MM-DD
account_number	Text	
sort_code	Text	
groups	Text	Comma separate string e.g Default,Group2,Group3
Id1_scan	File	png, gif, jpg, jpeg, bmp and pdf
Id2_scan	File	png, gif, jpg, jpeg, bmp and pdf

NOTE: All valid fields must be provided on update, otherwise existing fields may be blanked out.

Example Output XML :

```
<?xml version="1.0" encoding="utf-8"?>
<response>
    <status>SUCCESS</status>
    <result>
        <remitter>
            <remitter_id>10018</remitter_id>
            <firstname>Joe</firstname>
            <lastname>Blogger</lastname>
        </remitter>
    </result>
</response>
```

---

createBeneficiary

Group : **beneficiary**
Method : **createBeneficiary**

Input fields :

Name	Type	Notes
name *	Text	
address1 *	Text	
address2	Text	
address3	Text	
city *	Text	
state	Text	
postcode	Text	
country *	Text	Country Name, as per output of getDestinationCountries
dob	Date	YYYY-MM-DD
telephone	Text	
mobile	Text	
email	Text	
id_type	Code	See Appendix C for codes

id_details	Text	
card_number	Text	The actual number if known, or REQUESTED if the bank needs to create a new card
account_number	Text	
bank	Text	
bank_branch	Text	
bank_branch_city	Text	
bank_branch_state	Text	
bank_branch_telephone	Text	
bank_branch_manager	Text	
benef_bank_swift_code	Text	
benef_bank_ifsc_code	Text	
benef_bank_account_name	Text	
homedelivery_notes	Text	
enabled	Text	t=true, f=false (By default if left blank, beneficiary will be enabled)
remitter_id *	Number	The remitter this beneficiary is linked to
suspicious	Text	t=true, f=false (By default if left blank, beneficiary is NOT suspicious)
suspicion_reason	Text	
Id_scan	File	png, gif, jpg, jpeg, bmp and pdf

NOTE: If the Bank needs to create a new Card for the beneficiary, then specify the Card Number as 'REQUESTED'. This data will then be fed to the Bank dealing with that country for creation of the ATM Card.

Example Output XML :

```
<?xml version="1.0" encoding="utf-8"?>
<response>
    <status>SUCCESS</status>
    <new_beneficiary_id>7</new_beneficiary_id>
</response>
```

searchBeneficiary

Group : **beneficiary**
Method : **searchBeneficiary**

Input fields :

Name	Type	Notes
beneficiary_id	Number	
name *	Text	
city	Text	
state	Text	
postcode	Text	
country *	Text	Required, as per output of getDestinationCountries
dob	Date	YYYY-MM-DD
telephone	Text	
mobile	Text	
id_details	Text	
account_number	Text	
card_number	Text	
enabled	Text	

Example Output XML :

```
<?xml version="1.0" encoding="utf-8"?>
<response>
    <status>SUCCESS</status>
    <result>
        <beneficiaries>
            <beneficiary>
                <beneficiary_id>4</beneficiary_id>
                <name>Jahangir Khan</name>
                <address1>34 Small Lane</address1>
                <address2></address2>
                <address3></address3>
                <city>Mymensingh</city>
                <state></state>
                <postcode></postcode>
                <country>Bangladesh</country>
                <dob></dob>
                <telephone>38254235</telephone>
                <mobile>7367365</mobile>
                <email>jk@work.com</email>
```

```
                <status>t</status>
                <id_type>NATIONALID</id_type>
                <id_details>35345345435</id_details>
                <account_number>4534534534534</account_number>
                <bank>Agrani Bank</bank>
                <bank_branch>Agrani Chittagong</bank_branch>
                <bank_branch_city>Chittagong</bank_branch_city>
                <bank_branch_state>Chittagong</bank_branch_state>
                <bank_branch_telephone>87787876</bank_branch_telephone>
                <bank_branch_manager>Mr Manager</bank_branch_manager>
                <benef_bank_swift_code>SW736435</benef_bank_swift_code>
                <benef_bank_ifsc_code>IFSC435</benef_bank_ifsc_code>
                <benef_bank_account_name>Savings AC</benef_bank_account_name>
                <card_number>345345435</card_number>
                <homedelivery_notes></homedelivery_notes>
                <suspicious>f</suspicious>
                <suspicion_reason></suspicion_reason>
            </beneficiary>
        </beneficiaries>
    </result>
</response>
```

---

getRemitterBeneficiaries

Group : **beneficiary**
Method : **getRemitterBeneficiaries**

Input fields :

Name	Type	Notes
remitter_id	Number	

Example Output XML :

```
<?xml version="1.0" encoding="utf-8"?>
<response>
    <status>SUCCESS</status>
    <result>
        <beneficiaries>
            <beneficiary>
                <beneficiary_id>4</beneficiary_id>
                <name>Jahangir Khan</name>
                <address1>34 Small Lane</address1>
                <address2></address2>
                <address3></address3>
                <city>Mymensingh</city>
                <state></state>
                <postcode></postcode>
                <country>Bangladesh</country>
                <dob></dob>
```

```
                <telephone>38254235</telephone>
                <mobile>7367365</mobile>
                <email>jk@work.com</email>
                <status>t</status>
                <id_type>NATIONALID</id_type>
                <id_details>35345345435</id_details>
                <account_number>4534534534534</account_number>
                <bank>Agrani Bank</bank>
                <bank_branch>Agrani Chittagong</bank_branch>
                <bank_branch_city>Chittagong</bank_branch_city>
                <bank_branch_state>Chittagong</bank_branch_state>
                <bank_branch_telephone>87787876</bank_branch_telephone>
                <bank_branch_manager>Mr Manager</bank_branch_manager>
                <benef_bank_swift_code>SW736435</benef_bank_swift_code>
                <benef_bank_account_name>Savings AC</benef_bank_account_name>
                <card_number>345345435</card_number>
                <homedelivery_notes></homedelivery_notes>
                <suspicious>f</suspicious>
                <suspicion_reason></suspicion_reason>
            </beneficiary>
        </beneficiaries>
    </result>
</response>
```

---

updateBeneficiary

Group : **beneficiary**
Method : **updateBeneficiary**

Input fields :

Name	Type	Notes
beneficiary_id *	Number	
name	Text	
address1	Text	
address2	Text	
address3	Text	
city	Text	
state	Text	
postcode	Text	
country	Text	As per output of getDestinationCountries
dob	Date	YYYY-MM-DD
telephone	Text	

mobile	Text	
email	Text	
id_type	Code	See Appendix C for codes
id_details	Text	
card_number	Text	
account_number	Text	
bank	Text	
bank_branch	Text	
bank_branch_city	Text	
bank_branch_state	Text	
bank_branch_telephone	Text	
bank_branch_manager	Text	
benef_bank_swift_code	Text	
benef_bank_ifsc_code	Text	
benef_bank_account_name	Text	
homedelivery_notes	Text	
enabled	Text	t=true, f=false
suspicious	Text	t=true, f=false
suspicion_reason	Text	
Id_scan	File	png, gif, jpg, jpeg, bmp and pdf

NOTE: All valid fields must be provided on update, otherwise existing fields may be blanked out.

Example Output XML :

```
<?xml version="1.0" encoding="utf-8"?>
<response>
    <status>SUCCESS</status>
    <result>
        <beneficiary>
            <beneficiary_id>7</beneficiary_id>
            <name>Faisal Siddique</name>
        </beneficiary>
    </result>
</response>
```

assignBeneficiary

Group : **remitter**
Method : **assignBeneficiary**

Input fields :

Name	Type	Notes
remitter_id *	Number	
beneficiary_id *	Number	

Example Output XML :

```
<?xml version="1.0" encoding="utf-8"?>
<response>
    <status>SUCCESS</status>
    <result>
        <remitter>
            <remitter_id>10001</remitter_id>
            <firstname>James</firstname>
            <lastname>Foo</lastname>
        </remitter>
        <beneficiary>
            <beneficiary_id>3</beneficiary_id>
            <name>ZIAD MANNAN</name>
        </beneficiary>
    </result>
</response>
```

---

createTransaction

Group: **transaction**
Method: **createTransaction**

Input fields:

Name	Type	Notes
remitter_id *	Number	
beneficiary_id *	Number	
destination_country *	Text	Name of country retrieved from calling getDestinationCountries
agent_trans_ref	Text	Agent's reference number for transaction
trans_type *	Text	Account / Cash Collection / Card Transfer / Home Delivery / Mobile Transfer

purpose *	Code	See Appendix G for codes
source_of_income *	Code	See Appendix F for codes
collection_point	Text	Name of collection point where money will be collected by beneficiary. Required if transaction is of type Cash Collection. All the fields starting with 'collection_' below only apply to Cash Collection transactions.
collection_point_code	Text	Collection point code.
collection_point_bank	Text	Name of bank or organisation that the collection point is under. Required if transaction is of type Cash Collection.
collection_point_address	Text	Collection point address.
collection_point_city	Text	Collection point city.
collection_point_state	Text	Collection point state.
collection_point_telephone	Text	Collection point telephone number.
collection_pin	Numeric	A PIN number which the beneficiary needs to provide on cash pick-up. This may be required, please check with your partner.
benef_utilitybillcompany	Text	Name of the Utility Company where money will be paid. Required if transaction is of type Utility Bill.
benef_utilitybillaccountno	Text	Customer Account No. Required if transaction is of type Utility Bill.
benef_utilitybillinvoice	Text	Invoice No.
benef_utilitybillbank	Text	Bank to Pay.
benef_utilitybillbankcode	Text	Bank IBAN/SWIFT Code.
benef_utilitybilldescription	Text	Bill Description.
benef_mobiletransfer_number	Text	The mobile number of the beneficiary for mobile transfer.
benef_mobiletransfer_network	Text	The mobile phone network of the beneficiary for mobile transfer.
payment_method *	Code	See Appendix D for codes.
amount_deposited *	Numeric	Needed for Bank Transfer Payment Method
date_deposited *	Date	Needed for Bank Transfer Payment Method
bank_branch_deposited *	Text	Needed for Bank Transfer Payment Method
service_level *	Code	See Appendix E for codes.
sms_confirmation *	Boolean	t / f

sms_notification *	Boolean	t / f
sms_mobile	Text	Mobile number for Remitter to send SMS to
sms_benef_confirmation	Boolean	t / f
sms_benef_mobile	Text	Mobile number for Beneficiary to send SMS to
source_currency	Text	Source currency, if blank will use default
dest_currency	Text	Dest currency, if blank will use default
amount_type *		Whether the amount is specified in the source currency or the destination currency. Possible values : SOURCE / DESTINATION.
amount_to_send *	Numeric	

NOTE: After invoking this method, confirmTransaction must be called with the trans_session_id to successfully create the transaction.

Example Output XML :

```
<?xml version="1.0" encoding="utf-8"?>
<response>
    <status>SUCCESS</status>
    <result>
        <trans_session_id>245861246457499</trans_session_id>
        <remitter_id>10019</remitter_id>
        <remitter_name>MUHAMMAD KHAN</remitter_name>
        <beneficiary_id>5</beneficiary_id>
        <beneficiary_name>BENEF TEST</beneficiary_name>
        <trans_type>Card Transfer</trans_type>
        <destination_country>Philippines</destination_country>
        <source_currency>CAD</source_currency>
        <source_transfer_amount>100.00</source_transfer_amount>
        <rate>37.5300</rate>
        <destination_currency>PHP</destination_currency>
        <destination_amount>3753.00</destination_amount>
        <commission>10.50</commission>
        <agent_fee>0.00</agent_fee>
        <hq_fee>0.50</hq_fee>
        <tax>3.40</tax>
        <remitter_pay_amount>114.40</remitter_pay_amount>
        <agent_deduction>4.20</agent_deduction>
        <agent_to_pay_hq>110.20</agent_to_pay_hq>
        <delivery_date>2009-07-02 00:00:00</delivery_date>
        <payment_token>2fe1ebbfa197c7d4e4762d154602762ef941c110</payment_token>
    </result>
</response>
```

confirmTransaction

Group: **transaction**
Method: **confirmTransaction**

Input fields:

Name	Type	Notes
trans_session_id *	Numeric	Temporary ID generated by the system and returned as result of createTransaction

Example Output XML :

```
<?xml version="1.0" encoding="utf-8"?>
<response>
    <status>SUCCESS</status>
    <result>
        <reference_number>RB0003113</reference_number>
        <remitter_id>10019</remitter_id>
        <remitter_name>MUHAMMAD KHAN</remitter_name>
        <beneficiary_id>5</beneficiary_id>
        <beneficiary_name>BENEF TEST</beneficiary_name>
        <status>{$trans->status}</status>
        <trans_type>Card Transfer</trans_type>
        <destination_country>Philippines</destination_country>
        <source_currency>CAD</source_currency>
        <source_transfer_amount>100.00</source_transfer_amount>
        <rate>37.5300</rate>
        <destination_currency>PHP</destination_currency>
        <destination_amount>3753.00</destination_amount>
        <commission>10.50</commission>
        <agent_fee>0.00</agent_fee>
        <hq_fee>0.50</hq_fee>
        <tax>3.40</tax>
        <remitter_pay_amount>114.40</remitter_pay_amount>
        <agent_deduction>4.20</agent_deduction>
        <agent_to_pay_hq>110.20</agent_to_pay_hq>
        <delivery_date>2009-07-02 00:00:00</delivery_date>
        <payment_token>2fe1ebbfa197c7d4e4762d154602762ef941c110</payment_token>
        <compliance_check_required>f</compliance_check_required>
        <collection_pin>762634</collection_pin>
        <agent_trans_ref>GHT33762634</agent_trans_ref>
        <benef_trans_ref>GHT33762634</benef_trans_ref>
    </result>
</response>
```

---

insertTransaction

Group: **transaction**

Method: **insertTransaction**

Input fields:

Name	Type	Notes
agent_trans_ref *	Text	Transaction reference from the sending system.
trans_type*		Account / Cash Collection / Card Transfer / Home Delivery / Mobile Transfer
purpose	Text	See 'Description' on Appendix G
source_of_income	Text	See 'Description' on Appendix F
remitt_name	Text	
remitt_addr	Text	
remitt_tel	Text	
remitt_id_type	Text	
remitt_id_details	Text	
remitt_nationality	Text	2 letter country ISO code. Please refer to Appendix A.
remitt_dob	Date	YYYY-MM-DD
benef_name	Text	
benef_address	Text	
benef_address2	Text	
benef_address3	Text	
benef_city	Text	
benef_state	Text	
benef_postcode	Text	
benef_tel	Text	
benef_mobile	Text	
benef_id_type	Text	
benef_id_details	Text	
benef_ac	Text	
benef_bank	Text	
benef_bank_swift_code	Text	
benef_branch	Text	
benef_branch_code	Text	

benef_branch_address	Text	
benef_branch_tel	Text	
benef_branch_city	Text	
benef_branch_state	Text	
benef_card_number	Text	
collection_point	Text	
collection_point_code	Text	
collection_point_bank	Text	
collection_point_address	Text	
collection_point_city	Text	
collection_pin	Text	
benef_mobiletransfer_number	Text	
benef_mobiletransfer_network	Text	
payment_method*	Code	See Appendix D for codes.
source_currency*	Text	
source_amount*	Numeric	
dest_currency*	Text	
dest_amount*	Numeric	
rate*	Numeric	
commission*	Numeric	
source_tax	Numeric	
originating_country*	Text	2 letter country ISO code. Please refer to Appendix A.
destination_country*	Text	2 letter country ISO code. Please refer to Appendix A.
service_level	Code	See Appendix E for codes.
sms_notification*	Boolean	t / f
sms_confirmation*	Boolean	t / f
sms_benef_confirmation*	Boolean	t / f
agent_fee	Numeric	
agent_comments	Text	

sms_remitter_mobile	Text	
sms_benef_mobile	Text	

NOTE: Required fields will vary depending on the Transaction Type and configurations of the receiving system. Currently this methods is only used for importing Transactions from another RemitONE system.

Example Output XML :

```
<?xml version="1.0" encoding="utf-8"?>
<response>
    <status>SUCCESS</status>
    <result>
        <trans_ref>RA0003101</trans_ref>
        <agent_trans_ref>ABC1234567sss8</agent_trans_ref>
        <remitter_id>1111</remitter_id>
        <remitter_name>John Smith</remitter_name>
        <beneficiary_id>2222</beneficiary_id>
        <beneficiary_name>Jane Doe</beneficiary_name>
        <trans_type>Cash Collection</trans_type>
        <destination_country>GH</destination_country>
        <source_currency>USD</source_currency>
        <source_transfer_amount>94</source_transfer_amount>
        <rate>1.9900</rate>
        <destination_currency>GHS</destination_currency>
        <destination_amount>187.06</destination_amount>
        <commission>2.50</commission>
        <tax>1.00</tax>
        <agent_fee></agent_fee>
        <hq_fee>0.00</hq_fee>
        <remitter_pay_amount>97.50</remitter_pay_amount>
        <agent_deduction>0.00</agent_deduction>
        <agent_to_pay_hq>97.50</agent_to_pay_hq>
        <delivery_date>2012-01-01 00:00:00+00</delivery_date>
    </result>
</response>
```

---

getTransactionDetails

Group: **transaction**
Method: **getTransactionDetails**

Get details of a single transaction that has been created by the Agent.

Input fields:

Name	Type	Notes
trans_ref *	Text	

Example Output XML :

```
<?xml version="1.0" encoding="utf-8"?>
<response>
      <status>SUCCESS</status>
      <result>
            <transaction>
                  <trans_ref>RA20079127</trans_ref>
                  <status>HQ_OK</status>
                  <creation_date>2010-05-11 10:28:02.244553</creation_date>
                  <bank_branch_name></bank_branch_name>
                  <bank_branch_code></bank_branch_code>
                  <bank_accept_date>2010-05-11
10:28:35.435216</bank_accept_date>
                  <bank_branch_accept_date></bank_branch_accept_date>
                  <delivery_date>2010-05-18 00:00:00</delivery_date>
                  <processed_date></processed_date>
                  <processed_by></processed_by>
                  <delivery_date>2010-05-18 00:00:00</delivery_date>
                  <trans_type>Account</trans_type>
                  <benef_name>
                        <![CDATA[ZIAD HASSAN SYFULLAH]]>
                  </benef_name>
                  <benef_tel>
                        <![CDATA[]]>
                  </benef_tel>
                  <benef_mobile>
                        <![CDATA[07512487412]]>
                  </benef_mobile>
                  <benef_email>
                        <![CDATA[]]>
                  </benef_email>
                  <collection_point>
                        <![CDATA[BOGRA]]>
                  </collection_point>
                  <collection_point_code>
                        <![CDATA[]]>
                  </collection_point_code>
                  <collection_pin>
                        <![CDATA[]]>
                  </collection_pin>
                  <benef_id_type>
                        <![CDATA[NONE]]>
                  </benef_id_type>
                  <benef_id_detail>
                        <![CDATA[]]>
                  </benef_id_detail>
                  <benef_ac>
                        <![CDATA[1234567890]]>
                  </benef_ac>
                  <benef_bank>
                        <![CDATA[PRIME BANK LIMITED]]>
                  </benef_bank>
                  <benef_bank_swift_code>
                        <![CDATA[ABC123]>
                  </benef_bank_swift_code>
                  <benef_bank_ifsc_code>12340678912</benef_bank_ifsc_code>
                  <benef_branch>
```

```
                  <![CDATA[AGRABAD]]>
               </benef_branch>
               <benef_bank_city>
                  <![CDATA[CHITTAGONG]]>
               </benef_bank_city>
               <benef_bank_state>
                  <![CDATA[CHITTAGONG]]>
               </benef_bank_state>
               <benef_card_number>
                  <![CDATA[]]>
               </benef_card_number>
               <benef_address1>
                  <![CDATA[BOGRA]]>
               </benef_address1>
               <benef_address2>
                  <![CDATA[]]>
               </benef_address2>
               <benef_address3>
                  <![CDATA[]]>
               </benef_address3>
               <benef_city>
                  <![CDATA[BOGRA]]>
               </benef_city>
               <benef_state>
                  <![CDATA[]]>
               </benef_state>
               <benef_postcode>
                  <![CDATA[]]>
               </benef_postcode>
               <benef_mobiletransfer_number>
                  <![CDATA[01234567]]>
               </benef_mobiletransfer_number>
               <benef_mobiletransfer_network>
                  <![CDATA[mobileNetwork]]>
               </benef_mobiletransfer_network>
               <benef_mobiletransfer_network_credit_type><!
[CDATA[]]></benef_mobiletransfer_network_credit_type>
               <delivery_notes>
                  <![CDATA[]]>
               </delivery_notes>
               <utility_company><![CDATA[]]></utility_company>
               <utility_account_no><![CDATA[]]></utility_account_no>
               <utility_invoice><![CDATA[]]></utility_invoice>
               <utility_bank><![CDATA[]]></utility_bank>
               <utility_bank_code><![CDATA[]]></utility_bank_code>
               <utility_description><![CDATA[]]></utility_description>
               <remitter_name>
                  <![CDATA[ALI IMAN]]>
               </remitter_name>
               <remitter_id>1210</remitter_id>
               <remitter_address>
                  <![CDATA[#26-02, 9 TEMASEK BOULEVARD, SINGAPORE,
SINGAPORE]]>
               </remitter_address>
               <remitter_tel>
                  <![CDATA[]]>
               </remitter_tel>
               <remitter_mobile>
                  <![CDATA[]]>
```

```
                  </remitter_mobile>
                  <send_country>SG</send_country>
                  <send_currency>SGD</send_currency>
                  <send_amount>157.57</send_amount>
                  <rate>49.2800</rate>
                  <commission>5.00</commission>
                  <fees>0</fees>
                  <paid>162.57</paid>
                  <receive_country>BD</receive_country>
                  <receive_currency>BDT</receive_currency>
                  <receive_amount>7765.05</receive_amount>
                  <bank_sequence>2929</bank_sequence>
                  <pay_method></pay_method>
                  <issue_date></issue_date>
                  <bank_ref></bank_ref>
                  <benef_trans_ref>GHT33762634</benef_trans_ref>
                  <bank_comments></bank_comments>
                  <bank_credit_date></bank_credit_date>
                  <bank_clear_date></bank_clear_date>
            </transaction>
      </result>
</response>
```

---

getRemitterTransactions

Group : **transaction**
Method : **getTransactions**

Get details of a remitter's transactions for the past three months

Input fields :

Name	Type	Notes
remitter_id	Number	

Example Output XML :

```
<?xml version="1.0" encoding="utf-8"?>
<response>
      <status>SUCCESS</status>
      <result>
            <count>1</count>
            <transactions>
                  <transaction>
                        <trans_ref>RA20079112</trans_ref>
                        <trans_type>Account</trans_type>
                        <status>HQ_OK</status>
                        <creation_date>2010-05-07 16:25:12.26266</creation_date>
                        <originating_country>SG</originating_country>
                        <destination_country>BD</destination_country>
```

```
                        <source_currency>SGD</source_currency>
                        <source_amount>85.00</source_amount>
                        <commission>5.00</commission>
                        <tax>5.00</tax>
                        <dest_currency>BDT</dest_currency>
                        <dest_amount>4188.80</dest_amount>
                        <rate>49.2800</rate>
                        <remitter_name>ALI IMAN</remitter_name>
                        <remitter_address>123 New Street</remitter_address>
                        <remitter_city>London</remitter_city>
                        <remitter_tel>012345678</remitter_tel>
                        <remitter_mobile>012345678</remitter_mobile>
                        <remitter_id_type>passport</remitter_id_type>
                        <remitter_id_details>54321</remitter_id_details>
                        <remitter_id>11217</remitter_id>
                        <payment_method>1</payment_method>
                        <benef_name>Kevin Smith</benef_name>
                        <benef_mobile>0987654321</benef_mobile>
                        <benef_ac>87654321</benef_ac>
                        <benef_bank_swift_code></benef_bank_swift_code>
                        <benef_bank_ifsc_code></benef_bank_ifsc_code>
                        <benef_branch>Main Branch</benef_branch>
                        <collection_point_bank></collection_point_bank>
                        <account_transfer_bank>United
Bank</account_transfer_bank>
                        <benef_mobiletransfer_number><!
[CDATA[]]></benef_mobiletransfer_number>
                        <benef_mobiletransfer_network><!
[CDATA[]]></benef_mobiletransfer_network>
                        <benef_mobiletransfer_network_credit_type><!
[CDATA[]]></benef_mobiletransfer_network_credit_type>
                        <delivery_notes><![CDATA[]]></delivery_notes>
                        <utility_company><![CDATA[]]></utility_company>
                        <utility_account_no><![CDATA[]]></utility_account_no>
                        <utility_invoice><![CDATA[]]></utility_invoice>
                        <utility_bank><![CDATA[]]></utility_bank>
                        <utility_bank_code><![CDATA[]]></utility_bank_code>
                        <utility_description><![CDATA[]]></utility_description>
                        <source_agent_name>JOE BLOGGS</source_agent_name>
                        <source_agent_teller_name>JOHN
TELLER</source_agent_teller_name>
                        <bank_buy_rate>53.3200</rate>
                        <source_conv_rate>48.1400</source_conv_rate>
                        <dest_conv_rate>49.2800</dest_conv_rate>
                </transaction>
            </transactions>
      </result>
</response>
```

getTransactionStatus

Group: **transaction**
Method: **getTransactionStatus**

Input fields:

Name	Type	Notes
trans_ref *	Text	Transaction reference from the RemitONE system. See getTransactionStatusByAgentTransRef below to request using the agent's transaction reference.

Example Output XML :

```
<?xml version="1.0" encoding="utf-8"?>
<response>
    <status>SUCCESS</status>
    <result>
        <trans_ref>RA0003101</trans_ref>
        <agent_trans_ref>ABC12345678</agent_trans_ref>
        <benef_trans_ref>ABC12345678</benef_trans_ref>
        <status>SENT_FOR_PAY</status>
        <compliance_check_required>f</compliance_check_required>
        <compliance_checked>f</compliance_checked>
    </result>
</response>
```

---

getTransactionStatusByAgentTransRef

Group: **transaction**
Method: **getTransactionStatusByAgentTransRef**

Input fields:

Name	Type	Notes
trans_ref *	Text	Agent's unique transaction reference (if provided at the time of creation). See getTransactionStatus above to request the transaction status using the RemitONE's transaction reference.

Example Output XML :

```
<?xml version="1.0" encoding="utf-8"?>
<response>
    <status>SUCCESS</status>
    <result>
        <trans_ref>RA0003101</trans_ref>
        <agent_trans_ref>ABC12345678</agent_trans_ref>
        <benef_trans_ref>ABC12345678</benef_trans_ref>
        <status>SENT_FOR_PAY</status>
```

```
        <compliance_check_required>f</compliance_check_required>
        <compliance_checked>f</compliance_checked>
    </result>
</response>
```

---

getCharges

Group: **transaction**
Method: **getCharges**

Input fields:

Name	Type	Notes
destination_country *	Text	Name of country retrieved from calling getDestinationCountries
trans_type *	Text	Account / Cash Collection / Card Transfer / Home Delivery / Mobile Transfer
payment_method *	Code	See Appendix D for codes.
service_level *	Code	See Appendix E for codes.
sms_confirmation *	Boolean	t / f
sms_notification *	Boolean	t / f
amount_type *		Whether the amount is specified in the source currency or the destination currency. Possible values : SOURCE / DESTINATION.
amount_to_send *	Numeric	
Source Currency	Text	Same code as you get when calling getSourceCountries
Destination currency	Text	Same code as you get when calling getDestinationCountries

If source and destination currencies are not entered,then the default source and destination currencies will be used instead.

Example Output XML :

```
<?xml version="1.0" encoding="utf-8"?>
<response>
    <status>SUCCESS</status>
    <result>
        <source_currency>GBP</source_currency>
        <source_amount>100</source_amount>
```

```
        <rate>37.53</rate>
        <destination_currency>PHP</destination_currency>
        <destination_amount>3753.00</destination_amount>
        <commission>10.50</commission>
        <agent_fee>0.00</agent_fee>
        <hq_fee>0.50</hq_fee>
        <total_charges>11.00</total_charges>
        <tax>3.40</tax>
    </result>
</response>
```

---

getDeliveryBanks

Group: **deliveryBank**
Method: **getDeliveryBanks**

Input fields:

Name	Type	Notes
dest_country	Text	The name of the Destination Country, as per the output of **getDestinationCountries**.

Example Output XML :

```
<?xml version="1.0" encoding="utf-8"?>
<response>
    <responseId>42</responseId>
    <status>SUCCESS</status>
    <result>
        <delivery_banks>
            <delivery_bank>
                <bank_id>14</bank_id>
                <name>delivery bank</name>
                <country_id>999</country_id>
                <bank_code>del123</bank_code>
                <swift_code>sw123</swift_code>
                <address>address 123</address>
                <city>city123</city>
                <state>state123</state>
                <telephone>123</telephone>
                <account_number_mask>123</account_number_mask>
                <enabled>t</enabled>
            </delivery_bank>
        </delivery_banks>
    </result>
</response>
```

getDeliveryBankBranches

Group: **deliveryBankBranch**
Method: **getDeliveryBankBranches**

Input fields:

Name	Type	Notes
delivery_bank	Text	The name of the delivery bank, as per the output of **getDeliveryBanks**.

```
<?xml version="1.0" encoding="utf-8"?>
<response>
    <responseId>44</responseId>
    <status>SUCCESS</status>
    <result>
        <delivery_bank_branches>
            <delivery_bank_branch>
                <id>1</id>
                <name>Branch123</name>
                <branch_code>BRANCH-123</branch_code>
                <enabled>t</enabled>
                <delivery_bank>1</delivery_bank>
                <city>city123</city>
                <state>state123</state>
                <telephone>012345678</telephone>
                <manager>manager123</manager>
            </delivery_bank_branch>
        </delivery_bank_branches>
    </result>
</response>
```

getCollectionPoints

Group: collectionPoint
Method: **getCollectionPoints**

Input fields:

Name	Type	Notes
delivery_bank	Text	The name of the delivery bank, as per the output of **getDeliveryBanks**.

```
<?xml version="1.0" encoding="utf-8"?>
<response>
    <responseId>45</responseId>
    <status>SUCCESS</status>
    <result>
```

```
        <collection_points>
            <collection_point>
                <collection_id>1</collection_id>
                <name>colltion123</name>
                <bank>Bank 123</bank>
                <delivery_bank>1</delivery_bank>
                <address>address123</address>
                <city>city123</city>
                <state>state123</state>
                <country_id>123</country_id>
                <code>COLLECTION-123</code>
                <telephone>012345678</telephone>
                <fax>fax123</fax>
                <email>email123</email>
                <working_hours>1</working_hours>
                <contact_person>person123</contact_person>
                <default_in_country>t</default_in_country>
                <enabled>t</enabled>
                <collection_pin_prefix>123</collection_pin_prefix>
                <rate_markup>1</rate_markup>
            </collection_point>
        </collection_points>
    </result>
</response>
```

transactionPaymentCleared

Group: **transaction**
Method: **transactionPaymentCleared**

Marks a transaction which is in status PENDING_CLEARANCE (i.e still requires payment) as payment cleared to say that the payment has been made.

Input fields:

Name	Type	Notes
trans_ref	Text	Enter either trans_ref and agent_trans_ref
agent_trans_ref	Text	

```
<?xml version="1.0" encoding="utf-8"?>
<response>
    <responseId>45</responseId>
    <status>SUCCESS</status>
    <result>
       <trans_ref>RC12321321321</trans_ref>
       <message>Transaction payment cleared successfully</message>
     </result>
</response>
```

getCashCollectionTransactionDetails

Group: **transaction**
Method: **getCashCollectionTransactionDetails**

Look up for cash collection transaction as a **BIDI** agent.

Name	Type	Notes
trans_ref	Text	Transaction reference number
collection_pin_number	Text	Collection pin number
security_question	Text	Security question
security_answer	Text	Security answer

Input fields:
Need to input the trans_ref or/and collection_pin_number depending on the configuration setting.

Example Output XML :

```
<?xml version="1.0" encoding="utf-8"?>
<response>
    <status>SUCCESS</status>
    <result>
        <transaction>
            <trans_ref>RC000224000133</trans_ref>
            <status>HQ_OK</status>
            <creation_date>2014-09-19 10:41:40.755687+00</creation_date>
            <purpose>FAMILY SUPPORT</purpose>
            <bank_branch_name></bank_branch_name>
            <bank_branch_code></bank_branch_code>
            <bank_accept_date></bank_accept_date>
            <bank_branch_accept_date></bank_branch_accept_date>
            <delivery_date>2014-09-22 10:41:00+00</delivery_date>
            <processed_date></processed_date>
            <processed_by></processed_by>
            <delivery_date>2014-09-22 10:41:00+00</delivery_date>
            <trans_type>Cash Collection</trans_type>
            <benef_name>
                <![CDATA[MUM AND DAD]]>
</benef_name>
            <benef_tel>
                <![CDATA[45124897217421]]>
</benef_tel>
            <benef_mobile>
                <![CDATA[]]>
</benef_mobile>
            <benef_email>
                <![CDATA[hani.safa@remitone.com]]>
```

```
</benef_email>
            <collection_point>
                <![CDATA[COLLECTION POINT  UK]]>
</collection_point>
            <collection_point_bank>
                <![CDATA[DELIVERY BANK UK]]>
</collection_point_bank>
            <collection_point_code>
                <![CDATA[]]>
</collection_point_code>
            <collection_pin>
                <![CDATA[1497974]]>
</collection_pin>
            <benef_id_type>
                <![CDATA[NONE]]>
</benef_id_type>
            <benef_id_detail>
                <![CDATA[]]>
</benef_id_detail>
            <benef_ac>
                <![CDATA[]]>
</benef_ac>
            <benef_bank_swift_code>
                <![CDATA[]]>
</benef_bank_swift_code>
            <benef_bank>
                <![CDATA[]]>
</benef_bank>
            <benef_branch>
                <![CDATA[]]>
</benef_branch>
            <benef_branch_code>
                <![CDATA[]]>
</benef_branch_code>
            <benef_bank_city>
                <![CDATA[]]>
</benef_bank_city>
            <benef_bank_state>
                <![CDATA[]]>
</benef_bank_state>
            <benef_card_number>
                <![CDATA[]]>
</benef_card_number>
            <benef_address1>
                <![CDATA[]]>
</benef_address1>
            <benef_address2>
                <![CDATA[]]>
</benef_address2>
            <benef_address3>
                <![CDATA[]]>
</benef_address3>
            <benef_city>
                <![CDATA[]]>
</benef_city>
            <benef_state>
                <![CDATA[WALTHAMSTOW]]>
```

```
</benef_state>
            <benef_postcode>
                <![CDATA[E17]]>
</benef_postcode>
            <benef_mobiletransfer_number>
                <![CDATA[]]>
</benef_mobiletransfer_number>
            <benef_mobiletransfer_network>
                <![CDATA[]]>
</benef_mobiletransfer_network>
            <delivery_notes>
                <![CDATA[]]>
</delivery_notes>
            <utility_company><![CDATA[]]></utility_company>
            <utility_account_no><![CDATA[]]></utility_account_no>
            <utility_invoice><![CDATA[]]></utility_invoice>
            <utility_bank><![CDATA[]]></utility_bank>
            <utility_bank_code><![CDATA[]]></utility_bank_code>
            <utility_description><![CDATA[]]></utility_description>
            <remitter_name>
                <![CDATA[HANI SAFA]]>
</remitter_name>
            <send_country>UK-USD</send_country>
            <send_currency>USD</send_currency>
            <send_amount>10.00</send_amount>
            <rate>1.00000000</rate>
            <receive_country>UK-USD</receive_country>
            <receive_currency>USD</receive_currency>
            <receive_amount>10.00</receive_amount>
            <bank_sequence></bank_sequence>
            <pay_method></pay_method>
            <issue_date></issue_date>
            <bank_ref></bank_ref>
            <benef_trans_ref>RC000224000133</benef_trans_ref>
            <bank_comments></bank_comments>
            <bank_credit_date></bank_credit_date>
            <bank_clear_date></bank_clear_date>
        </transaction>
    </result>
</response>
```

---

processCashCollectionTransaction

Group: **transaction**
Method: **processCashCollectionTransaction**

Process cash collection transaction as a **BIDI** agent.

Name	Type	Notes
trans_ref	Text	Transaction reference number
collection_pin_number	Text	Collection pin number
benef_id_type	Text	Beneficiary ID Type
beneficiary_id_no	Text	Beneficiary ID number
security_question	Text	Security question
security_answer	Text	Security answer

Input fields:
Need to input the trans_ref or/and collection_pin_number depending on the configuration setting.

Example Output XML :

```
<?xml version="1.0" encoding="utf-8"?>
<response>
    <status>SUCCESS</status>
    <result>
        <trans_ref>RC000224000133</trans_ref>
        <process_result>SUCCESS</process_result>
        <message></message>
    </result>
</response>
```

---

getErrorTransactions

Group : **transaction**
Method : **getErrorTransactions**

Input fields :

Name	Type	Notes
from_date	Date	YYYY-MM-DD
to_date	Date	YYYY-MM-DD

Example Output XML :

```
<?xml version="1.0" encoding="utf-8"?>
<response>
    <responseId>326</responseId>
```

```
        <status>SUCCESS</status>
        <result>
            <count>{$trans_count}</count>
            <transactions>
                <transaction>
                    <trans_ref>CC123456789</trans_ref>
                    <agent_trans_ref></agent_trans_ref>
                    <trans_type>CASH_COLLECTION</trans_type>
                    <status>ERROR</status>
                    <error_date>2016-02-26</error_date>
                    <error_reason>Invalid Beneficiary ID</error_reason>
<previous_status_before_error>SENT_FOR_PAY</previous_status_before_error>
                    <error_user_id>1</error_user_id>
                    <error_username>admin</error_username>
                    <error_agent_code>123</error_agent_code>
                    <error_agent_name>Admin</error_agent_name>
                    <remitter_id>10000</remitter_id>
                    <remitter_name>John Doe</remitter_name>
                    <beneficiary_id>1</beneficiary_id>
                    <beneficiary_name>Jane Doe</beneficiary_name>
                    <destination_country>China</destination_country>
                    <originating_country>France</originating_country>
                    <source_currency>EUR</source_currency>
                    <source_transfer_amount>42</source_transfer_amount>
                    <rate>13.37</rate>
                    <destination_currency>CNY</destination_currency>
                    <destination_amount>561.54</destination_amount>
                    <delivery_date></delivery_date>
                </transaction>
            </transactions>
        </result>
    </response>
```

---

requestCancellation

Group : **transaction**
Method : **requestCancellation**

Input fields :

Name	Type	Notes
trans_ref	Text	Transaction reference I.e. **RA123451234**

Example Output XML :

```
<?xml version="1.0" encoding="utf-8"?>
<response>
```

```
    <responseId>326</responseId>
    <status>SUCCESS</status>
    <result>
        <trans_ref>RA123451234</trans_ref>
        <message>Transaction successfully aborted</message>
    </result>
</response>
```

Receiving Bank/Agent API

getPayoutTransactions

Group: **transaction**
Method: **getPayoutTransactions**

Get all transactions that have been assigned to receiving Bank/Agent for payout. Note: Calling this method does not assign the transactions to the Bank/Agent. The transaction(s) must be explicitly accepted by calling the method acceptPayoutTransactions for the transaction(s) to be accepted so that the Bank/Agent can payout the transaction.

Input fields:
none (apart from username, password and pin which are required in every invocation).

Example Output XML :

```
<?xml version="1.0" encoding="utf-8"?>
<response>
      <status>SUCCESS</status>
      <result>
            <count>1</count>
            <transactions>
                  <transaction>
                        <trans_ref>RA20079112</trans_ref>
                        <status>HQ_OK</status>
                        <creation_date>2010-05-07 16:25:12.26266</creation_date>
                        <bank_branch_name></bank_branch_name>
                        <bank_branch_code></bank_branch_code>
                        <bank_accept_date>2010-05-07
16:25:12.26266</bank_accept_date>
                        <bank_branch_accept_date></bank_branch_accept_date>
                        <delivery_date>2010-05-14 00:00:00</delivery_date>
                        <processed_date></processed_date>
                        <processed_by></processed_by>
                        <delivery_date>2010-05-14 00:00:00</delivery_date>
                        <trans_type>Account</trans_type>
                        <benef_name>
                              <![CDATA[HASSAN SYFULLAH]]>
                        </benef_name>
                        <benef_tel>
                              <![CDATA[]]>
                        </benef_tel>
                        <benef_email>
                              <![CDATA[]]>
                        </benef_email>
                        <collection_point>
                              <![CDATA[BOGRA]]>
                        </collection_point>
                        <collection_point_code>
```

```
      <![CDATA[]]>
</collection_point_code>
<collection_pin>
      <![CDATA[]]>
</collection_pin>
<benef_id_type>
      <![CDATA[NONE]]>
</benef_id_type>
<benef_id_detail>
      <![CDATA[]]>
</benef_id_detail>
<benef_ac>
      <![CDATA[1234567890]]>
</benef_ac>
<benef_bank>
      <![CDATA[PRIME BANK LIMITED]]>
</benef_bank>
<benef_bank_swift_code>
      <![CDATA[ABC123]>
</benef_bank_swift_code>
<benef_branch>
      <![CDATA[AGRABAD]]>
</benef_branch>
<benef_bank_city>
      <![CDATA[CHITTAGONG]]>
</benef_bank_city>
<benef_bank_state>
      <![CDATA[CHITTAGONG]]>
</benef_bank_state>
<benef_card_number>
      <![CDATA[]]>
</benef_card_number>
<benef_address1>
      <![CDATA[BOGRA]]>
</benef_address1>
<benef_address2>
      <![CDATA[]]>
</benef_address2>
<benef_address3>
      <![CDATA[]]>
</benef_address3>
<benef_city>
      <![CDATA[BOGRA]]>
</benef_city>
<benef_state>
      <![CDATA[]]>
</benef_state>
<benef_postcode>
      <![CDATA[]]>
</benef_postcode>
<benef_mobiletransfer_number>
      <![CDATA[01234567]]>
</benef_mobiletransfer_number>
<benef_mobiletransfer_network>
      <![CDATA[mobileNetwork]]>
</benef_mobiletransfer_network>
<delivery_notes>
      <![CDATA[]]>
</delivery_notes>
```

```
                        <utility_company><![CDATA[]]></utility_company>
                        <utility_account_no><![CDATA[]]></utility_account_no>
                        <utility_invoice><![CDATA[]]></utility_invoice>
                        <utility_bank><![CDATA[]]></utility_bank>
                        <utility_bank_code><![CDATA[]]></utility_bank_code>
                        <utility_description><![CDATA[]]></utility_description>
                        <remitter_name>
                              <![CDATA[ALI IMAN]]>
                        </remitter_name>
                        <remitter_id>1210</remitter_id>
                        <remitter_address>
                              <![CDATA[#123, 10 TEMASEK STREET, SINGAPORE,
SINGAPORE]]>
                        </remitter_address>
                        <remitter_city><![CDATA[]]></remitter_city>
                        <remitter_state><![CDATA[]]></remitter_state>
                        <remitter_type><![CDATA[]]></remitter_type>
                        <remitter_orgtype><![CDATA[]]></remitter_orgtype>
                        <remitter_gender><![CDATA[]]></remitter_gender>
                        <remitter_occupation><![CDATA[]]></remitter_occupation>
                        <remitter_id1_type><![CDATA[]]></remitter_id1_type>
                        <remitter_id1_details><!
[CDATA[]]></remitter_id1_details>
                        <remitter_id1_issue_place><!
[CDATA[]]></remitter_id1_issue_place>
                        <remitter_id1_expiry><![CDATA[]]></remitter_id1_expiry>
                        <remitter_nationality><!
[CDATA[]]></remitter_nationality>
                        <remitter_dob></remitter_dob>
                        <remitter_tel>
                              <![CDATA[]]>
                        </remitter_tel>
                        <remitter_mobile>
                              <![CDATA[]]>
                        </remitter_mobile>
                        <send_country>SG</send_country>
                        <send_currency>SGD</send_currency>
                        <send_amount>85.00</send_amount>
                        <rate>49.2800</rate>
                        <commission>5.00</commission>
                        <fees>0</fees>
                        <paid>90.00</paid>
                        <receive_country>BD</receive_country>
                        <receive_currency>BDT</receive_currency>
                        <receive_amount>4188.80</receive_amount>
                        <bank_sequence>82</bank_sequence>
                        <pay_method></pay_method>
                        <issue_date></issue_date>
                        <bank_ref></bank_ref>
                        <bank_comments></bank_comments>
                        <bank_credit_date></bank_credit_date>
                        <bank_clear_date></bank_clear_date>
                  </transaction>
            </transactions>
      </result>
</response>
```

getPayoutTransactionDetails

Group: **transaction**
Method: **getPayoutTransactionDetails**

Get details of a single transaction that has been allocated to Bank/Agent for payout.

Input fields:

Name	Type	Notes
trans_ref *	Text	

Example Output XML :

```
<?xml version="1.0" encoding="utf-8"?>
<response>
      <status>SUCCESS</status>
      <result>
            <transaction>
                  <trans_ref>RA20079127</trans_ref>
                  <status>HQ_OK</status>
                  <creation_date>2010-05-11 10:28:02.244553</creation_date>
                  <bank_branch_name></bank_branch_name>
                  <bank_branch_code></bank_branch_code>
                  <bank_accept_date>2010-05-11
10:28:35.435216</bank_accept_date>
                  <bank_branch_accept_date></bank_branch_accept_date>
                  <delivery_date>2010-05-18 00:00:00</delivery_date>
                  <processed_date></processed_date>
                  <processed_by></processed_by>
                  <delivery_date>2010-05-18 00:00:00</delivery_date>
                  <trans_type>Account</trans_type>
                  <benef_name>
                        <![CDATA[ZIAD HASSAN SYFULLAH]]>
                  </benef_name>
                  <benef_tel>
                        <![CDATA[]]>
                  </benef_tel>
                  <benef_email>
                        <![CDATA[]]>
                  </benef_email>
                  <collection_point>
                        <![CDATA[BOGRA]]>
                  </collection_point>
                  <collection_point_code>
                        <![CDATA[]]>
                  </collection_point_code>
                  <collection_pin>
                        <![CDATA[]]>
                  </collection_pin>
                  <benef_id_type>
                        <![CDATA[NONE]]>
                  </benef_id_type>
                  <benef_id_detail>
                        <![CDATA[]]>
```

```
</benef_id_detail>
<benef_ac>
      <![CDATA[1234567890]]>
</benef_ac>
<benef_bank>
      <![CDATA[PRIME BANK LIMITED]]>
</benef_bank>
<benef_bank_swift_code>
      <![CDATA[ABC123]>
</benef_bank_swift_code>
<benef_branch>
      <![CDATA[AGRABAD]]>
</benef_branch>
<benef_bank_city>
      <![CDATA[CHITTAGONG]]>
</benef_bank_city>
<benef_bank_state>
      <![CDATA[CHITTAGONG]]>
</benef_bank_state>
<benef_card_number>
      <![CDATA[]]>
</benef_card_number>
<benef_address1>
      <![CDATA[BOGRA]]>
</benef_address1>
<benef_address2>
      <![CDATA[]]>
</benef_address2>
<benef_address3>
      <![CDATA[]]>
</benef_address3>
<benef_city>
      <![CDATA[BOGRA]]>
</benef_city>
<benef_state>
      <![CDATA[]]>
</benef_state>
<benef_postcode>
      <![CDATA[]]>
</benef_postcode>
<benef_mobiletransfer_number>
      <![CDATA[01234567]]>
</benef_mobiletransfer_number>
<benef_mobiletransfer_network>
      <![CDATA[mobileNetwork]]>
</benef_mobiletransfer_network>
<delivery_notes>
      <![CDATA[]]>
</delivery_notes>
<utility_company><![CDATA[]]></utility_company>
<utility_account_no><![CDATA[]]></utility_account_no>
<utility_invoice><![CDATA[]]></utility_invoice>
<utility_bank><![CDATA[]]></utility_bank>
<utility_bank_code><![CDATA[]]></utility_bank_code>
<utility_description><![CDATA[]]></utility_description>
<remitter_name>
      <![CDATA[ALI IMAN]]>
</remitter_name>
<remitter_id>1210</remitter_id>
```

```
                  <remitter_address>
                        <![CDATA[#123, 10 TEMASEK STREET, SINGAPORE,
SINGAPORE]]>
                  </remitter_address>
                  <remitter_city><![CDATA[]]></remitter_city>
                  <remitter_state><![CDATA[]]></remitter_state>
                  <remitter_type><![CDATA[]]></remitter_type>
                  <remitter_orgtype><![CDATA[]]></remitter_orgtype>
                  <remitter_gender><![CDATA[]]></remitter_gender>
                  <remitter_occupation><![CDATA[]]></remitter_occupation>
                  <remitter_id1_type><![CDATA[]]></remitter_id1_type>
                  <remitter_id1_details><![CDATA[]]></remitter_id1_details>
                  <remitter_id1_issue_place><!
[CDATA[]]></remitter_id1_issue_place>
                  <remitter_id1_expiry><![CDATA[]]></remitter_id1_expiry>
                  <remitter_nationality><![CDATA[]]></remitter_nationality>
                  <remitter_dob></remitter_dob>
                  <remitter_tel>
                        <![CDATA[]]>
                  </remitter_tel>
                  <remitter_mobile>
                        <![CDATA[]]>
                  </remitter_mobile>
                  <send_country>SG</send_country>
                  <send_currency>SGD</send_currency>
                  <send_amount>157.57</send_amount>
                  <rate>49.2800</rate>
                  <commission>5.00</commission>
                  <fees>0</fees>
                  <paid>162.57</paid>
                  <receive_country>BD</receive_country>
                  <receive_currency>BDT</receive_currency>
                  <receive_amount>7765.05</receive_amount>
                  <bank_sequence>2929</bank_sequence>
                  <pay_method></pay_method>
                  <issue_date></issue_date>
                  <bank_ref></bank_ref>
                  <benef_trans_ref>GHT33762634</benef_trans_ref>
                  <bank_comments></bank_comments>
                  <bank_credit_date></bank_credit_date>
                  <bank_clear_date></bank_clear_date>
            </transaction>
      </result>
</response>
```

---

acceptPayoutTransactions

Group: **transaction**
Method: **acceptPayoutTransactions**

Accept transaction(s) so that the Bank/Agent can pay them out to beneficiaries.

Input fields:

Name	Type	Notes
trans_ref *	Text	Multiple transactions can be accepted in one call by providing the transaction references of all the transactions separated by commas.

Example Output XML :

```
<?xml version="1.0" encoding="utf-8"?>
<response>
      <status>SUCCESS</status>
      <result>
            <total_count>2</total_count>
            <success_count>2</success_count>
            <failed_count>0</failed_count>
            <transactions>
                  <transaction>
                        <trans_ref>RA20079112</trans_ref>
                        <operation_result>SUCCESS</operation_result>
                        <message></message>
                  </transaction>
                  <transaction>
                        <trans_ref>RA20079121</trans_ref>
                        <operation_result>SUCCESS</operation_result>
                        <message></message>
                  </transaction>
            </transactions>
      </result>
</response>
```

---

getCashCollectionTransactionDetails

Group: **transaction**
Method: **getCashCollectionTransactionDetails**

Look up for cash collection transaction as a **BIDI** agent.

Name	Type	Notes
trans_ref	Text	Transaction reference number
collection_pin_number	Text	Collection pin number
security_question	Text	Security question
security_answer	Text	Security answer

Input fields:
Need to input the trans_ref or/and collection_pin_number depending on the configuration setting.

Example Output XML :

```
<?xml version="1.0" encoding="utf-8"?>
<response>
    <status>SUCCESS</status>
    <result>
        <transaction>
            <trans_ref>RC000224000133</trans_ref>
            <status>HQ_OK</status>
            <creation_date>2014-09-19 10:41:40.755687+00</creation_date>
            <purpose>FAMILY SUPPORT</purpose>
            <bank_branch_name></bank_branch_name>
            <bank_branch_code></bank_branch_code>
            <bank_accept_date></bank_accept_date>
            <bank_branch_accept_date></bank_branch_accept_date>
            <delivery_date>2014-09-22 10:41:00+00</delivery_date>
            <processed_date></processed_date>
            <processed_by></processed_by>
            <delivery_date>2014-09-22 10:41:00+00</delivery_date>
            <trans_type>Cash Collection</trans_type>
            <benef_name>
                <![CDATA[MUM AND DAD]]>
</benef_name>
            <benef_tel>
                <![CDATA[45124897217421]]>
</benef_tel>
            <benef_mobile>
                <![CDATA[]]>
</benef_mobile>
            <benef_email>
                <![CDATA[hani.safa@remitone.com]]>
</benef_email>
            <collection_point>
                <![CDATA[COLLECTION POINT  UK]]>
</collection_point>
            <collection_point_bank>
                <![CDATA[DELIVERY BANK UK]]>
</collection_point_bank>
            <collection_point_code>
                <![CDATA[]]>
</collection_point_code>
            <collection_pin>
                <![CDATA[1497974]]>
</collection_pin>
            <benef_id_type>
                <![CDATA[NONE]]>
</benef_id_type>
            <benef_id_detail>
                <![CDATA[]]>
</benef_id_detail>
            <benef_ac>
```

```
                <![CDATA[]]>
</benef_ac>
            <benef_bank_swift_code>
                <![CDATA[]]>
</benef_bank_swift_code>
            <benef_bank>
                <![CDATA[]]>
</benef_bank>
            <benef_branch>
                <![CDATA[]]>
</benef_branch>
            <benef_branch_code>
                <![CDATA[]]>
</benef_branch_code>
            <benef_bank_city>
                <![CDATA[]]>
</benef_bank_city>
            <benef_bank_state>
                <![CDATA[]]>
</benef_bank_state>
            <benef_card_number>
                <![CDATA[]]>
</benef_card_number>
            <benef_address1>
                <![CDATA[]]>
</benef_address1>
            <benef_address2>
                <![CDATA[]]>
</benef_address2>
            <benef_address3>
                <![CDATA[]]>
</benef_address3>
            <benef_city>
                <![CDATA[]]>
</benef_city>
            <benef_state>
                <![CDATA[WALTHAMSTOW]]>
</benef_state>
            <benef_postcode>
                <![CDATA[E17]]>
</benef_postcode>
            <benef_mobiletransfer_number>
                <![CDATA[]]>
</benef_mobiletransfer_number>
            <benef_mobiletransfer_network>
                <![CDATA[]]>
</benef_mobiletransfer_network>
            <delivery_notes>
                <![CDATA[]]>
</delivery_notes>
            <utility_company><![CDATA[]]></utility_company>
            <utility_account_no><![CDATA[]]></utility_account_no>
            <utility_invoice><![CDATA[]]></utility_invoice>
            <utility_bank><![CDATA[]]></utility_bank>
            <utility_bank_code><![CDATA[]]></utility_bank_code>
            <utility_description><![CDATA[]]></utility_description>
            <remitter_name>
```

```
                <![CDATA[HANI SAFA]]>
</remitter_name>
            <send_country>UK-USD</send_country>
            <send_currency>USD</send_currency>
            <send_amount>10.00</send_amount>
            <rate>1.00000000</rate>
            <receive_country>UK-USD</receive_country>
            <receive_currency>USD</receive_currency>
            <receive_amount>10.00</receive_amount>
            <bank_sequence></bank_sequence>
            <pay_method></pay_method>
            <issue_date></issue_date>
            <bank_ref></bank_ref>
            <benef_trans_ref>RC000224000133</benef_trans_ref>
            <bank_comments></bank_comments>
            <bank_credit_date></bank_credit_date>
            <bank_clear_date></bank_clear_date>
        </transaction>
    </result>
```
</response>

getPendingPayoutTransactions

Group: **transaction**
Method: **getPendingPayoutTransactions**

Get all transactions that are to be paid to beneficiaries by the Bank/Agent. So these are transactions that were allocated to the Bank/Agent and the Bank/Agent explicitly accepted them.

Input fields:

none (apart from username, password and pin which are required in every invocation).

Example Output XML :

```
<?xml version="1.0" encoding="utf-8"?>
<response>
      <status>SUCCESS</status>
      <result>
            <count>1</count>
            <transactions>
                  <transaction>
                        <trans_ref>RT20278150</trans_ref>
                        <status>SENT_FOR_DELIVERY</status>
                        <creation_date>2010-03-21
17:09:13.622815</creation_date>
                        <bank_branch_name>DAULATPUR</bank_branch_name>
                        <bank_branch_code>47-1170</bank_branch_code>
                        <bank_accept_date>2010-03-21
```

```
17:39:48.760175</bank_accept_date>
                        <bank_branch_accept_date></bank_branch_accept_date>
                        <delivery_date>2010-03-21 00:00:00</delivery_date>
                        <processed_date></processed_date>
                        <processed_by></processed_by>
                        <delivery_date>2010-03-21 00:00:00</delivery_date>
                        <trans_type>Cash Collection</trans_type>
                        <benef_name>
                              <![CDATA[MD SAIFUL ISLAM]]>
                        </benef_name>
                        <benef_tel>
                              <![CDATA[08215112686]]>
                        </benef_tel>
                        <benef_email>
                              <![CDATA[]]>
                        </benef_email>
                        <collection_point>
                              <![CDATA[DAULATPUR, PUBALI]]>
                        </collection_point>
                        <collection_point_code>
                              <![CDATA[47-1170]]>
                        </collection_point_code>
                        <collection_pin>
                              <![CDATA[12345678]]>
                        </collection_pin>
                        <benef_id_type>
                              <![CDATA[NATIONAL_ID]]>
                        </benef_id_type>
                        <benef_id_detail>
                              <![CDATA[]]>
                        </benef_id_detail>
                        <benef_ac>
                              <![CDATA[]]>
                        </benef_ac>
                        <benef_bank>
                              <![CDATA[PUBALI BANK LIMITED]]>
                        </benef_bank>
                        <benef_bank_swift_code>
                              <![CDATA[ABC123]>
                        </benef_bank_swift_code>
                        <benef_branch>
                              <![CDATA[DAULATPUR]]>
                        </benef_branch>
                        <benef_bank_city>
                              <![CDATA[MANIKGONJ]]>
                        </benef_bank_city>
                        <benef_bank_state>
                              <![CDATA[MANIKGONJ]]>
                        </benef_bank_state>
                        <benef_card_number>
                              <![CDATA[]]>
                        </benef_card_number>
                        <benef_address1>
                              <![CDATA[MANIKGONJ]]>
                        </benef_address1>
                        <benef_address2>
                              <![CDATA[]]>
                        </benef_address2>
                        <benef_address3>
```

```
                        <![CDATA[]]>
                    </benef_address3>
                    <benef_city>
                        <![CDATA[MANIKGONJ]]>
                    </benef_city>
                    <benef_state>
                        <![CDATA[]]>
                    </benef_state>
                    <benef_postcode>
                        <![CDATA[]]>
                    </benef_postcode>
                    <benef_mobiletransfer_number>
                        <![CDATA[01234567]]>
                    </benef_mobiletransfer_number>
                    <benef_mobiletransfer_network>
                        <![CDATA[mobileNetwork]]>
                    </benef_mobiletransfer_network>
                    <delivery_notes>
                        <![CDATA[]]>
                    </delivery_notes>
<utility_company><![CDATA[]]></utility_company>
                    <utility_account_no><![CDATA[]]></utility_account_no>
                    <utility_invoice><![CDATA[]]></utility_invoice>
                    <utility_bank><![CDATA[]]></utility_bank>
                    <utility_bank_code><![CDATA[]]></utility_bank_code>
                    <utility_description><![CDATA[]]></utility_description>
                    <remitter_name>
                        <![CDATA[ALI IMAN]]>
                    </remitter_name>
                    <remitter_id>1210</remitter_id>
                    <remitter_address>
                        <![CDATA[#123, 10 TEMASEK STREET, SINGAPORE,
SINGAPORE]]>
                    </remitter_address>
                    <remitter_city><![CDATA[]]></remitter_city>
                    <remitter_state><![CDATA[]]></remitter_state>
                    <remitter_type><![CDATA[]]></remitter_type>
                    <remitter_orgtype><![CDATA[]]></remitter_orgtype>
                    <remitter_gender><![CDATA[]]></remitter_gender>
                    <remitter_occupation><![CDATA[]]></remitter_occupation>
                    <remitter_id1_type><![CDATA[]]></remitter_id1_type>
                    <remitter_id1_details><!
[CDATA[]]></remitter_id1_details>
                    <remitter_id1_issue_place><!
[CDATA[]]></remitter_id1_issue_place>
                    <remitter_id1_expiry><![CDATA[]]></remitter_id1_expiry>
                    <remitter_nationality><!
[CDATA[]]></remitter_nationality>
                    <remitter_dob></remitter_dob>
                    <remitter_tel>
                        <![CDATA[98012322]]>
                    </remitter_tel>
                    <remitter_mobile>
                        <![CDATA[]]>
                    </remitter_mobile>
                    <send_country>SG</send_country>
                    <send_currency>SGD</send_currency>
                    <send_amount>345.00</send_amount>
                    <rate>49.4000</rate>
```

```
                        <commission>5.00</commission>
                        <fees>0</fees>
                        <paid>350.00</paid>
                        <receive_country>BD</receive_country>
                        <receive_currency>BDT</receive_currency>
                        <receive_amount>17043.00</receive_amount>
                        <bank_sequence>65</bank_sequence>
                        <pay_method></pay_method>
                        <issue_date></issue_date>
                        <bank_ref></bank_ref>
                        <bank_comments></bank_comments>
                        <bank_credit_date></bank_credit_date>
                        <bank_clear_date></bank_clear_date>
                    </transaction>
                </transactions>
            </result>
</response>
```

---

processPayoutTransaction

Group: **transaction**
Method: **processPayoutTransaction**

Inform the RemitONE system that a transaction that was accepted by the Bank/Agent for payout has paid out and should be marked as processed with the details provided.

Input fields:

Name	Type	Notes
trans_ref *	Text	
pay_method *	Text	How the transaction was paid out.
bank_credit_date	Date	YYYY-MM-DD
bank_clear_date	Date	YYYY-MM-DD
po_clear_date	Date	YYYY-MM-DD
benef_id_type	Text	The type of ID the beneficiary provided at payout (if applicable)
benef_id_details	Text	The details of the ID provided at payout.
issue_date	Date	YYYY-MM-DD
bank_ref	Text	
bank_comments	Text	

Example Output XML :

```
<?xml version="1.0" encoding="utf-8"?>
<response>
	<status>SUCCESS</status>
	<result>
		<trans_ref>RA20079121</trans_ref>
		<process_result>SUCCESS</process_result>
		<message></message>
	</result>
</response>
```

---

errorPayoutTransaction

Group: **transaction**
Method: **errorPayoutTransaction**

Inform the RemitONE system that there is something wrong with this transaction that prevents the Bank/Agent being able to payout the transaction so it should be marked as ERROR.

Input fields:

Name	Type	Notes
trans_ref *	Text	
error_reason *	Text	The overall reason for error.
error_details	Text	Details of the error.

Example Output XML :

```
<?xml version="1.0" encoding="utf-8"?>
<response>
	<status>SUCCESS</status>
	<result>
		<trans_ref>RA20079084</trans_ref>
		<error_result>SUCCESS</error_result>
	</result>
</response>
```

---

getErrorTransactions

Group : **transaction**
Method : **getErrorTransactions**

Input fields :

Name	Type	Notes
from_date	Date	YYYY-MM-DD
to_date	Date	YYYY-MM-DD

Example Output XML :

```
<?xml version="1.0" encoding="utf-8"?>
<response>
    <responseId>326</responseId>
    <status>SUCCESS</status>
    <result>
        <count>{$trans_count}</count>
        <transactions>
            <transaction>
                <trans_ref>CC123456789</trans_ref>
                <agent_trans_ref></agent_trans_ref>
                <trans_type>CASH_COLLECTION</trans_type>
                <status>ERROR</status>
                <error_date>2016-02-26</error_date>
                <error_reason>Invalid Beneficiary ID</error_reason>
<previous_status_before_error>SENT_FOR_PAY</previous_status_before_error>
                <error_user_id>1</error_user_id>
                <error_username>admin</error_username>
                <error_agent_code>123</error_agent_code>
                <error_agent_name>Admin</error_agent_name>
                <remitter_id>10000</remitter_id>
                <remitter_name>John Doe</remitter_name>
                <beneficiary_id>1</beneficiary_id>
                <beneficiary_name>Jane Doe</beneficiary_name>
                <destination_country>China</destination_country>
                <originating_country>France</originating_country>
                <source_currency>EUR</source_currency>
                <source_transfer_amount>42</source_transfer_amount>
                <rate>13.37</rate>
                <destination_currency>CNY</destination_currency>
                <destination_amount>561.54</destination_amount>
                <delivery_date></delivery_date>
            </transaction>
        </transactions>
    </result>
</response>
```

3.Testing Web Services Functionality

It is possible to test the output of the WebServices if the system is in debugging mode. The URL for accessing forms for each of the WebServices is :

SYSTEM_URL/wstest/index.html

For example, https://www.remitone.com/wstest/index.html

You can enter values for each of the WebService Forms and the result will be presented back as neatly formatted HTML.

If the system is in live mode, then the result will be returned as pure XML, and hence you can still use the 'View Source' option in the Web Browser to see the XML that is returned.

Using Web Services in a Live Environment: Some suggestions

Sending Agent API

Although it is possible to use the WebServices in any way that seems fit, we would suggest the following procedure.

1. Obtain a list of valid Destination Countries using **getDestinationCountries**. This can be done on a weekly or monthly basis.
2. Obtain the current Agent Credit level using **getCurrentCredit**. The credit response will also indicate the *source currency* that the system is expecting transactions to be created in.
3. Create a new remitter using **createRemitter**, or search for an existing one using **searchRemitter**.
4. Create a new beneficiary using **createBeneficiary**, or search for an existing one using **searchBeneficiary**.
5. Create a transaction between this remitter and beneficiary by calling **createTransaction**.
6. Receive a transaction creation response containing the actual charges as calculated by the system, compliance check results, and a temporary transaction session id. It is the responsibility of the user to examine these results.
7. Once the user is satisfied with the results, call **confirmTransaction** and provide the temporary transaction session id from step 6 above to actually create the transaction in the system.
8. At some later time, **getTransactionStatus** or **getTransactionStatusByAgentTranRef** can be used to determine whether the transaction has been processed.

Receiving Agent API

In general, we suggest the following procedure :

1. Call **getPayoutTransactions** to get a list of transactions that need to be paid out by your Processing Bank.
2. Call **acceptPayoutTransactions** to 'accept' the transactions that you agree to payout. This will bring the status of the transactions to SENT_FOR_PAY or SENT_FOR_DELIVERY.
3. From your own systems, payout the transactions to the beneficiaries.
4. For each transaction that is paid out, call **processPayoutTransaction**.
5. If there is an error in processing a transaction call **errorPayoutTransaction**. These transactions will then need to be corrected by Admin and then passed back for payout.

Appendix A : Destination Country ISO Codes

Name	ISO code	Currency
Afghanistan	AF	AFA
Albania	AL	ALL
Algeria	DZ	DZD
American Samoa	AS	
Andorra	AD	ADP
Angola	AO	AON
Anguilla	AI	
Antarctica	AQ	
Antigua and Barbuda	AG	
Argentina	AR	ARS
Armenia	AM	AMD
Aruba	AW	AWG
Australia	AU	AUD
Austria	AT	EUR
Azerbaijan	AZ	AZN
Bahamas	BS	BSD
Bahrain	BH	BHD
Bangladesh	BD	BDT
Barbados	BB	BBD
Belarus	BY	BYR
Belgium	BE	EUR
Belize	BZ	BZD
Benin	BJ	
Bermuda	BM	BMD
Bhutan	BT	BTN
Bolivia	BO	BOB
Bosnia and Herzegovina	BA	BAM
Botswana	BW	BWP
Bouvet Island	BV	
Brazil	BR	BRE
British Indian Ocean Territory	IO	
Brunei Darussalam	BN	BND

Bulgaria	BG	BGL
Burkina Faso	BF	
Burundi	BI	BIF
Cambodia	KH	KHR
Cameroon	CM	XAF
Canada	CA	CAD
Cape Verde	CV	CVE
Cayman Islands	KY	KYD
Central African Republic	CF	XAF
Chad	TD	XAF
Chile	CL	CLF
China	CN	CNY
Christmas Island	CX	
Cocos (Keeling) Islands	CC	
Colombia	CO	COP
Comoros	KM	
Congo	CG	
Congo, the Democratic Republic of the	CD	
Cook Islands	CK	
Costa Rica	CR	CRC
Cote D_Ivoire	CI	
Croatia	HR	HRK
Cuba	CU	CUP
Cyprus	CY	CYP
Czech Republic	CZ	CZK
Denmark	DK	DKK
Djibouti	DJ	DJF
Dominica	DM	
Dominican Republic	DO	DOP
Ecuador	EC	ECS
Egypt	EG	EGP
El Salvador	SV	SVC
Equatorial Guinea	GQ	
Eritrea	ER	
Estonia	EE	EEK
Ethiopia	ET	ETB

Falkland Islands (Malvinas)	FK	
Faroe Islands	FO	
Fiji	FJ	FJD
Finland	FI	EUR
France	FR	EUR
French Guiana	GF	
French Polynesia	PF	
French Southern Territories	TF	
Gabon	GA	
Gambia	GM	GMD
Georgia	GE	
Germany	DE	EUR
Ghana	GH	GHC
Gibraltar	GI	GIP
Greece	GR	GRD
Greenland	GL	
Grenada	GD	
Guadeloupe	GP	
Guam	GU	
Guatemala	GT	GTQ
Guinea	GN	GNF
Guinea-Bissau	GW	GWP
Guyana	GY	GYD
Haiti	HT	HTG
Heard Island and Mcdonald Islands	HM	
Holy See (Vatican City State)	VA	
Honduras	HN	HNL
Hong Kong	HK	HKD
Hungary	HU	HUF
Iceland	IS	ISK
India	IN	INR
Indonesia	ID	IDR
Iran, Islamic Republic of	IR	
Iraq	IQ	IQD
Ireland	IE	EUR
Israel	IL	ILS

Italy	IT	EUR
Jamaica	JM	JMD
Japan	JP	JPY
Jordan	JO	JOD
Kazakhstan	KZ	
Kenya	KE	KES
Kiribati	KI	
Korea, Democratic People's Republic of	KP	
Korea, Republic of	KR	
Kuwait	KW	KWD
Kyrgyzstan	KG	
Lao People's Democratic Republic	LA	
Latvia	LV	
Lebanon	LB	LBP
Lesotho	LS	LSL
Liberia	LR	LRD
Libyan Arab Jamahiriya	LY	LYD
Liechtenstein	LI	
Lithuania	LT	
Luxembourg	LU	EUR
Macao	MO	
Macedonia, the Former Yugoslav Republic of	MK	
Madagascar	MG	MGF
Malawi	MW	MWK
Malaysia	MY	MYR
Maldives	MV	
Mali	ML	
Malta	MT	MTL
Marshall Islands	MH	
Martinique	MQ	
Mauritania	MR	MRO
Mauritius	MU	MUR
Mayotte	YT	
Mexico	MX	MXP
Micronesia, Federated States of	FM	
Moldova, Republic of	MD	

Monaco	MC	
Mongolia	MN	MNT
Montserrat	MS	
Morocco	MA	MAD
Mozambique	MZ	MZN
Myanmar	MM	
Namibia	NA	
Nauru	NR	
Nepal	NP	NPR
Netherlands	NL	EUR
Netherlands Antilles	AN	ANG
New Caledonia	NC	
New Zealand	NZ	NZD
Nicaragua	NI	NIO
Niger	NE	
Nigeria	NG	NGN
Niue	NU	
Norfolk Island	NF	
Northern Mariana Islands	MP	
Norway	NO	NOK
Oman	OM	OMR
Pakistan	PK	PKR
Palau	PW	
Palestinian Territory, Occupied	PS	
Panama	PA	PAB
Papua New Guinea	PG	PGK
Paraguay	PY	PYG
Peru	PE	PEN
Philippines	PH	PHP
Pitcairn	PN	
Poland	PL	PLZ
Portugal	PT	EUR
Puerto Rico	PR	
Qatar	QA	QAR
Reunion	RE	
Romania	RO	ROL

Russian Federation	RU	
Rwanda	RW	RWF
Saint Helena	SH	
Saint Kitts and Nevis	KN	
Saint Lucia	LC	
Saint Pierre and Miquelon	PM	
Saint Vincent and the Grenadines	VC	
Samoa	WS	WST
San Marino	SM	
Sao Tome and Principe	ST	
Saudi Arabia	SA	SAR
Senegal	SN	
Serbia and Montenegro	CS	
Seychelles	SC	SCR
Sierra Leone	SL	SLL
Singapore	SG	SGD
Slovakia	SK	
Slovenia	SI	
Solomon Islands	SB	SBD
Somalia	SO	SOS
South Africa	ZA	ZAR
South Georgia and the South Sandwich Islands	GS	
Spain	ES	EUR
Sri Lanka	LK	LKR
Sudan	SD	SDP
Suriname	SR	
Svalbard and Jan Mayen	SJ	
Swaziland	SZ	SZL
Sweden	SE	SEK
Switzerland	CH	CHF
Syrian Arab Republic	SY	
Taiwan, Province of China	TW	
Tajikistan	TJ	
Tanzania, United Republic of	TZ	
Thailand	TH	THB
Timor-Leste	TL	

Togo	TG	
Tokelau	TK	
Tonga	TO	TOP
Trinidad and Tobago	TT	TTD
Tunisia	TN	TND
Turkey	TR	TRL
Turkmenistan	TM	
Turks and Caicos Islands	TC	
Tuvalu	TV	
Uganda	UG	UGX
Ukraine	UA	
United Arab Emirates	AE	AED
United Kingdom	GB	GBP
United States	US	USD
United States Minor Outlying Islands	UM	
Uruguay	UY	UYP
Uzbekistan	UZ	
Vanuatu	VU	VUV
Venezuela	VE	VEB
Vietnam	VN	
Virgin Islands, British	VG	
Virgin Islands, U.s.	VI	
Wallis and Futuna	WF	
Western Sahara	EH	
Yemen	YE	YER
Zambia	ZM	ZMK
Zimbabwe	ZW	ZWD

Appendix B : Remitter ID Type Codes

Code	Description
Passport	Passport
Driving_License	Driving License
National_Insurance	National Insurance No.
National_ID	National ID
Utility_Bill	Utility Bill
Other	Other

Appendix C : Beneficiary ID Type Codes

Code	Description
PASSPORT	Passport
CHEQUEBOOK	Cheque Book
DRIVINGLICENSE	Driving License
NATIONALID	National ID
VOTINGCARD	Voting Card
OTHER	Other form of ID

Appendix D : Payment Method Codes

Code	Description
1	Cash
2	Cheque
3	Bank Transfer

Note: These codes may vary – please confirm with your Administrator

Appendix E : Service Level (Delivery Speed) Codes

Code	Description
1	5 Days
2	Next Day
3	Immediate

Note: These codes may vary – please confirm with your Administrator

Appendix F : Source of Income Codes

Code	Description
1	Salary
2	Business
3	Return on Investment
4	Gift
5	Pension

Note: These codes may vary – please confirm with your Administrator

Appendix G : Remittance Purpose Codes

Code	Description
1	Family Support
2	Medical Support
3	Education Support
4	Investment
5	Charity

Appendix H : Transaction Statuses

Status	Description
PENDING_CLEARANCE	Transaction has been created in the system but the remitter has not paid for transaction. Awaiting payment before transaction will be ready for processing.
ENTERED	Transaction awaiting approval by sending agent before processing.
AGENT_OK	Transaction awaiting HQ approval or routing before processing.
HQ_READY	Transaction has been approved by HQ and will be sent to processing bank/agent in the next batch. This only applies if you are using batch processing.
HQ_OK	Transaction awaiting processing bank/agent approval before ready for processing.
HQ_OK_PAID	Transaction awaiting processing bank/agent approval before ready for processing but transaction has been credited to processing bank/agent already. This status only applies in error correction scenarios.
SENT_FOR_PAY	Transaction ready to be paid out by processing bank/agent.
SENT_FOR_DELIVERY	Transaction ready to be paid out by processing bank/agent branch.
PROCESSED	Transaction has been processed.
ABORTED	Transaction has been accepted by processing bank/agent but now it has been requested to be cancelled. Awaiting processing bank/agent approval for cancellation or rejection of cancellation request.
ERROR	Transaction has some problem with it and is going through error correction cycle.
DELETED	Transaction has been cancelled.