PAYOUT API INTERFACE
Version 3.0

Technical Specifications Document

05-Mar-2015

Direct all queries related to this document and the Sigue API to:

partneronboardingintl@sigue.com

Document Confidentiality

All rights reserved. The content of this document is property of Sigue, confidential and copyrighted. Any reproduction in whole or in part is strictly prohibited without the written permission of Sigue. This document is subject to change. Comments, corrections or questions should be directed to the email id provided above.

Contents

1 Introduction 3
1.1 Scope of this document 3
1.2 Usage Policies and Guidelines 4
1.3 Connecting to the Sigue Payout API 5
2 Change Summary 6
3 API Methods Summary List 7
3.1 General Features 9
4 API Method Specifications 10
4.1 Payout Query (for cash transactions only) 10
4.2 Payout Search by Name (for cash transactions only) 13
4.3 Payout Update 15
4.4 Payout Confirmation (for cash transactions only) 17
4.5 Workflow Payout Query 18
4.6 Workflow Payout Query New 20
4.7 Workflow Payout Update 23
4.8 Nominated Payout Query (cash payout only) 24
4.9 Nominated Payout Update (cash payout only) 26
4.10 Get Settlement Report 27
4.11 Rollback Transaction 29
4.12 Get ID Types 29
4.13 Get Response Codes 30
4.14 Get Country Codes 30
4.15 Get Currency Code 31
4.16 Get Settlement Report USD 31
Appendix A: Testing and Certification 34
Appendix B: Request Sample Response Codes 35
Appendix C: Transaction Status Codes 39

1 Introduction

Sigue Money Transfer (SMT) has developed an online Application Programming Interface (API) to allow partners to connect the Sigue processing engine using their own front-end transaction capture application. The API offers all the required functional interface methods to allow partners to capture, submit and view transactions with SMT.

1.1 Scope of this document

This document will describe what the SMT API interface is designed to do and how it can be used. It also contains technical information to provide a general working direction for the Payout Partner.

The document also lists the Usage Policies and Guidelines.

The document includes a Change Summary section for the benefit of existing partners so they can focus on the incremental changes.

The Testing and Certification process is described at a high level.

In the Appendix, sample codes and reference XML files have been included for illustration.

1.2 Usage Policies and Guidelines

The contents of this document describe the Sigue Payout API implementation. However, both the API implementation and this document are subject to change based on business or technical requirements. Before commencing any integration development please check with the email id provided on the cover page for the latest version.

Partners should base their development of the interface on the live WSDL that will be provided by SMT upon request after an NDA or contract is signed and development by the partner is about to start.

All enhancements and modifications to the API will be classified as Mandatory and Optional.

Mandatory changes are generally as a result of regulatory or business process changes or technical issues. Partners will have to make the mandatory changes within the specified timeframe, without which they may not be able to connect to Sigue systems to execute transactions. Partners will be given as much notice as possible, however, based on the nature of the change and its implications, the notice may be short.

Optional changes are generally enhancements to offer new and enhanced features. Partners are encouraged to implement these changes at the earliest to take advantage of the new features, however, no deadlines will be enforced.

1.3 Connecting to the Sigue Payout API

There are two versions of the Sigue Payout API, test and production.

The test version is to be used by partners to ensure their application is working fine, before it is released to production. Sigue follows a comprehensive testing and certification process, on the successful completion of which, partners are granted access to the production system. Please see the section on Testing and Certification.

The production version is to be used by partners when they are ready to start sending live transactions to Sigue.

Access to the Sigue environments will be provided to appropriate partner environments. The test environment may only be access by the partner test environment and the production environment may only be accessed by the partner production environment. It will not be possible to provide access to the two environments from the same server on the partner side. Which means partners are expected to maintain a minimum of two servers, one for development and testing and one for production.

Access to both environments requires network and application level access credentials which can be obtained once all the on-boarding formalities are completed.

Once a development and testing schedule has been agreed upon, you will be provided with the following information:

- The URL to access the Test API environment
- Access credentials

SMT requires the following information from partners:

- One or more public static IP address for development and testing servers. Please note that requests only from this IP address will be able to connect to the Sigue API environment.

The SMT API builds on the standard Web Services model to provide security for messages from and to partner applications. Access to the API is over a secure HTTP (https) connection and all data traffic will be encrypted using SSL.

2 Change Summary

This section lists the changes made to the SMT Payout API from Version 2.0 to Version 3.0.

Change Description	**Mandatory (Deadline) /Optional**
1. A new method has been added to the API: - **Workflow Payout Query New (Response)** This method has to be developed mandatory, none the less some of the fields are optional when capturing a transaction, refer to the detail in section 4.6.1 This method has the following changes: i. To support payout in certain countries that have four-part names, two name fields have been added (Second First Name and Second Last Name). ii. To support Account Deposit payout in certain countries, Bank Account Type, Bank State have been added as mandatory fields. iii. To support Account Deposit payout in certain countries, Primary ID Type and Primary ID Number *Note: The existing method for Payout will continue to work as-is so there will be no disruptions to the integration while the new method is being integrated.*	Mandatory (30-Jun-15)

3 API Methods Summary List

The SMT Payout API is meant for use by all Payout Partners who would like to use their own transaction capture application. The API supports all SMT products, currently including Cash Pickup, Account Deposit and Cash Delivery.

The SMT Payout API provides the following functional methods.

- Get Country Codes
  This method is used to download standard 3 alphabets country ISO code.

- Get Currency Codes
  This method is used to download standard 3 alphabets currency ISO code.

- Get ID Types
  This method is used to request a list of all the ID types SMT uses.

- Get Response Codes
  This method is used to download up to date response codes generated by the API.

- Get Settlement Report
  This method is used to request a settlement report, provided the settlement process has been run for that period. The method only allows retrieving the settlement report no more than 3 months old.

- Get Settlement Report USD
  This method is used to request any settlement report on demand, provided the settlement process has been run. This method provides settlement values and FX revenue details in USD. The method only allows retrieving the settlement report no more than 3 months old.

- Nominated Payout Query
  This method is used to pull down all transactions that are nominated to be paid and cancelled. The API method retrieves only the transactions that the agent can mark as paid, acknowledged or canceled.

- Nominated Payout Update
  This method allows partner to do the followings:
  - Partner will consume API method NominatedPayoutUpdate to send acknowledge status for each transaction that should be paid.
  - Partner will consume API method NominatedPayoutUpdate to send cancellation confirmation for each transaction that can be cancelled.
  - Partner will consume API method NominatedPayoutUpdate to send cancellation refused for each transaction that can’t be cancelled.

- Payout Search By Name (for Cash transactions only)
  This method is used to request the details of a specific transaction to pay out, using the beneficiary’s last name and the originating country for the transaction. The partner application will provide valid values for the required parameters, and the system will validate the request against the business rules for a payout. If valid, the

full transaction details will be returned. The message will apply to transactions which can be paid out in cash only.

- Roll Back Paid Transaction
  This method is used to rollback a transaction to its previous state. This will usually occur if the partner encounters an error on their system after they have paid out a transaction. The request to rollback a transaction will not always be granted but a reason will be given.

- Work Flow Payout Query
  This method is used to retrieve the details of any transactions which require an Account Deposit and Courier Delivery payout service. The frequency with which the partner application calls this service will be agreed with the partner on a case by case basis, as it cannot be enforced or controlled by the SMT system.

- Work Flow Payout Query New
  This method is used to retrieve the details of any transactions which require an Account Deposit and Courier Delivery payout service. The frequency with which the partner application calls this service will be agreed with the partner on a case by case basis, as it cannot be enforced or controlled by the SMT system.

- Work Flow Payout Update
  This method is used to send an update for an Account Deposit or Cash Delivery transaction, for which the details have previously been obtained using the Workflow Payout Query. Reasons for update will include:
  - Confirmed Successful Payout
  - Acknowledgement of Transaction resulting from Workflow Payout Query
  - Confirmation of cancellation (as result of Send Agent's request)
  - Refer back to sending agent (problem with account detail or incorrect address)

- Payout Query (for Cash transactions only)
  This method is used to request the details of a specific transaction to pay out, using the SMT transaction number or any other partner-specific payout number (if supported). The partner application must provide valid values for the required parameters. The system will validate the request against the business rules for a payout. If valid, the full transaction details will be returned. The message will apply to transactions which can be paid out in cash only.

- Payout Update
  This method is used to send an update for an SMT cash transaction, for which details have previously been obtained using the Payout Query method.
  Reasons for update would include:
  - Payout
    This will be validated against the business rules for paying transactions. It is the equivalent of the Payout screen.
  - Payout Confirmation
    This is an optional step where Payout partner wish to have a confirmation or commit step in the process of paying out a transaction.

A detailed functional description and the technical specifications for each functional method is provided in the section on API Method Specifications.

3.1 General Features

For Cash Pickup Transactions

- The ability to identify SMT transactions which are intended to be paid out in a specific country. Transactions will be able to be paid out by any Payout Partner, on a first-come, first-serve basis.
- The ability for the Payout Partner to provide a SMT or other external payout number (given to them by a recipient requiring payout) and request the detail of the transaction to be paid out.
- As part of the response to the payout request, SMT will have the ability to validate the payout request against business rules and provide the details to the Payout Partner.
- The ability for the Payout Partner to update SMT with changes in payout status of the transaction.
- In order to minimize processing around Cancellations/Payout to Originator, SMT will not provide full payout transaction details to the partner for Cash transactions in advance, only at the time of actual payout.

For Account Deposit and Cash Delivery Transactions

- The ability for Payout Partner to retrieve details of transactions for payout, thus entering the transaction into the normal SMT workflow processing.
- The ability for the Payout Partner to update SMT with changes in payout status of the transaction.
- The process for SMT to communicate cancellation requests to the Payout Partner by means of online messages (initiated by a Send Agent rather than SMT Operations).
- The ability for Payout Partners to refer transactions back to sending agents.
- Some Payout Partners may require SMT to use the partner's own payout reference number. This option will be made available via the API on a case-by-case basis.

4 API Method Specifications

Notes:

i. Partners will be provided the following access credentials, one set each for test and production. These access credentials must be passed to every method when accessing it.
   - User Name
   - Password
   - Partner Id
   - Agent Id

ii. M = Mandatory and O = Optional

iii. M/O indicates that the field is mandatory under some conditions, optional otherwise.

iv. Product Ids are as listed below:
   - Cash Pickup (Product Id = 1)
   - Account Deposit (Product Id = 22)
   - Cash Delivery (Product Id = 25)

4.1 Payout Query (for cash transactions only)

4.1.1 Request from Partner to SMT

Field Name	Size	Type	Description	M/O
UserName	30	Varchar	User Name issued by SMT as part of access credentials.	M
Pwd	30	Varchar	Password issued by SMT as part of access credentials.	M
PartnerId		Numeric	Partner Id issued by SMT as part of access credentials.	M
AgentId		Int	Agent Id issued by SMT as part of access credentials.	M
TMTNumber		Int	Unique number identifying the SMT order	M
OtherPayoutNumber	30	Varchar	Other payout partner number	O
QueryReason		Int	01 = Payout request	M

4.1.2 Response from SMT to Partner

Field Name	Size	Type	Description	M/O
ResponseCode		Int	Contains code explaining outcome of message request	M
Message	255	Varchar	Text to elaborate on the response code	M
ProcessDateTime		DateTime	System time (GMT) at generating the response in UTC datetime format.	M
TMTNumber		Int	Unique number identifying the SMT order	M
OtherPayoutNumber	15	Varchar	Unique number provided by a payout partner which must be used by recipient to collect money	O
LocalReferenceNumber	30	Varchar	Sending agent's own reference for the transaction	O
StatusCode	2	Char	Status code of the transaction	M
StatusDescription	100	Varchar	Description of the status	M

Field Name	Size	Type	Description	M/O
TransactionDate		DateTime	Date transaction was created in UTC format	M
TransactionPaidDate		DateTime	Date when the transaction was PAID in UTC format. This field will only have value if the transaction has been paid.	O
OriginatingCountry	3	Char	Code identifying the sending country	M
OriginatingCurrency	3	Char	Code identifying the currency of the sending country	M
DestinationCountry	3	Char	Code identifying the receiving country	M
DestinationCurrency	3	Char	Code identifying the currency of the receiving country	M
ExchangeRate	20,6	Decimal	The consumer exchange rate used for the transaction	M
LocalAmount	19,4	Money	Amount of money to be sent in the local currency, i.e. currency of sending country	M
CustomerCharge	19,4	Money	Amount of money paid by the sending customer (localAmount + fees)	M
PayoutAmount	19,4	Money	Amount of money to be paid to the receiver (in payout currency)	M
ProductId		Int	Code identifying the primary product of the transaction	M
ServiceID		Int	Code identifying Value Added product (can be more than one, but currently only available with Money Transfer primary product)	O
Sender details				
GlobeCardNumber		Int	Globe Card number identifying a customer	O
FirstName	50	Varchar	First name of customer	M
LastName	50	Varchar	Last name of customer	M
Address1	100	Varchar	First line of customer address	M
Address2	100	Varchar	Second line of customer address	O
City	50	Varchar	City of customer address	M
State	50	Varchar	State/province of customer address	O
PostCode	10	Varchar	Postal or zip code of customer's address	O
Country	3	Varchar	Country of customer address (ISO code)	M
PhoneNumber	50	Varchar	Phone number of customer	O
MobileNumber	50	Varchar	Mobile number of customer	O
Email	50	Varchar	Email address of customer	O
SenderIdType		INT	The identifying code indicating what type of primary id was shown by the sender. Becomes mandatory if local amount is over a certain threshold (to be provided by SMT). Valid values: 01 – Passport 02 – National ID 03 – Driver's License 04 – Other Government ID 06 – Other	M/O
SenderIdProvided	100	Varchar	The reference number of the primary id shown by the sender, e.g. passport number. Becomes mandatory if ID1Type is Provided.	M/O
SendingAgentId		INT	Unique ID of Sending Agent	O
SendingAgentName	100	Varchar	Legal Name Of Sending Agent	O

Field Name	Size	Type	Description	M/O
Receiver details				
FirstName	50	Varchar	First name of receiving customer	M
LastName	50	Varchar	Last name of receiving customer	M
Address1	100	Varchar	First line of receiving customer address	O
Address2	100	Varchar	Second line of receiving customer address	O
City	50	Varchar	City of receiving customer address	O
State	50	Varchar	State/province of receiving customer address	O
StateCode	50	Varchar	State/province of receiving customer address (valid only for US states)	O
PostCode	10	Varchar	Postal or zip code of sending customer's address	O
Country	3	Varchar	Country of receiving customer address (ISO code)	O
PhoneNumber	50	Varchar	Phone number of receiving customer	O
MobileNumber	50	Varchar	Mobile Number of Receiving customer	O
Email	50	Varchar	Email address of receiving customer	O
TestQuestion	200	Varchar	Test question to be asked of receiver	O
TestAnswer	200	Varchar	Answer to test question	O
DataForServices	500	Varchar	Contains extra information, i.e. message	O
CPFNumber		Int	ID Number of Receiver. Mandatory for recipients in Brazil	O
PayoutAgentName	100	Varchar	Name Of Payout Agent	O

4.2 Payout Search by Name (for cash transactions only)

4.2.1 Request from Partner to SMT

Field Name	Size	Type	Description	M/O
UserName	30	Varchar	User name issued by SMT as part of access credentials.	M
Pwd	30	Varchar	Password issued by SMT as part of access credentials.	M
PartnerId		Numeric	Partner Id issued by SMT as part of access credentials.	M
AgentId		Int	Agent Id issued by SMT as part of access credentials.	M
SearchName	50	Varchar	Receiver Detail LastName.	M
OriginatingCountry	3	Varchar	ISO Code identifying the sending country	M

4.2.2 Response from SMT to Partner

Field Name	Size	Type	Description	M/O
ResponseCode		Int	Contains code explaining outcome of message request	M
Message	255	Varchar	Text to elaborate on the response code	M
ProcessDateTime		DateTime	System time (GMT) at generating the response in UTC datetime format.	M
TMTNumber		Int	Unique number identifying the SMT order	M
OtherPayoutNumber	15	Varchar	Unique number provided by a payout partner which must be used by recipient to collect money	O
LocalReferenceNumber	30	Varchar	Sending agent's own reference for the transaction	O
StatusCode	2	Char	Status code of the transaction	M
StatusDescription		Varchar	Description of the status	M
TransactionDate		DateTime	Date transaction was created in UTC format	M
TransactionPaidDate		DateTime	Date when the transaction was PAID in UTC format. This field will only has value if the transaction has been paid.	O
OriginatingCountry	3	Char	Code identifying the sending country	M
OriginatingCurrency	3	Char	Code identifying the currency of the sending country	M
DestinationCountry	3	Char	Code identifying the receiving country	M
DestinationCurrency	3	Char	Code identifying the currency of the receiving country	M
ExchangeRate	20,6	Decimal	The consumer exchange rate used for the transaction	M
LocalAmount	19,4	Money	Amount of money to be sent in the local currency, i.e. currency of sending country	M
CustomerCharge	19,4	Money	Amount of money paid by the sending customer (localAmount + fees)	M
PayoutAmount	19,4	Money	Amount of money to be paid to the receiver (in payout currency)	M
ProductId		Int	Code identifying the primary product of the transaction	M

Field Name	Size	Type	Description	M/O
ServiceID		Int	Code identifying Value Added product (can be more than one, but currently only available with Money Transfer primary product)	O
GlobeCardNumber		Int	Globe Card number identifying a customer	O
FirstName	50	Varchar	First name of customer	M
LastName	50	Varchar	Last name of customer	M
Address1	100	Varchar	First line of customer address	M
Address2	100	Varchar	Second line of customer address	O
City	50	Varchar	City of customer address	M
State	50	Varchar	State/province of customer address	O
PostCode	10	Varchar	Postal or zip code of customer's address	O
Country	3	Varchar	Country of customer address (ISO code)	M
PhoneNumber	50	Varchar	Phone number of customer	O
MobileNumber	50	Varchar	Mobile number of customer	O
Email	50	Varchar	Email address of customer	O
FirstName	50	Varchar	First name of receiving customer	M
LastName	50	Varchar	Last name of receiving customer	M
Address1	100	Varchar	First line of receiving customer address	O
Address2	100	Varchar	Second line of receiving customer address	O
City	50	Varchar	City of receiving customer address	O
State	50	Varchar	State/province of receiving customer address	O
StateCode	50	Varchar	State/province of receiving customer address (valid only for US states)	O
PostCode	10	Varchar	Postal or zip code of sending customer's address	O
Country	3	Varchar	Country of receiving customer address (ISO code)	O
PhoneNumber	50	Varchar	Phone number of receiving customer	O
MobileNumber	50	VarChar	Mobile Number of Receiving customer	O
Email	50	Varchar	Email address of receiving customer	O
TestQuestion	200	Varchar	Test question to be asked of receiver	O
TestAnswer	200	Varchar	Answer to test question	O
DataForServices	500	Varchar	Contains extra information, i.e. message	O
CPFNumber		Int	ID Number of Receiver. Mandatory for recipients in Brazil	O

4.3 Payout Update

4.3.1 Request from Partner to SMT

New Field Name	Size	Type	Description	M/O
UserName	30	Varchar	User name issued by SMT as part of access credentials.	M
Pwd	30	Varchar	Password issued by SMT as part of access credentials.	M
PartnerId		Numeric	Partner Id issued by SMT as part of access credentials.	M
AgentId		Int	Agent Id issued by SMT as part of access credentials.	M
TMTNumber		Int	Unique number identifying the SMT order	M
OtherPayoutNumber	30	Varchar	Other payout partner number	O
UpdateType		Int	01 = Payout	M
ProcessDateTime		DateTime	Partner's local time at generating the request in UTC datetime format.	M
PartnerPayoutAgentID	30	Varchar	Partner's own id for the agent making the payout (if not registered as an agent on SMT system)	O
ReceiverIDType		Int	Id type of the primary id shown by the recipient (who is actually the original sender in the case of payout to originator) Types allowed: 01=Passport 02=National ID 03=Driver's License 04=Other Government ID 06=Other	M
ReceiverIDProvided	100	Varchar	The number or identifier of the primary id shown by the receiver (who is actually the original sender in the case of payout to originator)	M
ReceiverAddress1	100	Varchar	First line of receiving customer address (must be returned for update type 1 as provided in transaction query, even if no update made)	M
ReceiverAddress2	100	Varchar	Second line of receiving customer address (must be returned for update type 1 as provided in transaction query, even if no update made)	O
ReceiverCity	50	Varchar	City of receiving customer address (must be returned for update type 1 as provided in transaction query, even if no update made)	M
ReceiverState	50	Varchar	State/province of receiving customer address (mandatory for USA) (must be returned for update type 1 as provided in transaction query, even if no update made)	O
ReceiverCountry	3	Varchar	Country of receiving customer address (ISO code) (must be returned for update type 1 as provided in transaction query, even if no update made)	M
ReceiverPhoneNumber	50	Varchar	Phone number of receiving customer (must be returned for update type 1 as provided in transaction query, even if no update made)	O

New Field Name	Size	Type	Description	M/O
ReceiverMobileNumber	50	Varchar	Mobile number of receiving customer (must be returned for update type 1 as provided in transaction query, even if no update made)	O
ReceiverPostCode	10	Varchar	Postal or zip code of receiving customer's address (mandatory for USA) (must be returned for update type 1 as provided in transaction query, even if no update made)	O
AgentRef	30	Varchar	Partner's own reference for the payout	O
ReceiverStateCode	30	Varchar	US State code (needed for the US only)	O
DateOfIssue		Date	The date of issue of the ID provided in YYYY-MM_DD format	O
DateOfExpiry		Date	The date of expiry of the ID provided in YYYY-MM-DD format	O
CountryOfIssue	50	Varchar	The country issuing the ID provided (ISO code)	O
DateOfBirth		Date	Receiver's date of birth in YYYY-MM-DD format	O
PlaceOfBirth	50	Varchar	The receiver's place of birth	O
Occupation	40	Varchar	The receiver's occupation	O
SocialSecurityNo	20	Varchar	The social security number of the receiver	O
Gender	1	Char	Gender of receiver	O
StateOfIssue	50	Varchar	The state issuing the ID provided	O
Nationality	40	Varchar	The nationality of the receiver	O

4.3.2 Response from SMT to Partner

New Field Name	Size	Type	Description	M/O
ResponseCode		Int	Contains code explaining outcome of message request	M
Message	255	Varchar	Text to elaborate on the response code	M
ProcessDateTime		DateTime	System time (GMT) at generating the response in UTC datetime format.	M
TMTNumber		Int	Unique number identifying the SMT order	M
OtherPayoutNumber	15	Varchar	Unique number provided by a payout partner which must be used by recipient to collect money	O
AgentRef	30	Varchar	Partner's own reference for the payout	O
OriginatingCountry	3	Char	Code identifying the sending country	M
OriginatingCurrrency	3	Char	Code identifying the currency of the sending country	M
DestinationCountry	3	Char	Code identifying the receiving country	M
DestinationCurrency	3	Char	Code identifying the currency of the receiving country	M
LocalAmount	19,4	Money	Amount of money to be sent in the local currency, i.e. currency of sending country	M
PayoutAmount	19,4	Money	Amount of money to be paid to the receiver (in payout currency)	M
ProductId		Int	Code identifying the primary product of the transaction	M

New Field Name	Size	Type	Description	M/O
ServiceId		Int	Code identifying Value Added product (can be more than one, but currently only available with Money Transfer primary product)	O

4.4 Payout Confirmation (for cash transactions only)

4.4.1 Request from Partner to SMT

Field Name	Size	Type	Description	M/O
UserName	30	Varchar	User name issued by SMT as part of access credentials.	M
Pwd	30	Varchar	Password issued by SMT as part of access credentials.	M
PartnerId		Numeric	Partner Id issued by SMT as part of access credentials.	M
AgentId		Int	Agent Id issued by SMT as part of access credentials.	M
TMTNumber		Int	Unique number identifying the SMT order	M

4.4.2 Response from SMT to Partner

Field Name	Size	Type	Description	M/O
ResponseCode		Int	Contains code explaining outcome of message request	M
Message	255	Varchar	Text to elaborate on the response code	M
ProcessDateTime		DateTime	System time (GMT) at generating the response in UTC datetime format.	M
TMTNumber		Int	Unique number identifying the SMT order	M

4.5 Workflow Payout Query

4.5.1 Request from Partner to SMT

Field Name	Size	Type	Description	M/O
UserName	30	Varchar	User name issued by SMT as part of access credentials.	M
Pwd	30	Varchar	Password issued by SMT as part of access credentials.	M
PartnerId		Numeric	Partner Id issued by SMT as part of access credentials.	M
AgentId		Int	Agent Id issued by SMT as part of access credentials. To be provided by SMT to partner (one agent id for test and one for live production). This is the franchise id that identifies the agent's location.	M
ProcessDateTime		DateTime	Partner's local time at generating the request in UTC datetime format.	M
ProductId		Int	ProductId: 22 – Account Deposit 25 – Courier Delivery	M
RetrievalType		Int	Retrieval Type: 01 – New transactions for Payout Agent to process 02 – Resolved items from Send Agent sent by Payout Agent previously 03 – Items requested for cancellation from Sending Agent 04 – Items has been acknowledged previously by Payout Agent 05 – Pending items which has been referred to Send Agent 06 – To find out individual transaction status	M
TMTNumber		Int	Unique number identifying the SMT order. This field is mandatory if RetrievalType = 06. Otherwise, please supply 0 as default value for other retrieval type.	M

4.5.2 Response from SMT to Partner

Field Name	Size	Type	Description	M/O
ResponseCode		Int	Contains code explaining outcome of message request	M
Message	255	Varchar	Text to elaborate on the response code	M
ProcessDateTime		DateTime	System time (GMT) at generating the response in UTC datetime format.	M
RetrievalType		Int		M
Transaction Detail				
TMTNumber		Int	Unique number identifying the SMT order	M
OtherPayoutNumber	15	Varchar	Unique number provided by a payout partner which must be used by recipient to collect money	O
StatusCode	2	Char	Status code of the transaction	M
StatusDescription		Varchar	Description of the status	M
TransactionDate		DateTime	The datetime (GMT) of the transaction was created in UTC datetime format	M
OriginatingCountry	3	Char	Code identifying the sending country	M
OriginatingCurrency	3	Char	Code identifying the currency of the sending country	M
LocalAmount	19,4	Money	Amount of money to be sent in the local currency, i.e. currency of sending country	M
DestinationCountry	3	Char	Code identifying the receiving country	M
DestinationCurrency	3	Char	Code identifying the currency of the receiving country	M

Field Name	Size	Type	Description	M/O
PayoutAmount	19,4	Money	Amount of money to be paid to the receiver (in payout currency)	M
ProductId		Int	Code identifying the primary product of the transaction	M
ServiceID		Int	Code identifying Value Added product (can be more than one, but currently only available with Money Transfer primary product)	O
Sender details				
FirstName	50	Varchar	First name of customer	M
LastName	50	Varchar	Last name of customer	M
Address1	100	Varchar	First line of customer address	M
Address2	100	Varchar	Second line of customer address	O
City	50	Varchar	City of customer address	M
State	50	Varchar	State/province of customer address	O
PostCode	10	Varchar	Postal or zip code of customer's address	O
Country	3	Varchar	Country of customer address (ISO code)	M
PhoneNumber	50	Varchar	Phone number of customer	O
MobileNumber	50	Varchar	Mobile number of customer	O
Email	50	Varchar	Email address of customer	O
Receiver details				
FirstName	50	Varchar	First name of receiving customer	M
LastName	50	Varchar	Last name of receiving customer	M
Address1	100	Varchar	First line of receiving customer address. Becomes mandatory for courier delivery (product 25)	O
Address2	100	Varchar	Second line of receiving customer address	O
City	50	Varchar	City of receiving customer address. Becomes mandatory for courier delivery (product 25)	O
State	50	Varchar	State/province of receiving customer address. Becomes mandatory for courier delivery (product 25)	O
StateCode	50	Varchar	State/province of receiving customer address (valid only for US states). Becomes mandatory for courier delivery (product 25)	O
PostCode	10	Varchar	Postal or zip code of sending customer's address. Becomes mandatory for courier delivery (product 25)	O
Country	3	Varchar	Country of receiving customer address (ISO code). Becomes mandatory for Courier Delivery (product 25)	O
PhoneNumber	50	Varchar	Phone number of receiving customer	O
MobileNumber	50	VarChar	Mobile Number of Receiving customer	O
Email	50	Varchar	Email address of receiving customer	O
DataForServices	500	Varchar	Contains extra information, i.e. message Becomes mandatory for courier delivery (product 25)	O
ReasonForPayment	100	Varchar	Message which can be included with transfer	O
BankAccount	8	Varchar	Bank account number to which money is to be transferred. Becomes mandatory for Account Deposit (Product 22)	O
Bank	100	Varchar	Name of bank at which bank account is held. Becomes mandatory for Account Deposit (Product 22)	O
LocalBankCode	50	Varchar	Local code for bank at which bank account is held. Becomes mandatory for Account Deposit (Product 22)	O
BankBranch	100	Varchar	Name of bank branch at which bank account is held.	O

Field Name	Size	Type	Description	M/O
			Becomes mandatory for Account Deposit (Product 22)	
BankAddress1	100	Varchar	Address of bank at which bank account is held. Becomes mandatory for Account Deposit (Product 22)	O
BankCity	50	Varchar	City of bank at which bank account is held. Becomes mandatory for Account Deposit (Product 22)	O
BankCountry	3	Char	ISO code of the country of Bank. Becomes mandatory for Account Deposit (Product 22).	O
IBAN	50	Varchar	International Bank Account Number (IBAN) is an international standard for identifying bank accounts across national borders. Becomes mandatory for account deposits where transactions are send to European Union countries or where the official currency is Euro (€) only (product 22).	O
CPFNumber		Int	ID number of receiver. Mandatory for send transaction to Brazil only. Default to 0 (zero) if not applicable	O

4.6 Workflow Payout Query New

4.6.1 Request from Partner to SMT

Field Name	Size	Type	Description	M/O
UserName	30	Varchar	User name issued by SMT as part of access credentials.	M
Pwd	30	Varchar	Password issued by SMT as part of access credentials.	M
PartnerId		Numeric	Partner Id issued by SMT as part of access credentials.	M
AgentId		Int	Agent Id issued by SMT as part of access credentials.	M
ProcessDateTime		DateTime	Partner's local time at generating the request in UTC datetime format.	M
ProductId		Int	ProductId: 22 – Account Deposit 25 – Courier Delivery	M
RetrievalType		Int	Retrieval Type: 01 – New transactions for Payout Agent to process 02 – Resolved items from Send Agent sent by Payout Agent previously 03 – Items requested for cancellation from Sending Agent 04 – Items has been acknowledged previously by Payout Agent 05 – Pending items which has been referred to Send Agent 06 – To find out individual transaction status	M
TMTNumber		Int	Unique number identifying the SMT order. This field is mandatory if RetrievalType = 06. Otherwise, please supply 0 as default value for other retrieval type.	M

4.6.2 Response from SMT to Partner

Field Name	Size	Type	Description	M/O
ResponseCode		Int	Contains code explaining outcome of message request	M
Message	255	Varchar	Text to elaborate on the response code	M
ProcessDateTime		DateTime	System time (GMT) at generating the response in UTC datetime format.	M
RetrievalType		Int		M

Field Name	Size	Type	Description	M/O
Transaction Detail				
TMTNumber		Int	Unique number identifying the SMT order	M
OtherPayoutNumber	15	Varchar	Unique number provided by a payout partner which must be used by recipient to collect money	O
StatusCode	2	Char	Status code of the transaction	M
StatusDescription		Varchar	Description of the status	M
TransactionDate		DateTime	The datetime (GMT) of the transaction was created in UTC datetime format	M
OriginatingCountry	3	Char	Code identifying the sending country	M
OriginatingCurrency	3	Char	Code identifying the currency of the sending country	M
LocalAmount	19,4	Money	Amount of money to be sent in the local currency, i.e. currency of sending country	M
DestinationCountry	3	Char	Code identifying the receiving country	M
DestinationCurrency	3	Char	Code identifying the currency of the receiving country	M
PayoutAmount	19,4	Money	Amount of money to be paid to the receiver (in payout currency)	M
ProductId		Int	Code identifying the primary product of the transaction	M
ServiceID		Int	Code identifying Value Added product (can be more than one, but currently only available with Money Transfer primary product)	O
Sender details				
FirstName	50	Varchar	First name of customer	M
SecondName	50	Varchar	Second name of customer	O
LastName	50	Varchar	Last name of customer	M
SecondLastName	50	Varchar	Second Last name of customer	O
Address1	100	Varchar	First line of customer address	M
Address2	100	Varchar	Second line of customer address	O
City	50	Varchar	City of customer address	M
State	50	Varchar	State/province of customer address	O
PostCode	10	Varchar	Postal or zip code of customer's address	O
Country	3	Varchar	Country of customer address (ISO code)	M
PhoneNumber	50	Varchar	Phone number of customer	O
MobileNumber	50	Varchar	Mobile number of customer	O
Email	50	Varchar	Email address of customer	O
Receiver details				
FirstName	50	Varchar	First name of receiving customer	M
SecondName	50	Varchar	Second name of receiving customer	O
LastName	50	Varchar	Last name of receiving customer	M
SecondLastName	50	Varchar	Second Last name of receiving customer	O
Address1	100	Varchar	First line of receiving customer address. Becomes mandatory for courier delivery (product 25)	O
Address2	100	Varchar	Second line of receiving customer address	O
City	50	Varchar	City of receiving customer address. Becomes mandatory for courier delivery (product 25)	O

Field Name	Size	Type	Description	M/O
State	50	Varchar	State/province of receiving customer address. Becomes mandatory for courier delivery (product 25)	O
StateCode	50	Varchar	State/province of receiving customer address (valid only for US states). Becomes mandatory for courier delivery (product 25)	O
PostCode	10	Varchar	Postal or zip code of sending customer's address. Becomes mandatory for courier delivery (product 25)	O
Country	3	Varchar	Country of receiving customer address (ISO code). Becomes mandatory for Courier Delivery (product 25)	O
PhoneNumber	50	Varchar	Phone number of receiving customer	O
MobileNumber	50	VarChar	Mobile Number of Receiving customer	O
Email	50	Varchar	Email address of receiving customer	O
DataForServices	500	Varchar	Contains extra information, i.e. message Becomes mandatory for courier delivery (product 25)	O
ReasonForPayment	100	Varchar	Message which can be included with transfer	O
BankAccount	8	Varchar	Bank account number to which money is to be transferred. Becomes mandatory for Account Deposit (Product 22)	O
Bank	100	Varchar	Name of bank at which bank account is held. Becomes mandatory for Account Deposit (Product 22)	O
LocalBankCode	50	Varchar	Local code for bank at which bank account is held. Becomes mandatory for Account Deposit (Product 22)	O
BankBranch	100	Varchar	Name of bank branch at which bank account is held. Becomes mandatory for Account Deposit (Product 22) only for some payout partners that required.	O
BankAddress1	100	Varchar	Address of bank at which bank account is held. Becomes mandatory for Account Deposit (Product 22) Only for some payout partners that required.	O
BankCity	50	Varchar	City of bank at which bank account is held. Becomes mandatory for Account Deposit (Product 22) only for some payout partners that required.	O
BankCountry	3	Char	ISO code of the country of Bank. Becomes mandatory for Account Deposit (Product 22).	O
IBAN	50	Varchar	International Bank Account Number (IBAN) is an international standard for identifying bank accounts across national borders. Becomes mandatory for account deposits where transactions are send to European Union countries or where the official currency is Euro (€) only (product 22).	O
CPFNumber		Int	ID number of receiver. Mandatory for send transaction to Brazil only. Default to 0 (zero) if not applicable	O
BankAccountType		Int	Types of Bank Account Becomes mandatory for Account Deposit (Product 22)only for some pay out partners of Latam Countries	O
BankState		Varchar	State of bank at which bank account is held. Becomes mandatory for Account Deposit (Product 22) only for some payout partners.	O
RIdType		Int	The identifying code indicating what type of primary id was provided by the sender for beneficiary. Valid values: 01 – Passport 02 – National ID 03 – Driver's License 04 – Other Government ID	O

Field Name	Size	Type	Description	M/O
			06 – Other Default to 0 (zero) if not applicable	
RIdProvided		Varchar	The reference number of the primary id provided by the sender for beneficiary, e.g. passport number. Becomes mandatory for account deposits only for some pay out partners of Latam Countries and if the ID1Type is provided only for some pay out partners that required and if the ID1Type is provided	O

4.7 Workflow Payout Update

4.7.1 Request from Partner to SMT

New Field Name	Size	Type	Description	M/O
UserName	30	Varchar	User name issued by SMT as part of access credentials.	M
Pwd	30	Varchar	Password issued by SMT as part of access credentials.	M
PartnerId		Numeric	Partner Id issued by SMT as part of access credentials.	M
AgentId		Int	Agent Id issued by SMT as part of access credentials.	M
TMTNumber		Int	Unique number identifying the SMT order	M
UpdateType		Int	Update Type: 01 : Acknowledged, under action 02: Transaction Paid 03: Approved cancellation request from sending agent 04: Unable to Cancel, transaction has been payout or in the process of paying out 05: Incomplete information, problem to be resolved by sending agent 06: Payout agent refused to process the transaction. Transaction to be refer to sending agent for cancellation – courier delivery transaction only	M
Comment	100	Varchar	Comments if the transaction needs further clarification from Send Agent. Becomes mandatory for Update Type: 04, 05, 06	O

4.7.2 Response from SMT to Partner

New Field Name	Size	Type	Description	M/O
ResponseCode		Int	Contains code explaining outcome of message request. Return response code: 4 if successful Return response code: 9000 if update fail	M
Message	255	Varchar	Text to elaborate on the response code	M
ProcessDateTime		DateTime	System time (GMT) at generating the response in UTC datetime format.	M
TMTNumber		Int	Unique number identifying the SMT order	M

4.8 Nominated Payout Query (cash payout only)

4.8.1 Request from the Partner to CMT

New Field Name	Size	Type	Description	M/O
UserName	30	Varchar	User name issued by SMT as part of access credentials.	M
Pwd	30	Varchar	Password issued by SMT as part of access credentials.	M
PartnerId	9	Numeric	Partner Id issued by SMT as part of access credentials. .	M
AgentId	10	Int	Agent Id issued by SMT as part of access credentials.	M
MaxTransactions		Int	Maximum number of transactions to get from method. When is set to 0, the method will return all available transactions.	M

4.8.2 Response from SMT to Partner

New Field Name	Size	Type	Description	M/O
ResponseCode	10	Int	Contains code explaining outcome of message request	M
Message	255	Varchar	Text to elaborate on the response code	M
ProcessDateTime		DateTime	Time of processing the request (GMT). Date format in YYYY-MM-DD HH:MM:SS	M
Transactions				
TransactionType		Int	1 = New Transaction 2=Cancellation Request from Send Agent	M
TMTNumber		Int	Unique number identifying the SMT order	M
OtherPayoutNo	15	Varchar	Unique number provided by a payout partner which must be used by recipient to collect money	O
PartnerTransactionNo	30	Varchar	Partner's own reference for the transaction. If provided in the transaction request message	O
StatusCode	2	Char	Status code of the transaction. Please refer to Transaction Status Codes	M
StatusDescription	50	Varchar	Description of the status	M
TransactionDate		DateTime	Date transaction was created	M
OriginatingCountry	3	Char	ISO code identifying the originating country	M
OriginatingCurrency	3	Char	ISO code identifying the currency of the sending country	M
DestinationCountry	3	Char	ISO code identifying the receiving country	M
DestinationCurrency	3	Char	ISO code identifying the currency of the receiving country	M
LocalAmount	19,4	Money	Amount of money to be send by the sender (in originating currency)	M
ExchangeRate	20,6	Decimal	The consumer exchange rate used for the transaction	M
ServiceCharge	19,4	Money	Send fee for this transaction in local amount	M

ProductId		Int	Code identifying the primary product of the transaction. Please refer to Get Corridor method in Send API for more detail on the product availability. Current ProductId: 1 – Money Transfer	M
OtherServiceCharge	19,4	Money	Total of fee charged for value added product chosen for this transaction	O
Discount	19,4	Money	The amount of discount applied to charge	O
CustomerCharge	19,4	Money	Total amount payable by customer including local amount plus any charges, and taking into account discount	M
TaxCharged	19,4	Money	Tax charged on the transaction	O
PayoutAmount	19,4	Money	Amount of money to be paid to the receiver (in destination currency)	M
Services				
ServiceID		Int	Code identifying Value Added product (can be more than one, but currently only available with Money Transfer primary product). Valid values: 21 – Message for Recipient 24 – Radio Notification 26 – Text message to sender when transaction is paid out.	O
SenderDetails				
FirstName	50	Varchar	First name of Sender	M
LastName	50	Varchar	Last name of Sender	M
Address1	100	Varchar	First line of customer address	M
Address2	100	Varchar	Second line of customer address	O
City	50	Varchar	City of customer address	M
State	50	Varchar	State/province of customer address	O
PostCode	10	Varchar	Postal or zip code of customer's address	O
Country	3	Varchar	ISO code of the country of customer address	M
PhoneNumber	50	Varchar	Phone number of customer	O
MobileNumber	50	Varchar	Mobile number of customer (if SMS text service is required). First 4 digits are country code, followed by number. No leading zeroes.	O
Email	50	Varchar	Email address of customer	O
SendingAgentId		INT	Unique ID of Sending Agent	O
SendingAgentName		Varchar	Legal Name Of Send Agent	O
SenderIdDetails				
ID1Type		Int	The identifying code indicating what type of primary id was shown by the sender Becomes mandatory if local amount is over a certain threshold (to be provided by SMT). Valid values: 01 – Passport 02 – National ID 03 – Driver's License 04 – Other Government ID 06 – Other	O
ID1Provided	100	Varchar	The reference number of the primary id shown by the sender, e.g. passport number. Becomes mandatory if ID1Type is Provided.	O
DateOfIssue		Date	The date of issue of the ID provided. Date format in YYYY-MM-DD	O
DateOfExpiry		Date	The date of expiry of the ID provided. Becomes mandatory if ID1Type is Provided	O

			Date format in YYYY-MM-DD.	
CountryOfIssue	3	Char	ISO code of the country of issue. Becomes mandatory if ID1Type is Provided	O
DateOfBirth		Date	Sender's date of birth. Date format in YYYY-MM-DD	O
PlaceOfBirth	50	Varchar	The sender's place of birth	O
Occupation	40	Varchar	The sender's occupation	O
SocialSecurityNo	20	Varchar	The social security number of the sender (US Sends only, if required). Applicable only to transactions sent from the USA	O
Gender	1	Char	Gender of sender M = Male F=Female	O
StateOfIssue	2	Char	ISO code of the state issuing the ID Applicable only to transactions sent from the USA	O
Nationality	3	Char	ISO code of the nationality	O
ReceiverDetails				
FirstName	50	Varchar	First name of receiver	M
LastName	50	Varchar	Last name of receiver	M
Address1	100	Varchar	First line of receiver address	O
Address2	100	Varchar	Second line of receiver address	O
City	50	Varchar	City of receiver address	O
State	50	Varchar	State/province of receiver address	O
PostCode	10	Varchar	Postal or zip code of receiver's address	O
Country	3	Varchar	ISO code of the country of receiver address	O
PhoneNumber	50	Varchar	Phone number of receiver	O
MobileNumber	50	Varchar	Mobile number of receiver	O
Email	50	Varchar	Email address of receiver	O
ReceiverPaymentDetails				
TestQuestion	200	Varchar	Test question to be asked of receiver Becomes mandatory for certain countries. Full list will be provided by SMT	O
TestAnswer	200	Varchar	Answer to test question. Becomes mandatory for certain countries. Full list will be provided by SMT	O
DataForServices	500	Varchar	Contains extra information, i.e. message for beneficiary or direction for delivery	O
ReasonForPayment	100	Varchar	Message which can be included with transfer. Becomes mandatory for certain countries. Full list will be provided by SMT.	O
CPFNumber		Int	ID number of receiver	O
PayoutAgentName	100	Varchar	Name Of Payout Agent	O

4.9 Nominated Payout Update (cash payout only)

4.9.1 Request from the Partner to SMT

New Field Name	Size	Type	Description	M/O
UserName	30	Varchar	User name issued by SMT as part of access credentials. .	M
Pwd	30	Varchar	Password issued by SMT as part of access credentials. .	M
PartnerId	9	Numeric	Partner Id issued by SMT as part of access credentials. .	M

AgentId	10	Int	Agent Id issued by SMT as part of access credentials.	M
TMTNumber		Int	Unique number identifying the SMT order	M
UpdateCode		Int	Contains code explaining outcome of message request. Please see table below for UpdateCode.	M
Comment	100	Varchar		O

4.9.2 Update Codes

Acknowledge	10000 Transaction accepted 19000 Unable to process – please contact 19001 Duplicate SMT transaction number 19002 Invalid partner transaction number 19003 Duplicate partner transaction number 19004 Invalid to country 19005 Invalid currency code 19006 Mandatory data missing Message = Name of field 19007 Error in field Message = Name of field	Response to Cancellation Request	30000 Acknowledge and approve Cancellation Request from Send Agent 30001 Update refused - transaction paid 30002 Update refused - transaction cancelled 30003 Update refused - void transaction 30004 Update refused - transaction rejected 39000 Unable to process - please contact 39001 Invalid SMT number 39002 Invalid partner transaction number

4.9.3 Response from SMT to Partner

New Field Name	Size	Type	Description	M/O
ResponseCode	10	Int	Contains code explaining outcome of message request	M
Message	255	Varchar	Text to elaborate on the response code	M
ProcessDateTime		DateTime	Time of processing the request (GMT). Date format in YYYY-MM-DD HH:MM:SS	M
TMTNumber		Int	Unique number identifying the SMT order	M

4.10 Get Settlement Report

4.10.1 Request from Partner to SMT

Field	Size	Type	Description	O/M
UserName	30	Varchar	User name issued by SMT as part of access credentials.	M
Pwd	30	Varchar	Password issued by SMT as part of access credentials. .	M
PartnerId	9	Numeric	Partner Id issued by SMT as part of access credentials.	M
AgentId	10	Int	Agent Id issued by SMT as part of access credentials.	M
SettlementDate		Datetime	The date of the settlement report require	M

4.10.2 Response from SMT to Partner

Field	Size	Type	Description	O/M
ResponseCode	10	Int	Contains code explaining outcome of message request	M
Message	255	Varchar	Text to elaborate on the response code	M
ProcessDateTime		DateTime	System time (GMT) at generating the response in UTC datetime format	M

Field	Size	Type	Description	O/M
SettlementDate		Datetime	The date of the settlement report requested	M
Send Summary				
LocalSendAmount		Money	Total of all send amount in originating country currency	M
ServiceCharge		Money	Total of all service charge in originating country currency	M
CustomerCharge		Money	Total of all customer charge in originating country currency	M
AgentCommission		Money	Total of all agent commission	M
Send Transactions (Repeated for each transaction)				
TMTNumber	10	Int	Unique number identifying the SMT order	M
TransactionDateTime		Datetime	The datetime (GMT) the transaction was created in UTC datetime format	M
UserName	30	Varchar	The user who transact the transaction	M
OriginatingCountry	3	Char	ISO code identifying the originating country	M
DestinationCountry	3	Char	ISO code identifying the receiving country	M
OriginatingAmount		Money	Send amount in originating country currency	M
ServiceCharge		Money	Send fee for this transaction in local amount	M
CustomerCharge		Money	Total amount payable by customer including local amount plus any charges, and taking into account discount	M
AgentCommission		Money	Commission earned by the Send Agent in this transaction	M
PayableToSMT		Money	The amount the send agent owes to SMT for this transaction. i.e. Customer Charge less Agent Commission	M
Cancellation Summary				
LocalAmount		Money	Total of all send amount in originating country currency	M
ServiceCharge		Money	Total of all service charge in originating country currency	M
CustomerCharge		Money	Total of all customer charge in originating country currency	M
AgentCommission		Money	Total of all agent commission	M
Cancellation Transactions (Repeated for each transaction)				
TMTNumber	10	Int	Unique number identifying the SMT order	M
TransactionDateTime		Datetime	The datetime (GMT) the transaction was cancelled in UTC datetime format	M
UserName	30	VarChar	The user who transact the transaction	M
OriginatingCountry	3	Char	ISO code identifying the originating country	M
DestinationCountry	3	Char	ISO code identifying the receiving country	M
OriginatingAmount		Money	Send amount in originating country currency	M
ServiceCharge		Money	Send fee for this transaction in local amount	M
CustomerCharge		Money	Total amount payable by customer including local amount plus any charges, and taking into account discount	M
AgentCommission		Money	Commission earned by the Send Agent in this transaction	M
PayableToAgent		Money	The amount SMT owes to the send agent for this transaction. i.e. Customer Charge less Agent Commission	M
Payout Summary				
PayoutAmount		Money	Amount of money to be paid to the receiver (in destination currency)	M
AgentCommission		Money	Commission earned by the Payout Agent in this transaction	M
Payout Transactions				
TMTNumber	10	Int	Unique number identifying the SMT order	M
TransactionDateTime		Datetime	The datetime (GMT) the transaction was payout in UTC datetime format	M
UserName	30	VarChar	The user who transact the transaction	M
OriginatingCountry	3	Char	ISO code identifying the originating country	M
DestinationCountry	3	Char	Send fee for this transaction in local amount	M
PayoutAmount		Money	Amount of money to be paid to the receiver (in destination currency)	M
AgentCommission		Money	Commission earned by the Payout Agent in this transaction	M

Field	Size	Type	Description	O/M
PayableToAgent		Money	The amount SMT owes to the payout agent for this transaction. i.e. Customer Charge plus Agent Commission	M

4.11 Rollback Transaction

4.11.1 Request from Partner to SMT

Field	Size	Type	Description	O/M
UserName	30	Varchar	User name issued by SMT as part of access credentials.	M
Pwd	30	Varchar	Password issued by SMT as part of access credentials.	M
PartnerId	9	Numeric	Partner Id issued by SMT as part of access credentials.	M
AgentId	10	Int	Agent Id issued by SMT as part of access credentials.	M
TMTNumber	10	Int	Unique number identifying the SMT order. This field is mandatory if OtherTransactionNo is not provided.	M
OtherTransactionNo	30	Varchar	Other payout partner number. Insert here the BTS number (11-digits) if transaction sent to a BTS network agent.	O

4.11.2 Response from SMT to Partner

Field	Size	Type	Description	O/M
responseCode	10	Int	Contains code explaining outcome of message request See Appendix: Response Codes	M
Message	255	Varchar	Text to elaborate on the response code	M
ProcessDateTime		DateTime	System time (GMT) at generating the response in UTC datetime format	M
TMTNumber	10	Int	Unique number identifying the SMT order	M
otherPayoutNumber	15	Varchar	Unique number provided by a payout partner which must be used by recipient to collect money. The BTS number (11-digits) if transaction sent to a BTS network agent.	O

4.12 Get ID Types

4.12.1 Request from Partner to SMT

Field	Size	Type	Description	O/M
UserName	30	Varchar	User name issued by SMT as part of access credentials.	M
Pwd	30	Varchar	Password issued by SMT as part of access credentials. .	M
PartnerId	9	Numeric	Partner Id issued by SMT as part of access credentials.	M
AgentId	10	Int	Agent Id issued by SMT as part of access credentials.	M

4.12.2 Response from SMT to Partner

Field	Size	Type	Description	O/M

Field	Size	Type	Description	O/M
ResponseCode	10	Int	Contains code explaining outcome of message request	M
Message	255	Varchar	Text to elaborate on the response code	M
ProcessDateTime		DateTime	System time (GMT) at generating the response in UTC datetime format	M
IDs				
Code	4	Int	ID Code	M
Description	200	Varchar	Description of the ID Code	M

4.13 Get Response Codes

4.13.1 Request from Partner to SMT

Field	Size	Type	Description	O/M
UserName	30	Varchar	User name issued by SMT as part of access credentials.	M
Pwd	30	Varchar	Password issued by SMT as part of access credentials.	M
PartnerId	9	Numeric	Partner Id issued by SMT as part of access credentials.	M
AgentId	10	Int	Agent Id issued by SMT as part of access credentials.	M

4.13.2 Response from SMT to Partner

Field	Size	Type	Description	O/M
ResponseCode	10	Int	Contains code explaining outcome of message request	M
Message	255	Varchar	Text to elaborate on the response code	M
ProcessDateTime		DateTime	System time (GMT) at generating the response in UTC datetime format	M
Codes				
Code	4	Int	ID Code	M
CodeDescription	255	Varchar	Description of the ID Code	M
Explanation	255	Varchar	Further explanation of the code	O

4.14 Get Country Codes

4.14.1 Request from Partner to SMT

Field	Size	Type	Description	O/M
UserName	30	Varchar	User name issued by SMT as part of access credentials.	M
Pwd	30	Varchar	Password issued by SMT as part of access credentials.	M
PartnerId	9	Numeric	Partner Id issued by SMT as part of access credentials.	M
AgentId	10	Int	Agent Id issued by SMT as part of access credentials.	M

4.14.2 Response from SMT to Partner

Field	Size	Type	Description	O/M
ResponseCode	10	Int	Contains code explaining outcome of message request	M
Message	255	Varchar	Text to elaborate on the response code	M
ProcessDateTime		DateTime	System time (GMT) at generating the response in UTC datetime format	M
Codes				
CountryCode	3	Char	Standard ISO country code	M
CountryName	50	Varchar	Country name	M

4.15 Get Currency Code

4.15.1 Request from Partner to SMT

Field	Size	Type	Description	O/M
UserName	30	Varchar	User name issued by SMT as part of access credentials.	M
Pwd	30	Varchar	Password issued by SMT as part of access credentials.	M
PartnerId	9	Numeric	Partner Id issued by SMT as part of access credentials.	M
AgentId	10	Int	Agent Id issued by SMT as part of access credentials.	M

4.15.2 Response from SMT to Partner

Field	Size	Type	Description	O/M
ResponseCode	10	Int	Contains code explaining outcome of message request	M
Message	255	Varchar	Text to elaborate on the response code	M
ProcessDateTime		DateTime	Time of processing the request (GMT)	M
Codes				
CurrencyCode	3	Char	Currency code	M
CurrencyName	50	Varchar	Currency name	M

4.16 Get Settlement Report USD

4.16.1 Request from Partner to SMT

Field	Size	Type	Description	O/M
UserName	30	Varchar	User name issued by SMT as part of access credentials.	M
Pwd	30	Varchar	Password issued by SMT as part of access credentials.	M
PartnerId	9	Numeric	Partner Id issued by SMT as part of access credentials.	M
AgentId	10	Int	Agent Id issued by SMT as part of access credentials.	M
SettlementDate		Datetime	The date of the settlement report require	M

4.16.2 Response from SMT to Partner

Field	Size	Type	Description	O/M
ResponseCode	10	Int	Contains code explaining outcome of message request	M
Message	255	Varchar	Text to elaborate on the response code	M
ProcessDateTime		DateTime	System time (GMT) at generating the response in UTC datetime format	M
SettlementDate		Datetime	The date of the settlement report requested	M
Send Summary				
LocalSendAmount		Money	Total of all send amount in originating country currency	M
ServiceCharge		Money	Total of all service charge in originating country currency	M
CustomerCharge		Money	Total of all customer charge in originating country currency	M
AgentCommission		Money	Total of all agent commission	M
LocalSendAmountUSD		Money	Total of all send amount in originating country in USD.	M
ServiceChargeUSD		Money	Total of all service charge in originating country in USD.	
CustomerChargeUSD		Money	Total of all customer charge of originating country in USD.	M
AgentCommissionUSD		Money	Total of all agent commission in USD	M
TotalFXRevenueUSD		Money	Total of all FX revenue in USD	M
AgentCommisionFxReveneUSD		Money	Total of all Agent commission earned of FX revenue in USD.	M
Send Transactions (Repeated for each transaction)				
TMTNumber	10	Int	Unique number identifying the SMT order	M
TransactionDateTime		Datetime	The datetime (GMT) the transaction was created in UTC datetime format	M
UserName	30	Varchar	The user who transact the transaction	M
OriginatingCountry	3	Char	ISO code identifying the originating country	M
DestinationCountry	3	Char	ISO code identifying the receiving country	M
OriginatingAmount		Money	Send amount in originating country currency	M
ServiceCharge		Money	Send fee for this transaction in local amount	M
CustomerCharge		Money	Total amount payable by customer including local amount plus any charges, and taking into account discount	M
AgentCommission		Money	Commission earned by the Send Agent in this transaction	M
PayableToSMT		Money	The amount the send agent owes to SMT for this transaction. i.e. Customer Charge less Agent Commission	M
OriginatingAmountUSD		Money	Send Amount in USD	M
ServiceChargeUSD		Money	Send fee for this transaction in USD	M
AgentCommisionUSD		Money	Commission earned by the Send Agent in this transaction in USD.	M
TotalFXRevenueUSD		Money	Total FX revenue in USD.	M
AgentCommisionFxReveneUSD		Money	Agent Commission earned of FX revenue in USD.	M
Cancellation Summary				
LocalAmount		Money	Total of all send amount in originating country currency	M
ServiceCharge		Money	Total of all service charge in originating country currency	M
CustomerCharge		Money	Total of all customer charge in originating country currency	M
AgentCommission		Money	Total of all agent commission	M
LocalAmountUSD		Money	Total of all send amount in originating country currency	M
ServiceChargeUSD		Money	Total of all service charge in	M
CustomerChargeUSD		Money	Total of all customer charge	M
AgentCommissionUSD		Money	Total of all agent commission	M

Field	Size	Type	Description	O/M
TotalFXRevenueUSD		Money	Total of all FX revenue in USD	M
AgentCommisionFxReveneUSD		Money	Total of all Agent commission earned of FX revenue in USD.	M
Cancellation Transactions (Repeated for each transaction)				
TMTNumber	10	Int	Unique number identifying the SMT order	M
TransactionDateTime		Datetime	The datetime (GMT) the transaction was cancelled in UTC datetime format	M
UserName	30	VarChar	The user who transact the transaction	M
OriginatingCountry	3	Char	ISO code identifying the originating country	M
DestinationCountry	3	Char	ISO code identifying the receiving country	M
OriginatingAmount		Money	Send amount in originating country currency	M
ServiceCharge		Money	Send fee for this transaction in local amount	M
CustomerCharge		Money	customer charge	M
CustomerChargeUSD		Money	Customer Charge in USD	M
AgentCommission	19,4	Money	Commission earned by the Send Agent in this transaction	M
PayableToAgent	19,4	Money	The amount SMT owes to the send agent for this transaction. i.e. Customer Charge less Agent Commission	M
OriginalAmountUSD	19,4	Money	Send amount in USD.	M
ServiceChargeUSD	19,4	Money	Send fee for this transaction in USD.	M
AgentCommisionUSD	19,4	Money	Commission earned by the Send Agent in this transaction in USD.	M
TotalFXRevenue	19,4	Money	Total FX revenue in USD.	M
AgentCommisionFxReveneue	19,4	Money	Agent Commission earned of FX revenue in USD.	M
Payout Summary				
PayoutAmount		Money	Amount of money to be paid to the receiver (in destination currency)	M
AgentCommission		Money	Commission earned by the Payout Agent in this transaction	M
SendAmountUSD		Money	Total Send Amount for the transaction (in USD)	
PayoutAmountUSD		Money	Amount of money to be paid to the receiver (in USD)	M
ServiceChargeUSD		Money	Total Customer Charge in USD	
AgentCommissionUSD		Money	Commission earned by the Payout Agent in this transaction in USD.	M
TotalFXRevenueUSD		Money	Total of all FX revenue	M
AgentCommisionFxReveneUSD		Money	Total of all Agent commission earned of FX revenue in USD.	M
Payout Transactions				
TMTNumber	10	Int	Unique number identifying the SMT order	M
TransactionDateTime		Datetime	The datetime (GMT) the transaction was payout in UTC datetime format	M
UserName	30	VarChar	The user who transact the transaction	M
OriginatingCountry	3	Char	ISO code identifying the originating country	M
DestinationCountry	3	Char	Send fee for this transaction in local amount	M
PayoutAmount		Money	Amount of money to be paid to the receiver (in destination currency)	M
AgentCommission		Money	Commission earned by the Payout Agent in this transaction	M
PayableToAgent		Money	The amount SMT owes to the payout agent for this transaction. i.e. Customer Charge plus Agent Commission	M
SendAmountUSD	19,4	Money	Send Amount for the transaction (in USD)	
PayoutAmountUSD	19,4	Money	Amount of money to be paid to the receiver (in USD)	M
ServiceChargeUSD	19,4	Money	Fee for the transaction in USD	M
AgentCommisionUSD	19,4	Money	Commission earned by the Payout Agent in this transaction in USD.	M
TotalFXRevenueUSD	19,4	Money	Total FX revenue in USD.	M
AgentCommisionFxReveneUSD	19,4	Money	Agent Commission earned of FX revenue in USD.	M

Appendix A: Testing and Certification

On confirmation that the partner has completed development, SMT will share a testing and certification test plan. The plan includes a comprehensive list of test cases along with test data.

The partner should execute all the test cases and submit the results to the Sigue QA team. These will be compared with the expected results and feedback provided to the partner.

Once all test cases have been successfully executed, the QA team will certify the integration ready for production deployment.

Partners are expected to execute their own test cases in addition to those provided by Sigue to ensure everything works fine from their end.

Appendix B: Request Sample Response Codes

The following are the response codes that will be used for all messages in the previous sections.

SMT Code	SMT Code description	Explanation
1	Request successful	
2	Order successful	
3	Order recorded – call Call Centre to complete	
4	Update successful	
5	Query successful	
6	No updates found	
7	Order successful but placed on Hold	
8	Payout place on Hold	
9000	Unable to process – please Contact	
9001	Quote request - invalid format	
9002	Invalid agent	Send Agent franchise id is not found in SMT.
9003	Invalid country or currency	Country or currency is not available in the SMT system
9004	Product / corridor not available	
9005	Unable to calculate exchange rate	
9006	Exceeds interface limit	The send limit for the send country set in the API has been reached (note: there may not be a limit)
9007	Exceeds country send limit	The transaction amount exceeds the allowed amount per transaction for the send country.
9008	Exceeds net liability threshold	The send agent has reached its net liability limit as set in the SMT system.
9009	Customer not found	Globe card number is not registered in SMT
9010	Customer name does not match	
9011	Four receivers already present - cannot have new receiver	
9013	Order request – invalid format	
9014	Receiver not found	
9015	Invalid ID type	
9016	Invalid SMT transaction number	
9017	Invalid send amount	
9018	Invalid date /time	This error occurs when a request date to payout a transaction happens before the creation date of the transaction or the date value is not well-formed.
9019	Invalid payout amount	
9020	Invalid payout agent	
9021	Invalid partner id	
9022	Mandatory data missing	The message that will come with the error response will detail what is missing.
9023	Invalid partner transaction number	
9024	Invalid update type	
9025	Transaction already cancelled	
9026	Payment already made	
9027	Payout is in progress, cannot cancel / payout to originator	
9028	Compliance checking is in progress, cannot cancel/payout to originator	Transaction is in Prime and cannot be cancelled until released by SMT
9029	Transaction in Progress. Transaction cannot be cancelled / paid out.	The transaction is in progress in SMT's Environment.
9030	Invalid service	
9031	Invalid state code	

SMT Code	SMT Code description	Explanation
9032	Invalid retrieval type	Retrieval type used in the Transaction Query or Agent Query requests is invalid.
9033	Agent not found	
9034	Invalid town code	
9035	Description is variable	This code feeds back when there was an error in the processing of the request which is related to any of the following scenarios: 1) The transaction has been already exported through GOPI interface. 2) The transaction has been already exported through BTS interface. 3) The country of the Payout Agent and the destination country of the transaction do not match. 4) The country of the Payout Agent and the source country of the transaction match. 5) The transaction has been put on hold and waits for Sender's required documentation. 6) The transaction has been put on-hold and waits for Receiver's required documentation. 7) Forex Margin for the destination country of the transaction has not been set up. 8) The transaction was not found in SMT's Database.
9036	Invalid query reason	
9037	Agent not entitled to query transaction	
9038	Transaction is not available for this agent to payout to originator	
9039	Transaction is not available for this agent to cancel	
9040	Invalid customer type	Customer type field used in a request is invalid.
9041	Message not valid for this partner	
9042	Incomplete search criteria supplied	Only valid for Payout Query message in Payout API.
9043	Transaction is not available for this agent to payout	Only valid for Payout API.
9044	Transaction cannot be updated using this message	Only valid for Payout API.
9045	Transaction cannot be completed due to current workflow status	Only valid for Payout API.
9046	Service cannot be updated due to current workflow status	Only valid for Payout API.
9047	Compliance checking is in progress, cannot update	Only valid for Payout API.
9048	Transaction cannot be updated via interface, please contact	Only valid for Payout API.
9049	No cancellation request outstanding	Only valid for Payout API.
9050	Transaction cannot be updated by this partner	
9051	Transaction has expired and cannot be confirmed	
9052	Invalid CPF number	
9053	Exceeds country payout limit	
9054	Rejected because of compliance rule	When internal SMT compliance rules have been applied.
9055	The following extra data is required for this transaction. (List of fields to appear in Message field)	
9056	This transaction, if created, would be Held for compliance reasons awaiting further information from sender - if you wish to proceed to create the Held transaction, must resend message with Confirm Hold set to True.	Wording may be more concise.
9057	This transaction has been rejected due to business or commercial reasons. Please contact your TMT representative if further information is required	When internal SMT compliance r
9058	This transaction has been held awaiting required documentation from sender and cannot be paid out	Only valid for Payout API.
9059	This transaction has been held awaiting required documentation from receiver and cannot be paid out	Only valid for Payout API.
9061	Invalid User or Password	User record does not exist in
9060	This payout, if created, would be Held for compliance reasons	Wording may be more concise.

SMT Code	SMT Code description	Explanation
	awaiting further information from receiver - if you wish to proceed to create the Held t	
9062	Paid to original sender	The transaction has been canceled
9063	This transaction is not a cash payout transaction.	The API can only pay out cash-
9064	Payment refunded to originator.	Payment has been already paid
9065	Requesting agent has no privilege to use SMT Payout API.	NULL
9066	A system error has occurred in the processing of your request.	A system exception has been th
9067	Transaction is Host Suspicious	The transaction has been marke
9068	Invalid data type	Data supplied for the request
9069	Invalid date range for the requested report	NULL
9070	No settlement data found	NULL
9071	Requesting agent has no privilege to use SMT Send API.	NULL
9072	Invalid System Transaction Status code	Status code supplied for the t
9073	Roll Back Transaction request denied	SMT does not allow to roll bac
9074	Invalid Notification code	Incorrect notification code su
9075	No Payout Agent data found	NULL
9076	Invalid Agents Country for Get Transaction	The Agents Country is not the
9077	Invalid date range for Get Transaction	NULL
9078	Invalid Status Code for Get Transaction	Status Code supplied for Get T
9079	Invalid Agents Country for Get Customer	The Agents Country is not the
9080	Agent not entitled to cancel this transaction	Only Send Agent for the transa
9081	Senders First and Last name does not match on SMT system	NULL
9082	Cannot register a Globe Card when Partner already supplied a Globe Card number.	NULL
9083	Cannot register and update a Customer detail for Globe Card detail in a single request	NULL
9084	Globe Card number is mandatory when updating Customers detail	NULL
9085	Corridor exist but no data for the corridor found	NULL
9086	Unable to calculate Send fee	NULL
9087	Corridor not found	Corridor not exists from origi
9088	NOT USED	NULL
9089	No Payout Agents found	The input criteria did not fin
9090	System cannot find the XML file in the expected path	The country rule (XML file)
9091	System does no have permission for read the XML file	NULL
9092	The transaction cannot be modify due to current transaction status	NULL
9093	Cannot make modification to this Account Deposit transaction	NULL
9094	No ID Type data found	NULL
9095	No country ISO Code found	NULL
9096	No country Currency Code found	NULL
9097	No country state code found	NULL
9098	Transaction status has been rolled back from Cancelled to be available for Payout	NULL
9099	Transaction status has been rolled back from Payout to Originator (Refund) to be available for Payout	NULL
9100	Unable to rollback transaction. Please contact SMT Support.	NULL
9101	Unable to cancel transaction. Please contact SMT Support.	NULL
9102	The transaction does not comply with Pre-AML rules for the specified corridor	NULL

SMT Code	SMT Code description	Explanation
9103	SMT transaction number was not provided	NULL
9104	Destination Payout Amount and Local Send Amount were not supplied	NULL
9105	NOT USED	NULL
9106	The agent does not belong to partner	Not exist a relation between A
9107	The Corridor is disabled	NULL
9108	Not found corridors	NULL
9109	Cancellation in progress	NULL
9110	Unable to refund transaction. Please contact SMT Support.	NULL
9111	Invalid ISO Country Code	The supplied ISO Country Code
9112	Invalid ISO Currency Code	The supplied ISO Currency Code
10	The operation has been requested. Please, contact Call Center in order to complete it	An operation (Cancellation, Mo
9113	Unable to modify transaction. Please contact SMT Support.	GetUTCDate()
9114	No transactions that match the supplied criteria were found	GetUTCDate()
9115	Transaction could not be sent	GetUTCDate()
9116	Invalid Data Value	NULL
9117	Agent not entitled to modify this transaction	Only Send Agent for the transaction can modify the transaction
9118	Agent not entitled to refund this transaction	Only Send Agent for the transaction can refund the transaction
9119	Refund in progress	NULL
9120	The user not has privilege to use requested functionality	NULL
9121	Invalid ISO State Code	The supplied ISO State Code is
9122	Agent not entitled to rollback this transaction	Only Send Agent for the transaction can roll back the transaction
9123	Agent not entitled to confirm this transaction	Only Send Agent for the transaction can confirm the transaction
9124	Aggregation	NULL
9125	Invalid zip code	NULL
9126	Invalid Text	When Sender or Receiver first name, last name or address has especial characters
9127	Invalid ID	NULL
9128	Unable to confirm paid transaction. Please contact SMT Support.	NULL
9129	Unable to confirm send transaction. Please contact SMT Support.	NULL
9130	Unable to update workflow. Please contact SMT Support.	NULL
9131	Agent not entitled to update this transaction	NULL
9132	This is not an Account Deposit or Courier Delivery transaction	NULL
9133	This is not a Courier Delivery transaction	NULL
9134	This is not an Account Deposit transaction	NULL

Appendix C: Transaction Status Codes

SMT has several send and payout status for transactions held in the SMT system. The following statuses of transactions are *the most commonly used* and can be shown in the reports produced by SMT and the API message responses.

Status Code	Meaning
PP	If the transaction has been stopped by Compliance check.
SQ	If the transaction is confirmed suspicious and will not be released until sending agent is contacted.
CN	When the transaction has been cancelled.
CP	When the transaction has been sent and is ready for payout.
IP	When the transaction is in an incomplete status or in progress. These can happen if: The transaction was not completed properly by the Send Partner. SMT sent the transaction it to an outside payout partner (via a payout interface) and SMT is waiting from payment confirmation. The Send Partner did not confirm the send transaction
PD	When the transaction has been paid to the customer, SMT will send status 'PD'
PO	When the transaction has been paid back to the originator (i.e. cancellation without fees).
RF	When the payout agent has refused to make the payment due to insufficient id or other reasons. This is a payout status only and is in combination with a send status of 'CP'.