2013

U Remit International Corporation

373 Front Street, West Suite 2702
M5V 3R7, Toronto, Canada

Document Version: 1.1
Author: Basharit Rafique

RECEIVE API DOCUMENT

This document contains information about the Receive API Interface designed for payout partners of U Remit International Corporation. For further information regarding integration, send email to basharit@uremit.ca

Table of Contents

Confidential Notice 3
API Document Revision History 4
Introduction:- 5
Scope of Receive API:- 5
1. *DisplayTranaction:-* 5
Input Parameters:- 5
Output Parameters:- 6
2. *DisplayTransactionList_Cash (Optional):-* 6
Input Parameters:- 6
Output Parameters:- 6
3. *DisplayTransactionList_Bank:-* 7
Input Parameters:- 7
Output Parameters:- 7
4. *PayTranaction:-* 7
Input Parameters:- 7
Output Parameters:- 8
5. *ChangePassword:-* 8
Input Parameters:- 8
Output Parameters:- 8
ID Type List:- 9
Response Code Details:- 9
Sample Code (C#.NET):- 10
- ***DisplayTransaction Method:-*** 10
- ***PayTransaction Method:-*** 10
- ***ChangePassword Method:-*** 11

Confidential Notice

Confidentiality:-

This document contains information confidential and proprietary to **U Remit International Corporation.** The information may not be used, disclosed or reproduced without the prior written authorization of ***UREMIT*** and those so authorized may only use the information for the purpose of evaluation consistent with authorization. Based upon the extent of the information provided, individuals with access to this information may be required to sign a nondisclosure confidentiality agreement

Intellectual Property Rights:-

The contents of this document remain the intellectual property of ***UREMIT*** at all times. Unauthorized reproduction, photocopying or disclosure to any other party, in whole or in part, without the expressed written consent of ***UREMIT*** is prohibited. All authorized reproductions must be returned to ***UREMIT*** immediately upon request

Trademarks:-

All trademarks mentioned herein, marked and not marked, are the property of their respective owners

API Document Revision History

Date	Document Version	Description	Revision By
18 Apr 2012	1.0	Preliminary Review	Basharit
19 Apr 2012	1.0	Preliminary Review	Dhiraj
19 Apr 2012	1.0	Final Review	Basharit
21 Aug 2012	1.0	Amendments	Basharit
10 Oct 2012	1.1	Amendments	Basharit
10 Dec 2012	1.1	Amendments	Basharit
01 Mar 2013	1.2	Amendments	Basharit

Introduction:-

UREMIT developed an online Application Programming Interface **(API)** which can be easily integrated in any system working on any platform. UREMIT's payout partner will call UREMIT API from their internal software/applications and would be able to pull out the transaction from UREMIT main web based remittance system. This API interface interacts with the UREMIT online remittance application in real time. This document describes what the interface is designed to do and how it can be used. It also contains technical information to provide a general working direction for the Payout Partner.

The Receive API is designed for Payout Partners that require real-time communication and transmission of messages via web services or SOA

Scope of Receive API:-

This document covers the generic online interface API developed by UREMIT to allow remittance transactions to be paid out by Payout Partners using their own systems instead of using UREMIT online remittance application interface. This API provides the facility to display and validate the transaction details as well as pull out (Payout) the transaction in real time. All the transmission through this API is real time and will affect the payout partner account in real time

Receive API Methods:-

1. DisplayTranaction:-

This method is used to request the details of a specific transaction which needs to be pay out. The Payout Partner will provide a UREMIT's transaction reference number (UTN), and the system will validate the request against the business rules for a payout. If valid, API will respond with full transaction details. This method contains the following Input and Output parameters

Input Parameters:-

DisplayTransactionRequest → From Partner To UREMIT			
Field Name	**Size**	**Type**	**Description**
UniqueID*	10	String	Unique ID assigned to Partner
Password*	20	String	Password assigned to Partner
SecurityKey*	30	String	Security Key assigned to Partner
TransactionNo*	20	String	Unique Transaction Reference Number of UREMIT
* Mandatory Field			

Output Parameters:-

DisplayTransactionResponse ← From UREMIT To Partner			
Field Name	**Size**	**Type**	**Description**
Successful		Bool	Result of API Call (True / False)
ResponseCode	2	String	Code explaining response of API request *See Page 9*
ResponseMessage	255	String	Message response of API request *See Page 8*
TransactionNo	20	String	Unique Transaction Reference Number of UREMIT
Status	50	String	Current Status of the Transaction
TransactionDate		String	Transaction send Date
ReceiveCountryCode	2	String	ISO Code of receive country
ReceiveCurrencyCode	3	String	ISO Code of Receive Currency
AmountToPay		Numeric	Amount to be Paid to Receiver
AmountToPayInWords	200	String	Amount in words to be Paid to Receiver
SenderFirstName	50	String	First Name of Sender
SenderLastName	50	String	Last Name of Sender
ReceiverFirstName	50	String	First Name of Receiver
ReceiverLastName	50	String	Last Name of Receiver
ReceiverAddress	100	String	Address of Receiver
ReceiverContactNo	50	String	Contact No of Receiver
ReceiverCity	50	String	City of Receiver
ReceiverNationality	2	String	Nationality of Receiver

2. *DisplayTransactionList_Cash (Optional):-*

This method is used to request the List of Cash Transactions which needs to be pay out. The Payout Partner will provide the Account No along with login credentials. System will validate the request against the business rules. If valid, it will respond with the list of Cash Transactions. Please note this method is only to get the list of Cash Transactions. To pull the transaction, you need to call the PayTransaction method for each transaction appeared in the list.

Please note this method is not available by default. You need to confirm with Operations Dept

This method contains the following Input and Output parameters

Input Parameters:-

DisplayTransactionListRequest → From Partner To UREMIT			
Field Name	**Size**	**Type**	**Description**
UniqueID*	10	String	Unique ID assigned to partner
Password*	20	String	Password assigned to partner
SecurityKey*	30	String	Security Key assigned to partner
AccountNo*	20	String	Partner Account No provided by UREMIT
* Mandatory Field			

Output Parameters:-

DisplayTransactionListResponse ← From UREMIT To Partner

Field Name	Size	Type	Description
Successful		Bool	Result of API Call (True / False)
ResponseCode	2	String	Code explaining response of API request See Page 9
ResponseMessage	255	String	Message response of API request See Page 9
dsTransactionList		String	DataSet with Cash Transaction List

3. DisplayTransactionList_Bank:-

This method is used to request the List of Bank Transactions which needs to be pay out. The Payout Partner will provide the Account No along with login credentials. System will validate the request against the business rules. If valid, it will respond with the list of Bank Transactions. Please note this method is only to get the list of Bank Transactions. To pull the transaction, you need to call the PayTransaction method for each transaction appeared in the list. This method contains the following Input and Output parameters

Input Parameters:-

DisplayTransactionListRequest → From Partner To UREMIT			
Field Name	**Size**	**Type**	**Description**
UniqueID*	10	String	Unique ID assigned to partner
Password*	20	String	Password assigned to partner
SecurityKey*	30	String	Security Key assigned to partner
AccountNo*	20	String	Partner Account No provided by UREMIT
* Mandatory Field			

Output Parameters:-

DisplayTransactionListResponse ← From UREMIT To Partner			
Field Name	**Size**	**Type**	**Description**
Successful		Bool	Result of API Call (True / False)
ResponseCode	2	String	Code explaining response of API request See Page 9
ResponseMessage	255	String	Message response of API request See Page 9
dsTransactionList		String	DataSet with Bank Transaction List

4. PayTranaction:-

This method is used to payout the UREMIT transaction. The Payout Partner will provide a UREMIT's transaction reference number (UTN) along with the complete ID details of Receiver, and the system will validate the request against the business rules for a payout. If valid, API will respond with the current status of the transaction. This method contains the following Input and Output parameters

Input Parameters:-

PayTransactionRequest → From Partner To UREMIT			
Field Name	**Size**	**Type**	**Description**
UniqueID*	10	String	Unique ID assigned to Partner
Password*	20	String	Password assigned to Partner

SecurityKey*	30	String	Security Key assigned to Partner
TransactionNo*	20	String	Unique Transaction Reference Number of UREMIT
ReceiverIDType*	1	String	ID Type Code See Page 9
ReceiverIDPlaceOfIssue*	2	String	ISO Code of Receiver ID Place of Issue Country
ReceiverIDNumber*	20	String	ID Number of Receiving Customer
ReceiverIDExpiryDate*		String	Valid ID Expiry Date of Receiving Customer (mm/dd/yyyy or dd MMM yyyy)
* Mandatory Field			

Output Parameters:-

PayTransactionResponse ← From UREMIT To Partner			
Field Name	**Size**	**Type**	**Description**
Successful		Bool	Result of API Call (True / False)
ResponseCode	2	String	Code explaining response of API request See Page 9
ResponseMessage	255	String	Message response of API request See Page 9
TransactionNo	20	String	Unique Transaction Reference Number of UREMIT
Status	50	String	Current Status of the transaction
ReceiveCountryCode	2	String	ISO Code of Receive Country
ReceiveCurrencyCode	3	String	ISO Code of Receive Currency
AmountToPay		Numeric	Amount to be paid to receiver
AmountToPayInWords	200	String	Amount in words to be paid to receiver
CommissionShareLC		Numeric	Commission Share in LC for Receiving Partner
CommissionShareUSD		Numeric	Commission Share in USD for Receiving Partner

5. ***ChangePassword:-***

This method is used to Change the password for payout partner

Input Parameters:-

ChangePasswordRequest → From Partner To UREMIT			
Field Name	**Size**	**Type**	**Description**
UniqueID*	10	String	Unique ID assigned to partner
Password*	20	String	Password assigned to partner
SecurityKey*	30	String	Security Key assigned to partner
NewPassword*	30	String	New Password to be updated
* Mandatory Field			

Output Parameters:-

APICallResponse ← From UREMIT To Partner			
Field Name	**Size**	**Type**	**Description**
Successful		Bool	Result of API Call (True / False)
ResponseCode	2	String	Code explaining response of API request See Page 9
ResponseMessage	255	String	Message response of API request See Page 9

ID Type List:-

While calling the PayTranasction method of API, Use the following for Receiver ID Type codes

Code	Message
1	National ID
2	Passport
3	Work Permit
4	Driving License
5	Iqama

Response Code Details:-

You can expect following Response Codes and Messages from the API

Code	Message
01	Successful API Call
02	Invalid Unique ID
03	Invalid Password
04	Invalid Security Key
05	User is Not Active
06	User Branch is Not Active
07	User Account is Not Active
08	User Authorization Not Found
09	Insufficient Rights to Pay Transaction
10	Invalid Transaction No
11	Transaction does not belongs to your country
12	Transaction does not belongs to your network
13	Transaction status is Cancelled
14	Transaction status is Paid
15	Transaction found and is under screening. Please try later
16	Receiver ID Type is invalid
17	Receiver ID Place of Issue is invalid
18	Receiver ID Number is invalid
19	Receiver ID Expiry Date is invalid. Please enter future date
00	General Exception
52	Invalid Account No
53	Insufficient Rights.[Message]

Sample Code (C#.NET):-

- ***DisplayTransaction Method:-***

```
ReceiveAPI.DisplayTransactionRequest dtReq = new ReceiveAPI.DisplayTransactionRequest();

dtReq.UniqueID = "UniqueID";                          //PROVIDED BY UREMIT
dtReq.Password = "Password";                          //PROVIDED BY UREMIT
dtReq.SecurityKey = "EncryptedSecurityKey";           //PROVIDED BY UREMIT
dtReq.TransactionNo = "2324587456321";                //PROVIDED BY RECEIVER

ReceiveAPI.ReceiveAPIClient Paycl = new ReceiveAPI.ReceiveAPIClient();
ReceiveAPI.DisplayTransactionResponse dtRes = new ReceiveAPI. DisplayTransactionResponse();

dtRes = Paycl.PayTransaction(ptReq);          //CALLING API'S DISPLAY TRANSACTION METHOD
if (dtRes.Successful)                         //VALIDATE IF SUCCESSFULL
{
        LabelStatus.Text= dtRes.Status;
        LabelResponseMessage.Text= dtRes.ResponseMessage;
        LabelAmount.Text= dtRes.Amount;
        LabelAmountInwords.Text= dtRes.AmountInWords;
        ////////////////////////////////////////////////////////
        //YOUR CODE GOES HERE TO DISPLAY THE TRANSACTION NFORMATION
}
else
{
        ////////////////////////////////////////////////////////
        //YOUR CODE GOES HERE FOR DECLINE MESSAGES
}
```

- ***PayTransaction Method:-***

```
ReceiveAPI.PayTransactionRequest ptReq = new ReceiveAPI.PayTransactionRequest();

ptReq.UniqueID = "UniqueID";                          //PROVIDED BY UREMIT
ptReq.Password = "Password";                          //PROVIDED BY UREMIT
ptReq.SecurityKey = "EncryptedSecurityKey";           //PROVIDED BY UREMIT
ptReq.TransactionNo = "2324587456321";                //PROVIDED BY RECEIVER
ptReq.ReceiverIDType = 1;                             //CODES PROVIDED BY UREMIT
ptReq.ReceiverIDPlaceOfIssue = "IN";                  //ISO CODE OF COUNTRY
ptReq.ReceiverIDNumber = "999444555";                 //ID NUMNER OF RECEIVER
ptReq.ReceiverIDExpiryDate = "04/31/2012";            // ID EXPIRY DATE

ReceiveAPI.ReceiveAPIClient Paycl = new ReceiveAPI.ReceiveAPIClient();
ReceiveAPI.PayTransactionResponse ptRes = new ReceiveAPI.PayTransactionResponse();

ptRes = Paycl.PayTransaction(ptReq);          //CALLING API'S PAY TRANSACTION METHOD
if (ptRes.Successful)                         //VALIDATE IF SUCCESSFULL
{
        LabelStatus.Text=ptRes.Status;
        LabelResponseMessage.Text= ptRes.ResponseMessage;
        ////////////////////////////////////////////////////////
        YOUR CODE GOES HERE FOR INTERNAL SYSTEM ENTRIES
}
else
{
        ////////////////////////////////////////////////////////
        YOUR CODE GOES HERE FOR DECLINE MESSAGES
}
```

- ***ChangePassword Method:-***

```
ReceiveAPI.ChangePasswordRequest cpReq = new ReceiveAPI. ChangePasswordRequest();

cpReq.UniqueID = "UniqueID";                          //PROVIDED BY UREMIT
cpReq.Password = "Password";                          //PROVIDED BY UREMIT
cpReq.SecurityKey = "EncryptedSecurityKey";           //PROVIDED BY UREMIT
cpReq.NewPassword= "NewPassword";                     //NEW PASSWORD TO BE UPDATED

ReceiveAPI.ReceiveAPIClient Paycl = new ReceiveAPI.ReceiveAPIClient();
ReceiveAPI.APICallResponse cpRes = new ReceiveAPI. APICallResponse();

cpRes = Paycl.ChangePassword(cpReq);          //CALLING API'S CHANGE PASSWORD METHOD
if (cpRes.Successful)                         //VALIDATE IF SUCCESSFULL
{
        LabelResponseMessage.Text= cpRes.ResponseMessage;
        ////////////////////////////////////////////////////////
        YOUR CODE GOES HERE FOR INTERNAL SYSTEM ENTRIES
}
else
{
        ////////////////////////////////////////////////////////
        YOUR CODE GOES HERE FOR DECLINE MESSAGES
}
```