

# Machine Learning and Having It Deep and Structured

## HOMEWORK #1

Training Deep Neural Network

呂相弘 吳彥謙

[r03942039@ntu.edu.tw](mailto:r03942039@ntu.edu.tw)

[b99901106@ntu.edu.tw](mailto:b99901106@ntu.edu.tw)

# Outline

- **DNN in Speech Recognition**
- **DNN**
- **Kaggle**
- **Dataset and Format**
- **Submission Requirements**
- **Grading**
- **GPU Acceleration**
- **Tips**
- **Baselines**
- **語音導覽(103-2)**

---


# DNN IN SPEECH RECOGNITION

# Speech Recognition

- In speech processing...
  - each word consists of syllables
  - each syllable consists of phonemes


“青色” → “青(く | ン)色(ム ㇿ、)” → ”く” (syllables)  
青:TSI --I -N (phonemes)  
色:S--@ (phonemes)
- Each time frame, with an observance (vector) mapped to a phoneme.

# Observation Sequences




# DNN in Speech Recognition

- **Goal:** predict **phoneme** given feature in each time frame.
  - Frame-wise prediction
- **Input:** acoustic features
  - Raw waveform, MFCC, FBANK or...
- **Output:** pronunciation units
  - Phonemes or...
- To know more about Automatic Speech Recognition(ASR), please refer to DSP



# Homework 1: Training Deep Neural Network






# Main Problems in HW1

- Model initialize
- Feedforward
- Backpropagate
- Update
- Predict

# Model Initialize


- DNN sometimes fails at local optimum problem, so **initialization matters**.
- Practically, there exists unsupervised pre-training technique on initialization.
- However, in this homework, we recommend you **initialize them randomly for the simplicity and efficiency**.




# Feedforward

$$y = f(x) = \sigma(W^L \dots \sigma(W^2 \sigma(W^1 x + b^1) + b^1) \dots + b^L)$$

$$\sigma(W^L a^{L-1} + b^L) = a^L = y$$



# Backpropagate



Example:  $(x^r, \hat{y}^r)$


$$\begin{aligned} \frac{\partial C^r}{\partial w_{ij}^L} &= \frac{\partial C^r}{\partial y_i^r} \frac{\partial y_i^r}{\partial z_i^L} \frac{\partial z_i^L}{\partial w_{ij}^L} \\ &= a_j^{L-1} \sigma'(z_i^L) (y_i^r - \hat{y}_i^r) \end{aligned}$$

# Update

Starting  
Parameters



$\theta^0$



$\theta^1$



$\theta^2$



.....

$C(\theta^0)$

$>$

$C(\theta^1)$

$>$

$C(\theta^2)$

$>$

.....

*Compute  $\nabla C(\theta^0)$*

$$\theta^1 = \theta^0 - \eta \nabla C(\theta^0)$$

*Compute  $\nabla C(\theta^1)$*

$$\theta^2 = \theta^1 - \eta \nabla C(\theta^1)$$

*Compute  $\nabla C(\theta^2)$*

In practice,  $\eta$  can simply set to be constant

$\eta$  is called “***learning rate***”

$\eta$  should be small enough, but should not be too small.

# Predict

- DNN classifier usually output the **1-best label** as prediction.
- Practically, the DNN may preserve certain number of good candidates for further processing due to the **structure of speech**.
  - That is, the best in one frame would be unacceptable when considering the context frames.
- The sequence “fixing” procedure is actually your HW2, comparable among the world as announced.
- In HW1, you should only predict the **framewise 1-best output**.


## More About Input...

- We provide **3 types** of feature for the DNN input w.r.t each frame.
  - Raw Waveform(16k sampling rate)
  - MFCC(dimension = 39)
  - FBANK(dimension = 69)
- MFCC and FBANK are 2 types of feature extracted from the wave. However, **the details lie beyond the scope of this course.**
- There does exist debates over which feature is better. So the choice is yours.

# More About Input...

- You could generate your own features based on the WAV/MFCC/FBANK.
- However, be sure your task can be evaluated in a frame-wise way.

$$\begin{bmatrix} x_1 \\ x_2 \\ \vdots \\ x_D \end{bmatrix} = o_1 \begin{bmatrix} x_1 \\ x_2 \\ \vdots \\ x_D \end{bmatrix} = o_2$$





## More About Output...

- We provide **3 types** of training target for the DNN output w.r.t each frame.
  - states(index from 0 to 1942)
  - 48 - phonemes
  - 39 - phonemes
- The difference also lies beyond the scope of this course. You could simply view them as more **delicate pronunciation units** at different level.

## More About Output...

- Actually, the framewise labels are usually absent. There are only human annotation w.r.t each sentence.
- Practically, we forcibly align the labels to each frame by generative models other than DNN.
- The alignment results are then prepared for DNN as training targets.
- **In this homework, you do not need to bother. The alignments are transformed into framewise labels for you.**

# Validation

- There are two scores displayed when you upload your results on the site.
- Public score is based on validation set and you can compare yours with others'.
- Private score is based on test set and should determine your final place.
- To better control your training procedure, you may want to test your model on a validation set after each epoch.
  - However, submitting the results onto the scoreboard after each epoch can be tedious,
  - In such case, it is recommended to **split your own validation set** from the training set.

# Evaluation

- **Framewise** phoneme prediction
- Frame Accuracy


$$\textit{Frame Accuracy} = \frac{\textit{\# of correct frames}}{\textit{\# of total frames}}$$

# Evaluation

- Despite the type of training target you used, you **have to** map all of them to 39 phoneme set for evaluation.
  - Some training targets would be merged into the same phoneme.
- The frame accuracy is calculated according to the merged prediction.

# Baseline


- Only one hidden layer
- 69x128x48
- 69: fbank features
- 128: 1 hidden layer
- 48: 48 phoneme set



# Pseudo Code

```
dnn = DNN( STRUCTURE , LEARNING_PARAMETERS );
train = Dataset( TRAIN_FILE , LEARNING_PARAMETERS );
valid = Dataset( DEV_FILE , LEARNING_PARAMETERS );
test = Dataset( TEST_FILE , LEARNING_PARAMETERS );
epoch = 0;
while epoch < MAX_EPOCH
    while ( batch = train.load_batch() )
        dnn.forward(batch);
        dnn.calculate_error( ERROR_FUNCTION );
        dnn.backpropagate( );
        dnn.update();
    end
    Ein = dnn.report_error_rate( train );
    Eval = dnn.report_error_rate( valid );
    epoch = epoch + 1;
end

while( batch = test.load_batch() )
    dnn.forward( batch )
    dnn.output_predict()
end
```





---

# KAGGLE

# Kaggle

- <http://www.kaggle.com/>
- A competition platform used by many academic institutes.
- Evaluate your result on this website.
  - With Scoreboard that can show off your improvement.
- You could upload your predictions **only twice a day**.
  - Be careful!

kaggle *in Class*

# Registration

kaggle

Sign up

Login

## The Home of Data Science

COMPETITIONS • CUSTOMER SOLUTIONS • JOBS BOARD

Get started »



# Registration

kaggle

Customer Solutions

Competitions

Community ▾

Sign up

Login

## Become a competitor

**One account per individual.** If you're joining as a company, please create one account for each individual in your group.

**Already have an account but need a university address to enter an InClass competition?** Change the email on your existing account via your profile settings.

Sign up in one click

(We won't share anything without your permission.)



or [manually create an account](#) »

As You Wish

# Registration

kaggle

Customer Solutions

Competitions

Community ▾

wyc2010

Logout

Hi wyc2010! We'd like to welcome you to Kaggle.

Since you're new, here's just a few ways to get started:



## Read more about how Kaggle works

Check out [How it Works](#).  
Ask a question on the [Kaggle Forum](#).



## Explore the competitions

Download some [active competition](#) data files and a sample entry. Or practice on a completed competition.



## Meet the community

Visit the [forums](#) for each competition to discuss methods & results.



wyc2010

[View /](#)  
[Edit Profile](#)

## On the Forums

Table comparing supervised learning algorithms

Viewing winner's code like in Topcoder

Methodological ML dispute with a Udacity teacher: Could you help me understanding if I'm right?

What was your favorite 2014 competition?

Are there other Kaggle contests with no labels of data?

sentiment analysis dataset

## On the Blog

Defending Champions Winners' ...

Reviewing the American Epilep...

Kaggle InClass: Stanford's "G...

CIFAR-10 Competition Winners:...

Convolutional Nets and CIFAR-...

2nd Place: The Hunt for Probi

## Active Competitions



## March Machine Learning Mania 2015

Predict the 2015 NCAA Basketball Tournament

14 days  
206 teams  
\$15,000

# SUCCESS!

# Join the Competition

- [https://kaggle.com/join/104\\_1\\_mlds\\_hw1](https://kaggle.com/join/104_1_mlds_hw1)

The screenshot shows the Kaggle interface for the 'MLDS\_HW1' competition. The top navigation bar includes the 'kaggle in Class' logo, the username 'wyc2010', and a 'Logout' button. The competition header features a teddy bear profile picture, the title 'MLDS\_HW1', and a progress bar indicating 'Wed 25 Feb 2015' and 'Sat 18 Apr 2015 (49 days to go)'. A left sidebar contains a menu with 'Dashboard', 'Home', 'Data', 'Make a submission', 'Information', 'Description', 'Evaluation', 'Rules', 'Forum', 'Leaderboard', and 'My Submissions'. The 'Data' and 'Make a submission' items are circled in red. The main content area displays 'Competition Details' with links to 'Get the Data' and 'Make a submission'. A yellow banner states 'This competition is private-entry. You've been invited to participate.' Below this, the title 'Training Deep Neural Network' is shown, followed by the text 'This is the home page of the competition.' At the bottom, the competition schedule is listed: 'Started: 10:52 pm, Wednesday 25 February 2015 UTC', 'Ends: 11:59 pm, Saturday 18 April 2015 UTC (52 total days)', 'Points: this competition does not award ranking points', and 'Tiers: this competition does not count towards tiers'. A 'Leaderboard' section at the bottom shows '1. SimpDanny Lu'.

1. Download Data & Read Description

2. Make a submission

# Join the Competition

1 team

1 player

1 entry

## Team Mergers

Team mergers are not allowed in this competition.

## Team Limits

There is no maximum team size.

## Submission Limits

You may submit a maximum of 2 entries per day.

You may select up to 2 final submissions for judging.

## Competition Timeline

Start Date: **2/25/2015 10:52:45 PM UTC**

Merger Deadline: **None**

First Submission Deadline: **None**

End Date: **4/18/2015 11:59:00 PM UTC**

## Rules Acceptance

**I understand and accept**

**I do not accept**

By clicking on the "I understand and accept" button below, you are indicating that you agree to be bound to the above rules.

# Join the Competition

kaggle  
*on Class*

wyc2010

Logout

Thank you for accepting the rules.



## SMS Verification

To make a submission, you must verify your Kaggle account via your mobile phone. You will only need to do this once. Do not use a public number or share your number with others.

8869XX-XXX-XXX

Phone number (inc. country code)



Enter phone number

Confirm

Remember to add country code(i.e. 886)



# Join the Competition

kaggle  
*on Class*

wyc2010

Logout

## SMS Verification

You should have received your verification  
code. Please enter it below.

123456  
Enter your code here

Confirm

Didn't receive a code?  
[Try again](#) with the same or a different number.



# Join the Competition



wyc2010

Logout

Your account has been successfully verified. Treat it nice, it's your only one!



Knowledge • 1 team

## MLDS\_HW1

Wed 25 Feb 2015

Sat 18 Apr 2015 (48 days to go)

Dashboard

Home

Data

Make a submission

Information

Description

Evaluation

Rules

Forum

Leaderboard

My Team

My Submissions


### Submit to MLDS\_HW1

Compete as myself

(You can always add team members later.)




Compete as a team



My Team

# Manage Your Team



Knowledge • 1 team

## MLDS\_HW1

Wed 25 Feb 2015

Sat 18 Apr 2015 (48 days to go)

Dashboard

- Home
  - Data
  - Make a submission
- Information
  - Description
  - Evaluation
  - Rules
- Forum
- Leaderboard
- My Team
- My Submissions

Leaderboard

1. Simpdanny Lu


Forum (0 topics)

### Manage Your Team

3. [Make a Submission](#) on behalf of your team.

1. Team Name

Team Members



wyc2010  
Team Leader

2. Invite someone to join your team

Email Address  [Send](#)

# Submitting for Team

The screenshot shows a web interface for a competition. On the left is a sidebar with navigation links: Dashboard, Home, Data, Make a submission, Information, Forum, Leaderboard, My Team, and My Submissions. The main content area is titled 'Competition Details » Get the Data » Make a submission'. It features a 'Make a submission' section with a sub-header 'Submitting for Team 飛語傳音'. A notification bar states 'You have 2 entries today. This resets 23 hours from now (00:00 UTC)'. Below this is a large yellow box with the text 'Click or drop your submission here'. Underneath is a text input field with the placeholder 'Enter a brief description of this submission here.'. At the bottom of the main area is a blue 'Submit' button. On the right side, there are two informational sections: 'File Format' which specifies CSV format and archive types, and '# of Predictions' which states the solution file should have 58,528 predictions and includes a link to a sample submission file. Three red circles are drawn on the page: one around the yellow submission box, one around the description text input field, and one around the blue 'Submit' button.

Dashboard

Home

Data

Make a submission

Information

Description

Evaluation

Rules

Forum

Leaderboard

My Team

My Submissions

Leaderboard

1. SimpDanny Lu

Forum (0 topics)

1 team

1 player

1 entry

Competition Details » Get the Data » Make a submission

Make a submission

Submitting for Team 飛語傳音

You have 2 entries today. This resets 23 hours from now (00:00 UTC).

Click or drop your submission here

Enter a brief description of this submission here.

Submit

**File Format**  
Your submission should be in CSV format. You can upload this in a zip/gz/rar/7z archive if you prefer.

**# of Predictions**  
We expect the solution file to have 58,528 predictions. The file should have a header row. Please see the sample submission file on the [data page](#) for an example of a valid submission.

# Final Rules

- Please team-up with a group name in Kaggle in 1 week.
- Any submission by individuals would be neglected and team mergers forbidden.
- Any submission by individuals would be neglected and team mergers forbidden.
- Any submission by individuals would be neglected and team mergers forbidden.
- Any submission by individuals would be neglected and team mergers forbidden.
- Any submission by individuals would be neglected and team mergers forbidden.

---


# Dataset and Format

# Dataset

- **TIMIT**(Texas Instrument and Massachusetts Institute of Technology)
- Well-transcribed speech of American English speakers of different sexes and dialects.
- Designed for the development and evaluation of ASR systems.

# Dataset


- Each instance consists of 3 parts:
  - speaker **faem0**, sentence **sil392**, the **37th** frame





# Data Format

- **WAV file: Speak-Sentence ID + .wav**
  - Check by your ear(s)
- **ARK file: Instance ID + features**



The image shows a screenshot of an ARK file with two lines of data. The first line is highlighted with a red oval around the instance ID '1' and a blue oval around the word 'features'. The second line is also highlighted with a red oval around the instance ID '2' and a blue oval around the word 'features'. The data consists of a sequence of numerical values representing features.

```
1 faem0_si1392_1 3.48541 3.60388 4.180700 3.526529 1.077076 6.677959 7.671936 7.826703 7.328356 7.501573 8.236745 7.386778 8.368101 9.175194 10.44421 9.683798 10.80442 11.04268 10.06622 10.55132 10.28832 11.0653 6 11.58939 0.2704574 0.05309612 -0.1586174 0.0615164 0.2801027 -0.226 3938 -0.412236 -0.5605489 -0.3172206 -2.384186e-07 -1.192093e-07 0.186 0594 -0.1076797 -0.2496915 -0.4659706 -0.2504535 -0.4384818 -0.254075 0.005485415 -2.384186e-07 0.1432481 -0.166646 -0.1194608 -0.1252215 -0.09690015 -0.2077889 -0.07074384 0.01680622 -0.06037173 -0.1450567 -0.1195837 -0.0516952 -0.04357988 -0.07634205 0.03012398 -0.01076791 -0.07573968 -0.155601 -0.06261331 -0.1235719 -0.1034293 -0.1540697e-08 -0.03 100324 -0.0533977 -0.0441806 -0.06928831 2 faem0_si1392_2 4.67213 4.400319 4.795176 3.526529 4.637282 6.426411 7.397112 6.217242 6.035976 7.336024 8.236745 8.184175 8.009169 8.50935 9.612121 9.683798 10.4058 10.89597 10.55984 10.9507 11.21048 10.79408 11.63718 -0.1763853 -0.18911 -0.8089488 -0.307582 0.196072 -0.5270134 -0.4397185 -0.5730056 -0.3994629 -0.1466 -0.2009004 0.1417596 -0.07178 64 -0.307953 -0.657351 -0.2283547 -0.478344 -0.3447649 0.0219395 -0.0599072 0.03480816 -0.01525 -0.1672461 -0.28692 -0.1340673 -0.1100322 -0.02306862 -0.0798292 -0.01635064 -0.07832487 0.05356358 0.06096881 -0.05751204 -0.09442315 -0.02923772 -0.001794666 0.01581386 -0.016641 91 -0.008102864 -0.01395154 -0.05501553 -0.03839263 -0.04878157 -0.101 0142 -0.005813509 -0.0769349
```

# Data Format

- LAB file: Instance ID + comma + label
- state label and 48 phones
- you have to map them to 39 phonemes yourselves.

```
1 maeb0_si1411_1,sil
2 maeb0_si1411_2,sil
3 maeb0_si1411_3,sil
4 maeb0_si1411_4,sil
5 maeb0_si1411_5,sil
6 maeb0_si1411_6,sil
7 maeb0_si1411_7,sil
8 maeb0_si1411_8,sil
9 maeb0_si1411_9,sil
10 maeb0_si1411_10,sil
11 maeb0_si1411_11,r
12 maeb0_si1411_12,r
13 maeb0_si1411_13,r
14 maeb0_si1411_14,r
15 maeb0_si1411_15,r
16 maeb0_si1411_16,r
17 maeb0_si1411_17,r
18 maeb0_si1411_18,r
19 maeb0_si1411_19,ix
20 maeb0_si1411_20,ix
21 maeb0_si1411_21,ix
22 maeb0_si1411_22,ix
```

# Data Format

- **MAP file: 2 mapping**
  - State ID - 48 phones - 39 phones
  - 48 phones - 39 phones
  - Delimiter: tab '\t'

0	sil	sil
1	aa	aa
2	ae	ae
3	ah	ah
4	ao	aa
5	aw	aw
6	ax	ah
7	ay	ay
8	b	b
9	ch	ch
10	cl	sil

aa	aa
ae	ae
ah	ah
ao	aa
aw	aw
ax	ah
ay	ay
b	b
ch	ch
cl	sil

# Data Format

- **CSV file:** Your prediction when submission.
- **Must mapped to 39-phonemes**
- **With header row: “Id,Prediction”**
- **Instance ID + comma + 39-phonemes**

```
Id,Prediction
fadg0_si1279_1,sil
fadg0_si1279_2,sil
fadg0_si1279_3,sil
fadg0_si1279_4,sil
fadg0_si1279_5,sil
fadg0_si1279_6,sil
fadg0_si1279_7,sil
fadg0_si1279_8,sil
fadg0_si1279_9,sil
fadg0_si1279_10,sil
```

---

# SUBMISSION REQUIREMENT

# Submission(Kaggle)

- Your predict.csv.
- Twice a day.
- Public score: validation set of TIMIT
- Private score: test set of TIMIT

#	Δ1d	Team Name	Score ?	Entries	Last Submission UTC (Best - Last Submission)
1	—	Simpdanny Lu	0.60880	2	Mon, 02 Mar 2015 15:12:21 (-4.3d)
		Simple Baseline	0.55088		
-		wyc2010	Waiting to pounce...	-	

# Submission(Ceiba)

- **Your source code and documentation**
  - Usage and environment Setting
  - Package dependency
  - **NO NN-based toolkit is allowed.**
    - Only matrix manipulation acceleration package can be utilized.
- **Report**
- Upload 1 copy per group.

# Report

- **Group Information 10%**
  - Group Name, Student Name, Student ID
  - Member Contribution
- **What have you done? 40%**
  - Data structure and algorithm design
  - Data preprocessing
  - Implementation tips and obstacles
  - Bug(s) and how to solve it(them).



# Report

- **Experiment Setting and Results 50%**
  - How you design your experiments
  - Compare different models/techniques
- **No more than 4 pages with font 12, A4 size.**

# Grading Policy

- **Accuracy 60%**
  - Simple Baseline in Kaggle (released day 7)
  - Once achieve the baseline, you can get the full credit.
  - 1 % less absolute accuracy = 1% absolute credit loss
- **Report 40%**
- **Implementation 20%.**
- **Bonus**
  - First Place 15%
  - First Runner-up 10%
  - Second Runner-up 5%

# Grading Policy

- Once you achieve simple baseline, you get 60% full credit **no matter how well your model performs.**
- Please do not get stuck in tuning learning rates or other basic parameters. However, they matter indeed.
- Your team members could be in charge of different methods to improve the results.

# Grading Policy

- 40% score is based on how many methods or extensions you have tried, with the experimental results in comparison.
- Momentum, dropout, CNN, RBM, learning rate policies, optimization algorithms or...
- Even if your score is not improved by some specific method, **the trial is worthy and you will get credits thereby.**

# Penalty

- **Latency**
  - Half-life = 24 hrs
  - The excess time will round up to hours.
  - The time is determined by ceiba upload.
- **Usage on NN-based toolkit**
  - **You shall get 0 credit in both implementation and accuracy parts.**
  - Please ask TAs whether you could use the package or not.

---


# GPU Acceleration

# Scalability Issue


- **GPU Acceleration**
  - C/C++: CUDA library
  - Python: Theano
  - Matlab: GPU toolbox
- **Typically, acceleration lies about 5-20 times.**
  - 20 – 80 hrs -> 4 hrs
  - You got 3 weeks to have your HW1 done.

# GPU Acceleration

## CPU (Multiple Cores)



## GPU (Hundreds of Cores)



PRO: Highly parallel with many micro floating point processors.  
CON: Memory transportation bottleneck.



# GPU Acceleration - C/C++

- **CUDA**
- **A good toolkit**
- **<https://github.com/botonchou/libcумatrix>**
- **Or write your toolkit! (Hard)**
- **<https://developer.nvidia.com/cublas>**

# GPU Acceleration - Python

- Theano is recommended
- Follow the instructions of Theano configuration
- <http://deeplearning.net/software/theano/library/config.html>

# GPU Acceleration - Matlab

- **gpuArray**
- **Usage**

```
Elapsed time is 1.542150 seconds.  
Elapsed time is 0.004115 seconds.
```

- **Reference**

```
% Init data  
A = rand( 2000, 4000 );  
gpu_A = gpuArray(A);  
  
B = rand( 4000, 5000 );  
gpu_B = gpuArray(B);  
  
% Perform A*B  
tic;  
C = A * B;  
toc;  
  
tic;  
gpu_C = gpu_A * gpu_B;  
toc;
```

# About Toolkits

- Theano is recommended for you to better comprehend GPU programming with easy usage.
- **However, theano.nnet is forbidden**
- Any package that wraps DNN together is not allowed.
- Ask if you're unsure about the usage of some specific package.

# Recommendation

- **Start as early as possible.**
  - In TA's poor machine(Nvidia GTX 660) , 1 epoch costs about 200 seconds.
  - 10 epochs are sufficient to achieve baseline if correctly implemented.
  - Bug is everywhere.

---

# Tips

# Tip 1

- Start-ups!
  - Group discussion and task assignments
  - Derive all formulas. Everyone.
  - Get familiar with Kaggle.
  - Which language?

## Tip 2

- Understand what happened....
  - Look over training data and testing data
  - Many decision
  - Data preprocessing.
  - Basic structure and core methods implementation.
  - Test on tiny set(make it yourselves!).



## Tip 3

- Everything settled down
  - Start training and report testing results.
  - Debugging...
  - Can you overfit the training data?
  - Precision overflow? (exponential)
  - Matrix multiplication?
  - Error backpropagation?

# Tip 4

- Basic learning techniques
  - Parameter selection
    - batch size, learning rate, or...
  - Frame shuffle?
  - Splice features in context window?
  - Regularization( weight decay )?
  - Learning rate decay?

---

# Baselines

## Simple Baseline - **0.5310**

- Once achieve this score, you will get **full credit in the grading part of accuracy.**
- However, only pure DNN is considered. Your mix learning techniques would help you better win the competition in Kaggle, but **your DNN alone should be powerful enough.**
- You must present your experiment results with pure DNN **in the report.**

# Simple Baseline - **0.5310**

Input	69	fbank features
Hidden	128	only one hidden layer
Output	48	-
Batchsize	128	-
Initial Learning Rate	0.0001	-
Learning Rate Decay	0.9999	decay with each batch updating
Initialization Variance	0.1	Model initial weights gaussian variance
Momentum	0.9	-
Training Time	about 5.5 mins	-

## Real Baseline - **0.6179**

- Due to the structure of the speech, **splicing contextual frames** (say previous 4 and subsequent 4) would usually helps
- Increase the model complexity with usage of **state level** pronunciation unit.
- A **real 2-3 days** training time required.

# Real Baseline - 0.6179

Input	621	previous 4 frames + subsequent 4 frames + center 1 frame = 9 frames fbank features
Hidden	1024-1024-1024-1024	4 layers
Output	1943	state label
Batchsize	256	-
Learning Rate	0.001	-
Dropout	0.1	-
Initialization	random [-0.1. 0.1]	uniform
Momentum	0.5	-
Training Time	2-3 days	600-700 seconds per epoch