Assured PNT
Challenges for Current Nav Technologies

Michael L. Carroll

November 12, 2024

©2024 by Michael L. Carroll

Introduction to Assured PNT

What is Assured PNT?

Introduction to Assured PNT

What is Assured PNT?

- **Assured Position, Navigation, and Timing (A-PNT):**

Introduction to Assured PNT

What is Assured PNT?

- **Assured Position, Navigation, and Timing (A-PNT):**
  - Provides reliable PNT information, even in GPS-degraded or denied environments

Introduction to Assured PNT

What is Assured PNT?

- **Assured Position, Navigation, and Timing (A-PNT):**
  - Provides reliable PNT information, even in GPS-degraded or denied environments
  - Critical for applications requiring high-precision and resilience, such as military, aviation, and critical infrastructure

Introduction to Assured PNT

What is Assured PNT?

- **Assured Position, Navigation, and Timing (A-PNT):**
  - Provides reliable PNT information, even in GPS-degraded or denied environments
  - Critical for applications requiring high-precision and resilience, such as military, aviation, and critical infrastructure
- **Main Goals of A-PNT**

Introduction to Assured PNT

What is Assured PNT?

- **Assured Position, Navigation, and Timing (A-PNT):**
  - Provides reliable PNT information, even in GPS-degraded or denied environments
  - Critical for applications requiring high-precision and resilience, such as military, aviation, and critical infrastructure
- **Main Goals of A-PNT**
  - Ensuring accuracy and integrity of position, navigation, and timing data

Introduction to Assured PNT

What is Assured PNT?

- **Assured Position, Navigation, and Timing (A-PNT):**
  - Provides reliable PNT information, even in GPS-degraded or denied environments
  - Critical for applications requiring high-precision and resilience, such as military, aviation, and critical infrastructure
- **Main Goals of A-PNT**
  - Ensuring accuracy and integrity of position, navigation, and timing data
  - Providing robustness against jamming, spoofing, and interference

Introduction to Assured PNT

What is Assured PNT?

- **Assured Position, Navigation, and Timing (A-PNT):**
  - Provides reliable PNT information, even in GPS-degraded or denied environments
  - Critical for applications requiring high-precision and resilience, such as military, aviation, and critical infrastructure
- **Main Goals of A-PNT**
  - Ensuring accuracy and integrity of position, navigation, and timing data
  - Providing robustness against jamming, spoofing, and interference
  - Mitigating risks of depending on GPS

Key Technologies in Assured PNT

Technologies Critical to A-PNT

Key Technologies in Assured PNT

Technologies Critical to A-PNT

- **Global Navigation Satellite Systems (GNSS):**

Key Technologies in Assured PNT

Technologies Critical to A-PNT

- **Global Navigation Satellite Systems (GNSS):**
  - Primary source of PNT data, with anti-jamming and anti-spoofing techniques (e.g., M-Code and SAASM for secure military applications)

Key Technologies in Assured PNT

Technologies Critical to A-PNT

- **Global Navigation Satellite Systems (GNSS):**
  - Primary source of PNT data, with anti-jamming and anti-spoofing techniques (e.g., M-Code and SAASM for secure military applications)
- **Inertial Navigation Systems (INS):**

Key Technologies in Assured PNT

Technologies Critical to A-PNT

- **Global Navigation Satellite Systems (GNSS):**
  - Primary source of PNT data, with anti-jamming and anti-spoofing techniques (e.g., M-Code and SAASM for secure military applications)
- **Inertial Navigation Systems (INS):**
  - Provides self-contained PNT information with accelerometers and gyroscopes, allowing operation in GPS-denied environments

Key Technologies in Assured PNT

Technologies Critical to A-PNT

- **Global Navigation Satellite Systems (GNSS):**
  - Primary source of PNT data, with anti-jamming and anti-spoofing techniques (e.g., M-Code and SAASM for secure military applications)
- **Inertial Navigation Systems (INS):**
  - Provides self-contained PNT information with accelerometers and gyroscopes, allowing operation in GPS-denied environments
- **Alternative PNT Sources:**

Key Technologies in Assured PNT

Technologies Critical to A-PNT

- **Global Navigation Satellite Systems (GNSS):**
  - Primary source of PNT data, with anti-jamming and anti-spoofing techniques (e.g., M-Code and SAASM for secure military applications)
- **Inertial Navigation Systems (INS):**
  - Provides self-contained PNT information with accelerometers and gyroscopes, allowing operation in GPS-denied environments
- **Alternative PNT Sources:**
  - Terrestrial-based signals (e.g., radio, cellular networks) and signals from Low Earth Orbit (LEO) satellites

Key Technologies in Assured PNT

Technologies Critical to A-PNT

- **Global Navigation Satellite Systems (GNSS):**
  - Primary source of PNT data, with anti-jamming and anti-spoofing techniques (e.g., M-Code and SAASM for secure military applications)
- **Inertial Navigation Systems (INS):**
  - Provides self-contained PNT information with accelerometers and gyroscopes, allowing operation in GPS-denied environments
- **Alternative PNT Sources:**
  - Terrestrial-based signals (e.g., radio, cellular networks) and signals from Low Earth Orbit (LEO) satellites
- **Precision Timing Sources:**

Key Technologies in Assured PNT

Technologies Critical to A-PNT

- **Global Navigation Satellite Systems (GNSS):**
  - Primary source of PNT data, with anti-jamming and anti-spoofing techniques (e.g., M-Code and SAASM for secure military applications)
- **Inertial Navigation Systems (INS):**
  - Provides self-contained PNT information with accelerometers and gyroscopes, allowing operation in GPS-denied environments
- **Alternative PNT Sources:**
  - Terrestrial-based signals (e.g., radio, cellular networks) and signals from Low Earth Orbit (LEO) satellites
- **Precision Timing Sources:**
  - Atomic clocks and GPS-disciplined oscillators to ensure reliable timing

Key Technologies in Assured PNT

Technologies Critical to A-PNT

- **Global Navigation Satellite Systems (GNSS):**
  - Primary source of PNT data, with anti-jamming and anti-spoofing techniques (e.g., M-Code and SAASM for secure military applications)
- **Inertial Navigation Systems (INS):**
  - Provides self-contained PNT information with accelerometers and gyroscopes, allowing operation in GPS-denied environments
- **Alternative PNT Sources:**
  - Terrestrial-based signals (e.g., radio, cellular networks) and signals from Low Earth Orbit (LEO) satellites
- **Precision Timing Sources:**
  - Atomic clocks and GPS-disciplined oscillators to ensure reliable timing

Security of M-Code Signals

Spoofing and Adversarial Threats

Security of M-Code Signals

Spoofing and Adversarial Threats

- **Purpose of M-Code:**

Security of M-Code Signals

Spoofing and Adversarial Threats

- **Purpose of M-Code:**
  - Developed by the U.S. Department of Defense (DoD) for enhanced security in military GPS

Security of M-Code Signals

Spoofing and Adversarial Threats

- **Purpose of M-Code:**
  - Developed by the U.S. Department of Defense (DoD) for enhanced security in military GPS
  - Provides stronger encryption, anti-jamming, and anti-spoofing features compared to earlier GPS signals

Security of M-Code Signals

Spoofing and Adversarial Threats

- **Purpose of M-Code:**
  - Developed by the U.S. Department of Defense (DoD) for enhanced security in military GPS
  - Provides stronger encryption, anti-jamming, and anti-spoofing features compared to earlier GPS signals
- **Current Status:**

Security of M-Code Signals

Spoofing and Adversarial Threats

- **Purpose of M-Code:**
  - Developed by the U.S. Department of Defense (DoD) for enhanced security in military GPS
  - Provides stronger encryption, anti-jamming, and anti-spoofing features compared to earlier GPS signals
- **Current Status:**
  - No publicly available evidence that adversaries have successfully spoofed M-Code signals

Security of M-Code Signals

Spoofing and Adversarial Threats

- **Purpose of M-Code:**
  - Developed by the U.S. Department of Defense (DoD) for enhanced security in military GPS
  - Provides stronger encryption, anti-jamming, and anti-spoofing features compared to earlier GPS signals
- **Current Status:**
  - No publicly available evidence that adversaries have successfully spoofed M-Code signals
  - M-Code's design makes spoofing significantly more challenging than with civilian signals

Security of M-Code Signals

Spoofing and Adversarial Threats

- **Purpose of M-Code:**
  - Developed by the U.S. Department of Defense (DoD) for enhanced security in military GPS
  - Provides stronger encryption, anti-jamming, and anti-spoofing features compared to earlier GPS signals
- **Current Status:**
  - No publicly available evidence that adversaries have successfully spoofed M-Code signals
  - M-Code's design makes spoofing significantly more challenging than with civilian signals
- **DoD Countermeasures:**

Security of M-Code Signals

Spoofing and Adversarial Threats

- **Purpose of M-Code:**
  - Developed by the U.S. Department of Defense (DoD) for enhanced security in military GPS
  - Provides stronger encryption, anti-jamming, and anti-spoofing features compared to earlier GPS signals
- **Current Status:**
  - No publicly available evidence that adversaries have successfully spoofed M-Code signals
  - M-Code's design makes spoofing significantly more challenging than with civilian signals
- **DoD Countermeasures:**
  - Ongoing assessment and improvements in GPS security to counter emerging threats

Security of M-Code Signals

Spoofing and Adversarial Threats

- **Purpose of M-Code:**
  - Developed by the U.S. Department of Defense (DoD) for enhanced security in military GPS
  - Provides stronger encryption, anti-jamming, and anti-spoofing features compared to earlier GPS signals
- **Current Status:**
  - No publicly available evidence that adversaries have successfully spoofed M-Code signals
  - M-Code's design makes spoofing significantly more challenging than with civilian signals
- **DoD Countermeasures:**
  - Ongoing assessment and improvements in GPS security to counter emerging threats
  - Continued vigilance as part of broader efforts to secure military navigation and timing

Security of M-Code Signals

Spoofing and Adversarial Threats

- **Purpose of M-Code:**
  - Developed by the U.S. Department of Defense (DoD) for enhanced security in military GPS
  - Provides stronger encryption, anti-jamming, and anti-spoofing features compared to earlier GPS signals
- **Current Status:**
  - No publicly available evidence that adversaries have successfully spoofed M-Code signals
  - M-Code's design makes spoofing significantly more challenging than with civilian signals
- **DoD Countermeasures:**
  - Ongoing assessment and improvements in GPS security to counter emerging threats
  - Continued vigilance as part of broader efforts to secure military navigation and timing

M-Code Resistance to Jamming

Key Features Enhancing M-Code Resilience

M-Code Resistance to Jamming

Key Features Enhancing M-Code Resilience

- **Higher Power Signal:**

M-Code Resistance to Jamming

Key Features Enhancing M-Code Resilience

- **Higher Power Signal:**
  - M-Code is broadcast at a higher power level than civilian GPS signals, making it harder to overwhelm with jamming signals

M-Code Resistance to Jamming

Key Features Enhancing M-Code Resilience

- **Higher Power Signal:**
  - M-Code is broadcast at a higher power level than civilian GPS signals, making it harder to overwhelm with jamming signals
- **Advanced Modulation Techniques:**

M-Code Resistance to Jamming

Key Features Enhancing M-Code Resilience

- **Higher Power Signal:**
  - M-Code is broadcast at a higher power level than civilian GPS signals, making it harder to overwhelm with jamming signals
- **Advanced Modulation Techniques:**
  - Uses Binary Offset Carrier (BOC) modulation, which improves signal separation and reduces interference

M-Code Resistance to Jamming

Key Features Enhancing M-Code Resilience

- **Higher Power Signal:**
  - M-Code is broadcast at a higher power level than civilian GPS signals, making it harder to overwhelm with jamming signals
- **Advanced Modulation Techniques:**
  - Uses Binary Offset Carrier (BOC) modulation, which improves signal separation and reduces interference
- **Narrower Beam Forming:**

M-Code Resistance to Jamming

Key Features Enhancing M-Code Resilience

- **Higher Power Signal:**
  - M-Code is broadcast at a higher power level than civilian GPS signals, making it harder to overwhelm with jamming signals
- **Advanced Modulation Techniques:**
  - Uses Binary Offset Carrier (BOC) modulation, which improves signal separation and reduces interference
- **Narrower Beam Forming:**
  - Directed beam shaping on modern GPS III satellites focuses signals for military users, increasing jamming resistance

M-Code Resistance to Jamming

Key Features Enhancing M-Code Resilience

- **Higher Power Signal:**
  - M-Code is broadcast at a higher power level than civilian GPS signals, making it harder to overwhelm with jamming signals
- **Advanced Modulation Techniques:**
  - Uses Binary Offset Carrier (BOC) modulation, which improves signal separation and reduces interference
- **Narrower Beam Forming:**
  - Directed beam shaping on modern GPS III satellites focuses signals for military users, increasing jamming resistance
- **Enhanced Encryption and Anti-Spoofing:**

M-Code Resistance to Jamming

Key Features Enhancing M-Code Resilience

- **Higher Power Signal:**
  - M-Code is broadcast at a higher power level than civilian GPS signals, making it harder to overwhelm with jamming signals
- **Advanced Modulation Techniques:**
  - Uses Binary Offset Carrier (BOC) modulation, which improves signal separation and reduces interference
- **Narrower Beam Forming:**
  - Directed beam shaping on modern GPS III satellites focuses signals for military users, increasing jamming resistance
- **Enhanced Encryption and Anti-Spoofing:**
  - Strong encryption and authentication make M-Code signals harder for adversaries to disrupt or imitate

M-Code Resistance to Jamming

Key Features Enhancing M-Code Resilience

- **Higher Power Signal:**
  - M-Code is broadcast at a higher power level than civilian GPS signals, making it harder to overwhelm with jamming signals
- **Advanced Modulation Techniques:**
  - Uses Binary Offset Carrier (BOC) modulation, which improves signal separation and reduces interference
- **Narrower Beam Forming:**
  - Directed beam shaping on modern GPS III satellites focuses signals for military users, increasing jamming resistance
- **Enhanced Encryption and Anti-Spoofing:**
  - Strong encryption and authentication make M-Code signals harder for adversaries to disrupt or imitate

Achieving Assured PNT

Strategies for Resilience and Accuracy

Achieving Assured PNT

Strategies for Resilience and Accuracy

- **Sensor Fusion Algorithms:**

Achieving Assured PNT

Strategies for Resilience and Accuracy

- **Sensor Fusion Algorithms:**
  - Integrate data from multiple sources (GNSS, INS, timing devices) to create a reliable composite solution

Achieving Assured PNT

Strategies for Resilience and Accuracy

- **Sensor Fusion Algorithms:**
  - Integrate data from multiple sources (GNSS, INS, timing devices) to create a reliable composite solution
  - Kalman filters and machine learning models are commonly used

Achieving Assured PNT

Strategies for Resilience and Accuracy

- **Sensor Fusion Algorithms:**
  - Integrate data from multiple sources (GNSS, INS, timing devices) to create a reliable composite solution
  - Kalman filters and machine learning models are commonly used
- **Robust Signal Authentication:**

Achieving Assured PNT

Strategies for Resilience and Accuracy

- **Sensor Fusion Algorithms:**
  - Integrate data from multiple sources (GNSS, INS, timing devices) to create a reliable composite solution
  - Kalman filters and machine learning models are commonly used
- **Robust Signal Authentication:**
  - Techniques to verify signal integrity and authenticity, essential for detecting spoofing and interference

Achieving Assured PNT

Strategies for Resilience and Accuracy

- **Sensor Fusion Algorithms:**
  - Integrate data from multiple sources (GNSS, INS, timing devices) to create a reliable composite solution
  - Kalman filters and machine learning models are commonly used
- **Robust Signal Authentication:**
  - Techniques to verify signal integrity and authenticity, essential for detecting spoofing and interference
- **System Redundancy:**

Achieving Assured PNT

Strategies for Resilience and Accuracy

- **Sensor Fusion Algorithms:**
  - Integrate data from multiple sources (GNSS, INS, timing devices) to create a reliable composite solution
  - Kalman filters and machine learning models are commonly used
- **Robust Signal Authentication:**
  - Techniques to verify signal integrity and authenticity, essential for detecting spoofing and interference
- **System Redundancy:**
  - Use of alternative PNT sources to maintain accuracy in contested or challenging environments

Achieving Assured PNT

Strategies for Resilience and Accuracy

- **Sensor Fusion Algorithms:**
  - Integrate data from multiple sources (GNSS, INS, timing devices) to create a reliable composite solution
  - Kalman filters and machine learning models are commonly used
- **Robust Signal Authentication:**
  - Techniques to verify signal integrity and authenticity, essential for detecting spoofing and interference
- **System Redundancy:**
  - Use of alternative PNT sources to maintain accuracy in contested or challenging environments
- **Intermittent GPS Synchronization:**

Achieving Assured PNT

Strategies for Resilience and Accuracy

- **Sensor Fusion Algorithms:**
  - Integrate data from multiple sources (GNSS, INS, timing devices) to create a reliable composite solution
  - Kalman filters and machine learning models are commonly used
- **Robust Signal Authentication:**
  - Techniques to verify signal integrity and authenticity, essential for detecting spoofing and interference
- **System Redundancy:**
  - Use of alternative PNT sources to maintain accuracy in contested or challenging environments
- **Intermittent GPS Synchronization:**
  - Periodic GPS updates improve INS drift performance and timing accuracy

Achieving Assured PNT

Strategies for Resilience and Accuracy

- **Sensor Fusion Algorithms:**
  - Integrate data from multiple sources (GNSS, INS, timing devices) to create a reliable composite solution
  - Kalman filters and machine learning models are commonly used
- **Robust Signal Authentication:**
  - Techniques to verify signal integrity and authenticity, essential for detecting spoofing and interference
- **System Redundancy:**
  - Use of alternative PNT sources to maintain accuracy in contested or challenging environments
- **Intermittent GPS Synchronization:**
  - Periodic GPS updates improve INS drift performance and timing accuracy

Assured Position, Navigation, and Timing (A-PNT)

System Components

Assured Position, Navigation, and Timing (A-PNT)

System Components

- **Primary Navigation Sources**

Assured Position, Navigation, and Timing (A-PNT)

System Components

- **Primary Navigation Sources**
  - GNSS (e.g., GPS), supplemented with anti-jamming technology

Assured Position, Navigation, and Timing (A-PNT)

System Components

- **Primary Navigation Sources**
  - GNSS (e.g., GPS), supplemented with anti-jamming technology
- **Alternative PNT Sources**

Assured Position, Navigation, and Timing (A-PNT)

System Components

- **Primary Navigation Sources**
  - GNSS (e.g., GPS), supplemented with anti-jamming technology
- **Alternative PNT Sources**
  - Terrestrial radio, cellular, and other satellite constellations

Assured Position, Navigation, and Timing (A-PNT)

System Components

- **Primary Navigation Sources**
  - GNSS (e.g., GPS), supplemented with anti-jamming technology
- **Alternative PNT Sources**
  - Terrestrial radio, cellular, and other satellite constellations
- **IMUs and Precise Clocks**

Assured Position, Navigation, and Timing (A-PNT)

System Components

- **Primary Navigation Sources**
  - GNSS (e.g., GPS), supplemented with anti-jamming technology
- **Alternative PNT Sources**
  - Terrestrial radio, cellular, and other satellite constellations
- **IMUs and Precise Clocks**
  - INS data for position and orientation in GPS-denied conditions

Assured Position, Navigation, and Timing (A-PNT)

System Components

- **Primary Navigation Sources**
  - GNSS (e.g., GPS), supplemented with anti-jamming technology
- **Alternative PNT Sources**
  - Terrestrial radio, cellular, and other satellite constellations
- **IMUs and Precise Clocks**
  - INS data for position and orientation in GPS-denied conditions

Kalman Filter State Model for INS/IMU, GPS, and Timing

State Vector

Kalman Filter State Model for INS/IMU, GPS, and Timing

State Vector

- Minimal State Vector $x = [P_x, P_y, P_z, V_x, V_y, V_z,$ Orientation, Accel Bias, Gyro Bias, Clock Bias, Clock Drift]

Kalman Filter State Model for INS/IMU, GPS, and Timing

State Vector

- Minimal State Vector $\mathrm{x} = [P_x, P_y, P_z, V_x, V_y, V_z,$ Orientation, Accel Bias, Gyro Bias, Clock Bias, Clock Drift]
- **Position and Velocity**

Kalman Filter State Model for INS/IMU, GPS, and Timing

State Vector

- Minimal State Vector $x = [P_x, P_y, P_z, V_x, V_y, V_z,$ Orientation, Accel Bias, Gyro Bias, Clock Bias, Clock Drift]
- **Position and Velocity**
- **Attitude and Orientation**

Kalman Filter State Model for INS/IMU, GPS, and Timing

State Vector

- Minimal State Vector $\mathrm{x} = [P_x, P_y, P_z, V_x, V_y, V_z,$ Orientation, Accel Bias, Gyro Bias, Clock Bias, Clock Drift]
- **Position and Velocity**
- **Attitude and Orientation**
- **Accelerometer and Gyroscope Biases**

Kalman Filter State Model for INS/IMU, GPS, and Timing

State Vector

- Minimal State Vector $x = [P_x, P_y, P_z, V_x, V_y, V_z,$ Orientation, Accel Bias, Gyro Bias, Clock Bias, Clock Drift]
- **Position and Velocity**
- **Attitude and Orientation**
- **Accelerometer and Gyroscope Biases**
- **Clock Bias and Drift**

Kalman Filter State Model for INS/IMU, GPS, and Timing

State Vector

- Minimal State Vector $x = [P_x, P_y, P_z, V_x, V_y, V_z,$ Orientation, Accel Bias, Gyro Bias, Clock Bias, Clock Drift]
- **Position and Velocity**
- **Attitude and Orientation**
- **Accelerometer and Gyroscope Biases**
- **Clock Bias and Drift**

Additional Navaids: The International GNSS Service (IGS)

Overview

Additional Navaids: The International GNSS Service (IGS)

Overview

- **What is IGS?**

Additional Navaids: The International GNSS Service (IGS)

Overview

- **What is IGS?**
  - IGS is a global collaborative network led by NASA's Jet Propulsion Laboratory (JPL)

Additional Navaids: The International GNSS Service (IGS)

Overview

- **What is IGS?**
  - IGS is a global collaborative network led by NASA's Jet Propulsion Laboratory (JPL)
  - Provides highly accurate GNSS data and products, supporting research, navigation, and Earth observation

Additional Navaids: The International GNSS Service (IGS)

Overview

- **What is IGS?**
  - IGS is a global collaborative network led by NASA's Jet Propulsion Laboratory (JPL)
  - Provides highly accurate GNSS data and products, supporting research, navigation, and Earth observation
  - Supported by 500+ Tracking Stations and Dozens of Analysis Centers

Additional Navaids: The International GNSS Service (IGS)

Overview

- **What is IGS?**
  - IGS is a global collaborative network led by NASA's Jet Propulsion Laboratory (JPL)
  - Provides highly accurate GNSS data and products, supporting research, navigation, and Earth observation
  - Supported by 500+ Tracking Stations and Dozens of Analysis Centers
- **GNSS Systems Supported:**

Additional Navaids: The International GNSS Service (IGS)

Overview

- **What is IGS?**
  - IGS is a global collaborative network led by NASA's Jet Propulsion Laboratory (JPL)
  - Provides highly accurate GNSS data and products, supporting research, navigation, and Earth observation
  - Supported by 500+ Tracking Stations and Dozens of Analysis Centers
- **GNSS Systems Supported:**
  - IGS includes data from multiple GNSS systems: GPS, GLONASS, Galileo, BeiDou, and QZSS

Additional Navaids: The International GNSS Service (IGS)

Overview

- **What is IGS?**
  - IGS is a global collaborative network led by NASA's Jet Propulsion Laboratory (JPL)
  - Provides highly accurate GNSS data and products, supporting research, navigation, and Earth observation
  - Supported by 500+ Tracking Stations and Dozens of Analysis Centers
- **GNSS Systems Supported:**
  - IGS includes data from multiple GNSS systems: GPS, GLONASS, Galileo, BeiDou, and QZSS
  - Enables multi-constellation support, increasing resilience when GPS signals are unavailable

Additional Navaids: The International GNSS Service (IGS)

Overview

- **What is IGS?**
  - IGS is a global collaborative network led by NASA's Jet Propulsion Laboratory (JPL)
  - Provides highly accurate GNSS data and products, supporting research, navigation, and Earth observation
  - Supported by 500+ Tracking Stations and Dozens of Analysis Centers
- **GNSS Systems Supported:**
  - IGS includes data from multiple GNSS systems: GPS, GLONASS, Galileo, BeiDou, and QZSS
  - Enables multi-constellation support, increasing resilience when GPS signals are unavailable

Key IGS Products

Applications in Navigation and PNT Systems

Key IGS Products

Applications in Navigation and PNT Systems

- **Precise GNSS Satellite Orbits:**

Key IGS Products

Applications in Navigation and PNT Systems

- **Precise GNSS Satellite Orbits:**
  - Provides satellite position data with centimeter-level accuracy

Key IGS Products

Applications in Navigation and PNT Systems

- **Precise GNSS Satellite Orbits:**
  - Provides satellite position data with centimeter-level accuracy
- **Satellite Clock Corrections:**

Key IGS Products

Applications in Navigation and PNT Systems

- **Precise GNSS Satellite Orbits:**
  - Provides satellite position data with centimeter-level accuracy
- **Satellite Clock Corrections:**
  - Offers high-accuracy clock corrections, improving timing accuracy across systems

Key IGS Products

Applications in Navigation and PNT Systems

- **Precise GNSS Satellite Orbits:**
  - Provides satellite position data with centimeter-level accuracy
- **Satellite Clock Corrections:**
  - Offers high-accuracy clock corrections, improving timing accuracy across systems
- **Earth Rotation Parameters (ERP):**

Key IGS Products

Applications in Navigation and PNT Systems

- **Precise GNSS Satellite Orbits:**
  - Provides satellite position data with centimeter-level accuracy
- **Satellite Clock Corrections:**
  - Offers high-accuracy clock corrections, improving timing accuracy across systems
- **Earth Rotation Parameters (ERP):**
  - Supports high-precision geospatial applications by modeling Earth's rotational variations

Key IGS Products

Applications in Navigation and PNT Systems

- **Precise GNSS Satellite Orbits:**
  - Provides satellite position data with centimeter-level accuracy
- **Satellite Clock Corrections:**
  - Offers high-accuracy clock corrections, improving timing accuracy across systems
- **Earth Rotation Parameters (ERP):**
  - Supports high-precision geospatial applications by modeling Earth's rotational variations
- **Ionospheric and Tropospheric Data:**

Key IGS Products

Applications in Navigation and PNT Systems

- **Precise GNSS Satellite Orbits:**
  - Provides satellite position data with centimeter-level accuracy
- **Satellite Clock Corrections:**
  - Offers high-accuracy clock corrections, improving timing accuracy across systems
- **Earth Rotation Parameters (ERP):**
  - Supports high-precision geospatial applications by modeling Earth's rotational variations
- **Ionospheric and Tropospheric Data:**
  - Models atmospheric effects on GNSS signals, enabling better correction and positioning accuracy

Key IGS Products

Applications in Navigation and PNT Systems

- **Precise GNSS Satellite Orbits:**
  - Provides satellite position data with centimeter-level accuracy
- **Satellite Clock Corrections:**
  - Offers high-accuracy clock corrections, improving timing accuracy across systems
- **Earth Rotation Parameters (ERP):**
  - Supports high-precision geospatial applications by modeling Earth's rotational variations
- **Ionospheric and Tropospheric Data:**
  - Models atmospheric effects on GNSS signals, enabling better correction and positioning accuracy

IGS Real-Time Satellite and Clock Corrections

IGS Real-Time Service (RTS)

IGS Real-Time Satellite and Clock Corrections

IGS Real-Time Service (RTS)

- **Real-Time Service (RTS):**

IGS Real-Time Satellite and Clock Corrections

IGS Real-Time Service (RTS)

- **Real-Time Service (RTS):**
  - Provides real-time GPS satellite orbit and clock correction parameters

IGS Real-Time Satellite and Clock Corrections

IGS Real-Time Service (RTS)

- **Real-Time Service (RTS):**
  - Provides real-time GPS satellite orbit and clock correction parameters
  - Distributed via RTCM State Space Representation (SSR) correction streams

IGS Real-Time Satellite and Clock Corrections

IGS Real-Time Service (RTS)

- **Real-Time Service (RTS):**
  - Provides real-time GPS satellite orbit and clock correction parameters
  - Distributed via RTCM State Space Representation (SSR) correction streams
- **Supports Multi-Constellation GNSS:**

IGS Real-Time Satellite and Clock Corrections

IGS Real-Time Service (RTS)

- **Real-Time Service (RTS):**
  - Provides real-time GPS satellite orbit and clock correction parameters
  - Distributed via RTCM State Space Representation (SSR) correction streams
- **Supports Multi-Constellation GNSS:**
  - Currently includes GPS and GLONASS, with plans for additional GNSS constellations

IGS Real-Time Satellite and Clock Corrections

IGS Real-Time Service (RTS)

- **Real-Time Service (RTS):**
  - Provides real-time GPS satellite orbit and clock correction parameters
  - Distributed via RTCM State Space Representation (SSR) correction streams
- **Supports Multi-Constellation GNSS:**
  - Currently includes GPS and GLONASS, with plans for additional GNSS constellations
- **Applications:**

IGS Real-Time Satellite and Clock Corrections

IGS Real-Time Service (RTS)

- **Real-Time Service (RTS):**
  - Provides real-time GPS satellite orbit and clock correction parameters
  - Distributed via RTCM State Space Representation (SSR) correction streams
- **Supports Multi-Constellation GNSS:**
  - Currently includes GPS and GLONASS, with plans for additional GNSS constellations
- **Applications:**
  - Enables real-time Precise Point Positioning (PPP) for high-accuracy positioning

IGS Real-Time Satellite and Clock Corrections

IGS Real-Time Service (RTS)

- **Real-Time Service (RTS):**
  - Provides real-time GPS satellite orbit and clock correction parameters
  - Distributed via RTCM State Space Representation (SSR) correction streams
- **Supports Multi-Constellation GNSS:**
  - Currently includes GPS and GLONASS, with plans for additional GNSS constellations
- **Applications:**
  - Enables real-time Precise Point Positioning (PPP) for high-accuracy positioning
  - Supports scientific, educational, and commercial applications needing real-time corrections

IGS Real-Time Satellite and Clock Corrections

IGS Real-Time Service (RTS)

- **Real-Time Service (RTS):**
  - Provides real-time GPS satellite orbit and clock correction parameters
  - Distributed via RTCM State Space Representation (SSR) correction streams
- **Supports Multi-Constellation GNSS:**
  - Currently includes GPS and GLONASS, with plans for additional GNSS constellations
- **Applications:**
  - Enables real-time Precise Point Positioning (PPP) for high-accuracy positioning
  - Supports scientific, educational, and commercial applications needing real-time corrections
- **Access via NTRIP:**

IGS Real-Time Satellite and Clock Corrections

IGS Real-Time Service (RTS)

- **Real-Time Service (RTS):**
  - Provides real-time GPS satellite orbit and clock correction parameters
  - Distributed via RTCM State Space Representation (SSR) correction streams
- **Supports Multi-Constellation GNSS:**
  - Currently includes GPS and GLONASS, with plans for additional GNSS constellations
- **Applications:**
  - Enables real-time Precise Point Positioning (PPP) for high-accuracy positioning
  - Supports scientific, educational, and commercial applications needing real-time corrections
- **Access via NTRIP:**
  - Data is accessible globally through IGS NTRIP broadcasters, facilitating real-time use

IGS Real-Time Satellite and Clock Corrections

IGS Real-Time Service (RTS)

- **Real-Time Service (RTS):**
  - Provides real-time GPS satellite orbit and clock correction parameters
  - Distributed via RTCM State Space Representation (SSR) correction streams
- **Supports Multi-Constellation GNSS:**
  - Currently includes GPS and GLONASS, with plans for additional GNSS constellations
- **Applications:**
  - Enables real-time Precise Point Positioning (PPP) for high-accuracy positioning
  - Supports scientific, educational, and commercial applications needing real-time corrections
- **Access via NTRIP:**
  - Data is accessible globally through IGS NTRIP broadcasters, facilitating real-time use

Bounding Gyro Errors with IGS Products

Role of IGS in GPS-Denied Scenarios

Bounding Gyro Errors with IGS Products

Role of IGS in GPS-Denied Scenarios

- **Multi-Constellation GNSS Data:**

Bounding Gyro Errors with IGS Products

Role of IGS in GPS-Denied Scenarios

- **Multi-Constellation GNSS Data:**
  - IGS provides real-time GNSS data from systems like GLONASS and Galileo, which can supplement GPS-denied times

Bounding Gyro Errors with IGS Products

Role of IGS in GPS-Denied Scenarios

- **Multi-Constellation GNSS Data:**
  - IGS provides real-time GNSS data from systems like GLONASS and Galileo, which can supplement GPS-denied times
- **Leveraging Precise Clock Corrections:**

Bounding Gyro Errors with IGS Products

Role of IGS in GPS-Denied Scenarios

- **Multi-Constellation GNSS Data:**
  - IGS provides real-time GNSS data from systems like GLONASS and Galileo, which can supplement GPS-denied times
- **Leveraging Precise Clock Corrections:**
  - Accurate timing corrections from IGS improve clock drift estimates, supporting INS and gyro-based dead reckoning

Bounding Gyro Errors with IGS Products

Role of IGS in GPS-Denied Scenarios

- **Multi-Constellation GNSS Data:**
  - IGS provides real-time GNSS data from systems like GLONASS and Galileo, which can supplement GPS-denied times
- **Leveraging Precise Clock Corrections:**
  - Accurate timing corrections from IGS improve clock drift estimates, supporting INS and gyro-based dead reckoning
- **Ionospheric Models for Error Mitigation:**

Bounding Gyro Errors with IGS Products

Role of IGS in GPS-Denied Scenarios

- **Multi-Constellation GNSS Data:**
  - IGS provides real-time GNSS data from systems like GLONASS and Galileo, which can supplement GPS-denied times
- **Leveraging Precise Clock Corrections:**
  - Accurate timing corrections from IGS improve clock drift estimates, supporting INS and gyro-based dead reckoning
- **Ionospheric Models for Error Mitigation:**
  - IGS's atmospheric data can be used to refine position estimates, reducing gyro error propagation

Bounding Gyro Errors with IGS Products

Role of IGS in GPS-Denied Scenarios

- **Multi-Constellation GNSS Data:**
  - IGS provides real-time GNSS data from systems like GLONASS and Galileo, which can supplement GPS-denied times
- **Leveraging Precise Clock Corrections:**
  - Accurate timing corrections from IGS improve clock drift estimates, supporting INS and gyro-based dead reckoning
- **Ionospheric Models for Error Mitigation:**
  - IGS's atmospheric data can be used to refine position estimates, reducing gyro error propagation
- **Earth Rotation Parameters (ERP):**

Bounding Gyro Errors with IGS Products

Role of IGS in GPS-Denied Scenarios

- **Multi-Constellation GNSS Data:**
  - IGS provides real-time GNSS data from systems like GLONASS and Galileo, which can supplement GPS-denied times
- **Leveraging Precise Clock Corrections:**
  - Accurate timing corrections from IGS improve clock drift estimates, supporting INS and gyro-based dead reckoning
- **Ionospheric Models for Error Mitigation:**
  - IGS's atmospheric data can be used to refine position estimates, reducing gyro error propagation
- **Earth Rotation Parameters (ERP):**
  - ERPs help maintain geodetic accuracy, which stabilizes navigation in the absence of direct GNSS signals

Bounding Gyro Errors with IGS Products

Role of IGS in GPS-Denied Scenarios

- **Multi-Constellation GNSS Data:**
  - IGS provides real-time GNSS data from systems like GLONASS and Galileo, which can supplement GPS-denied times
- **Leveraging Precise Clock Corrections:**
  - Accurate timing corrections from IGS improve clock drift estimates, supporting INS and gyro-based dead reckoning
- **Ionospheric Models for Error Mitigation:**
  - IGS's atmospheric data can be used to refine position estimates, reducing gyro error propagation
- **Earth Rotation Parameters (ERP):**
  - ERPs help maintain geodetic accuracy, which stabilizes navigation in the absence of direct GNSS signals

Benefits of IGS in Resilient PNT

Enhancing PNT Robustness with IGS Data

Benefits of IGS in Resilient PNT

Enhancing PNT Robustness with IGS Data

- **Increased Redundancy through Multi-GNSS Data:**

Benefits of IGS in Resilient PNT

Enhancing PNT Robustness with IGS Data

- **Increased Redundancy through Multi-GNSS Data:**
  - Enables fallback to alternative GNSS systems (e.g., GLONASS, Galileo), maintaining PNT resilience

Benefits of IGS in Resilient PNT

Enhancing PNT Robustness with IGS Data

- **Increased Redundancy through Multi-GNSS Data:**
  - Enables fallback to alternative GNSS systems (e.g., GLONASS, Galileo), maintaining PNT resilience
- **Reduced Dependence on Single GNSS System:**

Benefits of IGS in Resilient PNT

Enhancing PNT Robustness with IGS Data

- **Increased Redundancy through Multi-GNSS Data:**
  - Enables fallback to alternative GNSS systems (e.g., GLONASS, Galileo), maintaining PNT resilience
- **Reduced Dependence on Single GNSS System:**
  - IGS provides products compatible with multiple constellations, lowering the impact of GPS outages

Benefits of IGS in Resilient PNT

Enhancing PNT Robustness with IGS Data

- **Increased Redundancy through Multi-GNSS Data:**
  - Enables fallback to alternative GNSS systems (e.g., GLONASS, Galileo), maintaining PNT resilience
- **Reduced Dependence on Single GNSS System:**
  - IGS provides products compatible with multiple constellations, lowering the impact of GPS outages
- **Supports Continuous Navigation:**

Benefits of IGS in Resilient PNT

Enhancing PNT Robustness with IGS Data

- **Increased Redundancy through Multi-GNSS Data:**
  - Enables fallback to alternative GNSS systems (e.g., GLONASS, Galileo), maintaining PNT resilience
- **Reduced Dependence on Single GNSS System:**
  - IGS provides products compatible with multiple constellations, lowering the impact of GPS outages
- **Supports Continuous Navigation:**
  - By integrating IGS products, INS and gyro systems maintain bounded errors and reliable navigation

Benefits of IGS in Resilient PNT

Enhancing PNT Robustness with IGS Data

- **Increased Redundancy through Multi-GNSS Data:**
  - Enables fallback to alternative GNSS systems (e.g., GLONASS, Galileo), maintaining PNT resilience
- **Reduced Dependence on Single GNSS System:**
  - IGS provides products compatible with multiple constellations, lowering the impact of GPS outages
- **Supports Continuous Navigation:**
  - By integrating IGS products, INS and gyro systems maintain bounded errors and reliable navigation

Navigation Aids for Aircraft in GPS-Denied Environments

Assisting INS/ Kalman Filter Systems

Navigation Aids for Aircraft in GPS-Denied Environments

Assisting INS/ Kalman Filter Systems

- **Inertial Navigation System (INS):**

Navigation Aids for Aircraft in GPS-Denied Environments

Assisting INS/ Kalman Filter Systems

- **Inertial Navigation System (INS):**
  - Primary source when GPS is denied, but accuracy degrades over time

Navigation Aids for Aircraft in GPS-Denied Environments

Assisting INS/ Kalman Filter Systems

- **Inertial Navigation System (INS):**
  - Primary source when GPS is denied, but accuracy degrades over time
  - External measurement sources help to bound INS errors

Navigation Aids for Aircraft in GPS-Denied Environments

Assisting INS/ Kalman Filter Systems

- **Inertial Navigation System (INS):**
  - Primary source when GPS is denied, but accuracy degrades over time
  - External measurement sources help to bound INS errors
- **Ground-Based Navigation Aids:**

Navigation Aids for Aircraft in GPS-Denied Environments

Assisting INS/ Kalman Filter Systems

- **Inertial Navigation System (INS):**
  - Primary source when GPS is denied, but accuracy degrades over time
  - External measurement sources help to bound INS errors
- **Ground-Based Navigation Aids:**
  - **VOR (Very High Frequency Omnidirectional Range):** Provides azimuth or bearing information

Navigation Aids for Aircraft in GPS-Denied Environments

Assisting INS/ Kalman Filter Systems

- **Inertial Navigation System (INS):**
  - Primary source when GPS is denied, but accuracy degrades over time
  - External measurement sources help to bound INS errors
- **Ground-Based Navigation Aids:**
  - **VOR (Very High Frequency Omnidirectional Range):** Provides azimuth or bearing information
  - **DME (Distance Measuring Equipment):** Measures slant range for triangulation when combined with VOR

Navigation Aids for Aircraft in GPS-Denied Environments

Assisting INS/ Kalman Filter Systems

- **Inertial Navigation System (INS):**
  - Primary source when GPS is denied, but accuracy degrades over time
  - External measurement sources help to bound INS errors
- **Ground-Based Navigation Aids:**
  - **VOR (Very High Frequency Omnidirectional Range):** Provides azimuth or bearing information
  - **DME (Distance Measuring Equipment):** Measures slant range for triangulation when combined with VOR
  - **TACAN (Tactical Air Navigation):** Combines azimuth and distance, offering precise positioning for military aircraft

Navigation Aids for Aircraft in GPS-Denied Environments

Assisting INS/ Kalman Filter Systems

- **Inertial Navigation System (INS):**
  - Primary source when GPS is denied, but accuracy degrades over time
  - External measurement sources help to bound INS errors
- **Ground-Based Navigation Aids:**
  - **VOR (Very High Frequency Omnidirectional Range):** Provides azimuth or bearing information
  - **DME (Distance Measuring Equipment):** Measures slant range for triangulation when combined with VOR
  - **TACAN (Tactical Air Navigation):** Combines azimuth and distance, offering precise positioning for military aircraft

Additional Ground-Based and Radar-Based Aids

Supporting Position and Bearing Data

Additional Ground-Based and Radar-Based Aids

Supporting Position and Bearing Data

- **Automatic Direction Finder (ADF):**

Additional Ground-Based and Radar-Based Aids

Supporting Position and Bearing Data

- **Automatic Direction Finder (ADF):**
  - Uses Non-Directional Beacons (NDBs) for bearing; a backup to VOR/DME

Additional Ground-Based and Radar-Based Aids

Supporting Position and Bearing Data

- **Automatic Direction Finder (ADF):**
  - Uses Non-Directional Beacons (NDBs) for bearing; a backup to VOR/DME
- **Radar-Based Systems:**

Additional Ground-Based and Radar-Based Aids

Supporting Position and Bearing Data

- **Automatic Direction Finder (ADF):**
  - Uses Non-Directional Beacons (NDBs) for bearing; a backup to VOR/DME
- **Radar-Based Systems:**
  - **Secondary Surveillance Radar (SSR):** Provides range and bearing within controlled airspace

Additional Ground-Based and Radar-Based Aids

Supporting Position and Bearing Data

- **Automatic Direction Finder (ADF):**
  - Uses Non-Directional Beacons (NDBs) for bearing; a backup to VOR/DME
- **Radar-Based Systems:**
  - **Secondary Surveillance Radar (SSR):** Provides range and bearing within controlled airspace
  - **Multilateration (MLAT):** Uses transponder signal timing for precise position triangulation

Additional Ground-Based and Radar-Based Aids

Supporting Position and Bearing Data

- **Automatic Direction Finder (ADF):**
  - Uses Non-Directional Beacons (NDBs) for bearing; a backup to VOR/DME
- **Radar-Based Systems:**
  - **Secondary Surveillance Radar (SSR):** Provides range and bearing within controlled airspace
  - **Multilateration (MLAT):** Uses transponder signal timing for precise position triangulation
  - **Weather Radar:** Assists in dead reckoning using terrain and storm positioning

Additional Ground-Based and Radar-Based Aids

Supporting Position and Bearing Data

- **Automatic Direction Finder (ADF):**
  - Uses Non-Directional Beacons (NDBs) for bearing; a backup to VOR/DME
- **Radar-Based Systems:**
  - **Secondary Surveillance Radar (SSR):** Provides range and bearing within controlled airspace
  - **Multilateration (MLAT):** Uses transponder signal timing for precise position triangulation
  - **Weather Radar:** Assists in dead reckoning using terrain and storm positioning

Alternative Satellite and Sensor-Based Navigation Aids

Augmenting INS Accuracy

Alternative Satellite and Sensor-Based Navigation Aids

Augmenting INS Accuracy

- **Alternative Satellite Constellations:**

Alternative Satellite and Sensor-Based Navigation Aids

Augmenting INS Accuracy

- **Alternative Satellite Constellations:**
  - Multi-GNSS systems (e.g., GLONASS, Galileo) act as backups when GPS is unavailable

Alternative Satellite and Sensor-Based Navigation Aids

Augmenting INS Accuracy

- **Alternative Satellite Constellations:**
  - Multi-GNSS systems (e.g., GLONASS, Galileo) act as backups when GPS is unavailable
- **Onboard Vision and Sensor Systems:**

Alternative Satellite and Sensor-Based Navigation Aids

Augmenting INS Accuracy

- **Alternative Satellite Constellations:**
  - Multi-GNSS systems (e.g., GLONASS, Galileo) act as backups when GPS is unavailable
- **Onboard Vision and Sensor Systems:**
  - **Terrain-Referenced Navigation (TRN):** Matches terrain features with maps

Alternative Satellite and Sensor-Based Navigation Aids

Augmenting INS Accuracy

- **Alternative Satellite Constellations:**
  - Multi-GNSS systems (e.g., GLONASS, Galileo) act as backups when GPS is unavailable
- **Onboard Vision and Sensor Systems:**
  - **Terrain-Referenced Navigation (TRN):** Matches terrain features with maps
  - **Camera-Based Navigation:** Uses visual cues for position estimation (e.g., visual odometry)

Alternative Satellite and Sensor-Based Navigation Aids

Augmenting INS Accuracy

- **Alternative Satellite Constellations:**
  - Multi-GNSS systems (e.g., GLONASS, Galileo) act as backups when GPS is unavailable
- **Onboard Vision and Sensor Systems:**
  - **Terrain-Referenced Navigation (TRN):** Matches terrain features with maps
  - **Camera-Based Navigation:** Uses visual cues for position estimation (e.g., visual odometry)
  - **Air Data Systems:** Provides wind and airspeed data for dead reckoning

Alternative Satellite and Sensor-Based Navigation Aids

Augmenting INS Accuracy

- **Alternative Satellite Constellations:**
  - Multi-GNSS systems (e.g., GLONASS, Galileo) act as backups when GPS is unavailable
- **Onboard Vision and Sensor Systems:**
  - **Terrain-Referenced Navigation (TRN):** Matches terrain features with maps
  - **Camera-Based Navigation:** Uses visual cues for position estimation (e.g., visual odometry)
  - **Air Data Systems:** Provides wind and airspeed data for dead reckoning

Terrain-Referenced Navigation (TRN)

Overview

Terrain-Referenced Navigation (TRN)

Overview

- **What is TRN?**

Terrain-Referenced Navigation (TRN)

Overview

- **What is TRN?**
  - A navigation technique that uses terrain features to estimate position by matching observed data with known maps

Terrain-Referenced Navigation (TRN)

Overview

- **What is TRN?**
  - A navigation technique that uses terrain features to estimate position by matching observed data with known maps
- **Primary Application:**

Terrain-Referenced Navigation (TRN)

Overview

- **What is TRN?**
  - A navigation technique that uses terrain features to estimate position by matching observed data with known maps
- **Primary Application:**
  - Used in GPS-denied situations to provide navigation data in various terrains (e.g., mountains, valleys, coastlines)

Terrain-Referenced Navigation (TRN)

Overview

- **What is TRN?**
  - A navigation technique that uses terrain features to estimate position by matching observed data with known maps
- **Primary Application:**
  - Used in GPS-denied situations to provide navigation data in various terrains (e.g., mountains, valleys, coastlines)
- **Common Use Cases:**

Terrain-Referenced Navigation (TRN)

Overview

- **What is TRN?**
  - A navigation technique that uses terrain features to estimate position by matching observed data with known maps
- **Primary Application:**
  - Used in GPS-denied situations to provide navigation data in various terrains (e.g., mountains, valleys, coastlines)
- **Common Use Cases:**
  - Military aircraft and submarines for navigation in hostile or GPS-denied areas

Terrain-Referenced Navigation (TRN)

Overview

- **What is TRN?**
  - A navigation technique that uses terrain features to estimate position by matching observed data with known maps
- **Primary Application:**
  - Used in GPS-denied situations to provide navigation data in various terrains (e.g., mountains, valleys, coastlines)
- **Common Use Cases:**
  - Military aircraft and submarines for navigation in hostile or GPS-denied areas
  - Autonomous vehicles for precise navigation over land

Terrain-Referenced Navigation (TRN)

Overview

- **What is TRN?**
  - A navigation technique that uses terrain features to estimate position by matching observed data with known maps
- **Primary Application:**
  - Used in GPS-denied situations to provide navigation data in various terrains (e.g., mountains, valleys, coastlines)
- **Common Use Cases:**
  - Military aircraft and submarines for navigation in hostile or GPS-denied areas
  - Autonomous vehicles for precise navigation over land

How TRN Works

Matching Terrain Features to Maps

How TRN Works

Matching Terrain Features to Maps

- **Step 1: Data Collection**

How TRN Works

Matching Terrain Features to Maps

- **Step 1: Data Collection**
  - Onboard sensors (e.g., radar, LiDAR, or sonar) collect data on terrain features below the vehicle

How TRN Works

Matching Terrain Features to Maps

- **Step 1: Data Collection**
  - Onboard sensors (e.g., radar, LiDAR, or sonar) collect data on terrain features below the vehicle
- **Step 2: Terrain Matching**

How TRN Works

Matching Terrain Features to Maps

- **Step 1: Data Collection**
  - Onboard sensors (e.g., radar, LiDAR, or sonar) collect data on terrain features below the vehicle
- **Step 2: Terrain Matching**
  - The collected data is matched to a stored digital elevation model (DEM) of the terrain

How TRN Works

Matching Terrain Features to Maps

- **Step 1: Data Collection**
  - Onboard sensors (e.g., radar, LiDAR, or sonar) collect data on terrain features below the vehicle
- **Step 2: Terrain Matching**
  - The collected data is matched to a stored digital elevation model (DEM) of the terrain
  - Algorithms compare observed terrain patterns with the DEM to estimate location

How TRN Works

Matching Terrain Features to Maps

- **Step 1: Data Collection**
  - Onboard sensors (e.g., radar, LiDAR, or sonar) collect data on terrain features below the vehicle
- **Step 2: Terrain Matching**
  - The collected data is matched to a stored digital elevation model (DEM) of the terrain
  - Algorithms compare observed terrain patterns with the DEM to estimate location
- **Step 3: Position Update**

How TRN Works

Matching Terrain Features to Maps

- **Step 1: Data Collection**
  - Onboard sensors (e.g., radar, LiDAR, or sonar) collect data on terrain features below the vehicle
- **Step 2: Terrain Matching**
  - The collected data is matched to a stored digital elevation model (DEM) of the terrain
  - Algorithms compare observed terrain patterns with the DEM to estimate location
- **Step 3: Position Update**
  - Position estimate is continuously updated as the vehicle moves, using successive matches to terrain

How TRN Works

Matching Terrain Features to Maps

- **Step 1: Data Collection**
  - Onboard sensors (e.g., radar, LiDAR, or sonar) collect data on terrain features below the vehicle
- **Step 2: Terrain Matching**
  - The collected data is matched to a stored digital elevation model (DEM) of the terrain
  - Algorithms compare observed terrain patterns with the DEM to estimate location
- **Step 3: Position Update**
  - Position estimate is continuously updated as the vehicle moves, using successive matches to terrain

TRN Sensors and Data Sources

Onboard Sensors for Data Collection

TRN Sensors and Data Sources

Onboard Sensors for Data Collection

- **Radar Altimeters:**

TRN Sensors and Data Sources

Onboard Sensors for Data Collection

- **Radar Altimeters:**
  - Measures distance to the ground, commonly used on aircraft for altitude and terrain mapping

TRN Sensors and Data Sources

Onboard Sensors for Data Collection

- **Radar Altimeters:**
  - Measures distance to the ground, commonly used on aircraft for altitude and terrain mapping
- **LiDAR (Light Detection and Ranging):**

TRN Sensors and Data Sources

Onboard Sensors for Data Collection

- **Radar Altimeters:**
  - Measures distance to the ground, commonly used on aircraft for altitude and terrain mapping
- **LiDAR (Light Detection and Ranging):**
  - Uses laser pulses to create detailed terrain profiles; effective for both land and low-altitude applications

TRN Sensors and Data Sources

Onboard Sensors for Data Collection

- **Radar Altimeters:**
  - Measures distance to the ground, commonly used on aircraft for altitude and terrain mapping
- **LiDAR (Light Detection and Ranging):**
  - Uses laser pulses to create detailed terrain profiles; effective for both land and low-altitude applications
- **Sonar (Sound Navigation and Ranging):**

TRN Sensors and Data Sources

Onboard Sensors for Data Collection

- **Radar Altimeters:**
  - Measures distance to the ground, commonly used on aircraft for altitude and terrain mapping
- **LiDAR (Light Detection and Ranging):**
  - Uses laser pulses to create detailed terrain profiles; effective for both land and low-altitude applications
- **Sonar (Sound Navigation and Ranging):**
  - Used primarily by submarines to map the seafloor or underwater terrain

TRN Sensors and Data Sources

Onboard Sensors for Data Collection

- **Radar Altimeters:**
  - Measures distance to the ground, commonly used on aircraft for altitude and terrain mapping
- **LiDAR (Light Detection and Ranging):**
  - Uses laser pulses to create detailed terrain profiles; effective for both land and low-altitude applications
- **Sonar (Sound Navigation and Ranging):**
  - Used primarily by submarines to map the seafloor or underwater terrain

TRN Accuracy and Error Bounds

Factors Influencing Accuracy

TRN Accuracy and Error Bounds

Factors Influencing Accuracy

- **Resolution of Digital Elevation Model (DEM):**

TRN Accuracy and Error Bounds

Factors Influencing Accuracy

- **Resolution of Digital Elevation Model (DEM):**
  - Higher resolution DEMs enable more accurate terrain matching and smaller error bounds

TRN Accuracy and Error Bounds

Factors Influencing Accuracy

- **Resolution of Digital Elevation Model (DEM):**
  - Higher resolution DEMs enable more accurate terrain matching and smaller error bounds
  - Typical accuracy with high-resolution DEMs can be within 10-20 meters in well-mapped areas

TRN Accuracy and Error Bounds

Factors Influencing Accuracy

- **Resolution of Digital Elevation Model (DEM):**
  - Higher resolution DEMs enable more accurate terrain matching and smaller error bounds
  - Typical accuracy with high-resolution DEMs can be within 10-20 meters in well-mapped areas
- **Terrain Variability:**

TRN Accuracy and Error Bounds

Factors Influencing Accuracy

- **Resolution of Digital Elevation Model (DEM):**
  - Higher resolution DEMs enable more accurate terrain matching and smaller error bounds
  - Typical accuracy with high-resolution DEMs can be within 10-20 meters in well-mapped areas
- **Terrain Variability:**
  - Accuracy is higher in areas with distinct terrain features (e.g., mountains, valleys)

TRN Accuracy and Error Bounds

Factors Influencing Accuracy

- **Resolution of Digital Elevation Model (DEM):**
  - Higher resolution DEMs enable more accurate terrain matching and smaller error bounds
  - Typical accuracy with high-resolution DEMs can be within 10-20 meters in well-mapped areas
- **Terrain Variability:**
  - Accuracy is higher in areas with distinct terrain features (e.g., mountains, valleys)
  - Flat or homogeneous terrain may lead to larger error bounds due to lack of unique features

TRN Accuracy and Error Bounds

Factors Influencing Accuracy

- **Resolution of Digital Elevation Model (DEM):**
  - Higher resolution DEMs enable more accurate terrain matching and smaller error bounds
  - Typical accuracy with high-resolution DEMs can be within 10-20 meters in well-mapped areas
- **Terrain Variability:**
  - Accuracy is higher in areas with distinct terrain features (e.g., mountains, valleys)
  - Flat or homogeneous terrain may lead to larger error bounds due to lack of unique features
- **Sensor Accuracy and Noise:**

TRN Accuracy and Error Bounds

Factors Influencing Accuracy

- **Resolution of Digital Elevation Model (DEM):**
  - Higher resolution DEMs enable more accurate terrain matching and smaller error bounds
  - Typical accuracy with high-resolution DEMs can be within 10-20 meters in well-mapped areas
- **Terrain Variability:**
  - Accuracy is higher in areas with distinct terrain features (e.g., mountains, valleys)
  - Flat or homogeneous terrain may lead to larger error bounds due to lack of unique features
- **Sensor Accuracy and Noise:**
  - Higher-quality sensors (e.g., LiDAR vs. radar) generally provide better terrain mapping accuracy

TRN Accuracy and Error Bounds

Factors Influencing Accuracy

- **Resolution of Digital Elevation Model (DEM):**
  - Higher resolution DEMs enable more accurate terrain matching and smaller error bounds
  - Typical accuracy with high-resolution DEMs can be within 10-20 meters in well-mapped areas
- **Terrain Variability:**
  - Accuracy is higher in areas with distinct terrain features (e.g., mountains, valleys)
  - Flat or homogeneous terrain may lead to larger error bounds due to lack of unique features
- **Sensor Accuracy and Noise:**
  - Higher-quality sensors (e.g., LiDAR vs. radar) generally provide better terrain mapping accuracy
  - Sensor noise can lead to mismatches with the DEM, increasing position error

TRN Accuracy and Error Bounds

Factors Influencing Accuracy

- **Resolution of Digital Elevation Model (DEM):**
  - Higher resolution DEMs enable more accurate terrain matching and smaller error bounds
  - Typical accuracy with high-resolution DEMs can be within 10-20 meters in well-mapped areas
- **Terrain Variability:**
  - Accuracy is higher in areas with distinct terrain features (e.g., mountains, valleys)
  - Flat or homogeneous terrain may lead to larger error bounds due to lack of unique features
- **Sensor Accuracy and Noise:**
  - Higher-quality sensors (e.g., LiDAR vs. radar) generally provide better terrain mapping accuracy
  - Sensor noise can lead to mismatches with the DEM, increasing position error

Limitations and Challenges of TRN

Considerations for Effective Use

Limitations and Challenges of TRN

Considerations for Effective Use

- **Dependence on DEM Quality and Availability:**

Limitations and Challenges of TRN

Considerations for Effective Use

- **Dependence on DEM Quality and Availability:**
  - High-resolution DEMs may not be available for all regions, reducing TRN effectiveness in those areas

Limitations and Challenges of TRN

Considerations for Effective Use

- **Dependence on DEM Quality and Availability:**
  - High-resolution DEMs may not be available for all regions, reducing TRN effectiveness in those areas
- **Environmental Constraints:**

Limitations and Challenges of TRN

Considerations for Effective Use

- **Dependence on DEM Quality and Availability:**
  - High-resolution DEMs may not be available for all regions, reducing TRN effectiveness in those areas
- **Environmental Constraints:**
  - Poor weather, low visibility, or extreme terrain (e.g., deserts) can impact sensor readings

Limitations and Challenges of TRN

Considerations for Effective Use

- **Dependence on DEM Quality and Availability:**
  - High-resolution DEMs may not be available for all regions, reducing TRN effectiveness in those areas
- **Environmental Constraints:**
  - Poor weather, low visibility, or extreme terrain (e.g., deserts) can impact sensor readings
- **Resource Requirements:**

Limitations and Challenges of TRN

Considerations for Effective Use

- **Dependence on DEM Quality and Availability:**
  - High-resolution DEMs may not be available for all regions, reducing TRN effectiveness in those areas
- **Environmental Constraints:**
  - Poor weather, low visibility, or extreme terrain (e.g., deserts) can impact sensor readings
- **Resource Requirements:**
  - High-performance computing resources needed for real-time terrain matching and updating

Limitations and Challenges of TRN

Considerations for Effective Use

- **Dependence on DEM Quality and Availability:**
  - High-resolution DEMs may not be available for all regions, reducing TRN effectiveness in those areas
- **Environmental Constraints:**
  - Poor weather, low visibility, or extreme terrain (e.g., deserts) can impact sensor readings
- **Resource Requirements:**
  - High-performance computing resources needed for real-time terrain matching and updating

Communication-Based Positioning and RTK

Additional Measurement Sources

Communication-Based Positioning and RTK

Additional Measurement Sources

- **Real-Time Kinematic (RTK) Corrections:**

Communication-Based Positioning and RTK

Additional Measurement Sources

- **Real-Time Kinematic (RTK) Corrections:**
  - Ground-based RTK stations provide high-precision correction data, useful with partial GNSS

Communication-Based Positioning and RTK

Additional Measurement Sources

- **Real-Time Kinematic (RTK) Corrections:**
  - Ground-based RTK stations provide high-precision correction data, useful with partial GNSS
- **Communication-Based Positioning:**

Communication-Based Positioning and RTK

Additional Measurement Sources

- **Real-Time Kinematic (RTK) Corrections:**
  - Ground-based RTK stations provide high-precision correction data, useful with partial GNSS
- **Communication-Based Positioning:**
  - **ADS-B In/Out:** Provides positional data from nearby aircraft, allowing relative positioning

Communication-Based Positioning and RTK

Additional Measurement Sources

- **Real-Time Kinematic (RTK) Corrections:**
  - Ground-based RTK stations provide high-precision correction data, useful with partial GNSS
- **Communication-Based Positioning:**
  - **ADS-B In/Out:** Provides positional data from nearby aircraft, allowing relative positioning
  - **Cellular Networks:** Can support triangulation at low altitudes (e.g., over populated areas)

Communication-Based Positioning and RTK

Additional Measurement Sources

- **Real-Time Kinematic (RTK) Corrections:**
  - Ground-based RTK stations provide high-precision correction data, useful with partial GNSS
- **Communication-Based Positioning:**
  - **ADS-B In/Out:** Provides positional data from nearby aircraft, allowing relative positioning
  - **Cellular Networks:** Can support triangulation at low altitudes (e.g., over populated areas)

Integration with INS/GPS Kalman Filter

Enhancing Accuracy in GPS-Denied Conditions

Integration with INS/GPS Kalman Filter

Enhancing Accuracy in GPS-Denied Conditions

- **Kalman Filter Integration:**

Integration with INS/GPS Kalman Filter

Enhancing Accuracy in GPS-Denied Conditions

- **Kalman Filter Integration:**
  - Each alternative navigation aid can provide updates to the Kalman filter

Integration with INS/GPS Kalman Filter

Enhancing Accuracy in GPS-Denied Conditions

- **Kalman Filter Integration:**
  - Each alternative navigation aid can provide updates to the Kalman filter
  - Measurement sources correct INS drift, helping maintain accurate estimates of position, velocity, and attitude

Integration with INS/GPS Kalman Filter

Enhancing Accuracy in GPS-Denied Conditions

- **Kalman Filter Integration:**
  - Each alternative navigation aid can provide updates to the Kalman filter
  - Measurement sources correct INS drift, helping maintain accurate estimates of position, velocity, and attitude
- **Resilience in GPS-Denied Environments:**

Integration with INS/GPS Kalman Filter

Enhancing Accuracy in GPS-Denied Conditions

- **Kalman Filter Integration:**
  - Each alternative navigation aid can provide updates to the Kalman filter
  - Measurement sources correct INS drift, helping maintain accurate estimates of position, velocity, and attitude
- **Resilience in GPS-Denied Environments:**
  - Kalman filter dynamically uses available sources to ensure reliable navigation until GPS is restored

Integration with INS/GPS Kalman Filter

Enhancing Accuracy in GPS-Denied Conditions

- **Kalman Filter Integration:**
  - Each alternative navigation aid can provide updates to the Kalman filter
  - Measurement sources correct INS drift, helping maintain accurate estimates of position, velocity, and attitude
- **Resilience in GPS-Denied Environments:**
  - Kalman filter dynamically uses available sources to ensure reliable navigation until GPS is restored

Backup: Budgetary Challenges in Achieving Assured PNT

Impact of Program Delays

Backup: Budgetary Challenges in Achieving Assured PNT

Impact of Program Delays

- **Delayed GPS OCX and MGUE Programs:**

Backup: Budgetary Challenges in Achieving Assured PNT

Impact of Program Delays

- **Delayed GPS OCX and MGUE Programs:**
  - **GPS OCX (Next Generation Operational Control System):**
    Critical for improved anti-jamming and anti-spoofing capabilities, but delayed deployment affects A-PNT timelines

Backup: Budgetary Challenges in Achieving Assured PNT

Impact of Program Delays

- **Delayed GPS OCX and MGUE Programs:**
  - **GPS OCX (Next Generation Operational Control System):**
    Critical for improved anti-jamming and anti-spoofing capabilities, but delayed deployment affects A-PNT timelines
  - **GPS MGUE (Military GPS User Equipment):**
    Essential for integrating M-Code, which is designed to enhance signal security; delays impact military readiness for secure PNT

Backup: Budgetary Challenges in Achieving Assured PNT

Impact of Program Delays

- **Delayed GPS OCX and MGUE Programs:**
  - **GPS OCX (Next Generation Operational Control System):**
    Critical for improved anti-jamming and anti-spoofing capabilities, but delayed deployment affects A-PNT timelines
  - **GPS MGUE (Military GPS User Equipment):**
    Essential for integrating M-Code, which is designed to enhance signal security; delays impact military readiness for secure PNT
- **Increased Costs Due to Extended Timelines:**

Backup: Budgetary Challenges in Achieving Assured PNT

Impact of Program Delays

- **Delayed GPS OCX and MGUE Programs:**
  - **GPS OCX (Next Generation Operational Control System):**
    Critical for improved anti-jamming and anti-spoofing capabilities, but delayed deployment affects A-PNT timelines
  - **GPS MGUE (Military GPS User Equipment):**
    Essential for integrating M-Code, which is designed to enhance signal security; delays impact military readiness for secure PNT
- **Increased Costs Due to Extended Timelines:**
  - Project delays require additional funding to maintain and upgrade legacy systems as a stopgap solution

Backup: Budgetary Challenges in Achieving Assured PNT

Impact of Program Delays

- **Delayed GPS OCX and MGUE Programs:**
  - **GPS OCX (Next Generation Operational Control System):**
    Critical for improved anti-jamming and anti-spoofing capabilities, but delayed deployment affects A-PNT timelines
  - **GPS MGUE (Military GPS User Equipment):**
    Essential for integrating M-Code, which is designed to enhance signal security; delays impact military readiness for secure PNT
- **Increased Costs Due to Extended Timelines:**
  - Project delays require additional funding to maintain and upgrade legacy systems as a stopgap solution
- **Dependency on Supplemental PNT Solutions:**

Backup: Budgetary Challenges in Achieving Assured PNT

Impact of Program Delays

- **Delayed GPS OCX and MGUE Programs:**
  - **GPS OCX (Next Generation Operational Control System):**
    Critical for improved anti-jamming and anti-spoofing capabilities, but delayed deployment affects A-PNT timelines
  - **GPS MGUE (Military GPS User Equipment):**
    Essential for integrating M-Code, which is designed to enhance signal security; delays impact military readiness for secure PNT
- **Increased Costs Due to Extended Timelines:**
  - Project delays require additional funding to maintain and upgrade legacy systems as a stopgap solution
- **Dependency on Supplemental PNT Solutions:**
  - Delays in OCX and MGUE push agencies to invest in alternative PNT solutions (e.g., terrestrial or LEO-based systems), increasing overall costs

Backup: Budgetary Challenges in Achieving Assured PNT

Impact of Program Delays

- **Delayed GPS OCX and MGUE Programs:**
  - **GPS OCX (Next Generation Operational Control System):**
    Critical for improved anti-jamming and anti-spoofing capabilities, but delayed deployment affects A-PNT timelines
  - **GPS MGUE (Military GPS User Equipment):**
    Essential for integrating M-Code, which is designed to enhance signal security; delays impact military readiness for secure PNT
- **Increased Costs Due to Extended Timelines:**
  - Project delays require additional funding to maintain and upgrade legacy systems as a stopgap solution
- **Dependency on Supplemental PNT Solutions:**
  - Delays in OCX and MGUE push agencies to invest in alternative PNT solutions (e.g., terrestrial or LEO-based systems), increasing overall costs

Additional Budgetary Considerations for A-PNT

Adapting to Delays and Rising Costs

Additional Budgetary Considerations for A-PNT

Adapting to Delays and Rising Costs

- **Balancing Investment in Legacy Systems and Modernization:**

Additional Budgetary Considerations for A-PNT

Adapting to Delays and Rising Costs

- **Balancing Investment in Legacy Systems and Modernization:**
  - Funding needed to sustain legacy GPS systems until OCX and MGUE are operational, adding to budget strain

Additional Budgetary Considerations for A-PNT

Adapting to Delays and Rising Costs

- **Balancing Investment in Legacy Systems and Modernization:**
  - Funding needed to sustain legacy GPS systems until OCX and MGUE are operational, adding to budget strain
  - Resources diverted to address immediate operational gaps rather than long-term A-PNT advancements

Additional Budgetary Considerations for A-PNT

Adapting to Delays and Rising Costs

- **Balancing Investment in Legacy Systems and Modernization:**
  - Funding needed to sustain legacy GPS systems until OCX and MGUE are operational, adding to budget strain
  - Resources diverted to address immediate operational gaps rather than long-term A-PNT advancements
- **Investment in Alternative A-PNT Technologies:**

Additional Budgetary Considerations for A-PNT

Adapting to Delays and Rising Costs

- **Balancing Investment in Legacy Systems and Modernization:**
  - Funding needed to sustain legacy GPS systems until OCX and MGUE are operational, adding to budget strain
  - Resources diverted to address immediate operational gaps rather than long-term A-PNT advancements
- **Investment in Alternative A-PNT Technologies:**
  - Increased allocation for non-GPS-dependent solutions (e.g., IMUs, precision timing, and LEO constellations) adds to the budget but enhances resilience

Additional Budgetary Considerations for A-PNT

Adapting to Delays and Rising Costs

- **Balancing Investment in Legacy Systems and Modernization:**
  - Funding needed to sustain legacy GPS systems until OCX and MGUE are operational, adding to budget strain
  - Resources diverted to address immediate operational gaps rather than long-term A-PNT advancements
- **Investment in Alternative A-PNT Technologies:**
  - Increased allocation for non-GPS-dependent solutions (e.g., IMUs, precision timing, and LEO constellations) adds to the budget but enhances resilience
- **Cost of Integrating New Technologies:**

Additional Budgetary Considerations for A-PNT

Adapting to Delays and Rising Costs

- **Balancing Investment in Legacy Systems and Modernization:**
  - Funding needed to sustain legacy GPS systems until OCX and MGUE are operational, adding to budget strain
  - Resources diverted to address immediate operational gaps rather than long-term A-PNT advancements
- **Investment in Alternative A-PNT Technologies:**
  - Increased allocation for non-GPS-dependent solutions (e.g., IMUs, precision timing, and LEO constellations) adds to the budget but enhances resilience
- **Cost of Integrating New Technologies:**
  - Integrating supplemental technologies with existing infrastructure can be complex and costly

Additional Budgetary Considerations for A-PNT

Adapting to Delays and Rising Costs

- **Balancing Investment in Legacy Systems and Modernization:**
  - Funding needed to sustain legacy GPS systems until OCX and MGUE are operational, adding to budget strain
  - Resources diverted to address immediate operational gaps rather than long-term A-PNT advancements
- **Investment in Alternative A-PNT Technologies:**
  - Increased allocation for non-GPS-dependent solutions (e.g., IMUs, precision timing, and LEO constellations) adds to the budget but enhances resilience
- **Cost of Integrating New Technologies:**
  - Integrating supplemental technologies with existing infrastructure can be complex and costly
  - Ensuring interoperability between legacy and new systems is resource-intensive

Additional Budgetary Considerations for A-PNT

Adapting to Delays and Rising Costs

- **Balancing Investment in Legacy Systems and Modernization:**
  - Funding needed to sustain legacy GPS systems until OCX and MGUE are operational, adding to budget strain
  - Resources diverted to address immediate operational gaps rather than long-term A-PNT advancements
- **Investment in Alternative A-PNT Technologies:**
  - Increased allocation for non-GPS-dependent solutions (e.g., IMUs, precision timing, and LEO constellations) adds to the budget but enhances resilience
- **Cost of Integrating New Technologies:**
  - Integrating supplemental technologies with existing infrastructure can be complex and costly
  - Ensuring interoperability between legacy and new systems is resource-intensive

State of the Art in Gyroscope Technology

Overview

State of the Art in Gyroscope Technology

Overview

- **Optical Gyroscopes**

State of the Art in Gyroscope Technology

Overview

- **Optical Gyroscopes**
  - Fiber-Optic Gyroscopes (FOGs)
    Achieve accuracy of 0.1 to 0.0001 degrees per hour

State of the Art in Gyroscope Technology

Overview

- **Optical Gyroscopes**
  - Fiber-Optic Gyroscopes (FOGs)
    Achieve accuracy of 0.1 to 0.0001 degrees per hour
  - Optical Resonator Gyroscopes (ORGs)
    Random drift values as low as 0.06 degrees per hour

State of the Art in Gyroscope Technology

Overview

- **Optical Gyroscopes**
  - Fiber-Optic Gyroscopes (FOGs)
    Achieve accuracy of 0.1 to 0.0001 degrees per hour
  - Optical Resonator Gyroscopes (ORGs)
    Random drift values as low as 0.06 degrees per hour
- **Micro-Electro-Mechanical Systems (MEMS) Gyroscopes**

State of the Art in Gyroscope Technology

Overview

- **Optical Gyroscopes**
  - Fiber-Optic Gyroscopes (FOGs)
    Achieve accuracy of 0.1 to 0.0001 degrees per hour
  - Optical Resonator Gyroscopes (ORGs)
    Random drift values as low as 0.06 degrees per hour
- **Micro-Electro-Mechanical Systems (MEMS) Gyroscopes**
  - Miniaturization advances enable high-precision navigation-grade applications

State of the Art in Gyroscope Technology

Overview

- **Optical Gyroscopes**
  - Fiber-Optic Gyroscopes (FOGs)
    Achieve accuracy of 0.1 to 0.0001 degrees per hour
  - Optical Resonator Gyroscopes (ORGs)
    Random drift values as low as 0.06 degrees per hour
- **Micro-Electro-Mechanical Systems (MEMS) Gyroscopes**
  - Miniaturization advances enable high-precision navigation-grade applications
- **Quantum Gyroscopes**

State of the Art in Gyroscope Technology

Overview

- **Optical Gyroscopes**
  - Fiber-Optic Gyroscopes (FOGs)
    Achieve accuracy of 0.1 to 0.0001 degrees per hour
  - Optical Resonator Gyroscopes (ORGs)
    Random drift values as low as 0.06 degrees per hour
- **Micro-Electro-Mechanical Systems (MEMS) Gyroscopes**
  - Miniaturization advances enable high-precision navigation-grade applications
- **Quantum Gyroscopes**
  - Using double-mode surface-acoustic-wave cavities to surpass standard quantum limits

State of the Art in Gyroscope Technology

Overview

- **Optical Gyroscopes**
  - Fiber-Optic Gyroscopes (FOGs)
    Achieve accuracy of 0.1 to 0.0001 degrees per hour
  - Optical Resonator Gyroscopes (ORGs)
    Random drift values as low as 0.06 degrees per hour
- **Micro-Electro-Mechanical Systems (MEMS) Gyroscopes**
  - Miniaturization advances enable high-precision navigation-grade applications
- **Quantum Gyroscopes**
  - Using double-mode surface-acoustic-wave cavities to surpass standard quantum limits
- **Applications**

  Expanding to medical, sensing, imaging, and critical navigation

State of the Art in Gyroscope Technology

Overview

- **Optical Gyroscopes**
  - Fiber-Optic Gyroscopes (FOGs)
    Achieve accuracy of 0.1 to 0.0001 degrees per hour
  - Optical Resonator Gyroscopes (ORGs)
    Random drift values as low as 0.06 degrees per hour
- **Micro-Electro-Mechanical Systems (MEMS) Gyroscopes**
  - Miniaturization advances enable high-precision navigation-grade applications
- **Quantum Gyroscopes**
  - Using double-mode surface-acoustic-wave cavities to surpass standard quantum limits
- **Applications**

  Expanding to medical, sensing, imaging, and critical navigation

Navigation-Grade Gyroscope Performance

Criteria

Navigation-Grade Gyroscope Performance

Criteria

- Bias Instability (Drift Rate)

Navigation-Grade Gyroscope Performance

Criteria

- Bias Instability (Drift Rate)
  - Drift rates around 0.01 to 1 degree per hour

Navigation-Grade Gyroscope Performance

Criteria

- Bias Instability (Drift Rate)
  - Drift rates around 0.01 to 1 degree per hour
- Scale Factor Accuracy

Navigation-Grade Gyroscope Performance

Criteria

- Bias Instability (Drift Rate)
  - Drift rates around 0.01 to 1 degree per hour
- Scale Factor Accuracy
  - Accuracy within 50 ppm

Navigation-Grade Gyroscope Performance

Criteria

- Bias Instability (Drift Rate)
  - Drift rates around 0.01 to 1 degree per hour
- Scale Factor Accuracy
  - Accuracy within 50 ppm
- Noise Performance (Angle Random Walk)

Navigation-Grade Gyroscope Performance

Criteria

- Bias Instability (Drift Rate)
  - Drift rates around 0.01 to 1 degree per hour
- Scale Factor Accuracy
  - Accuracy within 50 ppm
- Noise Performance (Angle Random Walk)
  - Below 0.01 degrees per $\sqrt{\text{hour}}$

Navigation-Grade Gyroscope Performance

Criteria

- Bias Instability (Drift Rate)
  - Drift rates around 0.01 to 1 degree per hour
- Scale Factor Accuracy
  - Accuracy within 50 ppm
- Noise Performance (Angle Random Walk)
  - Below 0.01 degrees per $\sqrt{\text{hour}}$
- Thermal Stability and Bandwidth

Navigation-Grade Gyroscope Performance

Criteria

- Bias Instability (Drift Rate)
  - Drift rates around 0.01 to 1 degree per hour
- Scale Factor Accuracy
  - Accuracy within 50 ppm
- Noise Performance (Angle Random Walk)
  - Below 0.01 degrees per $\sqrt{\text{hour}}$
- Thermal Stability and Bandwidth
  - Consistent performance under varying temperatures and dynamic changes

Navigation-Grade Gyroscope Performance

Criteria

- Bias Instability (Drift Rate)
  - Drift rates around 0.01 to 1 degree per hour
- Scale Factor Accuracy
  - Accuracy within 50 ppm
- Noise Performance (Angle Random Walk)
  - Below 0.01 degrees per $\sqrt{\text{hour}}$
- Thermal Stability and Bandwidth
  - Consistent performance under varying temperatures and dynamic changes

MEMS Gyroscopes with Navigation-Grade Performance

Examples

MEMS Gyroscopes with Navigation-Grade Performance

Examples

- **CEA-Leti's Nano-Resistive Sensing Gyroscope**

MEMS Gyroscopes with Navigation-Grade Performance

Examples

- **CEA-Leti's Nano-Resistive Sensing Gyroscope**
  - Bias instability of $0.02^\circ/\mathrm{h}$ and angular random walk (ARW) of $0.004^\circ/\sqrt{\mathrm{h}}$

MEMS Gyroscopes with Navigation-Grade Performance

Examples

- **CEA-Leti's Nano-Resistive Sensing Gyroscope**
  - Bias instability of $0.02^\circ/\mathrm{h}$ and angular random walk (ARW) of $0.004^\circ/\sqrt{\mathrm{h}}$
- **Safran's Si-MEMS Gyroscope**

MEMS Gyroscopes with Navigation-Grade Performance

Examples

- **CEA-Leti's Nano-Resistive Sensing Gyroscope**
  - Bias instability of $0.02°/\mathrm{h}$ and angular random walk (ARW) of $0.004°/\sqrt{\mathrm{h}}$
- **Safran's Si-MEMS Gyroscope**
  - High-precision with optimization for CSWAP requirements

MEMS Gyroscopes with Navigation-Grade Performance

Examples

- **CEA-Leti's Nano-Resistive Sensing Gyroscope**
  - Bias instability of $0.02^\circ/\mathrm{h}$ and angular random walk (ARW) of $0.004^\circ/\sqrt{\mathrm{h}}$
- **Safran's Si-MEMS Gyroscope**
  - High-precision with optimization for CSWAP requirements
- **EMCORE's Quartz MEMS IMU**

MEMS Gyroscopes with Navigation-Grade Performance

Examples

- **CEA-Leti's Nano-Resistive Sensing Gyroscope**
  - Bias instability of $0.02^\circ/\mathrm{h}$ and angular random walk (ARW) of $0.004^\circ/\sqrt{\mathrm{h}}$
- **Safran's Si-MEMS Gyroscope**
  - High-precision with optimization for CSWAP requirements
- **EMCORE's Quartz MEMS IMU**
  - Angle random walk ¡ $0.006^\circ/\sqrt{\mathrm{h}}$, bias stability of $0.2^\circ/\mathrm{h}$ over temperature

MEMS Gyroscopes with Navigation-Grade Performance

Examples

- **CEA-Leti's Nano-Resistive Sensing Gyroscope**
  - Bias instability of $0.02^\circ/\mathrm{h}$ and angular random walk (ARW) of $0.004^\circ/\sqrt{\mathrm{h}}$
- **Safran's Si-MEMS Gyroscope**
  - High-precision with optimization for CSWAP requirements
- **EMCORE's Quartz MEMS IMU**
  - Angle random walk ¡ $0.006^\circ/\sqrt{\mathrm{h}}$, bias stability of $0.2^\circ/\mathrm{h}$ over temperature

Precise Clocks in MEMS Gyro-CSWAP Systems

Importance without GPS

Precise Clocks in MEMS Gyro-CSWAP Systems

Importance without GPS

- **Reducing Drift Accumulation**

Precise Clocks in MEMS Gyro-CSWAP Systems

Importance without GPS

- **Reducing Drift Accumulation**
  - Synchronizes timing, reducing drift over time

Precise Clocks in MEMS Gyro-CSWAP Systems

Importance without GPS

- **Reducing Drift Accumulation**
  - Synchronizes timing, reducing drift over time
- **Improving Dead Reckoning Accuracy**

Precise Clocks in MEMS Gyro-CSWAP Systems

Importance without GPS

- **Reducing Drift Accumulation**
  - Synchronizes timing, reducing drift over time
- **Improving Dead Reckoning Accuracy**
  - Enables consistent time-stamping of measurements

Precise Clocks in MEMS Gyro-CSWAP Systems

Importance without GPS

- **Reducing Drift Accumulation**
  - Synchronizes timing, reducing drift over time
- **Improving Dead Reckoning Accuracy**
  - Enables consistent time-stamping of measurements
- **Supporting Sensor Fusion Algorithms**

Precise Clocks in MEMS Gyro-CSWAP Systems

Importance without GPS

- **Reducing Drift Accumulation**
  - Synchronizes timing, reducing drift over time
- **Improving Dead Reckoning Accuracy**
  - Enables consistent time-stamping of measurements
- **Supporting Sensor Fusion Algorithms**
  - Accurate timing of multi-sensor data, improving algorithm performance

Precise Clocks in MEMS Gyro-CSWAP Systems

Importance without GPS

- **Reducing Drift Accumulation**
  - Synchronizes timing, reducing drift over time
- **Improving Dead Reckoning Accuracy**
  - Enables consistent time-stamping of measurements
- **Supporting Sensor Fusion Algorithms**
  - Accurate timing of multi-sensor data, improving algorithm performance
- **Supporting Assisted Inertial Navigation Systems (AINS)**

Precise Clocks in MEMS Gyro-CSWAP Systems

Importance without GPS

- **Reducing Drift Accumulation**
  - Synchronizes timing, reducing drift over time
- **Improving Dead Reckoning Accuracy**
  - Enables consistent time-stamping of measurements
- **Supporting Sensor Fusion Algorithms**
  - Accurate timing of multi-sensor data, improving algorithm performance
- **Supporting Assisted Inertial Navigation Systems (AINS)**
  - Assists in periodic GPS syncing for extended stability

Precise Clocks in MEMS Gyro-CSWAP Systems

Importance without GPS

- **Reducing Drift Accumulation**
  - Synchronizes timing, reducing drift over time
- **Improving Dead Reckoning Accuracy**
  - Enables consistent time-stamping of measurements
- **Supporting Sensor Fusion Algorithms**
  - Accurate timing of multi-sensor data, improving algorithm performance
- **Supporting Assisted Inertial Navigation Systems (AINS)**
  - Assists in periodic GPS syncing for extended stability

About EMCORE Corporation

Overview and History

About EMCORE Corporation

Overview and History

- Founded in 1984

About EMCORE Corporation

Overview and History

- Founded in 1984
- Specializes in fiber optic, MEMS, and ring laser gyro technology

About EMCORE Corporation

Overview and History

- Founded in 1984
- Specializes in fiber optic, MEMS, and ring laser gyro technology
- Applications in aerospace, defense, and industrial markets

About EMCORE Corporation

Overview and History

- Founded in 1984
- Specializes in fiber optic, MEMS, and ring laser gyro technology
- Applications in aerospace, defense, and industrial markets

FEI-Zyfer and Assured PNT

Timing Solutions for PNT

FEI-Zyfer and Assured PNT

Timing Solutions for PNT

- **GPS-Disciplined Time and Frequency Systems**

FEI-Zyfer and Assured PNT

Timing Solutions for PNT

- **GPS-Disciplined Time and Frequency Systems**
  - M-Code and SAASM GPS receivers for secure applications

FEI-Zyfer and Assured PNT

Timing Solutions for PNT

- **GPS-Disciplined Time and Frequency Systems**
  - M-Code and SAASM GPS receivers for secure applications
- **High-Precision Oscillators**

FEI-Zyfer and Assured PNT

Timing Solutions for PNT

- **GPS-Disciplined Time and Frequency Systems**
  - M-Code and SAASM GPS receivers for secure applications
- **High-Precision Oscillators**
  - Uses Rubidium Atomic Clocks for precise timing

FEI-Zyfer and Assured PNT

Timing Solutions for PNT

- **GPS-Disciplined Time and Frequency Systems**
  - M-Code and SAASM GPS receivers for secure applications
- **High-Precision Oscillators**
  - Uses Rubidium Atomic Clocks for precise timing
- **Certified for Defense Applications**

FEI-Zyfer and Assured PNT

Timing Solutions for PNT

- **GPS-Disciplined Time and Frequency Systems**
  - M-Code and SAASM GPS receivers for secure applications
- **High-Precision Oscillators**
  - Uses Rubidium Atomic Clocks for precise timing
- **Certified for Defense Applications**
  - Approved Host Application Equipment integrator

FEI-Zyfer and Assured PNT

Timing Solutions for PNT

- **GPS-Disciplined Time and Frequency Systems**
  - M-Code and SAASM GPS receivers for secure applications
- **High-Precision Oscillators**
  - Uses Rubidium Atomic Clocks for precise timing
- **Certified for Defense Applications**
  - Approved Host Application Equipment integrator