

[CTP-201] [CCDB Counters versus raw ctp counters](#) Created: 11/Jun/25 Updated: 11/Jun/25

Status:	Open		
Project:	ALICE Central Trigger Processor		
Component/s:	None		
Affects Version/s:	None		
Fix Version/s:	None		
Type:	Task	Priority:	Minor
Reporter:	Roman Lietava	Assignee:	Jan Musinsky
Resolution:	Unresolved	Votes:	0
Labels:	None		
Remaining Estimate:	Not Specified		
Time Spent:	Not Specified		
Original Estimate:	Not Specified		
Change scope:	Manifest change		
Checklist:	EMPTY		

Description

CTP Counters

All ctp counters are dumped to one file per day on tigger@ctpctr (and in grafana).
Subset of all ctp counters relevant for lumi calculation is saved for every run in CCDB.
For introduction to class counters see:
[Counters1](#)
[Counters2](#)
Note that word scaler is synonym of counter.

Class counters have to satisfy 'causality conditions':

- scalers should never decrease
- LMB >= LMA >= LOB >= LOA >= L1B >= L1A: 5 relations
The consistencyCeck is implemented in code at:
[o2::ctp::Scalers.cxx consistency check](#)
Errors are suppressed by if (eCnts.lmB < eCnts.MAXPRINT) { ... }

Steps in project:

- read run scalers from CCDB , see example in [CCDB macro](#)
- put eCnts.MAXPRINT to zero and find run with errors
- **follow the run by analysing ctp raw counters using your custom independent code and find bug on o2 scalers or confirm incosnstency in ctp raw counters**