

## Data Collection and Preprocessing Phase

Date	31 January 2026
Student Name	Muskan Nisar Shaikh
Project Title	Uncovering the Hidden Treasures of the Mushroom Kingdom A Classification Analysis
Maximum Marks	6 Marks

### Data Preprocessing

The images will be preprocessed by resizing, normalizing, augmenting, denoising, adjusting contrast, detecting edges, converting color space, cropping, batch normalizing, and whitening data. These steps will enhance data quality, promote model generalization, and improve convergence during neural network training, ensuring robust and efficient performance across various computer vision tasks.

Section	Description
Data Overview	This project uses image datasets of three mushroom species: <b>Boletus</b> , <b>Lactarius</b> , and <b>Russula</b> . The images are collected from various sources including <b>SmartInternz</b> , <b>custom fieldcaptured images</b> , and platforms like <b>Kaggle</b> and <b>Wikimedia</b> . This ensures rich visual diversity and robust generalization during training.

Resizing	All images are resized to <b>224×224 pixels</b> using OpenCV's <code>cv2.resize()</code> function to ensure uniform input dimensions for CNN-based models.
Normalization	Pixel values are normalized to the range <b>[0, 1]</b> by dividing by 255.0, improving convergence during model training.
Data Augmentation	Using <code>ImageDataGenerator</code> , images are augmented with <b>random rotation, shifts, zoom, horizontal/vertical flips</b> , and <b>fill modes</b> to avoid overfitting.
Denoising	OpenCV's <code>fastNlMeansDenoisingColored()</code> is applied to reduce environmental noise and improve image clarity, especially for field-captured data.

Edge Detection	<code>cv2.Canny()</code> is used for edge detection, helping to emphasize structure, texture, and contour features of different mushroom species.
Color Space Conversion	Images are converted from <b>BGR to HSV</b> color space using <code>cv2.cvtColor()</code> to better capture color-based patterns across lighting variations.
Image Cropping	Manual center cropping is done on some images to focus on the mushroom body and reduce irrelevant background noise, enhancing object recognition.
Batch Normalization	<code>BatchNormalization()</code> is applied in the neural network model to stabilize and accelerate the learning process by reducing internal covariate shift.
<b>Data Preprocessing Code Screenshots</b>	

Loading Data	<pre> 1  import os 2  import cv2 3  import numpy as np 4  from tensorflow.keras.preprocessing.image import ImageDataGenerator 5 6  data_dir = "path/to/mushroom_dataset" 7  categories = ["Boletus", "Lactarius", "Russula"] 8 9  data = [] 10 IMG_SIZE = 224 11 12 for category in categories: 13     folder = os.path.join(data_dir, category) 14     label = categories.index(category) 15     for img_name in os.listdir(folder): 16         img_path = os.path.join(folder, img_name) 17         img = cv2.imread(img_path) 18         if img is not None: 19             img = cv2.resize(img, (IMG_SIZE, IMG_SIZE)) 20             data.append([img, label]) 21 </pre>
Resizing	<pre> img = cv2.resize(img, (224, 224)) </pre>
Normalization	<pre> data = np.array(data, dtype=object) X = np.array([i[0] for i in data]) / 255.0 # Normalize pixel values y = np.array([i[1] for i in data]) </pre>
Data Augmentation	<pre> train_datagen = ImageDataGenerator(     rotation_range=30,     width_shift_range=0.1,     height_shift_range=0.1,     zoom_range=0.2,     horizontal_flip=True,     vertical_flip=True,     fill_mode='nearest' ) </pre>

Denoising	<pre>denoised_img = cv2.fastNlMeansDenoisingColored(img, None, 10, 10, 7, 21)</pre>
Edge Detection	<pre>edges = cv2.Canny(img, threshold1=100, threshold2=200)</pre>
Color Space Conversion	<pre>hsv_img = cv2.cvtColor(img, cv2.COLOR_BGR2HSV)</pre>
Image Cropping	<pre>cropped_img = img[30:194, 30:194] # Manual center crop</pre>
Batch Normalization	<pre>from tensorflow.keras.layers import BatchNormalization model.add(BatchNormalization())</pre>