

638W Backhoe loader



技术规格 Technical specification

部件	项目		638W
Overall Dimension 总尺寸	总长（铲斗放置地面）	Length(with bucket on ground)	7600mm
	总宽（支腿处）	Overall width (at stabilizer)	2230mm
	整机总宽(轮胎外沿)	Overall width (At the edge of the tyre)	2338mm
	铲斗宽度	Load Bucket width	2490±10mm
	高度（到驾驶室顶）	Height(To the top of the cab)	3100mm
	整机高度(到挖掘臂顶部)	Height(To the top of the digging pole)	3453mm
	轴距	Wheel base	2280 mm
	后轮轮距	Back wheel Tread	1750 mm
	最小离地间隙	Min. Ground Clearance	300mm
Main Loading Technical Specificati on 装载主要 技术参数	额定载重量	Rated load	2500KG
	操作重量	Operating weight	7820kg
	额定斗容	Rated bucket capacity	1m³
	最大卸载高度	Max. dump clearance	2720 mm
	卸载距离	Dump reach	900 mm
	最大掘起力	Max. load breakout force	≥45KN
	铲挖深度	Digging Depth	52mm
	铲斗提升时间	Bucket Lifting Time	6.8s
	铲斗下降时间	Bucket Lowering Time	3.1s



	铲斗卸载时间	Bucket Discharge Time	2.0s
Main Digging Technical Specificati on 挖掘主要 技术参数	额定挖掘斗斗容	Rated digging bucket capacity	0.3m ³
	最大挖掘深度	Max. digging depth	4080 mm
	最大挖掘半径	Max. digging radius	5600 mm
	最大卸载高度	Max. dumping height	3795 mm
	最大挖掘力	Max. digging force	≥44KN
	最大挖掘高度	Max. Digging Height	5467 mm
	挖斗回转角	wing Angle of Excavator Grab	180°
	挖斗挖掘力	Digging Power of Excavator Grab	50KN
	斗杆挖掘力	Digging Power of Dipper	44KN
Diesel engine 发动 机	型号	Model	WP3.6NG101E680
	形式	Type	直列、直喷、四冲程、 涡轮增压, 电控高压共 轨 In Line Direct injection Four-Stroke, Turbocha rged
	额定功率	Rated output	74KW
	排放限值	Emission limits	Euro V
	气缸数-内径*行程	Cylinder-Inside Diameter*Stroke	6-100*114mm
	排气量	Total exhaust of cylinder	3.58L
	额定转速	Rated speed	2200r/min
	最大扭矩	Max. Torque	450N. M/1400-1600r/m
	最低燃油率	Min. Fuel Consumption	≤216g/km. h
Transmissio n case 变速 箱	型号	Model	CARRARO
	形式	Type	Synchromesh mechanical shift 同步 机械换挡
	档位	Gear shift position	4 F、 4 R 前四后四档位
	速度 (F/R)	Speed	36km/h
	最大牵引力	Max. drawing force	67KN
	额定桥载荷	Rated Loader of Axle	22.5T/18.75T
	主传动形式	Type of main reducer	spiral bevel gear, single stage 单级螺旋 伞齿轮
	轮边减速型式	Final Reducer	一级轮边减速 Single Stage Final Reducer
Size of tire 轮胎型号	前轮	Front wheel	14-17.5-16PR
	后轮	Back Wheel	19.5L-24-14PR
	前轮气压	Pressure of Front wheel	0.4 Mpa

	后轮气压	Pressure of Back Wheel	0.35 Mpa
转向系统 Steering System	转向器型号	Model of Steering Device	BZZ5-250
	系统压力	Pressure of the system	20Mpa
	转向角	v	±36°
	最小转弯半径(以铲斗边缘)	Min. turning radius (Outside of bucket)	5410mm
	最小转弯半径(以前轮胎痕迹中心)	Min. turning radius (Center of front wheel)	4100mm
The hydraulic system 液压系统	工作泵排量	Working pump discharge	63ml/r
	工作泵压力	Working pump pressure	20Mpa
Oil Capacity 加油量	燃油	Fuel (diesel)	130 L
	机油	Engine lubricating oil	11 L
	变速箱油	Oil for converter and gear box	22 L
	液压系统油	Oil for hydraulic system	110 L
	前后驱动桥油	Oil for driving axles (F/R)	7.6 L+17 L
制动系统 Brake System	行车制动	Service Brake	湿式, 内置式 Wet internal
			自调节 Self-regulation
			自平衡 Self-balance
	驻车/紧急制动	Emergency Brake	操纵力实施制动 Operation Power Implementing brake
			手操纵力解除制动 Manual Operation Power Terminating Brake