

08 06 70 - Hardware Schedule

Key Schedule

Use this area to list all keys provided on project referencing appropriate Sections. The Campus prefers to have one listing for all keys

Key Schedule for {project name} {building number}						
Purpose / Location	Room Number	Keys Required	Total Keys	Model Number	Manufacturer	Section Reference
Toilet Accessories		2/ each building restroom/ accessory keyed differently				10 28 00 Toilet, Bath, and Laundry Accessories
Equipment		2 each				Division 11 – Equipment sections
Furnishings		2 each				Division 12 – Furnishings sections
Elevators		3 keys, 1 installed in elevator pit.				14 20 00 – Elevators
Fire Control Cabinets		2/ each cabinet				21 00 00 – Fire Suppression
Fire Control Padlocks		2/ each Padlock (SFIC cores)				21 00 00 – Fire Suppression
Plumbing		2/ Each were applies				22 00 00 – Plumbing
Plumbing Padlocks		2/ each Padlock (SFIC cores)				22 00 00 – Plumbing
HVAC Equipment Panels		2/ each Panel				23 00 00 – HVAC
HVAC Yard, Doors and Equipment Padlocks		2/ each Padlock (SFIC cores)				23 00 00 – HVAC

Key Schedule for {project name} {building number}						
Purpose / Location	Room Number	Keys Required	Total Keys	Model Number	Manufacturer	Section Reference
Electrical Panels		2/ each panel				26 00 00 – Electrical
Emergency Generator Panels and Equipment		2/ each Padlock (SFIC cores)				26 00 00 – Electrical
Lighting Control Panels		2/ each Panel				26 00 00 – Electrical
Lighting Switches		2/ each switch				26 00 00 – Electrical
Electrical Yard, Equipment, & Switches Padlocks		2/ each Padlock (SFIC cores)				26 00 00 – Electrical
Communications Equipment		2/ each lock				27 00 00 - Communications
Emergency Telephones (Blue Light Phones)		2/ each				27 00 00 - Communications
Communications Equipment Padlocks		2/ each Padlock (SFIC cores)				27 00 00 - Communications
Electronic Safety and Security Panels		2/ each panel				28 00 00 – Electronic Safety and Security
Electronic Safety and Security Equipment Padlocks		2/ each Padlock (SFIC cores)				28 00 00 – Electronic Safety and Security
Irrigation Equipment		2/ each				32 80 00 – Irrigation
Utilities		2/ each				33 00 00 - Utilities

Closeout Submittal: Key Schedule – Provide hard copies and one electronic copy of completed Key Schedule along with keys separated and labeled.

08 11 13 - Hollow Metal Doors and Frames

Basis of Design:

1. Steelcraft

Three-piece knockdown frames shall not be permitted.

Option for knockdown frames shall be submitted to Cal Poly for review and approval,

Timely door frames are not preferred.

Steel Doors:

- Exterior: Full flush doors (ANSI A250.8-1998 (SDI-100)), 1-3/4 inches thick, galvanized steel (ASTM A653/A653M-07), 14 gage closer reinforcement top and bottom with snap-in top caps.
- Interior: Full flush doors (ANSI A250.8-1998 (SDI-100)), 1-3/4 inches thick, 14 gage closer reinforcement top and bottom.
- Hardware preparation and reinforcement: Prepare for commercial hardware (ANSI A250.6-1997) and mortised locks (ANSI A115.1), no face holes unless coordinated with hardware schedule. Factory reinforce for surface applied hardware – 14 gage for closer. Locations per ANSI/DHI A115.
- Preferred Manufacturer and Model: Steelcraft L16 Series

Steel Door Frames:

- Exterior: 16 gage welded door frames; A60 hot dipped galvanized steel.
- Flush Frames: F-Series Frames, 16 gage.

http://www.steelcraft.com/downloads/pdfs/steelcraft_spec_l1.pdf

- Interior: 16 gage knock-down door frames.
- o Drywall Frames: DW-Series (using Baseboards) and K-Series (Not using Baseboards), 16 gage.
- http://www.steelcraft.com/pc_frames_drywall.asp
- http://www.steelcraft.com/downloads/pdfs/steelcraft_spec_dw1.pdf
- Reinforcement: 14 gage for closer, 4-7/8 inches ASA strike, and 4-1/2 inches hinges.
- Preferred Manufacturer: Steelcraft.

08 14 00 - Wood Doors

36 inches minimum, solid core, birch veneer.

Closeout Submittals: Samples for University Paint Shop: Submit documentation of painting system used on "pre-finished" doors, including two manufacturer's sample finishes for each color and system used on the project.

08 31 00 - Specialty Doors and Frames - Access Doors and Panels

1.1 MANUFACTURERS

- A. Source Limitations: Obtain Access Doors and Panels from single source from single manufacturer.
- B. Basis-of-Design Product: Subject to compliance with requirements, provide Elmdor, Morris Group International.

1. Or Approved Equal.

08 41 00 - Entrances and Storefronts

No underfloor closures

08 71 00 - Door Hardware

See 08 71 00 Exhibit A - Door Hardware

Keying System:

University Facility Services Campus Key Coordinator designs keying system

.

Contractor:

General: Submit proposed keying system to Architect for review and written approval by Trustees, and copy of Best Access (Stanley Security Solutions) Purchase Order Number to Architect for Trustees Records.

Closeout Submittal: Submit three hard copies and one electronic copy of final keying schedule.

Products: Key locks and cores at factory and maintain permanent records of information.

Execution: After submittal and approval of keying system by Trustees, submit manufacturer's Purchase Order Number for Trustees to order cores and keys. Manufacturer shall deliver permanent keys, control keys and cylinder cores directly to Trustees Representative. Installation of cores shall be by the University.

Coordinate installation of permanent cores by University Lock Shop with Trustees Representative.

Keys:

Keys shall be provided by and issued by the University Key Shop. This is to ensure chain of custody and to provide a level of security acceptable to the University.

Construction Keying:

Construction Master Keys:

Provide temporary construction master keys (provide adequate number of master keys during construction for University access and inspection.) See Section 08 06 05 – Key Schedule for other keys.

Construction Cylinders:

- Provide construction cores.
- Permanent Keying: University installs permanent cores.

08 71 00 Exhibit A - Door Hardware

Cal Poly State University San Luis Obispo

Door Hardware Standard

Attention: Architects, Design Professionals, Hardware Specifiers, Contractors, Project Managers and other concerned parties:

Cal Poly State University San Luis Obispo has standardized on the following door and hardware products. Please adhere to the following when specifying hardware for Specification Section 087100 in new construction, in renovation and tenant improvement work:

Key System	Best Small Format Interchangeable Core 7 Pins. Provide Construction Cores and Permanent Cores. University installs permanent cores. *Consult facilities for keying details.	No Substitute
Hinges	Ives-5 knuckle ball bearing mortise. 5BB1 series 4.5 x 4.5 652/630, SH (security studs for perimeter doors) or equal. Hager, McKinney, Stanley *Von Duprin EPT CON @ storefronts with electrified hardware.	Preferred Acceptable Preferred
Continuous Hinges	Not preferred. Must have University approval prior to specifying or installing. Allowed under special conditions only. Continuous Geared. Ives 112XY Pin and Barrell: Ives 700 Or equal, Pemko, Markar, McKinney	Preferred Preferred Acceptable
Pivots	Ives: 7200 series 626. Include intermediate pivots. @ Storefront Doors. Or equal. Rixon, National Door Controls 101 Retro kit	Preferred Acceptable
Locksets	Mortise: Best Access Systems 45H 15-J 626 (AT-VIT Inside indicators with Thumb Turn lockdown on occupied spaces) Mortise: Schlage L9000H 06-N Series 626 (Inside indicators with Thumb Turn lockdown on occupied spaces)	Preferred Acceptable
Exit Devices	Rim: Von Duprin: CDSI-PA-AX 99L 06 US26D (med/wide stile doors) . CDSI W/ Thumb Turn Lockdown. Rim: Von Duprin: PA-AX-99L-F-2SI 06 US26D (fire rated doors) 2SI W/ Thumb Turn Lockdown. Concealed Vertical Cable: Von Duprin CDSI-PA-AX-9949L-LBL 06 US26D (med/wide stile doors) . CDSI W/ Thumb Turn Lockdown. Rim: Electrified Devices: RX-QELX-PA-AX-99L 06 US26D or RX-QELX-PA-AX - 99L-F for rated openings.lcn	No Substitute
Push and Pull Plates	Ives: 8200/8303 series @ multi-occupancy restrooms. Ives: 8190EZHD 12" or 9264 36" @ Storefronts. Or equal: Don-Jo, Forms & Surfaces, Triangle Brass	Preferred Preferred Acceptable
Flush Bolts and Coordinators	Ives: FB30-40-50-60 Series. Flush Bolts: Ives FB30-40 (automatic) Series and FB50-60 (constant) as required or equal. Don-Jo, Hager, Door Controls International	Preferred Preferred Acceptable
Mullions	Von Duprin: Keyed Removable KR series with MT54 storage bracket kits.	No Substitute
Surface Closer	Interior/Exterior: LCN 4040XP EDA Arms. Parallel Arm mounting preferred. Architect to verify PUSH SIDE mounting where at all possible. Corbin-Russwin DC6200 series	Preferred Acceptable
Auto Operators and Actuators	Electromechanical: LCN 9500 Senior Swing series. Heavy Use. Electrohydraulic: LCN 4600 Auto Equalizer series @ multi-occupancy restrooms. Or equal: Norton Actuators: LCN 8310-836T full length actuators	No Substitute No Substitute Acceptable Preferred
Floor Closers	Not preferred because replacement is expensive and difficult.	Do not use
Kick Plates/Protection Plates	Kickplates: Ives 8400 Series 10'X 2' less than door width (1" LDW at non mullioned pairs). Or equal: Don-Jo, IPC Door and Wall Protection Systems, Inc, Triangle Brass	Preferred Acceptable

Cal Poly State University San Luis Obispo

1 Grand Ave.

Floor/Wall /Overhead Stops	Floor Interior: Ives FS439. Wall: Ives WS406/WS407 as required. Floor Exterior: Ives FS18 series or Hold Open FS40 series when requested by University. Or equal: Triangle Brass, Don-Jo Overhead Stops: Glynn-Johnson 90/100 series as required. Use only where floor or wall stops are inadvisable. When used, use heavy weight hinges. Or equal: Rixson, Norton	Preferred Preferred Acceptable Preferred Acceptable
Door Seals	Interior: Zero International 188SBK PSA. Exterior: Zero International 429AA-S Acoustic Doors: Zero International 770AA-S Sweeps: Zero International 8192AA @ Storefronts. Hollow Metal or Wood doors Zero International 39A. Auto Door Bottoms: Zero International 355AA @ Hollow Metal Doors and 369AA @ wood doors where required. Or Equal: National Guard Products, Inc, Pemko	Preferred Preferred Preferred Preferred Preferred Preferred Acceptable
Thresholds	Zero International as required for sill condition. Or Equal. National Guard Products, Pemko	Preferred Acceptable
Power Supply	Von Duprin: PS902/904/914 depending on hardware and application.	No Substitute
Hollow Metal Doors & Frames	Exterior: Steelcraft "L" series 16ga honeycomb core, galvanized, capped on top and with galvanized 16ga frames. Polyurethane and seamless edge.	Acceptable
Electronic Access Control, Credentials	Verify with University.	No Substitute

Cal Poly State University San Luis Obispo uses Allegion, PLC (909-610-2539) as its consultant for doors and door hardware. Contact with the firm is Leo Requejado (818-877-6755) We highly recommend that you contact our Security and Safety Consultants firm to write the hardware specification (Section 087100) for all campus projects. There is no fee for their service. **Cal Poly State University San Luis Obispo** personnel are trained in the installation and maintenance of the above material and the **Cal Poly State University San Luis Obispo** maintenance department owns considerable stock of material for repair work. The campus is not prepared to accommodate the adoption of an additional standard as the hardware standard in place serves the campus.

Title: Supervising Locksmith
Name: Pete Bagnall

End of Section 08 71 00 - Door Hardware