

08 06 70 - Hardware Schedule

Contractor

Key Schedule

Use this area to list all keys provided on project referencing appropriate Sections. The Campus prefers to have one listing for all keys. ~~The purpose of Key Schedule is to allow the Architect to coordinate requirements and specifications for all keys provided on the project (doors, cabinets, drawers, panels, accessories, toilet room fixtures, equipment, etc.), have one listing for all keys, organize key submittal to the University, and provide manufacturer model numbers for future key replacement.~~

Key Schedule for {project name} {building number}						
Purpose / Location	Room Number	Keys Required	Total Keys	Model Number	Manufacturer	Section Reference
Cabinet locks <i>OK</i>		<i>2 Ea</i>				06 40 00 - Architectural Woodwork
Construction Master		<i>APPLICABLE</i> 20	20			08 71 00 - Door Hardware
Construction - Control		2	2			08 71 00 - Door Hardware
Control		4	4			08 71 00 - Door Hardware
Master		6 per each master set				08 71 00 - Door Hardware
Grand Master		4	4			08 71 00 - Door Hardware
Extra Blank		1 per each lock				08 71 00 - Door Hardware
Building Entrance		2/each lock or cylinder				08 71 00 - Door Hardware
Interior Doors		___/each lock or cylinder				08 71 00 - Door Hardware
Toilet Accessories		<i>2</i> 2 each building restroom/ accessory keyed differently				10 28 00 Toilet, Bath, and Laundry Accessories
Equipment		<i>2/EACH</i>				Division 11 - Equipment sections

Coordinate with Best and Campus

Key Schedule for {project name} {building number}						
Purpose / Location	Room Number	Keys Required	Total Keys	Model Number	Manufacturer	Section Reference
Furnishings		2 EA.				Division 12 – Furnishings sections
Elevators		3 keys, 1 installed in elevator pit.				14 20 00 – Elevators
Fire Control Cabinets		2 EA.				21 00 00 – Fire Suppression
Fire Control Padlocks		2/ each Padlock (10 SFIC cores)				21 00 00 – Fire Suppression
Plumbing		2 EA WATER APPLIES				22 00 00 – Plumbing
Plumbing Padlocks		2/ each Padlock (10 SFIC cores)				22 00 00 – Plumbing
HVAC Equipment Panels		2/ each Panel				23 00 00 – HVAC
HVAC Yard, Doors and Equipment Padlocks		2/ each Padlock (10 SFIC cores)				23 00 00 – HVAC
Electrical Panels						26 00 00 – Electrical
Emergency Generator Panels and Equipment		2/ each Padlock (10 SFIC cores)				26 00 00 – Electrical
Lighting Control Panels		2/ each Panel				26 00 00 – Electrical
Lighting Switches		2/ each switch				26 00 00 – Electrical
Electrical Yard, Equipment, & Switches Padlocks		2/ each Padlock (10 SFIC cores)				26 00 00 – Electrical
Communications Equipment						27 00 00 - Communications

Key Schedule for {project name} {building number}						
Purpose / Location	Room Number	Keys Required	Total Keys	Model Number	Manufacturer	Section Reference
Emergency Telephones (Blue Light Phones)		2/ each				27 00 00 - Communications
Communications Equipment Padlocks		2/ each Padlock (10 SFIC cores)				27 00 00 - Communications
Electronic Safety and Security Panels		2 EACH				28 00 00 - Electronic Safety and Security
Electronic Safety and Security Equipment Padlocks		2/ each Padlock (10 SFIC cores) SFIC				28 00 00 - Electronic Safety and Security
Irrigation Equipment		2 EACH				32 80 00 - Irrigation
Utilities		2 EACH				33 00 00 - Utilities

Closeout Submittal: Key Schedule – Provide hard copies and one electronic copy of completed Key Schedule along with keys separated and labeled.

08 11 13 - Hollow Metal Doors and Frames

Steel Doors:

- Exterior: Full flush doors (ANSI A250.8-1998 (SDI-100)), 1-3/4 inches thick, galvanized steel (ASTM A653/A653M-07), 14 gage closer reinforcement top and bottom with snap-in top caps.
- Interior: Full flush doors (ANSI A250.8-1998 (SDI-100)), 1-3/4 inches thick, 14 gage closer reinforcement top and bottom.
- Hardware preparation and reinforcement: Prepare for commercial hardware (ANSI A250.6-1997) and mortised locks (ANSI A115.1), no face holes unless coordinated with hardware schedule. Factory reinforce for surface applied hardware – 14 gage for closer. Locations per ANSI/DHI A115.
- Preferred Manufacturer and Model: Steelcraft L16 Series

Steel Door Frames:

- Exterior: 16 gage welded door frames; A60 hot dipped galvanized steel.
- Flush Frames: F-Series Frames, 16 gage.
http://www.steelcraft.com/downloads/pdfs/steelcraft_spec_l1.pdf
- Interior: 16 gage knock-down door frames.
 - Drywall Frames: DW-Series (using Baseboards) and K-Series (Not using Baseboards), 16 gage.
 - http://www.steelcraft.com/pc_frames_drywall.asp
 - http://www.steelcraft.com/downloads/pdfs/steelcraft_spec_dw1.pdf
- Reinforcement: 14 gage for closer, 4-7/8 inches ASA strike, and 4-1/2 inches hinges.
- Preferred Manufacturer: Steelcraft.

Timely door frames are not preferred. *(talk to carey to understand why)*

08 14 00 - Wood Doors

36 inches minimum, solid core, birch veneer.

Closeout Submittals: Samples for University Paint Shop: Submit documentation of painting system used on "pre-finished" doors, including two manufacturer's sample finishes for each color and system used on the project.

08 41 00 - Entrances and Storefronts

No underfloor closures

08 71 00 - Door Hardware

Keying System:

University Facility Services Campus Key Coordinator designs keying system.

Contractor:

General: Submit proposed keying system to Architect for review and written approval by Trustees, and copy of Best Access (Stanley Security Solutions) Purchase Order Number to Architect for Trustees Records.

Closeout Submittal: Submit three hard copies and one electronic copy of final keying schedule.

Products: Key locks and cores at factory and maintain permanent records of information.

Execution: After submittal and approval of keying system by Trustees, submit manufacturer's Purchase Order Number for Trustees to order cores and keys. Manufacturer shall deliver permanent keys, control keys and cylinder cores to Trustees Representative.

Coordinate installation of permanent cores by University Lock Shop with Trustees Representative.

Keys:

Material: Nickel-silver. Stamp keys "Do Not Duplicate."

Quantity: Cylinder Keys (3 per core); and Extra Blank Keys (1 per core or lock).

Keying:

Telecommunication Spaces (Rooms): Use 112-series key lock. (Coordinate with Division 27 – Communications.)

Master Padlocks: Use where less security is required. Coordinate with Trustees Representative during design process for specific Campus Project requirements, and Divisions 21, 22, 23, 26 (Electrical Panels), 27, and 32 (Bollards). Key alike to Campus Specifications #2359, and provide 2 keys per panel, etc.

State Padlocks: Use where higher security is required, such as Electrical Yards and Switches, HVAC Yards and Equipment, etc. Coordinate with Trustees Representative during design process for specific Campus Project requirements, and Divisions 21, 22, 23 (HVAC Air Handling Units), 26 (Electrical Switchgear, Transformers), 27, and 32. Requires interchangeable cores complying with Campus Cylinders and Keying Standards. Interchangeable core.

Best Key
Cover with
water
Always
Piercing

(small format I.C.)
SFC

Hinges: ~~AND~~ PIVOTS :

Campus Preferred Manufacturers:

- Hager Companies: Exterior -- Stainless Steel, Ball Bearing Part #BB1191; Interior -- Plated with 626 Finish, #BB1279BB
- McKinney Products Company, Division of Assa Abloy
- Stanley.

Also this
to
next section
All doors
and
state
K
USE TOP/BOTTOM
AND INTERIOR
PIVOT

— CONTINUOUS HINGE IS NOT PREFERRED

ADJUSTABLE PIVOTS WORK BETTER — ALWAYS

Pivots and Pivot Hinges:

Campus Preferred Manufacturers:

- Ives; Division of Allegion
- Rixson-Firemark, Inc.; Div. of Assa Abloy
- National Manufacturing 101 Retro Kit

Continuous Pin and Barrel Hinges:

Campus Preferred Manufacturers:

- Pemko
- Markar Products, Inc.
- McKinney Products Company; Div. of Assa Abloy

CONTINUOUS HINGES MUST HAVE
APPROVAL OF UNIVERSITY PRIOR TO
SPECIFYING / ORDERING A.
-(SPECIAL CONDITIONS)
ONLY

Mechanical Locks and Latches:

Campus Preferred Manufacturers:

- Best Access Systems – 45H Series
- ~~Corbin Russwin – ML2000 Series~~
- Schlage Lock Company; an Ingersoll-Rand Company – L94 Series
- ~~Assa Abloy 8200 Series mortise locks~~

(WITH APPROVAL OF UNIVERSITY)
PRICE IS HINDERANCE

Electric Mortise Locksets:

Campus Preferred Manufacturer:

- Best Access Systems – 45H Series.
- SCHLAGE ~~L-SERIES~~ L-SERIES

Surface Bolt:

Campus Preferred Manufacturer:

- Door Controls International
- Don-Jo Manufacturing
- Hager Companies
- Ives: H.B. Ives
- Rockwood Manufacturing Company
- Triangle Brass Manufacturing Company, Inc.

Flush Bolts:

Campus Preferred Manufacturers:

- Door Controls International
- Don-Jo Manufacturing
- Hager Companies
- Ives: H.B. Ives
- Rockwood Manufacturing Company
- Triangle Brass Manufacturing Company, Inc.

Exit Devices:

Prefer rim device over vertical rods. Preferred Manufacturer:

- Von Duprin, Division of Allegion – Series 98 or 99. — MAINT. ISSUE FOR CAMPUS (THIS PRODUCT ONLY)
- Corbin Russwin – Series ED5000. — BEST ARE SUB PAR – PUSH PADS PUT
- Not Recommended: Adams Rite Manufacturing Co. Products are low quality and don't hold up.

CONES + Cylinders:

Small format interchangeable core type, constructed from brass or bronze, stainless steel, or nickel silver.

Number of Pins: Seven

Mortise Type: Threaded cylinders with rings and appropriate cam to suit lock function and type.

~~Functions: D-Storage; R-Classroom; N-Passage; A-Office; TA-Dormitory~~

Required Manufacturer:

- Best Access Systems.
- Medeco Keymark

Door Cylinders:

Best Model 1E Series or equivalent (Arrow, general).

Construction Keying:

Construction Master Keys:

Provide temporary construction master keys (20 construction master keys and 2 control keys). See

~~Section 08-06-05 – Key Schedule~~

PROVIDE ADEQUATE # AND
ADDITIONAL AS NEEDED

Construction Cylinders:

- Provide construction cores.
- Permanent Keying: University installs permanent cores.

Electric Strikes:

Campus Preferred Manufacturers:

- **BEST F2104 - FAIL SECURE - CONTINUOUS DUTY**
- Hes Innovations (1006, 9600)
- Von Duprin

Operating Trim (push/pulls):

Campus Preferred Manufacturers:

- Don-Jo Manufacturing
- Forms & Surfaces
- Triangle Brass Manufacturing Company, Inc.

Accessories for Pairs of Doors:

Campus Preferred Manufacturers:

- Coordinators:
 - Don-Jo Manufacturing
 - Hager Companies
 - Ives: H.B. Ives
 - Door Controls Internationals
- Removable Mullions:
 - Von Duprin, Division of Allegion
 - ~~Corbin Russwin Architectural Hardware, Division of Assa Abloy~~
 - Note: "Key Removable" when needed.
- Astragals:
 - National Guard Products, Inc.
 - Pemko Manufacturing Company, Inc.
 - Reese Enterprises, Inc.

Closers:

Campus Preferred Manufacturers:

- Surface-Mounted Closers:

Closers (cont'd)

- Preferred →
- LCN, Division of Ingersoll-Rand, 4040 Series, mounting: inside of door, parallel arm preferred.
 - Corbin Russwin, DC6200 Series.
 - Electromechanical Closers:
 - LCN, Division of Allegion, ~~4041 Series~~
 - Norton, Division of Assa Abloy
 - Concealed Floor Closers: Not preferred because replacement is expensive and difficult.
 - Closer Holder Release Devices:
 - Not preferred because of wear and tear on top hinge.
 - Corbin Russwin Architectural Hardware, Division of Assa Abloy.
 - Rixson-Firemark, Inc., Division of Assa Abloy.
 - Overhead Stops: Not preferred because pull hinges out causing door to sag, and damages door jambs.

Protective Trim Units:

Campus Preferred Manufacturers:

Metal Protective Trim Units:

- Don-Jo Manufacturing
- IPC Door and Wall Protection Systems, Inc.
- Triangle Brass Manufacturing Company, Inc.

Stops and Holders:

Preferred Manufacturers: Metal Protective Trim Units:

- Don-Jo Manufacturing
- Ives: H.B. Ives
- Norton Door Controls, Division of Assa Abloy.
- Rixson-Firemark, Inc., Division of Assa Abloy.
- Triangle Brass Manufacturing Company, Inc.

Door Gasketing:

Campus Preferred Manufacturers:

- Door Gasketing:
 - National Guard Products, Inc.
 - Pemko Manufacturing Company, Inc.
- Door Bottoms:

- National Guard Products, Inc.
- Pemko Manufacturing Company, Inc.

Thresholds:

Campus Preferred Manufacturers:

- Thresholds: Meet ADA Access requirements.
 - National Guard Products, Inc.
 - Pemko Manufacturing Company, Inc.
 - Rixson-Firemark, Inc., Division of Assa Abloy.