

22 40 00 - Plumbing Fixtures

Lavatory

- Student Housing: Heavy duty commercial grade single handle faucet; deck mounted with 4" centerset, chrome plated finish, vandal resistant handle, brass body, washerless design, rotating ball control mechanism with replaceable nonmetallic seats and stainless steel socket, vandal resistant 0.5 GPM flow restrictors spray outlet, left rod operated metal drain.
 - Preferred Manufacturer: American Standard
 - Lavatory – Wall Hung: American Standard Lucerne Model Numbers:0356.028.020, 20" by 18", high back.
 - Lavatory – Countertop: American Standard Rondalyn Countertop Sink Model Numbers: 0490.156.020 round, vitreous china, self-rimming front overflow design.
 - Faucets: Preferred Manufacturer and Model: Moen CA83005 Non-mixing Electronic Faucet (0.325 GPM Vandal Resistant Flow). http://www.moen.com/search?search_scope=0&search_terms=CA8305
- Public: Heavy duty commercial grade single handle faucet; deck mounted with 4" centerset, chrome plated finish, vandal resistant handle, brass body, washerless design, rotating ball control mechanism with replaceable nonmetallic seats and stainless steel socket, vandal resistant 0.5 GPM flow restrictor spray outlet, and grid drain.
 - Campus Lavatory Standard (as appropriate):
 - 0.375 gpm Tamper Resistant Laminar Flow Control for Existing Lavatory faucet: Neoperl 40.7059.733
 - Moen 8413 F03 Comm 4" cc .35 GPM Lav Faucet w/o
 - Moen 8551 Sensored Lay Fct
 - Campus Basin Standard: Lavatory Basin with 4" Centerset Holes – American Standard Lucerne 0355.012.020
- Kitchen, Student Housing: Heavy duty commercial grade, single handle faucet, deck mounted with 8" centers, 8" swing spout, chrome plated finish, vandal resistant handle, brass body, rotating stainless steel ball control mechanism with replaceable non-metallic seats and stainless steel socket, vandal resistant 2 GPM flow restrictor aerator.

Shower Valves

- Student Housing: Institutional grade, pressure balancing, adjustable safety limit temperature stop control.
- Public: Institutional grade, pressure balancing, adjustable safety limit temperature stop control.
- Campus Standard: 1.5 GPM Low-Flow Pressure Balancing Surface Mounted Shower System – Hydapipe 1-901

Fixture Traps:

Chrome plated, 17 gauge cast bronze.

Faucets, Supplies, and Trim:

Mechanical Trap Primers:

Standard: Reduce or eliminate use.

Hose Bibbs:

3/4" hose connection, chrome plated, with vacuum breaker, loose key.

Water Meters:

Domestic Water: Nutating disk, magnetic drive, bronze case

Irrigation Water: Turbine type, magnetic drive, bronze case

Pressure Reducing Valve: Bronze with Teflon disk and diaphragm Valves, General Purpose Ball Valves, 2-1/2" and smaller. Provide threaded valve with downstream union.