

Université de Sciences et Technologies Houari Boumedien

Faculty d'Informatique
Master 1 RSD

TP Reseaux BGP

TP Reseaux et Protocols

Prof: Mme Bouachi Farida

Etudiant: Belmouloud Mustapha Abdellah

Matricule: 212131092524

Groupe: 1

December 26, 2025

1 i hate this fucking subject, fucking whale of a teacher giving me assignmments during vacation FUCK YOU

2 TP1

1. create tablespace belmouloud_tbs datafile '/opt/oracle/oradata/XE/belmouloud_tbs.dbf' SIZE 100M AUTOEXTEND ON;

```
SQL> create tablespace belmouloud_tbs datafile '/opt/oracle/oradata/XE/belmouloud_tbs.dbf' SIZE 100M AUTOEXTEND ON;
Tablespace created.
```

create temporary tablespace belmouloud2_temptbs tempfile '/opt/oracle/oradata/XE/belmouloud2_temptbs.dbf' SIZE 100M AUTOEXTEND ON;

```
SQL> create temporary tablespace belmouloud2_temptbs tempfile '/opt/oracle/oradata/XE/belmouloud2_temptbs.dbf' SIZE 100M AUTOEXTEND ON;
Tablespace created.
```

2. create user tp1_belmouloud identified by musmus3108 default tablespace belmouloud_tbs temporary tablespace belmouloud2_temptbs;

```
SQL> create user tp1_belmouloud identified by musmus3108 default tablespace belmouloud_tbs temporary tablespace belmouloud2_temptbs;
User created.
```

3. GRANT ALL privileges to tp1_belmouloud;

```
SQL> GRANT ALL privileges to tp1_belmouloud;
Grant succeeded.
```

4. les tableaux proposés:

user(id primary key, name)

sellers(id primary key, name)

products(id primary key, name, seller_id foreign key, price(entre 20 et 100), category (tshirt, hoodie, jacket))

orders(product_id foreign key, user_id foreign key, primaryKey(product_id, use_id))

order_comments (id primary key, product_id foreign key, user_id foreign key,comments)

seller_reviews (id primary_key, seller_id foeignkey,user_id foreignkey,rating)

5. CREATE TABLE users (id NUMBER, name VARCHAR2(50), CONSTRAINT pk_users PRIMARY KEY (id));

CREATE TABLE sellers (id NUMBER, name VARCHAR2(50), CONSTRAINT pk_sellers PRIMARY KEY (id));

CREATE TABLE products (id NUMBER, name VARCHAR2(20), seller_id NUMBER, price NUMBER, category VARCHAR2(10), CONSTRAINT pk_products PRIMARY KEY (id), CONSTRAINT chk_price CHECK (price BETWEEN 20 AND 100), CONSTRAINT chk_category CHECK (category IN ('tshirt', 'hoodie', 'jacket')), CONSTRAINT fk_product_seller FOREIGN KEY (seller_id) REFERENCES sellers (id));

CREATE TABLE orders (product_id NUMBER, user_id NUMBER, CONSTRAINT pk_orders PRIMARY KEY (product_id, user_id), CONSTRAINT fk_order_product FOREIGN KEY (product_id) REFERENCES products (id), CONSTRAINT fk_order_user FOREIGN KEY (user_id) REFERENCES users (id));

CREATE TABLE order_comments (id NUMBER, product_id NUMBER, user_id NUMBER, commenttxt VARCHAR2(100), CONSTRAINT pk_order_comments PRIMARY KEY (id), CONSTRAINT fk_comment_order1 FOREIGN KEY (product_id) REFERENCES products(id), CONSTRAINT fk_comment_order2 FOREIGN KEY (user_id) REFERENCES users(id));

CREATE TABLE seller_reviews (id NUMBER, seller_id NUMBER, user_id NUMBER, rating NUMBER, CONSTRAINT pk_seller_reviews PRIMARY KEY (id), CONSTRAINT chk_rating CHECK (rating BETWEEN 1 AND 5), CONSTRAINT fk_review_seller FOREIGN KEY (seller_id) REFERENCES sellers (id), CONSTRAINT fk_review_user FOREIGN KEY (user_id) REFERENCES users (id));

```
SQL> CREATE TABLE users (
id NUMBER,
name VARCHAR2(50),
CONSTRAINT pk_users PRIMARY KEY (id)
); 2 3 4 5

Table created.

SQL> CREATE TABLE sellers (
id NUMBER,
name VARCHAR2(50),
CONSTRAINT pk_sellers PRIMARY KEY (id)
); 2 3 4 5

Table created.

SQL> CREATE TABLE products (
id NUMBER,
name VARCHAR2(20),
seller_id NUMBER,
price NUMBER,
category VARCHAR2(10),
CONSTRAINT pk_products PRIMARY KEY (id),
CONSTRAINT chk_price CHECK (price BETWEEN 20 AND 100),
CONSTRAINT chk_category CHECK (category IN ('tshirt', 'hoodie', 'jacket')),
CONSTRAINT 2 fk_product_seller FOREIGN KEY (seller_id) REFERENCES sellers (id)
); 3 4 5 6 7 8 9 10 11

Table created.
```

```
SQL> CREATE TABLE orders (
product_id NUMBER,
user_id     NUMBER,
CONSTRAINT pk_orders PRIMARY KEY (product_id, user_id),
CONSTRAINT fk_order_product FOREIGN KEY (product_id) REFERENCES products (id),
CONSTRAINT fk_order_user FOREIGN KEY (user_id) REFERENCES users (id)
); 2 3 4 5 6 7

Table created.
```

```
SQL> CREATE TABLE order_comments (
id          NUMBER,
product_id  NUMBER,
user_id     NUMBER,
commenttxt  VARCHAR2(100),
CONSTRAINT pk_order_comments PRIMARY KEY (id),
CONSTRAINT fk_comment_order1 FOREIGN KEY (product_id) REFERENCES products(id),
CONSTRAINT fk_comment_order2 FOREIGN KEY (user_id) REFERENCES users(id)
); 2 3 4 5 6 7 8 9

Table created.

SQL> CREATE TABLE seller_reviews (
id          NUMBER,
seller_id   NUMBER,
user_id     NUMBER,
rating      NUMBER,
CONSTRAINT pk_seller_reviews PRIMARY KEY (id),
CONSTRAINT chk_rating CHECK (rating BETWEEN 1 AND 5),
CONSTRAINT fk_review_seller FOREIGN KEY (seller_id) REFERENCES sellers (id),
CONSTRAINT fk_review_user FOREIGN KEY (user_id) REFERENCES users (id)
); 2 3 4 5 6 7 8 9 10

Table created.
```

6. alter table users add lastname varchar2(20);

```
SQL> alter table users add lastname varchar(20);

Table altered.

SQL> desc users;
Name                               Null?    Type
-----
ID                                  NOT NULL NUMBER
NAME                                VARCHAR2(50)
LASTNAME                           VARCHAR2(20)
```

7. alter table users modify name varchar2(50) not null;
alter table sellers modify name varchar2(50) not null;

```
SQL> desc sellers;
  Name                                         Null?      Type
-----
ID                                             NOT NULL   NUMBER
NAME                                           VCHAR2(50)

SQL> desc users;
  Name                                         Null?      Type
-----
ID                                             NOT NULL   NUMBER
NAME                                           VCHAR2(50)
LASTNAME                                       VCHAR2(20)

SQL> alter table users modify name varchar(50) not null;

Table altered.

SQL> alter table sellers modify name varchar(50) not null;

Table altered.
```

8. alter table users modify name varchar2(100);

```
SQL> alter table users modify name varchar(100);

Table altered.

SQL> desc users;
  Name                                         Null?      Type
-----
ID                                             NOT NULL   NUMBER
NAME                                           NOT NULL   VCHAR2(100)
LASTNAME                                       VCHAR2(20)
```

9. alter table users drop column lastname;

```
SQL> desc users;
  Name                                         Null?      Type
-----
ID                                             NOT NULL   NUMBER
NAME                                           NOT NULL   VCHAR2(100)
LASTNAME                                       VCHAR2(20)

SQL> alter table users drop column lastname;

Table altered.

SQL> desc users;
  Name                                         Null?      Type
-----
ID                                             NOT NULL   NUMBER
NAME                                           NOT NULL   VCHAR2(100)
```

10. alter table users rename column name to fullname;

```
SQL> desc users;
  Name                               Null?    Type
  -----
  ID                                NOT NULL NUMBER
  NAME                             NOT NULL VARCHAR2(100)

SQL> alter table users rename column name to fullname;

Table altered.

SQL> desc users;
  Name                               Null?    Type
  -----
  ID                                NOT NULL NUMBER
  FULLNAME                         NOT NULL VARCHAR2(100)
```

11. alter table orders add constraint fk_order_seller foreign key (seller_id) references sellers(id);

```
SQL> alter table orders add seller_id number;

Table altered.

SQL> alter table orders add constraint fk_order_seller foreign key (seller_id) references sellers(id);

Table altered.
```

12. alter table products add constraint dlp check(discount < price);

```
SQL> alter table products add discount number;

Table altered.

SQL> alter table products add constraint dlp check(discount < price);

Table altered.
```

13. CREATE OR REPLACE TRIGGER potr BEFORE INSERT OR UPDATE ON orders FOR EACH ROW DECLARE vdiscount products.discount BEGIN SELECT discount INTO vdiscount FROM products WHERE id = :NEW.product_id; IF :NEW.discounted != vdiscount THEN RAISE_APPLICATION_ERROR(-20001, 'Order discount must match product discount'); END IF; END; /

```

SQL> CREATE OR REPLACE TRIGGER potr
BEFORE INSERT OR UPDATE ON orders
FOR EACH ROW
DECLARE
    vdiscount products.discount%TYPE;
BEGIN
    SELECT discount
    INTO vdiscount
    FROM products
    WHERE id = :NEW.product_id;
    IF :NEW.discounted != v 2 3 discount THEN
        RAISE_APPLICATION_ERROR(-20001, 'Order discount must match product discount');
    END IF;
END;
/ 4 5 6 7 8 9 10 11 12 13 14 15

Trigger created.

```

14. INSERT INTO users (id, fullname) VALUES (1, 'Alice Johnson');
- INSERT INTO users (id, fullname) VALUES (2, 'Bob Smith');
- INSERT INTO users (id, fullname) VALUES (3, 'Charlie Brown');
- INSERT INTO users (id, fullname) VALUES (4, 'Diana Prince');
- INSERT INTO users (id, fullname) VALUES (5, 'Ethan Hunt');
- INSERT INTO users (id, fullname) VALUES (6, 'Fiona Apple');
- INSERT INTO users (id, fullname) VALUES (7, 'George Martin');

```

INSERT INTO sellers (id, name) VALUES (1, 'CoolTees');
INSERT INTO sellers (id, name) VALUES (2, 'HoodieHub');
INSERT INTO sellers (id, name) VALUES (3, 'JacketWorld');
INSERT INTO sellers (id, name) VALUES (4, 'UrbanWear');
INSERT INTO sellers (id, name) VALUES (5, 'FashionFiesta');
INSERT INTO sellers (id, name) VALUES (6, 'TrendSetters');
INSERT INTO sellers (id, name) VALUES (7, 'StreetStyle');

```

```

INSERT INTO products (id, name, seller_id, price, category, discount) VALUES (1,
'Classic Tee', 1, 25, 'tshirt', 5);
INSERT INTO products (id, name, seller_id, price, category, discount) VALUES (2,
'Premium Hoodie', 2, 60, 'hoodie', 10);
INSERT INTO products (id, name, seller_id, price, category, discount) VALUES (3,
'Leather Jacket', 3, 90, 'jacket', 15);
INSERT INTO products (id, name, seller_id, price, category, discount) VALUES (4,
'Graphic Tee', 1, 30, 'tshirt', 7);
INSERT INTO products (id, name, seller_id, price, category, discount) VALUES (5,
'Zip Hoodie', 2, 55, 'hoodie', 12);
INSERT INTO products (id, name, seller_id, price, category, discount) VALUES (6,
'Winter Jacket', 3, 95, 'jacket', 20);
INSERT INTO products (id, name, seller_id, price, category, discount) VALUES (7,
'Summer Tee', 1, 22, 'tshirt', 0);

```

```

INSERT INTO orders (product_id, user_id, seller_id, discounted) VALUES (1, 1, 1,

```

```

5);
INSERT INTO orders (product_id, user_id, seller_id, discounted) VALUES (2, 2, 2,
10);
INSERT INTO orders (product_id, user_id, seller_id, discounted) VALUES (3, 3, 3,
15);
INSERT INTO orders (product_id, user_id, seller_id, discounted) VALUES (4, 4, 1,
7);
INSERT INTO orders (product_id, user_id, seller_id, discounted) VALUES (5, 5, 2,
12);
INSERT INTO orders (product_id, user_id, seller_id, discounted) VALUES (6, 6, 3,
20);
INSERT INTO orders (product_id, user_id, seller_id, discounted) VALUES (7, 7, 1,
0);

```

```

INSERT INTO order_comments (id, product_id, user_id, commenttxt) VALUES (1,
1, 1, 'Great quality!');
INSERT INTO order_comments (id, product_id, user_id, commenttxt) VALUES (2,
2, 2, 'Very cozy hoodie. ');
INSERT INTO order_comments (id, product_id, user_id, commenttxt) VALUES (3,
3, 3, 'Love the jacket!');
INSERT INTO order_comments (id, product_id, user_id, commenttxt) VALUES (4,
4, 4, 'Nice graphic design. ');
INSERT INTO order_comments (id, product_id, user_id, commenttxt) VALUES (5,
5, 5, 'Good value for price. ');
INSERT INTO order_comments (id, product_id, user_id, commenttxt) VALUES (6,
6, 6, 'Perfect for winter. ');
INSERT INTO order_comments (id, product_id, user_id, commenttxt) VALUES (7,
7, 7, 'Light and comfortable. ');

```

```

INSERT INTO seller_reviews (id, seller_id, user_id, rating) VALUES (1, 1, 1, 5);
INSERT INTO seller_reviews (id, seller_id, user_id, rating) VALUES (2, 2, 2, 4);
INSERT INTO seller_reviews (id, seller_id, user_id, rating) VALUES (3, 3, 3, 5);
INSERT INTO seller_reviews (id, seller_id, user_id, rating) VALUES (4, 1, 4, 3);
INSERT INTO seller_reviews (id, seller_id, user_id, rating) VALUES (5, 2, 5, 4);
INSERT INTO seller_reviews (id, seller_id, user_id, rating) VALUES (6, 3, 6, 5);
INSERT INTO seller_reviews (id, seller_id, user_id, rating) VALUES (7, 1, 7, 4);

```

la requete "insert into orders (product_id, user_id, seller_id, discounted) values (1, 2, 1, 999);" vas echouer a cause de trigger deja déclaré qui necessite que discount = discounted

```

SQL> insert into orders (product_id, user_id, seller_id, discounted) values (1, 2, 1, 999);
insert into orders (product_id, user_id, seller_id, discounted) values (1, 2, 1, 999)
      *
ERROR at line 1:
ORA-20001: Order discount must match product discount
ORA-06512: at "SYSTEM.POTR", line 9
ORA-04088: error during execution of trigger 'SYSTEM.POTR'

```


la requete "INSERT INTO products (id, name, seller_id, price, category, discount) VALUES (8, 'Expensive Tee', 1, 150, 'tshirt', 10); " vas echouer a cause constarint check qui necessite price;discount

```
SQL> INSERT INTO products (id, name, seller_id, price, category, discount)
VALUES (8, 'Expensive Tee', 1, 150, 'tshirt', 10);
  2  INSERT INTO products (id, name, seller_id, price, category, discount)
*
ERROR at line 1:
ORA-02290: check constraint (SYSTEM.CHK_PRICE) violated
```

INSERT INTO products (id, name, seller_id, price, category, discount) VALUES (9, 'Fancy Pants', 2, 50, 'pants', 5); vas echouer car la category doit etre tshirt hoodie ou jacket

```
SQL> INSERT INTO products (id, name, seller_id, price, category, discount)
VALUES (9, 'Fancy Pants', 2, 50, 'pants', 5);
  2  INSERT INTO products (id, name, seller_id, price, category, discount)
*
ERROR at line 1:
ORA-02290: check constraint (SYSTEM.CHK_CATEGORY) violated
```

15. alter table products disable constraint chk_price;
16. delete from products where id=1;
contrainte d'integrité car on a pas specifié de qui fair on delete.

```
SQL> delete from products where id=1;
delete from products where id=1
*
ERROR at line 1:
ORA-02292: integrity constraint (SYSTEM.FK_COMMENT_ORDER1) violated - child
record found
```

17. assuré
18. select * from products, orders, users where orders.product_id = products.id and orders.user_id = users.id and products.discount <10;

```
SQL> select * from products, orders, users where orders.product_id = products.id and orders.user_id = users.id and products.discount >10;
```

ID	NAME	SELLER_ID	PRICE	CATEGORY	DISCOUNT
3	Leather Jacket	3	90	jacket	15
3		3	15	3	
Charlie Brown					
5	Zip Hoodie	2	55	hoodie	12
5		2	12	5	
Ethan Hunt					
6	Winter Jacket	3	95	jacket	20
6		3	20	6	
Fiona Apple					

19. select seller_id , avg(discounted) as average_discount from orders group by seller_id;

```
SQL> select seller_id , avg(discounted) as average_discount from orders group by seller_id;
```

SELLER_ID	AVERAGE_DISCOUNT
1	4
2	11
3	17.5

20. create view qst20 as select seller_id , avg(discounted) as average_discount from orders group by seller_id;

```
SQL> create view qst20 as select seller_id , avg(discounted) as average_discount from orders group by seller_id;
```

View created.

```
SQL> select * from qst20;
```

SELLER_ID	AVERAGE_DISCOUNT
1	4
2	11
3	17.5

3 Resultas

Example avec shiw ip route

Figure 1: Example Routeur OSPF