← 13 · If you get stuck | Step 14 of 15 — Tough questions | 15 · Recovery card →

Tough questions

Time	Difficulty	Steps	You will need
15 min	Easy	6 questions	Nothing — read and discuss

The questions people use to poke holes in the method. Only what is true.

Q: You typed the seed on a laptop. Isn’t that exposed?

Typed on Tails, networking off, one seed per boot, then a full shutdown — Tails forgets the session. A hardware keylogger is still possible. But one captured seed **still can’t spend**: the fund needs two. Never type two seeds on one boot.

Q: Why not start with a hardware wallet?

A signer can join later; it is not how these keys are made. The randomness is **dice you can watch** — no chip to trust, no firmware to audit.

Q: Is dice randomness weaker than a hardware RNG?

No. **256 bits is 256 bits**, whatever made them.

Q: If the map passphrase is lost, are the coins gone?

Not with all three plates — they rebuild the map exactly. But two plates plus a lost passphrase means the addresses are **unrecoverable**. Back up the passphrase paper in two places, away from the plates and USBs.

Q: What if someone finds one plate?

They can’t spend — one key alone opens nothing. But **never keep two plates in one place**: that’s the whole lock in one drawer.

Q: Shouldn’t I add a passphrase to the multisig?

No. The security is the **distribution**, not one more secret. A passphrase on the 2-of-3 is a single point of failure in disguise — lose it and two plates aren’t enough. The home plate’s small decoy wallet is the separate, optional place for a passphrase.

That is the whole method. Everything else is commentary.

Plebum Dominium · plebumbtc.io · Version 2026.10.21 · Built October 21, 2026
Content SHA-256: b6e79f937ff6f6625fa41335612f294e298d22b4e08fe0ca175cf8fed2f4edc8