# **ICON Namelist Overview**

June 21, 2019

## Contents

1.	ICON Namelists	2
	1.1. Scripts, Namelist files and Programs	2
	1.2. Namelist parameters	
		_
2.	Namelist parameters defining the atmospheric model	3
	2.1. assimilation_nml	
	2.2. coupling_mode_nml	
	2.3. diffusion_nml	
	2.4. dynamics_nml	7
	2.5. echam_cld_nml	7
	2.6. echam_cnv_nml	ć
	2.7. echam_cov_nml	10
	2.8. echam_gwd_nml	10
	2.9. echam_phy_nml	11
	2.10. echam rad nml	12
	2.11. echam sso nml	16
	2.12. echam vdf nml	16
	2.13. ensemble_pert_nml	
	2.14. gribout nml	
	2.15. grid_nml	
	2.16. gridref nml	
	2.17. ha dyn nml	
	2.18. initicon nml	
	2.19. interpol nml	28
	2.20. io_nml	
	$2.\overline{20}.1.$ Restart read/write mode:	
	2.21 les nml (parameters for LES turbulence scheme; valid for inwp_turb=5)	
	2.22. limarea_nml (Scope: l_limited_area=.TRUE. in grid_nml)	
	2.23. lnd nml	
	2.24. ls forcing nml (parameters for large-scale forcing; valid for torus geometry)	
	2.25. master nml	

	2.26. master model nml (repeated for each model)	3
	2.27. master_time_control_nml	
	$2.28. \ \mathrm{meteogram} \ \mathrm{output} \ \mathrm{nml}$	
	2.29. nonhydrostatic nml (relevant if run nml:iequations=3)	
	2.30. nudging nml	
	2.31. nwp phy nml	
	2.32. nwp_tuning_nml	
	2.33. output nml (relevant if run nml/output='nml')	
	2.34. parallel nml	
	2.35. psrad nml	
	2.36. radiation nml	
	2.37. run nml	
	$2.38. \text{ sleve } \text{nml (relevant if nonhydrostatic } \text{nml:ivctype=2)} \dots \dots$	
	2.39. synsat nml	
	2.40. time nml	
	$2.41. \ \text{transport nml (used if run nml/ltransport=.TRUE.)} \ldots \ldots \ldots \ldots \ldots$	
	2.42. turbdiff nml	
	<u></u>	•
3.	Ocean-specific namelist parameters	7
	3.1. ocean physics nml	7
	3.2. sea ice nml (relevant if run nml/iforcing=2 (ECHAM))	
4.	Namelist parameters for testcases (NAMELIST_ICON)	7!
	4.1. ha_testcase_nml (Scope: ltestcase=.TRUE. and iequations=[0,1,2] in run_nml)	
	4.2. nh_testcase_nml (Scope: ltestcase=.TRUE. and iequations=3 in run_nml)	7
F		ο,
Э.	External data 5.1. extpar nml (Scope: itopo=1 in run nml)	0.
	5.1. extpar_nmi (5cope: ntopo=1 in run_nmi)	٥.
6.	External packages	8
•		•
<b>7</b> .	Information on vertical level distribution	8
		•
8.	Compile flag for mixed precision	83
Α.	Arithmetic expression evaluation	8
	A.1. Examples for arithmetic expressions	8
	A.2. Expression syntax	
	A.2.1. List of functions	
	A.2.2. List of operators	
	A.2.3. List of available constants	
	A.3. Usage with Fortran	
	A.3.1. Fortran examples	
	A.3.2. Error handling	
	A.4. Remarks	
В.	Changes incompatible with former versions of the model code	8

## 1. ICON Namelists

## 1.1. Scripts, Namelist files and Programs

Run scripts starting the programs for the models are stored in run/. These scripts write namelist files containing the specified Fortran namelists. Programs are stored in < icon home>/build/<architecture>/bin/.

Table 1: Namelist files

Namelist file	Purpose	Made by script	Used by program
NAMELIST_GRAPH	Generate graphs	$create\_global\_grids.run$	grid_command
$NAMELIST\_GRID$	Generate grids	create_global_grids.run	$\operatorname{grid} \_\operatorname{command}$
NAMELIST_GRIDREF	Gen. nested domains	$create\_global\_grids.run$	$\operatorname{grid} \_\operatorname{command}$
NAMELIST_ICON	Run ICON models	exp. < name > .run	$\operatorname{control} \_\operatorname{model}$

#### 1.2. Namelist parameters

The following subsections tabulate all available Fortran namelist parameters by name, type, default value, unit, description, and scope:

- Type refers to the type of the Fortran variable, in which the value is stored: I=INTEGER, L=LOGICAL, R=REAL, C=character string
- Default is the preset value, if defined, that is assigned to this parameter within the programs.
- *Unit* shows the unit of the control parameter, where applicable.
- Description explains in a few words the purpose of the parameter.
- Scope explains under which conditions the namelist parameter has any effect, if its scope is restricted to specific settings of other namelist parameters.

Information on the file, where the namelist is defined and used, is given at the end of each table.

### 2. Namelist parameters defining the atmospheric model

Namelist parameters for the ICON models are organized in several thematic Fortran namelists controling the experiment, and the properties of dynamics, transport, physics etc.

#### 2.1. assimilation nml

The main switch for the Latent heat nudging scheme is called ldass llnn and has to be set in run nml.

Parameter	Type	Default	Unit	Description	Scope
nlhn_start	I	-9999	s	time in seconds when LHN is applied for the	$run\_nml:ldass\_lhn = .true.$
				first time	
nlhn_end	I	-9999	S	time in seconds when LHN is applied for the last	$run\_nml:ldass\_lhn = .true.$
				time	
lhn_coef	R	1.0		Nudging coefficient of adding the increments	
fac_lhn_up	R	2.0		Upper limit of the scaling factor of the	
				temperature profile.	
fac_lhn_down	R	0.5		Lower limit of the scaling factor of the	
				temperature profile.	
lhn_logscale	L	.TRUE.		Apply all scaling factors as logarithmic values	fac_lhn_down, fac_lhn_up,
					fac_lhn_artif
thres_lhn	R	0.1/3600.	mm/s	Minimal value of precipitation rate, either of	
				model or radar. LHN will be applied first for	
				precipitation above it.	
start_fadeout	R	1.0		Value to determine, at which model time step a	
				fading out of the increments might start.	
lhn_qrs	L	.TRUE.		Use a vertical average of precipitation fluxes as	
				reference to compare with radar observed	
				precipitation, to avoid severe overestimation due	
				to displacement of model surface precipitation.	
				If set .FALSE. the model surface precipitation	
				rate is used as reference.	

Parameter	Type	Default	Unit	Description	Scope
rqrsgmax	R	1.0		This value determines the height of the vertical	$lhn\_qrs = .TRUE.$
				averaging, to obtain the reference precipitation	
				rate	
				It is the model layer where the quotion of the	
				maximal precipitation flux occurred for the first	
				time.	
lhn_hum_adj	L	.TRUE.		Apply an increment of specific humidity with	
				respect to the estimated temperature increment	
				to maintain the relative humidty	
$lhn\_no\_ttend$	L	.FALSE.		Only apply moisture increments. Temperature	$lhn\_hum\_adj=.TRUE.$
				increments will only be used for calculation of	
				moisture increments	
lhn_incloud	L	.TRUE.		Apply increments only in model layers where the	lhn_artif_only=.FALSE.
				underlying latent heat release of the model is	
				positive.	
$lhn\_limit$	L	.TRUE.		Limitation of temperature increments	abs_lhn_lim
abs_lhn_lim	R	50./3600.	m K/s	Lower and upper limit for temperature	$lhn_limit = .TRUE.$
				increments to be added.	
$lhn\_filt$	L	.TRUE.		Vertical smoothing of the profile of temperature	
				increments	
lhn_relax	L	.FALSE.		Horizontal smoothing of radar data but also of	nlhn_relax
				incorporated model fields	
$nlhn\_relax$	I	2	$\operatorname{grid}$	Number of horizontal grid point, where	$ln_{relax} = .TRUE.$
			points	smoothing is applied.	
lhn_artif	L	.TRUE.		Apply an artificial temperature profile to	fac_lhn_artif, tt_artif_max,
				estimate increments at model grid points	zlev_artif_max, std_artif_ma
				without significant precipitation (determined by	
				fac_lhn_artif).	
fac_lhn_artif	R	5.0		Value of the ratio of radar to model precipitation	$lhn_{artif}=.TRUE.$
				rate, from which an artificial temperature profile	
				is applied	
lhn_artif_only	$\mid L \mid$	.FALSE.		Scaling the artificial temperature profile instead	tt_artif_max,
				of local model profile of latent heat release for	zlev_artif_max,
				calculation the increments at any model grid	std_artif_max
				point.	
				The scaling factor is still be determined by the	
				ratio of observed to modelled precipitation rate.	
tt_artif_max	R	0.0015	K	Maximal temperature of Gaussian shaped	lhn_artif, lhn_artif_only
				function used a artificial temperature profile.	
zlev_artif_max	R	1000.0	m	Height of maximum of Gaussian shaped function	lhn_artif, lhn_artif_only
				used a artificial temperature profile.	
$std\_artif\_max$	R	4.0	m	Parameter defining width of Gaussian shaped	lhn_artif, lhn_artif_only
				function used a artificial temperature profile.	
nlhnverif_start	I	-9999	S	time in seconds when online verification within	$run_nml:ldass_lhn = .true.$
				LHN is active for the first time	

Parameter	Type	Default	Unit	Description	Scope
nlhnverif_end	I	-9999	s	time in seconds when online verification within	$run_nml:ldass_lhn = .true.$
				LHN is active for the last time	
lhn_diag	L	.FALSE.		Enable a extensive diagnostic output, writing	
				into file lhn.log.	
				lhn_diag is set .TRUE. automatically, when	
				online verification is active.	
lhn_dt_obs	R	300.0	s	Frequency of the radar observations	
radar_in	C	'/'		Path where the radar data file is expected.	
radardata_file(:)	C			Name of the radar data file. This might be	
	$(n\_dom)$			either in GRIB2 or in NetCDF (recommended).	
lhn_black	L	.FALSE.		Apply a blacklist information in the radar data	
				obtained by comparison against satelite clound	
				information	
blacklist_file(:)	C			Name of blacklist file, containing a mask	lhn_black=.TRUE.
	$(n\_dom)$			concerning the quality of the radar data.	
				Value 1: good quality	
				Value 0: bad quality	
				This might be either in GRIB2 or in NetCDF	
				(recommended).	
lhn_bright	L	.FALSE.		Apply a model intern bright band detection to	
				avoid strong overestimation due to uncertain	
				radar observations.	
height_file(:)	C			Name of file containing the height of the lowest	lhn_bright=.TRUE.
	(n_dom)			scan for each possible radar station within the	
				given radar composite.	
				This file is required, when applying bright band	
				detection.	
				This might be either in GRIB2 or in NetCDF	
				(recommended).	
nradar	I	200		Maximal number of radar station contained	lhn_bright=.TRUE.
	$\mid (n\_dom)$			within height_file	

Defined and used in: src/namelists/mo\_assimilation\_nml.f90

# 2.2. coupling\_mode\_nml

Parameter	Type	Default	Unit	Description	Scope
coupled_mode	L	.FALSE.		.TRUE.: if yac coupling routines have to be	
				called	

Defined and used in: src/namelists/mo\_coupling\_nml.f90

# 2.3. diffusion\_nml

Parameter	Type	Default	Unit	Description	Scope
lhdiff temp	L	.TRUE.		Diffusion on the temperature field	
lhdiff vn	L	.TRUE.		Diffusion on the horizontal wind field	
lhdiff w	L	.TRUE.		Diffusion on the vertical wind field	
hdiff order	I	4 (hydro)		Order of $\nabla$ operator for diffusion:	Options 2, 24 and 42 are
_		5 (NH)		-1: no diffusion	allowed only in the hydrostatic
				2: $\nabla^2$ diffusion	atm model (iequations = 1 or 2)
				3: Smagorinsky $\nabla^2$ diffusion	in dynamics nml).
				4: $\nabla^4$ diffusion	_ ,
				5: Smagorinsky $\nabla^2$ diffusion combined with $\nabla^4$	
				background diffusion as specified via	
				hdiff efdt ratio	
				$24 \text{ or } 42$ : $\nabla 2$ diffusion from model top to a	
				certain level (cf. k2 pres max and	
				k2 klev max below); $\nabla^4$ for the lower levels.	
lsmag_3d	L	.FALSE.		.TRUE.: Use 3D Smagorinsky formulation for	hdiff order=3 or 5;
0_				computing the horizontal diffusion coefficient	itype_vn_diffu=1
				(recommended at mesh sizes finer than 1 km if	J F
				the LES turbulence scheme is not used)	
itype vn diffu	I	1		Reconstruction method used for Smagorinsky	iequations=3, hdiff order=3
J I				diffusion:	$\begin{array}{cccccccccccccccccccccccccccccccccccc$
				1: u/v reconstruction at vertices only	
				2: u/v reconstruction at cells and vertices	
itype t diffu	1	2		Discretization of temperature diffusion:	iequations=3, hdiff order=3
J I				1: $K_h \nabla^2 T$	$\begin{array}{cccccccccccccccccccccccccccccccccccc$
				$2: \nabla \cdot (K_h \nabla T)$	
k2 pres max	$\mid$ R	-99.	Pa	Pressure level above which $\nabla^2$ diffusion is	hdiff order = 24 or 42, and
				applied.	$\frac{-}{\text{dynamics nml:iequations}} = 1$
					$\int_{0}^{\infty} \frac{1}{2}$
k2 klev max	I	0		Index of the vertical level till which (from the	hdiff order = 24 or 42, and
				model top) $\nabla^2$ diffusion is applied. If a positive	$\frac{-}{\text{dynamics}\_\text{nml:iequations}} = 1$
				value is specified for k2 pres max,	$\int_{0}^{\infty} \frac{1}{2}$
				k2 klev max is reset accordingly during the	
				initialization of a model run.	
hdiff efdt ratio	$\mid$ R	1.0 (hydro)		ratio of e-folding time to time step (or 2* time	
		36.0 (NH)		step when using a 3 time level time stepping	
				scheme) (for triangular NH model, values above	
				30 are recommended when using hdiff order=5)	
hdiff w efdt ratio	$\mid$ R	15.0		ratio of e-folding time to time step for diffusion	iequations=3
				on vertical wind speed	
hdiff min efdt ratio	$\mid$ R	1.0		minimum value of hdiff efdt ratio near model	iequations=3 . AND.
				top	hdiff order=4

Parameter	Type	Default	Unit	Description	Scope
hdiff_tv_ratio	R	1.0		Ratio of diffusion coefficients for temperature	
				and normal wind: $T:v_n$	
hdiff_multfac	R	1.0		Multiplication factor of normalized diffusion	n_dom>1
				coefficient for nested domains	
hdiff smag fac	R	0.15 (hydro)		Scaling factor for Smagorinsky diffusion	iequations=3
		0.015  (NH)			

Defined and used in: src/namelists/mo\_diffusion\_nml.f90

## 2.4. dynamics nml

This namelist is relevant if run nml:ldynamics=.TRUE.

Parameter	Type	Default	Unit	Description	Scope
iequations	I	3		Equations and prognostic variables. Use positive	
				indices for the atmosphere and negative indices	
				for the ocean.	
				0: shallow water model	
				1: hydrostatic atmosphere, T	
				2: hydrostatic atm., $\theta$ -dp	
				3: non-hydrostatic atmosphere	
				-1: hydrostatic ocean	
idiv_method	I	1		Method for divergence computation:	
				1: Standard Gaussian integral.	
				Hydrostatic atm. model: for unaveraged normal	
				$\operatorname{components}$	
				Non-hydrostatic atm. model: for averaged	
				normal components	
				2: bilinear averaging of divergence	
divavg_cntrwgt	R	0.5		Weight of central cell for divergence averaging	$idiv\_method = 2$
lcoriolis	L	.TRUE.		Coriolis force	
sw_ref_height	R	$0.9*\ 2.94e4/g$	m	Reference height of shallow water model used for	
				linearization in the semi-implicit time stepping	
				scheme	

Defined and used in:  $src/namelists/mo_dynamics_nml.f90$ 

## 2.5. echam cld nml

The parameterization of cloud microphysics for the ECHAM physics is configured by a data structure  $echam\_cld\_config(jg=1:ndom)\% < param>$ , which is a 1-dimensional array extending over all domains. The structure contains parameters providing control over the parametrized effects:

Parameter	Type	Default	Unit	Description	Scope
echam_cld_config(jg)% zmaxcld	R	echam_phy_config zmaxcloudy	g(:)%	maximum height for cloud physics computations	$\begin{array}{l} echam\_phy\_config(jg)\% \\ dt\_cld > 0.000s \end{array}$

Parameter	Type	Default	Unit	Description	Scope
echam_cld_config(jg)% ccwmin	R	1.0e-7	kg/kg	cloud water and ice minimum mass mixing ratio	echam_phy_config(jg)%
echam_cld_config(jg)% cqtmin	R	1.0e-12	m kg/kg	for cover>0 cloud water/ice minimum for microphysical processes	$ \begin{array}{l} dt\_cld > 0.000s \\ echam\_phy\_config(jg)\% \\ dt\_cld > 0.000s \end{array} $
echam_cld_config(jg)% cthomi	R	$egin{array}{c} { m Tmelt} ext{-}35 = \ 238.15 \end{array}$	K	maximum temperature for homogeneous freezing	echam_phy_config(jg)% dt_cld > 0.000s
echam_cld_config(jg)% csecfrl	R	5.0e-6	kg/kg	minimum in-cloud water mass mixing ratio in mixed phase clouds	$\begin{array}{c} - \\ \mathrm{echam\_phy\_config(jg)\%} \\ \mathrm{dt} \ \ \mathrm{cld} > 0.000 \mathrm{s} \end{array}$
echam_cld_config(jg)% ccraut	R	15.		coefficient of autoconversion of cloud droplets to rain	$\begin{array}{c} -\text{ccham\_phy\_config(jg)}\% \\ \text{dt. cld} > 0.000 \text{s} \end{array}$
echam_cld_config(jg)% ccracl	R	6.		coefficient of accretion of cloud droplets by falling rain	$\operatorname{ccham\_phy\_config(jg)\%} $ $\operatorname{dt} \ \operatorname{cld} > 0.000 \operatorname{s}$
echam_cld_config(jg)% cauloc	R	10.		coefficient of local rainwater production by autoconversion	echam_phy_config(jg)% dt_cld > 0.000s
echam_cld_config(jg)% clmin	R	0.0		minimum for cauloc*dz/5000	echam_phy_config(jg)% dt_cld > 0.000s
echam_cld_config(jg)% clmax	R	0.5		maximum for cauloc* $dz/5000$	echam_phy_config(jg)% dt_cld > 0.000s
echam_cld_config(jg)% cvtfall	R	2.5		coefficient of sedimentation velocity of cloud ice	echam_phy_config(jg)% dt_cld > 0.000s
echam_cld_config(jg)% ceffmin	R	10.	1.e-6 m	min effective radius for ice cloud	echam_phy_config(jg)% dt_cld > 0.000s
echam_cld_config(jg)% ceffmax	R	150.	1.e-6 m	max effective radius for ice cloud	$\begin{array}{l} \text{dt\_chl} > 0.0008\\ \text{echam\_phy\_config(jg)}\%\\ \text{dt\_cld} > 0.0008 \end{array}$
echam_cld_config(jg)% crhoi	R	500.	m kg/m3	density of cloud ice	$\begin{array}{l} \text{dt\_chl} > 0.0008\\ \text{echam\_phy\_config(jg)}\%\\ \text{dt\_cld} > 0.0008 \end{array}$
echam_cld_config(jg)% crhosno	R	100.	m kg/m3	bulk density of snow	$\begin{array}{l} \text{dt\_chd} > 0.0008\\ \text{echam\_phy\_config(jg)}\%\\ \text{dt\_cld} > 0.0008 \end{array}$
echam_cld_config(jg)% ccsaut	R	95.0		coefficient of autoconversion of cloud ice to snow	echam_phy_config(jg)% dt_cld > 0.000s
echam_cld_config(jg)% ccsacl	R	0.1		coefficient of accretion of cloud droplets by falling snow	echam_phy_config(jg)% dt_cld > 0.000s
echam_cld_config(jg)% cn1lnd	R	defval	$1\mathrm{e}6/\mathrm{m}3$	cloud droplet number concentration over land, p <= 100 hPa	echam_phy_config(jg)% dt_cld > 0.000s
echam_cld_config(jg)% cn2lnd	R	defval	$1\mathrm{e}6/\mathrm{m}3$	cloud droplet number concentration over land, p >= 800 hPa	echam_phy_config(jg)% dt_cld > 0.000s
echam_cld_config(jg)% cn1sea	R	defval	$1\mathrm{e}6/\mathrm{m}3$	cloud droplet number concentration over sea, p <= 100 hPa	echam_phy_config(jg)% dt_cld > 0.000s
echam_cld_config(jg)% cn2sea	R	defval	$1\mathrm{e}6/\mathrm{m}3$	cloud droplet number concentration over sea, p >= 800 hPa	echam_phy_config(jg)% dt_cld > 0.000s
echam_cld_config(jg)% cinhomi	R	0.8		ice cloud inhomogeneity factor	echam_phy_config(jg)% dt_cld > 0.000s
echam_cld_config(jg)% cinhoml1	R	0.8		liquid cloud inhomogeneity factor, ktype $= 0 =$ stratiform clouds	$\begin{array}{l} \text{dt\_cid} > 0.000s \\ \text{echam\_phy\_config(jg)\%} \\ \text{dt\_cld} > 0.000s \end{array}$

Parameter	Type	Default	Unit	Description	Scope
echam_cld_config(jg)% cinhoml2	R	0.4		liquid cloud inhomogeneity factor, ktype = 4 =	echam_phy_config(jg)%
				shallow conv. (cf. clwprat)	$ m dt\_cld > 0.000s$
$- echam\_cld\_config(jg)\% cinhoml3$	R	0.8		liquid cloud inhomogeneity factor, ktype $= 1 =$	echam_phy_config(jg)%
				deep convection and $ktype = 2 = shallow conv.$	$ m dt\_cld > 0.000s$
				(cf. clwprat) and ktype $= 3 = \text{mid-level conv.}$	
echam_cld_config(jg)% clwprat	R	4.0		critical ratio of cloud liq.+ice paths below and	echam_phy_config(jg)%
				above the top of shallow convection; for ratio >	$ m dt\_cld > 0.000s$
				clwprat -> change ktype from 2 to 4	
$\operatorname{echam\_cld\_config(jg)}\%$ ncctop	I	13		index of highest level for tropopause calculation	echam_phy_config(jg)%
					$ m dt\_cld > 0.000s$
$\operatorname{echam\_cld\_config(jg)}\%$ nccbot	I	35		index of lowest level for tropopause calculation	echam_phy_config(jg)%
					$ m dt\_cld > 0.000s$

## 2.6. echam\_cnv\_nml

The parameterization of convection for the ECHAM physics is configured by a data structure  $echam\_cnv\_config(jg=1:ndom)\% < param>$ , which is a 1-dimensional array extending over all domains. The structure contains parameters providing control over the parametrized effects:

Parameter	Type	Default   Unit	Description	Scope
% echam_cnv_config(jg)% lmfpen	L	.TRUE.	Switch on penetrative convection.	$echam\_phy\_config(jg)\%$
				$dt_{cnv} > 0.000s$
echam_cnv_config(jg)% lmfmid	L	.TRUE.	Switch on midlevel convection.	$echam\_phy\_config(jg)\%$
				$dt_{cnv} > 0.000s$
echam_cnv_config(jg)% lmfdd	L	.TRUE.	Switch on cumulus downdraft.	echam_phy_config(jg)%
				$dt_{cnv} > 0.000s$
echam_cnv_config(jg)% lmfdudv	L	.TRUE.	Switch on cumulus friction.	echam_phy_config(jg)%
				$dt_{cnv} > 0.000s$
echam_cnv_config(jg)% entrmid	R	2.0e-4	Entrainment rate for midlevel convection.	$echam\_phy\_config(jg)\%$
				$dt\_cnv > 0.000s$
echam_cnv_config(jg)% entrscv	R	3.0e-3	Entrainment rate for shallow convection.	$\begin{array}{ c c c c c c c c c c c c c c c c c c c$
				$dt\_cnv > 0.000s$
$- echam\_cnv\_config(jg)\% entrpen$	R	2.0e-4	Entrainment rate for penetrative convection.	echam_phy_config(jg)%
				$dt\_cnv > 0.000s$
echam_cnv_config(jg)% entrdd	R	4.0e-4	Entrainment rate for cumulus downdrafts.	echam_phy_config(jg)%
				$dt_{-}cnv > 0.000s$
echam_cnv_config(jg)% cprcon	R	2.5e-4	Coefficient for determining conversion from	echam_phy_config(jg)%
			cloud water to rain.	dt $cnv > 0.000s$
echam_cnv_config(jg)% cmfctop	R	0.2	Fractional convective mass flux across the top of	echam_phy_config(jg)%
2 (1) 24			cloud.	dt = cnv > 0.000s
echam_cnv_config(jg)% cmfdeps	R	0.3	Fractional convective mass flux for downdrafts	echam_phy_config(jg)%
			at lfs.	dt = cnv > 0.000s
echam_cnv_config(jg)% cminbuoy	R	0.02	Minimum excess buoyancy.	echam_phy_config(jg)%
				dt = cnv > 0.000s
echam_cnv_config(jg)% cmaxbuoy	R	1.0	Maximum excess buoyancy.	echam_phy_config(jg)%
				$  dt\_cnv > 0.000s $

Parameter	Type	Default	Unit	Description	Scope
echam_cnv_config(jg)% cbfac	R	1.0		Factor for std dev of virtual pot temp.	echam_phy_config(jg)% dt cnv > 0.000s
echam_cnv_config(jg)% centrmax	R	3.0e-4		Maximum entrainment/detrainment rate.	echam_phy_config(jg)% dt cnv > 0.000s
echam_cnv_config(jg)% dlev_land	R	0	Pa	Minimum pressure thickness of clouds for precipitation over land.	echam_phy_config(jg)% dt cnv > 0.000s
echam_cnv_config(jg)% dlev_ocean	R	0	Pa	Minimum pressure thickness of clouds for precipitation over ocean.	echam_phy_config(jg)% dt cnv > 0.000s
echam_cnv_config(jg)% cmftau	R	3600.		Characteristic convective adjustment time scale.	echam_phy_config(jg)% dt cnv > 0.000s
echam_cnv_config(jg)% cmfcmin	R	1.0e-10		Minimum massflux value (for safety).	echam_phy_config(jg)% dt cnv > 0.000s
echam_cnv_config(jg)% cmfcmax	R	1.0		Maximum massflux value for updrafts.	echam_phy_config(jg)% dt_cnv > 0.000s

### 2.7. echam cov nml

The parameterization of cloud cover for the ECHAM physics is configured by a data structure  $echam\_cov\_config(jg=1:ndom)\% < param>$ , which is a 1-dimensional array extending over all domains. The structure contains the following control parameters:

Parameter	Type	Default	Unit	Description	Scope
echam_cov_config(jg)% zmaxcov	R	echam_phy_o	config(:)%	maximum height for cloud cover computation	
		zmaxcloudy			
echam_cov_config(jg)% icov	I	1		selects cloud cover scheme	
				1: fractional cloud cover based on rel. humidity	
				2: 0/1 cloud cover based on rel. humidity	
echam_cov_config(jg)% csat	R	1.0		relative humidity at which cloud cover is 1	
echam_cov_config(jg)% crs	R	0.968		critical relative humidity at surface	icov = 1
echam_cov_config(jg)% crt	R	0.8		critical relative humidity aloft	icov = 1
echam_cov_config(jg)% nex	I	2		transition parameter for critical relative	icov = 1
				humidity profile	
echam_cov_config(jg)% zinvmin	$\mathbb{R}$	200.	m	minimum height above sea level for search of	icov = 1
				inversion layer	
echam_cov_config(jg)% zinvmax	$\mathbb{R}$	2000.	m	maximum height above sea level for search of	icov = 1
				inversion layer	
echam_cov_config(jg)% cinv	$\mathbb{R}$	0.25		fraction of dry adiabatic lapse rate for search of	icov = 1
				top level of inversion layer over sea	
echam_cov_config(jg)% csatsc	$\mathbb{R}$	0.7		minimum effective saturation for cloud cover	icov = 1
				below an inversion layer over sea	

### 2.8. echam gwd nml

The parameterization of atmospheric gravity waves for the ECHAM physics is configured by a data structure  $echam\_gwd\_config(jg=1:ndom)\% < param>$ , which is a 1-dimensional array extending over all domains. The structure contains parameters providing control over the parametrized effects:

Parameter	Type	Default	Unit	Description	Scope
echam_gwd_config(jg)% lheatcal	L	.FALSE.		.TRUE.: compute drag, heating rate and	echam_phy_config(jg)%
				diffusion coefficient from the dissipation of	$dt_gwd > 0.000s$
				gravity waves	
				.FALSE.: compute drag only	
echam_gwd_config(jg)% emiss_lev	I	10		Index of model level, counted from the surface,	echam_phy_config(jg)%
				from which the gravity wave spectra are emitted	$dt_gwd > 0.000s$
echam_gwd_config(jg)% rmscon	R	0.87	m/s	Root mean square gravity wave wind at the	$echam\_phy\_config(jg)\%$
				emission level	$dt_gwd > 0.000s$
echam_gwd_config(jg)% kstar	R	5.0e-5	1/m	Typical gravity wave horizontal wavenumber	echam_phy_config(jg)%
					$dt_gwd > 0.000s$
$-$ echam_gwd_config(jg)% m_min	R	0.0	1/m	Minimum bound in vertical wavenumber	echam_phy_config(jg)%
					$ m dt\_gwd > 0.000s$

#### 2.9. echam phy nml

The ECHAM physics is configured by a data structure  $echam\_phy\_config(jg=1:ndom)\%<param>$ , which is a 1-dimensional array extending over all domains. The structure contains several parameters providing time control for the atmospheric forcing by the different parameterizations and additional logical switches for controlling the coupling between the parameterizations of the physics and between the dynamics and the physics. Further logical switches control how the atmospheric boundary conditions for the ECHAM physics are determined. Time control parameters are available for the following atmospheric processes:

prc	$parameterized\ process$
$\operatorname{rad}$	LW and SW radiation
vdf	vertical diffusion
$\operatorname{cnv}$	${ m cumulus}\ { m convection}$
$\operatorname{cld}$	cloud microphysics
$\operatorname{gwd}$	atmospheric gravity wave drag
sso	sub grid scale orographic effects
mox	methane oxidation and water vapor photolysis
car	Cariolle's linearized ozone chemistry
art	ART chemistry

The time control for an atmospheric forcing by a process prc consists of three components, the time interval  $dt\_prc$  for re-computing the forcing, and the start and end dates and times defining the interval  $[sd\_prc, ed\_prc]$ , in which the forcing is either computed, if the date/time coincides with the interval  $dt\_prc$ , or recycled. Recycling means that the forcing stored from the last computation is used again. Outside of the interval the forcing is set to zero.

If  $dt\_prc$  is not specified, or an empty string or a string of blanks or an interval of length 0s, e.g. "PT0S" is given, then the forcing is switched off for the entire experiment and the start and end dates and times are irrelevant.

If  $sd\_prc$  or  $ed\_prc$  are not specified, or an empty string or a string of blanks are given, then the experiment start date and the experiment stop date are used, respectively. Further the forcing control switch fc\\_prc can be used to decide if an active process (dt\_prc > 0) is used for the integration (fc\_prc = 1) or only computed for diagnostic purposes (fc\_prc = 0).

Parameter	Type	Default	Unit	Description	Scope
echam_phy_config(jg)% dt_prc	С	""		This is the time interval in ISO 8601-2004 format at which the forcing by the process prc is computed.	$run\_nml/iforcing = 2$

Parameter	Type	Default	Unit	Description	Scope
echam_phy_config(jg)% sd_prc	С	""		Defines the start date/time in ISO 8601-2004	${ m run\_nml/iforcing} = 2 { m \ and}$
				format of the interval [sd_prc,ed_prc], in which	$dt\_prc > 0.000 \mathrm{s}$
				the forcing by the process prc is computed in	
				intervals $dt_prc$ .	
$-$ echam_phy_config(jg)% ed_prc	C	""		Defines the end date/time in ISO 8601-2004	$-\operatorname{run\_nml/iforcing} = 2 \text{ and }$
				format of the interval [sd_prc,ed_prc], in which	$dt\_prc > 0.000 \mathrm{s}$
				the forcing by the process prc is computed in	
				intervals $dt\_prc$ .	
$-\operatorname{echam}_{\operatorname{phy}}_{\operatorname{config}}(jg)\%$ fc_prc	I	1		Forcing control for process <i>prc</i> .	$-\operatorname{run\_nml/iforcing} = 2 \text{ and }$
				$fc\_prc = 0$ : the forcing of the process is not	$dt\_prc > 0.000 \mathrm{s}$
				used in the integration.	
				fc_prc = 1: the forcing of the process is used in	
				the integration.	
$\operatorname{echam\_phy\_config(jg)}\%$ lice	L	.FALSE.		.TRUE. for sea-ice temperature calculation	$- \operatorname{run\_nml/iforcing} = 2$
$\operatorname{echam\_phy\_config(jg)\%\ lmlo}$	L	.FALSE.		.TRUE. for mixed layer ocean	$- \text{run\_nml/iforcing} = 2$
$\operatorname{echam}_{\operatorname{phy}_{\operatorname{config}}(jg)\%}$ ljsb	L	.FALSE.		TRUE. for using the JSBACH land surface	$- \operatorname{run\_nml/iforcing} = 2$
				model	
echam_phy_config(jg)% lamip	L	.FALSE.		.TRUE. for AMIP boundary conditions	$- \text{run\_nml/iforcing} = 2$
$\operatorname{echam\_phy\_config(jg)}\% \ \operatorname{iqneg\_d2p}$	I	0		If negative tracer mass fractions are found in the	$-\operatorname{run\_nml/iforcing} = 2$
				dynamics to physics interface, then:	
				1,3: they are reported;	
				2,3: they are replaced with zero	
$- echam\_phy\_config(jg)\% iqneg\_p2d$	I	0		If negative tracer mass fractions are found in the	$\begin{array}{ c c c c c c c c c c c c c c c c c c c$
				dynamics to physics interface, then:	
				1,3: they are reported;	
				2,3: they are replaced with zero	
echam_phy_config(jg)% zmaxcloudy	R	33000.	m	maximum height for clouds	

## 2.10. echam\_rad\_nml

The input from ECHAM physics to the PSrad scheme is configured by a data structure  $echam\_rad\_config(jg=1:ndom)\% < param>$ , which is a 1-dimensional array extending over all domains. The structure contains parameters providing control over the Earth orbit, the computation of the SW incoming flux at the top of the atmosphere and the atmospheric composition:

Parameter	Type	Default	Unit	Description	Scope
echam_rad_config(jg)% isolrad	I	0		Selects the spectral solar irradiation (SSI) at 1 AU distance from the sun 0: SSI of the SRTM scheme, TSI = 1368.222 Wm2. 1: SSI from an external file containing monthly mean time series 2: Average 1844–1856 of the SSI time series provided for CMIP5, TSI = 1360.875 W/m2 3: Average 1979–1988 of the SSI time series provided for CMIP5, TSI = 1361.371 W/m2 4: SSI for RCE-type simulation with diurnal cycle, TSI = 1069.315 W/m2 5: SSI for RCE-type simulation without diurnal cycle, TSI = 433.3371 W/m2 6: Average 1850-1873 of the SSI time series provided for CMIP6, TSI = 1360.744 W/m2	echam_phy_config(jg)% dt_rad > 0.000s
${\it echam\_rad\_config(jg)\%\ fsolrad}$	R	1		Scaling factor for the SSI	echam_phy_config(jg)% dt rad > 0.000s
${\rm echam\_rad\_config(jg)\%\ l\_orbvsop87}$	L	.TRUE.		.TRUE. for the realistic VSOP87 Earth orbit .FALSE. for the Kepler orbit	echam_phy_config(jg)% dt_rad > 0.000s
${\rm echam\_rad\_config(jg)\%\ cecc}$	R	0.016715		eccentricity of the Kepler orbit	echam_phy_config(jg)% dt_rad > 0.000s and l orbvsop87 = .FALSE.
echam_rad_config(jg)% cobld	R	23.44100	deg	obliquity of the Earth rotation axis on the Kepler orbit	echam_phy_config(jg)% dt_rad > 0.000s and l orbvsop87 = .FALSE.
${\it echam\_rad\_config(jg)\%\ clonp}$	R	282.7000	deg	longitude of perihelion with respect to vernal equinox on the Kepler orbit	echam_phy_config(jg)% dt_rad > 0.000s and l orbvsop87 = .FALSE.
echam_rad_config(jg)% lyr_perp	L	.FALSE.		.FALSE. for transient VSOP87 Earth orbit .TRUE.: VSOP87 Earth orbit of year yr_perp is perpertuated	echam_phy_config(jg)% dt_rad > 0.000s and l orbvsop87 = .TRUE.
echam_rad_config(jg)% yr_perp	L	-99999		year to be used for lyr_perp = .TRUE.	echam_phy_config(jg)% dt_rad > 0.000s and l orbvsop87 = .TRUE.
$echam\_rad\_config(jg)\%\ nmonth$	I	0		0: Earth circles on orbit 1-12: Earth orbit position fixed for specified month	echam_phy_config(jg)% dt_rad > 0.000s
$echam\_rad\_config(jg)\%\ ldiur$	L	.TRUE.		.TRUE. for diurnal cycle in solar irradiation .FALSE. for zonally averaged solar irradiation	echam_phy_config(jg)% dt rad > 0.000s
echam_rad_config(jg)% l_sph_symm_irr	L	.FALSE.		.TRUE. for a horizontally independent solar irradiation; .FALSE. for a horizontally resolved solar irradiation	20_100

Parameter	Type	Default	Unit	Description	Scope
echam_rad_config(jg)% irad_h2o	I			Selects source for concentration of water vapor, cloud water and cloud ice 0: set to zero (or epsilon)	echam_phy_config(jg)% dt_rad > 0.000s
				1: from tracer	
echam_rad_config(jg)% irad_co2	I	2		Selects source for concentration of CO2  0: set to zero (or epsilon)  1: from tracer  2: constant vol. mixing ration set by 'vmr co2'	echam_phy_config(jg)% dt_rad > 0.000s and CO2 tracer is defined
				4: spatially constant, time dependent vol. mixing ratio from file	
echam_rad_config(jg)% irad_ch4	I	3		Selects source for concentration of CH4  0: set to zero (or epsilon)  2: constant vol. mixing ration set by 'vmr _ch4'  3: horizontally constant, vertically decaying,	$\begin{array}{l} {\rm echam\_phy\_config(jg)\%} \\ {\rm dt\_rad} > 0.000 {\rm s} \end{array}$
				with surface vol. mixing ratio set by 'vmr _ch4' 4: horizontally constant, vertically decaying, time dependent with surface vol. mixing ratio from file	
echam_rad_config(jg)% irad_n2o	I	3		Selects source for concentration of N2O  0: set to zero (or epsilon)  2: constant vol. mixing ration set by 'vmr _n2o'  3: horizontally constant, vertically decaying, with surface vol. mixing ratio set by 'vmr _n2o'  4: horizontally constant, vertically decaying, time dependent with surface vol. mixing ratio	$ \begin{array}{l} echam\_phy\_config(jg)\% \\ dt\_rad > 0.000s \end{array} $
echam_rad_config(jg)% irad_o3	I	0		from file Selects source for concentration of O3 0: set to zero (or epsilon) 1: from tracer 2: 3-dim concentration, climatological annual cycle, monthly means from an annual file bc_ozone_picontrol.nc 4: 3-dim concentration, constant in time, 1st time slice file bc_ozone_picontrol.nc 8: 3-dim concentration, time dependent,	$ \begin{array}{l} echam\_phy\_config(jg)\% \\ dt\_rad > 0.000s \end{array} $
${\it echam\_rad\_config(jg)\%\ irad\_o2}$	I	2		monthly means from yearly files bc_ozone_historical_ <year>.nc Selects source for concentration of O2 0: set to zero (or epsilon) 2: constant vol. mixing ration set by 'vmr_o2'</year>	$ \begin{array}{l} echam\_phy\_config(jg)\% \\ dt\_rad > 0.000s \end{array} $

Parameter	Type	Default	Unit	Description	Scope
echam_rad_config(jg)% irad_cfc11	I	2		Selects source for concentration of CFC11 0: set to zero (or epsilon) 2: constant vol. mixing ration set by 'vmr	$\begin{array}{l} echam\_phy\_config(jg)\% \\ dt\_rad > 0.000s \end{array}$
				_cfc11' 4: spatially constant, time dependent vol.	
echam_rad_config(jg)% irad_cfc12	I	2		mixing ratio from file Selects source for concentration of CFC12	echam_phy_config(jg)%
				0: set to zero (or epsilon) 2: constant vol. mixing ration set by 'vmr	$ m dt\_rad > 0.000s$
				_cfc12' 4: spatially constant, time dependent vol.	
echam_rad_config(jg)% irad_aero	I	2		mixing ratio from file Selects source for concentration of XYZ	$\begin{array}{c} & & \\ & \text{echam\_phy\_config(jg)}\% \end{array}$
				13: tropospheric 'Kinne' aerosols, time dependent from file	$ m dt\_rad > 0.000s$
				14: stratospheric 'Stenchikov' aerosols, time	
				dependent from file 15: tropospheric 'Kinne' aerosols + stratospheric	
				'Stenchikov' aerosols, time dependent, both from file	
				18: tropospheric natural 'Kinne' aerosols for	
				1850 + time dep. stratospheric 'Stenchikov' aerosols, both from file + param. time dep.	
				antropogenic 'simple plumes' any other: set to zero	
${\it echam\_rad\_config(jg)\%~vmr\_co2}$	R	348.0e-06	m3/m3	Volume mixing ratio of CO2	$\begin{array}{c} {\rm echam\_phy\_config(jg)\%} \\ {\rm dt}  {\rm rad} > 0.000 {\rm s} \end{array}$
echam_rad_config(jg)% vmr_ch4	R	1650.0e-09	m3/m3	Volume mixing ratio of CH4	dt_rad > 0.000s   echam_phy_config(jg)%   dt_rad > 0.000s
echam_rad_config(jg)% vmr_n2o	R	306.0e-09	m3/m3	Volume mixing ratio of N2O	echam_phy_config(jg)% dt_rad > 0.000s
${\it echam\_rad\_config(jg)\%~vmr\_o2}$	R	0.20946	m3/m3	Volume mixing ratio of O2	echam_phy_config(jg)% dt_rad > 0.000s
echam_rad_config(jg)% vmr_cfc11	R	214.5e-12	m3/m3	Volume mixing ratio of CFC11	echam_phy_config(jg)% dt_rad > 0.000s
echam_rad_config(jg)% vmr_cfc12	R	371.1e-12	m3/m3	Volume mixing ratio of CFC11	echam_phy_config(jg)% dt_rad > 0.000s
echam_rad_config(jg)% frad_h2o	R	1.0		Scaling factor for concentration of water vapor, cloud water and cloud ice	echam_phy_config(jg)% dt_rad > 0.000s
echam_rad_config(jg)% frad_co2	R	1.0		Scaling factor for concentration of CO2	echam_phy_config(jg)% dt_rad > 0.000s
echam_rad_config(jg)% frad_ch4	R	1.0		Scaling factor for concentration of CH4	$\operatorname{ccham}_{\operatorname{phy}_{\operatorname{config}}(jg)}\%$ dt rad $> 0.000s$
echam_rad_config(jg)% frad_n2o	R	1.0		Scaling factor for concentration of N2O	$\operatorname{echam\_phy\_config(jg)}\%$ $\operatorname{dt} \operatorname{rad} > 0.000 \operatorname{s}$

Parameter	Type	Default	Unit	Description	Scope
$echam\_rad\_config(jg)\% \ frad\_o3$	R	1.0		Scaling factor for concentration of O3	$echam\_phy\_config(jg)\%$
					$ m dt\_rad > 0.000s$
$- \operatorname{echam\_rad\_config(jg)\% frad\_o2}$	R	1.0		Scaling factor for concentration of O2	$echam\_phy\_config(jg)\%$
					$ m dt\_rad > 0.000s$
$- \operatorname{echam\_rad\_config(jg)} \% \text{ frad\_cfc}$	R	1.0		Scaling factor for concentration of CFC11 and	$\operatorname{echam\_phy\_config(jg)}\%$
				CFC12	$ m dt\_rad > 0.000s$

### 2.11. echam sso nml

The parameterization of subgrid scale orographic (SSO) effects for the ECHAM physics is configured by a data structure  $echam\_sso\_config(jg=1:ndom)\% < param>$ , which is a 1-dimensional array extending over all domains. The structure contains parameters providing control over the parametrized effects:

Parameter	Type	Default	Unit	Description	Scope
echam_sso_config(jg)% gpicmea	R	40.	m	Minimum height difference of peak height and	$echam\_phy\_config(jg)\%$
				mean height to activate the SSO	$ m dt\_sso > 0.000s$
				parameterization.	
$\operatorname{echam\_sso\_config(jg)\%\ gstd}$	R	10.	m	Minimum standard deviation of the SSO height	$echam\_phy\_config(jg)\%$
				to activate the SSO parameterization.	$ m dt\_sso > 0.000s$
$-$ echam_sso_config(jg)% gkdrag	R	0.05		Coefficient for orographic gravity wave drag.	$echam\_phy\_config(jg)\%$
					$ m dt\_sso > 0.000s$
echam_sso_config(jg)% gkwake	R	0.		Coefficient for low level blocking.	$echam\_phy\_config(jg)\%$
					$ m dt\_sso > 0.000s$
echam_sso_config(jg)% gklift	R	0.		Coefficient for low level lift.	$echam\_phy\_config(jg)\%$
					$ m dt\_sso > 0.000s$
$-$ echam_sso_config(jg)% lsftlf	L	.TRUE.		.FALSE.: SSO effects are directly applied, for	$echam\_phy\_config(jg)\%$
				the case that SSO parameters are valid for the	$ m dt\_vdf > 0.000s$
				full cell area.	
				.TRUE.: SSO effects are scaled with the cell	
				area fraction of land including lakes (field sftlf),	
				for the case that SSO parameters are valid only	
				for this part of the cell area.	

### 2.12. echam vdf nml

The parameterization of vertical diffusion (VDF) for the ECHAM physics is configured by a data structure  $echam\_vdf\_config(jg=1:ndom)\% < param>$ , which is a 1-dimensional array extending over all domains. The structure contains parameters providing control over some of the parametrized effects:

Parameter	Type	Default	Unit	Description	Scope
$echam\_vdf\_config(jg)\%$	L	.TRUE.		switch on/off surface momentum flux	$echam\_phy\_config(jg)\%$
lsfc_mom_flux					$ m dt\_vdf > 0.000s$
echam_vdf_config(jg)% lsfc_heat_flux	L	.TRUE.		switch on/off surface heat flux	$echam_phy_config(jg)\%$
					$ m dt\_vdf > 0.000s$
$echam\_vdf\_config(jg)\% pr0$	R	1.0		neutral limit Prandtl number, can be varied	$echam_phy_config(jg)\%$
				from about 0.6 to 1.0	$ m dt\_vdf > 0.000s$

Parameter	Type	Default	Unit	Description	Scope
echam_vdf_config(jg)% f_tau0	R	0.17		neutral non-dimensional stress factor	echam_phy_config(jg)%
					$ m dt\_vdf > 0.000s$
echam_vdf_config(jg)% c_f	R	0.185		mixing length: coriolis term tuning parameter	echam_phy_config(jg)%
					$ m dt\_vdf > 0.000s$
$\operatorname{echam\_vdf\_config(jg)}\% \ \operatorname{c\_n}$	R	2.0		mixing length: stability term tuning parameter	echam_phy_config(jg)%
					$dt_vdf > 0.000s$
$\operatorname{echam\_vdf\_config(jg)}\%$ wmc	R	0.5		ratio of typical horizontal velocity to wstar at	$echam\_phy\_config(jg)\%$
				free convection	$dt_vdf > 0.000s$
$\operatorname{echam\_vdf\_config(jg)}\% \text{ fsl}$	R	0.4		fraction of first-level height at which surface	echam_phy_config(jg)%
				fluxes are nominally evaluated, tuning param for	$dt_vdf > 0.000s$
				sfc stress	
$\operatorname{echam\_vdf\_config(jg)}\% \text{ fbl}$	R	3.0		1/fbl: fraction of BL height at which lmix hat its	
				max	$ m dt\_vdf > 0.000s$

## 2.13. ensemble\_pert\_nml

Parameter	Type	Default	Unit	Description	Scope
use_ensemble_pert	L	.FALSE.		Main switch to activate physics parameter	$run_nml:iforcing = inwp$
				perturbations for ensemble forecasts / ensemble	
				data assimilation; the perturbations are applied	
				via random numbers depending on the	
				perturbationNumber (ensemble member ID)	
				specified in gribout_nml. Perturbations are	
				always turned off if perturbation Number $\leq 0$	
itype_pert_gen	I	1		Mode of ensemble perturbation generation	
				1: Equal distribution within perturbation range	
				2: Discrete distribution with 50% probability for	
				default value and $25\%$ probability for upper and	
				lower extrema	
timedep_pert	I	0		Time-dependence of ensemble perturbations	
				(except tkred_sfc, which oscillates with a time	
				scale of 20 days)	
				0: None	
				1: Random seed for perturbation generation	
				depends on initial date	
range_gkwake	R	0.5		Variability range for low level wake drag	
				$\operatorname{constant}$	
range_gkdrag	R	0.04		Variability range for orographic gravity wave	
				drag constant	
range_gfrcrit	R	0.1		Variability range for critical Froude number in	
				SSO scheme	
range_gfluxlaun	R	0.75e-3		Variability range for non-orographic gravity	
				wave launch momentum flux	

Parameter	Type	Default	Unit	Description	Scope
range_zvz0i	R	0.25	m/s	Variability range for terminal fall velocity of cloud ice	$inwp\_gscp = 1 \text{ or } 2$
range_rain_n0fac	R	4.		Multiplicative change of intercept parameter of raindrop size distribution	inwp_gscp = 1 or 2
range_entrorg	R	0.2e-3	1/m	Variability range for entrainment parameter in convection scheme	$inwp\_convection = 1$
range_rdepths	R	5.e3	Pa	Variability range for maximum allowed shallow convection depth	$inwp\_convection = 1$
range_rprcon	R	0.25e-3		Variability range for tuning parameter controlling conversion of cloud water into precipitation	$inwp\_convection = 1$
range_capdcfac_et	R	0.75		Maximum fraction of CAPE diurnal cycle correction applied in the extratropics	icapdcycl = 3
range_rhebc	R	0.05		Variability range for RH threshold for the onset of evaporation below cloud base	inwp_convection = 1
range_texc	R	0.05	K	Variability range for temperature excess value in test parcel ascent	$inwp\_convection = 1$
range_qexc	R	0.005		Variability range for mixing ratio excess value in test parcel ascent	inwp_convection = 1
range_box_liq	R	0.01		Variability range for box width scale of liquid clouds in cloud cover scheme	$inwp\_cldcover = 1$
range_box_liq_asy	R	0.25		Variability range for asymmetry factor for sub-grid scale liquid cloud distribution	$inwp\_cldcover = 1$
range_tkhmin	R	0.2	$\mathrm{m}^{2}\mathrm{s}^{-1}$	Variability range for minimum vertical diffusion for heat/moisture	$inwp\_turb = 1$
range_tkmmin	R	0.2	$\mathrm{m}^{2}\mathrm{s}^{-1}$	Variability range for minimum vertical diffusion for momentum	$inwp\_turb = 1$
range_turlen	R	150	m	Variability range for turbulent mixing length	$  inwp_turb = 1$
range_a_hshr	R	1		Variability range for scaling factor for extended horizontal shear term	$inwp\_turb = 1$
range_tkred_sfc	R	4.0		Range for multiplicative change of reduction of minimum diffusion coefficients near the surface	$inwp\_turb = 1$
range_rlam_heat	R	3.0		Variability range (multiplicative!) of laminar transport resistance parameter	$inwp\_turb = 1$
range_charnock	R	1.5		Variability range (multiplicative!) of upper and lower bound of wind-speed dependent Charnock parameter	$inwp\_turb = 1$
range_minsnowfrac	R	0.1		Variability range for minimum value to which snow cover fraction is artificially reduced in case of melting snow	$idiag\_snowfrac = 20/30/40$
range_c_soil	R	0.25		Variability range for evaporating fraction of soil	
range_cwimax_ml	R	2.0		Variability range for capacity of interception storage (multiplicative)	

Parameter	Type	Default	Unit	Description	Scope
range_z0_lcc	R	0.25		Variability range (relative change) of roughness	
				length attributed to each landuse class	
range_rootdp	R	0.2		Variability range (relative change) of root depth	
				attributed to each landuse class	
range_rsmin	R	0.2		Variability range (relative change) of minimum	
				stomata resistance attributed to each landuse	
				class	
range_laimax	R	0.15		Variability range (relative change) of leaf area	
				index (maximum of annual cycle) attributed to	
				each landuse class	
stdev_sst_pert	R	0.	K	Inserting the standard deviation of SST	
				perturbations (present in the model input data)	
				activates a correction factor for the saturation	
				vapor pressure over oceans, which compensates	
				the systematic increase of evaporation due to the	
				SST perturbations.	

Defined and used in: src/namelists/mo\_ensemble\_pert\_nml.f90

## 2.14. gribout\_nml

Parameter	Type	Default Unit	Description	Scope
preset	С	"determ"	Setting this different to "none" enables a couple	filetype=2
			of defaults for the other gribout_nml namelist	
			parameters. If, additionally, the user tries to set	
			any of these other parameters to a conflicting	
			value, an error message is thrown. Possible	
			values are "none", "deterministic", "ensemble".	
tablesVersion	I	15	Main switch for Table version	filetype=2
backgroundProcess	I	0	Background process	filetype=2
			- GRIB2 code table backgroundProcess.table	
generatingCenter	I	-1	Output generating center. If this key is not set,	filetype=2
			center information is taken from the grid file	
			DWD: 78	
			MPIMET: 98	
			ECMWF: 98	
generatingSubcenter	I	-1	Output generating Subcenter. If this key is not	filetype=2
			set, subcenter information is taken from the grid	
			file	
			DWD: 255	
			MPIMET: 232	
			ECMWF: 0	

Parameter	Type	Default	Unit	Description	Scope
generatingProcess	I(n_dom)	1		generating Process Identifier	filetype=2
Identifier				- GRIB2 code table	
				generatingProcessIdentifier.table	
numberOfForecastsIn- Ensemble	I	-1		Local definition for ensemble products, (only set	filetype=2
				if value changed from default)	
perturbationNumber	I	-1		Local definition for ensemble products, (only set	filetype=2
				if value changed from default)	
productionStatusOfPro-	I	1		Production status of data	filetype=2
cessedData				- GRIB2 code table 1.3	
significanceOfReference- Time	I	1		Significance of reference time	filetype=2
				- GRIB2 code table 1.2	
typeOfEnsembleForecast	I	-1		Local definition for ensemble products (only set if	filetype=2
				value changed from default)	
typeOfGeneratingPro- cess	I	-1		Type of generating process	filetype=2
				- GRIB2 code table 4.3	
typeOfProcessedData	I	-1		Type of data	filetype=2
				- GRIB2 code table 1.4	
localDefinitionNumber	I	-1		local Definition Number	filetype=2
				- GRIB2 code table	
				grib2LocalSectionNumber.78.table	
localNumberOfExperi- ment	I	1		local Number of Experiment	filetype=2
localTypeOfEnsemble-	I	-1		Local definition for ensemble products (only set if	filetype=2
Forecast				value changed from default)	
lspecialdate invar	$\mid$ L	.FALSE.		Special reference date for invariant and	filetype = 2
_				climatological fields	
				.TRUE.: set special reference date 0001-01-01,	
				00:00	
				.FASLE.: no special reference date	
ldate grib act	L	.TRUE.		GRIB creation date	filetype=2
				.TRUE.: add creation date	
				.FALSE.: add dummy date	
lgribout 24bit	$\mid$ L	.FALSE.		If TRUE, write thermodynamic fields $\rho$ , $\theta_v$ , $T$ , $p$	filetype=2
0 =				with 24bit precision instead of 16bit	

Defined and used in: src/namelists/mo\_gribout\_nml.f90

## 2.15. grid\_nml

Parameter	Type	Default	Unit	Description	Scope
lplane	L	.FALSE.		planar option	
is_plane_torus	L	.FALSE.		f-plane approximation on triangular grid	
corio_lat	R	0.0	deg	Center of the f-plane is located at this	lplane=.TRUE. and
				geographical latitude	$is\_plane\_torus=.TRUE.$
grid_angular _velocity	R	Earth's	$\mathrm{rad/s}$	The angular velocity in rad per sec.	

Parameter	Type	Default	Unit	Description	Scope
l_limited_area	$\mid L$	.FALSE.			
grid_rescale_factor	R	1.0		Defined as the inverse of the reduced-size earth reduction factor $X$ . Choose	
				grid_rescale_factor < 1 for a reduced-size	
				earth.	
				The geometry and the timestep will be	
				multiplied by this factor.	
				The angular velocity will be divided by this	
				factor.	
lfeedback	$L(n\_dom)$	.TRUE.		Specifies if feedback to parent grid is performed.	n_dom>1
				Setting lfeedback $(1)$ =.false. turns off feedback	
				for all nested domains; to turn off feedback for	
				selected nested domains, set lfeedback(1)=.true.	
	_			and set "false." for the desired model domains	
ifeedback_type	I	2		1: incremental feedback	n_dom>1
				2: relaxation-based feedback	
				Note: vertical nesting requires option 2 to run numerically stable over longer time periods	
start_time	R(n dom)	0.	g	Time when a nested domain starts to be active.	n dom>1
start_time	It(II_doili)	0.	S	Relative time w.r.t. experiment start date	
				(ini_datetime_string /	
				experimentStratDate).	
				(namelist entry is ignored for the global domain)	
end time	R(n dom)	1.E30	s	Time when a nested domain terminates.	n dom>1
_	, _ ,			Relative time w.r.t. experiment start date	
				(ini_datetime_string /	
				experimentStratDate).	
				(namelist entry is ignored for the global domain)	
patch_weight	R(n_dom)	0.		If patch_weight is set to a value > 0 for any of	n_dom>1
				the first level child patches, processor splitting	
				will be performed, i.e. every of the first level	
				child patches gets a subset of the total number	
				or processors corresponding to its patch_weight. A value of 0. corresponds to exactly 1 processor	
				for this patch, regardless of the total number of	
				processors. For the root patch and higher level	
				childs, patch weight is not used. However,	
				patch weight must be set to 0 for these patches	
				to avoid confusion.	
lredgrid_phys	L	.FALSE.		If set to .true. radiation is calculated on a	
				reduced grid (= one grid level higher)	
dynamics_grid_ filename	C			Array of the grid filenames to be used by the	
				dycore. May contain the keyword <path> which</path>	
				will be substituted by model_base_dir.	

Parameter	Type	Default	Unit	Description	Scope
dynamics_parent_ grid_id	I(n_dom)	i-1		Array of the indexes of the parent grid	
				filenames, as described by the	
				dynamics_grid_filename array. Indexes start at	
				1, an index of 0 indicates no parent.	
${f radiation\_grid\_filename}$	C			Array of the grid filenames to be used for the	$lredgrid\_phys=.TRUE.$
				radiation model. Filled only if the radiation grid	
				is different from the dycore grid. May contain	
				the keyword <path> which will be substituted by</path>	
				model_base_dir.	
dynamics_radiation_g rid_link	I(n_dom)	1 for i=1		Array of the indexes linking the dycore grids, as	
				described by the dynamics_grid_filename array,	
				and the radiation_grid_filename array. It	
				provides the link index of the	
				radiation_grid_filename, for each entry of the	
				dynamics_grid_filename array. Indexes start at	
				1, an index of 0 indicates that the radiation grid	
				is the same as the dycore grid. Only needs to be	
				filled when the radiation_grid_filename is	
	_	DAT CD		defined.	
create_vgrid	L	.FALSE.		.TRUE.: Write vertical grid files containing	
				(vct_a, vct_b, z_ifc, and z_ifv.	
vertical_grid_filename	C(n_dom)			Array of filenames. These files contain the	
				vertical grid definition (vct_a, vct_b, z_ifc). If	
				empty, the vertical grid is created within ICON	
ugo duplicated		.TRUE.		during the setup phase.	
use_duplicated_		. I N U E.		if .TRUE., the zero connectivity is replaced by the last non-zero value	
connectivity	L	.FALSE.		if .TRUE. then create a dummy cell and connect	
use_dummy_cell_closure	L	.FALSE.		it to cells and edges with no neighbor	
				It to cens and edges with no neighbor	

Defined and used in: src/namelists/mo\_grid\_nml.f90

# 2.16. gridref\_nml

Parameter	Type	Default	Unit	Description	Scope
$grf\_intmethod\_c$	I	2		Interpolation method for grid refinement	n_dom>1
				(cell-based dynamical variables):	
				1: parent-to-child copying	
				2: gradient-based interpolation	
grf_intmethod_ct	I	2		Interpolation method for grid refinement	n_dom>1
				(cell-based tracer variables):	
				1: parent-to-child copying	
				2: gradient-based interpolation	

Parameter	Type	Default	Unit	Description	Scope
grf_intmethod_e	I	6		Interpolation method for grid refinement (edge-based variables):	n_dom>1
				1: inverse-distance weighting (IDW)	
				2: RBF interpolation	
				3: combination gradient-based / IDW	
				4: combination gradient-based / RBF	
				5/6: same as $3/4$ , respectively, but direct	
				interpolation of mass fluxes along nest interface	
				edges	
grf_velfbk		1		Method of velocity feedback:	n_dom>1
				1: average of child edges 1 and 2	
				2: 2nd-order method using RBF interpolation	
grf_scalfbk	I	2		Feedback method for dynamical scalar variables	n_dom>1
				$(T, p_{sfc})$ :	
				1: area-weighted averaging	
				2: bilinear interpolation	
grf_tracfbk		2		Feedback method for tracer variables:	n_dom>1
				1: area-weighted averaging	
				2: bilinear interpolation	
grf_idw_exp_e12	R	1.2		exponent of generalized IDW function for child	n_dom>1
				m edges~1/2	
grf_idw_exp_e34	R	1.7		exponent of generalized IDW function for child	n_dom>1
				m edges~3/4	
rbf_vec_kern_grf_e	I	1		RBF kernel for grid refinement (edges):	n_dom>1
				1: Gaussian	
				$2: 1/(1+r^2)$	
				3: inverse multiquadric	_
rbf_scale_grf_e	$  R(n_{dom})  $	0.5		RBF scale factor for grid refinement (lateral	n_dom>1
				boundary interpolation to edges). Refers to the	
				respective parent domain and thus does not need	
				to be specified for the innermost nest. Lower	
				values than the default of 0.5 are needed for	
	_			child mesh sizes less than about 500 m.	
denom_diffu_t	R	135		Deniminator for lateral boundary diffusion of	n_dom>1
1.00	_	200		temperature	
denom_diffu_v	R	200		Deniminator for lateral boundary diffusion of	n_dom>1
	_			velocity	
l_mass_consvcorr		.FALSE.		.TRUE.: Apply mass conservation correction in	n_dom>1
, , , .	-	DATO:		feedback routine	1 4 4 3 7 7 10 11 1
l_density_nudging		.FALSE.		TRUE: Apply density nudging near lateral nest	$n_{\text{dom}} > 1$ .AND. lfeedback =
		10000		boundary if grf_intmethod_e \le 4	.TRUE.
fbk_relax_timescale	R	10800		Relaxation time scale for feedback	n_dom>1 .AND. lfeedback =
					.TRUEAND. ifeedback_type
					= 2

2.17. ha \_dyn \_nml

 $This \ name list \ is \ relevant \ if \ run\_nml: ldynamics=. TRUE. \ and \ dynamics\_nml: iequations=IHS\_ATM\_TEMP \ or \ IHS\_ATM\_THETA.$ 

Parameter	Type	Default	Unit	Description	Scope
itime_scheme	I	14		Time integration scheme:	
				11: pure advection (no dynamics)	
				12: 2 time level semi implicit (not yet	
				implemented)	
				13: 3 time level explicit	
				14: 3 time level with semi implicit correction	
				15: standard 4th-order Runge-Kutta method	
				(4-stage)	
				16: $SSPRK(5,4)$ scheme (5-stage)	
ileapfrog_startup	I	1		How to integrate the first time step when the	$itime\_scheme = 13 \text{ or } 14$
				leapfrog scheme is chosen. $1 = \text{Euler forward}$ ; 2	
				= a series of sub-steps.	
asselin_coeff	R	0.1		Asselin filter coefficient	$itime\_scheme = 13 \text{ or } 14$
si_2tls	R	0.6		weight of time step $n+1$ . Valid range: $[0,1]$	$itime\_scheme=12$
si_expl_scheme	I	2		scheme for the explicit part used in the 2 time	$itime\_scheme=12$
				level semi-implicit time stepping scheme. $1 =$	
				Euler forward; $2 = Adams$ -Bashforth 2nd order	
si_cmin	R	30.0	m/s	semi implicit correction is done for eigenmodes	$itime\_scheme=14$ and
				with speeds larger than si_cmin	$lsi\_3d=.FALSE.$
si_coeff	R	1.0		weight of the semi implicit correction	$itime\_scheme=14$
si_offctr	R	0.7			$itime\_scheme=14$
si_rtol	R	1.0e-3		relative tolerance for GMRES solver	$itime\_scheme=14$
lsi_3d	L	.FALSE.		3D GMRES solver or decomposistion into 2D	$lshallow\_water=.FALSE.$ and
				problems	itime_scheme=14
ldry_dycore		.TRUE.		Assume dry atmosphere	iequations $\in \{1,2\}$
lref_temp	L	.FALSE.		Set a background temperature profile as base	iequations $\in \{1,2\}$
				state when computing the pressure gradient force	

## 2.18. initicon\_nml

Parameter	Type	Default	Unit	Description	Scope
init_mode	I	2		1: MODE_DWDANA	
				start from DWD analysis or FG	
				2: MODE_IFSANA	
				start from IFS analysis	
				3: MODE_COMBINED	
				${ m IFS~atm} + { m ICON/GME~soil}$	
				4: MODE_COSMO	
				start from prognostic set of variables as used	
				by COSMO	
				5: MODE_IAU	
				start from DWD analysis with incremental	
				analysis update. Extension of	
				MODE_IAU_OLD including snow increments	
				6: MODE_IAU_OLD start from DWD analysis with incremental	
				analysis update. NOTE: Extension of mode	
				MODE DWDANA INC including W SO	
				increments.	
				7: MODE ICONVREMAP	
				start from DWD first guess with subsequent	
				vertical remapping (work in progress; so far,	
				changing the number of model levels does not	
				yet work)	
dt iau	$\mid$ R	10800	s	Duration of incremental analysis update (IAU)	init mode=5,6
_				procedure. Start time for IAU is the actual	
				model start time (see below).	
dt_shift	R	0	S	Time by which the actual model start time is	$_{ m init\_mode=5,6}$
				shifted ahead of the nominal date. The latter is	
				given by either ini_datetime_string or	
				experimentStartDate.dt_shift must be	
				NEGATIVE, usually $-0.5 \text{ dt}$ _iau.	
iterate_iau		.FALSE.		If .TRUE., the IAU phase is calculated twice	$\mid$ init_mode=5,6 and dt_shift < $\mid$
				with halved dt_shift in first cycle (allows	0
				writing a fully initialized analysis at the nominal	
				initialization date while using a centered IAU	
	D			window for the forecast).	
start_time_avg_fg	R	0	S	Start time for calculating temporally averaged	
and time arm f-	<i>D</i>			first guess output for data assimilation.	
end_time_avg_fg	R	0	S	End time for calculating temporally averaged first guess output for data assimilation.	
				Setting end_time_avg_fg >	
				start time avg fg activates the averaging	
interval_avg_fg	R	0	s	Corresponding averaging interval. Note that	
111001 vai _ 4 v 8 _ 18	10		ls .	end_time_avg_fg - start_time_avg_fg must	
				not be smaller than the averaging interval	
I	I	I		1100 be billarier than the averaging interval	

Parameter	Туре	Default	Unit	Description	Scope
ho_incr_filter_wgt	R	0		Vertical filtering weight on density increments	$_{ m init\_mode=5,6}$
$\operatorname{niter\_diffu}$	I	10		Number of diffusion iterations applied on wind increments	$ m init\_mode=5,6$
$niter\_divdamp$	I	25		Number of divergence damping iterations	$oxed{egin{array}{c}  ext{init\_mode}=5,6 \end{array}}$
type_iau_wgt	I	1		applied on wind increments Weighting function for performing IAU 1: Top-Hat 2: SIN2	init_mode=5,6
nlevsoil in	I	4		number of soil levels of input data	$\begin{array}{c c} \operatorname{init} & \operatorname{mode}=2 \end{array}$
zpbl1	R	500.0	m	bottom height (AGL) of layer used for gradient computation	
zpbl2	R	1000.0	m	top height (AGL) of layer used for gradient computation	
lread_ana	L	.TRUE.		If .FALSE., ICON is started from first guess only. Analysis field is not required, and skipped if provided.	$ m init\_mode=1,3$
${\bf use\_lakeiceana}$	L	.FALSE.		If TRUE., analysis data for sea ice fraction are also used for freshwater lakes (for the time being restricted to the Great Lakes; extension to other lakes needs to be tested)	$ m init\_mode=5,6$
${ m qcana\_mode}$	I	0		<ul> <li>If &gt; 0, analysis increments for cloud water are read and processed.</li> <li>1: QC increments are added to QV increments</li> <li>2: QC increments are added to QC if clouds are present, otherwise to QV increments</li> </ul>	$init\_mode=5$
qiana_mode	I	0		1: analysis increments for cloud ice are read and processed.	$init\_mode=5$
${ m lconsistency\_checks}$	L	.TRUE.		If .FALSE., consistency checks for Analysis and First Guess fields are skipped. On default, checks are performed for uvidOfHGrid and validity time.	$ m init\_mode=1,3,4,5,6$
$l\_coarse2fine\_mode$	$L(n\_dom)$	.FALSE.		If true, apply corrections for coarse-to-fine mesh interpolation to wind and temperature	
lp2cintp_incr	L(n_dom)	.FALSE.		If true, interpolate atmospheric data assimilation increments from parent domain.  Can be specified separately for each nested domain; setting the first (global) entry to true activates the interpolation for all nested domains.	$init\_mode=5,6$
lp2cintp_sfcana	L(n_dom)	.FALSE.		If true, interpolate atmospheric surface analysis data from parent domain.  Can be specified separately for each nested domain; setting the first (global) entry to true activates the interpolation for all nested domains.	$ m init\_mode=5,6$

Parameter	Type	Default	Unit	Description	Scope
ltile_init	L	.FALSE.		True: initialize tiled surface fields from a first	$ m init\_mode=1,5,6$
				guess coming from a run without tiles.	
				Along coastlines and lake shores, a neighbor	
				search is executed to fill the variables on	
				previously non-existing land or water points	
				with Itile, coldstort, — TRUE	
ltile coldstart	$oxed{L}$	.FALSE.		with ltile_coldstart = .TRUE.  If true, tiled surface fields are initialized with	$\begin{array}{c c} & & \\ & \text{init} & \text{mode} = 1,5,6 \end{array}$
title_colustatt	L	TALSE.		tile-averaged fields from a previous run with	
				tiles.	
				A neighbor search is applied to subgrid-scale	
				ocean points for SST and sea-ice fraction.	
lvert_remap_fg	L	.FALSE.		If true, vertical remapping is applied to the	init mode=5,6
				atmospheric first-guess fields, whereas the	_ ′
				analysis increments remain unchanged. The	
				number of model levels must be the same for	
				input and output fields, and the z_ifc (alias	
				HHL) field pertaining to the input fields must be	
				appended to the first-guess file.	
ifs2icon_filename	C			Filename of IFS2ICON input file, default	$\mid  ext{init\_mode} = 2$
				" <path>ifs2icon_R<nroot>B<jlev>_DOM</jlev></nroot></path>	
				<idom>.nc". May contain the keywords <path></path></idom>	
				which will be substituted by model_base_dir,	
				as well as nroot, nroot0, jlev, and idom	
dwdfg filename	ight] C			defining the current patch.  Filename of DWD first-guess input file, default	$\begin{array}{c c} & & \\ \text{init} & \text{mode}=1,3,5,6 \end{array}$
awargmename				" <pre>"<pre>"<pre>path&gt;dwdFG_R<nroot>B<jlev>_DOM</jlev></nroot></pre></pre></pre>	
				<pre><idom>.nc". May contain the keywords <path></path></idom></pre>	
				which will be substituted by model_base_dir,	
				as well as nroot, nroot0, jlev, and idom	
				defining the current patch.	
dwdana filename	$\mid$ C			Filename of DWD analysis input file, default	$\begin{array}{ c c c c c c c c c c c c c c c c c c c$
_				" <path>dwdana_R<nroot>B<jlev>_DOM</jlev></nroot></path>	
				<pre><idom>.nc". May contain the keywords <path></path></idom></pre>	
				which will be substituted by model_base_dir,	
				as well as nroot, nroot0, jlev, and idom	
				defining the current patch.	
filetype	I	-1 (undef.)		One of CDI's FILETYPE_XXX constants.	
				Possible values: 2 (=FILETYPE_GRB2), 4	
				(=FILETYPE_NC2). If this parameter has not	
				been set, we try to determine the file type by its	
	l		I	extension "*.grb*" or ".nc".	

Parameter	Type	Default	Unit	Description	Scope
check_fg(jg)%list	C(:)			In ICON a small subset of first guess input fields is declared 'optional', meaning that they are read in if present, but they are not mandatory to start the model. By adding optional fields to this list, they become mandatory for domain jg, such that the model aborts if any of them is missing. This list may include a subset of the optional first guess fields, or even the entire set of first guess fields. On default this list is empty, such that optional fields experience a cold-start initialization if they are missing and the model	init_mode=1,5,6
check_ana(jg)%list  ana_varnames_map_ file	C(:)			does not abort.  List of mandatory analysis fields for domain jg that must be present in the analysis file. If these fields are not found, the model aborts. For all other analysis fields, the FG-fields will serve as fallback position.  Dictionary file which maps internal variable names onto GRIB2 shortnames or NetCDF var names. This is a text file with two columns separated by whitespace, where left column:	$init\_mode=1,5,6$
				ICON variable name, right column: GRIB2 short name or NetCDF var name.	

Defined and used in: src/namelists/mo\_initicon\_nml.f90

## 2.19. interpol\_nml

Parameter	Type	Default	Unit	Description	Scope
l_intp_c2l	L	.TRUE.		DEPRECATED	
$l\_mono\_c2l$	L	.TRUE.		Monotonicity can be enforced by demanding	
				that the interpolated value is not higher or lower	
				than the stencil point values.	
llsq high consv	L	.TRUE.		conservative (T) or non-conservative (F)	
				least-squares reconstruction for high order	
				transport	
lsq_high_ord	I	3		polynomial order for high order reconstruction	
				1: linear	ihadv_tracer=4
				2: quadratic	
				30: cubic (no $3^{rd}$ order cross deriv.)	
				3: cubic	
llsq lin consv	L	.FALSE.		conservative (T) or non-conservative (F)	
				least-squares reconstruction for 2nd order	
				(linear) transport	

Parameter	Type	Default	Unit	Description	Scope
$\mathrm{nudge\_efold\_width}$	R	2.0		e-folding width (in units of cell rows) for lateral	
				boundary nudging coefficient. This switch and	
				the following two pertain to one-way nesting and	
				limited-area mode	,
$\operatorname{nudge} \operatorname{_{-max}\_{coeff}}$	R	0.02		Maximum relaxation coefficient for lateral	
<u> </u>				boundary nudging. Recommended range of	
				values for limited-area mode is $0.06 - 0.075$ .	l
nudge zone width	I	8		Total width (in units of cell rows) for lateral	l
0				boundary nudging zone. For the limited-area	
				mode, a minimum of 10 is recommended. If $< 0$	
				the patch boundary depth index is used.	
rbf dim c2l	I	10		stencil size for direct lon-lat interpolation: 4 =	
		•		nearest neighbor, 13 = vertex stencil, 10 = edge	
				stencil.	
rbf scale mode ll	I	$ $ $_2$		Specifies, how the RBF shape parameter is	
1.51_50010_111040_11		_		determined for lon-lat interpolation.	
				1: lookup table based on grid level	
				2: determine automatically.	
				So far, this routine only estimates the smallest	
				value for the shape parameter for which the	
				Cholesky is likely to succeed in floating point	
				arithmetic. 3: explicitly set shape parameter in	
				each output namelist (namelist parameter	
1. C 1		1		output_nml::rbf_scale, p. 54).	
rbf_vec_kern_c	I	1		Kernel type for reconstruction at cell centres:	
				1: Gaussian	
1.6	_			3: inverse multiquadric	
rbf_vec_kern_e	I	3		Kernel type for reconstruction at edges:	
				1: Gaussian	
				3: inverse multiquadric	
rbf_vec_kern_ll	I	1		Kernel type for reconstruction at lon-lat-points:	
				1: Gaussian	
				3: inverse multiquadric	
rbf_vec_kern_v	I	1		Kernel type for reconstruction at vertices:	
				1: Gaussian	
				3: inverse multiquadric	
$rbf\_vec\_scale\_c$	R(n_dom)	resolution-		Scale factor for RBF reconstruction at cell	
		dependent		centres	
rbf vec scale e	R(n dom)	resolution-		Scale factor for RBF reconstruction at edges	
	` = '	dependent			
rbf vec scale v	R(n dom)	resolution-		Scale factor for RBF reconstruction at vertices	
		dependent			
support baryctr intp	L	.FALSE.		Flag. If .FALSE. barycentric interpolation is	
r r / F	-	·		replaced by a fallback interpolation.	

Parameter	Type	Default	Unit	Description	Scope
lreduced_nestbdry_stencil	L	.FALSE.		Flag. If .TRUE. then the nest boundary points are taken out from the lat-lon interpolation	
				stencil.	

Defined and used in: src/namelists/mo\_interpol\_nml.f90

## 2.20. io\_nml

Parameter	Type	Default	Unit	Description	Scope
lkeep_in_sync	L	.FALSE.		Sync output stream with file on disk after each	
				timestep	
dt_diag	R	86400.	S	diagnostic integral output interval	run_nml:output = "totint"
dt_checkpoint	R	2592000	S	Time interval for writing restart files. Note that	output /= "none" (run_nml)
				if the value of dt_checkpoint resulting from	
				model default or user's specification is longer	
				than time_nml:dt_restart, it will be reset (by	
				the model) to dt_restart so that at least one	
				restart file is generated during the restart cycle.	
inextra_2d	I	0		Number of extra 2D Fields for	$dynamics_nml:iequations = 3$
				${ m diagnostic/debugging\ output.}$	(to be done for 1, 2)
inextra_3d	I	0		Number of extra 3D Fields for	$dynamics\_nml:iequations = 3$
				${\rm diagnostic/debugging\ output.}$	(to be done for 1, 2)
lflux_avg	L	.TRUE.		if .FALSE. the output fluxes are accumulated	iequations=3
				from the beginning of the run	iforcing=3
				if .TRUE. the output fluxes are average values	
				from the beginning of the run, except of	
				TOT_PREC that would be accumulated	
itype_pres_msl	I	1		Specifies method for computation of mean sea	
				level pressure (and geopotential at pressure	
				levels below the surface).	
				1: GME-type extrapolation,	
				2: stepwise analytical integration,	
				3: current IFS method,	
				4: IFS method with consistency correction	
				5: New DWD method constituting a mixture	
				between IFS and old GME method (departure	
				level for downward extrapolation between 10 m	
				and 150 m AGL depending on elevation)	
itype_rh	I	1		Specifies method for computation of relative	
				humidity	
				1: WMO-type: water only (e_s=e_s_water),	
				2: IFS-type: mixed phase (water and ice),	
	l D	9,000		3: IFS-type with clipping (rh $\leq 100$ )	
gust_interval	R	3600.	S	Interval over which wind gusts are maximized	iforcing=3

Parameter	Type	Default	Unit	Description	Scope
output_nml_dict	C	, ,		File containing the mapping of variable names to the internal ICON names. May contain the keyword <path> which will be substituted by</path>	output_nml namelists
				model_base_dir. The format of this file:	
				One mapping per line, first the name as given in	
				the ml_varlist, hl_varlist, pl_varlist or	
				il_varlist of the output_nml namelists, then	
				the internal ICON name, separated by an arbitrary number of blanks. The line may also	
				start and end with an arbitrary number of	
				blanks. Empty lines or lines starting with $\#$ are	
				treated as comments.	
				Names not covered by the mapping are used as	
linvert dict	L	.FALSE.		they are. If .TRUE., columns in dictionary file	
mirere_aret		, iiiibs E.		output nml dict are evaluated in inverse order.	
				This allows using the same dictionary file as for	
				input (ana_varnames_map_file in	
netcdf dict	$\mid$ C	, ,		initicon_nml). File containing the mapping from internal names	output_nml namelists,
netcar_arct				to names written to NetCDF. May contain the	NetCDF output
				keyword <path> which will be substituted by</path>	Trees BI sarpar
				model_base_dir.	
				The format of this file:	
				One mapping per line, first the name written to NetCDF, then the internal name, separated by	
				an arbitrary number of blanks (inverse to the	
				definition of output_nml_dict). The line may	
				also start and end with an arbitrary number of	
				blanks. Empty lines or lines starting with # are	
				treated as comments.  Names not covered by the mapping are output	
				as they are.	
				Note that the specification of output variables,	
				e.g. in ml_varlist, is independent from this	
				renaming, see the namelist parameter output_nml_dict for this.	
lnetcdf flt64 output	L	.FALSE.		If .TRUE. floating point variable output in	
				NetCDF files is written in 64-bit instead of	
				32-bit accuracy.	
restart_file_type	I	4		Type of restart file. One of CDI's	
				FILETYPE_XXX. So far, only 4 (=FILETYPE NC2) is allowed	
	I	I		(-ribbilib_no2) is allowed	

Parameter	Type	Default	Unit	Description	Scope
restart_write_mode	С	""		Restart read/write mode.	
				Allowed settings (character strings!) are listed	
				below.	
nrestart_streams	I	1		When using the restart write mode "dedicated	restart_write_mode =
				procs multifile", it is possible to split the restart	"dedicated procs multifile"
				output into several files, as if	
				<pre>nrestart_streams * num_io_procs restart</pre>	
				processes were involved. This speeds up the	
				read-in process, since all the files may then be	
				read in parallel.	
lmask_boundary	L	F		Set to .TRUE., if interpolation zone should be	
				masked in triangular output.	

#### 2.20.1. Restart read/write mode:

Allowed settings for restart\_write\_mode are:

#### "sync"

'Old' synchronous mode. PE # 0 reads and writes restart files. All other PEs have to wait.

#### "async"

Asynchronous restart writing: Dedicated PEs (num\_restart\_proc > 0) write restart files while the simulation continues. Restart PEs can only parallelize over different patches. — Read-in: PE # 0 reads while other PEs have to wait.

#### "joint procs multifile"

All worker PEs write restart files to a dedicated directory. Therefore, the directory itself is called the restart file. The information is stored in a way that it can be read back into the model independent from the processor count and the domain decomposition. — Read-in: All worker PEs read the data in parallel.

#### "dedicated procs multifile"

In this case, all the restart data is first transferred to memory buffers in dedicated restart writer PEs. After that, the work processes carry on with their work immediately, while the restart writers perform the actual restart writing asynchronously. Restart PEs can parallelize over patches and horizontal indices. — Read-in: All worker PEs read the data in parallel..

#### Fallback mode.

,, ,,

If num\_restart\_proc == 0 (parallel\_nml), then this behaves like "sync", otherwise like "async".

Defined and used in: src/namelists/mo\_io\_nml.f90

#### 2.21. les nml (parameters for LES turbulence scheme; valid for inwp turb=5)

Parameter	Type	Default	Unit	Description	Scope
sst	R	300	K	sea surface temperature for idealized LES	$isrfc\_type=5,4$
				simulations	
shflx	R	0.1	m Km/s	Kinematic sensible heat flux at surface	$isrfc\_type = 2$

Parameter	Type	Default	Unit	Description	Scope
lhflx	R	0	m/s	Kinematic latent heat flux at surface	$isrfc\_type = 2$
isrfc_type	I	1		surface type	
				0 = No fluxes and zero shear stress	
				1 = TERRA land physics	
				2 = fixed surface fluxes	
				3 = fixed buoyancy fluxes	
				$4 = RICO  ext{ test case}$	
				5 = fixed SST	
				$6 = time varying SST and qv_s case with$	
				prescribed roughness length for semi-idealized	
				setups	
ufric	ight  R	-999	m/s	friction velocity for idealized LES simulations; if	
				< 0 then it is automatically diagnosed	
psfc	$\mathbb{R}$	-999	Pa	surface pressure for idealized LES simulations; if	
				< 0 then it uses the surface pressure from	
				dynamics	
min sfc wind	$\mathbb{R}$	1.0	m/s	Minimum surface wind for surface layer useful in	
				the limit of free convection	
is_dry_cbl	$\mid L$	.FALSE.		switch for dry convective boundary layer	
_ ~ _				simulations	
smag constant	$ ight _{\mathrm{R}}$	0.23		Smagorinsky constant	
km_min	$\mathbb{R}$	0.0		Minimum turbulent viscosity	
max_turb_scale	$ ight _{\mathrm{R}}$	300.0		Asymtotic maximum turblence length scale	
				(useful for coarse grid LES and when grid is	
				vertically stretched)	
turb prandtl	ight] R	0.333333		turbulent Prandtl number	
bflux	$ ight _{\mathrm{R}}$	0.0007	$ m m^2/s^3$	buoyancy flux for idealized LES simulations	isrfc type=3
			,	(Stevens 2007)	_ 01
tran coeff	$ ight _{\mathrm{R}}$	0.02	m/s	transfer coefficient near surface for idealized LES	isrfc type=3
_			,	simulation (Stevens 2007)	_ 01
vert scheme type	I	2		type of time integration scheme in vertical	
				diffusion	
				1 = explicit	
				2 = fully implicit	
sampl freq sec	R	60	$\mathbf{s}$	sampling frequency in seconds for statistical (1D	
• • • • • • • • • • • • • • • • • • •				and 0D) output	
avg interval sec	R	900	$\mathbf{s}$	(time) averaging interval in seconds for 1D	
				statistical output	
expname	$\mid$ C	ICOLES		expname to name the statistical output file	
ldiag_les_out		.FALSE.		Control for the statistical output in LES mode	
les_metric	$\mid \overline{ m L} \mid$	.FALSE.		Switch to turn on Smagorinsky diffusion with 3D	
_				metric terms to account for topography	

# 2.22. limarea\_nml (Scope: I\_limited\_area=.TRUE. in grid\_nml)

Parameter	Type	Default	Unit	Description	Scope
itype_latbc	I	0		Type of lateral boundary nudging.  0: constant lateral boundary conditions derived from the initial conditions,  1: time-dependent lateral boundary conditions provided by an external source (IFS, COSMO or a coarser-resolution ICON run),  2: Test mode using time-dependent lateral boundary conditions from a nested ICON run in which the present limited-area domain was operated as a nested grid with identical(!) model level configuration.  Available for synchronous read mode	
$egin{array}{c}  ext{dtime}\_ ext{latbc} \end{array}$	R	10800.0	s	(num_prefetch_proc = 0) only! Time difference between two consecutive boundary data.	$itype\_latbc \geq 1$
init_latbc_from_fg	L	.FALSE.		If .TRUE., take lateral boundary conditions for initial time from first guess (or analysis) field	$itype\_latbc \ge 1$
nudge_hydro_pres	L	.TRUE.		If .TRUE., hydrostatic pressure is used to compute lateral boundary nudging	$itype\_latbc \ge 1$
latbc_filename	C			(recommended if boundary conditions contain hydrostatic pressure, which is usually the case) Filename of boundary data input file, these files must be located in the latbc_path directory. Default:	$itype\_latbc \geq 1$
latbc_path latbc_boundary_grid	CC	27 27		"prepiconR <nroot>B<jlev>_<y><m><d><h>.nc".  The filename may contain keyword tokens (day, hour, etc.) which will be automatically replaced during the run-time. See the table below for a list of allowed keywords.  Absolute path to boundary data.  Grid file defining the lateral boundary. Empty string means: whole domain is read for the lateral boundary. This NetCDF grid file must contain two integer index arrays: int global_cell_index(cell), int global_edge_index(edge), both with attributes nglobal which contains the global size size of the non-sparse cells and edges.</h></d></m></y></jlev></nroot>	$\begin{array}{l} itype\_latbc \geq 1 \\ itype\_latbc \geq 1 \end{array}$

Parameter	Type	Default	Unit	Description	Scope
latbc_varnames_map_ file	С			Dictionary file which maps internal variable	$num\_prefetch\_proc=1$
				names onto GRIB2 shortnames or NetCDF var	
				names. This is a text file with two columns	
				separated by whitespace, where left column:	
				ICON variable name, right column: GRIB2	
				short name. This list contains variables that are	
				to be read asynchronously for boundary data	
				nudging in a HDCP2 simulation. All new	
				boundary variables that in the future, would be	
				read asynchronously. Need to be added to text	
				file dict.latbc in run folder.	
nretries	I	0		If LatBC data is unavailable: number of retries	
retry_wait_sec	I	10		If LatBC data is unavailable: idle wait seconds	
				between retries	

Defined and used in: src/namelists/mo\_limarea\_nml.f90

## Keyword substitution in boundary data filename (latbc\_filename):

<y></y>	substituted by year (four digits)		
<m></m>	substituted by month (two digits)		
<d>&gt;</d>	substituted by day (two digits)		
<h>&gt;</h>	substituted by hour (two digits)		
<min></min>	substituted by minute (two digits)		
<sec></sec>	substituted by seconds (two digits)		
<ddhhmmss></ddhhmmss>	substituted by a <i>relative</i> day-hour-minute-second string.		
<dddhh></dddhh>	substituted by a <i>relative</i> (three-digit) day-hour string.		

## 2.23. lnd\_nml

Parameter	Type	Default	Unit	Description	Scope
nlev_snow	I	2		number of snow layers	lmulti_snow=.true.
ntiles	I	1		number of tiles	
lsnowtile	L	.FALSE.		.TRUE.: consider snow-covered and snow-free	ntiles>1
				tiles separately	
$frlnd\_thrhld$	R	0.05		fraction threshold for creating a land grid point	ntiles>1
frlake_thrhld	R	0.05		fraction threshold for creating a lake grid point	ntiles>1
frsea_thrhld	R	0.05		fraction threshold for creating a sea grid point	ntiles>1
frlndtile_thrhld	R	0.05		fraction threshold for retaining the respective	ntiles>1
				tile for a grid point	
lmelt	L	.TRUE.		.TRUE. soil model with melting process	
lmelt_var	L	.TRUE.		.TRUE. freezing temperature dependent on	
				water content	
lana_rho_snow	L	.TRUE.		.TRUE. take rho_snow-values from analysis file	$\operatorname{init\_mode}=1$

Parameter	Type	Default	Unit	Description	Scope
lmulti_snow	L	.FALSE.		.TRUE. for use of multi-layer snow model	
				(default is single-sayer scheme)	
l2lay_rho_snow	L	.FALSE.		.TRUE. predict additional snow density for	$lmulti\_snow = .FALSE.$
				upper part of the snowpack, having a maximum	
				depth of max_toplaydepth	
$\max_{toplaydepth}$	R	0.25	m	maximum depth of uppermost snow layer	lmulti_snow=.TRUE. or
_					l2lay_rho_snow=.TRUE.
idiag_snowfrac	I	1		Type of snow-fraction diagnosis:	
				1 = based on SWE only	
				2-4 = more advanced experimental methods	
				20, 30, 40 = same as  2, 3, 4,  respectively, but	
				with artificial reduction of snow fraction in case	
				of melting snow (shold be used only in	
				combination with lsnowtile=.TRUE.	
$itype\_snowevap$	I	2		Tuning of snow evaporation in vegetated areas:	lsnowtile=.TRUE.
				1: Tuning turned off	
				2: First level of tuning without additional	
				control variables	
				3: Second level of tuning with additional I/O	
				variables for snow age and maximum snow depth	
				(should be used only if these additional variables	
				are avaliable from the DWD assimilation cycle)	
itype_lndtbl	I	3		Table values used for associating surface	
				parameters to land-cover classes:	
				1 =  defaults from extpar (GLC2000 and	
				GLOBCOVER2009)	
				2 = Tuned version based on IFS values for	
				globcover classes (GLOBCOVER2009 only)	
				3 = even more tuned operational version	
				(GLOBCOVER2009 only)	
				4 = tuned version for new bare soil evaporation	
				scheme (itype evsl=4)	
itype_root	I	2		root density distribution:	
<del>-</del>				1 = constant	
				2 = exponential	
itype_evsl	I	2		type of bare soil evaporation parameterization	
· · _				2 = Dickinson (1984)	
				3 = Noilhan and Planton (1989)	
				4 = Resistance-based scheme by Jan-Peter	
				Schulz	

Parameter	Type	Default	Unit	Description	Scope
itype_trvg	I	2		type of plant transpiration parameterization	
				2 = BATS scheme, Dickinson (1984)	
				3 = Extended BATS scheme with additional	
				prognostic variable for integrated plant	
				transpiration since sunrise; should be used only	
				with an appropriate first guess for this variable	
				coming from the DWD assimilation cycle	
itype heatcond	I	2		type of soil heat conductivity	
· · ·				1 = constant soil heat conductivity	
				2 = moisture dependent soil heat conductivity	
				3 = variant of option 2 with reduced near-surface	
				heat conductivity in the presence of plant cover	
itype interception	I	1		type of plant interception	
· · ·				1 = standard scheme, effectively switched off by	
				tiny value cwimax ml	
				2 = Rain and snow interception (to be removed)	
cwimax ml	$\mid$ R	1.e-6	m	scaling parameter for maximum interception	itype interception = 1
_				storage (almost switched off);	v I I
				use 5.e-4 to activate interception storage	
c soil	$\mid$ R	1.		surface area density of the (evaporative) soil	
- <u>-</u>		*.		surface	
				allowed range: $0-2$	
c soil urb	$\mid$ R	1.		surface area density of the (evaporative) soil	
				surface, urban areas	
				allowed range: $0-2$	
itype_hydbound	I	1		type of hydraulic lower boundary condition	
roj po_nj doodna	*	_		1 = none	
				3 = ground water as lower boundary of soil	
				column	
lstomata	$\mid$ L	.TRUE.		If .TRUE., use map of minimum stomatal	
225 C 224 COO CO		111011		resistance	
				If .FALSE., use constant value of 150 s/m.	
l2tls	$\mid$ L	.TRUE.		If .TRUE., forecast with 2-Time-Level	
12010	1	, 110015		integration scheme (mandatory in ICON)	
lseaice	$\mid$ L	.TRUE.		.TRUE. for use of sea-ice model	
lprog_albsi	$ig _{ m L}^{ m L}$	.FALSE.		If .TRUE., sea-ice albedo is computed	lseaice=.TRUE.
throg_grosi	"	TALSE.		prognostically	iscaice—. I Ito E.
llake		.TRUE.		TRUE. for use of lake model	
паке	$\mid L$	I.IKUE.		. I ROE. for use of take model	

Parameter	Type	Default	Unit	Description	Scope
sstice_mode	I	1		1: SST and sea ice fraction are read from the	iequations=3
				analysis. The SST is kept constant whereas the	iforcing=3
				sea ice fraction can be modified by the seaice	
				model.	
				2: SST and sea ice fraction are read from the	
				analysis. The SST is updated by climatological	
				increments on a daily basis. The sea ice fraction	
				can be modified by the seaice model.	
				3: SST and sea ice fraction are updated daily,	
				based on climatological monthly means	
				4: SST and sea ice fraction are updated daily,	
				based on actual monthly means	
				5: SST and sea ice fraction are updated daily,	
				based on actual daily means (not yet implemented)	
sst td filename	$\mid$ C			Filename of SST input files for time dependent	sstice mode=3,4,5
				SST. Default is	_
				" <path>SST_<year>_<month>_<gridfile>".</gridfile></month></year></path>	
				May contain the keyword <path> which will be</path>	
				substituted by model_base_dir	
ci_td_filename	C			Filename of sea ice fraction input files for time	$sstice\_mode=3,4,5$
				dependent sea ice fraction. Default is	
				" <path>CI_<year>_<month>_<gridfile>".</gridfile></month></year></path>	
				May contain the keyword <path> which will be</path>	
				substituted by model_base_dir	

Defined and used in: src/namelists/mo\_lnd\_nwp\_nml.f90

## 2.24. ls\_forcing\_nml (parameters for large-scale forcing; valid for torus geometry)

Parameter	Type	Default	Unit	Description	Scope
is_subsidence_moment	L	.FALSE.		switch for enabling LS vertical advection due to	$is\_plane\_torus=.TRUE.$
				subsidence for momentum equations	
is_subsidence_heat	L	.FALSE.		switch for enabling LS vertical advection due to	$is\_plane\_torus=.TRUE.$
				subsidence for thermal equations	
is_advection	L	.FALSE.		switch for enabling LS horizontal advection	$is\_plane\_torus=.TRUE.$
				(currently only for thermal equations)	
is_nudging	L	.FALSE.		switch for enabling LS Newtonian relaxation	$is\_plane\_torus=.TRUE.$
				(nudging) for horizontal winds, temperature and	
				specific humidity	
is_geowind	L	.FALSE.		switch for enabling geostrophic wind	$is\_plane\_torus=.TRUE.$
is_rad_forcing	L	.FALSE.		switch for enabling radiative forcing	$is\_plane\_torus=.TRUE.$
					$  inwp_rad = .FALSE.$

Parameter	Type	Default	$\operatorname{Unit}$	Description	Scope
is_theta	L	.FALSE.		switch to indicate that the prescribed radiative	$is\_plane\_torus=.TRUE.$
				forcing is for potential temperature	$is\_rad\_forcing=.TRUE.$

Defined and used in: src/namelists/mo\_ls\_forcing\_nml.f90

## 2.25. master\_nml

Parameter	Type	Default	Unit	Description	Scope
institute	C	, ,		Acronym of the institute for which the full	
				institute name is printed in the log file. Options	
				are DWD, MPIM, KIT, or CSCS. Otherwise the	
				full names of MPIM and DWD are printed.	
lrestart	L	.FALSE.		If .TRUE.: Current experiment is started from a	
				restart.	
${f read\_restart\_namelists}$	L	.TRUE.		If .TRUE.: Namelists are read from the restart	
				file to override the default namelist settings,	
				before reading new namelists from the run	
				script. Otherwise the namelists stored in the	
				restart file are ignored.	
lrestart_write_last	L	.FALSE.		If .TRUE.: model run should create restart at	
				experiment end. This is independent from the	
				settings of the restart interval.	
$oxdot{oxdot}{oxdo$	C	, ,		General path which may be used in file names of	
				other name lists: If a file name contains the	
				keyword " <path>", then this model_base_dir</path>	
				will be substituted.	

## 2.26. master\_model\_nml (repeated for each model)

Parameter	Type	Default	Unit	Description	Scope
model name	С			Character string for naming this component.	
model namelist filename	C			File name containing the model namelists.	
model type	I	-1		Identifies which component to run.	
_				1=atmosphere	
				2=ocean	
				3=radiation	
				99=dummy_model	
model_min_rank	I	0		Start MPI rank for this model.	
model_max_rank	I	-1		End MPI rank for this model.	
model_inc_rank	I	1		Stride of MPI ranks.	

### 2.27. master\_time\_control\_nml

Parameter	Type	Default	Unit	Description	Scope
calendar	I	1		Selects the calendar type to use:	
				0 = calendar is not defined yet	
				1 = proleptic Gregorian calendar	
				2 = 365  day year without leap years	
				3 = 360  day year with  30  day months	
${\bf experiment Reference Date}$	C	experiment start		This specifies the reference date for the calendar	
		date		in use. It is an anchor date for cycling of events	
				on the time line. If this namelist parameter is	
				unspecified, then the reference date is set to the	
l and a second		TO CO GOT	1	experiment start date.	
experimentStartDate	$\mid$ C	ISO8601	date of	This is the start date of an experiment, which	
		formatted string	initial file	remains valid for the whole experiment. The	
				start date is also the reference date of the	
				experiment, which is the anchor point for cycling	
				events. In special cases the reference date might	
				be reset. Reasons might be debugging purposes or spinning off experiments from an existing	
				restart of an other experiment.	
experimentStopDate	ightharpoonup	ISO8601	n/a	This is the date an experiment is finished.	
		formatted string	11/4	This is the date an experiment is infinited.	
forecastLeadTime	C	ISO8601	n/a	Specifies the time span for a numerical weather	
		formatted string	/	forecast. It is used to set the experiment stop	
				time with respect to the experiment start date.	
checkpointTimeIntVal	$\mid$ C	ISO8601	n/a	Time interval for writing checkpoints.	
		formatted string		5 -	
restartTimeIntVal	C	ISO8601	n/a	Time interval for writing a restart file and	
		formatted string		interrupt the current running job.	

### $2.28.\ meteogram\_output\_nml$

Nearest neighbour 'interpolation' is used for all variables.

Parameter	Type	Default	Unit	Description	Scope
lmeteogram_enabled	L(n_dom)	.FALSE.		Flag. True, if meteogram of output variables is	
				desired.	
zprefix	C(n_dom)	"METEO		string with file name prefix for output file	
		GRAM "			
ldistributed	L(n dom)	.TRUE.		Flag. Separate files for each PE.	
loutput_tiles	L	.FALSE.		Write tile-specific output for some selected	
_				surface/soil fields	
n0_mtgrm	I(n_dom)	0		initial time step for meteogram output.	
ninc_mtgrm	I(n_dom)	1		output interval (in time steps)	

Parameter	Type	Default	Unit	Description	Scope
stationlist_tot		53.633, 9.983,		list of meteogram stations (triples with lat, lon,	
		'Hamburg'		name string)	
silent_flush	L(n_dom)	1		do not warn about flushing to disk if .TRUE.	
max_time_stamps	I(n_dom)	1		number of output time steps to record in	
				memory before flushing to disk	
var_list	C(:)	" "		Positive-list of variables (optional). Only	
				variables contained in this list are included in	
				the meteogram. If the default list is not changed	
				by user input, then all available variables are	
				added to the meteogram	

Defined and used in: src/namelists/mo\_mtgrm\_nml.f90

## 2.29. nonhydrostatic\_nml (relevant if run\_nml:iequations=3)

Parameter	Type	Default	Unit	Description	Scope
itime_scheme	I	4		Options for predictor-corrector time-stepping scheme:  4: Contravariant vertical velocity is computed in the predictor step only, velocity tendencies are computed in the corrector step only (most efficient option)  5: Contravariant vertical velocity is computed in both substeps (beneficial for numerical stability in very-high resolution setups with extremely steep slops, otherwise no significant impact)  6: As 5, but velocity tendencies are also computed in both substeps (no apparent benefit, but more expensive)	iequations=3
rayleigh_type	I	2		Type of Rayleigh damping 1: CLASSICAL (requires velocity reference state!) 2: Klemp (2008) type	
rayleigh_coeff	R(n_dom)	0.05		Rayleigh damping coefficient $1/\tau_0$ (Klemp, Dudhia, Hassiotis: MWR136, pp.3987-4004); higher values are recommended for R2B6 or finer resolution	
damp_height	R(n_dom)	45000	m	Height at which Rayleigh damping of vertical wind starts (needs to be adjusted to model top height; the damping layer should have a depth of at least 20 km when the model top is above the stratopause)	

Parameter	Type	Default	Unit	Description	Scope
${ m htop\_moist\_proc}$	R	22500.0	m	Height above which moist physics and advection	
				of cloud and precipitation variables are turned	
				off	
$hbot\_qvsubstep$	R	22500.0	m	Height above which QV is advected with	ihadv_tracer=22, 32, 42 or 52
				substepping scheme (must be at least as large as	
				htop_moist_proc)	
${ m vwind\_offctr}$	R	0.15		Off-centering in vertical wind solver. Higher	
				values may be needed for R2B5 or coarser grids	
				when the model top is above 50 km. Negative	
	-			values are not allowed	
${\it rhotheta\_offctr}$	R	-0.1		Off-centering of density and potential	
				temperature at interface level (may be set to 0.0	
				for R2B6 or finer grids; positive values are not	
1 1 6		0.05		recommended)	
$veladv\_offctr$	R	0.25		Off-centering of velocity advection in corrector	
	т			step. Negative values are not recommended	
ivctype	I	2		Type of vertical coordinate:	
				1: Gal-Chen hybrid	
d	т			2: SLEVE (uses sleve_nml)	
$ndyn\_substeps$	I	5		number of dynamics substeps per fast-physics /	
11- 1:0°¢	т	TDITE.		transport step	
lhdiff_rcf	L	.TRUE.		.TRUE.: Compute diffusion only at advection	
				time steps (in this case, divergence damping is	
lovetno differ	т	.TRUE.		applied in the dynamical core)	
lextra_diffu	L	I NUE.		.TRUE.: Apply additional momentum diffusion at grid points close to the stability limit for	
				vertical advection (becomes effective extremely	
				rarely in practice; this is mostly an emergency	
				fix for pathological cases with very large	
				orographic gravity waves)	
divdamp fac	R	0.0025		Scaling factor for divergence damping	ho = 1 lhdiff $ ho = 1$ TRUE.
divdamp_rac divdamp_order	I	4		Order of divergence damping:	$\begin{array}{ccc} \operatorname{Indin}_{-\operatorname{rcf}} & = \operatorname{.TRUE}. \\ \operatorname{lhdiff} & \operatorname{rcf} & = \operatorname{.TRUE}. \end{array}$
arvaamp_order	1	<b>1</b>		Order of divergence damping. $2 = \text{second-order divergence damping}$	mam_rer = . r ree E.
				4 = fourth-order divergence damping	
				24 = combined second-order and fourth-order	
				divergence damping and enhanced vertical wind	
				off-centering during the initial spinup phase	
				(does not allow checkpointing/restarting earlier	
				than 2.5 hours of integration)	
divdamp type	I	3		Type of divergence damping:	ho = TRUE.
				2 = divergence damping acting on 2D divergence	
				3 = divergence damping acting on 3D divergence	
				32 = combination of 3D div. damping in the	
				troposphere with transition to 2D div. damping	
				in the stratosphere	

Parameter	Type	Default	Unit	Description	Scope
$\operatorname{livdamp\_trans\_start}$	R	12500.		Lower bound of transition zone between 2D and 3D divergence damping	$ ext{divdamp\_type} = 32$
${ m livdamp\_trans\_end}$	R	17500.		Upper bound of transition zone between 2D and 3D divergence damping	$\operatorname{divdamp\_type} = 32$
nest substeps	T	2		Number of dynamics substeps for the child	
<u> </u>				patches.	
				DO NOT CHANGE!!! The code will not work	
				correctly with other values	
$\_{ m masscorr}\_{ m nest}$	$\mid L$	.FALSE.		.TRUE.: Apply mass conservation correction	ifeedback_type=1
				also in nested domain	
$\operatorname{adv}_{-}$ rhotheta	I	2		Advection method for rho and rhotheta:	
				1: simple second-order upwind-biased scheme	
				2: 2nd order Miura horizontal	
				3: 3rd order Miura horizontal (not	
ome dr. meethed		9		recommended)	
$\operatorname{gradp}_{-}\operatorname{method}$		3		Discretization of horizontal pressure gradient: 1: conventional discretization with metric	
				correction term	
				2: Taylor-expansion-based reconstruction of	
				pressure (advantageous at very high resolution)	
				3: Similar discretization as option 2, but uses	
				hydrostatic approximation for downward	
				extrapolation over steep slopes	
				4: Cubic/quadratic polynomial interpolation for	
				pressure reconstruction	
				5: Same as 4, but hydrostatic approximation for	
				downward extrapolation over steep slopes	
$_{ m zdiffu}_{ m t}$	L	.TRUE.		.TRUE.: Compute Smagorinsky temperature	hdiff_order=3/5 .AND.
l l l'œ	 	0.005		diffusion truly horizontally over steep slopes	lhdiff_temp = .true.
hslp_zdiffu	R	0.025		Slope threshold above which truly horizontal	hdiff_order=3/5 .AND.
				temperature diffusion is activated	lhdiff_temp=.trueAND.   l zdiffu t=.true.
hhgtd zdiffu	R	200	m	Threshold of height difference between	hdiff order=3/5 .AND.
ms.a_zama	16	200	111	neighboring grid points above which truly	lhdiff temp=.trueAND.
				horizontal temperature diffusion is activated	l zdiffu t=.true.
				(alternative criterion to thslp zdiffu)	
xner_expol	R	1./3.		Temporal extrapolation (fraction of dt) of Exner	
_ •		,		function for computation of horizontal pressure	
				gradient. This damps horizontally propagating	
				sound waves. For R2B5 or coarser grids, values	
				between $1/2$ and $2/3$ are recommended. Model	
				will be numerically unstable for negative values.	

Parameter	Type	Default	Unit	Description	Scope
l_open_ubc	L	.FALSE.		.TRUE.: Use open upper boundary condition	
				(rather than w=0) to allow vertical motions	
				related to diabatic heating to extend beyond the	
				model top	

Defined and used in: src/namelists/mo\_nonhydrostatic\_nml.f90

### 2.30 nudging\_nml

Parameters for the upper boundary nudging in the limited-area mode (grid\_nml: l\_limited\_area = .TRUE.). For the lateral boundary nudging, please see interpol\_nml and limarea\_nml. The characteristics of the driving data for the nudging can be specified in limarea\_nml.

Parameter	Type	Default	Unit	Description	Scope
nudge_type	I	0		Nudging type:	$run_nml:iforcing = 3 (NWP)$
				0: none	ivctype = 2 (SLEVE)
				1: upper boundary nudging	
				Please note:	
				$ \begin{array}{l} \text{- nudge\_type} = 1 \text{ requires l\_limited\_area} = \\ \text{.TRUE.} \end{array} $	
				- nudging is applied in primary domian only	
max_nudge_coeff_vn	R	0.04	1	Max. nudging coefficient for the horizontal wind	$\mathrm{nudge\_type} > 0$
				(i.e. the edge-normal wind component $v_n$ ).	
				Given the wind update due to the nudging term	
				on the rhs:	
				$v_n(t) = v_n^*(t) + \text{nudge\_coeff\_vn}(z) *$	
				$\operatorname{ndyn\_substeps} * [\overline{v_n}(t) - v_n^{\star}(t)],$	
				where $t$ and $z$ denote time and height,	
				respectively, $\overline{v_n}(t)$ is the target wind to nudge to,	
				and $v_n^*$ is the value before the nudging, the	
				vertical profile of the nudging coefficient reads: nudge coeff $vn(z) = max$ nudge coeff $vn *$	
				$[(z - \text{hudge\_start\_height})]^2$ , nudge_start_height)] <sup>2</sup> ,	
				for nudge start height $\leq z \leq$ top height (see	
				nudge start height below), and is zero	
				elsewhere.	
				The range of validity is max nudge coeff $vn \in$	
				$[0, \sim 1/\text{ndyn substeps}]$ , where the lower	
				boundary is mandatory.	
				, and the second	

Parameter	Type	Default	Unit	Description	Scope
max_nudge_coeff	R	0.075	1	Max. nudging coefficient for the thermodynamic	$\mathrm{nudge\_type} > 0$
thermdyn				variables selected by limarea_nml:	
				nudge_hydro_pres. The range of validity is	
				$\max_{\text{nudge\_coeff\_thermdyn}} \in [0, \sim]$	
				1/ndyn_substeps], where the lower boundary is	
				mandatory.	
nudge_start_height	R	12000	m	Nudging is applied for:	$\mathrm{nudge\_type} > 0$
				$nudge\_start\_height \le z \le top\_height,$	
				where $z$ denotes the nominal height of the grid	
				layer center, and top_height is the height of the	
				model top (see sleve_nml).	

Defined and used in: src/namelists/mo\_nudging\_nml.f90

### 2.31. nwp phy nml

The switches for the physics schemes and the time steps can be set for each model domain individually. If only one value is specified, it is copied to all child domains, implying that the same set of parameterizations and time steps is used in all domains. If the number of values given in the namelist is larger than 1 but less than the number of model domains, then the settings from the highest domain ID are used for the remaining model domains.

If the time steps are not an integer multiple of the advective time step (dtime), then the time step of the respective physics parameterization is automatically rounded to the next higher integer multiple of the advective time step. If the radiation time step is not an integer multiple of the cloud-cover time step it is automatically rounded to the next higher integer multiple of the cloud cover time step.

Parameter	Type	Default	Unit	Description	Scope
inwp_gscp	I (max_	1		cloud microphysics and precipitation	$run\_nml:iforcing = inwp$
	dom)			0: none	
				1: hydci (COSMO-EU microphysics, 2-cat ice:	
				cloud ice, snow)	
				2: hydci_gr (COSMO-DE microphysics, 3-cat	
				ice: cloud ice, snow, graupel)	
				3: as 1, but with improved ice nucleation scheme	
				by C. Koehler	
				4: Two-moment microphysics by A. Seifert	
				9: Kessler scheme	
qi0	R	0.0	kg/kg	cloud ice threshold for autoconversion	inwp_gscp=1
qc0	R	0.0	kg/kg	cloud water threshold for autoconversion	inwp_gscp=1
mu_rain	R	0.0		shape parameter in gamma distribution for rain	inwp_gscp>0
rain_n0_factor	R	1.0		tuning factor for intercept parameter of raindrop	inwp_gscp>0
				size distribution	
mu_snow	R	0.0		shape parameter in gamma distribution for snow	inwp_gscp>0
icpl_aero_gscp	I	0		0: off	currently only for inwp_gscp
				1: simple coupling between autoconversion and	= 1
				Tegen aerosol climatology; requires irad_aero=6	
				More advanced options are in preparation	

Parameter	Type	Default	Unit	Description	Scope
${\bf inwp\_convection}$	$\begin{array}{ c c c c c c c c c c c c c c c c c c c$	1		convection 0: none	run_nml:iforcing = inwp
$lshallowconv\_only$	$ \begin{array}{ c c } L \ (\max\_\\ dom) \end{array} $	.FALSE.		1: Tiedtke/Bechtold convection .TRUE.: use shallow convection only	$inwp\_convection = 1$
ldetrain_conv_prec	$\begin{bmatrix} L \ (\max\_\\ dom) \end{bmatrix}$	.FALSE.		.TRUE.: Activate detrainment of convective rain and snow	$inwp\_convection = 1$
icapdcycl	I	0		Type of CAPE correction to improve diurnal cycle for convection:  0 = none (IFS default prior to autumn 2013)  1 = intermediate testing option  2 = correctoins over land and water now operational at ECMWF  3 = correction over land as in 2 restricted to the tropics, no correction over water (this choice optimizes the NWP skill scores)	$inwp\_convection = 1$
icpl_aero_conv	I	0		0: off 1: simple coupling between autoconversion and Tegen aerosol climatology; requires irad aero=6	
iprog_aero	I	0		0: off 1: simple prognostic aerosol scheme for mineral dust, based on 2D aerosol optical depth fields of Tegen climatology 2: as option 1, but for all 5 aerosol types	irad_aero=6
$icpl\_o3\_tp$	I	1		0: off 1: simple coupling between the ozone mixing ratio and the thermal tropopause, restricted to the extratropics	$irad\_o3 = 7 \text{ or } 9$
${\bf inwp\_cldcover}$	I (max_dom)	1		cloud cover scheme for radiation 0: no clouds (only QV) 1: diagnostic cloud cover (by Martin Koehler) 2: prognostic total water variance (not yet started) 3: clouds from COSMO SGS cloud scheme 4: clouds as in turbulence (turbdiff) 5: grid scale clouds	$run\_nml:iforcing = inwp$
$inwp\_radiation$	I (max_dom)	1		radiation 0: none 1: RRTM radiation 2: Ritter-Geleyn radiation 3: PSRAD radiation	$run\_nml:iforcing = inwp$
$\mathbf{inwp\_satad}$	I	1		saturation adjustment 0: none 1: saturation adjustment at constant density	$run\_nml:iforcing = inwp$

Parameter	v 2	Default	Unit	Description	Scope
$rac{ ext{inwp\_turb}}{ ext{}}$	I (max_ 1			vertical diffusion and transfer	$run\_nml:iforcing = inwp$
_	dom)			0: none	
				1: COSMO diffusion and transfer	
				2: GME turbulence scheme	
				3: EDMF-DUALM (work in progress)	
				5: Classical Smagorinsky diffusion	
inwp sso	I (max   1			subgrid scale orographic drag	run nml:iforcing = inwp
mwp_550	$\begin{vmatrix} 1 & (max_{-}) \\ dom \end{vmatrix}$			0: none	Tun_mm.moremg mwp
	(dolli)			1: Lott and Miller scheme (COSMO)	
inwn gwd	I (max 1			non-orographic gravity wave drag	run nml:iforcing = inwp
$inwp\_gwd$					run_mm.noreing = mwp
	dom			0: none	
•				1: Orr-Ern-Bechtold-scheme (IFS)	1.6
$inwp\_surface$	$ I(\max_{-} 1$			surface scheme	run_nml:iforcing = inwp
	dom )			0: none	
			, , , , , , , , , , , , , , , , , , ,	1: TERRA	
ustart_raylfric	R   1	60.0	m/s	wind speed at which extra Rayleigh friction	$inwp_gwd > 0$
				starts	
$efdt\_min\_raylfric$	R 1	0800.	s	minimum e-folding time of Rayleigh friction	$inwp_gwd > 0$
				(effective for $u > ustart_raylfric + 90 m/s$ )	
latm_above_top	L (max_   .1	FALSE.		.TRUE.: take into account atmosphere above	$inwp\_radiation > 0$
<del>`</del>	$ \dot{dom}\rangle$			model top for radiation computation	
itype z0				Type of roughness length data used for	inwp turb $> 0$
· · <u> </u>				turbulence scheme:	· —
				1 = land-cover-related roughness including	
				contribution from sub-scale orography (does not	
				account for tiles)	
				2 = land-cover-related roughness based on	
				tile-specific landuse class	
				3 = land-cover-related roughness based on	
				tile-specific landuse class including contribution	
•		0.0		from sub-scale orography	1.6
${ m dt\_conv}$	\ \ =	00.	S	time interval of convection and cloud-cover call.	run_nml:iforcing = inwp
	dom )			If convection is switched off, dt_conv controlls	
				the time interval of cloud-cover, only.	
				currently each subdomain has the same value	
$\mathrm{dt}$ _rad	R (max_   1	800.	S	time interval of radiation call	$run\_nml$ :iforcing = inwp
	dom)			currently each subdomain has the same value	
${ m dt}$ sso	R (max_   1	200.	s	time interval of sso call	$run_nml:iforcing = inwp$
<del>_</del>	$  dom \rangle$			currently each subdomain has the same value	
dt gwd	1 '	200.	s	time interval of gwd call	run nml:iforcing = inwp
_~	dom			currently each subdomain has the same value	
lrtm filename	1 / /	ertmg lw.nc"		NetCDF file containing longwave absorption	
				coefficients and other data for RRTMG LW	
				k-distribution model.	1
				K distribution inode.	

Parameter	Type	Default	Unit	Description	Scope
${ m cldopt\_filename}$	C(:)	"ECHAM		NetCDF file with RRTM Cloud Optical	
		6_CldOpt		Properties for ECHAM6.	
		Props.nc"			

Defined and used in: src/namelists/mo\_nwp\_phy\_nml.f90

### 2.32. nwp\_tuning\_nml

Please note: These tuning parameters are NOT domain specific.

Parameter	Type	Default	Unit	Description	Scope
SSO (Lott and Miller)					
tune_gkwake	R (max_dom)	1.5		low level wake drag constant	run_nml:iforcing = inwp
tune_gkdrag	R (max_dom)	0.075		gravity wave drag constant	run_nml:iforcing = inwp
tune_gfrcrit	R (max_dom)	0.4		critical Froude number (controls depth of blocking layer)	run_nml:iforcing = inwp
tune_grcrit	R (max_dom)	0.25		critical Richardson number (controls onset of wave breaking)	run_nml:iforcing = inwp
GWD (Warner McIntyre)	•				·
tune_gfluxlaun	R	2.50e-3		total launch momentum flux in each azimuth (rho_o x F_o)	run_nml:iforcing = inwp
Grid scale microphysics (one momen	t)				
tune_zceff_min	R	0.01		Minimum value for sticking efficiency	$run_nml:iforcing = inwp$
tune_v0snow	R	25.0		factor in the terminal velocity for snow	$run_nml:iforcing = inwp$
tune_zvz0i	R	1.25	m/s	Terminal fall velocity of ice	$run\_nml:iforcing = inwp$
tune_icesedi_exp	R	0.33		Exponent for density correction of cloud ice sedimentation	run_nml:iforcing = inwp
Convection scheme					
tune_entrorg	R	1.85e-3	1/m	Entrainment parameter valid for dx=20 km (depends on model resolution)	run_nml:iforcing = inwp
tune_rprcon	R	1.4e-3		Coefficient for conversion of cloud water into precipitation	run_nml:iforcing = inwp
tune_rdepths	R	2.e4	Pa	Maximum allowed depth of shallow convection	$run\_nml:iforcing = inwp$
tune_capdcfac_et	R	0.5		Fraction of CAPE diurnal cycle correction applied in the extratropics	m icapdcycl = 3
tune_rhebc_land	R	0.75		RH threshold for onset of evaporation below cloud base over land	run_nml:iforcing = inwp
tune_rhebc_land_trop	R	0.75		RH threshold for onset of evaporation below cloud base over land in the tropics	run_nml:iforcing = inwp
tune_rhebc_ocean	R	0.85		RH threshold for onset of evaporation below cloud base over sea	run_nml:iforcing = inwp

Parameter	Type	Default	Unit	Description	Scope
tune_rhebc_ocean_trop	R	0.80		RH threshold for onset of evaporation below cloud base over sea in the tropics	run_nml:iforcing = inwp
tune_rcucov	R	0.05		Convective area fraction used for computing evaporation below cloud base	run_nml:iforcing = inwp
tune_rcucov_trop	R	0.05		Convective area fraction used for computing evaporation below cloud base in the tropics	run_nml:iforcing = inwp
tune_texc	R	0.125	K	Excess value for temperature used in test parcel ascent	run_nml:iforcing = inwp
tune_qexc	R	0.0125		Excess fraction of grid-scale QV used in test parcel ascent	run_nml:iforcing = inwp
tune_box_liq	R	0.05		Box width for liquid cloud diagnostic in cloud cover scheme	run_nml:iforcing = inwp; inwp_cldcover = 1
tune_box_liq_asy	R	2.5		Asymmetry factor for liquid cloud cover diagnostic	run_nml:iforcing = inwp; inwp_cldcover = 1
lcalib_clcov	L	.TRUE.		Apply calibration of layer-wise cloud cover diagnostics	run_nml:iforcing = inwp
Misc		·	·		
itune_albedo	I	0		MODIS albedo tuning 0: None 1: dimmed sahara	$\begin{array}{c} \operatorname{run\_nml:iforcing} = \operatorname{inwp} \\ \operatorname{albedo\_type} = 2 \end{array}$
tune_minsnowfrac	R	0.2		Minimum value to which the snow cover fraction is artificially reduced in case of melting show	$\begin{array}{l} lnd\_nml:idiag\_snowfrac = \\ 20/30/40 \end{array}$
IAU					
max_freshsnow_inc	R	0.025		Maximum allowed freshsnow increment per analysis cycle (positive or negative)	init_mode=5 (MODE_IAU)

Defined and used in: src/namelists/mo\_nwp\_tuning\_nml.f90

## 2.33. output\_nml (relevant if run\_nml/output='nml')

Please note: There may be several instances of output\_nml in the namelist file, every one defining a list of variables with separate attributes for output.

Parameter	Type	Default	Unit	Description	Scope
dom	I(:)	-1		Array of domains for which this name-list is	
				used. If not specified (or specified as -1 as the	
				first array member), this name-list will be used	
				for all domains.	
				Attention: Depending on the setting of the	
				parameter l_output_phys_patch these are	
				either logical or physical domain numbers!	

Parameter	Type	Default	Unit	Description	Scope
file_interval	С	7 7		Defines the length of a file in terms of an ISO-8601 duration string. An example for this time stamp format is given below. This namelist parameter can be set instead of steps_per_file.	
filename_format	С	see description.		Output filename format. Includes keywords path, output_filename, physdom, etc. (see below). Default is <pre><output_filename>_DOM<physdom>_<levtype>_</levtype></physdom></output_filename></pre>	
filename_extn	С	"default"		<pre><jfile> User-specified filename extension (empty string also possible). If this namelist parameter is chosen as "default", then we have ".nc" for NetCDF output files, and ".grb" for GRIB1/2.</jfile></pre>	
filetype	I	4		One of CDI's FILETYPE_XXX constants.  Possible values: 2=FILETYPE_GRB2, 4=FILETYPE_NC2, 5=FILETYPE_NC4	
m_levels	C	None		Model level indices (optional). Allowed is a comma- (or semicolon-) separated list of integers, and of integer ranges like "1020". One may also use the keyword "nlev" to denote the maximum integer (or, equivalently, "n" or "N"). Furthermore, arithmetic expressions like "(nlev - 2)" are possible. Basic example: m_levels = "1,3,510,20(nlev-2)"	
h_levels	R(:)	None	m	height levels	
p_levels	R(:)	None	Pa	pressure levels	
i_levels	R(:)	None	K	isentropic levels	
ml_varlist hl_varlist pl_varlist il_varlist include_last	C(:) C(:) C(:) C(:) L	None None None None .TRUE.		Name of model level fields to be output.  Name of height level fields to be output.  Name of pressure level fields to be output.  Name of isentropic level fields to be output.  Flag whether to include the last time step	

Parameter	Type	Default	Unit	Description	Scope
mode	I	2		$1 =  ext{forecast mode}, 2 =  ext{climate mode}$	
				In climate mode the time axis of the output file	
				is set to TAXIS_ABSOLUTE. In forecast mode	
				it is set to TAXIS RELATIVE. Till now the	
				forecast mode only works if the output is at	
				multiples of 1 hour	
taxis tunit	I	2		Time unit of the TAXIS RELATIVE time axis.	$\mod e=1$
<del>_</del>				$1 = \text{TUNIT SECOND}^-$	
				2 = TUNIT MINUTE	
				5 = TUNIT HOUR	
				9 = TUNIT  DAY	
				For a complete list of possible values see cdilib.c	
output bounds	R(k*3)	None		Post-processing times: start, end, increment. We	
output_bounds	$\mathbf{n}(\kappa * \mathbf{o})$	None		choose the advection time step matching or	
				following the requested output time, therefore we	
				require output_bounds(3) > dtime. Multiple	
				triples are possible in order to define multiple	
				starts/ends/intervals. See namelist parameters	
				output_start, output_end, output_interval	
				for an alternative specification of output events.	
${f output\_time\_unit}$	I	1		Units of output bounds specification.	
				1 = second	
				$2 = { m minute}$	
				$3 = \mathrm{hour}$	
				4 = day	
				$5=\mathrm{month}$	
				6 = year	
output filename	$\mid$ C	None		Output filename prefix (which may include	
				path). Domain number, level type, file number	
				and extension will be added, according to the	
				format given in namelist parameter	
				"filename format".	
output grid	$\mid$ L	.FALSE.		Flag whether grid information is added to	
output_grid		TITLESE.		output.	
output start	C(:)	5 5		ISO8601 time stamp for begin of output. An	
output_start	(.)			example for this time stamp format is given	
				below. More than one value is possible in order	
				to define multiple start/end/interval triples. See	
				namelist parameter output_bounds for an	
				alternative specification of output events.	

Parameter	Type	Default	Unit	Description	Scope
output_end	C(:)	5 5		ISO8601 time stamp for end of output. An	
_				example for this time stamp format is given	
				below. More than one value is possible in order	
				to define multiple start/end/interval triples. See	
				namelist parameter output_bounds for an	
				alternative specification of output events.	
output interval	C(:)	5 5		ISO8601 time stamp for repeating output	
o dop do _ moer var				intervals. We choose the advection time step	
				matching or following the requested output time,	
				therefore we require output_bounds(3) >	
				dtime. An example for this time stamp format	
				is given below. More than one value is possible	
				in order to define multiple start/end/interval	
				triples. See namelist parameter output_bounds	
				for an alternative specification of output events.	
openation	- C	None		Use this variable for internal diagnostics applied	
operation		None		9 11	
				on all given output variables or groups except time-constant ones: mean for generating time	
				averaged, square for time averaged square	
				values, max or min for maximum and minimum	
				values within the corresponding interval, i.e.	
				output_interval.	
				Supported are 2D, 3D and single values like	
				global means on model levels of all components.	
				All operations can be used on global and nested	
				grids.	
pe_placement_il	$\mid I(:)$	-1		Advanced output option: Explicit assignment of	
				output MPI ranks to the isentropic level output	
				file. At most stream_partitions_il different	
				ranks can be specified. See namelist parameter	
				<pre>pe_placement_ml for further details.</pre>	
$pe\_placement\_hl$	I(:)	-1		Advanced output option: Explicit assignment of	
				output MPI ranks to the height level output file.	
				At most stream_partitions_hl different ranks	
				can be specified. See namelist parameter	
				<pre>pe_placement_ml for further details.</pre>	
pe placement ml	I(:)	-1		Advanced output option: Explicit assignment of	
				output MPI ranks to the model level output file.	
				At most stream_partitions_ml different ranks	
				can be specified, out of the following list: 0	
				(num_io_procs - 1). If this namelist parameters	
				is not provided, then the output ranks are	
				chosen in a Round-Robin fashion among those	
				ranks that are not occupied by explicitly placed	
				output files.	
	I	1	l	Sacpas mosi	

Parameter	Type	Default	Unit	Description	Scope
pe_placement_pl	I(:)	-1		Advanced output option: Explicit assignment of	
				output MPI ranks to the pressure level output	
				file. At most stream_partitions_pl different	
				ranks can be specified. See namelist parameter	
				pe_placement_ml for further details.	
ready_file	$\mid$ C	'default'		A ready file is a technique for handling	
				dependencies between the NWP processes. The	
				completion of the write process is signalled by	
				creating a small file with name ready_file.	
				Different output_nml's may be joined together	
				to form a single ready file event. The setting of	
				ready_file = "default" does not create a	
				ready file. The ready file name may contain	
				string tokens <path>, <datetime>, <ddhhmmss>,</ddhhmmss></datetime></path>	
				<dddhhmmss> which are substituted as described</dddhhmmss>	
				for the namelist parameter filename_format.	
reg_def_mode	I	0		Specify if the "delta" value prescribes an interval	remap=1
				size or the total *number* of intervals: 0: switch	
				automatically between increment and no. of grid	
				points, 1: reg_lon/lat_def(2) specifies	
				increment, 2: reg_lon/lat_def(2) specifies no.	
				of grid points.	
remap	I	0		interpolate horizontally	
				0: none	
				1: to regular lat-lon grid	
$north\_pole$	R(2)	0,90		definition of north pole for rotated lon-lat grids	
				([longitude, latitude].	
$reg\_lat\_def$	R(3)	None		start, increment, end latitude in degrees.	remap=1
				Alternatively, the user may set the number of	
				grid points instead of an increment. Details for	
				the setting of regular grids is given below	
				together with an example.	
$reg\_lon\_def$	R(3)	None		The regular grid points are specified by three	remap=1
				values: start, increment, end given in degrees.	
				Alternatively, the user may set the number of	
				grid points instead of an increment. Details for	
				the setting of regular grids is given below	
				together with an example.	
$steps\_per\_file$	I	-1		Max number of output steps in one output file.	
				If this number is reached, a new output file will	
				be opened.	
steps_per_file_inclfirst	L	see descr.		Defines if first step is counted wrt.	
				steps_per_file files count. The default is	
				.FALSE. for GRIB2 output, and .TRUE.	
				otherwise.	

Parameter	Type	Default	Unit	Description	Scope
stream_partitions_hl	I	1		Splits height level output of this namelist into	
				several concurrent alternating files. See namelist	
				parameter stream_partitions_ml for details.	
stream_partitions_il	I	1		Splits isentropic level output of this namelist into	
				several concurrent alternating files. See namelist	
				parameter stream_partitions_ml for details.	
stream_partitions_ml	I	1		Splits model level output of this namelist into	
				several concurrent alternating files. The output	
				is split into $N$ files, where the start date of part	
				$i$ gets an offset of $(i-1)*$ output_interval.	
				The output interval is then replaced by	
				$N*$ output_interval, the include_last flag is	
				set to .FALSE., the steps_per_file_inclfirst	
				flag is set to .FALSE., and the steps_per_file	
				counter is set to 1.	
stream_partitions_pl	I	1		Splits pressure level output of this namelist into	
				several concurrent alternating files. See namelist	
				parameter stream_partitions_ml for details.	
rbf_scale	R	-1.		Explicit setting of RBF shape parameter for	$ $ interpol_nml:rbf_scale_mode_ $\parallel$ =3
				interpolated lon-lat output. This namelist	
				parameter is only active in combination with	
				$interpol\_nml:rbf\_scale\_mode\_ll=3.$	

Defined and used in: src/io/shared/mo\_name\_list\_output\_init.f90

Interpolation onto regular grids: Horizontal interpolation onto regular grids is possible through the namelist setting remap=1, where the mesh is defined by the parameters

- reg\_lon\_def: mesh latitudes in degrees,
- reg\_lat\_def: mesh longitudes in degrees,
- north\_pole: definition of north pole for rotated lon-lat grids.

The regular grid points in reg\_lon\_def, reg\_lat\_def are each specified by three values, given in degrees: start, increment, end. The mesh then contains all grid points start + k \* increment <= end, where k is an integer. Instead of defining an increment it is also possible to prescribe the number of grid points.

- Setting the namelist parameter reg\_def\_mode=0: Switch automatically from increment specification to no. of grid points, when the reg\_lon/lat\_def(2) value is larger than 5.0.
- 1: reg\_lon/lat\_def(2) specifies increment
- 2: reg\_lon/lat\_def(2) specifies no. of grid points

For longitude values the last grid point is omitted if the end point matches the start point, e.g. for 0 and 360 degrees.

#### Examples

local grid with 0.5 degree increment:

 $reg_lon_def = -30., 0.5, 30.$ 

global grid with 720x361 grid points:

```
reg_lat_def = 90.,-0.5, -90.
reg_lon_def = 0.,720,360.
reg_lat_def = -90.,360,90.
```

Time stamp format: The namelist parameters output\_start, output\_end, output\_interval allow the specification of time stamps according to ISO 8601. The general format for time stamps is YYYY-MM-DDThh:mm:ss where Y: year, M: month, D: day for dates, and hh: hour, mm: minute, ss: second for time strings. The general format for durations is PnYnMnDTnHnMnS. See, for example, http://en.wikipedia.org/wiki/ISO\_8601 for details and further specifications.

NOTE: as the mtime library underlaying the output driver currently has some restrictions concerning the specification of durations:

- 1. Any number n in PnYnMnDTnHnMnS must have two digits. For instance use "PT06H" instead of "PT6H"
- 2. In a duration string PnyearYnmonMndayDTnhrHnminMnsecS the numbers nxyz must not pass the carry over number to the next larger time unit: 0<=nmon<=12, 0<=nhr<=23, 0<=nmin<=59, 0<=nsec<=59.999. For instance use "PO1D" instead of "PT01M" instead of "PT60S".

Soon the formatting problem will be resolved and the valid number ranges will be enlarged. (2013-12-16).

#### Examples

```
date and time representation (output_start, output_end) duration (output interval)
```

2013-10-27T13:41:00Z POODTO6HOOMOOS

#### Variable Groups

Keyword "group:": Using the "group:" keyword for the namelist parameters ml\_varlist, hl\_varlist, pl\_varlist, sets of common variables can be added to the output:

```
group:all
                                                                 output of all variables (caution: do not combine with mixed vertical interpolation)
                                                                 basic atmospheric variables on model levels
group:atmo_ml_vars
                                                                 same set as atmo ml vars, but except pres
group:atmo_pl_vars
                                                                 same set as atmo ml vars, but expect height
group:atmo_zl_vars
                                                                 additional prognostic variables of the nonhydrostatic model
group:nh_prog_vars
                                                                 derived atmospheric variables
group:atmo_derived_vars
group:rad_vars
group:precip_vars
group:cloud_diag
group:pbl_vars
group:phys_tendencies
group:land_vars
                                                                 snow variables
group:snow_vars
                                                                 multi-layer snow variables
group:multisnow_vars
group:additional_precip_vars
group:dwd_fg_atm_vars
                                                                 DWD first guess fields (atmosphere)
                                                                 DWD first guess fields (surface/soil)
group:dwd_fg_sfc_vars
                                                                 ART volcanic ash fields
group:ART_AERO_VOLC
group:ART_AERO_RADIO
                                                                 ART radioactive tracer fields
                                                                 ART mineral dust aerosol fields
group:ART_AERO_DUST
                                                                 ART sea salt aerosol fields
group:ART_AERO_SEAS
group:prog_timemean
                                                                 time mean output: temp, u, v, rho
```

group:tracer\_timemean
group:echam\_timemean
group:atmo\_timemean

time mean output: qv, qc, qi

time mean output: most echam surface variables

time mean variables from prog\_timemean,tracer\_timemean, echam\_timemean

Keyword "tiles:": The "tiles:" keyword allows to add all tiles of a specific variable to the output, without the need to specify all tile fields separately. E.g. "tiles:t\_g" (read: "tiles of t\_g") automatically adds all t\_g\_t\_X fields to the output. Here, X is a placeholder for the tile number. Make sure to specify the name of the aggregated variable rather than the name of the corresponding tile container (i.e. in the given example it must be t\_g, and not t\_g\_t!).

#### Note:

There exists a special syntax which allows to remove variables from the output list, e.g. if these undesired variables were contained in a previously selected group. Typing "-<varname>" (for example "-temp") removes the variable from the union set of group variables and other selected variables. Note that typos are not detected but that the corresponding variable is simply not removed!

#### Keyword substitution in output filename (filename\_format):

path
output\_filename
physdom
levtype
levtype\_l
jfile
datetime
datetime2
datetime3
ddhhmmss
dddhhmmss
hhmmss
npartitions
ifile\_partition
total index

substituted by model base dir substituted by output\_filename substituted by physical patch ID substituted by level type "ML", "PL", "HL", "IL" like levtype, but in lower case substituted by output file counter substituted by ISO-8601 date-time stamp in format YYYY-MM-DDThh:mm:ss.ssz substituted by ISO-8601 date-time stamp in format YYYYMMDDThhmmssZ substituted by ISO-8601 date-time stamp in format YYYYMMDDThhmmss.sssZ substituted by relative day-hour-minute-second string substituted by relative three-digit day-hour-minute-second string substituted by relative hour-minute-second string If namelist is split into concurrent files: number of stream partitions. If namelist is split into concurrent files: stream partition index of this file. If namelist is split into concurrent files: substituted by the file counter (like in jfile), which an "unsplit" namelist would have produced

### 2.34. parallel\_nml

Parameter	Type	Default	Unit	Description	Scope
nproma	I	1		chunk length	
n_ghost_rows	I	1		number of halo cell rows	
division_method	I	1		method of domain decomposition	
				0: read in from file	
				1: use built-in geometric subdivision	
division_file_name	C			Name of division file	$division\_method = 0$
ldiv_phys_dom	L	.TRUE.		.TRUE.: split into physical domains before	$division\_method = 1$
				computing domain decomposition (in case of	
				merged domains)	
				(This reduces load imbalance; turning off this	
				option is not recommended except for very small	
				processor numbers)	
p_test_run	L	.FALSE.		TRUE. means verification run for MPI	
				parallelization (PE 0 processes full domain)	
num test pe	I	-1		If set to more than 1, use this many ranks for	p  test run = .TRUE.
				testing and switch to different consistency test.	
				This enables tests for identity in setups which	
				are too big to run on a single rank but is limited	
				to comparing one MPI parallelization setup vs.	
				another, obviously.	
l test openmp	L	.FALSE.		if .TRUE. is combined with	$p_{test_run} = .TRUE.$
				p test run=.TRUE. and OpenMP	
				parallelization, the test PE gets only 1 thread in	
				order to verify the OpenMP parallelization	
l log checks	L	.FALSE.		if .TRUE. messages are generated during each	
				synchonization step (use for debugging only)	
l_fast_sum	L	.FALSE.		if .TRUE., use fast (not	
				processor-configuration-invariant) global	
				summation	
use_dycore_barrier	L	.FALSE.		if .TRUE., set an MPI barrier at the beginning	
				of the nonhydrostatic solver (do not use for	
				production runs!)	
itype_exch_barrier	I	0		1: set an MPI barrier at the beginning of each	
				MPI exchange call	
				2: set an MPI barrier after each MPI WAIT call	
				3: 1+2 (do not use for production runs!)	
iorder_sendrecv	I	1		Sequence of send/receive calls:	
				$1 = \mathrm{irecv/send}$	
	I	1			1
				$2=\mathrm{isend/rec} v$	

Parameter	Type	Default	Unit	Description	Scope
default_comm-	I	1		Default implementation of mo_communication	
_pattern_type				to be used:	
				1 = original	
				2 = YAXT	
itype comm	I	1		1: use local memory for exchange buffers	
				3: asynchronous halo communication for	
				dynamical core (currently deactivated)	
num io procs	I	0		Number of I/O processors (running exclusively	
				for doing I/O)	
num restart procs	I	0		Number of restart processors (running	
				exclusively for doing restart)	
num prefetch proc	I	1		Number of processors for prefetching of	itype latbc $\geq 1$
				boundary data asynchronously for a limited area	
				run (running exclusively for reading Input	
				boundary data. Maximum no of processors used	
				for it is limited to 1).	
pio_type	I	1		Type of parallel I/O.	
pro_type	1			1: Classical async I/O processors	
				2: CDI-PIO (Experimental!) Experimental!	
use_icon_comm	L	.FALSE.		Enable the use of MPI bulk communication	
		.FALSE.		through the icon comm lib	
icon comm debug	brack L	.FALSE.		Enable debug mode for the icon comm lib	
max send recv-	I	131072		Size of the send/receive buffers for the	
_buffer_size	1	131072		icon comm lib.	
	$\mid$ L	.FALSE.		Enable this flag if output fields shall be gathered	
use_dp_mpi2io	L	.FALSE.		by the output processes in DOUBLE	
				PRECISION.	
negtont shaple sign	T	1		(Advanced namelist parameter:) Number of	
restart_chunk_size	1	1		levels to be buffered by the asynchronous restart	
				process. The (asynchronous) restart is capable of	
				writing and communicating more than one 2D	
	т	1		slice at once.	
num_dist_array_replicas	I	1		(Advanced namelist parameter:) Number of	
				replicas of the distributed array used for the	
is present stride		1		pre_patch.	
io_process_stride	1	-1		(Advanced namelist parameter:) Stride of	
				processes taking part in reading of data. (Few	
				reading processes, i.e. a large stride, often gives	
				best performance.)	
io_process_rotate	1	0		(Advanced namelist parameter:) Rotate of	
				processes taking part in reading of data.	
				(Process taking part if p_pe_work % stride ==	
				rotate)	

### 2.35. psrad\_nml

Parameter	Type	Default	Unit	Description	Scope
lradforcing	L(2)	.FALSE.		switch for diagnostics of aerosol forcing in the	
				solar spectral range (lradforcing(1)) and the	
				thermal spectral range $(lradforcing(2))$ .	
lw_gpts_ts	I	1		number of g-points in Monte-Carlo spectral	
				integration for thermal radiation, see	
				$lw\_spec\_samp$	
$lw\_spec\_samp$	I	1		sampling of spectral bands in radiation	
				calculation for thermal radiation	
				$lw\_spec\_samp = 1$ : standard broad band	
				sampling	
				lw_spec_samp = 2: Monte-Carlo spec- tral	
				integration (MSCI); lw_gpts_ts randomly	
				chosen g-points per column and radiation call	
				$lw\_spec\_samp = 3$ : choose g-points not	
				completely randomly in order to reduce errors in	
				the surface radiative fluxes	
rad_perm	I	0		integer number that influences the perturba-	
	_			tion of the random seed from column to column	
$sw\_gpts\_ts$		1		number of g-points in Monte-Carlo spectral	
				integration for solar radiation, see	
				sw_spec_samp	
$sw\_spec\_samp$	1	1		sampling of spectral bands in radiation	
				calculation for solar radiation	
				$sw\_spec\_samp = 1$ : standard broad band	
				sampling	
				sw_spec_samp = 2: Monte-Carlo spectral	
				integration (MSCI); lw_gpts_ts randomly	
				chosen g-points per column and radiation call	
				sw_spec_samp = 3: choose g-points not	
				completely randomly in order to reduce errors in	
				the surface radiative fluxes	

Defined and used in: src/echam\_phy\_psrad/mo\_psrad\_radiation.f90

## 2.36. radiation\_nml

Parameter	Type	Default	Unit	Description	Scope
ldiur	L	.TRUE.		switch for solar irradiation:	
				.TRUE.:diurnal cycle,	
				.FALSE.:zonally averaged irradiation	

Parameter	Type	Default   Unit	Description	Scope
nmont h	I	0	0: Earth circles on orbit	
			1-12: Earth orbit position fixed for specified	
			month	
lyr_perp	L	.FALSE.	.FALSE.: transient Earth orbit following	
			VSOP87	
			.TRUE.: Earth orbit of year yr perp of the	
			VSOP87 orbit is perpertuated	
yr_perp	L	-99999	year used for lyr $perp = .TRUE$ .	
isolrad	I	0	Insolation scheme	
			0: Use original SRTM insolation.	
			1: Use insolation from external file containing	
			the spectrally resolved insolation (monthly	
			means)	
			2: Use preindustrial insolation as in CMIP5	
			(average from 1844–1856)	
			3: Use insolation for AMIP-type CMIP5	
			simulation (average from 1979–1988)	
			4: Use insolation for RCE-type simulation with	
			$\cos(\text{zenith angle}) = \text{pi}/4 \text{ (with PSRAD: use "4")}$	
			if the diurnal cycle is switched on)	
			5: Use insolation for RCE-type simulation with	
			PSRAD if the diurnal cycle is switched off.	
izenith		4	Choice of zenith angle formula for the radiative	
	-		transfer computation.	
			0: Sun in zenith everywhere	
			1: Zenith angle depends only on latitude	
			2: Zenith angle depends only on latitude. Local	
			time of day fixed at 07:14:15 for radiative	
			transfer computation ( $\sin(\text{time of day}) = 1/\text{pi}$	
			3: Zenith angle changing with latitude and time	
			of day	
			4: Zenith angle and irradiance changing with	
			season, latitude, and time of day (iforcing=inwp	
			only)	
islope rad		0	Slope correction for surface radiation:	
	-		0: None	
			1: Slope correction for direct solar radiation	
			without shading effects	
albedo_type	T	1	Type of surface albedo	iforcing=inwp
arsono_upe	_	<u> </u>	1: based on soil type specific tabulated values	moroung mark
			(dry soil)	
			2: MODIS albedo	
	I	1	2. MODIO anocao	1

Parameter	Type	Default	Unit	Description	Scope
direct_albedo	I	4		Direct beam surface albedo. Options mainly	iforcing=inwp
				differ in terms of their solar zenith angle (SZA)	albedo_type=2
				dependency)	
				1: SZA dependency following Ritter-Geleyn;	
				applied to unconditionally all grid points	
				2: SZA dependency following Zaengl (pers.	
				comm.). Same as 1 for water, but for 'rough	
				surfaces' over land the direct albedo is not	
				allowed to exceed the corresponding broadband	
				diffuse albedo.	
				3: SZA dependency following Yang (2008) for	
				snow-free land points. Same as 1 for water/ice	
				and 2 for snow.	
				4: SZA dependency following Briegleb (1992) for	
				snow-free land points. Same as 1 for water/ice and 2 for snow.	
ield evenlen	T			Method for cloud overlap calculation in	iforcing=inwp
icld_overlap	1			shortwave part of RRTM	inwp radiation=1
				1: maximum-random overlap	IIIwp_radration=1
				2: generalized overlap (Hogan, Illingworth, 2000)	
				3: maximum overlap	
				4: random overlap	

Parameter	Type	Default	Unit	Description	Scope
irad_h2o	I	1		Switches for the concentration of radiative agents	
$irad\_co2$		2		$irad_xyz = 0$ : set to zero	
$irad\_ch4$		3		$irad_h2o = 1$ : vapor, cloud water and cloud ice	
$irad_n2o$		3		from tracer variables	
$irad_o3$		0		$irad\_co2 = 1$ : $CO_2$ from tracer variable	
$irad_o2$		2		$\mathrm{irad\_co2/ch4/n2o/o2/cfc11/cfc12} = 2$ :	
irad cfc11		2		concentration given by	
irad cfc12		2		m vmr co2/ch4/n2o/o2/cfc11/cfc12	
_				$\frac{1}{1}$ irad $\frac{1}{1}$ ch4/n2o = 3: tanh-profile with surface	
				concentration given by vmr ch4/n2o	
				irad $co2/cfc11/cfc12 = 4$ : time dependent	
				concentration from greenhouse gas file	
				$irad_ch4/n2o = 4$ : time dependent tanh-profile	
				with surface concentration from greenhouse gas	
				file irad o $3 = 2$ : ozone climatology from MPI	
				irad o $3 = 4$ : ozone clim for Aqua Planet Exp	
				a irad $a$ o3 = 6: ozone climatology with T5	
				geographical distribution and Fourier series for	
				seasonal cycle for run $nml/iforcing = 3 (NWP)$	
				irad o $3 = 7$ : GEMS ozone climatology (from	
				IFS) for run nml/iforcing = 3 (NWP)	
				irad o $3 = 8$ : ozone climatology for AMIP	
				irad o3 = 9: MACC ozone climatology (from	
				IFS) for run nml/iforcing = 3 (NWP)	
				irad o3 = 79: Blending between GEMS and	
				MACC ozone climatologies (from IFS) for	
				run nml/iforcing = 3 (NWP); MACC is used	
				over Antarctica	
				irad o $3 = 97$ : As 79, but MACC is also used	
				above 1 hPa with transition zone between 5 hPa	
				and 1 hPa	
				irad o3 = 10: Linearized ozone chemistry (ART	
				extension necessary) for run nml/iforcing = 3	
				(NWP)	
vmr co2	R	348.0e-6		Volume mixing ratio of the radiative agents	
vmr ch4	11	1650.0e-9		volume mixing radio of the radiative agents	
		306.0e-9			
vmr_n2o		0.20946			
vmr_o2		0.20946 214.5e-12			
vmr_cfc11					
${ m vmr\_cfc}12$		371.1e-12			

Parameter	Type	Default	Unit	Description	Scope
fh2o	R	1.		Scaling factors for concentrations used in	$run\_nml/iforcing=2$
fco2		1.		radiation	(ECHAM)
fch4		1.			
fn2o		1.			
fo3		1.			
fo2		1.			
fcfc		1.			
irad_aero	I	2		Aerosols  1: prognostic variable  2: global constant  3: externally specified  5: Tanre aerosol climatology for run_nml/iforcing = 3 (NWP)  6: Tegen aerosol climatology for run_nml/iforcing = 3 (NWP) .AND. itopo =1  9: ART online aerosol radiation interaction, uses Tegen for aerosols not chosen to be represented in ART for run_nml/iforcing = 3 (NWP) .AND. itopo =1 .AND. lart=TRUE .AND. iart_ari=1	
lrad_aero_diag	L	.FALSE.		writes actual aerosol optical properties to output	
ighg	I	0		Select dynamic greenhouse gases scenario (read from file)  0: select default gas volume mixing ratios - 1990	run_nml/iforcing=2 (ECHAM)
				values (CMIP5)	
				1 : transient CMIP5 scenario from file	

Defined and used in: src/namelists/mo\_radiation\_nml.f90

## 2.37. run\_nml

Parameter	Type	Default	Unit	Description	Scope
nsteps	I	-999		Number of time steps of this run. Allowed range	
				is $\geq 0$ ; setting a value of 0 allows writing initial	
				output (including internal remapping) without	
				calculating time steps.	

Parameter	Type	Default	Unit	Description	Scope
dtime	R	600.0	s	time step.	
				For real case runs the maximum allowable time	
				step can be estimated as	
				$1.8 \cdot \text{ndyn} \text{ substeps} \cdot \overline{\Delta x}  \text{s km}^{-1}$ ,	
				where $\frac{\overline{\Delta x}}{\Delta x}$ is the average resolution in km and	
				ndyn_substeps is the number of dynamics	
				substeps set in nonhydrostatic nml.	
				ndyn substeps should not be increased beyond	
				the default value 5.	
144	т	.TRUE.		Idealized testcase runs	
ltestcase	L				
ldynamics	L	.TRUE.		Compute adiabatic dynamic tendencies	
iforcing	1	0		Forcing of dynamics and transport by	
				parameterized processes. Use positive indices for	
				the atmosphere and negative indices for the	
				ocean.	
				0: no forcing	
				1: Held-Suarez forcing	
				2: ECHAM forcing	
				3: NWP forcing	
				4: local diabatic forcing without physics	
				5: local diabatic forcing with physics	
				-1: MPIOM forcing (to be done)	
ltransport	L	.FALSE.		Compute large-scale tracer transport	
ntracer	I	0		Number of advected tracers handled by the	
norucci	1			large-scale transport scheme	
lvert nest	L	.FALSE.		If set to .true. vertical nesting is switched on	
Tvertnest	L	TALSE.			
1	T/	9.1		(i.e. variable number of vertical levels)	I A TIDLE
${ m num\_lev}$	I(max_	31		Number of full levels (atm.) for each domain	lvert_nest=.TRUE.
1.0	dom)				, , , , , , , , , , , , , , , , , , , ,
nshift	I(max_	0		vertical half level of parent domain which	lvert_nest=.TRUE.
	dom)			coincides with upper boundary of the current	
				domain required for vertical refinement, which is	
				not yet implemented	
ltimer	L	.TRUE.		TRUE: Timer for monitoring the runtime of	
				specific routines is on (FALSE = off)	
timers_level	I	1			
activate_sync_timers	L	F		TRUE: Timer for monitoring runtime of	
<u> </u>				communication routines (FALSE = off)	
msg level	I	10		controls how much printout is written during	
				runtime.	
				For values less than 5, only the time step is	
				written.	
msg timestamp	L	.FALSE.		If .TRUE., precede output messages by time	
mo8_umestamp	"	(ITIDE)			
			I	stamp.	

Parameter	Type	Default	Unit	Description	Scope
test_mode  debug_check_level  output	I C(:)	0 "nml", "totint"		Setting a value larger than 0 activates a dummy mode in which time stepping is changed into just doing iterations, and MPI communication is replaced by copying some value from the send buffer into the receive buffer (does not work with nesting and reduced radiation grid because the send buffer may then be empty on some PEs) Setting a value larger than 0 activates debug checks.  Main switch for enabling/disabling components of the model output. One or more choices can be set (as an array of string constants). Possible choices are:  • "none": switch off all output;  • "nml": new output mode (cf. output_nml);  • "totint": computation of total integrals.  • "maxwinds": write max. winds to separate ASCII file "maxwinds.log".  If the output namelist parameter is not set	m iequations = 3
restart_filename	C			explicitly, the default setting "nml", "totint" is assumed.  File name for restart/checkpoint files (containing keyword substitution patterns <gridfile>,</gridfile>	
				<pre><idom>, <rsttime>, <mtype>). default: "<gridfile>_restart_<mtype>_<rsttime>.nc".</rsttime></mtype></gridfile></mtype></rsttime></idom></pre>	
profiling_output	I	1		controls how profiling printout is written:  TIMER_MODE_AGGREGATED=1,  TIMER_MODE_DETAILED=2,  TIMER_MODE_WRITE_FILES=3.	
lart	L	.FALSE.		Main switch which enables the treatment of atmospheric aerosol and trace gases (The ART package of KIT is needed for this purpose)	
ldass_lhn	L	.FALSE.		Main switch which enables the assimilation of radar derived precipitation rate via Latent Heat Nudging	
check_uuid_gracefully	L	.FALSE.		If this flag is set to .TRUE. we give only warnings for non-matching UUIDs.	

Defined and used in: src/namelists/mo\_run\_nml.f90

### 2.38. sleve\_nml (relevant if nonhydrostatic\_nml:ivctype=2)

Parameter	Type	Default	Unit	Description	Scope
min_lay_thckn	R	50	m	Layer thickness of lowermost layer; specifying	
				zero or a negative value leads to constant layer	
				thicknesses determined by top_height and nlev	
max_lay_thckn	R	25000	m	Maximum layer thickness below the height given	
				by htop_thcknlimit (NWP recommendation:	
				400 m)	
				Use with caution! Too ambitious settings may	
				result in numerically unstable layer	
1.1.1.1.1.		15000		configurations.	
htop_thcknlimit	R	15000	m	Height below which the layer thickness does not	
1 11 1	т	1		exceed max_lay_thckn	
itype_laydistr	1	1		Type of analytical function used to specify the distribution of the vertical coordinate surfaces	
				1: transformed cosine, 2: third-order polynomial; in this case, stretch_fac should be less than 1,	
				particularly for large numbers of model levels;	
				the algorithm always works for stretch fac=0.5	
top height	$\mid$ R	23500.0	m	Height of model top	
stretch fac	R	1.0		Stretching factor to vary distribution of model	
	10	1.0		levels; values <1 increase the layer thickness	
				near the model top	
decay scale 1	$\mid$ R	4000	m	Decay scale of large-scale topography component	
decay_scale_2	R	2500	m	Decay scale of small-scale topography component	
decay exp	$\mathbb{R}$	1.2		Exponent of decay function	
flat height	R	16000	m	Height above which the coordinate surfaces are	
_				flat	
$lread\_smt$	L	.FALSE.		read smoothed topography from file (TRUE) or	
				compute internally (FALSE)	

Defined and used in: src/namelists/mo\_sleve\_nml.f90

### 2.39. synsat nml<sup>1</sup>

This namelist enables the RTTOV library incorporated into ICON for simulating satellite radiance and brightness temperatures. RTTOV is a radiative transfer model for nadir-viewing passive visible, infrared and microwave satellite radiometers, spectrometers and interferometers, see

https://nwpsaf.eu/deliverables/rtm

for detailed information.

<sup>&</sup>lt;sup>1</sup>Important note: This feature is currently active for configuration dwd+cray only.

Parameter	Type	Default	Unit	Description	Scope
lsynsat	L	.FALSE.		Main switch: Enables/disables computation of	
	(max_dom)			synthetic satellite imagery for each model	
				domain.	
nlev_rttov	I	51		Number of RTTOV levels.	

Enabling the synsat module makes the following 32 two-dimensional output fields available:

SYNMSG_RAD_CL_IR3.9	SYNMSG_BT_CL_IR3.9	SYNMSG_RAD_CL_WV6.2	SYNMSG_BT_CL_WV6.2
SYNMSG_RAD_CL_WV7.3	SYNMSG_BT_CL_WV7.3	SYNMSG_RAD_CL_IR8.7	SYNMSG_BT_CL_IR8.7
SYNMSG_RAD_CL_IR9.7	SYNMSG_BT_CL_IR9.7	SYNMSG_RAD_CL_IR10.8	SYNMSG_BT_CL_IR10.8
SYNMSG_RAD_CL_IR12.1	SYNMSG_BT_CL_IR12.1	SYNMSG_RAD_CL_IR13.4	SYNMSG_BT_CL_IR13.4
SYNMSG_RAD_CS_IR3.9	SYNMSG_BT_CS_IR3.9	SYNMSG_RAD_CS_WV6.2	SYNMSG_BT_CS_WV6.2
SYNMSG_RAD_CS_WV7.3	SYNMSG_BT_CS_WV7.3	SYNMSG_RAD_CS_IR8.7	SYNMSG_BT_CS_IR8.7
SYNMSG_RAD_CS_IR9.7	SYNMSG_BT_CS_IR9.7	SYNMSG_RAD_CS_IR10.8	SYNMSG_BT_CS_IR10.8
SYNMSG_RAD_CS_IR12.1	SYNMSG_BT_CS_IR12.1	SYNMSG_RAD_CS_IR13.4	SYNMSG_BT_CS_IR13.4

Here, RAD denotes radiance, BT brightness temperature, CL cloudy, and CS clear sky, supplemented by the channel name. Defined and used in: src/namelists/mo\_synsat\_nml.f90

## 2.40. time\_nml

Parameter	Type	Default	Unit	Description	Scope
calendar	I	1		Calendar type:	
				0=Julian/Gregorian	
				1=proleptic Gregorian	
				$2{=}30{ m day/month},360{ m day/year}$	
$dt_restart$	R	86400.*30.	s	Length of restart cycle in seconds. This namelist	
				parameter specifies how long the model runs	
				until it saves its state to a file and stops. Later,	
				the model run can be resumed, s. t. a simulation	
				over a long period of time can be split into a	
				chain of restarted model runs.	
				Note that the frequency of writing restart files is	
				controlled by io_nml:dt_checkpoint. Only if	
				the value of dt_checkpoint resulting from	
				model default or user's specification is longer	
				than dt_restart, it will be reset (by the model)	
				to dt_restart so that at least one restart file is	
				generated during the restart cycle. If	
				dt_restart is larger than but not a multiple of	
				dt_checkpoint, restart file will not be	
				generated at the end of the restart cycle.	

Parameter	Type	Default	Unit	Description	Scope
ini_datetime_string	С	'2008- 09-01T		Initial date and time of the simulation	
		00:00:00Z'			
${ m end\_datetime\_string}$	C	'2008- 09-01T		End date and time of the simulation	
		01:40:00Z'			
is_relative_time	L	.FALSE.		.TRUE., if time loop shall start with step 0	
				regardless whether we are in a standard run or in	
				a restarted run (which means re-initialized run).	

Length of the run If "nsteps" in run\_nml is positive, then nsteps\*dtime is used to compute the end date and time of the run. Else the initial date and time, the end date and time, dt\_restart, as well as the time step are used to compute "nsteps".

# 2.41. transport\_nml (used if run\_nml/ltransport=.TRUE.)

Parameter	Type	Default	Unit	Description	Scope
lvadv_tracer	L	.TRUE.		TRUE: compute vertical tracer advection FALSE: do not compute vertical tracer advection	
ihadv_tracer	I(ntracer)	2		<ul> <li>Tracer specific method to compute horizontal advection:</li> <li>0: no horiz. transport (note that the specific tracer quantity q is kept constant and not tracer mass ρq)</li> <li>1: upwind (1st order)</li> <li>2: Miura (2nd order, linear reconstr.)</li> <li>3: Miura3 (quadr. or cubic reconstr.)</li> <li>4: FFSL (quadr. or cubic reconstr.)</li> <li>5: hybrid Miura3/FFSL (quadr. or cubic reconstr.)</li> <li>20: miura (2nd order, lin. reconstr.) with subcycling</li> <li>22: combination of miura and miura with subcycling</li> </ul>	$\begin{split} & \operatorname{lsq\_high\_ord} \in [2,3] \\ & \operatorname{lsq\_high\_ord} \in [2,3] \\ & \operatorname{lsq\_high\_ord} \in [2,3] \end{split}$
ivadv_tracer	I(ntracer)	3		<ul> <li>32: combination of miura 3 and miura with subcycling</li> <li>42: combination of FFSL and miura with subcycling</li> <li>52: combination of hybrid FFSL/Miura3 with subcycling</li> <li>Subcycling means that the integration from time step n to n+1 is splitted into substeps to meet the stability requirements. For NWP runs, substepping is generally applied above z = 22 km (see nonhydrostatic nml/hbot qvsubstep). Tracer specific method to compute vertical advection:</li> <li>0: no vert. transport (note that tracer mass ρq instead of the specific tracer quantity q is kept constant. This differs from the behaviour in horizontal direction!)</li> <li>1: upwind (1st order)</li> </ul>	$lvadv\_tracer\!=\!TRUE$
$iadv\_tke$	I	0		<ul> <li>3: Piecewise parabolic method (PPM): handles CFL &gt; 1</li> <li>4: Piecewise parabolic method (PPM): GPU-enabled version, handles CFL &gt; 1</li> <li>Type of TKE advection</li> <li>0: no TKE advection</li> <li>1: vertical advection only</li> </ul>	$_{\rm inwp\_turb=1}$

Parameter	Type	Default	Unit	Description	Scope
		<u>.</u>		2: vertical and horizontal advection	
lstrang	$\mid L \mid$	.FALSE.		Time splitting method	
				TRUE: second order Strang splitting	
		1. a.g. (1) 1		FALSE: first order Godunov splitting	
tracer_names	C(:)	'Int2Str(i)'		Tracer-specific name suffixes. When running	iforcing≠ inwp, iecham'
				idealized cases or the hydrostatic ICON, this	
				variable is used to specify tracer names. If	
				nothing is specified, the tracer name is given as	
				PREFIX+Int2String(i), where i is the tracer index. Note that this namelist variable has no	
				effect for nonhydrostatic real-case runs, if the	
				NWP- or ECHAM physics packages are switched	
				on.	
npassive tracer	T	0		number of additional passive tracers which have	
inpublic_uldedi	1			no sources and are transparent to any physical	
				process (no effect).	
				Passive tracers are named Qpassive ID, where	
				ID is a number between ntracer and	
				ntracer+npassive_tracer.	
				NOTE: By default, limiters are switched of for	
				passive tracers and the scheme 52 is selected for	
				horizontal advection.	
init_formula	C	, ,		Comma-separated list of initialization formulas	$npassive\_tracer > 0$
	-/			for additional passive tracers.	
itype_hlimit	I(ntracer)	4		Type of limiter for horizontal transport:	
				0: no limiter	
				3: monotonous flux limiter 4: positive definite flux limiter	
itype vlimit	I(ntracer)	1		Type of limiter for vertical transport:	
Ttype_viiiit		1		0: no limiter	
				1: semi-monotone slope limiter	
				2: monotonous slope limiter	
				4: positive definite flux limiter	
beta_fct	R	1.005		factor of allowed over-/undershooting in	$itype\_hlimit = 3$
_				monotonous limiter	_
iord_backtraj	I	1		order of backward trajectory calculation:	
				1: first order	
				2: second order (iterative; currently 1 iteration	ihadv_tracer='miura'
				hardcoded; experimental!)	
igrad_c_miura	I	1		Method for gradient reconstruction at cell center	
				for 2nd order miura scheme	
				1: Least-squares (linear, non-consv)	$ihadv\_tracer{=}2$
1				2: Green-Gauss	

Parameter	Type	Default	Unit	Description	Scope
ivcfl_max	I	5		determines stability range of vertical	ivadv_tracer=3
				PPM-scheme in terms of the maximum allowable	
				CFL-number	
llsq svd	L	.TRUE.		use QR decomposition (FALSE) or SV	
_				decomposition (TRUE) for least squares design	
				matrix A	
lclip_tracer	$\mid$ L	.FALSE.		Clipping of negative values	

Defined and used in: src/namelists/mo\_advection\_nml.f90

# 2.42. turbdiff\_nml

Parameter	Type	Default	Unit	Description	Scope
imode_turb	I	1		Mode of solving the TKE equation for atmosph.	
				layers:	
				0: diagnostic equation	
				1: prognostic equation (current version)	
				2: prognostic equation (intrinsically positive	
				definite)	
imode_tran	I	0		Same as $imode\_turb$ but only for the transfer	
				layer	
icldm_turb	I	2		Mode of water cloud representation in	
				turbulence for atmosph. layers:	
				-1: ignoring cloud water completely (pure dry	
				scheme)	
				0: no clouds considered (all cloud water is	
				evaporated)	
				1: only grid scale condensation possible	
				2: also sub grid (turbulent) condensation	
				considered	
icldm_tran	I	2		Same as $icldm\_turb$ but only for the transfer	
_				layer	
q_crit	R	1.6		critical value for normalized super-saturation	
itype_wcld	I	2		type of water cloud diagnosis within the	icldm_turb=2 or
				turbulence scheme:	$\operatorname{icldm\_tran} = 2$
				1: employing a scheme based on relative	_
				humitidy	
				2: employing a statistical saturation adjustment	

Parameter	Type	Default	Unit	Description	Scope
$itype\_sher$	I	0		Type of shear forcing used in turbulence:	
				0: only vertical shear of horizontal wind	
				1: previous plus horizontal shear correction	
				2: previous plus shear from vertical velocity	
				3: same as option 1, but (when combined with	
				ltkeshs=.TRUE.) scaling of coarse-grid	
				horizontal shear production term with $\frac{1}{\sqrt{Ri}}$	
ltkeshs	L	.FALSE.		Include correction term for coarse grids in	itype sher $\geq 1$
	-			horizontal shear production term (needed at	VF
				non-convection-resolving model resolutions in	
				order to get a non-negligible impact)	
ltkesso	$\mid$ L	.TRUE.		Consider TKE-production by sub grid SSO	$   ext{inwp sso} = 1$
TURCOOO	"	. 11001.		wakes	11111 P_220 — 1
imode these		1		mode of calculat. the SSO source term for TKE	
$imode\_tkesso$	1	1			
				production: 1: original implementation	
ltkaaan		EVICE		2: Ri-dependent reduction factor for Ri>1	inwp corv 1
ltkecon	L	.FALSE.		Consider TKE-production by sub grid convective	$\lim p = conv = 1$
1411	T	TATOD		plumes (inactive)	
ltkeshs	$\mid L \mid$	.FALSE.		Consider TKE-production by separated	
1.				horizontal shear eddies (inactive)	
ltmpcor	L	.FALSE.		Consider thermal TKE sources in enthalpy	
				equation	
lsflcnd	L	.TRUE.		Use lower flux condition for vertical diffusion	
				calculation (TRUE) instead of a lower	
				concentration condition (FALSE)	
lexpcor	L	.FALSE.		Explicit corrections of implicitly calculated	
				vertical diffusion of non-conservative scalars that	
				are involved in sub grid condensation processes	
tur_len	R	500.0	m	Asymptotic maximal turbulent distance	
				$(\kappa * tur\_len$ is the integral turbulent master	
				length scale)	
pat_len	R	100.0	m	Effective length scale of thermal surface patterns	
<del>_</del>				controlling TKE-production by sub grid	
				kata/ana-batic circulations. In case of	
				pat $len = 0$ , this production is switched off.	
$c_{diff}$	R	0.2	1	Length scale factor for vertical diffusion of TKE.	
_		J	-	In case of $c$ diff $f = 0$ , TKE is not diffused	
				vertically.	
$a\_stab$	R	0.0	1	Factor for stability correction of turbulent length	
a_5tab		0.0	1	scale. In case of $a$ $stab = 0$ , the turbulent	
				scale. In case of $a\_stab = 0$ , the turbulent length scale is not reduced for stable	
				stratification.	

Parameter	Type	Default	Unit	Description	Scope
a_hshr	R	0.20	1	Length scale factor for the separated horizontal shear mode. In case of $a\_hshr = 0$ , this shear mode has no effect.	ltkeshs=.TRUE.
alpha0	ight  R	0.0123	1	Lower bound of velocity-dependent Charnock parameter	
alpha0_max	R	0.0335	1	Upper bound of velocity-dependent Charnock parameter. Setting this parameter to 0.0335 or higher values implies unconstrained velocity dependence	
alpha1	ight  R	0.75	1	Scaling parameter for molecular roughness of ocean waves	
tkhmin	R	0.75	$m^2/s$	Scaling factor for minimum vertical diffusion coefficient (proportional to $Ri^{-2/3}$ ) for heat and moisture	
tkmmin	R	0.75	$m^2/s$	Scaling factor for minimum vertical diffusion coefficient (proportional to $Ri^{-2/3}$ ) for momentum	
tkmmin_strat	R	4	$\mathrm{m}^2/\mathrm{s}$	Scaling factor for stratospheric minimum vertical diffusion coefficient (proportional to $Ri^{-1/3}$ ) for momentum, valid above 17.5 km (tropics above 22.5 km)	
tkhmin_strat	R	0.75	$\mathrm{m}^2/\mathrm{s}$	Scaling factor for stratospheric minimum vertical diffusion coefficient (proportional to $Ri^{-1/3}$ ) for heat and moisture, valid above 17.5 km (tropics above 22.5 km)	
$itype\_synd$	I	2		Type of diagnostics of synoptic near surface variables: 1: Considering the mean surface roughness of a grid box 2: Considering a fictive surface roughness of a SYNOP lawn	
rlam_heat	R	1.0	1	Scaling factor of the laminar boundary layer for heat (scalars). The larger rlam_heat, the larger is the laminar resistance.	
rat_sea	R	10.0	1	Ratio of laminar scaling factors for scalars over sea and land. The larger rat_sea, the larger is the laminar resistance for a sea surface compared to a land surface.	
tkesmot	ight  R	0.15	1	Time smoothing factor within $[0, 1]$ for TKE. In case of $tkesmot = 0$ , no smoothing is active.	
frcsmot	R	0.0	1	Vertical smoothing factor within $[0, 1]$ for TKE forcing terms. In case of $frcmot = 0$ , no smoothing is active.	

Parameter	Type	Default	Unit	Description	Scope
$imode\_frcsmot$	I	1		1 = apply vertical smoothing (if frcsmot > 0)	
				uniformly over the globe	
				2 = restrict vertical smoothing to the tropics	
				(reduces the moist bias in the tropics while	
				avoiding adverse effects on NWP skill scores in	
				the extratropics)	
impl_s	R	1.20	1	Implicit weight near the surface (maximal value)	
impl_t	R	0.75	1	Implicit weight near top of the atmosphere	
				(minimal value)	
lconst_z0	L	.FALSE.		TRUE: horizontally homogeneous roughness	
				length z0	
const_z0	R	0.001	m	value for horizontally homogeneous roughness	lconst z0=.TRUE.
				length z0	
ldiff qi	L	.FALSE.		Turbulent diffusion of cloud ice, if .TRUE.	
itype_tran	I	2		type of surface-atmosphere transfer	
lprfcor	L	.FALSE.		using the profile values of the lowest main level	
				instead of the mean value of the lowest layer for	
				surface flux calculations	
lnonloc	L	.FALSE.		nonlocal calculation of vertical gradients used for	
				turbul. diff.	
lfreeslip	L	.FALSE.		.TRUE.: use a free-slip lower boundary	
				condition, i.e. neither momentum nor	
				heat/moisture fluxes (use for idealized runs	
				only!)	
lcpfluc	L	.FALSE.		consideration of fluctuations of the heat capacity	
				of air	

Defined and used in: src/namelists/mo\_turbdiff\_nml.f90

## 3. Ocean-specific namelist parameters

## 3.1. ocean\_physics\_nml

Parameter	Type	Default	Unit	Description	Scope
i_sea_ice	I	1		0: No sea ice, 1: Include sea ice	
				.FALSE.: compute drag only	
richardson_factor_tracer	I	0.5e-5	m/s		
richardson factor veloc	I	0.5e-5	m/s		
l_constant_mixing	L	.FALSE.	·		

# 3.2. sea\_ice\_nml (relevant if run\_nml/iforcing=2 (ECHAM))

Parameter	Type	Default	Unit	Description	Scope
i_ice_therm	I	2		Switch for thermodynamic model:	In an ocean run i_sea_ice
				1: Zero-layer model	must be $>=1$ . In an
				2: Two layer Winton (2000) model	atmospheric run the ice surface
				3: Zero-layer model with analytical forcing (for	type must be defined.
				diagnostics)	
				4: Zero-layer model for atmosphere-only runs	
				(for diagnostics)	
i_ice_dyn	I	0		Switch for sea-ice dynamics:	
				0: No dynamics	
				1: FEM dynamics (from AWI)	
i_ice_albedo	I	1		Switch for albedo model. Only one is	
				implemented so far.	
i_Qio_type	I	2		Switch for ice-ocean heat-flux calculation	Defaults to 1 when
				method:	i_ice_dyn=0 and 2 otherwise.
				1: Proportional to ocean cell thickness (like	
				MPI-OM)	
				2: Proportional to speed difference between ice	
				and ocean	
kice	I	1		Number of ice classes (must be one for now)	
hnull	R	0.5	m	Hibler's $h_0$ parameter for new-ice growth.	
hmin	R	0.05	m	Minimum sea-ice thickness allowed.	
ramp_wind	R	10	days	Number of days it takes the wind to reach	
				correct strength. Only used at the start of an	
				OMIP/NCEP simulation (not after restart).	

## 4. Namelist parameters for testcases (NAMELIST\_ICON)

The ICON model code includes several experiments, so-called test cases, for the shallow water model as well as the 3-dimensional atmosphere. Depending on the specified experiment, initial conditions and boundary conditions are computed internally.

## $4.1. \ ha\_testcase\_nml \ (Scope: \ ltestcase=.TRUE. \ and \ iequations=[0,1,2] \ in \ run\_nml)$

Parameter	Type	Default	Unit	Description	Scope
ctest_name	С	'JWw'		Name of test case:	
				'SW_GW': gravity wave	$lshallow\_water=.TRUE.$
				'USBR': unsteady solid body rotation	$lshallow\_water=.TRUE.$
				'Will_2': Williamson test 2	$lshallow\_water=.TRUE.$
				'Will_3': Williamson test 3	$lshallow\_water=.TRUE.$
				'Will_5': Williamson test 5	$lshallow\_water=.TRUE.$
				'Will_6': Williamson test 6	$lshallow\_water=.TRUE.$
				'GW': gravity wave (nlev=20 only!)	$lshallow\_water=.FALSE.$
				'LDF': local diabatic forcing test without physics	lshallow_water=.FALSE.
					and iforcing=4

Parameter	Type	Default	Unit	Description	Scope
				'LDF-Moist': local diabatic forcing test with	lshallow_water=.FALSE.,
				physics initalised with zonal wind field	and iforcing=5
				'HS': Held-Suarez test	$lshallow\_water=.FALSE.$
				'JWs': Jablonowski-Will. steady state	lshallow_water=.FALSE.
				'JWw': Jablonowski-Will. wave test	lshallow water=.FALSE.
				'JWw-Moist': Jablonowski-Will. wave test	lshallow water=.FALSE.
				including moisture	_
				'APE': aqua planet experiment	lshallow water=.FALSE.
				'MRW': mountain induced Rossby wave	lshallow water=.FALSE.
				'MRW2': modified mountain induced Rossby	lshallow water=.FALSE.
				wave	
				'PA': pure advection	lshallow water=.FALSE.
				'SV': stationary vortex	lshallow water=.FALSE.,
				SV . Stationary voicex	$\begin{array}{c} \text{Ishanow}\_\text{water}\\text{FALSE.}, \\ \text{ntracer} = 2 \end{array}$
				'DF1': deformational flow test 1	Intracer — 2
				'DF2': deformational flow test 1	
				'DF3': deformational flow test 2	
				'DF4': deformational flow test 4	
					1 1 11 A TRAICTE
	T()	•		'RH': Rossby-Haurwitz wave test	lshallow_water=.FALSE.
tracer_inidist_list	I(:)	1		For a subset of testcases pre-defined initial tracer	ha_testcase_nml='PA',
				distributions are available. This namelist	'JABW','DF'
				parameter specifies the initial distribution for	
				each tracer. In the following the testcases and	
				the pre-defined numbers are given:	
				'PA': 4,5,6,7,8	
				'JABW':1,2,3,4	
				'DF': 5,6,7,8,9	
				For more details on the initial distributions,	
				please have a look into the code.	
rotate_axis_deg	R	0.0	$\deg$	Earth's rotation axis pitch angle	ctest_name= 'Will_2',
					'Will_3', 'JWs', 'JWw', 'PA',
					'DF1234'
gw_brunt_vais	R	0.01	1/s	Brunt Vaisala frequency	ctest_name= 'GW'
gw_u0	R	0.0	m/s	zonal wind parameter	ctest_name= 'GW'
gw_lon_deg	R	180.0	$\deg$	longitude of initial perturbation	ctest_name= 'GW'
gw_lat_deg	R	0.0	$\deg$	latitude of initial perturbation	ctest_name= 'GW'
jw_uptb	$\mathbb{R}$	1.0	m/s (?)	amplitude of the wave pertubation	ctest_name= 'JWw'
mountctr lon deg	R	90.0	deg	longitude of mountain peak	ctest name= 'MRW(2)'
mountctr lat deg	R	30.0	$\deg$	latitude of mountain peak	ctest name= 'MRW(2)'
mountctr height	$\mathbb{R}$	2000.0	m	mountain height	ctest name= 'MRW(2)'
mountctr half width	R	1500000.0	m	mountain half width	$\cot \operatorname{ctest}^- \operatorname{name} = \operatorname{MRW}(2),$
mount u0	R	20.0	m/s	wind speed for MRW cases	ctest name = MRW(2)
rh wavenum		4	, -	wave number	ctest name= 'RH'
rh init shift deg	R	0.0	$\deg$	pattern shift	ctest name= 'RH'
1		1 0.0	1 46	Passessii siiiis	10000

Parameter	Type	Default	Unit	Description	Scope
ihs_init_type	I	1		Choice of initial condition for the Held-Suarez	ctest_name= 'HS'
				test. 1: the zonal state defined in the JWs test case; other integers: isothermal state (T=300 K,	
				ps=1000 hPa, u=v=0.)	
lhs_vn_ptb	L	.TRUE.		Add random noise to the initial wind field in the	ctest name= 'HS'
		111002		Held-Suarez test.	
$hs\_vn\_ptb\_scale$	R	1.	m/s	Magnitude of the random noise added to the	ctest_name= 'HS'
				initial wind field in the Held-Suarez test.	
lrh_linear_pres	L	.FALSE.		Initialize the relative humidity using a linear	ctest_name=
				function of pressure.	'JWw-Moist','APE',
nh at 1000hna	<sub>R</sub>	0.75		relative humidity	'LDF-Moist'
rh_at_1000hpa	l n	0.79		relative number $0,1$	ctest_name= 'JWw-Moist','APE',
				,	'LDF-Moist'
	_			at 1000 hPa	
linit_tracer_fv		TRUE.		Finite volume initialization for tracer fields	ctest_name='PA'
ape_sst_case	ightharpoons C	'sst1'		SST distribution selection	ctest_name='APE'
				'sst1': Control experiment 'sst2': Peaked experiment	
				'sst3': Flat experiment	
				'sst4': Control-5N experiment	
				'sst qobs': Qobs SST distribution exp	
				'sst ice': Control SST distribution with -1.8 C	
				$\overline{\text{above 64 N/S}}$ .	
ildf_init_type	I	0		Choice of initial condition for the Local diabatic	ctest_name= 'LDF'
				forcing test. 1: the zonal state defined in the	
				JWs test case; other: isothermal state (T=300	
1.10	T	mpire.		K, ps=1000 hPa, u=v=0.)	
ldf_symm	L	.TRUE.		Shape of local diabatic forcing: .TRUE.: local diabatic forcing symmetric about	ctest_name= 'LDF','LDF-Moist'
				the equator (at 0 N)	LDF , LDF-MOISt
				.FALSE.: local diabatic forcing asym. about the	
				equator (at 30 N)	

Defined and used in: src/testcases/mo\_ha\_testcases.f90

# 4.2. nh\_testcase\_nml (Scope: ltestcase=.TRUE. and iequations=3 in run\_nml)

Parameter	Type	Default	Unit	Description	Scope
nh_test_name	С	'jabw'		testcase selection	
				'zero': no orography	
				'bell': bell shaped mountain at 0E,0N	
				'schaer': hilly mountain at 0E,0N	
				'jabw': Initializes the full Jablonowski	
				Williamson test case.	

Parameter	Type	Default	Unit	Description	Scope
				'jabw_s': Initializes the Jablonowski	
				Williamson steady state test case.	
				'jabw_m': Initializes the Jablonowski	
				Williamson test case with a mountain instead of	
				the wind perturbation (specify mount_height).	
				'mrw_nh': Initializes the full	
				Mountain-induced Rossby wave test case.	
				'mrw2_nh': Initializes the modified	
				mountain-induced Rossby wave test case.	
				'mwbr_const': Initializes the mountain wave	
				with two layers test case. The lower layer is	
				isothermal and the upper layer has constant	
				brunt vaisala frequency. The interface has	
				constant pressure.	
				'PA': Initializes the pure advection test case.	
				'HS_nh': Initializes the Held-Suarez test case.	
				At the moment with an isothermal atmosphere	
				at rest (T=300K, ps=1000hPa, u=v=0,	
				topography=0.0).	
				'HS jw': Initializes the Held-Suarez test case	
				with Jablonowski Williamson initial conditions	
				and zero topography.	
				'APE nwp, APE echam, APE nh,	
				<b>APEc</b> nh, ': Initializes the APE experiments.	
				With the jabw test case, including moisture.	
				'wk82': Initializes the Weisman Klemp test case	l limited area = .TRUE.
				'g lim area': Initializes a series of general	
				limited area test cases: itype_atmos_ana	
				determines the atmospheric profile,	
				itype anaprof uv determines the wind profile	
				and itype topo ana determines the topography	
				'dcmip bw 11': Initializes (moist) baroclinic	
				instability/wave (DCMIP2016)	
				'dcmip pa 12': Initializes Hadley-like	
				meridional circulation pure advection test case.	
				'dcmip rest 200': atmosphere at rest test	lcoriolis = .FALSE.
				(Schaer-type mountain)	
				'dcmip mw 2x': nonhydrostatic mountain	lcoriolis = .FALSE.
				waves triggered by Schaer-type mountain	
				'dcmip gw 31': nonhydrostatic gravity waves	
				triggered by a localized perturbation (nonlinear)	
				'dcmip gw 32': nonhydrostatic gravity waves	l limited area =.TRUE.
				triggered by a localized perturbation (linear)	and lcoriolis = .FALSE.

Parameter	Type	Default	Unit	Description	Scope
				'dcmip_tc_51': tropical cyclone test case with	lcoriolis = .TRUE.
				'simple physics' parameterizations (not yet	
				implemented)	
				'dcmip_tc_52': tropical cyclone test case with	$    ext{coriolis} = .  ext{TRUE}.$
				with full physics in Aqua-planet mode	
				'CBL': convective boundary layer simulations	$is\_plane\_torus=.TRUE.$
		DATOD		for LES package on torus (doubly periodic) grid	
is_toy_chem	L	.FALSE.		Terminator toy chemistry activated when	
though inidiat list	T(.)	1		TRUE.	nh tost name 'DA'
tracer_inidist_list	I(:)	1		For a subset of testcases pre-defined initial tracer distributions are available. This namelist	nh_test_name='PA', 'JABW','DF'
				parameter specifies the initial distribution for	JADW, DI
				each tracer. In the following the testcases and	
				the pre-defined numbers are given:	
				'PA': 4,5,6,7,8	
				'JABW':1,2,3,4	
				'DF': 5,6,7,8,9	
				For more details on the initial distributions,	
				please have a look into the code.	
demip bw%				DCMIP2016 baroclinic wave test	'dcmip_bw_11'
deep	I	0		deep atmosphere	
				(1 = yes or 0 = no)	
moist	I	0		include moisture, i.e. $qv \neq 0$	
				(1 = yes or 0 = no)	
pertt	I	0		type of initial perturbation	
				0 = exponential, $1 = $ stream function)	
toy_chem%			_	terminator toy chemistry	is_toy_chem=.TRUE.
dt_chem	R	300	S	chemistry tendency update interval	
$dt_{cpl}$	R	300	S	chemistry-transport coupling interval	
id_cl		$\frac{1}{2}$		Tracer container slice index for species CL	
id_cl2	1 D	2	,	Tracer container slice index for species CL2	
jw_up	R	1.0	m/s	amplitude of the u-perturbation in jabs test case	nh_test_name='jabw'
$u_0$ mrw	R	20.0	m/s	wind speed for mrw(2) and mwbr_const cases	nh_test_name='mrw(2)_nh' and 'mwbr_const'
mount_height_mrw	ight] R	2000.0	m	maximum mount height in mrw(2) and mwbr const	nh_test_name= 'mrw(2)_nh' and 'mwbr_const'
mount_half_width	ight  R	1500000.0	m	half width of mountain in mrw(2), mwbr_const	$nh\_test\_name = 'mrw(2)\_nh',$
mount_lonctr_mrw_deg	R	90.	deg	and bell lon of mountain center in mrw(2) and	'mwbr_const' and 'bell' nh_test_name= 'mrw(2)_nh'
			_	mwbr_const	and 'mwbr_const'
mount_latctr_mrw_deg	R	30.	deg	lat of mountain center in mrw(2) and	$\begin{array}{ c c c c c c c c c c c c c c c c c c c$
				mwbr_const	and 'mwbr_const'
$temp\_i\_mwbr\_const$	R	288.0	K	temp at isothermal lower layer for mwbr_const	nh_test_name= 'mwbr_const'
				case	

Parameter	Type	Default	Unit	Description	Scope
p_int_mwbr_const	R	70000.	Pa	pres at the interface of the two layers for mwbr const case	nh_test_name= 'mwbr_const'
bruntvais_u_mwbr_const	R	0.025	1/s	constant brunt vaissala frequency at upper layer for mwbr const case	nh_test_name= 'mwbr_const'
mount_height	$\mid$ R	100.0	m	peak height of mountain	nh_test_name= 'bell'
layer_thickness	R	-999.0	m	thickness of vertical layers	If layer_thickness < 0, the vertical level distribution is
					read in from externally given HYB_PARAMS_XX.
n_flat_level	I			level number for which the layer is still flat and not terrain-following	layer_thickness > 0
nh_u0	R	0.0	m/s	initial constant zonal wind speed	$nh_{test\_name} = 'bell'$
nh_t0	R	300.0	K	initial temperature at lowest level	nh_test_name = 'bell'
nh_brunt_vais	R	0.01	1/s	initial Brunt-Vaisala frequency	nh_test_name = 'bell'
torus_domain_length	R	100000.0	m	length of slice domain	nh_test_name = 'bell', lplane=.TRUE.
rotate_axis_deg	R	0.0	$\deg$	Earth's rotation axis pitch angle	nh_test_name= 'PA'
lhs_nh_vn_ptb	L	.TRUE.		Add random noise to the initial wind field in the Held-Suarez test.	nh_test_name= 'HS_nh'
lhs_fric_heat	L	.FALSE.		add frictional heating from Rayleigh friction in the Held-Suarez test.	nh_test_name= 'HS_nh'
hs_nh_vn_ptb_scale	ight  R	1.	m m/s	Magnitude of the random noise added to the initial wind field in the Held-Suarez test.	nh_test_name= 'HS_nh'
rh at 1000hpa	R	0.7	1	relative humidity at 1000 hPa	nh test name='jabw',
					nh test name= 'mrw'
qv_max	ight  R	20.e-3	kg/kg	specific humidity in the tropics	nh_test_name= 'jabw', nh_test_name= 'mrw'
ape_sst_case	C	'sst1'		SST distribution selection 'sst1': Control experiment 'sst2': Peaked experiment 'sst3': Flat experiment 'sst4': Control-5N experiment 'sst_qobs': Qobs SST distribution exp. 'sst_const': constant SST	nh_test_name='APE_nwp', 'APE_echam'
ape_sst_val	R	29.0	$\deg C$	aqua planet SST for ape_sst_case='sst_const'	nh_test_name= 'APE_nwp', 'APE_echam'
linit tracer fv	L	.TRUE.		Finite volume initialization for tracer fields	pure advection tests, only
lcoupled rho	L	.FALSE.		Integrate density equation 'offline'	pure advection tests, only
qv_max_wk	R	0.014	m Kg/kg	maximum specific humidity near the surface, range 0.012 - 0.016 used to vary the buoyancy	nh_test_name='wk82'
u_infty_wk	R	20.	m m/s	zonal wind at infinity height range 0 45. used to vary the wind shear	nh_test_name='wk82'
bub_amp	$\mid$ R	2.	K	maximum amplitud of the thermal perturbation	nh_test_name='wk82'

Parameter	Type	Default	Unit	Description	Scope
bubctr_lat	R	0.	deg	latitude of the center of the thermal perturbation	$nh\_test\_name='wk82'$
bubctr_lon	R	90.	deg	longitude of the center of the thermal	$nh\_test\_name='wk82'$
				perturbation	
bubctr z	R	1400.	m	height of the center of the thermal perturbation	nh test name='wk82'
bub hor width	R	10000.	m	horizontal radius of the thermal perturbation	$ \frac{1}{1} $ $ \frac{1} $ $ \frac{1}{1} $ $ \frac{1}{1$
bub ver width	R	1400.	m	vertical radius of the thermal perturbation	$ \frac{1}{1} $ $ \frac{1} $ $ \frac{1}{1} $ $ \frac{1}{1$
itype atmo ana		1		kind of atmospheric profile:	$ \frac{1}{1} $ $ \frac{1} $ $ \frac{1}{1} $ $ \frac{1}{1$
<i>o</i> 1				1 piecewise N constant layers	'g lim area'
				2 piecewise polytropic layers	
itype anaprof uv	1	1		kind of wind profile:	nh test name=
				1 piecewise linear wind layers	'g lim area'
				2 constant zonal wind	8
				3 constant meridional wind	
itype topo ana	1	1		kind of orography:	${ m nh} \;\; { m test} \;\; { m name} =$
10, PC_00PO_ana		1		1 schaer test case mountain	'g lim area'
				2 gaussian 2d mountain	8 ar ca
				3 gaussian 3d mountain	
				any other no orography	
nlavore neonet		1		Number of the desired layers with a constant	${ m nh} \;\; { m test} \;\; { m name} =$
nlayers_nconst		1			'g lim area' and
				Brunt-Vaisala-frequency	g_nm_area and itype atmo ana=1
n hage nagnat		1,00000	Pa	programs at the bage of the first N constant lower	· ·
p_base_nconst	R	100000.	га	pressure at the base of the first N constant layer	nh_test_name=
					'g_lim_area' and
11 . 0 1		000	T/		itype_atmo_ana=1
$theta0\_base\_nconst$	R	288.	K	potential temperature at the base of the first N	$ \operatorname{nh\_test\_name} =  $
				constant layer	'g_lim_area' and
		0 1500 10000			itype_atmo_ana=1
$h\_nconst$	' '	0., 1500., 12000.	m	height of the base of each of the N constant	$ \frac{\text{nh\_test\_name}}{\text{nh\_test\_name}} $
	-nconst			layers	'g_lim_area' and
	_,				itype_atmo_ana=1
N_nconst	' '	0.01	1/s	Brunt-Vaisala-frequency at each of the N	$nh\_test\_name =$
	-nconst			constant layers	'g_lim_area' and
					$itype\_atmo\_ana{=}1$
$rh\_nconst$	\ \	0.5	%	relative humidity at the base of each N constant	$nh\_test\_name =$
	-nconst			layers	'g_lim_area' and
					itype_atmo_ana=1
$rhgr\_nconst$	' '	0.	%	relative humidity gradient at each of the N	$nh\_test\_name =$
	_nconst)			constant layers	'g_lim_area' and
					$itype\_atmo\_ana=1$
nlayers_poly		2		Number of the desired layers with constant	${ m nh\_test\_name} =$
				gradient temperature	'g_lim_area' and
					$type_atmo_ana=2$
p_base_poly	R	100000.	Pa	pressure at the base of the first polytropic layer	$ \begin{array}{ccc}     & \underline{} & \underline{} \\     & \underline{} & \underline{} & \underline{} \\     & \underline{} & \underline{} & \underline{} & \underline{} \\     & \underline{} & \underline{} & \underline{} & \underline{} & \underline{} \\     & \underline{} & \underline{} & \underline{} & \underline{} & \underline{} & \underline{} \\     & \underline{} \\     & \underline{} & \phantom{$
_					'g lim area' and
					itype atmo ana=2

Parameter	Type	Default	Unit	Description	Scope
h_poly	R(nlayers	0., 12000.	m	height of the base of each of the polytropic layers	$nh\_test\_name =$
	poly)				'g_lim_area' and
					itype_atmo_ana=2
t_poly	R(nlayers	288., 213.	K	temperature at the base of each of the polytropic	$nh\_test\_name =$
	poly)			layers	'g_lim_area' and
					itype_atmo_ana=2
rh_poly	R(nlayers	0.8, 0.2	%	relative humidity at the base of each of the	$nh\_test\_name =$
	poly)			polytropic layers	'g_lim_area' and
					itype_atmo_ana=2
rhgr_poly	R(nlayers	5.e-5, 0.	%	relative humidity gradient at each of the	$nh\_test\_name =$
	-poly			polytropic layers	'g_lim_area' and
					itype_atmo_ana=2
nlayers_linwind	I	2		Number of the desired layers with constant U	nh_test_name=
				gradient	'g_lim_area' and
					itype_anaprof_uv=1
h_linwind	R(nlayers	0., 2500.	m	height of the base of each of the linear wind	nh_test_name=
	$   $ $_{-}$ linwind)			layers	'g_lim_area' and
	5/.		,		itype_anaprof_uv=1
$u_{linwind}$	R(nlayers	5, 10.	m/s	zonal wind at the base of each of the linear wind	nh_test_name=
	$   $ $_{-}$ $			layers	'g_lim_area' and
	5/.				itype_anaprof_uv=1
ugr_linwind	R(nlayers	0., 0.	1/s	zonal wind gradient at each of the linear wind	nh_test_name=
	$\begin{bmatrix} -\text{linwind} \end{bmatrix}$			layers	'g_lim_area' and
		20			itype_anaprof_uv=1
vel_const	R	20.	m/s	constant zonal/meridional wind	$nh\_test\_name =$
				$(itype\_anaprof\_uv=2,3)$	'g_lim_area' and
	D.	0.0	,		itype_anaprof_uv=2,3
mount_lonc_deg	R	90.	$\deg$	longitud of the center of the mountain	$nh\_test\_name = $
	D.		,		'g_lim_area'
mount_latc_deg	R	0.	deg	latitud of the center of the mountain	$\begin{array}{c} \text{nh\_test\_name} = \\ \text{,} \end{array}$
1 10	D.	050			'g_lim_area'
schaer_h0	R	250.	m	h0 parameter for the schaer mountain	nh_test_name=
					'g_lim_area' and
ashaon a	D	£000		-a- parameter for the schaer mountain,	itype_topo_ana=1
schaer_a	R	5000.	m	<del>-</del>	nh_test_name=
				also half width in the north and south side of the finite ridge to round the sharp edges	'g_lim_area' and
schaer lambda	R	4000.	m	lambda parameter for the schaer mountain	itype_topo_ana=1,2   nh test name=
schael_lambua	11	4000.	m	lamoda parameter for the schaer mountain	'g lim area' and
					g_nm_area and   itype topo ana=1
Ishoor demin	L	FALSE		run dcmip mw 2x with/without vertical wind	nh test name=
lshear_dcmip	L	FALSE		shear	'dcmip mw 2x'
				FALSE: dcmip mw 21: non-sheared	demip_mw_2x
				TRUE: dcmip_mw_21: non-sneared TRUE: dcmip_mw_22: sheared	
			I	1102. dcmp_mw_22. sneared	

Parameter	Type	Default	Unit	Description	Scope
halfwidth_2d	R	10000.	m	half lenght of the finite ridge in the north-south	$nh\_test\_name =$
				direction	'g_lim_area' and
					$  itype\_topo\_ana=1,2$
m_height	R	1000.	m	height of the mountain	$nh\_test\_name =$
					'g_lim_area' and
					$itype\_topo\_ana=2,3$
m_width_x	R	5000.	m	half width of the gaussian mountain in the	nh_test_name=
				east-west direction	'g_lim_area' and
				half width in the north-south direction in the	$itype\_topo\_ana=2,3$
				rounding of the finite ridge (gaussian_2d)	
m_width_y	R	5000.	m	half width of the gaussian mountain in the	$nh\_test\_name =$
				north-south direction	'g_lim_area' and
_			,		itype_topo_ana=2,3
gw_u0	R	0.	m/s	maximum amplitude of the zonal wind	nh_test_name=
1			1	T. C. C. L. D. C.	'dcmip_gw_3X'
gw_clat	R	90.	$\deg$	Lat of perturbation center	nh_test_name=
1.1.	D	0.01	T.7		'dcmip_gw_3X'
$gw_{delta\_temp}$	R	0.01	K	maximum temperature perturbation	nh_test_name=
11(0)	D		/ 1		'dcmip_gw_32'
u_cbl(2)	R	0:0	m/s and	to prescribe initial zonal velocity profile for	$nh\_test\_name=CBL$
			1/s	convective boundary layer simulations where	
				u_cbl(1) sets the constant and u_cbl(2) sets the vertical gradient	
w chl(2)	R	0:0	m/s and	to prescribe initial meridional velocity profile for	nh test name=CBL
v_cbl(2)	110	0.0	1/s	convective boundary layer simulations where	mi_test_name=CBL
			1/8	v_cbl(1) sets the constant and v_cbl(2) sets the	
				v_cbi(1) sets the constant and v_cbi(2) sets the vertical gradient	
th_cbl(2)	R	290:0.006	K and	to prescribe initial potential temperature profile	nh test name=CBL
	10	230.0.000	K and K/m	for convective boundary layer simulations where	m_ccsc_name=CDE
			11 / 111	th_cbl(1) sets the constant and th_cbl(2) sets	
				the gradient	
				one gradient	

Defined and used in: src/testcases/mo\_nh\_testcases.f90

## 5. External data

# 5.1. extpar\_nml (Scope: itopo=1 in run\_nml)

Parameter	Type	Default	Unit	Description	Scope
itopo	I	0		0: analytical topography/ext. data	
				1: topography/ext. data read from file	

Parameter	Type	Default	Unit	Description	Scope
itype_vegetation_cycle	I	1		1: annual cycle of LAI solely based on NDVI	
				climatology	
				2: additional use of monthly T2M climatology to	
				get more realistic values in extratropics (requires	
				external parameter data contining this field)	
				3: as 2 with additional coupling of vegetation	
				parameters to T2M bias in transitional seasons	
				(requires DWD assimilation cycle including soil	
		_		moisture analysis)	
n_iter_smooth_topo	$I(n_{dom})$	0		iterations of topography smoother	itopo = 1
fac_smooth_topo	R	0.015625		pre-factor of topography smoother	$n_{\text{iter\_smooth\_topo}} > 0$
hgtdiff_max_smooth_topo	R	$\mid 0.$	m	RMS height difference to neighbor grid points at which the smoothing pre-factor	$n_{\text{iter\_smooth\_topo}} > 0$
				fac_smooth_topo reaches its maximum value	
				(linear proportionality for weaker slopes)	
heightdiff_threshold	$R(n\_dom)$	3000.	m	height difference between neighboring grid points	
				above which additional local nabla2 diffusion is	
				applied	
lrevert_sea_height	L	.FALSE.		If .TRUE., sea point heights will be reverted to	$n_{iter\_smooth\_topo} > 0$
				original (raw data) heights after topography	
				smoothing was applied.	
l_emiss	L	.TRUE.		read and use external surface emissivity map	itopo = 1
${ m extpar\_filename}$	C			Filename of external parameter input file,	
				default: " <path>extpar_<gridfile>". May</gridfile></path>	
				contain the keyword <path> which will be</path>	
1 ' 1'	т	   .FALSE.		substituted by model_base_dir.	
read_nc_via_cdi	$\mid L \mid$	.FALSE.		.TRUE.: read NetCDF input data via cdi library .FALSE.: read NetCDF input data using parallel	
				NetCDF library	
				Note: GRIB2 input data is always read via cdi	
				library / GRIB API. For NetCDF input, this	
				switch allows optimizing the input performance,	
				but there is no general rule which option is	
				faster.	
extpar varnames map file	ightharpoonup	, ,		Filename of external parameter dictionary, This	
				is a text file with two columns separated by	
				whitespace, where left column: NetCDF name,	
				right column: GRIB2 short name. It is required,	
				if external parameter are read from a file in	
				GRIB2 format.	

Defined and used in: src/namelists/mo\_extpar\_nml.f90

### 6. External packages

#### 7. Information on vertical level distribution

If no vertical sleve coordinate is chosen (ivctype / =2), the hydrostatic and nonhydrostatic models need hybrid vertical level information to generate the terrain following coordinates. The hybrid level specification is stored in <icon home>/hyb\_params/HYB\_PARAMS\_<nlev>. The hydrostatic model assumes to get pressure based coordinates, the nonhydrostatic model expects height based coordinates. For further information see <icon home>/hyb\_params/README.

### 8. Compile flag for mixed precision

To speed up code parts strongly limited by memory bandwidth (primarily the dynamical core and the tracer advection), an option exists to use single precision for variables that are presumed to be insensitive to computational accuracy. This affects most local arrays in the dynamical core routines (solve\_nonhydro and velocity\_advection), some local arrays in the tracer transport routines, the metrics coefficients, arrays used for storing tendencies or differenced fields (gradients, divergence etc.), reference atmosphere fields, and interpolation coefficients. Prognostic variables and intermediate variables affecting the accuracy of mass conservation are still treated in double precision. To activate the mixed-precision option, the cpp flags '-D\_\_MIXED\_PRECISION' and '-D\_\_MIXED\_PRECISION\_2' need to be specified in the configuration settings used for generating the Makefile. The latter flag is used for physics tendencies. Note that interpolation to a latitude-longitude grid is not supported for single-precision variables; if you desire to output physics tendency fields on a regular grid for diagnostic purposes, do not set '-D\_\_MIXED\_PRECISION\_2'.

### A. Arithmetic expression evaluation

The mo\_expression module evaluates basic arithmetic expressions specified by character-strings. It is possible to include mathematical functions, operators, and constants. An application of this module is the evaluation of arithmetic expressions povided as namelist parameters.

Besides, Fortran variables can be linked to the expression and used in the evaluation. The implementation supports scalar input variables as well as 2D and 3D fields. From a users' point of view, the basic usage of this module is described in Section A.1 below. Technically, infix expressions are processed based on a Finite State Machine (FSM) and Dijkstra's shunting yard algorithm. A more detailed described of the Fortran interface is given in Section A.3.

#### A.1. Examples for arithmetic expressions

Basic examples:

- "sqrt(2.0)"
- "sin(45\*pi/180.) \* 10 + 5"
- "if(1. > 2, 99, -1.\*pi)"
- "min(1,2)"

Variables are used with a bracket notation:

• "sqrt([u]^2 + [v]^2)"

Note that the use of variables requires that these are enabled ("linked") by the Fortran routine that calls the mo\_expression module.

#### A.2. Expression syntax

#### A.2.1. List of functions

name	$\# { m args}$	description
log(), exp()	1	natural logarithm and its inverse function.
sin(), cos()	1	trigonometric functions
sqrt()	1	square root
min(), max()	2	minimum and maximum of two values
if(value, then, else)	3	conditional expression (value > 0.)

#### A.2.2. List of operators

name	evaluates to			
a + b, a - b,	(a+b), (a-b), (a*b), (a/b)			
a * b, a / b				
a ^ b	$a^b$			
a > b	$\begin{cases} 1, & \text{if } a > b, \\ 0, & \text{otherwise.} \end{cases}$			
a < b	$\begin{cases} 1, & \text{if } a < b, \\ 0, & \text{otherwise.} \end{cases}$			

#### A.2.3. List of available constants

name of constant	assigned value	description
pi	4 atan(1)	mathematical constant equal to a circle's cir-
		cumference divided by its diameter
r	$6.371229 \cdot 10^6$	Earth's radius <sup>1</sup>

#### A.3. Usage with Fortran

The minimal Fortran interface is as follows:

- 1. The TYPE expression which is initialized with the character-string that specifies the arithmetic expression.
- 2. The type-bound procedure evaluate(), which returns the result (scalar or array-shaped) as a POINTER.
- 3. The type-bound procedure link() connecting a variable to a name in the character-string expression.

#### A.3.1. Fortran examples

The following examples illustrate the arithmetic expression parser. The calls to DEALLOCATE the data structures have been ommitted for the sake of brevity:

1. Scalar arithmetic expression:

```
formula = expression("sin(45*pi/180.) * 10 + 5")
CALL formula%evaluate(val)
... use "val" for some purpose ...
```

2. Masking of a 2D array as an example for the link procedure:

```
formula = expression("if([z_sfc] > 2., [z_sfc], 0. )")
CALL formula%link("z_sfc", z_sfc)
CALL formula%evaluate(val_2D)
... use "val_2D(:,:)" for some purpose ...
```

#### A.3.2. Error handling

Invalid arithmetic expressions yield "empty" expression objects. When these are evaluated, a NULL() pointer is returned. A successful expression evaluation can be tested with the err\_no variable:

```
IF (formula%err_no == ERR_NONE) THEN
   ...
END IF
```

In case of error, the err\_no variable also provides the reason for the aborted evaluation process.

#### A.4. Remarks

- Variable names are treated case-sensitive!
- For 3D array input it is implicitly assumed that 2D fields are embedded in 3D fields as "3D(:,level,:) = 2D(:,:)".

### B. Changes incompatible with former versions of the model code

```
Change: var_names_map_file, out_varnames_map_file
Date of Change: 2013-04-25
Revision: 12016
```

- $\bullet \ {\rm Renamed} \ {\bf var} \ \ {\bf names} \ \ {\bf map} \ \ {\bf file} \to {\bf output} \ \ {\bf nml} \ \ {\bf dict}.$
- $\bullet \ {\rm Renamed} \ \mathbf{out} \ \ \mathbf{varnames} \ \ \mathbf{map} \ \ \mathbf{file} \to \mathbf{netcdf} \ \ \mathbf{dict}.$
- The dictionary in netcdf\_dict is now reversed, s.t. the same map file as in output\_nml\_dict can be used to translate variable names to the ICON internal names and back.

<sup>&</sup>lt;sup>1</sup>This number seems to be based on Hayford's 1910 estimate of the Earth. It is used in ICON as well as MPAS and was almost certainly taken from the Jablonowski and Williamson test case (QJRMS, 2006).

Change: output nml: namespace

 Date of Change:
 2013-04-26

 Revision:
 12051

• Removed obsolete namelist variable namespace from output nml.

Change: gribout nml: generatingCenter, generatingSubcenter

 Date of Change:
 2013-04-26

 Revision:
 12051

• Introduced new namelist variables **generatingCenter** and **generatingSubcenter**.

• If not set explicitly, center and subcenter information is copied from the input grid file

Change: radiation nml: albedo type

 Date of Change:
 2013-05-03

 Revision:
 12118

- ullet Introduced new namelist variable **albedo type**
- If set to 2, the surface albedo will be based on the MODIS data set.

Change: initicon nml: dwdinc filename

 Date of Change:
 2013-05-24

 Revision:
 12266

• Renamed dwdinc\_filename to dwdana\_filename

Change: initicon nml: l ana sfc

 Date of Change:
 2013-06-25

 Revision:
 12582

- $\bullet$  Introduced new namelist flag  $l_ana_sfc$
- If true, soil/surface analysis fields are read from the analysis fiel dwdfg\_filename. If false, surface analysis fields are not read. Soil and surface are initialized with the first guess instead.

Change: new\_nwp\_phy\_tend\_list: output names consistent with variable names

 Date of Change:
 2013-06-25

 Revision:
 12590

ullet temp tend radlw o ddt temp radlw

ullet temp tend turb ightarrow ddt temp turb

• temp tend  $drag \rightarrow ddt$  temp drag

Change: prepicon nml, remap nml, input field nml

 Change:
 prepicon\_n

 Date of Change:
 2013-06-25

 Revision:
 12597

- Removed the sources for the "prepicon" binary!
- The "prepicon" functionality (and most of its code) has become part of the ICON tools.

Change: initicon\_nml
Date of Change: 2013-08-19
Revision: 13311

• The number of vertical input levels is now read from file. The namelist parameter **nlev** in has become obsolete in r12700 and has been removed.

 Change:
 parallel\_nml

 Date of Change:
 2013-10-14

 Revision:
 14160

• The namelist parameter exch\_msgsize has been removed together with the option iorder\_sendrecv=4.

Change: parallel\_nml
Date of Change: 2013-08-14
Revision: 14164

• The namelist parameter use sp\_output has been replaced by an equivalent switch use dp\_mpi2io (with an inverse meaning, i.e. we have use dp\_mpi2io = .NOT. use sp\_output).

 $egin{array}{lll} {\it Change:} & {\it parallel\_nml} \\ {\it Date of Change:} & {\it 2013-08-15} \\ {\it Revision:} & {\it 14175} \\ \hline \end{array}$ 

• The above-mentioned namelist parameter use \_dp \_mpi2io got the default .FALSE. By this, the output data are sent now in single precision to the output processes.

Change: initicon nml: l ana sfc

 Date of Change:
 2013-10-21

 Revision:
 14280

• The above-mentioned namelist parameter l\_ana\_sfc has been replaced by lread\_ana. The default is set to .TRUE., meaning that analysis fields are required and read on default. With lread\_ana=.FALSE. ICON is able to start from first guess fields only.

Change: output nml: lwrite ready, ready directory

Date of Change: 2013-10-25

*Revision*: 14391

- The namelist parameters lwrite ready and ready directory have been replaced by a single namelist parameter ready\_file, where ready\_file /= 'default' enables writing ready files.
- Different output\_nml's may be joined together to form a single ready file event they share the same ready\_file.

Change: output nml: output bounds

Date of Change: 2013-10-25

*Revision:* 14391

• The namelist parameter **output\_bounds** specifies a start, end, and increment of output invervals. It does no longer allow multiple triples.

Change: output\_nml: steps\_per\_file

 Date of Change:
 2013-10-30

 Revision:
 14422

• The default value of the namelist parameter steps per file has been changed to -1.

 Change:
 run\_nml

 Date of Change:
 2013-11-13

 Revision:
 14759

- The dump/restore functionality for domain decompositions and interpolation coefficients has been removed from the model code. This means, that the parameters
  - ldump\_states,
  - $-\ {\tt lrestore\_states},$
  - ldump\_dd,
  - lread\_dd,

```
- nproc_dd,
```

- dd\_filename,
- dump\_filename,
- l\_one\_file\_per\_patch

have been removed together with the corresponding functionality from the ICON model code.

Change: output nml: filename format

 Date of Change:
 2013-12-02

 Revision:
 15068

• The string token <ddhhmmss> is now substituted by the relative day-hour-minute-second string, whereas the absolute date-time stamp can be inserted using <datetime>.

Change: output nml: ready file

 Date of Change:
 2013-12-03

 Revision:
 15081

• The ready file name has been changed and may now contain string tokens <path>, <datetime>, <ddhhmmss> which are substituted as described for the namelist parameter filename\_format.

Change: interpl nml: rbf vec scale ll

 Date of Change:
 2013-12-06

 Revision:
 15156

- The real-valued namelist parameter rbf\_vec\_scale\_ll has been removed.
- Now, there exists a new integer-valued namelist parameter, rbf\_scale\_mode\_ll which specifies the mode, how the RBF shape parameter is determined for lon-lat interpolation.

 $\begin{array}{ll} \textit{Change:} & \text{io\_nml} \\ \textit{Date of Change:} & \textbf{2013-12-06} \\ \textit{Revision:} & \textbf{15161} \end{array}$ 

- Removed remaining vlist-related namelist parameter. This means that the parameters
  - out filetype
  - $\ {\rm out\_expname}$
  - dt\_data
  - dt file
  - lwrite\_dblprec, lwrite\_decomposition, lwrite\_vorticity, lwrite\_divergence, lwrite\_pres, lwrite\_tracer, lwrite\_tend\_phy, lwrite\_radiation, lwrite\_precip, lwrite\_cloud, lwrite\_tke, lwrite\_surface, lwrite\_initial, lwrite\_oce\_timestepping

are no longer available.

 $\begin{array}{ll} \textit{Change:} & \textit{gridref\_nml} \\ \textit{Date of Change:} & 2014\text{-}01\text{-}07 \\ \textit{Revision:} & 15436 \end{array}$ 

• Changed namelist defaults for nesting: grf\_intmethod\_e, 1\_mass\_consvcorr, 1\_density\_nudging.

 $\begin{array}{ll} {\it Change:} & {\it interpol\_nml} \\ {\it Date of Change:} & {\it 2014-02-10} \\ {\it Revision:} & {\it 16047} \end{array}$ 

• Changed namelist default for rbf\_scale\_mode\_11: The RBF scale factor for lat-lon interpolation is now determined automatically by default.

Change: echam\_phy\_nml

 Date of Change:
 2014-02-27

 Revision:
 16313

• Replace the logical switch lcover by the integer switch icover that is used in ECHAM-6.2. Values are transferred as follows: .FALSE. = 1 (=default), .TRUE. = 2.

 $\begin{array}{ll} \textit{Change:} & \textit{turbdiff\_nml} \\ \textit{Date of Change:} & \textit{2014-03-12} \\ \textit{Revision:} & \textit{16527} \end{array}$ 

• Change constant minimum vertical diffusion coefficients to variable ones proportional to  $1/\sqrt{Ri}$  for inwp\_turb = 10; at the same time the defaults for tkhmin and tkmmin are increased from  $0.2 \,\mathrm{m}^2/\mathrm{s}$  to  $0.75 \,\mathrm{m}^2/\mathrm{s}$ .

 Change:
 nwp\_phy\_nml

 Date of Change:
 2014-03-13

 Revision:
 16560

• Removed namelist parameter dt\_ccov, since practically it had no effect. For the quasi-operational NWP-setup, the calling frequency of the cloud cover scheme is the same as that of the convection scheme. I.e. both are synchronized.

 Change:
 nwp\_phy\_nml

 Date of Change:
 2014-03-24

 Revision:
 16668

• Changed namelist default for **itype z0**: use land cover related roughness only (itype\_z0=2).

Change: nonhydrostatic nml

 Date of Change:
 2014-05-16

 Revision:
 17293

• Removed switch for vertical TKE advection in the dynamical core (lvadv\_tke). TKE advection has been moved into the transport scheme and can be activated with iadv\_tke=1 in the transport nml.

Change: nonhydrostatic\_nml

 Date of Change:
 2014-05-27

 Revision:
 17492

• Removed namelist parameter model\_restart\_info\_filename in namelist master\_model\_nml.

 Change:
 transport\_nml

 Date of Change:
 2014-06-05

 Revision:
 17654

• Changed namelist default for itype\_hlimit from monotonous limiter (3) to positive definite limiter (4).

 Change:
 nh\_pzlev\_nml

 Date of Change:
 2014-08-28

 Revision:
 18795

• Removed namelist nh\_pzlev\_nml. Instead, each output namelist specifies its separate list of p\_levels, h\_levels, and i\_levels.

Change: nonhydrostatic nml

 Date of Change:
 2014-10-27

 Revision:
 19670

• Removed namelist parameter l\_nest\_rcf in namelist nonhydrostatic\_nml.

Change: nonhydrostatic nml

 Date of Change:
 2014-11-24

 Revision:
 20073

• Removed namelist parameter iadv\_rcf in namelist nonhydrostatic\_nml. The number of dynamics substeps per advective step are now specified via ndyn\_substeps.

The meaning of run\_nml:dtime has changed and denotes the advective time step.

 Change:
 io\_nml

 Date of Change:
 2015-03-25

 Revision:
 21501

• Namelist parameter lzaxis\_reference is deprecated and has no effect anymore. However, users are not forced to modify their scripts instantaneously: lzaxis\_reference=.FALSE. is still a valid namelist setting, but it has no effect and a warning will be issued. lzaxis\_reference finally removed in r24606.

 $egin{array}{lll} {\it Change:} & & {\it limarea\_nml} \\ {\it Date of Change:} & & {\it 2016-02-08} \\ {\it Revision:} & & {\it 26390} \\ \end{array}$ 

• Namelist parameter dt\_latbc has been removed. Its value is now identical to the namelist parameter dtime\_latbc.

 $\begin{array}{ll} \textit{Change:} & \text{interpol\_nml} \\ \textit{Date of Change:} & \textbf{2016-02-11} \\ \textit{Revision:} & \textbf{26423} \end{array}$ 

• Namelist parameter 1\_intp\_c21 is deprecated and has no effect anymore.

 Change:
 lnd\_nml

 Date of Change:
 2016-07-21

 Revision:
 28536

• The numbering of the various options for sstice\_mode has changed. Former option 2 became 3, former option 3 became 4, and former option 4 became 5. This was necessary, because a new option was introduced (option 2).

 $egin{array}{lll} {\it Change:} & & {\it initicon\_nml} \\ {\it Date of Change:} & & {\it 2016-07-22} \\ {\it Revision:} & & {\it 28556} \\ \hline \end{array}$ 

• Namelist parameter latbc\_varnames\_map\_file has been moved to the namelist limarea\_nml.

 Change:
 transport\_nml

 Date of Change:
 2016-09-22

 Revision:
 29339

• Namelist parameter niter\_fct has been removed, since the functionality of iterative flux correction is no longer available.

Change: initicon\_nml
Date of Change: 2016-10-07
Revision: 29484

• Namelist parameter l\_sst\_in has been removed. In case of init\_mode=2 (IFSINIT), sea points are now initialized with SST, if provided in the input file. Otherwise sea points are initialized with the skin temperature. The possibility to use the skin temperature despite having the SST available has been dropped.

Change: initicon\_nml
Date of Change: 2016-12-14

Revision: 62288ed77b2975182204a2ec6fa210a3fb1ad8a7

• Namelist parameters ana\_varlist, ana\_varlist\_n2 have been renamed to check\_ana(jg)%list, with jg indicating the patch ID.

Change: initicon\_nml
Date of Change: 2017-01-27
Revision: ae1be66f

• The default value of the namelist parameter num\_prefetch\_proc has been changed to 1, i.e. asynchronous read-in of lateral boundary data is now enabled.

 $egin{array}{lll} {\it Change:} & & {\it interpol\_nml} \\ {\it Date of Change:} & & {\it 2017-01-31} \\ {\it Revision:} & & {\it e1c56104} \\ \hline \end{array}$ 

• With the introduction of the namelist parameter lreduced\_nestbdry\_stencil in the namelist interpol\_nml the nest boundary points are no longer removed from lat-lon interpolation stencil by default.

 Change:
 limarea\_nml

 Date of Change:
 2017-03-14

 Revision:
 631b731627

• The namelist parameter nlev\_latbc is now deprecated. Information about the vertical level number is taken directly from the input file.

Change: echam phy nml / mpi phy nml

Date of Change: 2017-04-19

Revision: icon-aes:icon-aes-mag 9ecee54f69108716308029d8d7aa0296c343a3c2

• The namelist echam\_phy\_nml is replaced by the namelist mpi\_phy\_nml, which extends the control to multiple domains and introduces time control in terms of start and end date/time [sd\_prc,ed\_prc] and time interval dt\_prc for individual atmospheric processes prc.

Change: mpi phy nml / echam phy nml and mpi sso nml / echam sso nml

Date of Change: 2017-11-22

Revision: icon-aes-cfgnml f84219511329281d441d81923fe97ce1d7ecf007

• The namelists, configuration variables and related modules are renamed from ...mpi\_phy... to ...echam\_phy... because programmers felt that the acronym "mpi" for "Max Planck Institute" in relation to physics cannot be distinguished from "mpi" for "Message Passing Interface" as used in the parallelization.

Change: gw hines nml / echam gwd nml

Date of Change: 2017-11-24

Revision: icon-aes:icon-aes-cfgnml 699346b5d318d53be215e0b8e8b5ba8631d44c48

• The namelists gw hines nml is replaced by the namelist echam gwd nml, which extends the control to multiple domains.

Change: vdiff nml / echam vdf nml

Date of Change: 2017-11-27

Revision: icon-aes-cfgnml f1dec0a0d3b8ec506861975cd59a729fe43fdf8e

• The namelists vdiff\_nml is replaced by the namelist echam\_vdf\_nml, which additionally includes tuning parameters for the total turbulent energy scheme, and extends the control to multiple domains.

Change: echam\_conv\_nml / echam\_cnv\_nml

Date of Change: 2017-11-29

Revision: icon-aes:icon-aes-cfgnml 099c40f88dbaae6c7cc79ea878e5862847ef7e27

• The namelists echam conv nml is replaced by the namelist echam cnv nml, which extends the control to multiple domains.

Change: echam cloud nml / echam cld nml

Date of Change: 2017-12-04

Revision: icon-aes:icon-aes-cfgnml afacc102a87b03f78ff47ad0b7af8f348bacef6f

• The namelists echam\_cloud\_nml is replaced by the namelist echam\_cld\_nml, which extends the control to multiple domains.

Change: psrad orbit nml / radiation nml / echam rad nml

Date of Change: 2017-12-12

 ${\it Revision:} \qquad \qquad {\rm icon-aes:icon-aes-cfgnml~8da087238b81183c337a3b1ae81d2b2e3dafdba8}$ 

• For controlling the input of ECHAM physics to the PSrad scheme, the namelists psrad\_orbit\_nml and radiation\_nml are replaced by the namelist echam\_rad\_nml, which extends the control to multiple domains. For controlling the input of NWP physics to the RRTMG radiation, the radiation\_nml namelist remains valid. The psrad orbit nml namelist, which is not used for RRTMG radiation, is deleted.

 ${\it Change:} \hspace{1.5cm} {\it echam\_cld\_nml / echam\_cov\_nml}$ 

**Date of Change:** 2019-06-07

Revision: icon-aes:icon-aes-cover 09233f275f207d59d2cb6ad75bd13adf81c0d0c2

• The control parameters for the cloud cover parameterization (crs, crt, nex, jbmin, jbmax, cinv, csatsc) are shifted to the new namelist echam cov nml.

Change: echam cov nml / echam cov nml

Date of Change:  $2019-0\overline{6}-12$ 

Revision: icon-aes:icon-aes-cover 419e7ed54faa6db86a7151ece33b8e0b24737129 and e66e8e0f9cd439b81d7db63e0a4e03004d7f8144

• The control parameters jks, jbmin and jbmax, specifying heights by the index of the vertical grid, are replaced by parameters zcovmax, zinvmax, and zinvmin, respectively, which directly specify the heights of interest. The change is as follows:

- jks=15 -> zmaxcov=echam phy config%zmaxcloudy
- jbmin=43 -> zmaxinv=2000m
- jbmax=45 -> zmininv=300m

Change: echam\_cld\_nml / echam\_cld\_nml

Date of Change:  $2019-0\overline{6}-12$ 

 $\frac{Revision:}{\text{icon-aes:icon-aes-cover ab95fc16a944dde96a76aeb1f63a7c847d78da06 and e66e8e0f9cd439b81d7db63e0a4e03004d7f8144}{\text{icon-aes:icon-aes-cover ab95fc16a944dde96a76aeb1f63a7c847d78da06 and e66e8e0f9cd439b81d7db63e0a4e03004d7f8144}{\text{icon-aes:icon-aes-cover ab95fc16a944dde96a76aeb1f63a7c847d78da06}}$ 

• The control parameters jks, specifying height by the index of the vertical grid, is replaced by the parameters zcldmax, which directly specify the height of interest. The change is as follows:

- jks=15 -> zmaxcld=echam phy config%zmaxcloudy