

Documentation - Scheduled runs of the ICON code at ECMWF

Document version: Phase 0 (Q2/2012)

General Notes

Case Setup

Objectives

- run time: 10 days
- time step size: 60 sec, $10 \times 24 \times 3600 / 60 = 14400$ steps
- output every 3h = 10800 sec, 80 output actions

Restrictions

- Results are stored in a dedicated directory
- IFS2ICON based on Ruby scripting language
- (Experimental) GRIB2 output available for plot suite

TODO

- Write platform independent scripts (using includes and conditionals).
- (With full access to IFS MARS data:) Enable retrieval for SMSDATE in task `get_data.sms`
- increase no. of SMSTRIES for operational use
- ~~• set wall clock time limits and node numbers~~
- check error code of the model binary
- runs build and dumpstate computation with a larger frequency.
- ~~• Show a current computation date in XGDP~~
- Use multi-threaded version of CDOs
- Use `/home/ms/de/dw7/bin/grib_def` for GRIB definition.
- perform IFS2ICON in a temporary directory (otherwise this might exceed the quota on \$PERM).
- Use SVN access on c1a for SVN update
- ~~• Build with 03~~

SMS suite ICON_R2B06_10d

The ICON runs employ ECMWF's scheduler "SMS", cf. <http://www.ecmwf.int/publications/manuals/sms/>.

- Model is run by a dedicated user.
- SMS files are stored in the Redmine svn version control system

The described scheduler setup for the ICON model is partly based on a similar script suite for BCeps (H. Frank, User zde), see


`/home/ms/de/zde/BCeps/bceps.def`

Directory layout

- The actual case setup for ICON is stored in the file `def/case_setup`.
- The SMS suite is defined in `$HOME/ICON_R2B06_10d/def/smsfiles/icon.def`
- All temporary SMS files are stored in `$HOME/sms_server` and `$HOME/sms`.
- Temporary results are stored in `$TMPDIR` on `ecgate` and `$TEMP/sms` on the cluster file system.

All script files and the model setup are located in a directory `$HOME/ICON_R2B06_10d` of the following layout:

```
$HOME/ICON_R2B06_10d
def                                ! scripts for operating the suite
  smsfiles
  include
  icon_scripts                     ! checkout from ICON SVN: trunk/icon-dev/scripts
  bin                             ! additional script files
output
  model                           ! current model output
  log                             ! SMS suite logfiles
doc                               ! this documentation
cluster                           ! [only on compute cluster]
  icon-dev                       ! latest build of SVN trunk [only on compute
cluster]
  input                           ! static input (time-independent)
    extpar
    grids
    radiation
    ifs2icon                      ! model input from IFS
    cellweights
    config
  dumpstate                       ! interpolation coefficients
```



Note: An identical directory structure is necessary on the compute cluster file system,
/perm/ms/de/dfi0

Note: Not all necessary contents are stored in the Redmine repository

<https://svn.zmaw.de/svn/icon/trunk/icon-dev/schedulers/ecmwf/ICON> r2B06 10d


After the initial check-out one must add

- def/icon_scripts (from <https://svn.zmaw.de/svn/icon/trunk/icon-dev/scripts>)
- [On cluster:] cluster/icon-dev

Suite definition

Diagram of the ICON SMS suite:

- Dependencies between tasks are denoted with lines.
- Less frequently processed tasks are denoted by brackets [].



List of SMS tasks

task	description	depends on event
init		
get_data	retrieve IFS data from MARS	
init_data	process IFS data for ICON	get_data==complete
init_svn	update ICON sources	NOT \$skip_build_process
init_build	build ICON binary	NOT \$skip_build_process AND init_svn==complete
forecast		init===complete
pre_clean	initial clean-up	
dumpstate	create/check for dump state	
model	model run	fct_prepare==complete
postprocess		fct_model:run_model
post_archive	copy output/store in database/trigger transfer to	

	DWD	
post_process	extract output, generate plots	

- The task `init_data` comprises the computation of `cell_weights` – but only if they have not been previously computed. This is indicated by the existence of a file
`cluster/input/ifs2icon/cellweights/initialized.flag`
- The task `init_data` loads the Climate data Operators `cdo` version 1.5.0. Note that the default version 1.4.6 installed on `cla` cannot be used with `ifs2icon` while for the newer 1.5.3 NetCDF support has not been compiled in.
- The task `init_data(ifs2icon` contains a call to `cdo merge` which consumes a considerable amount of memory (for R2B06, the default of ~780MB is not sufficient).

Trigger mechanism

The whole SMS suite is restarted (repeat `date` keyword) on a regular basis. The suite contains an artificial dummy task, `fct_ifs`, whose completion is the starting condition for the whole suite.

There exists a small shell script `def/smsfiles/job.trigger` which is triggered by the IFS framework itself, i.e. via

```
ecaccess-job-submit
```

This shell script calls a CDP command:

```
force complete fct_ifs
```

and thus activates the whole ICON SMS suite.

Setting up the SMS

sms_start

command

```
sms_start
```

gives

```
User "3455" attempting to start sms server on "ecgate" using PROGNUM = "903455"
and with SMSHOME of "/home/ms/de/dfi0/sms_server"
```

```
Checking if the SMS is already running on ecgate
...
```

Then write host and number to `.cdprc`:

```
alias myalias set SMS_PROG 903455 \; login ecgate UID 1
```

Running the suite

In `ICON_r2B06_10d/def/smsfiles/` call

```
./start_sms.sh
```

Run the suite with

```
cdp
```

```
CDP> myalias
CDP> play icon.def
CDP> begin icon
```

Check the status of the suite with

```
cdp
```

```
CDP> myalias
CDP> status -f
/{sub}    icon{sub}    t1[sub]
```

Restarting the suite

Add the following to your \$HOME/.cdprc file:

```
define icon_restart {
    cancel -y icon
    play icon.def
    begin icon
}
```

Then restart the ICON suite by typing

cdp

```
CDP> myalias
CDP> icon_restart

cancel:/icon by UID@220
unknown:/
# MSG:play:Sending icon to ecgate
# MSG:play:Suite icon defined.
begin:/icon started by UID@220
```

Logserver

On the compute cluster c1a a special process is in charge of copying log files back to ecgate s.t. they can be viewed in xcdp:

```
cd $HOME/ICON_r2B06_10d/def/bin
./logserver
```

Now a log server daemon must be running:

```
ps -ef | grep $USER
```

yield something like

```
... 418144      1   0 10:34:29 pts/172   0:00 /usr/bin/perl
/usr/local/bin/logsvr.pl
```

Technical infrastructure

.rhosts

Enable rcp and rsh between the compute cluster and ecgate by setting the \$HOME/.rhosts file:

```
echo "ecga02 $USER" >> ~/.rhosts
```

For copying files between ecgate and compute cluster we use the commands rcp or ecrpcp.

SVN access

Automatic builds perform a complete svn export.

Please note: For direct access to ZMAW's subversion repository, changes in \$HOME/.subversion/servers are necessary:

```
http-proxy-host = *****
http-proxy-port = *****
```

(Ask L. Kornblueh, F. Prill for details).

Local Ruby installation

Script language ruby has to be installed locally (user account).

Prerequisites:

1. Ruby source code downloaded from <http://www.ruby-lang.org/de/downloads/> to \$PERM/software.
2. Package "extcsv" required; download from <http://rubygems.org/gems/extcsv> to \$PERM/software/packages.
3. Package "gnuplot" required; download from <http://rubygems.org/gems/gnuplot> to \$PERM/software/packages.

Installation process:

```
tar xvf ruby-1.9.3-p125.tar
cd ruby-1.9.3-p125
./configure --prefix=$PERM/software/ruby-1.9.3-p125_build
gmake -j6
gmake install
cd ../packages
$PERM/software/ruby-1.9.3-p125_build/bin/gem install extcsv
$PERM/software/ruby-1.9.3-p125_build/bin/gem install gnuplot
```

Patch required: In \$PERM/software/ruby-1.9.3-p125_build/lib/ruby/gems/1.9.1/gems/extcsv-0.12.0/lib/extcsv_diagram.rb comment out require statement:

```
#require 'extcsv_units'
```

Local CDO installation

It is necessary to compile a local version of the [Climate Data Operators](#), which is newer than v1.5.0, because the system installation of the CDOs on c1a has not been compiled with NetCDF support. The configure script must be provided with the correct system paths for NetCDF, Jasper and GRIB_API:

```
ls -rlt
gunzip cdo-1.5.4.tar.gz
tar xvf cdo-1.5.4.tar
cd cdo-1.5.4
./configure -with-netcdf=/usr/local/apps/netcdf/3.6.3/LP64
--prefix=/perm/ms/de/dfi0/software/cdo-1.5.4_build --with-
grib_api=/usr/local/lib/metaps/lib/grib_api/1.9.9 --with-
jasper=/usr/local/apps/jasper/1.900.1/LP64
gmake -j2
gmake install
```

After successful compilation, all IFS2ICON processes must run with

\$PERM/software/cdo-1.5.4_build/bin/cdo

To this end, the task `init_data.sms` exports an environment variable `CDOBIN` which is then used by the Ruby script `ifs2icon.rb`.

GRIB_API settings

We want to use the same IFS2ICON configuration settings for ECMWF as well as for DWD, therefore the GRIB2 short names must be taken from DWD's definition files:

```
export GRIB_DEFINITION_PATH=%SCPERM%/software/usr/local/grib_api/release/share-
1.9.9/definitions.edzw:/usr/local/lib/metaps/lib/grib_api/1.9.9/share/definition
s
```

The directory "%SCPERM%/software/usr/local/grib_api/release/share-1.9.9/definitions.edzw" can be

tar'ed and copied from DWD's HPC file system.

Alternative approach: DWD GRIB definitions are already installed under

`~dwd/grib_api/definitions.edzw-${my_api_version}`

One can set them using the script `/home/ms/de/dw7/bin/grib_def`.

Local settings

MARS4ICON script must be executable:

```
chmod +x ~/ICON_r2B06_10d/icon-dev/scripts/preprocessing/mars4icon_smi_32r3+
```

Date conversion script `datconv` must be in PERL's search path:

```
cd $HOME/bin
ln -s ~dfr/routfox/bin/datconv .
ln -s ~dfr/routfox $HOME/
export PERL5LIB="/home/ms/de/dfi0/routfox/perl"
```