DEEP CYCLE LITHIUM BATTERIES

The LiFePO4 battery shares the same structural specifications as lead-acid batteries but offers advantages such as high safety, reliability, long cycle life, and excellent temperature performance. Its unique benefits make it suitable for various applications,including RVs,sightseeing carts,marineuse,scooters,tricycles,emergencylighting,and security monitoring.It serves as an ideal drop-in replacement for traditional lead-acid batteries.

Flexibility

From 7Ah to 300Ah, with 12V / 24V variants

Versatile in multiple application scenarios

Standard group size, down to upgrade of old batteries

Techno-convenience

Bluetooth pre-installed with the built-in smart BMS

Free cell phone app accessible for monitoring and micro-adjusting

Cutting-edge Quality

Capable of connecting 4 batteries together in either series or parallel

Tier-1 Top brands' A-grade LFP cells



LT-12020H



LT-12050H



LT-12100H/S



LT-12150H/S LT-24100H



LT-12300H

www.life-tech.es info@life-tech.es

Main Parameters

	LT-12008H	LT-12012H	LT-12020H	LT-12050H	LT-12100H/S	LT-12150H/S	LT-12200H/S	LT-12300H	LT-24100H
Cell Type	LiFePO4								
Nominal Capacity (Ah)	8	12	20	50	100	150	200	300	100
Rated Energy (Wh)	1024	1536	256	640	1280	1920	2560	3840	2560
Rated Voltage (V)	12.8								25.6
Charge Ending Voltage (V)	14.6(Max.14.6)								28.4 (Max.29.2)
Discharge Ending Voltage (V)	10	10	10	10	10	10	10	10	20
Standard Charge Current (A)	1.6	2.4	4	10	20	30	40	60	20
Max. Charge Current (A)	≤ 8	≤ 12	≤ 20	≤ 50	≤100	≤150	≤150	≤150	≤100
Standard Discharge Current (A)	4	6	10	25	50	75	100	100	50
Max. Discharge Current (A)	10	15	≤20	≤50	≤ 100	≤150	≤150	≤150	≤100
Operating Temperature	Charge: 0°C ~ +55°C ;Discharge: -20°C ~ +55°C								
Operating Voltage (V)	10.0-14.6								20.0-29.2
Weight (kg) L*W*H (mm)	0.8	1.1	3.5	8	13.5	18	23	33	21
	150*65 *94	150*99 *94	180*76 *168	223*134 *177	332*172 *220	483*168 *240	483*168 *240	383*193.3 *250	483*170 *240

Charger or inverter/charge settings

Max Charge Current(A)	≤ 6.6	≤ 9.9	≤ 19.8	≤ 50	≤ 100	≤ 150	≤ 150	≤ 150	≤ 100
Charge Profile	Lithium, fixed								
Absorption Voltage(V)	14.2								28.4
Absorption Time(h)	12								12
Float Voltage(V)	13.5								27
Storage Voltage(V)	13.5								27