When Evidence Is Not Enough: Planning, Program Generation, and Verification in Memory-Constrained Financial Reasoning

Anonymous submission

Abstract

Executable programs and verification can improve numerical reasoning, but neither guarantees that a small language model constructs the right calculation. We study this distinction in two complementary CPU-only settings using Qwen2.5 models and financial question answering. A nominal 16 GB deployment comparison on 160 FinQA questions from 50 reports finds that a resident F16 specialist team delivers 5 correct answers versus 78 for a 14B Q4 single-model pipeline under reported-answer scoring, while withholding 152 versus 34. A completed Ubuntu replication preserves these outcomes with no observed process swap under a swap-disabled scope. Separate Windows experiments under an 8 GB application-budget tier find candidate failures even when an annotated solution is executable from the available evidence. On 15 enriched diagnostic reports, supplying reference operation structure and an operand shortlist raises execution matches from 0 to 10; these answer-key interventions are not deployable improvements. A subsequent evidence-only planner on 96 project-held-out TAT-QA contexts increases correct deliveries from 6 to 10 but wrong deliveries from 23 to 25, failing its prespecified success criterion. Correct candidates decrease from 26 to 25, exact paired $p = 0.125$ for correct delivery, and a 28-context secondary comparison shows no delivery gain. The evidence supports a bounded failure analysis, not a general architectural ranking: evidence availability, calculation construction, and selective delivery must be evaluated separately, with explicit scoring and resource qualifications.

1 Introduction

Financial question answering requires selecting quantities from tables and prose, constructing a calculation, and interpreting its units. An executable answer can use genuine source values yet compute the wrong quantity. A verifier can reduce wrong deliveries by withholding most answers, without improving candidate generation. These distinctions matter when available memory limits both model capacity and the number of resident specialists.

Program-aided reasoning delegates arithmetic to an interpreter (Gao et al. 2023; Chen et al. 2023); multiagent debate can improve reasoning in other settings (Du et al. 2024). Neither result implies that a small resident team is preferable to a larger quantized model, or that additional planning is beneficial at a fixed token ceiling. Equal-budget reasoning studies and multiagent failure taxonomies already question simple architectural advantages (Tran and Kiela 2026; Cemri et al. 2025). Our contribution is a trace-based empirical analysis of specific financial reasoning recipes, including a prospective test that fails to translate answer-key diagnostic potential into a practical planning gain.

We separate two studies. Study A compares a 14B Q4 single-model pipeline with a resident 1.5B/3B/0.5B F16 team on the same FinQA questions under an 11.5 GB sampled application RSS ceiling. Study B uses smaller quantized models and learned role adapters on Windows, with a 6.1 GB worker commit ceiling and a 6.4 GB sampled working-set guard. The second setting is called the "8 GB tier" in the experimental record; it runs on a 16.39 GB host and does not establish physical 8 GB feasibility. The studies differ in models, precision, adaptation, runtime and data. They are complementary investigations, not a factorial architecture experiment or a cross-tier scaling curve.

Three questions organize the evidence: (1) does the resident team provide useful correct delivery under the larger budget? (2) when evidence is available, which constraints expose remaining generation failures? and (3) can an evidence-only planner realize the potential suggested by reference-informed constraints? We retain failures of retrieval expansion, precision increases, verification transfer and repair. We report stronger direct-answer comparators, both numerical scoring conventions, and interrupted runs. No new inference was performed for manuscript preparation.

Study A's original questions concern delivery trade-offs (RQ1), failure location (RQ2), shared prompt/repair interventions (RQ3), and memory and time per useful answer (RQ4). Its primary operational hypothesis (H1) is fewer wrong deliveries without losing correct deliveries. Secondary hypotheses ask whether the analysis/demonstration bundle improves correct delivery (H2), repair adds correct answers without adding wrong ones (H3), and fewer team parameters mean no greater resident memory (H4). H1, H3 and H4 fail in the observed recipes; H2 is descriptively favorable but does not isolate analysis from demonstrations. The later planner has its own prespecified criterion below.

This is an anonymized submission for review purposes only. Distribution, citation, or public sharing of this manuscript is strictly prohibited. Copyright and publication details will appear in the final version if accepted.

Extended tests, strata and utility analyses are post hoc, not retrospectively confirmatory.

2 Related Work

Financial and program-based reasoning. FinMAN already decomposes financial QA into formula selection, extraction, calculation and lightweight verification (Liu et al. 2025); DCRC learns evidence auditing and executable program synthesis (Chen et al. 2026). Bench360 measures deployment quality/resource trade-offs across inference configurations (Stuhlmann, Argerich, and Fürst 2026). We do not claim these components or the general need for resource-aware evaluation as novel, nor reproduce those systems under our ceilings. FinQA provides expert questions and annotated programs over financial reports (Chen et al. 2021). TAT-QA combines tables and text with arithmetic and other answer types (Zhu et al. 2021); our experiments cover numerical FinQA and arithmetic TAT-QA subsets, not full benchmark leaderboards. PAL separates program synthesis from execution (Gao et al. 2023). Program of Thoughts evaluates executable reasoning on financial datasets, including FinQA and TAT-QA, and discusses semantic binding (Chen et al. 2023). Our source-reference grammar restricts operand provenance, but does not establish that the selected operands or formula answer the question. We test this limitation rather than claim a new program-reasoning method.

Planning, collaboration and verification. Multiagent debate reports gains from repeated exchange (Du et al. 2024); self-consistency samples multiple reasoning paths (Wang et al. 2023). We do not replicate either protocol. Tran and Kiela (Tran and Kiela 2026) compare single- and multiagent reasoning under matched thinking-token budgets. Our ceilings include generated tokens across stages but do not equalize actual tokens, parameter-weighted compute or FLOPs. MAST analyzes system-design, inter-agent and verification failures across broader frameworks (Cemri et al. 2025). Our evidence is narrower: saved arithmetic programs permit direct inspection of candidate correctness, source binding and final delivery.

Self-Refine demonstrates iterative self-feedback (Madaan et al. 2023); Huang et al. (Huang et al. 2024) find intrinsic reasoning correction unreliable without external feedback. CRITIC incorporates tool feedback (Gou et al. 2024). These results motivate controls for both positive and negative effects of review. In recent financial QA work, VeriFin independently authorizes facts and formulas using XBRL and symbolic verification (Hall, Shome, and Eiers 2026); our source-membership checks are substantially weaker. BudgetVerify learns which verification tier to invoke from offline correctness and cost outcomes (Jenq and Shen 2026). We neither reproduce those systems nor claim priority for verification, repair or budget allocation. Our diagnostic reference structures explicitly supply information unavailable to an ordinary learned planner.

Adaptation and selective delivery. LoRA and QLoRA provide established parameter-efficient adaptation mechanisms (Hu et al. 2021; Dettmers et al. 2023); role adapters are experimental components, not our novelty. Selective prediction distinguishes coverage from error among accepted predictions (Geifman and El-Yaniv 2019). Accordingly, we report correct, wrong and withheld outcomes over all questions. A lower wrong-delivery rate alone is not an improvement, and zero observed errors on a small constructed challenge is not a safety guarantee.

3 Methods and Evaluation

3.1 Programs, Candidates and Delivery

All models belong to the Qwen2.5 instruction-tuned family (Qwen Team 2024). Public evidence packets are built without answer labels. FinQA packets use lexical top-eight source-unit retrieval. The source-quantity catalog maps reference IDs to numerical values and source spans. Program generation uses constrained JSON with arithmetic operations (addition, subtraction, multiplication and division), supported constants, and references to earlier steps. A deterministic executor checks source membership and evaluates the final step. This provides arithmetic and provenance checks, not financial semantic validation.

Let K_i indicate a correct executable candidate and D_i indicate delivery on question i. The main rates are

$$C = n^{-1} \sum_i D_i K_i, \tag{1}$$

$$W = n^{-1} \sum_i D_i (1 - K_i), \tag{2}$$

$$H = n^{-1} \sum_i (1 - D_i), \qquad C + W + H = 1. \tag{3}$$

For repair policies, K_i refers to the final candidate; initial candidates are reported separately. A gate with no repair cannot deliver more correct answers than exist in its candidate pool. Candidate and delivery accuracy therefore answer different questions. Invalid outputs, refusals and rejected programs remain in denominators as withheld. Conditional error $W/(C+W)$ is descriptive of each policy's selected answers, not a matched comparison at fixed coverage.

3.2 Study A: Nominal 16 GB Deployment Recipes

The frozen cohort contains 160 FinQA development-source numerical questions from 50 company-year reports and 36 companies. Reports were selected by fixed ID hash after excluding recorded earlier report exposure; every eligible question in a selected report was retained. Public packets and scoring annotations are separate. Public-data and checkpoint pretraining overlap are not ruled out.

The single-agent system (SAS) uses an unadapted Qwen2.5-14B-Instruct Q4_K_M model for the pipeline. The multiagent system (MAS) keeps distinct unadapted 1.5B F16 extractor, 3B F16 drafter and 0.5B F16 verifier instances resident. The extractor suggests sources; the program and its execution are checked before delivery. This comparison changes parameter allocation, precision and role specialization together. "SAS" describes one model instance, not one model call.

Both recipes use CPU-only inference, eight threads, context 4,096, greedy decoding, seed 42, no memory mapping, and a 2,048 generated-token ceiling per question across stages. The primary profile includes a 128-token analysis allowance, two fixed training demonstrations, binary review and no repair. The direct control removes both analysis and demonstrations; the repair ablation adds full regeneration and review. These are bundled profile contrasts. Equal ceilings do not imply equal expenditure.

The completed Ubuntu run uses the frozen original code and pinned `llama-cpp-python` 0.3.16 runtime. It retains 16 worker attempts across interruptions, with an 11.5 decimal GB sampled controller-plus-worker RSS ceiling and a scope configured with `MemorySwapMax=0`. The Linux host reports approximately 15.44 GB usable physical RAM and a Ryzen 5 8645HS CPU. The historical run had process-swap failures; its resource invalidity is retained. The Ubuntu run repeats the same questions and is not a new statistical sample.

3.3 Study B: Diagnostics and Evidence-Only Planning

Windows comparisons use native `llama.cpp` b12202 CPU inference on a Ryzen 5 8645HS, generally context 4,096 and eight threads. Later runs impose a 6.1 GB aggregate worker Job Object commit ceiling in addition to the sampled 6.4 GB working-set guard. Earlier sampled-only pilots are not retroactively hard-capped. Commit, resident memory and paging are distinct quantities.

Exploratory interventions examine retrieval, catalog coverage, Q4/Q8 precision from a common F16 source, endpoint selection, model capacity, output format and review. Cohorts and their reuse are enumerated in the supplement. A 15-report enriched FinQA diagnostic requires that the annotated program be executable from the original catalog. Its two-by-two intervention supplies either the reference operand-value shortlist, reference operation scaffold, both, or neither. The scaffold fixes operations, constants, operand types, dependencies and endpoint. It is a substantial answer-key intervention; the shortlist can exclude valid alternatives and does not resolve equal-valued cell identities.

The deployable follow-up predicts operations and dependency edges from the question and evidence only. Its grammar uses unbound `VALUE` slots; a binding pass chooses actual source references and constants. Empty, invalid or disconnected shapes fall back to ordinary drafting. A 12-report development pilot motivated this revised grammar, which was frozen before held-out inference. No reference program or answer is supplied to this planner.

The main held-out cohort comprises 96 arithmetic table contexts from official TAT-QA development data, held out within this project. The secondary cohort comprises all 28 remaining eligible contexts from the official test data. Selection uses fixed hash ordering, one question per table, a nonempty numerical catalog, exclusions of prior table IDs, and normalized exact-table deduplication. Development contexts also exclude exact tables in the full test split. The source does not provide company-year mappings; report overlap across contexts and across benchmarks remains unverified. FinQA had only one eligible report left after recorded evaluation and actual adapter-training exclusions, motivating this benchmark change.

Four arms share evidence and a 960-token generation ceiling. Direct 7B emits a number and scale; program 7B emits a cited program and scale. Both use the same unadapted 7B Q4 checkpoint. Current MAS uses two separately resident 3B Q4 instances with fixed common-actor and control-critic adapters, allocating 768 tokens to drafting and 192 to review. Planner MAS allocates 192 to structure, 576 to binding (also the fallback cap), and 192 to the unchanged critic. Only executable candidates receiving PASS are delivered. This is a planner-plus-budget-allocation intervention, not planning at unchanged draft allowance. Both resident arms disable the RAM prompt cache.

The prespecified primary endpoint is planner-minus-MAS correct delivery. Practical success requires a positive paired interval *and no observed increase in wrong delivery*. The secondary cohort checks direction. The 7B arms are competitive comparators, not matched controls for the planner. Full templates, adapters, hashes and decoding details are in the reproducibility supplement and preserved traces.

3.4 Scoring and Statistical Analysis

Study A retains two historical numerical scores: reported-answer rounding with declared units, and raw execution-reference matching within $\max(10^{-5}, 10^{-5}|y|)$ of reference y. Neither is official FinQA program equivalence. Windows FinQA program experiments additionally translate arithmetic programs for the pinned official execution evaluator. Direct answers are compared with programs using their shared reported-answer metric, not an inapplicable program-equivalence score. TAT-QA uses the authors' pinned exact-match and F1 evaluator with predicted scales. Numerical label agreement does not establish unique or semantically correct provenance.

Study A intervals resample the 50 whole reports, retaining paired questions and question weighting, using 10,000 draws; company clustering is a sensitivity analysis. The paper's recomputation uses NumPy seed 42 and percentile quantiles. Its small endpoint differences from the original Python bootstrap are implementation differences, not changes in outcomes. Planner intervals reproduce the archived 10,000 paired table-context bootstrap draws (Python seed 73), alongside two-sided exact McNemar tests. Context pairs cannot substitute for unavailable report clusters. Tests for other interventions are exploratory; no multiplicity-adjusted discovery or equivalence claim is made. Bootstrap intervals reflect sampled cases, not seed or model-family variability. Sparse discordance can make percentile bootstrap intervals misleadingly reassuring.

4 Results

4.1 The Resident F16 Team Mostly Withholds

The primary SAS delivers 78 correct, 48 wrong and withholds 34 under reported-answer scoring; MAS delivers 5 correct, 3 wrong and withholds 152 (Figure 1). The MAS-minus-SAS correct-delivery difference is -45.6 percentage




Figure 1: Study A: all six completed Ubuntu jobs, each on the same 160 questions. Segments show correct (teal), wrong (orange) and withheld (gray); labels are counts where space permits. Both scoring conventions are retained. Fewer MAS errors accompany substantially lower correct delivery.

points, with a report-cluster 95% interval $[-53.9, -36.6]$. Raw execution matching changes SAS correct delivery to 38 and wrong delivery to 88, while MAS remains at 5 and 3. Thus the direction is robust to these scores, but the magnitude is not interchangeable across them.

Reported-score transitions are SAS-correct to MAS-correct/wrong/withheld: 5/1/72; SAS-wrong: 0/2/46; SAS-withheld: 0/0/34. Thus 46 avoided wrong deliveries accompany 72 lost correct deliveries through withholding, plus one correct-to-wrong transition. SAS has higher correct delivery on 33 reports, ties on 17, and loses on none. This is specific to reported scoring: raw scoring has one MAS-only correct answer. Conditional precision is 78/126 versus 5/8 (61.9% versus 62.5%), at 78.8% versus 5.0% coverage; similar precision does not establish equivalent usefulness. The other report-cluster effects are reported wrong -28.1 pp $[-37.1, -20.1]$, raw correct -20.6 $[-28.3, -13.4]$, and raw wrong -53.1 $[-61.9, -44.1]$. Company clustering and alternative weighting preserve these directions (supplement).

Candidate analysis locates the primary failure. SAS produces 150 executable candidates, 84 reported-correct; review withholds six correct and 18 executable wrong candidates. MAS produces only ten executable candidates, five reported-correct; it delivers all five correct and three wrong, withholding two executable wrong candidates. Its other 150 program-stage outputs are INSUFFICIENT, although all 160 responses parse as JSON. The team is therefore mainly generation-limited, not a strong solver hidden behind an excessively conservative final gate.

All annotated evidence spans occur in 138/160 packets. Within that reference-dependent stratum, SAS delivers 74 correct answers and MAS five; MAS still has 128 insufficient/invalid outputs. This descriptive audit does not prove unique catalog expressibility or causal sufficiency of retrieval. It does show that missing annotated spans alone cannot explain the observed coverage collapse.

For example, AAPL/2003/page_24.pdf-1 supplies 290 and 92 in the selected sentence. SAS subtracts them to obtain the reference 198; MAS selects the sentence but emits INSUFFICIENT. Conversely, on PNC/2018/page_171.pdf-1 the team passes a source-cited but numerically wrong calculation. These traces illustrate separate generation and verification failures; they do not isolate model capacity as their cause. The grammar lacks direct aggregate operations, and MAS withholds all 56 cases whose reference programs have multiple steps. Full traces and reference-defined strata appear in the supplement.

Direct control yields SAS 50/66/44 and MAS 0/5/155 correct/wrong/withheld. Repair yields SAS 79/50/31 and MAS 5/3/152. Initial candidates match the no-repair primary across paired cases. SAS repair releases one additional reported-correct and two wrong answers; by raw execution it releases zero correct and three wrong. MAS attempts 152 repairs without improving final delivery. More stages do not resolve the observed generation shortfall.

The Ubuntu run repeats all 960 historical delivery flags and score objects. Its 668,817 memory samples across 16 attempts show zero process-swap bytes and a maximum RSS of 10.946 GB, below the 11.5 GB sampled ceiling. This is stronger resource evidence than the earlier swap-affected run, but not uninterrupted execution or a bound on unsampled peaks. Primary SAS/MAS sampled peaks are 10.075/10.946 GB. Summed primary inference time is 11.668 hours for SAS and 3.383 for MAS; the latter's speed accompanies pervasive insufficient answers. Restart overhead and aborted work are excluded.

Constraint ($n = 15$)	Execution	Reported
Neither	0	0
Operand shortlist only	0	0
Operation structure only	4	4
Structure and shortlist	10	7

Table 1: Enriched FinQA diagnostic, correct candidates. The last three rows use reference information unavailable at deployment. No deployment accuracy claim follows from these scores.

4.2 Evidence and Precision Do Not Resolve Generation

On 96 additional FinQA reports, an annotated correct program can execute from the original evidence/catalog on 82. Each matched 3B Q4 and Q8 condition misses 80 of those 82 and achieves only 2/96 official execution matches overall. The Q4/Q8 comparison has two gains and two losses, with a company-cluster difference interval about $[-4.3, +4.0]$ points. Increasing weight precision does not establish a general gain here; it is not evidence that precision never matters.

Wider lexical retrieval improves complete annotated-span coverage from 750/883 to 827/883 in a development screen. A 16-report generation pilot improves from 1 to 4 official matches, but a separate 21-report replication changes 2 to 1 (one gain, two losses). All three initial gains use only original spans. Expanding the catalog improves an enriched five-report diagnostic from 0 to 2, but changes 2/96 to 1/96 on the broader cohort. Retrieval coverage, catalog expressibility and generated accuracy are distinct outcomes.

The 15-report answer-key diagnostic shows where conditional potential remains (Table 1). Operand restriction alone leaves accuracy at zero despite reducing the median selectable IDs from 23 to two. Structure alone recovers four answers; structure plus the shortlist recovers ten official matches but seven reported matches. The remaining five official failures assign at least one source slot a different numerical value from the reference; three additional official-correct outputs mislabel a fractional result as percentage points. Because the scaffold supplies most of the calculation, this is not a learned planning result or an upper bound over all valid reasoning strategies.

4.3 The Evidence-Only Planner Fails Its Criterion

All four arms complete the 96-context cohort (Figure 2). Direct 7B delivers 19 correct, 76 wrong and withholds one; program 7B delivers 15, 80 and one. Current MAS delivers 6, 23 and 67; planner MAS delivers 10, 25 and 61. Planning gains four correct deliveries and loses none: $+4.2$ percentage points, paired context-bootstrap 95% interval $[+1.0, +8.3]$. However, only four pairs are discordant, giving exact $p = 0.125$. We do not treat the positive percentile interval as reliable evidence of a population gain. Wrong deliveries increase by two, so the prespecified practical criterion fails regardless of that interval.

Correct candidates decline from 26 to 25, with four gains and five losses. All four candidate gains are delivered. Two gains acquire a matching operator tree; the other two already had matching tree structure and improve numerical binding. Among 87 parseable reference derivations, operator-tree matches fall from 46 to 40 (three gains, nine losses). This diagnostic replaces numerical leaves with placeholders and sorts commutative arguments; it does not recognize all algebraic equivalences or verify source identities. Figure 3 reports uncertainty for these paired changes.

Connected shapes are usable on 57/96 contexts. The other 39 have operations outside the final dependency graph and fall back; all 39 saved drafts and verdicts reproduce the baseline. Passing structural validation does not guarantee a correct calculation. The fixed critic rejects 20 of 26 correct baseline candidates and 15 of 25 planner candidates. Its changed acceptance pattern improves correct delivery without a net generation gain and still accepts 25 wrong planned answers.

On the separate 28-context official-test cohort, both MAS arms deliver two correct, ten wrong and withhold 16; correct candidates decrease from five to three. This is a small negative directional check, not proof of equality. The 7B comparison stops after two contexts because of a 352,342,016-byte CPU compute-buffer allocation failure; a recovery attempt also fails. We retain the partial records but do not report a complete four-arm official-test comparison.

Planning also costs time: median resident request latency increases from 25.2 to 33.9 seconds; generated tokens increase from 6,672 to 9,863. Peak worker commit remains about 5.26 GB (Figure 4). Direct and program 7B medians are 34.3 and 46.8 seconds with approximately 5.44 GB peak commit, but include model loading and are not matched resident latency comparisons.

4.4 Stronger Baselines and Nontransferable Gains

The result is not that larger or direct models always fail to help. On 120 fresh TAT-QA contexts, direct 7B scores 29 versus 12 for direct 3B (22 gains, five losses; exact paired $p = 0.00151$). An earlier 40-context comparison is inconclusive at six versus five. On the shared 96-report FinQA cohort, fixed 7B direct output scores 35 versus 20 for cited programs under reported-answer matching (21 direct-only, six program-only; $p = 0.00592$). In contrast, a 72-context TAT-QA subset favors programs 19 versus 14 (14 program-only, nine direct-only; $p = 0.405$). Output-format effects depend on task, representation and scoring; no universal direct-answer advantage is supported.

Scoring sensitivity is substantial. FinQA's unmodified official execution score for those 7B programs is 1/96. A post-hoc declared-percent conversion recovers 18, yielding 19/96; the original score is retained. Three unsupported reported-reference labels remain in denominators. These observations do not license replacing the primary scorer with a favorable convention.

FinQA actor adaptation transfers to 72 other TAT-QA contexts with correct candidates increasing from three to eight (six gains, one loss; $p = 0.125$); the critic delivers six correct, ten wrong and withholds 56. On fixed FinQA candidates, an initially favorable trained-critic pilot does not reproduce zero wrong deliveries in a 21-report transfer: control delivers 1/5/15 and crossed critic 1/2/18. Earlier crossed-critic devel-




Figure 2: Primary held-out TAT-QA cohort. Left: all correct, wrong and withheld deliveries. Right: correct candidates before review versus correct final deliveries. Planning delivers more correct answers but generates fewer correct candidates and more wrong deliveries.




Figure 3: Planner-minus-MAS effects with archived 95% paired context-bootstrap intervals. Correct delivery has only four discordant pairs (exact $p = 0.125$). Wrong delivery is an adverse outcome; its observed increase fails the practical criterion. Tree agreement uses 87 parseable cases.

opment also fails its no-correct-loss adoption rule against the stronger original critic. These observations remain part of the negative sequence.

The clearest engineering improvement is cache configuration. On a fixed resident 21-report workload, disabling RAM prompt caching preserves every draft, verdict and delivery while reducing peak worker commit from approximately 6.101 to 5.264 GB and eliminating logged prompt-cache allocation failures. The default-cache completion involved allocation fallback near the cap. This change improves observed resource headroom, not reasoning accuracy, and does not prove absence of Windows paging.

5 Discussion and Limitations

The evidence supports a sequence of distinct constraints. In Study A, the selected F16 team generally does not attempt a useful calculation. In Study B, available reference-executable evidence can coexist with wrong candidate programs. Supplying reference structure exposes conditional potential, but predicting usable structure remains difficult, source assignment can still fail, and review can discard correct candidates or accept wrong ones. The planner's final delivery increase is therefore insufficient evidence of a generation improvement.

This is an empirical result about specific Qwen2.5 recipes, prompts, grammars and financial subsets. Parameter size and precision are confounded in Study A; the Windows planner changes draft allocation as well as adding a stage. Greedy single-seed experiments do not estimate training-seed or stochastic-decoding variance. Repeated development studies, enriched oracle diagnostics and reused cohorts cannot be pooled as independent confirmations. Project-held-out public data do not establish freedom from pretraining contamination; FinQA splits overlap at report level, and TAT-QA report clusters are unavailable. Sparse paired improvements and multiple exploratory comparisons limit inferential strength.

Resource claims are equally bounded. Windows job commit is not physical RAM feasibility; sampled RSS can miss peaks. Linux swap-disabled scope records and zero sampled process swap strengthen the Ubuntu evidence, but the run was interrupted and the SSD suffered filesystem errors. Seven unreadable analysis artifacts were reconstructed offline: all six replay hashes and all 40 recorded evidence hashes match, as does the regenerated summary; the regenerated text report has no original recorded hash. The original export tarball and one bootstrap log remain unavailable. Separately verified repository archives preserve the usable evidence. These qualifications preclude claims of uninterrupted deployment reliability.




Figure 4: Primary held-out resources. Left: resident request-time distributions (median, quartiles and 1.5-IQR whiskers; outliers omitted from display, retained in data). Right: observed peak worker commit and configured limit. Peaks are descriptive measurements, not physical-RAM feasibility bounds; cross-arm loading policies differ.

We have not evaluated frontier models, alternative families, a broad prompt search, trained planners, XBRL-authorized formulas, or all published verification baselines. We report numerical benchmark agreement rather than expert financial adjudication, calibration or operational safety. Full prompts may contain ambiguity, and correct numbers do not ensure correct provenance. The systems' error rates do not support autonomous financial decisions. The supplement retains historical positive, null and adverse findings, unsuccessful resource attempts and a machine-readable artifact census; no historical result is silently revised.

6 Conclusion

Within the evaluated resource limits, a resident F16 specialist team is not competitive with the larger quantized single-model recipe on correct delivery. Smaller quantized models also fail to generate correct programs despite reference-executable evidence. Answer-key structure and operand constraints demonstrate conditional diagnostic potential, but an evidence-only planner fails its practical criterion: it adds wrong deliveries, decreases correct candidates, costs more time, and shows no secondary-cohort delivery gain. The defensible contribution is the separation of evidence availability, program construction and selective delivery, with explicit numerical and resource validity limits. These results motivate better tests of planning and verification; they do not establish a universal failure of multiagent reasoning.

References

Cemri, M.; Pan, M. Z.; Yang, S.; Agrawal, L. A.; Chopra, B.; Tiwari, R.; Keutzer, K.; Parameswaran, A.; Klein, D.; Ramchandran, K.; Zaharia, M.; Gonzalez, J. E.; and Stoica, I. 2025. Why Do Multi-Agent LLM Systems Fail? arXiv:2503.13657.

Chen, H.; Tang, X.; Liu, Q.; Shi, W.; Li, S.; Lyu, F.; Luo, W.; Du, X.; and He, X. 2026. Fighting Numerical Hallucinations via Data-centric Compilation for Online Financial QA. arXiv:2605.31064.

Chen, W.; Ma, X.; Wang, X.; and Cohen, W. W. 2023. Program of Thoughts Prompting: Disentangling Computation from Reasoning for Numerical Reasoning Tasks. arXiv:2211.12588.

Chen, Z.; Chen, W.; Smiley, C.; Shah, S.; Borova, I.; Langdon, D.; Moussa, R.; Beane, M.; Huang, T.-H.; Routledge, B.; and Wang, W. Y. 2021. FinQA: A Dataset of Numerical Reasoning over Financial Data. In Moens, M.-F.; Huang, X.; Specia, L.; and Yih, S. W.-t., eds., *Proceedings of the 2021 Conference on Empirical Methods in Natural Language Processing*, 3697–3711. Online and Punta Cana, Dominican Republic: Association for Computational Linguistics.

Dettmers, T.; Pagnoni, A.; Holtzman, A.; and Zettlemoyer, L. 2023. QLoRA: Efficient Finetuning of Quantized LLMs. arXiv:2305.14314.

Du, Y.; Li, S.; Torralba, A.; Tenenbaum, J. B.; and Mordatch, I. 2024. Improving Factuality and Reasoning in Language Models through Multiagent Debate. In Salakhutdinov, R.; Kolter, Z.; Heller, K.; Weller, A.; Oliver, N.; Scarlett, J.; and Berkenkamp, F., eds., *Proceedings of the 41st International Conference on Machine Learning*, volume 235 of *Proceedings of Machine Learning Research*, 11733–11763. PMLR.

Gao, L.; Madaan, A.; Zhou, S.; Alon, U.; Liu, P.; Yang, Y.; Callan, J.; and Neubig, G. 2023. PAL: Program-aided Language Models. In Krause, A.; Brunskill, E.; Cho, K.; Engelhardt, B.; Sabato, S.; and Scarlett, J., eds., *Proceedings of the 40th International Conference on Machine Learning*, volume 202 of *Proceedings of Machine Learning Research*, 10764–10799. PMLR.

Geifman, Y.; and El-Yaniv, R. 2019. SelectiveNet: A Deep Neural Network with an Integrated Reject Option. In Chaudhuri, K.; and Salakhutdinov, R., eds., *Proceedings of the 36th*

International Conference on Machine Learning, volume 97 of *Proceedings of Machine Learning Research*, 2151–2159. PMLR.

Gou, Z.; Shao, Z.; Gong, Y.; Shen, Y.; Yang, Y.; Duan, N.; and Chen, W. 2024. CRITIC: Large Language Models Can Self-Correct with Tool-Interactive Critiquing. arXiv:2305.11738.

Hall, B.; Shome, S.; and Eiers, W. 2026. VeriFin: A Neurosymbolic Framework for Verifying LLM-Generated Financial Claims. arXiv:2608.10213.

Hu, E. J.; Shen, Y.; Wallis, P.; Allen-Zhu, Z.; Li, Y.; Wang, S.; Wang, L.; and Chen, W. 2021. LoRA: Low-Rank Adaptation of Large Language Models. arXiv:2106.09685.

Huang, J.; Chen, X.; Mishra, S.; Zheng, H. S.; Yu, A. W.; Song, X.; and Zhou, D. 2024. Large Language Models Cannot Self-Correct Reasoning Yet. arXiv:2310.01798.

Jenq, J.; and Shen, H. 2026. BudgetVerify: Budget-Tiered Verification for Financial QA. arXiv:2609.33052.

Liu, C.; Liu, Q.; Zhu, Z.; Fei, H.; and Mahanti, A. 2025. David vs. Goliath: Cost-Efficient Financial QA via Cascaded Multi-Agent Reasoning. In Christodoulopoulos, C.; Chakraborty, T.; Rose, C.; and Peng, V., eds., *Findings of the Association for Computational Linguistics: EMNLP 2025*, 4212–4229. Suzhou, China: Association for Computational Linguistics. ISBN 979-8-89176-335-7.

Madaan, A.; Tandon, N.; Gupta, P.; Hallinan, S.; Gao, L.; Wiegreffe, S.; Alon, U.; Dziri, N.; Prabhumoye, S.; Yang, Y.; Gupta, S.; Majumder, B. P.; Hermann, K.; Welleck, S.; Yazdanbakhsh, A.; and Clark, P. 2023. Self-Refine: Iterative Refinement with Self-Feedback. arXiv:2303.17651.

Qwen Team. 2024. Qwen2.5 Technical Report. arXiv:2412.15115v1.

Stuhlmann, L.; Argerich, M. F.; and Fürst, J. 2026. Bench360: Benchmarking Local LLM Inference from 360 Degrees. arXiv:2511.16682.

Tran, D.; and Kiela, D. 2026. Single-Agent LLMs Outperform Multi-Agent Systems on Multi-Hop Reasoning Under Equal Thinking Token Budgets. arXiv:2604.02460.

Wang, X.; Wei, J.; Schuurmans, D.; Le, Q.; Chi, E.; Narang, S.; Chowdhery, A.; and Zhou, D. 2023. Self-Consistency Improves Chain of Thought Reasoning in Language Models. arXiv:2203.11171.

Zhu, F.; Lei, W.; Huang, Y.; Wang, C.; Zhang, S.; Lv, J.; Feng, F.; and Chua, T.-S. 2021. TAT-QA: A Question Answering Benchmark on a Hybrid of Tabular and Textual Content in Finance. In Zong, C.; Xia, F.; Li, W.; and Navigli, R., eds., *Proceedings of the 59th Annual Meeting of the Association for Computational Linguistics and the 11th International Joint Conference on Natural Language Processing (Volume 1: Long Papers)*, 3277–3287. Online: Association for Computational Linguistics.