

Thirdprocess

Michael Pearson

8/14/2018

Remove the one-offs

now let's process the ones with multiple bigrams

```
blocky <- function(trap, tim, ful_tri) {
  a <- floor(nrow(tim)/100)
  b <- 101
  c <- a
  d <- 1
  full_tri <- data.table()
  for (j in 1:b)
  {
    mid_tri <- data.table()
    if(nrow(tim) - a >= c )
    {
      setkey(trixy,word1)
      for (i in d:a)
      {
        ##setkey(trixy,bigrams)
        tardis <- trixy[as.character(aggy$word1[i])]
        tardis$prob <- tardis$bi_gram_ns_ns/aggy$sum[i]
        mid_tri <- rbind(mid_tri, tardis)
        ##trixy <- trixy[bigrams != aggy$bigrams[i],]
        ##print(paste("i is ",i))
        ##print(paste("number of rows in trixy is ",nrow(trixy)))
      }
      d <- a + 1
      a <- a + c
    }
    else {
      a <- nrow(tim)
      d <- 100*floor(nrow(tim)/100) + 1
      for (i in d:a)
      {
        tardis <- trixy[word1 == aggy$word1[i],]
        tardis$prob <- tardis$bi_gram_ns_ns/aggy$sum[i]
        mid_tri <- rbind(mid_tri, tardis)
      }
      full_tri <- rbind(full_tri, mid_tri)
    }
  }
  return(full_tri)
}

combi_bi_ns_ns <- read.csv("/Users/mutecypher/Documents/Coursera/Capstone Project/20sample/bi_gram_ns_n
combi_bi_ns_ns <- data.table(combi_bi_ns_ns)
trixy <- combi_bi_ns_ns[combi_bi_ns_ns$bi_gram_ns_ns >= 6,]
```

```
##trixy <- data.table(combi_bi_ns_ns)
aggy <- trixy[,.(sum = sum(bi_gram_ns_ns)), by = word1]
aggy <- aggy[aggy$sum >= 3]
aggy <- data.table(aggy)
blah <- blocky(trixy, aggy, full_tri)
write.csv(blah,file = "/Users/mutecypher/Documents/Coursera/Capstone Project/20sample/nosingles_bi_ns_ns.csv")
rm(trixy)
rm(aggy)
rm(combi_bi_ns_ns)
rm(blah)
```

Now the Trigrams

```
blocky <- function(trap, tim, ful_tri) {
a <- floor(nrow(tim)/1000)
b <- 1001
c <- a
d <- 1
full_tri <- data.table()
for (j in 1:b)
{
mid_tri <- data.table()
if(nrow(tim) - a >= c )
{
setkey(trixy,bigrams)
for (i in d:a)
{
tardis <- trixy[as.character(aggy$bigrams[i])]
tardis$prob <- tardis$tri_gram_ns_ns/aggy$sum[i]
mid_tri <- rbind(mid_tri, tardis)
}

d <- a + 1
a <- a + c
}
else {
a <- nrow(tim)
d <- 100*floor(nrow(tim)/1000) + 1
for (i in d:a)
{
tardis <- trixy[bigrams == aggy$bigrams[i],]
tardis$prob <- tardis$tri_gram_ns_ns/aggy$sum[i]
mid_tri <- rbind(mid_tri, tardis)
##trixy <- trixy[bigrams != aggy$bigrams[i],]
}
}
full_tri <- rbind(full_tri, mid_tri)
}
return(full_tri)
}

combi_tri_ns_ns <- read.csv("/Users/mutecypher/Documents/Coursera/Capstone Project/20sample/combi_tri_ns_ns.csv")
combi_tri_ns_ns <- data.table(combi_tri_ns_ns)
trixy <- combi_tri_ns_ns[combi_tri_ns_ns$tri_gram_ns_ns >= 4,]
```

```

##trixy <- data.table(combi_tri_ns_ns)
aggy <- trixy[,.(sum = sum(tri_gram_ns_ns)), by = bigrams]
aggy <- aggy[aggy$sum >= 3]
aggy <- data.table(aggy)
blah <- blocky(trixy, aggy, full_tri)
write.csv(blah,file = "/Users/mutecypher/Documents/Coursera/Capstone Project/20sample/nosingles_tri_ns_
rm(trixy)
rm(aggy)
rm(combi_tri_ns_ns)
rm(blah)

```

should run first

```

blocky <- function(trap, tim, ful_tri) {
a <- floor(nrow(tim)/100)
b <- 101
c <- a
d <- 1
full_tri <- data.table()
for (j in 1:b)
{
mid_tri <- data.table()
if(nrow(tim) - a >= c )
{
setkey(trixy,trigrams)
for (i in d:a)
{
tardis <- trixy[as.character(aggy$trigrams[i])]
tardis$prob <- tardis$quad_gram_ns_ns/aggy$sum[i]
mid_tri <- rbind(mid_tri, tardis)
}

d <- a + 1
a <- a + c
}
else {
a <- nrow(tim)
d <- 100*floor(nrow(tim)/100) + 1
for (i in d:a)
{
tardis <- trixy[as.character(aggy$trigrams[i])]
tardis$prob <- tardis$tri_gram_ns_ns/aggy$sum[i]
mid_tri <- rbind(mid_tri, tardis)
}
}
full_tri <- rbind(full_tri, mid_tri)
}
return(full_tri)
}

combi_quad_ns_ns <- read.csv("/Users/mutecypher/Documents/Coursera/Capstone Project/20sample/combi_quad_
combi_quad_ns_ns <- data.table(combi_quad_ns_ns)
trixy <- combi_quad_ns_ns[combi_quad_ns_ns$quad_gram_ns_ns >= 2,]
##trixy <- data.table(combi_quad_ns_ns)

```

```

aggy <- trixy[,.(sum = sum(quad_gram_ns_ns)), by = trigrams]
aggy <- aggy[aggy$sum >= 6]
aggy <- data.table(aggy)
blah <- blocky(trixy, aggy, full_tri)
write.csv(blah,file = "/Users/mutecypher/Documents/Coursera/Capstone Project/20sample/nosingles_quad_ns,
rm(trixy)
rm(aggy)
rm(combi_quad_ns_ns)
rm(blah)

```

Now the Quin-grams

```

blocky <- function(trap, tim, ful_tri) {
a <- floor(nrow(tim)/100)
b <- 101
c <- a
d <- 1
full_tri <- data.table()
for (j in 1:b)
{
mid_tri <- data.table()
if(nrow(tim) - a >= c )
{
setkey(trixy,quadgrams)
for (i in d:a)
{
tardis <- trixy[as.character(aggy$quadgrams[i])]
tardis$prob <- tardis$quin_gram_ns_ns/aggy$sum[i]
mid_tri <- rbind(mid_tri, tardis)
}

d <- a + 1
a <- a + c
}
else {
a <- nrow(tim)
d <- d <- 100*floor(nrow(tim)/100) + 1
for (i in d:a)
{
tardis <- trixy[as.character(aggy$trigrams[i])]
tardis$prob <- tardis$quad_gram_ns_ns/aggy$sum[i]
mid_tri <- rbind(mid_tri, tardis)
}
}
full_tri <- rbind(full_tri, mid_tri)
}
return(full_tri)
}

combi_quin_ns_ns <- read.csv("/Users/mutecypher/Documents/Coursera/Capstone Project/20sample/combi_quin,
combi_quin_ns_ns <- data.table(combi_quin_ns_ns)
trixy <- combi_quin_ns_ns[combi_quin_ns_ns$quin_gram_ns_ns >= 1,]
##trixy <- data.table(combi_quin_ns_ns)
aggy <- trixy[,.(sum = sum(quin_gram_ns_ns)), by = quadgrams]
aggy <- aggy[aggy$sum >= 3]
aggy <- data.table(aggy)

```

```
blah <- blocky(trixy, aggy, full_tri)
write.csv(blah, file = "/Users/mutecypher/Documents/Coursera/Capstone Project/20sample/nosingles_quin_ns.
rm(trixy)
rm(aggy)
rm(combi_quin_ns_ns)
rm(blah)
```