

Mesh Networking



Sebastian Büttrich, wire.less.dk
edit: February 2008 @ ICTP



<http://creativecommons.org/licenses/by-nc-sa/3.0/>

Agenda

- **What is a mesh?**
- **Why mesh?**
- **How to mesh? Routing protocols**
- **Who can mesh? Hardware**
- **Planning and implementing a mesh network**
- **Mesh case stories**
- **Labs**

Agenda

Mesh lab


- **Lab: Flashing a wireless router**
- **Lab: Configuring a Freifunk based mesh network**
plus optionally
- **Lab: Running olsrd on a PC/laptop**
- **Lab: Running batmand on a PC/laptop**
- **Lab: Building a Meraki mesh**
- **Lab: Mesh with Metrix boxes**

What is a mesh?

- A mesh network is a network that employs one of two connection arrangements:
full mesh topology or partial mesh topology.
- In the **full mesh topology**, each node is connected **directly to each of the others.**
In the **partial mesh topology**, nodes are **connected to only some**, not all, of the other nodes."


What is a mesh?

A full mesh



What is a mesh?

Full and partial meshes




What is a mesh?

A common understanding

- A network that handles many-to-many connections and is capable of dynamically updating and optimizing these connections
- In a wireless mesh network, all wireless cards are in *ad-hoc* mode (not *infrastructure*)
- Note: A mesh does not have to be (very) dynamic!
- Often, you will meet the term *Mobile ad-hoc network (MANET)*


What is a mesh?

Example of a community mesh



Why mesh?

- Meshing allows for
 - robust
 - dynamic
 - self healing
 - long distance
- wireless networks






Why mesh?

Mesh networking ...

- Makes good use of community resources through sharing
- Lends itself nicely to favourable social models: sharing models, distributed responsibility models, where *personal interest = shared interest*
- Is often called *self-configuring and easy to set up*

well ... that may be argued :) ... we will see in the Lab

Why mesh?



How to mesh?

- Routing protocols are the engines or brains of mesh networking
- Routing protocols take care of ...

Node discovery

Border discovery

Link metrics

Route calculation

IP address management

Uplink/backhaul management

How to mesh?

Routing protocols

- Proactive:
OLSR (Optimized Link State Protocol)
B.A.T.M.A.N. (Better Approach to Mobile Ad-Hoc Networking)
- Reactive:
AODV (Ad-hoc on Demand Distance Vector)
SrcRR (MIT Roofnet)
- Hybrid:
HSLS (Hazy Sighted Link State Routing, CuWin)
- These are just some of the most relevant protocols in *our* context ... there are many more!

Who can mesh?

- Any computing device with the necessary CPU power and wireless interface can take part in a mesh network
- For example:

Desktop or laptop PCs

Dedicated mesh hardware, e.g. Fonera, Meraki, Meshnode a.o.

Off-the-shelf, inexpensive wireless routers, reconfigured

Who can mesh?

Firmware for Wireless routers

- **The GPL firmware of the original Linksys WRT54 has been improved and forked into many types of firmware,
e.g. DD-WRT, EWRT, OpenWRT/Freifunk, ..**
- **Examples of Hardware suitable for OpenWRT and Freifunk Firmware:**

Linksys WRT54G(L)

Asus WL500G

Buffalo WHR-G54S

Who can mesh?

The Linksys WRT54G

- **Pay attention to Hardware revisions if using OpenWRT/Freifunk on Linksys!**

Tested versions:

Linksys WRT54G-v1.x|2.0|2.2|3.0|3.1|4.0

NOT 5.0 and up

WRT54GL-v1.0|1.1

<http://wiki.openwrt.org/OpenWrtDocs/Hardware/Linksys/WRT54G>

- **Price: circa EUR 60**

Who can mesh?


Fonera & Meraki



Planning a mesh

- **Planning a mesh is in equal parts a technical and an organizational/social process**
- **Questions of Implementation / Support / Maintenance / Ownership need to be carefully considered**
- **Distributed ownership models benefit from social gatherings (e.g. Organisation, device configuration, antenna soldering, etc)**
- **The fact alone that IP distribution via DHCP is missing in mesh networks demands focus on planning and communication**

Planning a mesh IP planning



Planning a mesh

Planning helps

APPENDIX G: Planning Sheet	
Device Details	Model number
	Router serial number
	MAC address

Planning a mesh

Planning helps

APPENDIX G: Planning Sheet	
Device Details	Model number
	Router serial number
	MAC address

Planning a mesh

Planning helps

APPENDIX G: Planning Sheet	
Device Details	Model number
	Router serial number
	MAC address

Planning a mesh

Planning helps

APPENDIX G: Planning Sheet	
Device Details	Model number
	Router serial number
	MAC address

Planning a mesh

Planning helps

APPENDIX G: Planning Sheet	
Device Details	Model number
	Router serial number
	MAC address

Planning a mesh

Planning helps

APPENDIX G: Planning Sheet	
Device Details	Model number
	Router serial number
	MAC address

Planning a mesh

Planning helps

APPENDIX G: Planning Sheet	
Device Details	Model number
	Router serial number
	MAC address

Planning a mesh

Planning helps

Device Details	
Model number	
Router serial number	
MAC address	

Planning a mesh

Planning helps

APPENDIX G: Planning Sheet	
Device Details	Model number
	Router serial number
	MAC address

Planning a mesh

Planning helps

APPENDIX G: Planning Sheet	
Device Details	Model number
	Router serial number
	MAC address

Planning a mesh

Planning helps

APPENDIX G: Planning Sheet	
Device Details	Model number
	Router serial number
	MAC address

Planning a mesh

Planning helps

APPENDIX G: Planning Sheet	
Device Details	Model number
	Router serial number
	MAC address

Planning a mesh

Planning helps

APPENDIX G: Planning Sheet	
Device Details	Model number
	Router serial number
	MAC address

Mesh cases


The Freifunk movement

- Community network started in Berlin/Germany, to fill a gap in broadband (DSL/fiber) access
- Home of the Freifunk Firmware
- Number of Nodes: 500+ Berlin, many more with several 100s




Mesh cases

The Freifunk movement



Mesh cases

CuWin / USA



Mesh cases

Dharamsala / India

- Using Linksys WRT54G with OpenWRT firmware
- Using OLSR with ETX
- Connecting non-profit organizations
- Developed by
Dharamsala Information Technology Group / TibTec



Mesh cases **Peebles Valley,** **Mpumalanga, South Africa**

- Meraka Institute, CSIR Pretoria
- Using FreifunkFirmware
- < 10 nodes right now, but growing
- First node was the Aids care training and support (ACTS) clinic



Further Reading

Mesh networking URLs


- <http://OpenWRT.org> OpenWRT Firmware
- <http://freifunk.net> Freifunk
- http://wirelessafrika.meraka.org.za/wiki/index.php/DIY_Mesh_Guide
- <https://www.open-mesh.net/batman> B.A.T.M.A.N.
- <http://drupal.airjaldi.com/> Dharamsala mesh
- <http://wikipedia.org> Many articles

Further Reading

Mesh networking Books

- Corinna “Elektra” Aichele:
Mesh
Open Source Press 2007

available in english
August 2008



Lab: Freifunk Firmware on Linksys WRT54G

Lab: Freifunk Firmware on Linksys WRT54G Flashing a WRT54G

- Find out exactly what model and hardware revision you have
- Find the right firmware accordingly and verify that it will run
- Find out the device's default IP, e.g. 192.168.1.1 for Linksys WRT54GL
- Set your own IP by `> ifconfig eth1 192.168.1.99 up` or get a DHCP lease
- Connect to the device's original web interface (see: Access Point configuration) and find the "Firmware Update" button
- Using the Update Button, upload the firmware file, e.g. "openwrt-g-freifunk-x.y.z-en.bin" for a Freifunk Firmware
- NOW: REMEMBER TO WAIT! DO NOT PRESS CONTINUE WHEN IT SHOWS!!! DONT!!! WAIT UNTIL THE LEDS STOP BLINKING! TYPICALLY 4-6 MINUTES!
- MAKE SURE YOU HAVE STABLE POWER WHILE DOING THIS!

Lab: Freifunk Firmware on Linksys WRT54G

Debricking a WRT54G

- power down the WRT54GL
- Example of a tftp transmission:
on a linux command line, do
`[root@samsarix /]# ifconfig eth1 192.168.1.99 up`
`[root@samsarix /]# tftp -v -m binary 192.168.1.1`
mode set to octet
Connected to 192.168.1.1 (192.168.1.1), port 69
`tftp> put openwrt-g-freifunk-1.6.25-en.bin`
<NOW POWER UP THE WRT54GL! and if you are lucky... it will say>
putting openwrt-g-freifunk-1.6.25-en.bin to 192.168.1.1:openwrt-g-freifunk-1.6.25-en.bin [octet]
Sent 1303552 bytes in 7.9 seconds [1326539 bit/s]
`tftp>`
- If debricking via tftp fails, you will have to open the device and do some pin magic – read more here:

http://www.notsecure.us/debrick_wrt54g_without_void_warrenty.html

[http://www.ranvik.net/prosjekter-](http://www.ranvik.net/prosjekter-privat/jtag_for_wrt54g_og_wrt54gs/HairyDairyMaid_WRT54G_v22.pdf)

[privat/jtag_for_wrt54g_og_wrt54gs/HairyDairyMaid_WRT54G_v22.pdf](http://www.ranvik.net/prosjekter-privat/jtag_for_wrt54g_og_wrt54gs/HairyDairyMaid_WRT54G_v22.pdf)

<http://www.freewebs.com/wrt54grevival/wrt54grevial.htm.html>

Lab: Freifunk Firmware on Linksys WRT54G

Flashing step-by-step



Lab: Freifunk Firmware on Linksys WRT54G

Flashing step-by-step

Basic Setup - Mozilla Firefox

File Edit View History Bookmarks Tools Help

http://192.168.1.1/

BBC News BBC News Africa BBC News Europe SPIEGEL

LINKSYS
A Division of Cisco Systems, Inc.

Firmware Version: v4.30.7

Wireless-G Broadband Router WRT54GL

Setup

Setup Wireless Security Access Restrictions Applications & Gaming Administration Status

Basic Setup | DDNS | MAC Address Clone | Advanced Routing

Internet Setup

Internet Connection Type: Automatic Configuration - DHCP

Optional Settings (required by some ISPs)

Router Name: WRT54GL

Host Name:

Domain Name:

MTU: Auto

Size: 1500

Network Setup

Router IP

Local IP Address: 192 . 168 . 1 . 1

Subnet Mask: 255.255.255.0

Automatic Configuration - DHCP
: This setting is most commonly used by Cable operators.

Host Name : Enter the host name provided by your ISP.

Domain Name : Enter the domain name provided by your ISP.
More...

Local IP Address :

Done

Lab: Freifunk Firmware on Linksys WRT54G

Flashing step-by-step

Management - Mozilla Firefox

File Edit View History Bookmarks Tools Help

http://192.168.1.1/Management.asp

BBC News BBC News Africa BBC News Europe SPIEGEL

LINKSYS
A Division of Cisco Systems, Inc.

Firmware Version: v4.30.7

Wireless-G Broadband Router WRT54GL

Administration Setup Wireless Security Access Restrictions Applications & Gaming Administration Status

Management Log Diagnostics Factory Defaults Firmware Upgrade Config Management

Router Password

Local Router Access

Router Password:
Re-enter to confirm:

Web Access

Access Server: ☒ HTTP ☐ HTTPS
Wireless Access Web: ☒ Enable ☐ Disable

Remote Router Access

Remote Management: ☐ Enable ☒ Disable
Management Port: 8080
Use https: ☐


Local Router Access :
You can change the Router's password from here. Enter a new Router password and then type it again in the Re-enter to confirm field to confirm.

Web Access : Allows you to configure access options to the router's web utility.
More...

Remote Router Access : Allows you to...


Done

Lab: Freifunk Firmware on Linksys WRT54G Flashing step-by-step




Lab: Freifunk Firmware on Linksys WRT54G

Flashing step-by-step




Lab: Freifunk Firmware on Linksys WRT54G

Flashing step-by-step



Lab: Freifunk Firmware on Linksys WRT54G

Flashing step-by-step



Lab: Freifunk Firmware on Linksys WRT54G

configuring step-by-step

[Home](#) | [Admin](#)

freifunk.firmware

v1.6.25

Admin

Password

Contact info

System

OLSR

Wireless

LAN

WAN

Software 1

Software 2

Firmware

Restart

Admin: Password

New Password:

Repeat Password:

Apply

Cancel

Please note: The OLSR wireless network is normally not encrypted. Therefore, the password is transmitted as clear text for every page access. For security reasons, the admin pages should be viewed over wired network links only.

Tip: Start a secured connection with `ssh -L 8080:localhost:80 root@[wrt-ip]` (Linux) or `C:\Program Files\Putty\PuTTY -L 8080:localhost:80 root@[wrt-ip]` (Windows). Now browse to <http://localhost:8080/>.

→

←

Changed: 27.8.2007

Top of page

Lab: Freifunk Firmware on Linksys WRT54G

configuring step-by-step

[Home](#) | [Admin](#)

freifunk.firmware

v1.6.25

Admin

Password

Contact info

System

OLSR

Wireless

LAN

WAN

Software 1

Software 2

Firmware

Restart

Admin: Contact info

Nickname:

seb

Name:

sebastian

Email:

s@less.dk

Phone:

+45 31 79 78 97

Location:

copenhagen

URL Net Homepage:

less.dk

Notes:

Apply

Cancel

Tip: The settings on this page are visible for visitors on the [Contact](#) page.

Changed: 17.10.2007

Top of page

Lab: Freifunk Firmware on Linksys WRT54G

configuring step-by-step

[Home](#) | [Admin](#)

freifunk.firmware

v1.6.25

Admin

Password

Contact info

System

OLSR

Wireless

LAN

WAN

Software 1

Software 2

Firmware

Restart

Admin: System

Host Name:

GPS Position:

Domain:

DNS Server:

Use mini_fo:☒ Enable ☐ Disable

IPK Source:

Network start messages: ☒ Enable ☐ Disable

Timezone:

Country:

Tip: To ensure a convenient network access, you should enter the **Host Name** (a single name without dots) and the internal **Domain** (multiple names separated by dots).
Example: If you set **Host Name** to "mywrt" and **Domain** to "mynet.freifunk.net", it should be possible to call up the pages of this device with <http://mywrt.mynet.freifunk.net/> as well as with <http://mywrt.mynet.freifunk.net/>

Lab: Freifunk Firmware on Linksys WRT54G

configuring step-by-step

[Home](#) | [Admin](#)

freifunk.firmware

v1.6.25

[Admin](#)
[Password](#)
[Contact info](#)
[System](#)
[OLSR](#)
[Wireless](#)
[LAN](#)
[WAN](#)
[Software 1](#)
[Software 2](#)
[Firmware](#)
[Restart](#)

Admin: OLSR

OLSR Filter:

DMZ Redirect:

OLSR Services:

HNA4:

IP4 Broadcast:

OLSR Speed:

Willingness:

QOS Protocol (ETX): ☒ Enable ☐ Disable

OLSR LQ-Multiplier:

Hysteresis: ☐ Enable ☒ Disable

Hysteresis Scaling:

High Threshold:

Low Threshold:

Policy Routing: ☐ Enable ☒ Disable

PING Addresses:

Nameservice: ☒ Enable ☐ Disable

Arp Refresh: ☒ Enable ☐ Disable

Httpinfo: ☒ Enable ☐ Disable

OLSR Traffic Shaping: ☒ Enable ☐ Disable

Fisheye Routing: ☒ Enable ☐ Disable

Optimized Dijkstra: ☒ Enable ☐ Disable

Apply

Cancel

Tip1: The IP Address and the Netmask settings on the [Wireless](#) page determines the ip address range used for OLSR. It is possible to configure an additional IP address out of the OLSR range on the [LAN](#) and/or [WAN](#) page. In this case the OLSR signaling is activated for the respective interface and the firewall configuration for the interface is deactivated. It is best to use a "narrower" netmask on the additional OLSR-IPs. This will ensure connectivity from

Lab: Freifunk Firmware on Linksys WRT54G

configuring step-by-step

Home | Admin

freifunk.firmware

v1.6.25

Admin

Password

Contact info

System

OLSR

Wireless

LAN

WAN

Software 1

Software 2

Firmware

Restart

Admin: Wireless

WLAN Protocol:	Static
WLAN-IP Address:	10.0.0.9
WLAN Netmask:	255.255.255.0
WLAN Default Route:	10.0.0.1
WLAN Mode:	Ad Hoc (Peer to Peer)
ESSID:	mesh
BSSID:	02:CA:EE:EE:BA:BE
Channel:	1
Card Type:	<input type="radio"/> 802.11a <input checked="" type="radio"/> 802.11b/g
RX Antenna:	<input checked="" type="radio"/> Auto <input type="radio"/> Antenna A <input type="radio"/> Antenna B
TX Antenna:	<input checked="" type="radio"/> Auto <input type="radio"/> Antenna A <input type="radio"/> Antenna B
TX Power:	Regulatory Limit: 20 dBm = 100 mW Cable/Plug Loss: 3 dB Antenna Gain: 8.5 dBi Result: 58 qdBm = 28 mW <<<
Distance (Meter):	
Radio Mode:	Mixed B/G



Lab: Freifunk Firmware on Linksys WRT54G configuring step-by-step

[Home](#) | [Admin](#)

v1.6.25

Admin

Password

Contact info

System

OLSR

Wireless

LAN

WAN

Software 1

Software 2

Firmware

Restart

Admin: Firmware

Writing the /tmp/WRT54GL_4.30.7_ETSI_code.bin firmware file to flash memory. Please wait...

10/10

ok

Lab: Configuring a Freifunk Mesh

- **Using Freifunk Firmware on Linksys WRT54G or similar**
- **Prerequisites:**
Knowing how to flash and debrick
General IP networking basics, Network design

Lab: Configuring a Freifunk Mesh Mesh planning

- **Planning is about people! Consider the social dynamics, ownership, support, ...**
- **Map / Site Survey**
- **Select network topology**
- **Channel allocation (mesh, backbone, local hotspots)**
- **IP address allocation**
- **Draw the network diagram**

Lab: Configuring a Freifunk Mesh Mesh planning

- Our scenario:

6 villages (or houses / households)

Managed by the people themselves! That means:
By you!

Lab: Configuring a Freifunk Mesh Guide

Meraka Institute Mesh Guide APPENDIX G: Planning Sheet

- For the planning for each device:
e.g.
Meraka Mesh Guide Form

Device Details	Model number																			
	Router serial number																			
	MAC address																			
Download appropriate software	Freifunk firmware version																			
	DD-WRT firmware version																			
Node type	Gateway node																			X
	Backbone mesh node																			X
	Mesh cluster node																			X
	Wireless access point																			X
System settings	Host Name																			
Wireless settings	WLAN-IP address					.			.			.								
	WLAN netmask					.			.			.								
	ESSID																			
	BSSID																			
	Channel number (1,6,11)																			
LAN settings	LAN IP					.			.			.								
	LAN netmask					.			.			.								
OLSR	HNA4					.			.			.				0	/	2	4	
WAN Settings	WAN IP					.			.			.								
	WAN netmask					.			.			.								
Setup – Basic Setup	AP LAN IP address					.			.			.								
	Subnet mask					.			.			.								
	DHCP Server IP address					.			.			.								
Wireless – Basic Settings	SSID																			
Device history																				
Date (DD/MM/YYYY)	Description																			
/ /	Device build date (firmware upgrade, configuration, assembly)																			
/ /	Device installation date																			
	Location installed																			

Lab: Configuring a Freifunk Mesh Configuring: System

Home | Admin

freifunk.firmware

v1.4.5

Admin

Password

Contact info

System

OLSR

Wireless

LAN

WAN

Publish

Software 1

Software 2

Firmware

Restart

Admin: System

Host Name:	<input type="text" value="Ajay_Home"/>
Domain:	<input type="text"/>
DNS Server:	<input type="text"/>
Use mini_fo:	<input checked="" type="radio"/> Enable <input type="radio"/> Disable
IPK Source:	<input type="text"/>
Network start messages:	<input checked="" type="radio"/> Enable <input type="radio"/> Disable
Timezone:	<input type="text" value="MET-1MEST-2,M3.3.0,M10.5.0"/>
Country:	<input type="text" value="ZA - SOUTH AFRICA"/>
<input type="button" value="Apply"/> <input type="button" value="Cancel"/>	

Tip: To ensure a convenient network access, you should enter the **Host Name** (a single name without dots) and the internal **Domain** (multiple names separated by dots). Example: If you set **Host Name** to "mywrt" and **Domain** to "mynet.freifunk.net", it should be possible to call up the pages of this device with <http://mywrt.mynet.freifunk.net/> as well as with <http://mywrt/>.

Changed: 30.11.2006

Top of page

Lab: Configuring a Freifunk Mesh Configuring: System

- **Click Admin > System**
- **Host Name**
- **Select Country**
- **Restart**

Lab: Configuring a Freifunk Wireless

Home | Admin

freifunk.firmware

v1.4.5

Admin Wireless

Wireless

WLAN Protocol: Static

WLAN-IP Address: 10.1.1.4

WLAN Netmask: 255.255.255.0

WLAN Default Route:

WLAN Mode: Ad Hoc (Peer to Peer)

ESSID: ptamesh

BSSID: 02:02:6f:34:21:a0

Channel: 6

Card Type: ☐ 802.11a ☒ 802.11b/g

RX Antenna: ☒ Auto ☐ Antenna A ☐ Antenna B

TX Antenna: ☒ Auto ☐ Antenna A ☐ Antenna B

TX Power:

Distance (Meter):

Radio Mode: Mixed B/G

Broadcast (E)SSID: ☒ Enable ☐ Disable

Basic Rate: Default

Transmission Rate: Auto

CTS Protection Mode: Disable

Frame Burst: Disable

Beacon Interval: 100

DTIM Interval: 1

Fragmentation Threshold: 2346

RTS Threshold: 2347

MTU Value:

Apply Cancel

Tip: For most devices, the setting **Antenna A** activates the left antenna (seen from the front).

Changed: 18.11.2006

Top of page

Lab: Configuring a Freifunk Mesh

Configuring: Wireless

- **WLAN Protocol: Static**
- **WLAN IP address: As assigned in project – must be unique!**
- **WLAN Netmask: As assigned in project**
- **WLAN Default Route:**
- **WLAN Mode: Ad-hoc**
- **ESSID: e.g. “school08” - check spelling!**
- **BSSID: e.g. 02:CA:FF:EE:BA:BE or anything you can remember and agree on! Must be the same for all nodes! Lock the BSSID! Beware of cell splitting!**
- **Channel - Make sure you all use the same!**
- **Antenna mode: Auto**
- **Apply and restart**

Lab: Configuring a Freifunk Mesh

Configuring: LAN

Home | Admin

freifunk.firmware

v1.4.5

Admin

Password

Contact info

System

OLSR

Wireless

LAN

WAN

Publish

Software 1

Software 2

Firmware

Restart

Admin: LAN

LAN Protocol:	Static
LAN IP:	10.2.4.1
LAN Netmask:	255.255.255.0
LAN Default Route:	
Static Routes:	
Disable NAT:	<input checked="" type="checkbox"/>
Disable Firewall:	<input checked="" type="checkbox"/>
DHCP Start IP:	192.168.1.100
DHCP Number of Users:	50 (DHCP off with "0")
DHCP Lease Time:	seconds
<input type="button" value="Apply"/> <input type="button" value="Cancel"/>	

Tip: These settings influence the configuration, which is sent to wired clients via DHCP. To ensure a convenient network access, you should enter the **Host Name** and the internal **Domain** (-> [System](#)).

Changed: 2.10.2006

 Top of page

Lab: Configuring a Freifunk Mesh

Configuring: WAN

[Home](#) | [Admin](#)

freifunk.firmware

v1.4.5



Admin

Password

Contact info

System

OLSR

Wireless

LAN

WAN

Publish

Software 1

Software 2

Firmware

Restart

Admin: WAN

WAN Protocol:	<input type="text" value="Static"/>
WAN IP:	<input type="text" value="10.4.1.1"/>
WAN Netmask:	<input type="text" value="255.255.255.0"/>
WAN Default Route:	<input type="text"/>
RJ45 Connectors:	<input type="text" value="45"/>
Permit SSH:	<input type="checkbox"/>
Permit HTTP:	<input type="checkbox"/>
Permit Ping:	<input type="checkbox"/>
<input type="button" value="Apply"/> <input type="button" value="Cancel"/>	

Changed: 18.11.2006

[Top of page](#)

Lab: Configuring a Freifunk Mesh OLSR

OLSR Filter:	<input type="text"/>
DMZ Redirect:	<input type="text"/>
OLSR Services:	<input type="text"/>
HNA4:	<input type="text" value="10.2.4.0/24"/>
IP4 Broadcast:	<input type="text"/>
OLSR Speed:	<input type="text"/>
Willingness:	<input type="text"/>
QOS Protocol (ETX):	<input checked="" type="radio"/> Enable <input type="radio"/> Disable
OLSR LQ-Multiplier:	<input type="text"/>
Hysteresis:	<input type="radio"/> Enable <input checked="" type="radio"/> Disable
Hysteresis Scaling:	<input type="text"/>
High Threshold:	<input type="text"/>
Low Threshold:	<input type="text"/>
DynGW:	<input checked="" type="radio"/> Enable <input type="radio"/> Disable
PING Addresses:	<input type="text"/>
Nameservice:	<input checked="" type="radio"/> Enable <input type="radio"/> Disable
Httpinfo:	<input checked="" type="radio"/> Enable <input type="radio"/> Disable
Mcast Forward:	<input checked="" type="radio"/> Enable <input type="radio"/> Disable
OLSR Traffic Shaping:	<input checked="" type="radio"/> Enable <input type="radio"/> Disable
Fisheye Routing:	<input checked="" type="radio"/> Enable <input type="radio"/> Disable
Optimized Dijkstra:	<input checked="" type="radio"/> Enable <input type="radio"/> Disable
<input type="button" value="Apply"/> <input type="button" value="Cancel"/>	

Lab: Configuring a Freifunk Mesh

Configuring: OLSR

- **OLSR Filter:** excludes nodes where needed, e.g. wired neighbours
- **DMZ Redirect:** make local PCs visible to outside
- **OLSR DHCP:** make node available as hotspot for non-mesh clients
- **HNA4:** Host Network Announce for your local LAN
- e.g. 10.5.70/24;192.168.42.0/24
- **Broadcast IP:** leave at default
- **OLSR Speed:** Hello speed .. 2 secs for small, 5 secs for bigger networks
- **Willingness:** 0-7 (leave blank for intelligent default)
- **ETX:** enable!
- **OLSR-LQ Multiplier:** manipulate your own ETX value
- **Hysteresis:** not needed if ETX - ignore! RFC 3626 legacy ..

Lab: Configuring a Freifunk Mesh

Configuring: OLSR contnd

- **DynGW: to announce internet gateway! Only announce if you have one!**
- **Ping Addresses:**
- **Nameservice**
- **Httpinfo: nice to have**
- **Mcast forward: for multimedia streaming - experimental**
- **OLSR Traffic Shaping: favors OLSR protocol packets! activate**
- **Fishey Routing: yes**
- **Optimized Dijkstra: enable for larger networks**

Lab: Running olsrd / batmand on a laptop

- Olsr demons are available for Linux, Mac OS X, BSD, Windows: <http://www.olsr.org/?q=download>
- Also: Ubuntu plugins, .debs, Nokia, iPhone
- Linux: install via the normal make routine
Do this in the lib directories too to activate libs!
- Windows: GUI OLSR-Switch might be out of date!
- Biggest obstacle in all of this: card and driver issues (ad-hoc mode often badly buggy)

Lab: Running olsrd / batmand on a laptop olsrd on Linux

- Download sources, build

```
(in olsr dir)
# make
# make install
# cd lib
# make install
(...)
```

Lab: Running olsrd / batmand on a laptop olsrd on Linux

- Prepare settings and start the demon

- example session:

```
# killall NetworkManager
# killall NetworkManagerDispatcher
# killall olsrd
# ifconfig ath0 172.31.1.19 netmask
255.255.255.0
# iwconfig ath0 essid roadshow-mesh mode ad-hoc
channel 1
# olsrd -i ath0 -d 5
# netstat -nr
```

That was it ...

Thank you!

sebastian@less.dk
<http://wire.less.dk>

Sebastian Büttrich, wire.less.dk
edit: February 2008



<http://creativecommons.org/licenses/by-nc-sa/3.0/>

Source of some illustrations and portions of the guide:
Meraka Institute Mesh Guide, see URL above

**“As a net is made up by a series of knots,
so everything in this world is connected by a
series of knots.**

**If anyone thinks that the mesh of a net is an
independent, isolated thing, he is mistaken.**

**It is called a net because it is made up of a
series of connected meshes,
and
each mesh has its place and responsibilities to
other meshes.”**

Buddha Shakyamuni, circa 2500 years ago