

SFTL CLASS to TMF673 GeographicSubAddress

Table of contents:

- [externalId](#)
- [buildingName](#)
- [subUnitType & subUnitNumber](#)
 - [Default rule / Catch all](#)
- [levelType & levelNumber](#)
- [privateStreetNumber & privateStreetName](#)
- [sectionType & sectionNumber](#)
- [postalCode](#)

References:

- [SFTL CLASS to TMF673 GeographicAddress](#)
- [SFTL CLASS to TMF673 BellGeographicSubAddressAlias](#)
- [NDW/Network Hadoop \(Postal Code & Geocode\) to TMF673](#)

Notes :

- APTN & ADRDSCT can be in conflict as APTN is always a unit of type APARTMENT and ADRDSCT can have a subUnitType pattern. See subUnitType & subUnitNumber section below.
- AUXBDGT & ADRDSCT can be in conflict as AUXBDGT is always a building name and ADRDSCT can have a buildingName pattern. See buildingName section below.
- BDGN & ADRDSCT can be in conflict as BDGN being a LOT (L##### or R#####) and ADRDSCT can have a sectionType pattern. See sectionType & sectionNumber section below.

externalId

This attribute is a Bell Canada extension to provide a standard address ID format. For Manitoba it is: province + dash + ID.

Ex. if BDGN is 123456789 and ABRPRVM is MB, then externalId is: MB-123456789

buildingName

General mapping rule :

- If **AUXBDGT is NOT null/blank**, then copy value as is to buildingName
 - AUXBDGT
 - 126 buildingName: 126
 - 56R buildingName: 56R
 - BB 9 buildingName: BB 9
 - E6-1 buildingName: E6-1
 - (2F) buildingName: (2F)
 - (3RD buildingName: (3RD
 - If **AUXBDGT is null/blank**, then look for buildingName pattern at the beginning of **ADRDSCT**. If a pattern is found, copy ADRDSCT as is to buildingName.
 - ADRDSCT
 - HSE 460A buildingName: HSE 460A
 - HSE 1216LL buildingName: HSE 1216LL
 - BDG CONDO buildingName: BDG CONDO
 - HSE 3-14WL buildingName: HSE 3-14WL
 - TCH 9041 A buildingName: TCH 9041 A
- **Conflict resolution:** If **AUXBDGT and ADRDSCT are NOT null/blank**, in the case of a conflict (ADRDSCT is also a buildinName), then priority is on AUXBDGT and ADRDSCT value will appear only in BellGeographicSubAddressAlias.
- **buildingName patterns:**
 - HSE
 - BDG
 - BLDG
 - TCH

Exceptions :

- In the case of a conflict between AUXBDGT and ADRDSCT, see 'Conflict resolution' rule above.

Linked Rules : None

subUnitType & subUnitNumber

General mapping rule :

- If **APTN is NOT null/blank**, set subUnitType to APARTMENT and copy APTN value to subUnitNumber.
 - APTN
 - 10W subUnitType: APARTMENT, subUnitNumber: 10W
 - #10W subUnitType: APARTMENT, subUnitNumber: #10W
 - B22 subUnitType: APARTMENT, subUnitNumber: B22
 - RB-1A subUnitType: APARTMENT, subUnitNumber: RB-1A
 - 37-38 subUnitType: APARTMENT, subUnitNumber: 37-38
- If **APTN is null/blank**, then look for a subUnitType pattern at the beginning of ADDRDSCT. If a pattern is found, set subUnitType to the ENUM value of the pattern found and set subUnitNumber to the string following the subUnitType pattern.
 - Trim leading spaces
 - ADDRDSCT
 - TLR 10W subUnitType: TRAILER, subUnitNumber: 10W
 - TLR CONST subUnitType: TRAILER, subUnitNumber: CONST
 - BLK 3W subUnitType: BLOCK, subUnitNumber: 3W
 - TLR 5 1/2 subUnitType: TRAILER, subUnitNumber: 5 1/2
 - UNIT#E1-01 subUnitType: TRAILER, subUnitNumber: #E1-01
- **Conflict resolution:** If **APTN and ADDRDSCT are NOT null/blank**, in the case of a conflict (ADDRDSCT is also a subUnitType), then priority is on APTN and ADDRDSCT value will appear only in BellGeographicSubAddressAlias.
- **subUnitType patterns:**
 - TLR = TRAILER
 - TRLR = TRAILER
 - UNIT = UNIT
 - BLK = BLOCK

Exceptions : *None*

- In the case of a conflict between APTN and ADDRDSCT, see rule above.

Linked Rules : None

Default rule / Catch all

If **APTN is null/blank and ADDRDSCT is NOT null/blank**, and no pattern were found for buildingName, or for subUnitType, or for levelType, or for sectionType, then set subUnitType to UNIT and set subUnitNumber to the full string in ADDRDSCT.

- LOCK A: subUnitType = UNIT and subUnitNumber = LOCK A
- PAYPHONE: subUnitType = UNIT and subUnitNumber = PAYPHONE

levelType & levelNumber

General mapping rule :

- If **ADDRDSCT is NOT null/blank**, then look for a levelType pattern at the beginning of ADDRDSCT. If a pattern is found, set levelType to the ENUM value of the pattern found and set levelNumber to the string following the levelType pattern found.
 - Trim leading spaces
- ADDRDSCT
 - FLR 2 levelType: FLOOR, levelNumber: 2
 - FLR MN levelType: FLOOR, levelNumber: MN
 - FLR BSMT levelType: FLOOR, levelNumber: BSMT
 - FLR BED1 levelType: FLOOR, levelNumber: BED 1
 - BSMT R levelType: BASEMENT, levelNumber: R
 - BSMT SOUTH levelType: BASEMENT, levelNumber: SOUTH
 - (BSMT LR) levelType:, levelNumber:
 - LEVEL A levelType: LEVEL, levelNumber: A
 - LEVEL 1 levelType: LEVEL, levelNumber: 1
 - PENTHOUSE levelType: PENT, levelNumber:
 - ATTIC levelType: PENT, levelNumber:
 - FLR BED #1 levelType: FLOOR, levelNumber: BED #1
- **levelType patterns:**

- FLR = FLOOR
- BSMT = BASEMENT
- LEVEL= LEVEL
- PENT = PENT
- PENTHOUSE = PENT
- ATTIC = PENT

Exceptions : None

Linked Rules : None

privateStreetNumber & privateStreetName

This attribute will always be blank because there is no pattern indicating private street in Address description(ADRDSCT) or Auxiliary building (AUXBDGT).

sectionType & sectionNumber

General mapping rule :

- If **BDGN** is a **LOT** number (BDGN starting with '**L**' or starting with '**R**'), then set sectionType to LOT and sectionNumber to the value of BDGN.
 - **BDGN**
 - L12345 sectionType: LOT, sectionNumber: L12345
 - L A1 sectionType: LOT, sectionNumber: L A1
 - LC12 sectionType: LOT, sectionNumber: LC12
 - LOT S9 sectionType: LOT, sectionNumber: LOT S9
 - LF1 sectionType: LOT, sectionNumber: LF1
 - R00264 sectionType: LOT, sectionNumber: R00264
- If **BDGN** is **NOT** a **LOT** and **ADRDSCT** is not null/blank, then look for a sectionType pattern at the beginning of ADRDSCT. If a pattern is found, set sectionType to the ENUM value of the pattern found and set sectionNumber to the string following the sectionType pattern.
 - Trim leading spaces
 - **ADRDSCT**
 - LOT 40 sectionType: LOT, sectionNumber: 40
 - LOT C sectionType: LOT, sectionNumber: C
 - LOT68 sectionType: LOT, sectionNumber: 68
 - BAY 20 sectionType: BAY, sectionNumber: 20
 - BAY # 2 sectionType: BAY, sectionNumber: # 2
 - BAY AREA sectionType: BAY, sectionNumber: AREA
 - (CABIN 10) sectionType:, sectionNumber:
 - **Conflict resolution:** If **BDGN** is a **LOT** and **ADRDSCT** is **NOT** null/blank, in the case of a conflict (ADRDSCT is also a sectionType), then priority is on BDGN and ADRDSCT value will appear only in BellGeographicSubAddressAlias.
- **sectionType patterns:**
 - LOT = LOT
 - BAY = BAY
 - CABIN = CABIN
 - BB = GATE
 - Building Barrier

Exceptions :

- In the case of a conflict between BDGN and ADRDSCT, see rule above.

Linked Rules : None

postalCode

ADD RULES FOR UPDATES FROM NDW ??????????????????????

General mapping rule :

- Copy **PCC** as is to postalCode

Exceptions : None

Linked Rules : None