==
PM2 COMMANDS WITH EXAMPLES AND EXPECTED OUTPUT
Example applications: frontend, backend, worker
==

1. pm2 list
Purpose: View all applications managed by PM2
Command:
pm2 list

Expected output:
id name   status   cpu   memory
0   frontend   online   1%   45mb
1   backend   online   0%   80mb
2   worker   online   0%   35mb

Meaning: Shows application names, status, CPU and memory.

2. pm2 status
Purpose: Check application status
Command:
pm2 status

Expected output:
id name   status
0   frontend   online
1   backend   online
2   worker   online

Meaning: Shows whether applications are running or stopped.

3. pm2 logs
Purpose: View logs from all applications

Command:
pm2 logs

Expected output:
0|frontend | Server listening on port 3000
1|backend | Database connected successfully
2|worker | Background job started

Meaning: Displays live logs from all managed applications.
Press Ctrl+C to exit log viewing without stopping apps.

4. pm2 monit
Purpose: Monitor CPU and memory usage
Command:
pm2 monit

Expected output:
Interactive monitoring dashboard
frontend CPU: 1%   Memory: 45 MB
backend   CPU: 2%   Memory: 80 MB
worker   CPU: 0%   Memory: 35 MB

Meaning: Displays live process resource usage.
Press Ctrl+C to exit the dashboard.

5. pm2 restart app
Purpose: Restart an application named app
Example:
pm2 restart backend

Expected output:
[PM2] Applying action restartProcessId on app [backend]
[PM2] [backend](1) ✓

Meaning: Restarts backend. This can interrupt service briefly.

6**. pm2 stop app**
Purpose: Stop an application
Example:
pm2 stop backend

Expected output:
[PM2] Applying action stopProcessId on app [backend]
[PM2] [backend](1) ✓

Meaning: Stops backend but keeps it in PM2's process list.

7. **pm2 delete app**
Purpose: Remove an application from PM2 management
Example:
pm2 delete backend

Expected output:
[PM2] Applying action deleteProcessId on app [backend]
[PM2] [backend](1) ✓

Meaning: Removes backend from PM2's process list.
It does not delete the application's source code.

8. **pm2 start app.js**
Purpose: Start a Node.js application
Example:
pm2 start app.js --name backend

Expected output:
[PM2] Starting app.js in fork_mode
[PM2] Done.
#
id name   status

```
# 0   backend   online

# Meaning: Starts app.js under PM2 if the file exists
# and the application starts successfully.


# ==========================================
# IMPORTANT:
# - Examples are illustrative; actual output varies.
# - Replace backend and app.js with actual values.
# - Restart, stop and delete change application state.
# - Do not run all commands blindly on production.
# ==========================================
```