

## 100 Days of Azure DevOps

## Day 18 Handout — Moving apartments — bring the furniture (history), leave the broken IKEA (secrets)

2 - Azure Repos & Git Mastery · Personal lab only · Educational content · Not a sales pitch

### Architecture A — import paths (history is commits, not ZIP files)

| Path                               | What is preserved                           | Lab choice                           |
|------------------------------------|---------------------------------------------|--------------------------------------|
| ADO Import (Repos → Import)        | Git history from a public URL you can reach | Small public GitHub sample           |
| git clone --bare + push --mirror   | All refs: branches, tags                    | When Import UI cannot see the source |
| git remote add + push --all --tags | Named branches you pick                     | When you do not want every junk ref  |
| TFVC import                        | Changesets → Git (lossy-ish)                | Mention only — stay on Git           |
| ZIP upload                         | One tree, no history                        | Not a migration                      |
| LFS objects                        | Pointers unless LFS migrated                | Skip LFS for this lab sample         |

### Architecture B — decide what NOT to bring

| Object                         | Bring?                       | Why                                              |
|--------------------------------|------------------------------|--------------------------------------------------|
| Commit DAG + tags              | Yes                          | git log must show old authors/dates              |
| main / master history          | Yes, then set default main   | Pipelines trigger on the default                 |
| .env / PATs in old blobs       | No — rewrite or leave behind | Rotate every secret that ever lived in Git       |
| node_modules from old mistakes | No                           | BFG / git filter-repo if already imported        |
| Work remote URL in README      | No                           | Rewrite clone instructions to personal ADO       |
| Wiki / Boards                  | Separate                     | Import is Git only; work items do not ride along |

### Architecture C — pitfalls that look like 'history vanished'

| Pitfall                                | What you see                    | Fix                                                                  |
|----------------------------------------|---------------------------------|----------------------------------------------------------------------|
| Push without --mirror, missing tags    | git tag empty on ADO            | git push origin --tags or redo --mirror                              |
| Import of a huge monorepo              | UI timeout / LFS 404            | Pick a tiny public repo for the lab                                  |
| Default branch still empty main        | Imported code on master only    | Repos → Branches → set default; delete empty main or merge           |
| Auth during Import                     | Cannot fetch private GitHub     | Use --bare from a machine that already has access — still no work IP |
| Force-push mirror onto a repo with PRs | Rewrote SHAs under existing PRs | Import into a NEW empty repo imported-sample                         |
| Secrets survived                       | git log -S 'AKIA' still hits    | filter-repo + rotate; do not publish                                 |

## One-liner to remember

Migrations are moving apartments — history is the furniture; leave the broken IKEA shelf (secrets) behind.

## Step-by-step lab (personal Azure / Azure DevOps only)

Personal project azure-100-labs. Create a NEW empty repo imported-sample. Do not import employer code.

- 1 Repos → New repository → Name imported-sample → do NOT add a README (empty, ready for import).
- 2 Option A: imported-sample → Import → paste a SMALL public GitHub URL you own or a well-known tiny sample. Import.
- 3 Option B (if Import fails): `git clone --bare https://github.com/<user>/<small-repo>.git` then `git push --mirror https://dev.azure.com/<org>/azure-100-labs/_git/imported-sample`
- 4 Clone imported-sample locally. `git log --oneline -10`. Confirm old commits (dates/messages) survived.
- 5 Repos → Branches: set default to main if the source used main; if only master exists, leave it or rename.
- 6 Search the tree for `.env`, `id_rsa`, `nuget.config` with keys. If found, document in notes — do not push fixes to a work repo.
- 7 Write docs/migration-day18.md in azure-100-labs (the main repo): which option you used and that git log still shows history.

## Mirror a public Git history into an empty Azure Repos repo

```
git clone --bare https://github.com/<user>/<small-public-repo>.git
cd <small-public-repo>.git
git push --mirror https://dev.azure.com/<org>/azure-100-labs/_git/imported-sample
cd ..
git clone https://dev.azure.com/<org>/azure-100-labs/_git/imported-sample
cd imported-sample
git log --oneline --decorate -10
```

## Done checklist

- imported-sample exists in the personal project
- git log shows commits from before the import
- Did not import employer / private work history
- Documented Import UI vs --mirror in the main lab repo

## Tomorrow — Day 19

Repo security