

100 Days of Azure DevOps

Day 31 Handout — Classic is the old mall. YAML CD is a deployment job, an environment, and runOnce.deploy

4 - Continuous Delivery · Personal lab only · Educational content · Not a sales pitch

Architecture A — CD objects (same run, different job type)

Object	YAML	Why it exists
Classic Release	UI designer, not in the repo	Brownfield literacy. Not the lab default
stage	stage: DeployDev	A gate. Can dependOn CI / previous env
deployment job	deployment: Deploy (not job:)	Environment checks attach here
environment	environment: dev	Azure DevOps record: history, checks, resources
strategy	runOnce.deploy.steps	Smallest CD. rolling/canary come later as ideas
bits	download: current artifact: drop	Consume Phase 3. Rebuilding here invents ghosts

Architecture B — Classic vs YAML for this series

Question	YAML CD	Classic Release
Where is the workflow?	In git. Reviews as a diff	In the service. Reviews as screenshots
Approvals later (Day 38)	Checks on the Environment	Pre-deployment conditions on a stage
Multi-env (Day 39)	dependsOn chain + same drop	Stage-to-stage; still can rebuild if you let it
Lab default	Use this	Open once so you can recognize it; do not live there

Architecture C — pitfalls that impersonate CI

Pitfall	What you see	Fix
job: instead of deployment:	environment: ignored or no check history	Use deployment: + strategy.runOnce
Rebuild in Deploy	dotnet publish in the release job	download: current artifact: drop
No Environment object	YAML names prod; UI has empty list	Pipelines → Environments → New → dev
Classic + YAML twins	Two sources of truth, one of them stale	Pick YAML. Leave Classic unused

One-liner to remember

Classic releases are the old mall; YAML CD is the street you actually live on — a deployment job aimed at environment: dev.

Step-by-step lab (personal Azure / Azure DevOps only)

Personal Azure DevOps org only. Project azure-100-labs. No Azure spend required today — echo is a legal first proof.

- 1 Pipelines → Environments → New environment → name: dev → create with no resources. This is an Azure DevOps object, not a folder on disk.
- 2 Add pipelines/cd-dev.yml (starter below): stage DeployDev, deployment job, environment: dev, download drop if CI published it, else echo.
- 3 If drop is missing, run the Phase 3 CI once so current has an artifact — or keep echo-only and note the gap.
- 4 Run the pipeline. Open Environments → dev → deployments and confirm this run is listed.

- 5 Pipelines → Releases (Classic). Open it once. Write one line: why labs stay on YAML. Do not create a Classic release.
- 6 docs/cd-yaml-day31.md: deployment vs job, environment, download: current.

Starter YAML — deployment job on environment dev

```
# pipelines/cd-dev.yml
trigger: none
resources:
  pipelines:
    - pipeline: ci
      source: azure-100-labs # name of your CI pipeline
      trigger: true
stages:
- stage: DeployDev
  jobs:
  - deployment: Deploy
    environment: dev
    pool: { vmImage: ubuntu-latest }
    strategy:
      runOnce:
        deploy:
          steps:
            - download: ci
              artifact: drop
            - script: echo "Deploying $(Pipeline.Workspace)/ci/drop to dev"
              displayName: Proof – no rebuild
```

Done checklist

- Environment dev exists under Pipelines → Environments
- A deployment job (not a regular job) targeted it
- YAML does not rebuild the app in Deploy
- Classic was viewed, not adopted

Tomorrow — Day 32

Deploy to Azure App Service — F1 plan, AzureWebApp@1, the zip you already published.