Revisiting Multi-Agent Social Reasoning for Conversational Power: Factor Graphs, Decision Models, and Context

Muttaqi Ahmad Alladin[*] Purdue University

Krish Patel[*] Purdue University

Jiwon Kim[*] Purdue University

Abstract

Wu et al. (2025) predict which of two speakers in a six-turn meeting excerpt is the professor, with a factor graph over LLM-written reasons and rebuttals. We proposed to improve the graph with quote-checked arguments and Dung's grounded extension. On the 151 released snippets neither change helps, and no method we tried scores above the majority label. Tracing every snippet back to the ICSI Meeting Corpus shows that the released text and labels disagree about who is speaking: under the reading of the speaker letters that makes the labels correct, 57.6% of the words are displayed under the other speaker's letter. We rebuilt the snippets from the corpus, taking speaker turns from the corpus itself. On the 150 rebuilt snippets a System One decision model (Jev) identifies the professor in 71.3% of cases against a 56.7% majority baseline, and in 89.3% when it also sees 60 segments of meeting on each side. Their factor graph, rerun call by call with arguments from GPT-6.1 Terra and scores from Jev, reaches 72.0%, level with asking Terra directly (72.7%). A factor graph built from typed yes/no statements, with no generated arguments, matches the direct question at every context length.

1 Introduction

Wu et al. (2025) study professor-student exchanges of six turns from the ICSI Meeting Corpus (Janin et al., 2003) and take the professor to hold more power. They report 46.3% for six PhD judges, 49.0% for GPT-3.5 on the snippet alone, and 54.3% for a factor graph over LLM-written reasons and rebuttals solved with AD3 (Martins et al., 2011). In the label file they released, speaker A is the higher-power speaker in 83 of 151 rows, so always answering A scores 55.0%.

Our proposal kept their cached arguments and changed three things: a quote check on every argument, a rebuttal prompt that shows the rebuttal, and Dung's grounded extension (Dung, 1995) in place of their XOR program. Section 2 reports those experiments on the released snippets. Section 3 traces the released snippets back to the corpus, shows that their displayed speakers and their labels disagree, and describes a snippet set rebuilt from the corpus. Section 4 reports the same task on snippets rebuilt from the corpus, with the original factor graph, a decision model, zero-shot LLMs, and longer context.

Method	Correct	Acc.
Always A	83	55.0
XOR graph, cached GPT-3.5 scores	82	54.3
Grounded extension, as proposed	69	45.7
XOR graph with quote filter	64	42.4
Gemma 4 zero-shot	66	43.7
Jev, "is X the professor"	72	47.7
XOR graph, Jev scores	76	50.3
Preference grounded, cached scores	79	52.3
Preference grounded, Jev scores	71	47.0
Typed-statement graph (Jev)	77	51.0

Table 1: Accuracy on the 151 released snippets. Beating the 55.0% base rate at $p < 0.05$ needs 94 correct.

2 The released snippets

Table 1 lists the runs. Our reimplementation of the XOR graph as an integer program reproduces the published 54.3% exactly (82 of 151). The quote filter kept 33.8% of the 7,248 arguments and lowered accuracy.

The grounded extension is degenerate as we specified it. Every reason has one paired rebuttal and nothing attacks a rebuttal, so every rebuttal is IN and all 3,624 reasons are OUT. All 151 decisions fall to the tie-break. Removing weak rebuttals does not help, because we also made each reason for A and each reason for B attack each other, and under grounded semantics a mutual attack leaves both arguments undecided. A preference-based

[*]These authors contributed equally.

framework, where an attack succeeds only when the attacker scores at least as high as its target, removes both problems and gives a decision from IN counts on every snippet. It is well behaved and no more accurate (79 of 151 with cached scores).

Rescoring does not help. A logistic regression fit to the cached validity and grounding scores, evaluated leave-one-out, reaches 53.0 to 57.0%. Rescoring all arguments with Jev, including the corrected rebuttal question on all 3,624 rebuttals, gives 50.3% under the XOR graph.

3 Data

Sources. The released test set is the file `meeting.csv` of Wu et al. (2025): 151 rows, each with a conversation between speakers A and B and a label naming the higher-power speaker.[1] The snippets come from the ICSI Meeting Corpus (Janin et al., 2003). We use its original MRT transcripts, in which every segment carries a start time, a participant ID and the transcribed text, and its participant metadata, which records each participant's education level.[2]

Locating the released snippets. After removing transcript markup, the non-empty lines of a released snippet are a run of consecutive corpus segments. Matching on that sequence finds all 151 snippets, each in exactly one place, across 45 meetings. This step uses only the released text. It gives, for every line of every snippet, the participant who said it.

Displayed speakers against corpus speakers. In the released text each displayed turn ends with the first segment of the next corpus speaker, as in Table 2: the turn shown under A contains the professor's remarks and then the other participant's "Mm-hmm." A letter therefore does not stand for one participant throughout a snippet, and there are two ways to read it.

If each letter is read as the speaker of the last line of its turns, the letters map one-to-one onto the two participants in 128 snippets with exactly one professor, and the released label names the professor in 128 of those 128. Under that reading, 7,596 of the 13,185 words in those snippets (57.6%) are displayed under the other participant's letter, and in 73 of the 128 snippets more than half of the words are.

Shown	Said by	Text
A	professor	Uh, maybe you have to…
A	other	Mm-hmm.
B	professor	but -
A	other	Yeah, I guess.
B	professor	Yeah.
A	professor	do you have any way of…
A	other	Mmm.
B	other	No, we don't.
B	professor	Yeah.

Table 2: Released snippet 0 (meeting Bro025, starting at 1273.5 s, abridged). "Shown" is the letter the line appears under in the released text. "Said by" is from the corpus participant IDs. The released label is B.

If instead each letter is read as whoever says most of the words shown under it, the text is mostly attributed correctly, and the released label names the letter that carries most of the professor's words in only 69 of the 128 snippets.

Under either reading the text and the labels disagree: the letter that a reader sees doing the professor's talking is, in about half of the snippets, not the letter the label rewards. In the remaining 23 snippets a letter covers two participants (22) or only one participant speaks (1). Appendix A lists every snippet.

What we can and cannot conclude. The cached GPT-3.5 arguments in the release were generated from this text: the conversation stored with each cached snippet is identical to the corresponding row of `meeting.csv` for all 151. The code that built the snippets from the corpus is not in the public repository, so we cannot say which step produced the mismatch. We do not know whether the human judges of Wu et al. (2025) saw the same text, or whether the numbers in their paper were computed from this file. We have not yet confirmed these observations with the authors.

Consequence for the task. A reader or model that judges the displayed text will, in many snippets, credit the professor's behaviour to the other letter. This is consistent with Section 2, where every method is at or slightly below the majority rate, and with the near-chance human and LLM accuracies reported by Wu et al. (2025). It also predicts that the same judgments should become accurate once speech is attributed to the people who said it,

[1] https://github.com/kandicew/social-reasoning, commit fed11b6, data/meeting.csv.

[2] https://groups.inf.ed.ac.uk/ami/icsi/download: ICSI_original_transcripts.zip and ICSI_core_NXT.zip (speakers.xml), distributed under CC BY 4.0.

which Section 4 tests.

The rebuilt set. We rebuilt each snippet from the located corpus segments. Speakers are the corpus participant IDs, consecutive segments by one participant form a turn, and the professor is the participant whose education level in `speakers.xml` is Professor. A snippet is kept if it has exactly one professor and at least two speakers, which drops one snippet and leaves 150. In the 128 snippets above, the letters follow the last-line reading, so the released labels carry over unchanged; in the other 22, the first of the two speakers to talk is A. In total 142 of the 150 labels equal the released label, and the professor is A in 85 (a 56.7% base rate). Three snippets include a third participant, shown as C. Each snippet is rendered at three lengths: its own segments, and 15 or 60 further corpus segments on each side, with other participants shown as C, D, and so on. The other speaker's education level is PhD in 117 snippets, Grad in 30 and Postdoc in 3, so "student" follows the usage of Wu et al. (2025). The builder is deterministic and regenerates the set byte for byte from the three source files.

4 Snippets rebuilt from the corpus

All experiments in this section use the rebuilt set of Section 3: 150 snippets with speakers taken from the corpus, at the same span as the released snippet and with 15 or 60 extra segments on each side.

Jev. Jev is a decision model that returns a probability for each typed yes/no question about a supplied state.[3] The direct question is "Is speaker X the professor?", asked for A and for B, and we predict the speaker with the higher probability.

The factor graph of Wu et al. We ran their method on the rebuilt snippets with arguments from current models, in two ways. In the first, GPT-6.1 Terra wrote the arguments call by call with their prompt templates: one independent request for each aspect summary, each list of three reasons, and each rebuttal (36 requests per snippet), with tools disabled and no access to labels. In the second, Claude Haiku wrote all arguments for a snippet in one pass. Jev scored both sets: validity and grounding of each argument, whether each rebuttal counters its reason, and similarity and contradiction of reason pairs. A separate Haiku instance also scored the Haiku arguments. Their rule file and weights (reason 20, rebuttal 18) do the inference, in the three variants of the paper.

[3] TypeSafe AI, `jev-1.14.0`, https://docs.typesafe.ai. The questions used on the rebuilt snippets were fixed before that data was built.

	Rel.	Rebuilt	±15	±60
More words	46.0	66.7	66.0	68.7
Longer turns		68.0	69.3	66.7
Jev, professor	48.0	71.3	84.7	89.3
Jev, more power	48.0	70.7	79.3	88.0
Typed-statement graph	51.3	70.0	80.7	90.7

Table 3: Accuracy (%) on the 150 snippets. "Rel." uses the released text and labels for the same snippets. The other columns use the rebuilt text at the same span and with 15 or 60 extra segments per side. Always answering A scores 56.7%. The blank cell was not run.

Grounded extension. We also ran the aggregator from our proposal on the same arguments. The framework has 48 arguments per snippet, 24 reasons and their 24 rebuttals. A reason has strength $P(\text{valid}) \cdot P(\text{grounded})$ and a rebuttal has strength $P(\text{counters its reason}) \cdot P(\text{grounded})$. In the *proposed* relation every rebuttal attacks its reason, and every reason for A and every reason for B attack each other. In the *preference* relation an attack succeeds only if the attacker is at least as strong as its target: a rebuttal defeats its reason when it is no weaker, and a reason defeats an opposing reason when it is strictly stronger. The grounded labelling marks an argument IN when all its attackers are OUT and OUT when some attacker is IN. The speaker with more IN reasons is predicted, with ties going to the larger sum of reason strengths and then to A.

Typed-statement factor graph. We also keep their graph and replace the generated text. For each of their four aspects we wrote three yes/no statements, such as "Does speaker X evaluate speaker Y's work?". Jev's probability for a statement about X is the weight of a reason for X, in the manner of Kassner et al. (2023), and the same statement about the other speaker is its rebuttal. One call with 24 questions replaces the generation and scoring calls for 48 arguments per snippet. Unlike the argumentation scoring studied by Sanayei et al. (2025), no model is asked to reason over the graph.

Results. Table 3 gives accuracy by input for the methods that need no generated arguments. On the rebuilt snippets at the same span, the direct Jev question identifies the professor in 107 of 150 cases. Against always answering A this is 34 wins

Args.	Scores	Dir.	Reas.	+Reb.	All	Gr.
Terra	Jev	72.7	66.7	72.0	72.0	70.0
Haiku	Jev	68.0	73.3	70.0	70.0	73.3
Haiku	Haiku	68.0	68.7	67.3	68.0	64.7

Table 4: Argument-based methods on the rebuilt snippets at the same span (accuracy, %). Rows give who wrote and who scored the arguments. "Dir." is the argument-writing model asked directly. "Reas.", "+Reb." and "All" are the three variants of the factor graph of Wu et al. (2025). "Gr." is the grounded extension with the preference relation. For comparison, the direct Jev question scores 71.3% and Claude Sonnet asked directly scores 76.0%.

and 12 losses (exact McNemar $p = 0.0016$), and a bootstrap that resamples whole meetings gives a 95% interval of 6.7 to 22.0 points for the difference. The same question on the released text scores 72 of 150, and the paired contrast between the two inputs is 52 wins to 17 losses ($p < 0.0001$). Context helps further: ± 15 segments against the same span is 30 wins to 10 losses ($p = 0.002$). The word-count rules reach 66.7% and 68.0%, but their paired tests against the majority label are not significant ($p = 0.10$ and $p = 0.053$).

Table 4 gives the argument-based methods. With Terra's arguments and Jev's scores the full factor graph of Wu et al. (2025) reaches 72.0%. That is level with Terra asked directly (72.7%, 14 wins to 15 losses) and with the direct Jev question (14 to 13). With Haiku's arguments it reaches 70.0% under Jev's scores and 68.0% under Haiku's, against 68.0% for Haiku asked directly. The parts of the graph do not behave consistently across the two sets of arguments. Rebuttals add 5.3 points with Terra's arguments (11 wins to 3 losses, $p = 0.057$) and cost 3.3 points with Haiku's under the same scorer, and adding the relations changes accuracy in neither Jev-scored run. A plain sum of reason scores with no graph equals the reasons-only graph in all three rows. The best single result at this span is a stronger model asked directly (Sonnet, 76.0%), which is not distinguishable from Jev (27 wins to 20 losses, $p = 0.38$) or from Terra (15 to 10, $p = 0.42$).

The grounded extension behaves on the rebuilt snippets as it did on the released ones. Under the proposed relation no reason is ever IN in any run, so all 150 decisions are made by the tie-break and the accuracy is that of the sum of reason strengths. The preference relation gives a real decision: with Jev scores every snippet is decided by IN counts, and accuracy is 70.0% with Terra's arguments and 73.3% with Haiku's, the latter level with the direct Jev question (13 wins to 10 losses, $p = 0.68$). With the coarser Haiku scores it reaches 64.7%. We also searched 288 grounded policies over the Haiku arguments and Jev scores, varying the strength definitions, the rule for when a rebuttal attacks (preference or a threshold on Jev's judgment that it counters its reason), the cross-side rule, and the decision rule. Choosing the best policy on a development half of the meetings and scoring it on the other half, over 500 random splits, gives 69.7% on average against 71.5% for the direct Jev question on the same halves, so no policy in this family improves on asking directly.

The typed-statement graph tracks the direct Jev question at every input (70.0% against 71.3% at the same span, 21 wins to 23 losses, $p = 0.88$). It is a cheaper way to run the method and exposes which statements drive a decision, and we do not claim it is more accurate than asking directly.

Jev's probabilities are informative on the rebuilt snippets. Its Brier score is 0.189 at the same span and 0.095 at ± 60, against 0.246 for the base rate, and its most confident fifth of answers is 93.3% correct at the same span.

5 Limitations

The order of work was exploratory. The mismatch in the released file was found, and the rebuilt set constructed, after many runs on the released file, and every number in Section 2 was computed on test data with no development split. The questions used on the rebuilt snippets were written before that data existed, and each run was made once.

Neither rerun of the factor graph uses the original model. The Terra run follows the pipeline call by call, but the text comes from GPT-6.1 Terra and the scores from Jev, because the command-line interface we used does not expose token probabilities. The Haiku run wrote each snippet's arguments in one pass, so reasons were written with the conversation in view, and its Haiku scores are stated probabilities with about 15 distinct values. In both, each rebuttal is judged against its own reason and grounded on its own text.

The rebuilt set has four professors, and one of them is the professor in 110 of the 150 snippets. Jev's accuracy for that professor is 69.1% at the same span, and 73.3 to 100% for the others, so the

result is not carried by one person, but the meeting-level bootstrap is the more honest interval. With 60 extra segments a model can use cues that a six-turn excerpt lacks, including how others address the two speakers.

We did not rerun GPT-3.5, Gemma, or a human study on the rebuilt snippets. Jev is a proprietary model in early access whose training and calibration claims are not peer reviewed. The 40-item human audit from our proposal was not completed.

Earlier work predicts power from word choice and thread structure with supervised models (Danescu-Niculescu-Mizil et al., 2012; Prabhakaran and Rambow, 2014), and Ziems et al. (2024) find that LLMs often trail such models. Our numbers say only that the role is recoverable from these excerpts, and they are not a comparison with that line of work.

6 Reproducibility

The repository contains the rebuilt snippets with corpus offsets, every model answer, and all code.[4] One command downloads the five external inputs (the released `meeting.csv`, argument cache and rule file, and the two ICSI annotation archives), verifies each by SHA-256, regenerates the snippet set byte for byte, and recomputes every number in this report from the stored model answers without calling a model. The model answers themselves come from hosted models and cannot be regenerated exactly; the scripts and instructions used to collect them are included. The ICSI corpus is distributed under CC BY 4.0.

References

Cristian Danescu-Niculescu-Mizil, Lillian Lee, Bo Pang, and Jon Kleinberg. 2012. Echoes of power: Language effects and power differences in social interaction. In *Proceedings of the 21st International Conference on World Wide Web*, pages 699–708.

Phan Minh Dung. 1995. On the acceptability of arguments and its fundamental role in nonmonotonic reasoning, logic programming and n-person games. *Artificial Intelligence*, 77(2):321–357.

Adam Janin, Don Baron, Jane Edwards, Dan Ellis, David Gelbart, Nelson Morgan, Barbara Peskin, Thilo Pfau, Elizabeth Shriberg, Andreas Stolcke, and Chuck Wooters. 2003. The ICSI meeting corpus. In *Proceedings of ICASSP*, volume 1, pages I–364.

[4] https://github.com/muttaqiahmadalladin/cs-577

Nora Kassner, Oyvind Tafjord, Ashish Sabharwal, Kyle Richardson, Hinrich Schütze, and Peter Clark. 2023. Language models with rationality. In *Proceedings of the 2023 Conference on Empirical Methods in Natural Language Processing*, pages 14190–14201, Singapore. Association for Computational Linguistics.

André F. T. Martins, Mário A. T. Figueiredo, Pedro M. Q. Aguiar, Noah A. Smith, and Eric P. Xing. 2011. An augmented Lagrangian approach to constrained MAP inference. In *Proceedings of the 28th International Conference on Machine Learning*, pages 169–176.

Vinodkumar Prabhakaran and Owen Rambow. 2014. Predicting power relations between participants in written dialog from a single thread. In *Proceedings of the 52nd Annual Meeting of the Association for Computational Linguistics (Volume 2: Short Papers)*, pages 339–344, Baltimore, Maryland. Association for Computational Linguistics.

Reza Sanayei, Srdjan Vesic, Eduardo Blanco, and Mihai Surdeanu. 2025. Can LLMs judge debates? evaluating non-linear reasoning via argumentation theory semantics. In *Findings of the Association for Computational Linguistics: EMNLP 2025*, pages 21244–21262. Association for Computational Linguistics.

Zhaoqing Wu, Dan Goldwasser, Maria Leonor Pacheco, and Leora Morgenstern. 2025. Identifying power relations in conversations using multi-agent social reasoning. In *Proceedings of the 2025 Conference of the Nations of the Americas Chapter of the Association for Computational Linguistics: Human Language Technologies (Volume 2: Short Papers)*, pages 855–865, Albuquerque, New Mexico. Association for Computational Linguistics.

Caleb Ziems, William Held, Omar Shaikh, Jiaao Chen, Zhehao Zhang, and Diyi Yang. 2024. Can large language models transform computational social science? *Computational Linguistics*, 50(1):237–291.

A Differences between the released file and the rebuilt set, by snippet

Table 5 has one row for each of the 151 released snippets. **ID** is the row index in the released `meeting.csv`. **Meeting** and **Start** give the ICSI meeting and the start time in seconds of the snippet's first corpus segment. **Seg.** and **Words** are the numbers of corpus segments and words in the snippet. **Misplaced** is the number of words displayed under the other participant's letter when each released letter is read as the speaker of the last line of its turns, and **%** is that number as a share of the snippet's words; both are blank when the letters do not map one-to-one onto two participants. **Rel.** is the released label and **Reb.** is the professor's letter in the rebuilt set, marked † where the two differ. **Letters** says whether the rebuilt letters follow the released ones (kept) or the first of the two speakers to talk was made A (reassigned).

In total, 150 of the 151 snippets are in the rebuilt set. Letters are kept in 128 and reassigned in 22, and the label differs from the released label in 8. Over the 128 snippets with a one-to-one mapping, 7,596 of 13,185 words are misplaced; 121 of them have at least one misplaced word, 7 have none, and the median share is 55%. The same rows are in `data/released_vs_rebuilt.csv` in the repository.

Table 5: Every released snippet against the rebuilt set.

ID	Meeting	Start	Seg.	Words	Misplaced	%	Rel.	Reb.	Letters	Note
0	Bro025	1273.5	15	98	89	91	B	B	kept	
1	Bro008	332.0	11	218	113	52	B	B	kept	
2	Bro003	618.0	10	50	31	62	A	A	kept	
3	Bmr029	1138.4	14	122	–	–	B	A†	reassigned	a letter covers two participants
4	Bed004	3006.4	10	143	90	63	B	B	kept	
5	Bro005	2065.7	10	71	35	49	B	B	kept	
6	Bro027	3074.1	10	83	17	20	A	A	kept	
7	Bmr015	1350.5	15	117	66	56	B	B	kept	
8	Bro013	1135.9	8	49	20	41	A	A	kept	
9	Bmr001	1839.5	8	87	37	43	B	B	kept	
10	Bed011	1007.8	12	108	66	61	A	A	kept	
11	Bro011	1266.0	69	356	–	–	A	A	reassigned	a letter covers two participants
12	Bed004	1404.9	8	80	26	32	A	A	kept	
13	Bmr025	613.7	9	83	38	46	A	A	kept	
14	Bmr006	748.7	8	73	3	4	A	A	kept	
15	Bmr009	579.0	12	103	–	–	A	B†	reassigned	a letter covers two participants
16	Bmr014	493.0	11	138	83	60	B	B	kept	
17	Bmr029	789.9	6	59	0	0	A	A	kept	
18	Bro008	777.2	27	472	321	68	A	A	kept	
19	Bmr005	2826.9	8	64	12	19	A	A	kept	
20	Bmr001	1916.4	8	55	15	27	B	B	kept	
21	Bro004	1902.2	11	81	49	60	A	A	kept	
22	Bro026	2882.0	10	88	29	33	A	A	kept	
23	Bro027	999.1	13	91	50	55	B	B	kept	
24	Bro017	1268.5	6	44	0	0	A	A	kept	
25	Bro005	1215.7	6	31	–	–	A	A	reassigned	a letter covers two participants
26	Bmr029	885.3	8	54	23	43	B	B	kept	
27	Bro027	2509.2	6	41	0	0	A	A	kept	
28	Bmr006	2931.2	8	87	–	–	B	B	reassigned	a letter covers two participants
29	Bmr008	371.2	8	37	15	41	A	A	kept	
30	Bro008	4.3	16	136	83	61	A	A	kept	
31	Bro005	2429.2	19	107	75	70	A	A	kept	
32	Bro007	577.3	12	71	55	77	A	A	kept	
33	Bro027	3401.9	8	69	3	4	B	B	kept	
34	Bed014	1023.1	8	39	5	13	B	B	kept	
35	Bro017	1982.4	14	183	114	62	B	B	kept	
36	Bmr006	651.8	10	86	45	52	A	A	kept	third participant
37	Bro023	1211.8	21	273	218	80	A	A	kept	
38	Bro017	2372.0	13	84	44	52	B	B	kept	
39	Bro005	3410.5	22	249	–	–	A	A	reassigned	a letter covers two participants
40	Bro017	1881.0	9	123	27	22	B	B	kept	
41	Bro018	1387.7	14	119	–	–	B	B	reassigned	a letter covers two participants
42	Bmr024	2428.3	8	82	11	13	B	B	kept	
43	Bro014	2559.0	6	63	0	0	B	B	kept	
44	Bro023	725.6	11	141	47	33	B	B	kept	

ID	Meeting	Start	Seg.	Words	Misplaced	%	Rel.	Reb.	Letters	Note
45	Bro016	732.4	8	88	–	–	A	A	reassigned	a letter covers two participants
46	Bro004	2362.6	7	44	8	18	A	A	kept	
47	Bro028	100.4	8	46	–	–	A	B†	reassigned	a letter covers two participants
48	Bed009	3005.9	22	182	166	91	A	A	kept	
49	Bro016	1752.7	9	67	15	22	B	B	kept	
50	Bro010	303.8	18	88	61	69	B	B	kept	
51	Bro004	1974.2	24	201	136	68	B	B	kept	
52	Bed014	809.3	10	106	–	–	B	–	–	one participant only; dropped
53	Bro027	1958.0	8	58	6	10	A	A	kept	
54	Bro007	1634.5	19	183	153	84	B	B	kept	
55	Bed011	3009.4	10	57	25	44	A	A	kept	
56	Bmr023	3018.5	8	84	37	44	A	A	kept	
57	Bro017	1843.6	14	138	94	68	B	B	kept	
58	Bro005	3498.5	13	132	82	62	A	A	kept	
59	Bro017	490.8	9	113	66	58	A	A	kept	
60	Bmr009	0.0	7	29	1	3	A	A	kept	
61	Bro024	3861.2	13	79	30	38	B	B	kept	
62	Bro005	2377.8	10	49	29	59	B	B	kept	
63	Bro005	1191.3	10	69	44	64	A	A	kept	
64	Bmr009	402.1	16	109	–	–	A	A	reassigned	a letter covers two participants
65	Bmr008	2880.7	10	81	55	68	A	A	kept	
66	Bed004	2208.7	14	140	82	59	B	B	kept	
67	Bro017	1170.9	7	56	–	–	A	A	reassigned	a letter covers two participants
68	Bro023	924.6	11	88	49	56	A	A	kept	
69	Bro004	1866.2	13	75	61	81	A	A	kept	
70	Bro012	2127.7	7	85	1	1	B	B	kept	
71	Bro023	3492.6	14	202	150	74	B	B	kept	
72	Bmr009	429.6	11	55	40	73	A	A	kept	
73	Bed010	2902.1	13	84	55	65	A	A	kept	
74	Bro007	1618.4	7	43	5	12	B	B	kept	
75	Bro026	2907.4	7	95	1	1	A	A	kept	
76	Bro026	193.2	12	55	39	71	A	A	kept	
77	Bro017	1661.9	12	70	41	59	B	B	kept	
78	Bmr006	2068.6	8	57	27	47	A	A	kept	
79	Bed014	2997.4	14	145	–	–	B	A†	reassigned	a letter covers two participants
80	Bmr010	2417.0	8	68	21	31	A	A	kept	
81	Bro017	1031.2	15	214	155	72	B	B	kept	
82	Bed005	2361.9	17	92	72	78	B	B	kept	
83	Bro005	1937.1	8	77	34	44	B	B	kept	
84	Bro017	161.4	16	238	141	59	A	A	kept	
85	Bro008	264.4	9	114	52	46	B	B	kept	
86	Bed008	4062.8	7	46	2	4	B	B	kept	
87	Bro007	8.2	47	197	187	95	A	A	kept	
88	Bro028	3057.3	7	92	–	–	B	A†	reassigned	a letter covers two participants
89	Bro010	170.5	10	93	54	58	A	A	kept	
90	Bmr007	645.4	7	88	1	1	A	A	kept	
91	Bro010	1522.3	12	132	76	58	B	B	kept	
92	Bro018	276.6	8	76	47	62	B	B	kept	
93	Bmr025	219.4	8	75	38	51	A	A	kept	
94	Bed011	1688.3	10	78	47	60	A	A	kept	
95	Bro027	2973.0	13	170	102	60	A	A	kept	
96	Bro004	703.2	24	139	119	86	A	A	kept	
97	Bed004	1947.2	35	295	255	86	B	B	kept	
98	Bro014	2034.0	6	66	0	0	B	B	kept	
99	Bro019	1835.1	8	55	11	20	A	A	kept	
100	Bed002	420.1	12	107	58	54	B	B	kept	
101	Bro004	3620.1	22	93	81	87	B	B	kept	
102	Bmr026	1655.9	9	104	–	–	B	B	reassigned	a letter covers two participants
103	Bmr005	1882.2	21	190	145	76	A	A	kept	
104	Bmr015	2175.0	7	96	21	22	B	B	kept	
105	Bmr024	2201.3	25	127	107	84	B	B	kept	
106	Bro018	2115.4	11	63	42	67	A	A	kept	
107	Bro012	3103.6	8	116	2	2	B	B	kept	
108	Bro016	2392.7	16	73	48	66	B	B	kept	third participant
109	Bro022	2026.3	9	62	38	61	B	B	kept	
110	Bro028	449.3	19	112	103	92	B	B	kept	
111	Bro026	2536.3	12	126	–	–	B	A†	reassigned	a letter covers two participants
112	Bro019	2258.2	16	161	85	53	B	B	kept	

ID	Meeting	Start	Seg.	Words	Misplaced	%	Rel.	Reb.	Letters	Note
113	Bed008	2944.1	13	79	–	–	A	A	reassigned	a letter covers two participants
114	Bro018	705.3	10	65	51	78	A	A	kept	
115	Bro018	2418.2	22	186	136	73	B	B	kept	
116	Bmr007	1128.4	10	83	–	–	A	A	reassigned	a letter covers two participants
117	Bed004	3046.9	17	111	102	92	B	B	kept	
118	Bro012	1095.0	12	86	15	17	B	B	kept	
119	Bro017	2942.0	8	43	–	–	A	B†	reassigned	a letter covers two participants
120	Bro026	248.3	13	93	74	80	B	B	kept	
121	Bro017	2039.3	19	160	–	–	B	A†	reassigned	a letter covers two participants
122	Bro018	1186.9	25	347	331	95	A	A	kept	third participant
123	Bed004	3228.2	10	80	45	56	A	A	kept	
124	Bro028	130.7	7	22	3	14	A	A	kept	
125	Bro024	1896.6	11	96	47	49	B	B	kept	
126	Bmr024	2244.4	24	122	104	85	B	B	kept	
127	Bro016	2058.3	7	30	2	7	A	A	kept	
128	Bmr009	525.8	11	32	–	–	B	B	reassigned	a letter covers two participants
129	Bed010	571.6	9	50	29	58	A	A	kept	
130	Bmr016	107.0	6	51	0	0	A	A	kept	
131	Bro017	530.2	7	37	16	43	A	A	kept	
132	Bmr006	1533.8	11	61	–	–	A	A	reassigned	a letter covers two participants
133	Bro027	3033.0	14	139	70	50	A	A	kept	
134	Bro013	56.7	9	44	24	55	B	B	kept	
135	Bro008	683.9	18	262	236	90	A	A	kept	
136	Bmr006	2774.4	6	73	–	–	A	A	reassigned	a letter covers two participants
137	Bro027	2603.4	15	93	78	84	A	A	kept	
138	Bro017	779.8	11	103	47	46	B	B	kept	
139	Bmr013	1012.2	14	92	72	78	A	A	kept	
140	Bed009	1365.9	9	81	37	46	A	A	kept	
141	Bro019	102.1	16	107	59	55	B	B	kept	
142	Bed005	3404.3	19	144	96	67	A	A	kept	
143	Bro023	1185.4	9	88	39	44	A	A	kept	
144	Bro003	4872.2	9	87	27	31	A	A	kept	
145	Bmr005	4210.8	8	104	43	41	A	A	kept	
146	Bed002	1965.5	11	90	52	58	B	B	kept	
147	Bed009	2960.8	16	102	84	82	A	A	kept	
148	Bro005	1470.7	7	20	5	25	A	A	kept	
149	Bro017	1433.0	6	52	0	0	A	A	kept	
150	Bed008	1505.7	11	44	14	32	A	A	kept	