

*.DDT FILE

Definition

EXAMPLE:

;0;1;PREM;0;11;PREM;0;14;11.2,11.2,C,F;movenum;TBLOFF,PR013001;N;N;N;N;11200;630;12010;

1 2 3 4 5 6 7 8 9 10 11 12 - 15 16 17 18

#	Max Length	DESCRIPTION
1	4	Source File Number. Default = 0 (Not used in POINT IN DocProd)
2	4	Source record OCCURRENCE number (Always start at 1)
3	17	Source record FIELD name from ExtrFile. Refer to offset files, PTDOFFFL.DAT and PGMOFFFL.DAT
4	4	Offset into the Source Record Field. Default = 0, meaning begin at the first position of the field.
5	4	Source Record Field length or length of data to be retrieved from the source record field
6	17	Destination Field Name on the IMAGE
7	4	Offset into the Destination Field on the IMAGE. Default = 0
8	4	Destination Field Length on the IMAGE
9	32	Format Mask or blank
10	32	Rule Name – not case sensitive (It will be upper cased during processing)
11	1024	Data Parm Area – Refer to the rule used for this format
12	1	Processing Flag (Y/N) – Default =N
13	1	Processing Flag (Y/N) – Default =N
14	1	Processing Flag (Y/N) – Default =N (Y If field is WIP)
15	1	Processing Flag (Y/N) – Default =N
16		X coord from the left edge
17		Y coord from the top edge
18		Font ID

Caveat:

This is to be used as a cheat sheet only.

You can also change the DDT file through the Image Editor when you double click on a field.

For complete documentation, refer to CSC Technical User Guide – beginning at Page 121