

Document Production (C.0)

Technical User Guide for Exceed

The Document Production *Technical User Guide for Exceed* provides information on Document Production functions and utilities that only apply to CSC's Exceed enterprise system.

Revision date - November 20, 2007



© 2008 Computer Sciences Corporation. El Segundo, California. All rights reserved. No part of this publication may be reproduced by any means without written permission from Computer Sciences Corporation. Printed in U.S.A. All questions regarding this documentation should be routed through customer assistance, Blythewood, SC, 803-333-6200 or email pcssupport@csc.com.

Table of Contents

Chapter 1: CSCOFFS/DDF File Utility	3
Overview.....	3
OFFSET File Utility Processing Program	3
Input Files	3
Output Files	4
Program Processing	5
Chapter 2: Document Change Log	7

Chapter 1: CSCOFFS/DDF File Utility

This chapter describes the CSCOFFS utility.

Overview

CSCOFFS is a utility that creates the OFFSETS file used in Document Production processing for Exceed. Document Production uses a process known as OFFSET File Processing, which references an offset file containing field datanames and their relative position within the data extract file. These offsets are used to map variable data from the extract file to Document Production documents.

The OFFSET file insulates the end-user from changes in the layout of the extract file.

OFFSET File Utility Processing Program

Program Name

CSCOFFS

Input Files

Filename

RECFILE.INI

Type

Sequential

Format

Fixed

Positions 1-19

Contains the data extract record name (for example, POLICY)

Position 20 on

Contains the copybooks used to make up the data extract record (for example, PEILTSQ,PEILB01)

Filename

OFSFLDNM.TBL

Type

Sequential

Format

Fixed

Positions 1-49

Contains the copybook field name (for example, EB01-AGT-COM-FCT)

Positions 50 on

Contains the document variable field name that corresponds to copybook field (for example, EB01AGTCOMFCT)

Filename

Copybook files (for example, PEILTSQ)

Type

Sequential

Output Files***Filename***

Offsfile.DAT (The filename will be generated for each run of the program.)

Type

Sequential

Filename

Offsfile.DDF (The filename will be generated for each run of the program.)

Type

Sequential

Filename

Report (The filename will be generated for each run of the program, and it will also match the offsfilename.)

Type

Sequential

Program Processing

- The OFSFLDNM.TBL file is read in and stored in two arrays, one to hold the copybook field name and one for the corresponding document variable field name. Once this is complete, the file is closed and is not accessed again for processing.
- After loading the field name arrays, the RECFILE.INI is opened. This file will be read one line at a time until the EOF.
- Positions one to nineteen will be extracted and stored. The remaining string will then be parsed looking for commas. The number of commas will determine the number of copybooks that are associated with that record. The individual copybooks will be extracted and stored in an array. This array will then be processed.
- The name of the copybook will be extracted from the array and then that copybook file will be opened. The copybook file will be read one line at a time and each line will be processed. If the line contains an "*" in column seven, the line will be omitted because it is only a comment. Otherwise, the string will be parsed and the field name and length extracted and stored in an array.
- Once every line for that copybook has been read and processed, the array (containing the field names and lengths) that was extracted from the copybook will be processed.

- The field names, the lengths, and any associated switches for that field will be pulled from the arrays. The field name will be compared to names loaded from the OFSFLDNM.TBL file.
- If the field is found in that list and there is a corresponding document variable field name, then a record will be added to the offssfile. Otherwise, a record will be added to the report file.
- Once all entries in the array are processed, the program will read in the next copybook, or if that was the last copybook for that current data extract record, the next record in the RECFILE.INI file will be read and processing will continue as mentioned above.
- The offssfile.DAT, offssfile.DDF, and report.DAT files will have a name generated each time the program is executed. The name of the offssfile will be OFF, followed by the current time in HHMMSS format. There will be one with a DAT extension and one with a DDF extension. Offssfile.DAT will contain the offset, the length, and the document variable field name. Offssfile.DDF will contain the information needed for a Data Dictionary entry. The file is delimited by semicolons and contains the record name, field name, length, and several constant fields.
- Only the records that have a match in the OFSFLDNM file will be written to the OFFXXXXXX.DAT and OFFXXXXXX.DDF files.
- The report file will be designated with an "R" followed by the HHMMSS format and will have a DAT extension. The time will only be received once. Therefore, the time value will be the same for all files for a single execution.
- The report file will be a listing of all the records that did not have a matching entry in OFSFLDNM or that had an entry but no document variable field name associated with it.
- All input files must reside in the same directory as the program. This includes all of the copybook files.
- The output files will also be created in the same working directory.

Chapter 2: Document Change Log

.....

Date	Release for which change sub made	Heading and heading where change made	Description	Initials