Madhavan Mukund

https://www.cmi.ac.in/~madhavan

Mathematics for Data Science 1 Week 10

BFS and DFS

Breadth first search

- Explore graph level by level
- Keep track of
 - \blacksquare visited : $V \rightarrow \{\mathsf{True},\mathsf{False}\}$
 - Queue of unexplored vertices
- BFS from vertex *j*
 - Set visited(j) = True
 - Add j to the queue
- Explore vertex i at head of queue
 - For edge (i, j), if visited(j) is False,
 - Set visited(*j*) to True
 - \blacksquare Append j to the queue
- Stop when queue is empty

BFS and DFS

Breadth first search

- Explore graph level by level
- Keep track of
 - lacktriangle visited : $V \rightarrow \{\mathsf{True},\mathsf{False}\}$
 - Queue of unexplored vertices
- BFS from vertex *j*
 - Set visited(j) = True
 - Add j to the queue
- Explore vertex i at head of queue
 - For edge (i, j), if visited(j) is False,
 - Set visited(*j*) to True
 - \blacksquare Append j to the queue
- Stop when queue is empty

Depth first search

- Start from i, visit an unexplored neighbour j
- Suspend the exploration of i and explore j instead
- Continue till you reach a vertex with no unexplored neighbours
- Backtrack to nearest suspended vertex that still has an unexplored neighbour
- Keep track of
 - visited : $V \rightarrow \{\mathsf{True},\mathsf{False}\}$
 - Stack of suspended vertices

Mathematics for Data Science 1, Week 10

- G = (V, E)
 - |V| = n
 - |E| = m
 - If G is connected, m can vary from n-1 to n(n-1)/2

- G = (V, E)
 - |V| = n
 - |E| = m
 - If G is connected, m can vary from n-1 to n(n-1)/2
- In both BFS and DFS, each reachable vertex is visited exactly once
 - Visit and explore at most *n* vertices

- \blacksquare G = (V, E)
 - |V| = n
 - |E| = m
 - If G is connected, m can vary from n-1 to n(n-1)/2
- In both BFS and DFS, each reachable vertex is visited exactly once
 - Visit and explore at most *n* vertices
- Each visited vertex is explored once
 - Check all outgoing edges
 - How long does this take?

- G = (V, E)
 - |V| = n
 - |E| = m
 - If G is connected, m can vary from n-1 to n(n-1)/2
- In both BFS and DFS, each reachable vertex is visited exactly once
 - Visit and explore at most *n* vertices
- Each visited vertex is explored once
 - Check all outgoing edges
 - How long does this take?

Adjacency matrix

- \blacksquare To explore *i*, scan row *i*
- Look up n entries, regardless of number of actual edges from i
 - Degree of i
- Overall, n^2 steps

- G = (V, E)
 - |V| = n
 - |E| = m
 - If G is connected, m can vary from n-1 to n(n-1)/2
- In both BFS and DFS, each reachable vertex is visited exactly once
 - Visit and explore at most *n* vertices
- Each visited vertex is explored once
 - Check all outgoing edges
 - How long does this take?

Adjacency matrix

- \blacksquare To explore *i*, scan row *i*
- Look up n entries, regardless of number of actual edges from i
 - Degree of i
- Overall, n^2 steps

Adjacency list

- To explore i, scan list of neighbours of i
- Time to explore *i* is degree of *i*
- Degree varies across vertices
- Estimate overall time?

Adjacency list

- To explore *i*, scan list of neighbours of *i*
- Time to explore *i* is degree of *i*
- Total time is the sum of the degrees

Adjacency list

- To explore *i*, scan list of neighbours of *i*
- Time to explore *i* is degree of *i*
- Total time is the sum of the degrees

Sum of degrees

- Each edge (*i*, *j*) contributes to degree of both *i* and *j*
- Sum of degrees is 2*m*

Adjacency list

- To explore i, scan list of neighbours of i
- Time to explore *i* is degree of *i*
- Total time is the sum of the degrees

Sum of degrees

- Each edge (*i*, *j*) contributes to degree of both *i* and *j*
- Sum of degrees is 2*m*

BFS/DFS with adjacency list

- n steps to visit each vertex
- 2m steps (sum of degrees) to explore all vertices
- Overall time proportional to n + m

Adjacency list

- To explore *i*, scan list of neighbours of *i*
- Time to explore *i* is degree of *i*
- Total time is the sum of the degrees

Sum of degrees

- Each edge (*i*, *j*) contributes to degree of both *i* and *j*
- Sum of degrees is 2*m*

BFS/DFS with adjacency list

- n steps to visit each vertex
- 2m steps (sum of degrees) to explore all vertices
- Overall time proportional to n + m

BFS/DFS with adjacency matrix

- n steps to visit each vertex
- n steps to explore each vertex
- Overall time proportional to n^2

Adjacency list

- To explore *i*, scan list of neighbours of *i*
- Time to explore *i* is degree of *i*
- Total time is the sum of the degrees

Sum of degrees

- Each edge (i, j) contributes to degree of both i and j
- Sum of degrees is 2*m*

BFS/DFS with adjacency list

- n steps to visit each vertex
- 2m steps (sum of degrees) to explore all vertices
- Overall time proportional to n + m

BFS/DFS with adjacency matrix

- n steps to visit each vertex
- n steps to explore each vertex
- Overall time proportional to n^2

If m is proportional to n, big saving by using adjacency list representation

Mathematics for Data Science 1. Week 10

■ Degree of a vertex *i* is

- Degree of a vertex *i* is
 - Number of 1's in row i of adjacency matrix

- Degree of a vertex *i* is
 - Number of 1's in row i of adjacency matrix
 - Number of 1's in column i of adjacency matrix

- Degree of a vertex *i* is
 - Number of 1's in row i of adjacency matrix
 - Number of 1's in column i of adjacency matrix
 - Length of adjacency list for i

- Degree of a vertex *i* is
 - Number of 1's in row i of adjacency matrix
 - Number of 1's in column i of adjacency matrix
 - Length of adjacency list for i
- Sum of degrees is 2*m*

- Degree of a vertex *i* is
 - Number of 1's in row i of adjacency matrix
 - Number of 1's in column i of adjacency matrix
 - Length of adjacency list for i
- Sum of degrees is 2*m*
 - Sum is an even number

- Degree of a vertex *i* is
 - Number of 1's in row i of adjacency matrix
 - Number of 1's in column i of adjacency matrix
 - Length of adjacency list for i
- Sum of degrees is 2*m*
 - Sum is an even number
 - For each vertex with odd degree, must be another vertex of odd degree to make the sum even

- Degree of a vertex *i* is
 - Number of 1's in row i of adjacency matrix
 - Number of 1's in column i of adjacency matrix
 - Length of adjacency list for i
- Sum of degrees is 2*m*
 - Sum is an even number
 - For each vertex with odd degree, must be another vertex of odd degree to make the sum even
 - Number of vertices of odd degree is even

- Degree of a vertex *i* is
 - Number of 1's in row i of adjacency matrix
 - Number of 1's in column i of adjacency matrix
 - Length of adjacency list for i
- Sum of degrees is 2*m*
 - Sum is an even number
 - For each vertex with odd degree, must be another vertex of odd degree to make the sum even
 - Number of vertices of odd degree is even

- Degree of a vertex between 0 and n-1
 - Degree 0 disconnected vertex
 - Degree n-1 connected to all other vertices

- Degree of a vertex *i* is
 - Number of 1's in row i of adjacency matrix
 - Number of 1's in column i of adjacency matrix
 - Length of adjacency list for i
- Sum of degrees is 2*m*
 - Sum is an even number
 - For each vertex with odd degree, must be another vertex of odd degree to make the sum even
 - Number of vertices of odd degree is even

- Degree of a vertex between 0 and n-1
 - Degree 0 disconnected vertex
 - Degree n-1 connected to all other vertices
- Complete graph every vertex has degree n-1

- Degree of a vertex *i* is
 - Number of 1's in row i of adjacency matrix
 - Number of 1's in column i of adjacency matrix
 - Length of adjacency list for i
- Sum of degrees is 2*m*
 - Sum is an even number
 - For each vertex with odd degree, must be another vertex of odd degree to make the sum even
 - Number of vertices of odd degree is even

- Degree of a vertex between 0 and n-1
 - Degree 0 disconnected vertex
 - Degree n-1 connected to all other vertices
- Complete graph every vertex has degree n-1
- If all degrees are bounded by k, at most kn/2 edges

- Degree of a vertex *i* is
 - Number of 1's in row i of adjacency matrix
 - Number of 1's in column i of adjacency matrix
 - Length of adjacency list for i
- Sum of degrees is 2*m*
 - Sum is an even number
 - For each vertex with odd degree, must be another vertex of odd degree to make the sum even
 - Number of vertices of odd degree is even

- Degree of a vertex between 0 and n-1
 - Degree 0 disconnected vertex
 - Degree n-1 connected to all other vertices
- Complete graph every vertex has degree n-1
- If all degrees are bounded by k, at most kn/2 edges
- For directed graphs, indegree and outdegree

- Degree of a vertex *i* is
 - Number of 1's in row i of adjacency matrix
 - Number of 1's in column i of adjacency matrix
 - Length of adjacency list for i
- Sum of degrees is 2*m*
 - Sum is an even number
 - For each vertex with odd degree, must be another vertex of odd degree to make the sum even
 - Number of vertices of odd degree is even

- Degree of a vertex between 0 and n-1
 - Degree 0 disconnected vertex
 - Degree n-1 connected to all other vertices
- Complete graph every vertex has degree n-1
- If all degrees are bounded by k, at most kn/2 edges
- For directed graphs, indegree and outdegree
- Sum of indegrees = m = Sum of outdegrees

Summary

- BFS and DFS with adjacency matrix time proportional to n^2
- BFS and DFS with adjacency list time proportional to n + m
 - Exploring vertices examines each edge twice, sum of the degrees, 2m steps
- For a connected graph, m varies from n-1 to n(n-1)/2
- Considerable saving with small m
 - All degrees bounded by k, at most kn/2 edges