



Incident report analysis

Instructions

As you continue through this course, you may use this template to record your findings after completing an activity or to take notes on what you've learned about a specific tool or concept. You can also use this chart as a way to practice applying the NIST framework to different situations you encounter.

Summary	Not long ago my organisation faced an attack(DoS), where the organisation network server went down for two hours. The server stopped responding because it was being flooded with ICMP packets. The team responded by blocking the coming ICMP packets, shutting down less important network services and restoring critical ones. The cyber team investigated the incident and come to conclusion that there was unconfigured firewall through which the malicious actor flooded with ping of ICMP packets to the organisation's network thereby overwhelming the network through DoS attack.
Identify	The incident and cybersecurity team of the organizations investigated the incident and found a gap in the security. They found that the organisation network was compromised by a malicious attacker by flooding ping of ICMP packets through an unconfigured firewall in the organization network system thereby overwhelming the organisation's network through DoS attack.
Protect	The network security team implemented a firewall rule to limit the rate at which ICMP packets are allowed to enter the network. Additionally, IDS/ IPS system was implemented to filter and prevent known threat signatures and anomalies on incoming ICMP packets.
Detect	To detect new unauthorized entry or network interception, the team

	implemented source IP addresses verification on the firewall to check spoofed IP addresses on incoming ICMP packets. Also a monitoring software was installed to detect abnormal traffic patterns.
Respond	For future security events the cybersecurity team will isolate the affected system to prevent more damage to the rest of the system. They will try and restore the critical network services that were affected by the events. Also the team will analyze logs to find suspicious and abnormal activities and report all processes to upper management.
Recover	To recover from a DDoS attack by ICMP flooding, access to network services need to be restored to a normal functioning state. In the future, external ICMP flood attacks can be blocked at the firewall. Then, all non-critical network services should be stopped to reduce internal network traffic. Next, critical network services should be restored first. Finally, once the flood of ICMP packets have timed out, all non-critical network systems and services can be brought back online.

Reflections/Notes: