

P4 - Encryption Scheme

Most text encryption schemes use a secret key string to convert the plain text to the enciphered text in some way. A novel method being tested by the Australian Security Service consists of a transformation of a key string K into a target string P using block moves. Each *block move* is of the form $copy(start, length)$, where $start$ indicates a position in K and $length$ is the number of characters to be copied from K to P . Since the idea is to eventually transmit only the block moves, the principle is to use as few block moves as possible. For example if:

K: abaabba P: aaabbbabbbbaaa

Assuming that here string positions start with 1, two shortest block move sequences would be:

$copy(3,2);copy(4,3);copy(2,2);copy(5,2);copy(2,3);copy(1,1)$

or

$copy(7,1);copy(3,3);copy(5,2);copy(4,2);copy(5,3);copy(3,2)$

The actual shortest block move sequences are not unique but the minimum number is, 6 in this case. If the moves are now transmitted, then it is possible to construct the plaintext message P from the key string K .

The Australian Security Service is now automating this procedure, so given K and P they need to count the minimum number of block moves from K to P . To make things simple at the beginning, they are considering strings comprised of lowercase letters and digits. The set of characters within string P is a subset of the set of characters of the key string K .

You are to help the Australian Security Service by writing a program to get two strings K and P as above, and print the minimum number of block moves from K to P . Your code will be tested with a sequence of lines. Odd lines are to be used as the key strings K , and even lines to be used as target strings P . The output will consist solely of the minimum number of block moves for each pair. The input will be terminated by a '#' by itself in the place of a K string.

Assume that each of K and P is made up of 1 to 120 characters (K is allowed to be longer than P).

SAMPLE INPUT

```
abaabba  
aaabbbabbbaaa  
xy0z  
zzz0yyy0xxx  
#
```

SAMPLE OUTPUT

```
6  
10
```

COMMENTS

The first sample is discussed on the first page. Here follows a minimal sequence of block moves for the second sample:

```
copy(4,1);copy(4,1);copy(4,1);copy(3,1);  
copy(2,1);copy(2,1);copy(2,2);  
copy(1,1);copy(1,1);copy(1,1)
```