

cqs — Admin & Packaging Cheat Sheet

For maintainers: build, package, publish, and distribute cqs offline

OFFLINE INSTALL ARTEFACT
cqs-audit-2.1.0.tgz
npm pack → copy → install

✓ Verify: **cqs --list-stacks**

v2.1.0

A • Build, Package & Distribute

Build the bundles → pack a .tgz → install it on a machine with no npm access

ADMIN — BUILD & DISTRIBUTE

```
# First-time setup — clone, then build
git clone https://github.com/mv-vasanth/\
  code-quality-studio.git
cd code-quality-studio/cli
npm install
npm run build:all
npm install -g .
```

```
# Create shareable tarball
npm run build && npm pack
# → cqs-audit-2.1.0.tgz
```

```
# Publish to npm (bump version first)
npm run build && npm publish --access
public
```

⚙️ Bump version: edit "version" in package.json before rebuilding

INSTALL FROM .TGZ (OFFLINE / INTERNAL)

```
# With admin rights
sudo npm install -g ./cqs-audit-2.1.0.tgz

# Without admin (no sudo)
npm install -g ./cqs-audit-2.1.0.tgz --
prefix ~/.npm-global
echo 'export PATH="$HOME/.npm-
global/bin:$PATH"' >> ~/.zshrc
source ~/.zshrc

# Windows
npm install -g .\cqs-audit-2.1.0.tgz
```

BUILD OUTPUTS & MCP SERVER

BUILD BOTH BUNDLES

```
# CLI + MCP server in one go
npm run build:all

# Or individually
npm run build
npm run build:mcp
```

ARTEFACTS PRODUCED

dist/cqs.js — the CLI (self-contained)
dist/cqs-mcp.js — the MCP server

VERSION IS AUTOMATIC

The build injects __CQS_VERSION__ from package.json .
Bump the version there only — never edit the string in source.

REGENERATE THIS CHEAT SHEET

```
chrome --headless=new --print-to-pdf=out.pdf
sheet.html
```

