

cqs — Code Quality Studio CLI

18 stacks · 533 rules · offline · CI-ready · Node 18+

INSTALL FROM NPM (ANYWHERE)

```
npm install -g cqs-audit
```

npmjs.com/package/cqs-audit

✓ Verify: **cqs --version**

v2.3.3

1 · Install & Everyday Use

Install → verify → run your first audit

2 AI-Assisted Review

INSTALL FROM NPM (PUBLIC — ANY MACHINE)

AI SETUP — ANTHROPIC & OPENAI

npm install -g cqs-audit
ANTHROPIC (CLAUDE)

```
# 1. Key from console.anthropic.com
# 2. Persist it in your shell profile
echo 'export ANTHROPIC_API_KEY=sk-ant-xxx' >> ~/.zshrc
source ~/.zshrc
# 3. Run — key picked up automatically
cqs ./tests/ --ai anthropic
```

OPENAI (GPT)

```
# 1. Key from platform.openai.com
echo 'export OPENAI_API_KEY=sk-xxx' >> ~/.zshrc
source ~/.zshrc
# 2. Run (default model gpt-4o-mini)
cqs ./tests/ --ai openai
```

Set the key **once** — every later run reads it from the environment.

NEW IN 2.3.3 — BEHAVIOUR CHANGES

AI SETUP — BEDROCK & VERTEX

AWS BEDROCK **json / summary** and when piped, so CI stays clean. **--no-report** prints out

```
echo 'export AWS_REGION=us-east-1' >> ~/.zshrc
echo 'export AWS_ACCESS_KEY_ID=AKIAxxx' >> ~/.zshrc
echo 'export AWS_SECRET_ACCESS_KEY=xxx' >> ~/.zshrc
source ~/.zshrc
cqs ./tests/ --ai bedrock
```

GOOGLE VERTEX AI

```
# Service-account JSON from the GCP console
echo 'export VERTEX_PROJECT=my-proj' >> ~/.zshrc
echo 'export VERTEX_LOCATION=us-central1' >> ~/.zshrc
echo 'export GOOGLE_APPLICATION_CREDENTIALS=~/.sa.json' >> ~/.zshrc
source ~/.zshrc
cqs ./tests/ --ai vertex
```

INLINE (CI — no env var)

```
cqs ./tests/ --ai anthropic --api-key sk-ant-xxx
cqs ./tests/ --ai openai --api-key sk-xxx
cqs ./tests/ --ai bedrock --aws-region us-east-1 \
  --aws-access-key KEY --aws-secret-key SECRET
cqs ./tests/ --ai vertex --vertex-project proj \
  --vertex-location us-central1 --vertex-key-file sa.json
```

Set up MCP key so that every run can include an AI second eye

CORE COMMANDS

CORE AI COMMANDS (AFTER KEY IS SET)

cqs . Analyse current folder —

```
# Audit with AI second-eye review
cqs ./tests/ --stack playwright --ai anthropic
cqs ./tests/ --stack playwright --ai openai
cqs ./tests/ --stack playwright --ai bedrock
cqs ./tests/ --stack playwright --ai vertex
```

cqs ./tests/ Show only critical findings

```
# Review only the critical files
cqs ./tests/ --ai anthropic --severity critical
```

```
# AI review + open HTML report
cqs ./tests/ --ai anthropic --open
```

```
# AI review + save JSON
cqs ./tests/ --ai anthropic --output json > r.json
```

PICK A TESTS/ER-MODEL Terminal output only — skip

```
cqs ./tests/ --ai anthropic --model claude-sonnet-5
cqs ./tests/ --ai openai --model gpt-4o
```

cqs --read-report report.json A review run after the offline rules and only on files that already have critical or warning findings. Print summary of a saved JSON report

cqs --read-report report.json --open Open saved report as HTML in browser

cqs --list-stacks Show all 18 available stacks + IDs

cqs --version Print the installed version (also **-v**)

cqs mcp-config cursor Print ready-to-paste MCP config (or **claude**)

3 · CI/CD, Output Formats & Packaging

CI / CD INTEGRATION

GITHUB ACTIONS

ALL 18 STACKS (--STACK <ID>)

- name: Audit test quality

run: cqs ./tests/ --output summary

exit 1 on criticals = failed step

playwright_python

selenium_java

quality-gate:

script: cqs ./tests/ --output json > r.json

artifacts: { paths: [r.json] }

PRE-COMMIT HOOK

restassured

karate

cqs . --severity critical --output summary

|| exit 1

java_api

java_frontend

typescript

ts_frontend

python_api

python_frontend

OUTPUT FORMATS & ADVANCED

pretty

 Colour terminal — scores, findings, bars (default)

json

 Machine-readable — pipe to file for CI artefacts

summary

 One-liner: score 90 · 5 critical · 12 warning

ADVANCED COMMANDS

Filter by category

cqs ./tests/ --category reliability

Multiple paths

cqs ./src/tests/ ./e2e/ --stack playwright

Plain text (no ANSI — for log files)

cqs ./tests/ --no-color

Save + open later

cqs ./tests/ --output json > r.json

cqs --read-report r.json --open

COMMAND	DESCRIPTION
cqs --help	Show help text and version number

USING CQS WITH CURSOR IDE

OPTION 1 — Terminal inside Cursor

```
# Open terminal in Cursor (Ctrl+`), then
run normally
cqs ./tests/ --stack playwright --open
# HTML report opens in your default browser
```

OPTION 2 — Cursor Task (tasks.json)

```
// .vscode/tasks.json
"tasks": [{
  "label": "cqs audit",
  "type": "shell",
  "command": "cqs ${workspaceFolder}/tests/ --open",
  "group": "test"
}]
```

OPTION 3 — Cursor AI + cqs together

1. Run: `cqs ./tests/ --output json > r.json`
2. Open `r.json` in Cursor
3. Ask Cursor AI: "Fix the critical findings in this report"
4. Cursor reads the JSON + your test files and applies fixes

MCP SERVER — CQS AS AN AI TOOL

BUILD THE MCP SERVER

```
# From the cqs CLI source directory
cd code-quality-studio/cli
node build-mcp.mjs
# → produces dist/cqs-mcp.js
```

CONFIG — SAME JSON FOR BOTH CLIENTS

```
{
  "mcpServers": {
    "cqs": {
      "command": "node",
      "args": ["/abs/path/dist/cqs-mcp.js"]
    }
  }
}
```

Cursor → `.cursor/mcp.json`

Claude Code → `~/.claude/settings.json`

MCP TOOLS EXPOSED

`cqs_audit` — audit a path, returns findings
`cqs_list_stacks` — list all 18 supported stacks
`cqs_read_report` — summarise a JSON report file

Once registered, ask the AI: "Audit my tests folder" — the AI calls `cqs_audit` automatically.

CLAUDE CODE /CQS SKILL

INSTALL THE SKILL (one-time)

```
# Create the skill directory
mkdir -p ~/.claude/skills/cqs

# Copy SKILL.md from the cqs repo
cp cli/bin/cqs-skill.md
~/.claude/skills/cqs/SKILL.md
```

```
# Or download directly (if cqs-audit is
installed globally)
cqs --version # verify cqs is working
```

USE IN CLAUDE CODE SESSION

```
# In any Claude Code session, just type:
/cqs

# Claude will ask you for the path, then
run the audit
# and summarise findings directly in the
conversation
```

EXAMPLE PROMPTS WITH SKILL

```
"Audit my tests and fix all critical issues"
"Run cqs on ./e2e/ and summarise what's wrong"
"Check my Playwright tests for quality issues"
"Review ./tests/ with AI — use Anthropic"
```

SKILL FILE LOCATION

```
~/.claude/skills/cqs/SKILL.md
```

Claude Code auto-loads skills from `~/.claude/skills/` — no restart needed after adding SKILL.md.

 REMEDIATION AGENT

Fixes findings in place. Every fix is re-audited before it is kept.

PREVIEW FIRST

```
cqs remediate ./tests/ --ai anthropic \
  --dry-run
# prints the diff, writes nothing
```

APPLY

```
cqs remediate ./tests/ --ai anthropic

# apply on a branch and commit
cqs remediate ./tests/ --ai anthropic \
  --branch fix/cqs --commit
```

FLAGS

`--severity` what to fix (default critical)

`--max-files` cap per run (default 10)

`--force` write even if git is dirty

`--provider` alias for `--ai`

 PR REVIEW BOT

Audits the files a PR changed and posts one review with inline comments.

IN GITHUB ACTIONS — NO FLAGS

```
cqs pr-review --stack playwright \
  --threshold 80
# repo, PR and token come from the env
```

MANUALLY, AGAINST ANY PR

```
cqs pr-review --repo owner/name --pr 42 \
  --token ghp_xxx --dry-run
```

WORKFLOW PERMISSION

```
permissions:
  contents: read
  pull-requests: write
```

`--threshold` exits non-zero below the score

`--only-added` comment only on added lines

`--max-comments` cap inline comments (30)

 WHAT STOPS A BAD FIX

Both agents re-audit before trusting AI output. A fix is **rejected** when it:

- introduces a new critical finding
- leaves the file unchanged
- returns no code block
- drops more than half the file

THE CLASSIC CHEAT

Deleting an assertion removes the finding but leaves a test that verifies nothing. Re-auditing catches it — the missing assertion is itself a critical.

GIT SAFETY

remediate refuses to write unless the tree is clean, so every applied fix is revertable with `git checkout`.