

 cqs — Admin & Packaging Cheat Sheet

For maintainers: build, package, publish, and distribute cqs offline

OFFLINE INSTALL ARTEFACT
cqs-audit-2.1.0.tgz
npm pack → copy → install

✓ Verify: **cqs --list-stacks**

v2.1.0

A • Build, Package & Distribute

Build the bundles → pack a .tgz → install it on a machine with no npm access

 **ADMIN — BUILD & DISTRIBUTE**

```
# First-time setup
cd playwright-quality-studio/cli
npm install
npm run build
npm install -g .

# Create shareable tarball
npm run build && npm pack
# → cqs-audit-2.1.0.tgz

# Publish to npm (bump version first)
npm run build && npm publish --access public
```

 Bump version: edit "version" in package.json before rebuilding

 **INSTALL FROM .TGZ (OFFLINE / INTERNAL)**

```
# With admin rights
sudo npm install -g ./cqs-audit-2.1.0.tgz

# Without admin (no sudo)
npm install -g ./cqs-audit-2.1.0.tgz --
prefix ~/.npm-global
echo 'export PATH="$HOME/.npm-global/bin:$PATH"' >> ~/.zshrc
source ~/.zshrc

# Windows
npm install -g .\cqs-audit-2.1.0.tgz
```

 **BUILD OUTPUTS & MCP SERVER**

BUILD BOTH BUNDLES

```
# CLI + MCP server in one go
npm run build:all

# Or individually
npm run build
npm run build:mcp
```

ARTEFACTS PRODUCED

dist/cqs.js — the CLI (self-contained)

dist/cqs-mcp.js — the MCP server

VERSION IS AUTOMATIC

The build injects __CQS_VERSION__ from package.json . Bump the version there only — never edit the string in source.

REGENERATE THIS CHEAT SHEET

```
chrome --headless=new --print-to-pdf=out.pdf
sheet.html
```