

Supply Chain Data Dictionary

Asterion Devices — SCS.INVENTORY (Snowflake)

37 tables, 214 columns — table and column names, data types, keys, relationships, and business meaning

Generated from 01_base_tables_and_data.sql via the ontology catalog
(ontology/supply_chain_catalog.json).

Table Index

Table	Cols	Description
DIM_DATE	11	Calendar dimension from 2022-01-01 to 2026-12-31
DIM_GEO_REGION	2	Geographic regions
DIM_GEO_COUNTRY	4	Countries mapped to regions
DIM_COMMODITY	2	Top-level commodity classification
DIM_SUB_COMMODITY	3	Sub-commodity classification
DIM_CURRENCY	3	Currency reference with approximate USD exchange rates
DIM_UOM	2	Units of measure
DIM_INCOTERM	2	Incoterms 2020
DIM_PORT	5	Major ports and airports for logistics
DIM_SUPPLIER	9	Supplier master — 500 suppliers across commodities and countries
DIM_SUPPLIER_SITE	8	Supplier manufacturing and shipping sites
DIM_MANUFACTURER	3	Component manufacturers
DIM_PART	10	Part master — 30,000 parts across all commodities
DIM_PRODUCT_FAMILY	2	Finished product families
DIM_PRODUCT	5	Finished products — 500 SKUs
BOM_HEADER	5	Bill of Materials headers — one per product revision
BOM_LINE	5	BOM line items — components per assembly
DIM_PLANT	5	Manufacturing plants for Asterion Devices
DIM_WAREHOUSE	7	Warehouses — plant-attached and distribution centers
DIM_CUSTOMER	6	Customer master — 80 customers
DIM_CARRIER	3	Logistics carriers
DIM_LANE	6	Shipping lanes between ports
DIM_CONTRACT	8	Supplier contracts
SUPPLIER_PART_APPROVAL	6	Approved supplier-part combinations — 40,000 rows
PO_HEADER	7	Purchase order headers — 20,000 POs
PO_LINE	6	Purchase order line items — 60,000 lines
GOODS_RECEIPT	6	Goods receipts — 90,000 receipts against PO lines
SALES_ORDER_HEADER	6	Customer sales order headers — 10,000 orders
SALES_ORDER_LINE	6	Sales order line items — 40,000 lines
SHIPMENT_HEADER	6	Shipment headers — 18,000 shipments
SHIPMENT_LINE	5	Shipment line items linking to orders or POs
SHIPMENT_MILESTONE_EVENT	5	Shipment tracking milestones — 250,000 events
IOT_SENSOR_READING	10	IoT container sensor readings — 500,000 rows, ~1.5% breach rate
WORK_ORDER	7	Manufacturing work orders — 10,000
QUALITY_INSPECTION	9	Incoming quality inspections — 10,000
NONCONFORMANCE_REPORT	10	Non-conformance reports — 1,000 NCRs
FACT_INVENTORY_SNAPSHOT	9	Inventory snapshots — ~1.2M rows (part x warehouse x month-end)

DIM_DATE

Calendar dimension from 2022-01-01 to 2026-12-31

aka: Calendar Date, date, day, calendar, time dimension • referenced by: FACT_INVENTORY_SNAPSHOT.SNAPSHOT_DATE

Column	Type	Key	Description / business meaning	Synonyms & sample values
DATE_KEY	DATE	PK	—	—
YEAR	INT	NOT NULL	—	—
QUARTER	INT	NOT NULL	—	—
MONTH	INT	NOT NULL	—	—
MONTH_NAME	VARCHAR(10)	NOT NULL	—	values: Apr, Aug, Dec, Feb, Jan, Jul, Jun, Mar ...
WEEK_OF_YEAR	INT	NOT NULL	—	—
DAY_OF_WEEK	INT	NOT NULL	—	—
DAY_NAME	VARCHAR(10)	NOT NULL	—	values: Fri, Mon, Sat, Sun, Thu, Tue, Wed
IS_WEEKEND	BOOLEAN	NOT NULL	—	—
FISCAL_YEAR	INT	NOT NULL	—	—
FISCAL_QUARTER	INT	NOT NULL	—	—

DIM_GEO_REGION

Geographic regions

aka: Region, geography, geo region, world region • referenced by: DIM_GEO_COUNTRY.REGION_ID

Column	Type	Key	Description / business meaning	Synonyms & sample values
REGION_ID	INT	PK	—	—
REGION_NAME	VARCHAR(50)	NOT NULL	—	—

DIM_GEO_COUNTRY

Countries mapped to regions

aka: Country, nation, country of origin • references: DIM_GEO_REGION.REGION_ID • referenced by: DIM_CUSTOMER.COUNTRY_ID, DIM_MANUFACTURER.COUNTRY_ID, DIM_PLANT.COUNTRY_ID, DIM_PORT.COUNTRY_ID, DIM_SUPPLIER.COUNTRY_ID, DIM_SUPPLIER_SITE.COUNTRY_ID, DIM_WAREHOUSE.COUNTRY_ID

Column	Type	Key	Description / business meaning	Synonyms & sample values
COUNTRY_ID	INT	PK	—	—
COUNTRY_NAME	VARCHAR(50)	NOT NULL	—	—
COUNTRY_CODE	VARCHAR(3)	NOT NULL	—	—
REGION_ID	INT	NOT NULL / FK→ DIM_GEO_REGION.REGION_ID	—	—

DIM_COMMODITY

Top-level commodity classification

aka: Commodity, category, commodity group, spend category • referenced by: DIM_PART.COMMODITY_ID, DIM_SUB_COMMODITY.COMMODITY_ID, DIM_SUPPLIER.COMMODITY_ID

Column	Type	Key	Description / business meaning	Synonyms & sample values
COMMODITY_ID	INT	PK	—	—
COMMODITY_NAME	VARCHAR(50)	NOT NULL	—	—

DIM_SUB_COMMODITY

Sub-commodity classification

aka: Sub-Commodity, subcategory, sub commodity • references: DIM_COMMODITY.COMMODITY_ID • referenced by: DIM_PART.SUB_COMMODITY_ID

Column	Type	Key	Description / business meaning	Synonyms & sample values
SUB_COMMODITY_ID	INT	PK	—	—
SUB_COMMODITY_NAME	VARCHAR(80)	NOT NULL	—	—
COMMODITY_ID	INT	NOT NULL / FK→ DIM_COMMODITY.COMMODITY_ID	—	—

DIM_CURRENCY

Currency reference with approximate USD exchange rates

aka: Currency, fx, currency code • referenced by: DIM_CONTRACT.CURRENCY_CODE, PO_HEADER.CURRENCY_CODE

Column	Type	Key	Description / business meaning	Synonyms & sample values
CURRENCY_CODE	VARCHAR(3)	PK	—	values: BRL, CNY, EUR, GBP, INR, JPY, KRW, MXN ...
CURRENCY_NAME	VARCHAR(50)	NOT NULL	—	—
TO_USD_RATE	DECIMAL(10,4)	NOT NULL	Approximate fixed rate for demo	—

DIM_UOM

Units of measure

aka: Unit of Measure, uom, unit • referenced by: DIM_PART.UOM_CODE

Column	Type	Key	Description / business meaning	Synonyms & sample values
UOM_CODE	VARCHAR(5)	PK	—	values: BOX, EA, FT, KG, L, LB, M, PAL ...
UOM_NAME	VARCHAR(30)	NOT NULL	—	—

DIM_INCOTERM

Incoterms 2020

aka: Incoterm, shipping terms, trade terms, incoterms 2020 • referenced by: DIM_CONTRACT.INCOTERM_CODE

Column	Type	Key	Description / business meaning	Synonyms & sample values
INCOTERM_CODE	VARCHAR(3)	PK	—	values: CFR, CIF, CIP, CPT, DAP, DDP, DPU, EXW ...
INCOTERM_NAME	VARCHAR(50)	NOT NULL	—	—

DIM_PORT

Major ports and airports for logistics

aka: Port, seaport, airport, terminal • references: DIM_GEO_COUNTRY.COUNTRY_ID • referenced by: DIM_LANE.DEST_PORT_ID, DIM_LANE.ORIGIN_PORT_ID

Column	Type	Key	Description / business meaning	Synonyms & sample values
PORT_ID	INT	PK	—	—
PORT_NAME	VARCHAR(80)	NOT NULL	—	—
PORT_CODE	VARCHAR(10)	NOT NULL	—	—
COUNTRY_ID	INT	NOT NULL / FK→ DIM_GEO_COUNTRY.COUNTRY_ID	—	—
PORT_TYPE	VARCHAR(10)	NOT NULL	SEA, AIR, or BOTH	values: AIR, BOTH, SEA

DIM_SUPPLIER

Supplier master — 500 suppliers across commodities and countries

aka: Supplier, vendor, supplier master, source, seller • references: DIM_COMMODITY.COMMODITY_ID, DIM_GEO_COUNTRY.COUNTRY_ID • referenced by: DIM_CONTRACT.SUPPLIER_ID, DIM_SUPPLIER_SITE.SUPPLIER_ID, NONCONFORMANCE_REPORT.SUPPLIER_ID, PO_HEADER.SUPPLIER_ID, QUALITY_INSPECTION.SUPPLIER_ID, SUPPLIER_PART_APPROVAL.SUPPLIER_ID

Column	Type	Key	Description / business meaning	Synonyms & sample values
SUPPLIER_ID	INT	PK	—	—
SUPPLIER_NAME	VARCHAR(200)	NOT NULL	—	—
SUPPLIER_CODE	VARCHAR(20)	NOT NULL	—	—
COUNTRY_ID	INT	NOT NULL / FK→ DIM_GEO_COUNTRY.COUNTRY_ID	—	—
COMMODITY_ID	INT	NOT NULL / FK→ DIM_COMMODITY.COMMODITY_ID	—	—
RELIABILITY_RATING	DECIMAL(3,2)	NOT NULL	0.00-1.00 scale	syn: reliability, supplier score, otd rating
IS_PROBLEM	BOOLEAN	—	Flagged problem supplier for demo scenarios	syn: problem supplier, at risk supplier, flagged supplier
ACTIVE	BOOLEAN	—	—	—
IS_SYNTHETIC	BOOLEAN	—	—	—

DIM_SUPPLIER_SITE

Supplier manufacturing and shipping sites

aka: Supplier Site, supplier facility, vendor site, manufacturing site • references: DIM_GEO_COUNTRY.COUNTRY_ID, DIM_SUPPLIER.SUPPLIER_ID • referenced by: SUPPLIER_PART_APPROVAL.SITE_ID

Column	Type	Key	Description / business meaning	Synonyms & sample values
SITE_ID	INT	PK	—	—
SUPPLIER_ID	INT	NOT NULL / FK→ DIM_SUPPLIER.SUPPLIER_ID	—	—
SITE_NAME	VARCHAR(200)	NOT NULL	—	—
CITY	VARCHAR(100)	NOT NULL	—	—
COUNTRY_ID	INT	NOT NULL / FK→ DIM_GEO_COUNTRY.COUNTRY_ID	—	—
LEAD_TIME_DAYS	INT	NOT NULL	Average lead time in calendar days	syn: lead time, replenishment lead time
IS_PRIMARY	BOOLEAN	—	—	—
ACTIVE	BOOLEAN	—	—	—

DIM_MANUFACTURER

Component manufacturers

aka: Manufacturer, oem, component manufacturer, mfr • references: DIM_GEO_COUNTRY.COUNTRY_ID

Column	Type	Key	Description / business meaning	Synonyms & sample values
MANUFACTURER_ID	INT	PK	—	—
MANUFACTURER_NAME	VARCHAR(200)	NOT NULL	—	—
COUNTRY_ID	INT	NOT NULL / FK→ DIM_GEO_COUNTRY.COUNTRY_ID	—	—

DIM_PART

Part master — 30,000 parts across all commodities

aka: Part, component, material, sku, item, part master • references: DIM_COMMODITY.COMMODITY_ID, DIM_SUB_COMMODITY.SUB_COMMODITY_ID, DIM_UOM.UOM_CODE • referenced by: BOM_LINE.PART_ID, FACT_INVENTORY_SNAPSHOT.PART_ID, NONCONFORMANCE_REPORT.PART_ID, PO_LINE.PART_ID, QUALITY_INSPECTION.PART_ID, SUPPLIER_PART_APPROVAL.PART_ID

Column	Type	Key	Description / business meaning	Synonyms & sample values
PART_ID	INT	PK	—	—
PART_NUMBER	VARCHAR(30)	NOT NULL	—	—
PART_NAME	VARCHAR(200))	NOT NULL	—	—
COMMODITY_ID	INT	NOT NULL / FK→ DIM_COMMODIT Y.COMMODITY_I D	—	—
SUB_COMMODITY_ID	INT	NOT NULL / FK→ DIM_SUB_COMM ODITY.SUB_COM MODITY_ID	—	—
UOM_CODE	VARCHAR(5)	FK→DIM_UOM.U OM_CODE	—	—
UNIT_COST_USD	DECIMAL(10,2))	NOT NULL	Standard cost in USD	syn: standard cost, part cost, unit cost
WEIGHT_KG	DECIMAL(8,3)	—	—	—
LIFECYCLE_STATUS	VARCHAR(20)	—	ACTIVE, EOL, OBSOLETE, NRND	syn: lifecycle, eol status, part status values: ACTIVE, EOL, NRND, OBSOLETE
IS_SYNTHETIC	BOOLEAN	—	—	—

DIM_PRODUCT_FAMILY

Finished product families

aka: Product Family, product line, family • referenced by: DIM_PRODUCT.PRODUCT_FAMILY_ID

Column	Type	Key	Description / business meaning	Synonyms & sample values
PRODUCT_FAMILY_ID	INT	PK	—	—
PRODUCT_FAMILY_NAME	VARCHAR(100)	NOT NULL	—	—

DIM_PRODUCT

Finished products — 500 SKUs

aka: Product, finished good, sku, end item • references: DIM_PRODUCT_FAMILY.PRODUCT_FAMILY_ID • referenced by: BOM_HEADER.PRODUCT_ID, SALES_ORDER_LINE.PRODUCT_ID, WORK_ORDER.PRODUCT_ID

Column	Type	Key	Description / business meaning	Synonyms & sample values
PRODUCT_ID	INT	PK	—	—
PRODUCT_NAME	VARCHAR(200)	NOT NULL	—	—
PRODUCT_FAMILY_ID	INT	NOT NULL / FK→ DIM_PRODUCT_FAMILY.PRODUCT_FAMILY_ID	—	—
UNIT_PRICE_USD	DECIMAL(10,2)	NOT NULL	—	syn: list price, selling price
IS_SYNTHETIC	BOOLEAN	—	—	—

BOM_HEADER

Bill of Materials headers — one per product revision

aka: Bill of Materials, bom, product structure, recipe • references: DIM_PRODUCT.PRODUCT_ID • referenced by: BOM_LINE.BOM_ID

Column	Type	Key	Description / business meaning	Synonyms & sample values
BOM_ID	INT	PK	—	—
PRODUCT_ID	INT	NOT NULL / FK→ DIM_PRODUCT.P RODUCT_ID	—	—
BOM_VERSION	VARCHAR(10)	NOT NULL	—	values: A, B, C
EFFECTIVE_DATE	DATE	NOT NULL	—	—
STATUS	VARCHAR(20)	—	—	values: ACTIVE

BOM_LINE

BOM line items — components per assembly

aka: Bill of Materials Line, bom line, bom component • references: BOM_HEADER.BOM_ID, DIM_PART.PART_ID

Column	Type	Key	Description / business meaning	Synonyms & sample values
BOM_LINE_ID	INT	PK	—	—
BOM_ID	INT	NOT NULL / FK→ BOM_HEADER.BOM_ID	—	—
PART_ID	INT	NOT NULL / FK→ DIM_PART.PART_ID	—	—
QUANTITY_PER	DECIMAL(10,4))	NOT NULL	—	syn: qty per, usage per assembly, quantity per assembly
FIND_NUMBER	INT	NOT NULL	Position on the BOM	—

DIM_PLANT

Manufacturing plants for Asterion Devices

aka: Plant, factory, manufacturing site, works • references: DIM_GEO_COUNTRY.COUNTRY_ID • referenced by: DIM_WAREHOUSE.PLANT_ID, NONCONFORMANCE_REPORT.PLANT_ID, PO_HEADER.PLANT_ID, SALES_ORDER_HEADER.PLANT_ID, WORK_ORDER.PLANT_ID

Column	Type	Key	Description / business meaning	Synonyms & sample values
PLANT_ID	INT	PK	—	—
PLANT_CODE	VARCHAR(10)	NOT NULL	—	—
PLANT_NAME	VARCHAR(100))	NOT NULL	—	—
CITY	VARCHAR(100))	NOT NULL	—	—
COUNTRY_ID	INT	NOT NULL / FK→ DIM_GEO_COUNTRY.COUNTRY_ID	—	—

DIM_WAREHOUSE

Warehouses — plant-attached and distribution centers

aka: Warehouse, dc, distribution center, stocking location • references: DIM_GEO_COUNTRY.COUNTRY_ID, DIM_PLANT.PLANT_ID • referenced by: FACT_INVENTORY_SNAPSHOT.WAREHOUSE_ID, GOODS_RECEIPT.WAREHOUSE_ID

Column	Type	Key	Description / business meaning	Synonyms & sample values
WAREHOUSE_ID	INT	PK	—	—
WAREHOUSE_CODE	VARCHAR(10)	NOT NULL	—	—
WAREHOUSE_NAME	VARCHAR(100))	NOT NULL	—	—
PLANT_ID	INT	FK→DIM_PLANT. PLANT_ID	—	—
CITY	VARCHAR(100))	NOT NULL	—	—
COUNTRY_ID	INT	NOT NULL / FK→ DIM_GEO_COUNTRY.COUNTRY_I D	—	—
CAPACITY_UNITS	INT	NOT NULL	—	—

DIM_CUSTOMER

Customer master — 80 customers

aka: Customer, account, buyer, client • references: DIM_GEO_COUNTRY.COUNTRY_ID • referenced by: SALES_ORDER_HEADER.CUSTOMER_ID

Column	Type	Key	Description / business meaning	Synonyms & sample values
CUSTOMER_ID	INT	PK	—	—
CUSTOMER_NAME	VARCHAR(200)	NOT NULL	—	—
CUSTOMER_CODE	VARCHAR(20)	NOT NULL	—	—
COUNTRY_ID	INT	NOT NULL / FK→ DIM_GEO_COUNTRY.COUNTRY_ID	—	—
CUSTOMER_TIER	VARCHAR(10)	NOT NULL	PLATINUM, GOLD, SILVER, BRONZE	syn: tier, segment, customer segment values: BRONZE, GOLD, PLATINUM, SILVER
IS_SYNTHETIC	BOOLEAN	—	—	—

DIM_CARRIER

Logistics carriers

aka: Carrier, freight forwarder, shipping line, logistics provider • referenced by: SHIPMENT_HEADER.CARRIER_ID

Column	Type	Key	Description / business meaning	Synonyms & sample values
CARRIER_ID	INT	PK	—	—
CARRIER_NAME	VARCHAR(100))	NOT NULL	—	—
CARRIER_MODE	VARCHAR(20)	NOT NULL	OCEAN, AIR, TRUCK, RAIL, MULTIMODAL	values: AIR, MULTIMODAL, OCEAN, RAIL, TRUCK

DIM_LANE

Shipping lanes between ports

aka: Lane, shipping lane, trade lane, route, corridor • references: DIM_PORT.PORT_ID • referenced by: SHIPMENT_HEADER.LANE_ID

Column	Type	Key	Description / business meaning	Synonyms & sample values
LANE_ID	INT	PK	—	—
ORIGIN_PORT_ID	INT	NOT NULL / FK→DIM_PORT.PORT_ID	—	—
DEST_PORT_ID	INT	NOT NULL / FK→DIM_PORT.PORT_ID	—	—
TRANSPORT_MODE	VARCHAR(20)	NOT NULL	—	values: AIR, OCEAN
TRANSIT_DAYS_AVG	INT	NOT NULL	—	syn: transit time, average transit days
IS_PROBLEM_LANE	BOOLEAN	—	—	—

DIM_CONTRACT

Supplier contracts

aka: Contract, supplier agreement, purchase agreement • references: DIM_CURRENCY.CURRENCY_CODE, DIM_INCOTERM.INCOTERM_CODE, DIM_SUPPLIER.SUPPLIER_ID

Column	Type	Key	Description / business meaning	Synonyms & sample values
CONTRACT_ID	INT	PK	—	—
SUPPLIER_ID	INT	NOT NULL / FK→DIM_SUPPLIER.SUPPLIER_ID	—	—
CONTRACT_CODE	VARCHAR(20)	NOT NULL	—	—
START_DATE	DATE	NOT NULL	—	—
END_DATE	DATE	NOT NULL	—	—
CURRENCY_CODE	VARCHAR(3)	FK→DIM_CURRENCY.CURRENCY_CODE	—	—
INCOTERM_CODE	VARCHAR(3)	FK→DIM_INCOTERM.INCOTERM_CODE	—	—
STATUS	VARCHAR(20)	—	—	values: ACTIVE

SUPPLIER_PART_APPROVAL

Approved supplier-part combinations — 40,000 rows

aka: Supplier Part Approval, approved vendor list, avl, asl, approved source • references: DIM_PART.PART_ID, DIM_SUPPLIER.SUPPLIER_ID, DIM_SUPPLIER_SITE.SITE_ID

Column	Type	Key	Description / business meaning	Synonyms & sample values
APPROVAL_ID	INT	PK	—	—
SUPPLIER_ID	INT	NOT NULL / FK→ DIM_SUPPLIER.S UPPLIER_ID	—	—
SITE_ID	INT	NOT NULL / FK→ DIM_SUPPLIER_ SITE.SITE_ID	—	—
PART_ID	INT	NOT NULL / FK→ DIM_PART.PART _ID	—	—
APPROVAL_DATE	DATE	NOT NULL	—	—
STATUS	VARCHAR(20)	—	—	values: APPROVED

PO_HEADER

Purchase order headers — 20,000 POs

aka: Purchase Order, po, procurement order, purchase requisition • references: DIM_CURRENCY.CURRENCY_CODE, DIM_PLANT.PLANT_ID, DIM_SUPPLIER.SUPPLIER_ID • referenced by: PO_LINE.PO_ID

Column	Type	Key	Description / business meaning	Synonyms & sample values
PO_ID	INT	PK	—	—
PO_NUMBER	VARCHAR(20)	NOT NULL	—	—
SUPPLIER_ID	INT	NOT NULL / FK→DIM_SUPPLIER.SUPPLIER_ID	—	—
PLANT_ID	INT	NOT NULL / FK→DIM_PLANT.PLANT_ID	—	—
ORDER_DATE	DATE	NOT NULL	—	—
CURRENCY_CODE	VARCHAR(3)	FK→DIM_CURRENCY.CURRENCY_CODE	—	—
STATUS	VARCHAR(20)	NOT NULL	OPEN, RECEIVED, PARTIAL, CANCELLED	values: CANCELLED, OPEN, PARTIAL, RECEIVED

PO_LINE

Purchase order line items — 60,000 lines

aka: Purchase Order Line, po line, po item • references: DIM_PART.PART_ID, PO_HEADER.PO_ID • referenced by: GOODS_RECEIPT.PO_LINE_ID, SHIPMENT_LINE.PO_LINE_ID

Column	Type	Key	Description / business meaning	Synonyms & sample values
PO_LINE_ID	INT	PK	—	—
PO_ID	INT	NOT NULL / FK→ PO_HEADER.PO_ID	—	—
PART_ID	INT	NOT NULL / FK→ DIM_PART.PART_ID	—	—
QUANTITY	DECIMAL(12,2))	NOT NULL	—	—
UNIT_PRICE	DECIMAL(10,2))	NOT NULL	—	syn: po price, purchase price
PROMISE_DATE	DATE	NOT NULL	Original supplier promise date	—

GOODS_RECEIPT

Goods receipts — 90,000 receipts against PO lines

aka: Goods Receipt, grn, receipt, goods received note, delivery • references: DIM_WAREHOUSE.WAREHOUSE_ID, PO_LINE.PO_LINE_ID • referenced by: QUALITY_INSPECTION.RECEIPT_ID

Column	Type	Key	Description / business meaning	Synonyms & sample values
RECEIPT_ID	INT	PK	—	—
PO_LINE_ID	INT	NOT NULL / FK→ PO_LINE.PO_LINE_ID	—	—
RECEIPT_DATE	DATE	NOT NULL	Actual physical receipt date	—
QUANTITY_RECEIVED	DECIMAL(12,2)	NOT NULL	—	—
WAREHOUSE_ID	INT	NOT NULL / FK→ DIM_WAREHOUSE.WAREHOUSE_ID	—	—
DAYS_VARIANCE	INT	NOT NULL	Days early (negative) or late (positive) vs promise date	syn: delivery variance, days late, schedule variance, otd variance

SALES_ORDER_HEADER

Customer sales order headers — 10,000 orders

aka: Sales Order, so, customer order, demand • references: DIM_CUSTOMER.CUSTOMER_ID, DIM_PLANT.PLANT_ID • referenced by: SALES_ORDER_LINE.ORDER_ID

Column	Type	Key	Description / business meaning	Synonyms & sample values
ORDER_ID	INT	PK	—	—
ORDER_NUMBER	VARCHAR(20)	NOT NULL	—	—
CUSTOMER_ID	INT	NOT NULL / FK→ DIM_CUSTOMER. CUSTOMER_ID	—	—
ORDER_DATE	DATE	NOT NULL	—	—
PLANT_ID	INT	NOT NULL / FK→ DIM_PLANT.PLA NT_ID	—	—
STATUS	VARCHAR(20)	NOT NULL	—	values: OPEN, PARTIAL, SHIPPED

SALES_ORDER_LINE

Sales order line items — 40,000 lines

aka: Sales Order Line, so line, order line • references: DIM_PRODUCT.PRODUCT_ID, SALES_ORDER_HEADER.ORDER_ID • referenced by: SHIPMENT_LINE.ORDER_LINE_ID

Column	Type	Key	Description / business meaning	Synonyms & sample values
ORDER_LINE_ID	INT	PK	—	—
ORDER_ID	INT	NOT NULL / FK→SALES_ORDER_HEADER.ORDER_ID	—	—
PRODUCT_ID	INT	NOT NULL / FK→DIM_PRODUCT.PRODUCT_ID	—	—
QUANTITY	DECIMAL(12,2)	NOT NULL	—	—
UNIT_PRICE	DECIMAL(10,2)	NOT NULL	—	—
REQUESTED_DATE	DATE	NOT NULL	—	—

SHIPMENT_HEADER

Shipment headers — 18,000 shipments

aka: Shipment, freight, consignment, load • references: DIM_CARRIER.CARRIER_ID, DIM_LANE.LANE_ID • referenced by: IOT_SENSOR_READING.SHIPMENT_ID, SHIPMENT_LINE.SHIPMENT_ID, SHIPMENT_MILESTONE_EVENT.SHIPMENT_ID

Column	Type	Key	Description / business meaning	Synonyms & sample values
SHIPMENT_ID	INT	PK	—	—
CARRIER_ID	INT	NOT NULL / FK→ DIM_CARRIER.C ARRIER_ID	—	—
LANE_ID	INT	NOT NULL / FK→ DIM_LANE.LANE _ID	—	—
SHIP_DATE	DATE	NOT NULL	—	—
DELIVERY_DATE	DATE	—	—	—
STATUS	VARCHAR(20)	NOT NULL	—	values: DELAYED, DELIVERED, IN_TRANSIT

SHIPMENT_LINE

Shipment line items linking to orders or POs

aka: Shipment Line, shipment item • references: PO_LINE.PO_LINE_ID, SALES_ORDER_LINE.ORDER_LINE_ID, SHIPMENT_HEADER.SHIPMENT_ID

Column	Type	Key	Description / business meaning	Synonyms & sample values
SHIPMENT_LINE_ID	INT	PK	—	—
SHIPMENT_ID	INT	NOT NULL / FK→SHIPMENT_HEADER.SHIPMENT_ID	—	—
ORDER_LINE_ID	INT	FK→SALES_ORDER_LINE.ORDER_LINE_ID	—	—
PO_LINE_ID	INT	FK→PO_LINE.PO_LINE_ID	—	—
QUANTITY	DECIMAL(12,2)	NOT NULL	—	—

SHIPMENT_MILESTONE_EVENT

Shipment tracking milestones — 250,000 events

aka: Shipment Milestone Event, tracking event, milestone, shipment status event • references: SHIPMENT_HEADER.SHIPMENT_ID

Column	Type	Key	Description / business meaning	Synonyms & sample values
EVENT_ID	INT	PK	—	—
SHIPMENT_ID	INT	NOT NULL / FK→ SHIPMENT_HEADER.SHIPMENT_ID	—	—
MILESTONE	VARCHAR(50)	NOT NULL	—	values: ARRIVED_PORT, BOOKING_CONFIRMED, CUSTOMS_CLEARANCE, DELIVERED, DEPARTED, GATE_IN, GATE_OUT, INVOICE_SENT ...
EVENT_TS	TIMESTAMP	NOT NULL	—	—
LOCATION	VARCHAR(100)	—	—	—

IOT_SENSOR_READING

IoT container sensor readings — 500,000 rows, ~1.5% breach rate

aka: Sensor Reading, iot reading, telemetry, container sensor, cold chain reading • references: SHIPMENT_HEADER.SHIPMENT_ID

Column	Type	Key	Description / business meaning	Synonyms & sample values
READING_ID	INT	PK	—	—
SHIPMENT_ID	INT	NOT NULL / FK→ SHIPMENT_HEADER.SHIPMENT_ID	—	—
READING_TS	TIMESTAMP	NOT NULL	—	—
TEMPERATURE_C	DECIMAL(5,1)	—	—	syn: temperature, temp
HUMIDITY_PCT	DECIMAL(5,1)	—	—	—
SHOCK_G	DECIMAL(5,2)	—	—	—
TILT_DEG	DECIMAL(5,1)	—	—	—
GPS_LAT	DECIMAL(9,6)	—	—	—
GPS_LON	DECIMAL(9,6)	—	—	—
BREACH_FLAG	BOOLEAN	NOT NULL	TRUE if any reading exceeds threshold	syn: breach, excursion, threshold breach, cold chain breach

WORK_ORDER

Manufacturing work orders — 10,000

aka: Work Order, wo, production order, manufacturing order • references: DIM_PLANT.PLANT_ID, DIM_PRODUCT.PRODUCT_ID

Column	Type	Key	Description / business meaning	Synonyms & sample values
WORK_ORDER_ID	INT	PK	—	—
PRODUCT_ID	INT	NOT NULL / FK→ DIM_PRODUCT.P RODUCT_ID	—	—
PLANT_ID	INT	NOT NULL / FK→ DIM_PLANT.PLA NT_ID	—	—
START_DATE	DATE	NOT NULL	—	—
END_DATE	DATE	—	—	—
QUANTITY	DECIMAL(12,2)	NOT NULL	—	—
STATUS	VARCHAR(20)	NOT NULL	—	values: COMPLETED, IN_PROGRESS, ON_HOLD

QUALITY_INSPECTION

Incoming quality inspections — 10,000

aka: Quality Inspection, incoming inspection, iqc, quality check • references: DIM_PART.PART_ID, DIM_SUPPLIER.SUPPLIER_ID, GOODS_RECEIPT.RECEIPT_ID • referenced by: NONCONFORMANCE_REPORT.INSPECTION_ID

Column	Type	Key	Description / business meaning	Synonyms & sample values
INSPECTION_ID	INT	PK	—	—
RECEIPT_ID	INT	NOT NULL / FK→GOODS_RECEIPT.RECEIPT_ID	—	—
PART_ID	INT	NOT NULL / FK→DIM_PART.PART_ID	—	—
SUPPLIER_ID	INT	NOT NULL / FK→DIM_SUPPLIER.SUPPLIER_ID	—	—
INSPECTION_DATE	DATE	NOT NULL	—	—
SAMPLE_SIZE	INT	NOT NULL	—	—
DEFECT_COUNT	INT	NOT NULL	—	syn: defects, rejects
RESULT	VARCHAR(20)	NOT NULL	PASS, FAIL, CONDITIONAL	values: CONDITIONAL, FAIL, PASS
PPM	DECIMAL(10,1)	NOT NULL	Parts per million defect rate	syn: defect rate, parts per million, ppm defect rate

NONCONFORMANCE_REPORT

Non-conformance reports — 1,000 NCRs

aka: Nonconformance Report, ncr, quality issue, defect report, car • references: DIM_PART.PART_ID, DIM_PLANT.PLANT_ID, DIM_SUPPLIER.SUPPLIER_ID, QUALITY_INSPECTION.INSPECTION_ID

Column	Type	Key	Description / business meaning	Synonyms & sample values
NCR_ID	INT	PK	—	—
INSPECTION_ID	INT	FK→QUALITY_IN SPECTION.INSPE CTION_ID	—	—
SUPPLIER_ID	INT	NOT NULL / FK→ DIM_SUPPLIER.S UPPLIER_ID	—	—
PART_ID	INT	NOT NULL / FK→ DIM_PART.PART _ID	—	—
PLANT_ID	INT	NOT NULL / FK→ DIM_PLANT.PLA NT_ID	—	—
NCR_DATE	DATE	NOT NULL	—	—
SEVERITY	VARCHAR(20)	NOT NULL	CRITICAL, MAJOR, MINOR	values: CRITICAL, MAJOR, MINOR
ROOT_CAUSE	VARCHAR(500)	—	—	values: Cracked substrate from shock, Dimensional out-of-spec, Documentation mismatch, ESD damage in shipping, Electrical test failure, Material contamination, Solder joint defect, Surface finish degradation ...
DISPOSITION	VARCHAR(20)	NOT NULL	SCRAP, REWORK, USE_AS_IS, RETURN	values: RETURN, REWORK, SCRAP, USE_AS_IS
STATUS	VARCHAR(20)	—	—	values: CLOSED, OPEN

FACT_INVENTORY_SNAPSHOT

Inventory snapshots — ~1.2M rows (part x warehouse x month-end)

aka: Inventory Snapshot, stock on hand, inventory position, soh, stock level • references: DIM_DATE.DATE_KEY, DIM_PART.PART_ID, DIM_WAREHOUSE.WAREHOUSE_ID

Column	Type	Key	Description / business meaning	Synonyms & sample values
SNAPSHOT_ID	INT	PK	—	—
SNAPSHOT_DATE	DATE	NOT NULL / FK→ DIM_DATE.DATE_KEY	—	—
PART_ID	INT	NOT NULL / FK→ DIM_PART.PART_ID	—	—
WAREHOUSE_ID	INT	NOT NULL / FK→ DIM_WAREHOUSE.WAREHOUSE_ID	—	—
ON_HAND_QTY	DECIMAL(12,2))	NOT NULL	—	syn: stock on hand, soh, on hand quantity, inventory quantity
UNIT_COST_USD	DECIMAL(10,2))	NOT NULL	—	—
ON_HAND_VALUE	DECIMAL(14,2))	NOT NULL	on_hand_qty * unit_cost_usd	syn: inventory value, stock value, tied up capital
DAILY_USAGE_QTY	DECIMAL(10,2))	—	Average daily consumption	syn: daily usage, consumption rate, burn rate
DOI	DECIMAL(10,1))	—	Days of inventory = on_hand / daily_usage	syn: days of inventory, days of supply, dos, coverage days