LAB 05

Mutipath Load Balancer

```
Client connecting to 192.168.1.2, TCP port 5001
TCP window size: 442 KByte (default)
  3] local 192.168.1.1 port 39848 connected with 192.168.1.2 port 5001
  4] local 192.168.1.1 port 39858 connected with 192.168.1.2 port 5001
  5] local 192.168.1.1 port 39864 connected with 192.168.1.2 port 5001
  6] local 192.168.1.1 port 39868 connected with 192.168.1.2 port 5001
  7] local 192.168.1.1 port 39876 connected with 192.168.1.2 port 5001
 ID] Interval
                    Transfer
                                Bandwidth
  5]
      0.0-60.2 sec 16.7 GBytes 2.39 Gbits/sec
     0.0-60.2 sec 16.5 GBytes 2.35 Gbits/sec
  6]
     0.0-60.2 sec 16.5 GBytes 2.35 Gbits/sec
  71
  3]
      0.0-60.2 sec 16.1 GBytes 2.29 Gbits/sec
     0.0-60.2 sec 16.1 GBytes 2.30 Gbits/sec
  41
[SUM] 0.0-60.2 sec 81.8 GBytes 11.7 Gbits/sec
mininet>
```

Meter Table:

```
mininet> h1 iperf -u -c h2 -b 10m

Client connecting to 10.0.0.2, UDP port 5001
Sending 1470 byte datagrams, IPG target: 1176.00 us (kalman adjust)
UDP buffer size: 208 KByte (default)

[ 3] local 10.0.0.1 port 53621 connected with 10.0.0.2 port 5001
read failed: Connection refused
[ 3] WARNING: did not receive ack of last datagram after 5 tries.
[ 1D] Interval Transfer Bandwidth
[ 3] 0.0-10.0 sec 11.9 MBytes 10.0 Mbits/sec
[ 3] Sent 8504 datagrams
mininet> h2 iperf -u -c h1 -b 10m

Client connecting to 10.0.0.1, UDP port 5001
Sending 1470 byte datagrams, IPG target: 1176.00 us (kalman adjust)
UDP buffer size: 208 KByte (default)

[ 3] local 10.0.0.2 port 48188 connected with 10.0.0.1 port 5001
read failed: Connection refused
[ 3] WARNING: did not receive ack of last datagram after 2 tries.
[ 10] Interval Transfer Bandwidth
[ 3] 0.0-10.0 sec 11.9 MBytes 10.0 Mbits/sec
[ 3] Sent 8504 datagrams
miningets Particular Paragets 10.0 Mbits/sec
```

```
student@VM1:~$ sudo ovs-ofctl -0 OpenFlow13 dump-flows s1
cookie=0x0, duration=45.454s, table=0, n_packets=0, n_bytes=0, priority=100,dl_dst=ff:ff:ff:ff:ff:ff actions=FL000
cookie=0x0, duration=35.888s, table=0, n_packets=0, n_bytes=0, priority=100,dl_dst=00:00:00:00:00:00:00:01 actions=meter:1,output:"s1-eth
1"
cookie=0x0, duration=31.912s, table=0, n_packets=0, n_bytes=0, priority=100,dl_dst=00:00:00:00:00:00:00:00 actions=output:"s1-eth2"
cookie=0x0, duration=124.853s, table=0, n_packets=4, n_bytes=280, priority=0 actions=CONTROLLER:65535
student@VM1:~$ sudo ovs-ofctl -0 OpenFlow13 dump-meters s1
OFPST_METER_CONFIG reply (OF1.3) (xid=0x2):
meter=1 kbps bands=
type=drop rate=1000
student@VM1:~$ ovs-ofctl -0 OpenFlow13 meter-stats s1
ovs-ofctl: /var/run/openvswitch/s1.mgmt: failed to open socket (Permission denied)
student@VM1:~$ sudo ovs-ofctl -0 OpenFlow13 meter-stats s1
OFPST_METER reply (OF1.3) (xid=0x2):
meter:1 flow_count:1 packet_in_count:8527 byte_in_count:12871270 duration:222.042s bands:
0: packet_count:7596 byte_count:11485152
student@VM1:~$
```

FLOW MANAGER:

Packets being dropped for h1 from h3 or h4

```
mininet> h3 ping h1
PING 10.1.1.1 (10.1.1.1) 56(84) bytes of data.
^C
--- 10.1.1.1 ping statistics ---
9 packets transmitted, 0 received, 100% packet loss, time 8188ms
mininet> h4 ping h1
PING 10.1.1.1 (10.1.1.1) 56(84) bytes of data.
^C
--- 10.1.1.1 ping statistics ---
4 packets transmitted, 0 received, 100% packet loss, time 3069ms
mininet> pingall
*** Ping: testing ping reachability
h1 -> h2 X X
h2 -> h1 h3 h4
h3 -> X h2 h4
h4 -> X h2 h3
*** Results: 33% dropped (8/12 received)
mininet>
```

After deleting the flow we added before, h1 can ping h3 now

```
mininet> pingall

*** Ping: testing ping reachability

h1 -> h2 X X

h2 -> h1 h3 h4

h3 -> X h2 h4

h4 -> X h2 h3

*** Results: 33% dropped (8/12 received)

mininet> pingall

*** Ping: testing ping reachability

h1 -> h2 h3 h4

h2 -> h1 h3 h4

h3 -> h1 h2 h4

h4 -> h1 h2 h3

*** Results: 0% dropped (12/12 received)

mininet>

Description
```

Deleting flow with OUTPUT Port number 1:

in_port = 1 eth_src = 00:00:00:00:00:02 eth_dst = 00:00:00:00:00:04

— ♦ Flow Table 0										
	PRIORITY	MATCH FIELDS	COOKIE	DURATION	IDLE TIMEOUT	HARD TIMEOUT	INSTRUCTIONS	PACKET	BYTE COUNT	F
	65535	eth_dst = 01:80:c2:00:00:0e eth_type = 35020	0	373	0	0	OUTPUT:CONTROLLER	830	49800	0
	1	in_port = 1 eth_src = 00:00:00:00:00:01 eth_dst = 00:00:00:00:00:03	0	354	0	0	OUTPUT:2	9	546	0
	1	in_port = 1 eth_src = 00:00:00:00:00:01 eth_dst = 00:00:00:00:00:04	0	354	0	0	OUTPUT:2	9	546	0
	1	in_port = 1 eth_src = 00:00:00:00:00:02 eth_dst = 00:00:00:00:00	0	354	0	0	OUTPUT:2	10	700	0

0

373

0

OUTPUT:2

OUTPUT:CONTROLLER 110

10

0

700

10362 0

Deleting All Flows:

1

□ 0

