Kaveri-ERD

21-01-2026 DbSchema.com © DATE Wise Coders

Diagrams

1. Main Diagram . . . 1

Tables

kaveri.aadhaar_auth_data [1] . . . 2
kaveri.aadhar_authentication_log [1] . . . 2
kaveri.aadhar_authentication_log_citizen [1] . . . 2
kaveri.additionaldocumentinfo [1] . . . 3
kaveri.additionalpartyinfo [1] . . . 3
kaveri.agrilandroadrates [1] . . . 4
kaveri.agrilandroadrates_new [1] . . . 5
kaveri.agrilandtypemaster [1] . . . 7
kaveri.alienatedconsentbhoomisearch [1] . . . 7
kaveri.ams_bankinstrumentnumberdetails [1] . . . 7
kaveri.ams_mas_epaymentstatus [1] . . . 8
kaveri.ams_refundchallandetails [1] . . . 8
kaveri.ams_refundchallanusagedetails [1] . . . 8
kaveri.ams_reg_epaymentamtpaiddetails [1] . . . 9
kaveri.ams_reg_epaymentamtpaiddetails_cd140 [1] . . . 9
kaveri.ams_reg_epaymentbankackdetails [1] . . . 9
kaveri.ams_reg_epaymentbankackdetails_cd140 [1] . . . 10
kaveri.ams_reg_epaymenttransdetails [1] . . . 10
kaveri.ams_reg_epaymenttransdetails_cd140 [1] . . . 11
kaveri.ams_reg_khajaneresponselog [1] . . . 12
kaveri.ams_reg_khajaneresponselog_cd140 [1] . . . 12
kaveri.anywhere_reg_log [1] . . . 12
kaveri.applicantapplicationdetails [1] . . . 13
kaveri.applicantapplicationdetails_11092023 [1] . . . 14
kaveri.applicantapplicationdetails_bck_newregpay [1] . . . 15
kaveri.applicantapplicationdetails_cd140 [1] . . . 15
kaveri.applicantapplicationdetails_newregepayment [1] . . . 16
kaveri.applicantapplicationdetails_newregpayment [1] . . . 17
kaveri.applicantdashboarddetails [1] . . . 18
kaveri.application_audit_scrutiny_history [1] . . . 18
kaveri.application_audit_scrutiny_queue [1] . . . 18
kaveri.application_for_scrutiny_property_master [1] . . . 18
kaveri.applicationaudit [1] . . . 19
kaveri.applicationaudit_dashboard [1] . . . 19
kaveri.applicationdetails [1] . . . 20
kaveri.applicationforscrutiny [1] . . . 20

kaveri.applicationlimitdetails [1] . . . 21
kaveri.applicationreviewdetails [1] . . . 21
kaveri.applicationreviewmaster [1] . . . 22
kaveri.applicationtypemaster [1] . . . 22
kaveri.applicationverification [1] . . . 22
kaveri.appointmentmaster [1] . . . 23
kaveri.appointmenttypemaster [1] . . . 23
kaveri.areatypemaster [1] . . . 23
kaveri.aregisterfiledetails [1] . . . 24
kaveri.aregistergenerationdetails [1] . . . 24
kaveri.articlefeecalculationdetails [1] . . . 24
kaveri.articlesuppdoc [1] . . . 25
kaveri.authoritymaster [1] . . . 25
kaveri.bankbranchdetailsmaster [1] . . . 25
kaveri.bannedparties [1] . . . 25
kaveri.bannedproperties [1] . . . 26
kaveri.bannedpropertynumbers [1] . . . 27
kaveri.bbmpxml [1] . . . 27
kaveri.bchain_property [1] . . . 28
kaveri.bchain_response [1] . . . 28
kaveri.bda_fileuploaddetails [1] . . . 28
kaveri.bdaxml [1] . . . 28
kaveri.bhoomi_old_method_jslip_acknowledgment_details [1] . . . 29
kaveri.bhoomi_old_method_jslip_acknowledgments [1] . . . 29
kaveri.bhoomicategoriesmaster [1] . . . 30
kaveri.bhoomicents_data [1] . . . 30
kaveri.bhoomidistrictmaster [1] . . . 30
kaveri.bhoomifileuploaddetails [1] . . . 30
kaveri.bhoomihoblimaster [1] . . . 31
kaveri.bhoomihoblimaster_15feb2025 [1] . . . 31
kaveri.bhoomimappingdetails [1] . . . 32
kaveri.bhoomimappingdetails_15feb2025 [1] . . . 32
kaveri.bhoomipartyinfo [1] . . . 33
kaveri.bhoomitaluk [1] . . . 33
kaveri.bhoomitalukamapping [1] . . . 33
kaveri.bhoomitalukmaster [1] . . . 34
kaveri.bhoomivillagemaster [1] . . . 34
kaveri.bhoomivillagemaster_15feb2025 [1] . . . 34
kaveri.bhoomixmllog [1] . . . 35
kaveri.blacklistedcitizen [1] . . . 35
kaveri.blacklistedcitizenloginloginfo [1] . . . 36
kaveri.book1_part3_court [1] . . . 36
kaveri.booki_iii_iv_data [1] . . . 37
kaveri.booktypemaster [1] . . . 37
kaveri.bucketmaster [1] . . . 37

kaveri.bulk_email_status_log [1] . . . 37
kaveri.captcha [1] . . . 38
kaveri.cc_applicationdetails [1] . . . 38
kaveri.cc_applicationdetails_analysis [1] . . . 39
kaveri.cc_applicationdetails_dashboard [1] . . . 40
kaveri.cc_cscapplicantdetails [1] . . . 40
kaveri.cc_documents [1] . . . 41
kaveri.cc_esignfilepath [1] . . . 41
kaveri.cc_qrcodedetails [1] . . . 41
kaveri.cc_remarkdetails [1] . . . 42
kaveri.cc_remarks [1] . . . 42
kaveri.cc_requiredfees [1] . . . 42
kaveri.cc_signedfilepaths [1] . . . 42
kaveri.checkslipinfo [1] . . . 43
kaveri.citizendashboard [1] . . . 43
kaveri.citizenloginloginfo [1] . . . 44
kaveri.citizenloginloginfo_new [1] . . . 44
kaveri.citizenloginotp [1] . . . 45
kaveri.citizenmaster [1] . . . 45
kaveri.citizenmaster_cd140 [1] . . . 46
kaveri.citizenmaster_tmp [1] . . . 46
kaveri.citizeotpdetails [1] . . . 47
kaveri.company [1] . . . 47
kaveri.companytype [1] . . . 47
kaveri.constructioncostmaster [1] . . . 47
kaveri.constructioncostmaster_kaveri1 [1] . . . 48
kaveri.correctiondetails [1] . . . 48
kaveri.correctionmaster [1] . . . 48
kaveri.courtorders [1] . . . 49
kaveri.cropfruitsmaster [1] . . . 49
kaveri.cvcopeningclosing [1] . . . 49
kaveri.daily_apps_revenue_scheduler_history [1] . . . 50
kaveri.daily_dashboard_apps_revenue_details [1] . . . 50
kaveri.dailyreceiptfees [1] . . . 51
kaveri.dataentry_documentmaster [1] . . . 52
kaveri.dec_drordermaster [1] . . . 52
kaveri.dec_drpndnote [1] . . . 53
kaveri.dec_populatesearchkeystatus [1] . . . 53
kaveri.declarationmaster [1] . . . 53
kaveri.deleted_record_villagemaster [1] . . . 54
kaveri.departmentaccesslotmaster [1] . . . 54
kaveri.departmentloginloginfo [1] . . . 55
kaveri.departmentloginloginfo_new [1] . . . 55
kaveri.departmentuserroles [1] . . . 55
kaveri.departmentusers [1] . . . 56

kaveri.departmentusers_biometrics [1] . . . 57
kaveri.departmentusers_complete [1] . . . 58
kaveri.departmentusers_deo_service_history [1] . . . 59
kaveri.departmentusers_service_history [1] . . . 60
kaveri.deps_saved_ddl [1] . . . 60
kaveri.deptmentusergroup [1] . . . 60
kaveri.deptotpdetails [1] . . . 60
kaveri.desigmaster [1] . . . 61
kaveri.districtmaster [1] . . . 61
kaveri.districtmaster_prod1 [1] . . . 61
kaveri.doc_path_bucket_ref [1] . . . 61
kaveri.docserialnumbers [1] . . . 62
kaveri.document_esign [1] . . . 62
kaveri.document_esign_bck [1] . . . 62
kaveri.document_to_be_included_in_old_method_jslips [1] . . . 62
kaveri.documentacceslog [1] . . . 63
kaveri.documentmaster [1] . . . 63
kaveri.documentmaster_cd140 [1] . . . 65
kaveri.documentmaster_dashboard [1] . . . 66
kaveri.documentmaster_dashboard_1 [1] . . . 68
kaveri.documentrescandetails [1] . . . 70
kaveri.documentsummary [1] . . . 70
kaveri.documentsupportdocs [1] . . . 70
kaveri.documenttypemaster [1] . . . 71
kaveri.drc_push_kaveri_response [1] . . . 71
kaveri.dummy_bhoomi [1] . . . 71
kaveri.dummy_eaasthi [1] . . . 71
kaveri.dummy_eaasthi_test [1] . . . 71
kaveri.dummy_eswathu [1] . . . 71
kaveri.dummy_eswathu_test [1] . . . 71
kaveri.eaasthipidnumberdetails [1] . . . 71
kaveri.eaasti_eswatuxmllog [1] . . . 72
kaveri.easthi_eswathu_fileuploaddetails [1] . . . 72
kaveri.ec_accesslog [1] . . . 72
kaveri.ec_applicationdetails [1] . . . 73
kaveri.ec_applicationdetails_dashboard [1] . . . 74
kaveri.ec_checkedproperties [1] . . . 75
kaveri.ec_cscapplicantdetails [1] . . . 75
kaveri.ec_deptreferencecoderequiredfeemapping [1] . . . 76
kaveri.ec_esignfilepath [1] . . . 76
kaveri.ec_mapped_details_old [1] . . . 76
kaveri.ec_prepared [1] . . . 77
kaveri.ec_propertynumberdetails [1] . . . 77
kaveri.ec_qrcodedetails [1] . . . 77
kaveri.ec_remarkdetails [1] . . . 78

kaveri.ec_requiredfees [1] . . . 78
kaveri.ec_signedfilepaths [1] . . . 78
kaveri.ec_uncheckedproperties [1] . . . 79
kaveri.eccertificate [1] . . . 79
kaveri.ecexemptiondetails [1] . . . 79
kaveri.ecmisseddata [1] . . . 80
kaveri.ecmisseddata_lastbatch [1] . . . 80
kaveri.ecmisseddata_nopropnodetails [1] . . . 80
kaveri.ecname_mapped_details_new [1] . . . 80
kaveri.ecnamesearchkeyvalues [1] . . . 80
kaveri.ecpropertysearchkeyvalues [1] . . . 81
kaveri.ecsearchdocumentnodetails [1] . . . 81
kaveri.ecsearchpartydetails [1] . . . 82
kaveri.ecsearchpropertynodetails [1] . . . 82
kaveri.eligibleappointmentdatedetails [1] . . . 82
kaveri.emp_transfer_details [1] . . . 83
kaveri.empleavebalance [1] . . . 83
kaveri.empleavedetails [1] . . . 83
kaveri.employeetypemaster [1] . . . 84
kaveri.encryption_key_vault [1] . . . 84
kaveri.endorsementflowmaster [1] . . . 84
kaveri.endorsementmaster [1] . . . 85
kaveri.exemptmaster [1] . . . 85
kaveri.extent [1] . . . 85
kaveri.failed_jobs [1] . . . 85
kaveri.fectchdeed [1] . . . 86
kaveri.feedashboarddetails [1] . . . 86
kaveri.feedashboarddetails_new [1] . . . 86
kaveri.feeruleslabs [1] . . . 86
kaveri.feesrequired [1] . . . 87
kaveri.feesrequired_cd140 [1] . . . 88
kaveri.feesrequired_dashboard_1 [1] . . . 88
kaveri.feesrequired_paymentchk [1] . . . 89
kaveri.feesrequired_regrepayment [1] . . . 90
kaveri.feesresssurcharg [1] . . . 90
kaveri.feesrulemaster [1] . . . 91
kaveri.filing_book1 [1] . . . 91
kaveri.fingertypemaster [1] . . . 92
kaveri.fingerverificationstatusmaster [1] . . . 92
kaveri.firmamendment [1] . . . 92
kaveri.firmbranches [1] . . . 92
kaveri.firmmaster [1] . . . 93
kaveri.firmparty [1] . . . 94
kaveri.firmsakalapending [1] . . . 94
kaveri.frm_addressdetails [1] . . . 94

kaveri.frm_applicationforwarddetails [1] . . . 95
kaveri.frm_checkslipsdetails [1] . . . 95
kaveri.frm_endorsementdetails [1] . . . 96
kaveri.frm_feerequired_paymentmapping [1] . . . 96
kaveri.frm_finaluploadeddocs [1] . . . 96
kaveri.frm_firmbranches [1] . . . 97
kaveri.frm_firmdetails [1] . . . 97
kaveri.frm_firmpaymentdetails [1] . . . 98
kaveri.frm_firmprocessforfee [1] . . . 98
kaveri.frm_firmrefusaldetails [1] . . . 99
kaveri.frm_partnerdetails [1] . . . 99
kaveri.frm_supporteddocuments [1] . . . 100
kaveri.frm_witnessdetails [1] . . . 100
kaveri.fruits_data_recv_details [1] . . . 100
kaveri.function_def [1] . . . 101
kaveri.function_def_lastet [1] . . . 101
kaveri.function_dll [1] . . . 101
kaveri.functiondef [1] . . . 102
kaveri.functionmaster [1] . . . 102
kaveri.gendermaster [1] . . . 102
kaveri.graphcnt_dashboad [1] . . . 102
kaveri.group_roll_mapping [1] . . . 103
kaveri.hoblimaster [1] . . . 103
kaveri.hoblimaster_15feb2025 [1] . . . 103
kaveri.hoblimaster_prod1 [1] . . . 104
kaveri.hoblimaster_prod2 [1] . . . 104
kaveri.holidaymaster [1] . . . 104
kaveri.index_1_data [1] . . . 104
kaveri.index_fragmented [1] . . . 105
kaveri.individualapartmentdetails [1] . . . 105
kaveri.integrationdepartment [1] . . . 106
kaveri.jobs [1] . . . 106
kaveri.jslipoldmethodlog [1] . . . 106
kaveri.jslipstatus [1] . . . 106
kaveri.k1documentdetails [1] . . . 107
kaveri.k1jslipdata [1] . . . 107
kaveri.k1pendingdashboard [1] . . . 107
kaveri.k1pendingregistrationdata [1] . . . 108
kaveri.kaveri1documentcorrection [1] . . . 108
kaveri.khatabdaresptable [1] . . . 109
kaveri.khatadrcresptable [1] . . . 109
kaveri.khatakhbresptable [1] . . . 109
kaveri.latestfunctiondef [1] . . . 109
kaveri.lbpasxml [1] . . . 109
kaveri.leasetypemaster [1] . . . 110

kaveri.leavetypemaster [1] 110
kaveri.lgd_districtmaster [1] 110
kaveri.lgd_eswath_mapping [1] 111
kaveri.lgd_mapping_test [1] 111
kaveri.lgd_statemaster [1] 111
kaveri.lgd_talukmaster [1] 112
kaveri.lgd_test [1] 112
kaveri.lgd_villagemaster [1] 112
kaveri.liabilitydetails [1] 112
kaveri.liabilitydetails_new [1] 113
kaveri.liabilitynoteadditionaldetails [1] 113
kaveri.liabilityonpropertydetails [1] 114
kaveri.liabilitypropertymapped [1] 114
kaveri.loanpurposesmaster [1] 114
kaveri.mainapartmentdetails [1] 114
kaveri.mandatorysupportdocuments [1] 115
kaveri.mas_alm_frm_sendmessageconfiguration [1] 115
kaveri.mas_ams_accountheads [1] 116
kaveri.mas_ams_accountheadsfeetypesmapping [1] 116
kaveri.mas_ams_khajaneddocodemapping [1] 116
kaveri.mas_ams_khajaneddocodemapping_docdb [1] 117
kaveri.mas_ctitizenecccfee [1] 117
kaveri.mas_districts [1] 117
kaveri.mas_feerules [1] 117
kaveri.mas_feerules_kaveri1 [1] 118
kaveri.mas_frm_amendmenttypes [1] 118
kaveri.mas_frm_applicationtypes [1] 118
kaveri.mas_frm_checksliptypeamendmenttypemapping [1] 119
kaveri.mas_frm_checksliptypes [1] 119
kaveri.mas_frm_firmbusinesstypes [1] 119
kaveri.mas_frm_firmdissolutiontypes [1] 119
kaveri.mas_frm_firmmemberdesignations [1] 120
kaveri.mas_frm_firmnatures [1] 120
kaveri.mas_frm_presentertypes [1] 120
kaveri.mas_frm_refusalreasons [1] 120
kaveri.mas_frm_stamparticles [1] 121
kaveri.mas_frm_stampcalculationvaluetypes [1] 121
kaveri.mas_frm_stamprules [1] 121
kaveri.mas_frm_supportdocuments [1] 122
kaveri.mas_idprooftypes [1] 122
kaveri.mas_marriagebeforestatus [1] 122
kaveri.mas_marriagemode [1] 123
kaveri.mas_marriagetype [1] 123
kaveri.mas_officemaster [1] 123
kaveri.mas_officemaster_docdb [1] 124

kaveri.mas_officetimings [1] 124
kaveri.mas_officetypes [1] 125
kaveri.mas_persontype [1] 125
kaveri.mas_prooftypes [1] 125
kaveri.mas_prooftypes_idproof_mapping [1] 125
kaveri.mas_registration [1] 125
kaveri.mas_servicemaster [1] 126
kaveri.mas_val_agrilandtypes [1] 126
kaveri.mas_val_annexurecalculationrules [1] 126
kaveri.mas_val_annexurerules [1] 126
kaveri.mas_val_apartmentfloorrates [1] 127
kaveri.mas_val_apartmentsamenities [1] 127
kaveri.mas_val_apartmentspecialameneties [1] 127
kaveri.mas_val_apartmentspecialamenetyrules [1] 128
kaveri.mas_val_buildingfloors [1] 128
kaveri.mas_val_constructionrates [1] 128
kaveri.mas_val_constructiontypes [1] 129
kaveri.mas_val_flatrates [1] 129
kaveri.mas_val_openbuiltrates [1] 129
kaveri.mas_val_parkingrates [1] 129
kaveri.mas_val_parkingtypes [1] 130
kaveri.mas_val_readyreckoner_flats [1] 130
kaveri.mas_valratedetail [1] 130
kaveri.mas_valratedetail_prod [1] 131
kaveri.mas_valrateheader [1] 131
kaveri.mas_valuationrates [1] 132
kaveri.mas_valuationrates_prod [1] 132
kaveri.measunitmaster [1] 133
kaveri.measurementmaster [1] 133
kaveri.minutebook [1] 133
kaveri.minutebook_data [1] 134
kaveri.modulemaster [1] 134
kaveri.mojanixml [1] 135
kaveri.mrg_requiredfees [1] 135
kaveri.ngdrs_dashboard_data [1] 136
kaveri.noticemaster [1] 136
kaveri.openbuiltratedetail [1] 136
kaveri.openbuiltratedetail_prod [1] 137
kaveri.orders [1] 137
kaveri.orgdatajslip [1] 137
kaveri.otherfeesrequired [1] 138
kaveri.otherreasonmaster [1] 138
kaveri.otherreasonremarks [1] 138
kaveri.otherreceiptdetails [1] 139
kaveri.otherreceiptdetails_cr0924003000267708 [1] 139

kaveri.otherreceiptpartyinfo [1] . . . 140
kaveri.partyinfo_cd140 [1] . . . 141
kaveri.partyinfo_claimaint [1] . . . 143
kaveri.partyorganizationinfo [1] . . . 145
kaveri.partyschedules [1] . . . 145
kaveri.partyschedules_cd140 [1] . . . 146
kaveri.partytypemaster [1] . . . 146
kaveri.partywitness [1] . . . 146
kaveri.paymentmodemaster [1] . . . 146
kaveri.pendingreasonmaster [1] . . . 147
kaveri.persondetails [1] . . . 147
kaveri.persons_additional [1] . . . 148
kaveri.post_office_details [1] . . . 149
kaveri.propertybankdetails [1] . . . 149
kaveri.propertybuildingusagetypedetails [1] . . . 149
kaveri.propertyclassification [1] . . . 150
kaveri.propertyfloornumberdetails [1] . . . 150
kaveri.propertyfloortypesdetails [1] . . . 150
kaveri.propertymaster [1] . . . 150
kaveri.propertymaster_11092023 [1] . . . 152
kaveri.propertymaster_cd140 [1] . . . 154
kaveri.propertymaster_dashboard_1 [1] . . . 156
kaveri.propertynotypemaster [1] . . . 158
kaveri.propertynumberdetails [1] . . . 158
kaveri.propertynumberdetails_cd140 [1] . . . 158
kaveri.propertynumberdetails_space_bck [1] . . . 159
kaveri.propertyrooftypedetails [1] . . . 159
kaveri.propertyschedules [1] . . . 159
kaveri.propertyschedules_cd140 [1] . . . 160
kaveri.propertytypedescmaster [1] . . . 161
kaveri.propertytypemaster [1] . . . 161
kaveri.propertywoodtypedetails [1] . . . 162
kaveri.queue_service [1] . . . 162
kaveri.queues [1] . . . 162
kaveri.rateagriculturaldetail [1] . . . 162
kaveri.rdpr_document_details [1] . . . 163
kaveri.rdpr_documents [1] . . . 163
kaveri.rdprxml [1] . . . 164
kaveri.rdprxmltypemapping [1] . . . 164
kaveri.rdprxmltypes [1] . . . 165
kaveri.reasonmaster [1] . . . 165
kaveri.reasonmaster_k1 [1] . . . 165
kaveri.receiptdetails [1] . . . 165
kaveri.receiptdetails_cd140 [1] . . . 165
kaveri.receiptmaster [1] . . . 166

kaveri.receiptmaster_cd140 [1] 166
kaveri.receiptpaymentdetails [1] 166
kaveri.receiptpaymentdetails_cd140 [1] 167
kaveri.receipttypemaster [1] 167
kaveri.referencemaster [1] 167
kaveri.referencesthroghmaster [1] 168
kaveri.referencetransactionmaster [1] 169
kaveri.regionmaster [1] 169
kaveri.regionpvg [1] 169
kaveri.registrationarticles [1] 169
kaveri.registrationlog [1] 170
kaveri.registrationotpdetails [1] 170
kaveri.relationshipmasters [1] 170
kaveri.remittedtypemaster [1] 170
kaveri.rescandetails [1] 171
kaveri.revised_form_7_statutory [1] 171
kaveri.revised_form_7_statutory_cc [1] 172
kaveri.revised_form_7_statutory_cc_reg [1] 173
kaveri.revised_form_7_statutory_doc_reg [1] 173
kaveri.revised_form_7_statutory_ec [1] 174
kaveri.revised_form_7_statutory_ec_reg [1] 175
kaveri.roadmaster [1] 176
kaveri.roadmaster_kaveri1 [1] 176
kaveri.roadmaster_prod [1] 176
kaveri.roadmasterdmp [1] 177
kaveri.role_module_function_mapping [1] 177
kaveri.rule17filing [1] 177
kaveri.rule17filingremarks [1] 178
kaveri.sakala_department_officecodemaster [1] 179
kaveri.sakala_marriagepartydetails [1] 179
kaveri.sakala_orphan_settle_log [1] 179
kaveri.sakala_partydetails [1] 180
kaveri.sakala_transactionerrorlog [1] 180
kaveri.sakala_uploadfiledetails [1] 180
kaveri.sakalaservicecodemaster [1] 181
kaveri.sakalasubservicecodemaster [1] 181
kaveri.salutationmaster [1] 182
kaveri.scanmaster [1] 182
kaveri.scannedfileuploaddetails [1] 182
kaveri.scn_frm_scandetails [1] 182
kaveri.scrutiny_remarks_mapping [1] 183
kaveri.scrutinyfeechange [1] 183
kaveri.scrutinyremarks [1] 184
kaveri.scrutinyremarksmaster [1] 184
kaveri.scrutinyremarkstitle [1] 184

kaveri.securityqstmaster [1] 185
kaveri.servicesmaster [1] 185
kaveri.signed_file_upload_details [1] 185
kaveri.skipped_document_numbers [1] 186
kaveri.slotconfigurationmaster [1] 186
kaveri.slotmaster [1] 186
kaveri.slotsrvcstatusmaster [1] 187
kaveri.slottxn [1] 187
kaveri.sms_master [1] 187
kaveri.sms_transaction_details [1] 188
kaveri.sromaster [1] 188
kaveri.sromaster_prod1 [1] 189
kaveri.sroserialmaster [1] 189
kaveri.srowrkingdayexemption [1] 189
kaveri.stamparticleoptions [1] 189
kaveri.stamparticles [1] 190
kaveri.stampdetails [1] 190
kaveri.stampfeerulerelations [1] 191
kaveri.stampregrelations [1] 191
kaveri.stamprules [1] 191
kaveri.stamprules_preprod [1] 192
kaveri.stamprules_temp [1] 193
kaveri.stamprulesflag [1] 194
kaveri.stamprulesflag_preprod [1] 196
kaveri.stamprulesflag_tmp [1] 198
kaveri.stampruleslabs [1] 200
kaveri.stamprulseminvalue_change [1] 200
kaveri.stampss [1] 201
kaveri.stamptypemaster [1] 202
kaveri.statemaster [1] 202
kaveri.statement [1] 203
kaveri.submodulemaster [1] 203
kaveri.supportdocumentmaster [1] 203
kaveri.supportdocuments [1] 204
kaveri.supportdocumentuploads [1] 204
kaveri.surveynodetails [1] 204
kaveri.t22 [1] 204
kaveri.t6 [1] 205
kaveri.table_def [1] 205
kaveri.table_update_request_logs [1] 205
kaveri.tabledef [1] 205
kaveri.talukmaster [1] 205
kaveri.talukmaster_prod1 [1] 206
kaveri.talukmaster_prod2 [1] 206
kaveri.tbl_book1_part3_remarks [1] 206

kaveri.temptableforjslip [1] . . . 207
kaveri.third_partyintegrationkeys [1] . . . 207
kaveri.tmp [1] . . . 207
kaveri.transactionauditlog [1] . . . 207
kaveri.ulbmapping [1] . . . 207
kaveri.ulbmaster [1] . . . 208
kaveri.ulms_property_importlog [1] . . . 208
kaveri.upordecisionmaster [1] . . . 208
kaveri.uporpropertytypemaster [1] . . . 208
kaveri.uporrestrictiontypemaster [1] . . . 209
kaveri.uporxml [1] . . . 209
kaveri.usrtypemst [1] . . . 209
kaveri.val_agriculturedetails [1] . . . 210
kaveri.val_annexuredetails [1] . . . 210
kaveri.val_apartmentamenitydetails [1] . . . 210
kaveri.val_app [1] . . . 211
kaveri.val_constructionratedetails [1] . . . 211
kaveri.val_flatfloordetails [1] . . . 211
kaveri.val_flatratedetails [1] . . . 212
kaveri.val_openbuiltvaluationdetails [1] . . . 212
kaveri.val_parkingratedetails [1] . . . 212
kaveri.val_userapartmentamenitydetails [1] . . . 213
kaveri.valdetails_temp [1] . . . 213
kaveri.valuationdetails [1] . . . 213
kaveri.valuationdetails_cd140 [1] . . . 214
kaveri.valuationtypemaster [1] . . . 215
kaveri.viewdef [1] . . . 215
kaveri.views_def [1] . . . 215
kaveri.villagemaster [1] . . . 215
kaveri.villagemaster_15feb2025 [1] . . . 216
kaveri.villagemaster_prod [1] . . . 216
kaveri.villagemaster_prod1 [1] . . . 217
kaveri.villagemaster_prod2 [1] . . . 217
kaveri.villageurbanmappeddiffdump [1] . . . 217
kaveri.villageurbanmapping [1] . . . 218
kaveri.villagewardmapping [1] . . . 218
kaveri.villagewardmapping_file_data [1] . . . 218
kaveri.warddetails [1] . . . 218
kaveri.withdrawapplications [1] . . . 218
kaveri.witnessinfo [1] . . . 219
kaveri.wrkflowmaster [1] . . . 220
kaveri.yearlyleavebalance [1] . . . 220
kaveri.zonemaster [1] . . . 220

Views

kaveri.sakalaonlyaccept [1] 220
kaveri.sakalnos [1] 220
kaveri.vw_ddd [1] 220

Main Diagram

Table aadhaar_auth_data

Idx	Name	Data Type
* Pk	id	integer DEFAULT nextval('kaveri.aadhaar_auth_data_id_seq'::regclass)
*	transactionnumber	varchar
*	transactiondatetime	varchar
*	aadhaardetails	text
*	created_on	timestamp DEFAULT CURRENT_TIMESTAMP

Indexes

Type	Name	On
Pk	aadhaar_auth_data_pkey	id

Table aadhar_authentication_log

Idx	Name	Data Type
* Pk	id	bigint DEFAULT nextval('kaveri.aadhar_log_id_seq'::regclass)
Idx	applicationnumber	varchar(50)
Idx	partyid	bigint
	linkpartyid	bigint
	nameasperaadhar	varchar(500)
	masked_aadhar	varchar(500)
	aadharhash	varchar(500)
	vault_id	varchar(500)
Unq	ekyctxnno	varchar(500)
	ekyctimestamp	varchar(500)
	responsestatus	varchar(500)
	errormessage	varchar(500)
	error	varchar(500)
	inserteddatetime	timestamp DEFAULT CURRENT_TIMESTAMP

Indexes

Type	Name	On
Pk	pk_aadhar_log_id	id
	idx_authentication_log_appno	applicationnumber
	idx_authentication_log_prtyid	partyid
Unq	uk_aadhar_authentication_log_ccnew	ekyctxnno
Unq	uk_aadhar_authentication_log_ccnew1	ekyctxnno
Unq	uk_aadhar_authentication_log	ekyctxnno

Table aadhar_authentication_log_citizen

Idx	Name	Data Type
* Pk	id	bigint DEFAULT nextval('kaveri.aadhar_citizen_log_id_seq'::regclass)
Idx	applicationnumber	varchar(50)
Idx	partyid	bigint
	linkpartyid	bigint
	nameasperaadhar	varchar(500)
	masked_aadhar	varchar(500)
Idx	aadharhash	varchar(500)
Idx	vault_id	varchar(500)

Table aadhar_authentication_log_citizen

Unq	ekyctxnno	varchar(500)
	ekyctimestamp	varchar(500)
	responsestatus	varchar(500)
	errormessage	varchar(500)
	error	varchar(500)
	inserteddatetime	timestamp DEFAULT CURRENT_TIMESTAMP
	addresse	text
	addressk	text
	aadharphotopath	text
	ekycdata	text

Indexes

Type	Name	On
	idx_authenticationcit_log_appno	applicationnumber
	idx_authenticationcit_log_prtyid	partyid
Pk	pk_aadharauth_id	id
Unq	uk_ekyctranxno_ccnew	ekyctxnno
	idx_authenticationcit_log_vault_id	vault_id
	index_aadhar_authcation_citizen_resonpsestatus	aadharhash
Unq	uk_ekyctranxno	ekyctxnno

Table additionaldocumentinfo

Idx	Name	Data Type
* Pk	documentid	bigint
	dateofreturn	timestamp
	numberofcopies	integer
	descriptionofduplicate	varchar(1000)
	documentstage	smallint DEFAULT 0
	sdrefund	decimal
	rfrefund	decimal
*	isrefunded	boolean DEFAULT false
	orderno	varchar(50)
	paymentofmoney	varchar(1000)
	denotationstamp	varchar(500)
	userid	integer
* Pk	srocode	integer
	drordernumber	varchar(50)
	istransmitted	boolean
	inserteddatetime	timestamp DEFAULT CURRENT_TIMESTAMP
	k1k2_flag	smallint DEFAULT 2

Indexes

Type	Name	On
Pk	pk_additionaldocumentinfo	documentid, srocode

Table additionalpartyinfo

Idx	Name	Data Type
* Pk	partyid	bigint
* Pk	srocode	integer
	uid	char(12)

Table additionalpartyinfo

	email	varchar(50)
	uporownerno	integer
	isonline	boolean
	passportno	varchar(20)
	drivinglicenceno	varchar(50)
	inserteddatetime	timestamp DEFAULT CURRENT_TIMESTAMP
	k1k2_flag	smallint DEFAULT 2

Indexes

Type	Name	On
Pk	pk_additionalpartyinfo	partyid, srocode

Table agrilandroadrates

Idx	Name	Data Type
Idx	roadcode	bigint
	Mining	decimal
	Dry, No Source of Irrigation,Red Soil	decimal
	Dry, No Source of Irrigation,Other	decimal
	Plantation, Coffee/Pepper	decimal
	Dry, Paddy-rainwater,BlackSoil	decimal
	Dry, Paddy-rain water, Red Soil	decimal
	Dry, Paddy-rain water, Other Soil	decimal
	Dry, Irrigation by pumping water from river-canal, Black Soil	decimal
	Dry, Irrigation by pumping water from river-canal, Red Soil	decimal
	Dry, Irrigation by pumping water from river-canal, Other Soil	decimal
	Bagayat, Dry	decimal
	Bagayat, Wet	decimal
	Wet (Assured Water Supply from Government Tanks/Canals), Two Cr	decimal
	Wet (Assured Water Supply from Government Tanks/Canals), Sugarc	decimal
	Wet (Assured Water Supply from Government Tanks/Canals), One Cr	decimal
	Wet (Assured Water Supply from Government Tanks/Canals), Lift I	decimal
	Wet (Assured Water Supply from Government Tanks/Canals), Garden	decimal
	Plantation, Cardamom/Pepper	decimal
	Plantation, Rubber/Areca nut	decimal
	Plantation, Tea	decimal
	Plantation, Teak	decimal
	Wet Pond	decimal
	Plantation, Cashew Nut	decimal
	Dry Agriculture Land, Irrigated By Bore / Well / Pumpset, Other	decimal
	Dry, No Source of Irrigation, Loamy Soil	decimal
	Dry, Paddy/Areca/Coconut/Mango/Grapes/Fruit grown with rain wat	decimal
	Dry, Irrigation by pumping water from river/ canal/ stream/ pon	decimal
	Dry,Areca,coconut,Rubber,CashewNut	decimal
	Plantation Coffee(Low Grade)	decimal
	Plantation Coffee(High Grade)	decimal

Table agrilandroadrates

	Bagayat Coconut(Plant Within 2 years)	decimal
	Bagayat Coconut	decimal
	Bagayat Arecanut & venilla(Plant Within 2 years)	decimal
	Bagayat Arecanut & venilla	decimal
	Plantation, Cardamom/Pepper(Low Grade)	decimal
	Plantation, Cardamom/Pepper(High Grade)	decimal
	Plantation, Coffee/Cardamom	decimal
	Plantation, Coffee/Cardamom/Pepper	decimal
	Dry, No Source of Irrigation,Maradi	decimal
	Dry, No Source of Irrigation, Garasu	decimal
	Non-Agriculture Land	decimal
	Dry Agriculture Land, Irrigated By Bore / Well / Pumpset, Black	decimal
	Dry Agriculture Land, Irrigated By Bore / Well / Pumpset, Red S	decimal
	NA Dry land (Undeveloped) - Residential Use	decimal
	NA Dry land (Undeveloped) - Commercial Use	decimal
	NA Dry land (Undeveloped) - Industrial Use	decimal
	NA Dry land Industrial Purpose (developed)	decimal
	NA Wet land (Undeveloped) - Residential Use	decimal
	NA Wet land (Undeveloped) - Commercial Use	decimal
	NA Wet land (Undeveloped) - Industrial Use	decimal
	NA Bhagayat land (Undeveloped) - Residential Use	decimal
	NA Bhagayat land (Undeveloped) - Commercial Use	decimal
	NA Bhagayat land (Undeveloped) - Industrial Use	decimal
	Coconut Tree in Dry Land	decimal
	Coconut Tree in Wet Land	decimal
	Arecanut Tree in Dry Land	decimal
	Arecanut Tree in Wet Land	decimal
	Bagayath - Garasu	decimal
	Bagayath - Maradi	decimal
	Bagayath - Masari	decimal
	Bagayath - yari	decimal
	Dry, No Source of Irrigation, Black Soil	decimal

Indexes

Type	Name	On
	idxroadcodeonnewagritype	roadcode

Table agrilandroadrates_new

Idx	Name	Data Type
	roadcode	bigint
	Mining	decimal
	Dry No Source of IrrigRed Soil	decimal
	Dry No Source of IrrigOther	decimal
	Dry Paddy/Areca/Coconu Black Soil	decimal
	Dry Paddy/Areca/Coconu Red Soil	decimal
	Dry Paddy/Areca/Coconu Other Soil	decimal
	Dry Irrigation by pump Black Soil	decimal
	Dry Irrigation by pump Red Soil	decimal

Table agrilandroadrates_new

Dry Irrigation by pump Other Soil	decimal
Bagayat Dry	decimal
Bagayat Wet	decimal
Wet (Assured Water Supply from Government Tanks/Canals) Two Cro	decimal
Wet (Assured Water Supply from Government Tanks/Canals) Sugarca	decimal
Wet (Assured Water Supply from Government Tanks/Canals) One Cro	decimal
Wet (Assured Water Supply from Government Tanks/Canals) Lift Ir	decimal
Wet (Assured Water Supply from Government Tanks/Canals) Garden/	decimal
Plantation Coffee/Pepper	decimal
Plantation Cardamom/Pepper	decimal
Plantation Rubber/Areca nut	decimal
Plantation Tea	decimal
Plantation Teak	decimal
Wet Pond	decimal
Plantation Cashew Nut	decimal
Dry Agriculture Land Irrigated By Bore Other Soil	decimal
Dry No Source of Irrig Loamy Soil	decimal
Dry Paddy/Areca/Coconu	decimal
Dry Irrigation by pump loamy Soil	decimal
DryArecacoconut	decimal
Plantation Coffee(Low Grade)	decimal
Plantation Coffee(High Grade)	decimal
Bagayat Coconut(Plant Within 2 years)	decimal
Bagayat Coconut	decimal
Bagayat Arecanut & venilla(Plant Within 2 years)	decimal
Bagayat Arecanut & venilla	decimal
Plantation Cardamom/Pepper(Lo	decimal
Plantation Cardamom/Pepper(Hi	decimal
Plantation Coffee/Cardamom	decimal
Plantation Coffee/Cardamom/Pe	decimal
Dry No Source of IrrigMaradi	decimal
Dry No Source of Irrig Garasu	decimal
Non-Agriculture Land	decimal
Dry Agriculture Land Irrigated By Bore Black Soil	decimal
Dry Agriculture Land Irrigated By Bore Red Soil	decimal
NA Dry land (Undeveloped) - Residential Use	decimal
NA Dry land (Undeveloped) - Commercial Use	decimal
NA Dry land (Undeveloped) - Industrial Use	decimal
NA Dry land Industrial Purpose (developed)	decimal
NA Wet land (Undeveloped) - Residential Use	decimal
NA Wet land (Undeveloped) - Commercial Use	decimal
NA Wet land (Undeveloped) - Industrial Use	decimal
NA Bhagayat land (Undeveloped) - Residential Use	decimal
NA Bhagayat land (Undeveloped) - Commercial Use	decimal
NA Bhagayat land (Undeveloped) - Industrial Use	decimal
Coconut Tree in Dry Land	decimal

Table agrilandroadrates_new

	Coconut Tree in Wet Land	decimal
	Arecanut Tree in Dry Land	decimal
	Arecanut Tree in Wet Land	decimal
	Bagayath - Garasu	decimal
	Bagayath - Maradi	decimal
	Bagayath - Masari	decimal
	Bagayath - yari	decimal
	Dry No Source of Irrig Black Soil	decimal

Table agrilandtypemaster

Idx	Name	Data Type
* Pk	agrilandtypeid	integer
*	agrilandtypenamee	varchar(255)
*	agrilandtypenamek	varchar(255)
	inserteddatetime	timestamp DEFAULT CURRENT_TIMESTAMP
	k1k2_flag	smallint DEFAULT 2

Indexes

Type	Name	On
Pk	pk_agrilandtypemaster	agrilandtypeid
	idx_agrilandtypemaster_ag	agrilandtypeid

Table alienatedconsentbhoomisearch

Idx	Name	Data Type
	propertyid	integer
	isbuilding	boolean
	applicationnumber	varchar(50)

Table ams_bankinstrumentnumberdetails

Idx	Name	Data Type
* Pk	row_id	integer
	instrumentnumber	varchar(100)
	instrumentdate	date
	stamptypeid	integer
	receiptpaymentmode	bigint
	receiptid	bigint
	stampdetailsid	bigint
	receiptnumber	integer
	receipt_stampdate	timestamp
	srocode	integer
	drocode	integer
	isdro	integer
	uniquereqid	decimal
	inserteddatetime	timestamp
	sourceofreceipt	varchar(100)
	isthroughsyncoperation	integer
	amount	decimal
	serviceid	integer
	documentid	bigint

Table ams_bankinstrumentnumberdetails

	documentpendingnumber	varchar(100)
	partyname	varchar(1000)
	k1k2_flag	integer DEFAULT 2

Indexes

Type	Name	On
Pk	pk_rowid	row_id

Table ams_mas_epaymentstatus

Idx	Name	Data Type
* Pk	paymentstatuscode	varchar(25)
	paymentstatus	varchar(25)
	paymentstatusdesc	varchar(500)
	k1k2_flag	smallint DEFAULT 2

Indexes

Type	Name	On
Pk	pk_paymntstatuscode_ams_mas_epaymentstatus	paymentstatuscode

Table ams_refundchallandetails

Idx	Name	Data Type
* Pk	rowid	bigint
	instrumentnumber	varchar(50)
	instrumentdate	timestamp
	srocode	integer
	drocode	integer
	isdrapproved	boolean
	applicationdatetime	timestamp
	challanamount	decimal
	partyname	varchar(1000)
	rejectionreason	varchar(200)
	srouserid	bigint
	drouserid	bigint
	approvedatetime	timestamp
	partymobilenumber	varchar(11)
	refundamount	decimal
	isfinalized	boolean
	insertdatetime	timestamp
	absolutefilepath	varchar(1000)
	relativepath	varchar(1000)
	filename	varchar(500)
	ordernumber	varchar(200)
	orderdate	timestamp
	k1k2_flag	smallint DEFAULT 2

Indexes

Type	Name	On
Pk	pk_refundchallandetails	rowid

Table ams_refundchallanusagedetails

Idx	Name	Data Type

Table ams_refundchallanusagedetails

* Pk	id	bigint
	rowid	bigint
	challanpurposedescription	varchar(500)
	feerulecode	integer
	inserteddatetime	timestamp DEFAULT CURRENT_TIMESTAMP
	k1k2_flag	smallint DEFAULT 2

Indexes

Type	Name	On
Pk	pk_refundchallanusagedetails	id

Table ams_reg_epaymentamtpaiddetails

Idx	Name	Data Type
* Idx	chlnrefnum	varchar(23)
*	deptpurposeid	smallint
*	headofaccount	varchar(50)
* Idx	amountpaid	bigint
Idx	applicationnumber	varchar(50)
Idx	deptreferencecode	varchar(18)
Idx	totalamount	bigint
* Pk	id	bigint DEFAULT nextval('kaveri.ams_reg_epaymentamtpaiddetails_id_seq'::regclass)
	inserteddatetime	timestamp DEFAULT CURRENT_TIMESTAMP
	k1k2_flag	smallint DEFAULT 2

Indexes

Type	Name	On
	idx_ams_reg_epaymentamtpaiddetails_applicationnumber	applicationnumber
Pk	pk_id_ams_reg_epaymentamtpaiddetails	id
	idx_ams_reg_epaymentamtpaiddetails_amountpaid	amountpaid
	idx_ams_reg_epaymentamtpaiddetails_chlnrefnum	chlnrefnum
	idx_ams_reg_epaymentamtpaiddetails_deptre	deptreferencecode
	idx_ams_reg_epaymentamtpaiddetails_totalamount	totalamount

Table ams_reg_epaymentamtpaiddetails_cd140

Idx	Name	Data Type
	chlnrefnum	varchar(23)
	deptpurposeid	smallint
	headofaccount	varchar(50)
	amountpaid	bigint
	applicationnumber	varchar(50)
	deptreferencecode	varchar(18)
	totalamount	bigint
	id	bigint
	inserteddatetime	timestamp
	k1k2_flag	smallint

Table ams_reg_epaymentbankackdetails

Idx	Name	Data Type
* Unq	deptreferencecode	varchar(18)

Table ams_reg_epaymentbankackdetails

* Unq	banktransactionnumber	varchar(30)
*	bankname	varchar(50)
	paymentmode	varchar(30)
* Unq	paymentstatuscode	varchar(25)
*	transactiontimestamp	timestamp
	amount	bigint
	checksum	varchar(100)
* Pk	transactionid	bigint DEFAULT nextval('kaveri.ams_reg_epaymentbankackdetails_transactionid_seq'::regclass)
	bankackid	bigint
	inserteddatetime	timestamp DEFAULT CURRENT_TIMESTAMP
	k1k2_flag	smallint DEFAULT 2

Indexes

Type	Name	On
Unq	uq_ams_reg_epaybankdtls	deptreferencecode, banktransactionnumber, paymentstatuscode
Pk	pk_tranid_ams_reg_epaymentbankackdetails	transactionid

Table ams_reg_epaymentbankackdetails_cd140

Idx	Name	Data Type
	deptreferencecode	varchar(18)
	banktransactionnumber	varchar(30)
	bankname	varchar(50)
	paymentmode	varchar(30)
	paymentstatuscode	varchar(25)
	transactiontimestamp	timestamp
	amount	bigint
	checksum	varchar(100)
	transactionid	bigint
	bankackid	bigint
	inserteddatetime	timestamp
	k1k2_flag	smallint

Table ams_reg_epaymenttransdetails

Idx	Name	Data Type
	applicationid	bigint
*	officeid	smallint
*	remittername	varchar(50)
*	totalamount	bigint
	receiptid	bigint
Idx	chlnrefnum	varchar(23)
Idx	deptreferencecode	varchar(18)
	uirnumber	varchar(75)
	statuscode	varchar(50)
	statusdescription	varchar(100)
	transactionstatus	bit(1)
	transactiondatetime	timestamp
	userid	bigint
	ipadd	varchar(15)

Table ams_reg_epaymenttransdetails

	serviceid	integer
	paymentstatuscode	varchar(25)
Idx	ecid	bigint
Idx	ccid	bigint
	epid	bigint
Idx	applicationnumber	varchar(50)
	treasurycode	varchar(20)
* Pk	transactionid	bigint DEFAULT nextval('kaveri.ams_reg_epaymenttransdetails_transactionid_seq'::regclass)
	ddocode	bigint
	isdelete	boolean DEFAULT false
	lastupdateddate	timestamp DEFAULT CURRENT_TIMESTAMP
	documentid	bigint
	feerulecode	integer
	inserteddatetime	timestamp DEFAULT CURRENT_TIMESTAMP
	k1k2_flag	smallint DEFAULT 2

Indexes

Type	Name	On
	idx_ams_reg_epaymenttransdetails_appnum	applicationnumber
Pk	pk_tranid_ams_reg_epaymenttransdetails	transactionid
	idx_ams_reg_epaymenttransdetails_chlnrefnum	chlnrefnum
	idx_ams_reg_epaymenttransdetails_ecid	ecid
	idx_ams_reg_epaymenttransdetails_ccid	ccid
	idx_ams_reg_epaymenttransdetails_deptref_ccnew2	deptreferencecode

Table ams_reg_epaymenttransdetails_cd140

Idx	Name	Data Type
	applicationid	bigint
	officeid	smallint
	remittername	varchar(50)
	totalamount	bigint
	receiptid	bigint
	chlnrefnum	varchar(23)
	deptreferencecode	varchar(18)
	uirnumber	varchar(75)
	statuscode	varchar(50)
	statusdescription	varchar(100)
	transactionstatus	bit(1)
	transactiondatetime	timestamp
	userid	bigint
	ipadd	varchar(15)
	serviceid	integer
	paymentstatuscode	varchar(25)
	ecid	bigint
	ccid	bigint
	epid	bigint
	applicationnumber	varchar(50)
	treasurycode	varchar(20)

Table ams_reg_epaymenttransdetails_cd140

	transactionid	bigint
	ddocode	bigint
	isdelete	boolean
	lastupdateddate	timestamp
	documentid	bigint
	feerulecode	integer
	inserteddatetime	timestamp
	k1k2_flag	smallint

Table ams_reg_khajaneresponselog

Idx	Name	Data Type
Idx	deptreferencecode	varchar(18)
	datetimestamp	timestamp
	khajanexmlrespone	text
	khajaneinputxml	text
Idx	applicationnumber	varchar(50)
	transactionid	varchar(50)
* Pk	logid	bigint DEFAULT nextval('kaveri.ams_reg_khajaneresponselog_logid_seq'::regclass)
	inserteddatetime	timestamp DEFAULT CURRENT_TIMESTAMP
	k1k2_flag	smallint DEFAULT 2

Indexes

Type	Name	On
	idx_ams_reg_khajaneresponselog_applicationnumber	applicationnumber
Pk	pk_logid_ams_reg_khajaneresponselog	logid
	idx_ams_reg_khajaneresponselog_deptref	deptreferencecode

Table ams_reg_khajaneresponselog_cd140

Idx	Name	Data Type
	deptreferencecode	varchar(18)
	datetimestamp	timestamp
	khajanexmlrespone	text
	khajaneinputxml	text
	applicationnumber	varchar(50)
	transactionid	varchar(50)
	logid	bigint
	inserteddatetime	timestamp
	k1k2_flag	smallint

Table anywhere_reg_log

Idx	Name	Data Type
* Pk	logid	integer DEFAULT nextval('kaveri.anywhere_reg_log_logid_seq'::regclass)
	documentid	bigint
Idx	applicationnumber	varchar
Idx	propertyid	bigint
Idx	regsrocode	bigint
	srocode	bigint

Table anywhere_reg_log

	ismemosent	boolean
	isjurisdictionsroaccepted	boolean
	inserteddatetime	timestamp DEFAULT CURRENT_TIMESTAMP
	k1k2_flag	smallint DEFAULT 2
	memosentdatetime	timestamp
	memoaccepteddatetime	timestamp
Idx	newapplicationnumber	varchar(50)

Indexes

Type	Name	On
	idx_anywhere_reg_log_regsrocode	regsrocode
	idx_anywhere_reg_log_applicationnumber	applicationnumber
	anywhere_reg_log_newapplicationnumber_idx	newapplicationnumber
	idx_anywhere_reg_log_propertyid	propertyid
	idx_anywhere_reg_log	applicationnumber, propertyid, regsrocode
Pk	anywhere_reg_log_pkey	logid

Foreign Keys

Type	Name	On
	anywhere_reg_log_applicationnumber_fkey (applicationnumber) ref applicantapplicationdetails (applicationnumber)	

Table applicantapplicationdetails

Idx	Name	Data Type
* Pk	citizenid	bigint
* Pk	applicationnumber	varchar(50)
Idx	srocode	integer
Idx	regsrocode	integer
	applicationtypeid	integer
	applicationstartdate	timestamp DEFAULT now()
	applicationenddate	timestamp
* Idx	currentstatus	varchar(5)
Idx	assignedto	text
	aroapplicationnumber	varchar(50)
	stamparticlecode	integer
	stampruleid	integer
	deedattachpath	text
	registrationstartdate	timestamp
	registrationenddate	timestamp
	lastupdatedby	text
Idx	regarticlecode	integer
	bookid	integer
	remarks	text
Idx	sfdaid	bigint
Idx	deoid	bigint
	applicationdate	timestamp
	issubmitted	boolean DEFAULT false
	isduecorrection	boolean DEFAULT false
	ispayment	boolean
	isdueschedule	boolean
	annexurepath	text

Table applicantapplicationdetails

	k1k2_flag	smallint DEFAULT 2
	inserteddatetime	timestamp DEFAULT CURRENT_TIMESTAMP
	refuseremarks	text
	remarksk	text
*	isdeleted	boolean DEFAULT false

Indexes

Type	Name	On
	idx_applicantapplicationdetails_deoids	deoid
	idx_applicantapplicationdetails_regarticlecode	regarticlecode
Pk	pk_applicantapplicationdetails	citizenid, applicationnumber
Unq	uk_applicantapplicationdetails	applicationnumber
	idx_applicantapplicationdetails_assignedto	assignedto
	idx_applicationdetails_currentstatus	currentstatus
	idx_applicantapplicationdetails_regsrocode	regsrocode, srocode
	idx_applicationdetails_sfdaid	sfdaid

Table applicantapplicationdetails_11092023

Idx	Name	Data Type
	citizenid	bigint
* Pk	applicationnumber	varchar(50)
	srocode	integer
	regsrocode	integer
	applicationtypeid	integer
	applicationstartdate	timestamp
	applicationenddate	timestamp
	currentstatus	varchar(5)
	assignedto	text
	aroapplicationnumber	varchar(50)
	stamparticlecode	integer
	stampruleid	integer
	deedattachpath	text
	registrationstartdate	timestamp
	registrationenddate	timestamp
	lastupdatedby	text
	regarticlecode	integer
	bookid	integer
	remarks	text
	sfdaid	bigint
	deoid	bigint
	applicationdate	timestamp
	issubmitted	boolean
	isduecorrection	boolean
	ispayment	boolean
	isdueschedule	boolean
	annexurepath	text
	k1k2_flag	smallint
	inserteddatetime	timestamp
	refuseremarks	text

Table applicantapplicationdetails_11092023

	remarksk	text

Indexes

Type	Name	On
Pk	pk_applicantapplicationdetails_11_applicationnumber	applicationnumber

Table applicantapplicationdetails_bck_newregpay

Idx	Name	Data Type
	citizenid	bigint
	applicationnumber	varchar(50)
	srocode	integer
	regsrocode	integer
	applicationtypeid	integer
	applicationstartdate	timestamp
	applicationenddate	timestamp
	currentstatus	varchar(5)
	assignedto	text
	aroapplicationnumber	varchar(50)
	stamparticlecode	integer
	stampruleid	integer
	deedattachpath	text
	registrationstartdate	timestamp
	registrationenddate	timestamp
	lastupdatedby	text
	regarticlecode	integer
	bookid	integer
	remarks	text
	sfdaid	bigint
	deoid	bigint
	applicationdate	timestamp
	issubmitted	boolean
	isduecorrection	boolean
	ispayment	boolean
	isdueschedule	boolean
	annexurepath	text
	k1k2_flag	smallint
	inserteddatetime	timestamp
	refuseremarks	text
	remarksk	text
	isdeleted	boolean

Table applicantapplicationdetails_cd140

Idx	Name	Data Type
	citizenid	bigint
	applicationnumber	varchar(50)
	srocode	integer
	regsrocode	integer
	applicationtypeid	integer
	applicationstartdate	timestamp

Table applicantapplicationdetails_cd140

	applicationenddate	timestamp
	currentstatus	varchar(5)
	assignedto	text
	aroapplicationnumber	varchar(50)
	stamparticlecode	integer
	stampruleid	integer
	deedattachpath	text
	registrationstartdate	timestamp
	registrationenddate	timestamp
	lastupdatedby	text
	regarticlecode	integer
	bookid	integer
	remarks	text
	sfdaid	bigint
	deoid	bigint
	applicationdate	timestamp
	issubmitted	boolean
	isduecorrection	boolean
	ispayment	boolean
	isdueschedule	boolean
	annexurepath	text
	k1k2_flag	smallint
	inserteddatetime	timestamp
	refuseremarks	text
	remarksk	text

Table applicantapplicationdetails_newregepayment

Idx	Name	Data Type
	citizenid	bigint
	applicationnumber	varchar(50)
	srocode	integer
	regsrocode	integer
	applicationtypeid	integer
	applicationstartdate	timestamp
	applicationenddate	timestamp
	currentstatus	varchar(5)
	assignedto	text
	aroapplicationnumber	varchar(50)
	stamparticlecode	integer
	stampruleid	integer
	deedattachpath	text
	registrationstartdate	timestamp
	registrationenddate	timestamp
	lastupdatedby	text
	regarticlecode	integer
	bookid	integer
	remarks	text
	sfdaid	bigint

Table applicantapplicationdetails_newregepayment

	deoid	bigint
	applicationdate	timestamp
	issubmitted	boolean
	isduecorrection	boolean
	ispayment	boolean
	isdueschedule	boolean
	annexurepath	text
	k1k2_flag	smallint
	inserteddatetime	timestamp
	refuseremarks	text
	remarksk	text
	isdeleted	boolean

Table applicantapplicationdetails_newregpayment

Idx	Name	Data Type
	citizenid	bigint
	applicationnumber	varchar(50)
	srocode	integer
	regsrocode	integer
	applicationtypeid	integer
	applicationstartdate	timestamp
	applicationenddate	timestamp
	currentstatus	varchar(5)
	assignedto	text
	aroapplicationnumber	varchar(50)
	stamparticlecode	integer
	stampruleid	integer
	deedattachpath	text
	registrationstartdate	timestamp
	registrationenddate	timestamp
	lastupdatedby	text
	regarticlecode	integer
	bookid	integer
	remarks	text
	sfdaid	bigint
	deoid	bigint
	applicationdate	timestamp
	issubmitted	boolean
	isduecorrection	boolean
	ispayment	boolean
	isdueschedule	boolean
	annexurepath	text
	k1k2_flag	smallint
	inserteddatetime	timestamp
	refuseremarks	text
	remarksk	text
	isdeleted	boolean

Table applicantdashboarddetails

Idx	Name	Data Type
Idx	applicationtypeid	integer
Idx	applicationtypename	varchar(100)
Idx	bookid	integer
Idx	bookname	varchar(150)
Idx	cnt_totalapplication	bigint
	lastrefreshdate	timestamp

Indexes

Type	Name	On
	idx_applicantdashboarddetila_app	applicationtypeid, applicationtypename, bookid, bookname, cnt_totalapplication

Table application_audit_scrutiny_history

Idx	Name	Data Type	Description
*	id	bigint DEFAULT nextval('kaveri.application_audit_scrutiny_history_seq'::regclass)	
*	applicationnumber	varchar(50)	
*	app_srocode	integer	
*	previous_auditor	bigint	
*	previous_auditor_srocode	integer	
*	current_auditor	bigint	
*	current_auditor_srocode	integer	
*	previous_dateofallocation	timestamp DEFAULT CURRENT_TIMESTAMP	
*	current_dateofallocation	timestamp DEFAULT CURRENT_TIMESTAMP	
*	status	smallint DEFAULT 1	1-Assigned 2-Re-Assigned 3-Completed
*	inserted_date	timestamp DEFAULT CURRENT_TIMESTAMP	

Table application_audit_scrutiny_queue

Idx	Name	Data Type	Description
*	id	bigint DEFAULT nextval('kaveri.application_audit_scrutiny_queue_seq'::regclass)	
*	service_id	bigint	
*	queue_id	bigint	
*	applicationnumber	varchar(50)	
*	status	smallint DEFAULT 1	1-PENDING 2-PROCESSED 3-CANCELLED 4-NOT VALID 5-RETRY
	queue_data	text	
*	inserted_date	timestamp DEFAULT CURRENT_TIMESTAMP	
	srocode	integer	

Table application_for_scrutiny_property_master

Idx	Name	Data Type

Table application_for_scrutiny_property_master

*	id	bigint DEFAULT nextval('kaveri.application_for_scrutiny_property_master_id_seq'::regclass)
* Idx	propertyid	bigint
	auditorstamparticlecode	bigint
	auditorstampruleid	bigint
	auditorregarticlecode	bigint
	auditormarketvalue	decimal
	auditorconsideration	decimal
Idx	applicationnumber	varchar(50)
	inserteddatetime	timestamp DEFAULT CURRENT_TIMESTAMP
	auditorroadcode	bigint
	auditornoofscanpages	integer
	auditorvaluationreport	varchar
	auditorstampduty	decimal
	auditorcessduty	decimal
	auditorsurcharge	decimal

Indexes

Type	Name	On
	application_for_scrutiny_property_master_propertyid_idx	propertyid
	idx_application_for_scrutiny_property_master_appno_ccnew	applicationnumber
	idx_application_for_scrutiny_property_master_appno	applicationnumber

Table applicationaudit

Idx	Name	Data Type
* Idx	applicationnumber	varchar(50)
Idx	srocode	integer
* Idx	wrkflowstatusid	varchar(5)
	activityby	text
	activityorder	decimal(10,0)
	remarks	text
	remarks1	text
	remarks2	text
	crtusr	varchar(10)
Idx	crtdt	timestamp DEFAULT now()
	k1k2_flag	smallint DEFAULT 2

Indexes

Type	Name	On
	indx_appaudit_crtwrk	wrkflowstatusid, crtdt
	indx_appaudit_appnumbr	applicationnumber
	indx_appaudit_crtdt	crtdt
	indx_appaudit_srocode	srocode
	indx_appaudit_wrkflowstatusid	wrkflowstatusid

Foreign Keys

Type	Name	On
	fk_applicationaudit_applicantapplicationdetails (applicationnumber) ref applicantapplicationdetails (applicationnumber)	

Table applicationaudit_dashboard

Idx	Name	Data Type

Table applicationaudit_dashboard

	applicationnumber	varchar(50)
	srocode	integer
	wrkflowstatusid	varchar(5)
	activityby	text
	activityorder	decimal(10,0)
	remarks	text
	remarks1	text
	remarks2	text
	crtusr	varchar(10)
	crtdt	timestamp
	k1k2_flag	smallint

Table applicationdetails

Idx	Name	Data Type
* Pk	applicationid	bigint
*	applicationnumber	varchar(30)
*	applicationtypeid	integer
*	applicantname	varchar(100)
*	applicationdate	timestamp
* Pk	requestfromsro	integer
*	requesttosro	integer
*	searchfromdate	timestamp
*	searchtodate	timestamp
*	villagecode	bigint
*	iscertificategenerated	boolean
	countrycode	varchar(4)
	mobilenumber	varchar(11)
	email	varchar(100)
*	ownerno	integer
	propertyschedule	varchar(1000)
	sroapplicationnumber	varchar(30)
	inserteddatetime	timestamp DEFAULT CURRENT_TIMESTAMP
	k1k2_flag	smallint DEFAULT 2

Indexes

Type	Name	On
Pk	pk_applicationdetails	applicationid, requestfromsro

Table applicationforscrutiny

Idx	Name	Data Type
* Pk	id	bigint DEFAULT nextval('kaveri.applicationforscruitny_id_seq'::regclass)
Unq	applicationnumber	varchar(50)
Idx	regarticlecode	bigint
	auditor	integer
	dateofallocation	timestamp
	noofallocations	integer
	isaccepted	boolean
	sr_remarks	varchar(1000)
	isauditcompleted	boolean

Table applicationforscrutiny

	auditcompleteddatetime	timestamp
	audtr_rmrksfilepath	varchar(1000)
	inserteddatetime	timestamp DEFAULT CURRENT_TIMESTAMP
Idx	stamparticlecode	integer
Idx	stampruleid	integer
	auditorstampruleid	integer
	auditorstamparticlecode	integer
	srocode	integer
	auditorregarticlecode	bigint
	auditormarketvalue	decimal
	auditorconsideration	decimal
	isauditexpired	boolean DEFAULT false

Indexes

Type	Name	On
Pk	pk_applicationforscruitny_id	id
Unq	applicationforscrutiny_un	applicationnumber
	applicationforscrutiny_stampruleid_idx_ccnew	stampruleid
	applicationforscrutiny_regarticlecode_idx_ccnew	regarticlecode
	applicationforscrutiny_regarticlecode_idx_ccnew1	regarticlecode
	applicationforscrutiny_stampruleid_idx_ccnew1	stampruleid
	applicationforscrutiny_stamparticlecode_idx_ccnew	stamparticlecode
	applicationforscrutiny_regarticlecode_idx	regarticlecode
	applicationforscrutiny_stamparticlecode_idx	stamparticlecode
	applicationforscrutiny_stampruleid_idx	stampruleid

Table applicationlimitdetails

Idx	Name	Data Type
* Pk	id	bigint DEFAULT nextval('kaveri.applicationlimitdetails_id_seq'::regclass)
	citizenid	bigint
Idx	applicationnumber	varchar(40)
	maxproperty	integer
	maxparty	integer
*	inserteddatetime	timestamp DEFAULT CURRENT_TIMESTAMP
	k1k2_flag	integer DEFAULT 2

Indexes

Type	Name	On
Pk	applicationlimitdetails_pkey	id
	idx_applicationnumber_limit	applicationnumber

Table applicationreviewdetails

Idx	Name	Data Type
* Pk	applicationreviewid	bigint DEFAULT nextval('kaveri.applicationreviewdetails_applicationreviewid_seq'::regclass)
Idx	reviewid	integer
Idx	applicationnumber	varchar(50)
	isverified	boolean DEFAULT false
	remarks	text

Table applicationreviewdetails

	deptuserid	bigint
	crtdate	timestamp DEFAULT now()
	issroremarks	boolean
	k1k2_flag	smallint DEFAULT 2

Indexes

Type	Name	On
Pk	pkey_applicationreviewdetails	applicationreviewid
	applicationreviewdetails_applicationnumber_idx	applicationnumber
	idx_applicationreviewdetails_rev	reviewid

Foreign Keys

Type	Name	On
	fk_applicationreviewdetails_applicantapplicationdetails (applicationnumber) ref applicantapplicationdetails (applicationnumber)	

Table applicationreviewmaster

Idx	Name	Data Type
* Pk	reviewid	integer DEFAULT nextval('kaveri.applicationreviewmaster_reviewid_seq'::regclass)
*	reviewname	text
	serviceid	integer
	k1k2_flag	smallint DEFAULT 2

Indexes

Type	Name	On
Pk	pkey_applicationreviewmaster	reviewid

Table applicationtypemaster

Idx	Name	Data Type
* Pk	applicationtypeid	integer
*	applicationtype	varchar(100)
	k1k2_flag	smallint DEFAULT 2

Indexes

Type	Name	On
Pk	pk_applicationtypemaster	applicationtypeid

Table applicationverification

Idx	Name	Data Type
* Pk	verify_id	bigint DEFAULT nextval('kaveri.applicationverification_verify_id_seq'::regclass)
	applicationnumber	varchar(100)
	eval_presentor	boolean
	eval_executiondate	boolean
	eval_partydetails	boolean
	eval_scheduleid	boolean
	eval_voluntaryexec	boolean
	eval_docclasstype	boolean
	eval_valuationduty	boolean
	eval_payment	boolean
	eval_requireddocuments	boolean
	eval_deedattachment	boolean
	eval_attestation	boolean

Table applicationverification

	inserteddatetime	timestamp DEFAULT CURRENT_TIMESTAMP
	k1k2_flag	smallint DEFAULT 2
	eval_annexure	boolean DEFAULT false
	eval_executantsbeforeme	boolean DEFAULT false

Indexes

Type	Name	On
Pk	pk_verifyid_applicationverification	verify_id

Table appointmentmaster

Idx	Name	Data Type
* Pk	appointmentid	integer DEFAULT nextval('kaveri.appointmentmaster_appointmentid_seq'::regclass)
	appointmenttypeid	integer
	srocode	integer
	deoperator	integer
Idx	applicationnumber	varchar(50)
Idx	appointmentdate	timestamp
	starttime	time
	endtime	time
	noofapplicants	integer
Idx	status	varchar(10)
	k1k2_flag	smallint DEFAULT 2
	inserteddatetime	timestamp DEFAULT CURRENT_TIMESTAMP
	reschedulefrmtool	boolean DEFAULT false

Indexes

Type	Name	On
	idx_appointmentmaster_status	status
Pk	appointmentmaster_pkey	appointmentid
	idx_appointmentmaster_appnumber	applicationnumber
	idx_appointmentmaster_appdate	appointmentdate

Table appointmenttypemaster

Idx	Name	Data Type
Idx	appointmenttypeid	integer
	appointmenttype	varchar
	k1k2_flag	smallint DEFAULT 2

Indexes

Type	Name	On
	idx_appointmenttypemaster	appointmenttypeid

Table areatypemaster

Idx	Name	Data Type
* Pk	areatypeid	integer
*	descriptione	varchar(100)
*	descriptionk	varchar(100)
*	rate	decimal
	inserteddatetime	timestamp DEFAULT CURRENT_TIMESTAMP
	k1k2_flag	smallint DEFAULT 2

Table areatypemaster

Indexes

Type	Name	On
Pk	pk_areatypemaster	areatypeid

Table aregisterfiledetails

Idx	Name	Data Type
* Pk	fileid	bigint
	districtcode	integer
* Pk	srocode	integer
	searchsrocode	integer
	searchdrocode	integer
	searchdate	timestamp
	filegenerationdate	timestamp
	isdroffice	boolean
	pfilepath	varchar(500)
	vfilepath	varchar(500)
	userid	bigint
	id	bigint
	inserteddatetime	timestamp DEFAULT CURRENT_TIMESTAMP
	k1k2_flag	smallint DEFAULT 2

Indexes

Type	Name	On
Pk	pk_aregisterfiledetails	fileid, srocode

Table aregistergenerationdetails

Idx	Name	Data Type
* Pk	id	bigint
* Pk	srocode	integer
	receiptdate	timestamp
	isreceiptssynchronized	boolean
	isaregistergenerated	boolean
	inserteddatetime	timestamp DEFAULT CURRENT_TIMESTAMP
	k1k2_flag	smallint DEFAULT 2

Indexes

Type	Name	On
Pk	pk_aregistergenerationdetails	id, srocode

Table articlefeecalculationdetails

Idx	Name	Data Type
*	id	bigint GENERATED ALWAYS AS IDENTITY
*	applicationnumber	varchar(50)
	propertyid	integer
	stampruleid	integer
	ownerratio	decimal(18,4)
	moneyfromowner	integer
	moneyfrombuilder	integer
	moneyifany	integer
	insupddate	timestamp DEFAULT CURRENT_TIMESTAMP

Table articlefeecalculationdetails

Foreign Keys

Type	Name	On
	fk_applictiondetails_appno (applicationnumber) ref applicantapplicationdetails (applicationnumber)	

Table articlesuppdoc

Idx	Name	Data Type
* Pk	articlesuppid	integer
* Pk	regarticlecode	integer
* Pk	supportdocid	integer
	k1k2_flag	smallint DEFAULT 2

Indexes

Type	Name	On
Pk	pk_articlesupport	articlesuppid, regarticlecode, supportdocid

Table authoritymaster

Idx	Name	Data Type
* Pk	id	integer
	name	char(50)
	inserteddatetime	timestamp DEFAULT CURRENT_TIMESTAMP
	k1k2_flag	smallint DEFAULT 2

Indexes

Type	Name	On
Pk	pk_authoritymaster	id

Table bankbranchdetailsmaster

Idx	Name	Data Type
*	id	bigint DEFAULT nextval('kaveri.bankbranchdetailsmaster_id_seq'::regclass)
	bankname	varchar(500)
Unq	ifsc	varchar(15)
	branchname	varchar(250)
	bankaddress	text
	city1	varchar(100)
	city2	varchar(100)
	state	varchar(100)
	stdcode	integer
	phone	varchar(15)
	activestatus	boolean DEFAULT true
	inserteddatetime	timestamp DEFAULT CURRENT_TIMESTAMP
	k1k2_flag	smallint DEFAULT 2

Indexes

Type	Name	On
Unq	uniq_ifsc_bankbranchdetailsmaster	ifsc

Table bannedparties

Idx	Name	Data Type
	partyid	bigint
* Pk	srocode	integer

Table bannedparties

*	orderid	bigint
	firstname	varchar(1000)
	middlename	varchar(1000)
	lastname	varchar(1000)
	age	integer
	address	varchar(1000)
* Pk	courtpartyid	bigint DEFAULT nextval('kaveri.bannedparties_courtpartyid_seq'::regclass)
	orderid_old	bigint
	isdelete	boolean DEFAULT false
	salutation	varchar(10)
	house_building_name	varchar(200)
	statecode	integer
	districtcode	integer
	villagecode	bigint
	pincode	integer
	inserteddatetime	timestamp DEFAULT CURRENT_TIMESTAMP
	k1k2_flag	smallint DEFAULT 2

Indexes

Type	Name	On
Pk	pk_courtpartyid_bannedparties	courtpartyid, srocode

Table bannedproperties

Idx	Name	Data Type
Idx	propertyid	bigint
* Pk	srocode	integer
* Idx	orderid	bigint
*	jurisdictionsrcode	integer
*	villagecode	bigint
	propertydescription	varchar(1000)
*	isagriculturalproperty	boolean
	northboundary	varchar(500)
	southboundary	varchar(500)
	eastboundary	varchar(500)
	westboundary	varchar(500)
	extentinformation	varchar(500)
	area	decimal(18,4) DEFAULT 0
Idx	measurementunit	integer DEFAULT 0
* Pk	courtpropertyid	bigint DEFAULT nextval('kaveri.bannedproperties_courtpropertyid_seq'::regclass)
	orderid_old	bigint
	isdelete	boolean DEFAULT false
	inserteddatetime	timestamp DEFAULT CURRENT_TIMESTAMP
	k1k2_flag	smallint DEFAULT 2

Indexes

Type	Name	On
	idx_bannedproperties_measurementunit	measurementunit
	idx_bannedproperties_orderid	orderid
Pk	pk_bannedproperties_propidsrocode	courtpropertyid, srocode

Table bannedproperties

	bannedproperties_propid_indx	propertyid

Table bannedpropertynumbers

Idx	Name	Data Type
	id	bigint
* Pk	srocode	integer
Idx	propertyid	bigint
Idx	orderid	bigint
Idx	currentpropertytypeid	integer
	currentnumber	varchar(300)
	oldpropertytypeid	integer
	oldnumber	varchar(300)
	description	varchar(1000)
	survey_no	integer
	surnoc	varchar(20)
	hissa_no	varchar(30)
	injuction_or_stay_flag	varchar
* Pk	courtpropertynumberid	bigint DEFAULT nextval('kaveri.bannedpropertynumbers_courtpropertynumberid_seq'::regclass)
	orderid_old	bigint
	propertyid_old	bigint
	isdelete	boolean DEFAULT false
	inserteddatetime	timestamp DEFAULT CURRENT_TIMESTAMP
	k1k2_flag	smallint DEFAULT 2

Indexes

Type	Name	On
Pk	pk_courtpropertynumberid_courtpropertynumberid	courtpropertynumberid, srocode
	idx_bannedpropertynumber_orderid	orderid
	idx_bannedpropertynumber_propertyid	propertyid
	idx_bannedpropertynumber_srocode	srocode
	idx_bannedpropertynumbers_orderid	currentpropertytypeid

Table bbmpxml

Idx	Name	Data Type
* Pk	logid	bigint
* Pk	documentid	bigint
* Pk	propertyid	bigint
* Pk	srocode	integer
	inputownerdetails	text
	ownerdetails	text
	verified	boolean
	transactingextent	decimal(18,0)
	isuploaded	boolean
	acknumber	bigint
	uploaddatetime	timestamp
	inserteddatetime	timestamp DEFAULT CURRENT_TIMESTAMP
	k1k2_flag	smallint DEFAULT 2

Indexes

Table bbmpxml

Type	Name	On
Pk	pk_bbmpxml	logid, documentid, propertyid, srocode

Table bchain_property

Idx	Name	Data Type
* Pk	propertyid	bigint
	blockchainpropertyid	varchar(400)
	assignedblockchainpid	varchar(200)
	srocode	integer
	inserteddatetime	timestamp DEFAULT CURRENT_TIMESTAMP
	k1k2_flag	smallint DEFAULT 2

Indexes

Type	Name	On
Pk	pk_bchainprop_propid	propertyid

Table bchain_response

Idx	Name	Data Type
* Pk	responseid	bigint
*	integrationid	bigint
*	requestid	bigint
*	responsetext	varchar
*	inserteddatetime	timestamp
	status	boolean
	k1k2_flag	smallint DEFAULT 2

Indexes

Type	Name	On
Pk	pk_bchain_response	responseid

Table bda_fileuploaddetails

Idx	Name	Data Type
* Pk	referenceid	bigint DEFAULT nextval('kaveri.referenceid_seq_bdafile'::regclass)
	uploaddate	timestamp
	jslipxml	text
	acknowledgeno	varchar(8000)
	finalregistrationnumber	varchar(50)
	remarks	text
	pid	varchar(100)
	k1k2_flag	smallint

Indexes

Type	Name	On
Pk	pk_referenceid_bda_fileuploaddetails_fileuploaddetails	referenceid

Table bdaxml

Idx	Name	Data Type
* Pk	logid	bigint
* Pk	srocode	integer
*	documentid	bigint

Table bdaxml

*	propertyid	bigint
	inputownerdetails	text
	ownerdetails	text
	verified	boolean
	isuploaded	boolean
	acknumber	bigint
	ackxmldetails	text
	isboundaryimported	boolean
	uploaddatetime	timestamp
	sentxmldetails	text
*	istransmitted	boolean
	inserteddatetime	timestamp DEFAULT CURRENT_TIMESTAMP
	k1k2_flag	smallint DEFAULT 2

Indexes

Type	Name	On
Pk	pk_bdaxml	logid, srocode

Table bhoomi_old_method_jslip_acknowledgment_details

Idx	Name	Data Type
*	id	integer GENERATED BY DEFAULT AS IDENTITY
*	bhoomi_old_method_jslip_acknowledgment_id	bigint
	finalregistrationnumber	varchar(100) DEFAULT NULL::character varying
	initialstatus	text
	receiveddate	timestamp
	receivedmethod	varchar(30) DEFAULT NULL::character varying
	registrationdate	date
	acknowledgeno	integer
	talukname	varchar(100) DEFAULT NULL::character varying
*	bhoomi_fetch_success	smallint DEFAULT 0
*	bhoomi_fetch_fail	smallint DEFAULT 0
	bhoomi_message	text
*	created_at	timestamp DEFAULT CURRENT_TIMESTAMP
*	updated_at	timestamp DEFAULT CURRENT_TIMESTAMP
	deleted_at	timestamp

Table bhoomi_old_method_jslip_acknowledgments

Idx	Name	Data Type
*	id	integer GENERATED BY DEFAULT AS IDENTITY
	name	varchar(255) DEFAULT NULL::character varying
	path	text
*	data_imported	smallint DEFAULT 0
*	fetch_status	smallint DEFAULT 0
	uploaded_by	bigint
*	created_at	timestamp DEFAULT CURRENT_TIMESTAMP
*	updated_at	timestamp DEFAULT CURRENT_TIMESTAMP
	deleted_at	timestamp

Table bhoomicategoriesmaster

Idx	Name	Data Type
* Pk	categoryid	integer
	categorycode	varchar(3)
	description	varchar(100)
	istransactionallow	varchar(3)
	inserteddate	timestamp DEFAULT CURRENT_TIMESTAMP
	username	varchar(20)
	k1k2_flag	smallint DEFAULT 2

Indexes

Type	Name	On
Pk	pk_boomicategoriesmaster_categoryid	categoryid

Table bhoomicents_data

Idx	Name	Data Type
	bhoomi_district_code	integer
	bhoomi_taluk_code	integer
	unit	varchar(50)

Table bhoomidistrictmaster

Idx	Name	Data Type
* Pk	districtcode	integer
*	districtnamee	varchar(75)
*	districtnamek	varchar(150)
	shortnamee	varchar(5)
	shortnamek	varchar(15)
	digcode	integer
	bhoomidistrictcode	integer
	k1k2_flag	smallint DEFAULT 2

Indexes

Type	Name	On
Pk	pk_bhoomidistrictmaster	districtcode

Table bhoomifileuploaddetails

Idx	Name	Data Type
* Pk	referenceid	bigint
	uploaddate	timestamp
*	jslipxml	text
*	jslipindexxml	text
	jslipxmlfinal	text
	jslipindexxmlfinal	text
	acknowledgeno	varchar(8000)
Idx	finalregistrationnumber	varchar(50)
	remarks	varchar(1000)
	confirmationsent	boolean
	filepath	varchar(150)
	referencenumber	varchar(100)
	srocode	smallint
	bhoomivillagecode	bigint

Table bhoomifileuploaddetails

	createddate	timestamp DEFAULT CURRENT_TIMESTAMP
	k1k2_flag	smallint DEFAULT 2
	changeremarks	varchar(500)
	sentfromtool	smallint DEFAULT 0
	errorcode	varchar
	haschange	varchar

Indexes

Type	Name	On
Pk	pk_bhoomifileuploaddetails	referenceid
	idx_bhoomifileuploaddetails_finalreg_ccnew	finalregistrationnumber
	idx_bhoomifileuploaddetails_finalreg	finalregistrationnumber

Table bhoomihoblimaster

Idx	Name	Data Type
* Idx	hoblicode	integer
Idx	districtcode	integer
Idx	talukcode	integer
	hoblinamek	varchar(500)
	hoblinamee	varchar(500)
	shortnamek	varchar(5)
	shortnamee	varchar(5)
	bhoomihoblicode	integer
	bhoomihobliname	varchar(100)
	bhoomitalukcode	integer
	bhoomitalukname	varchar(100)
	bhoomidistrictcode	integer
	k1k2_flag	smallint DEFAULT 2
	bhoomihobliid	integer

Indexes

Type	Name	On
	idx_bhoomihoblimaster_hoblicode	hoblicode
	idx_bhoomihoblimaster_talukcode	talukcode
	idx_bhoomihoblimaster_districtcode	districtcode

Table bhoomihoblimaster_15feb2025

Idx	Name	Data Type
	hoblicode	integer
	districtcode	integer
	talukcode	integer
	hoblinamek	varchar(500)
	hoblinamee	varchar(500)
	shortnamek	varchar(5)
	shortnamee	varchar(5)
	bhoomihoblicode	integer
	bhoomihobliname	varchar(100)
	bhoomitalukcode	integer
	bhoomitalukname	varchar(100)
	bhoomidistrictcode	integer

Table bhoomihoblimaster_15feb2025

	k1k2_flag	smallint
	bhoomihobliid	integer

Table bhoomimappingdetails

Idx	Name	Data Type
* Pk	bhoomimappingid	bigint
	districtcode	integer
	districtnamee	varchar
	kaverisrocode	integer
	kaverisroname	varchar
Idx	kaverivillagecode	integer
	kaverivillagename	varchar
	kaverihobicode	integer
	kaverihobiname	varchar
	bhoomidistrictcode	integer
	bhoomitalukcode	integer
	bhoomitalukname	varchar
Idx	bhoomihobicode	integer
	bhoomihobiname	varchar
Idx	bhoomivillagecode	integer
	bhoomivillagename	varchar
	isupdated	boolean
	inserteddatetime	timestamp DEFAULT CURRENT_TIMESTAMP
	k1k2_flag	smallint DEFAULT 2

Indexes

Type	Name	On
	idx_bhoomimappingdetails_kaverivillagecode	kaverivillagecode
	idx_bhoomimappingdetails_bhoomihobicode	bhoomihobicode
	idx_bhoomimappingdetails_bhoomivillagecode	bhoomivillagecode
Unq	bhoomimappingdetails_pkey1_ccnew	bhoomimappingid
Pk	bhoomimappingdetails_pkey1	bhoomimappingid

Table bhoomimappingdetails_15feb2025

Idx	Name	Data Type
	bhoomimappingid	bigint
	districtcode	integer
	districtnamee	varchar
	kaverisrocode	integer
	kaverisroname	varchar
	kaverivillagecode	integer
	kaverivillagename	varchar
	kaverihobicode	integer
	kaverihobiname	varchar
	bhoomidistrictcode	integer
	bhoomitalukcode	integer
	bhoomitalukname	varchar
	bhoomihobicode	integer
	bhoomihobiname	varchar

Table bhoomimappingdetails_15feb2025

	bhoomivillagecode	integer
	bhoomivillagename	varchar
	isupdated	boolean
	inserteddatetime	timestamp
	k1k2_flag	smallint

Table bhoomipartyinfo

Idx	Name	Data Type
* Pk	partyid	bigint
	enumberr	varchar(20)
	alienatedauthorityid	integer
	alienatedorder	varchar(200)
* Pk	srocode	integer
	claimingblocknumber	varchar(1)
	retainingblocknumber	varchar(1)
	inserteddatetime	timestamp DEFAULT CURRENT_TIMESTAMP
	k1k2_flag	smallint DEFAULT 2

Indexes

Type	Name	On
Pk	pk_bhoomipartyinfo	partyid, srocode

Table bhoomitaluk

Idx	Name	Data Type
* Pk	talukacode	varchar(4)
	talukaname	varchar(50)
	unit	char(1)
	inserteddatetime	timestamp DEFAULT CURRENT_TIMESTAMP
	k1k2_flag	smallint DEFAULT 2

Indexes

Type	Name	On
Pk	pk_talukacode_bhoomitaluk	talukacode
	idx_bhoomitaluk_talukacode	talukacode

Table bhoomitalukamapping

Idx	Name	Data Type
* Pk	villagecode	bigint
*	villagename	varchar(500)
*	hoblicode	integer
*	srocode	integer
*	sroname	varchar(50)
*	hobliname	varchar(500)
	talukacode	varchar(4)
	inserteddatetime	timestamp DEFAULT CURRENT_TIMESTAMP
	k1k2_flag	smallint DEFAULT 2

Indexes

Type	Name	On
Pk	pk_bhoomitalukamapping	villagecode

Table bhoomitalukmaster

Idx	Name	Data Type
* Idx	talukcode	integer
Idx	districtcode	integer
*	taluknamek	varchar(150)
*	taluknamee	varchar(150)
	inserteddatetime	timestamp DEFAULT CURRENT_TIMESTAMP
	k1k2_flag	smallint DEFAULT 2
	talukid	integer
	unit	varchar(50)

Indexes

Type	Name	On
	idx_bhoomitalukmaster_talukcode	talukcode
	idx_bhoomitalukmaster_districtcode	districtcode

Table bhoomivillagemaster

Idx	Name	Data Type
* Idx	villagecode	bigint
	srocode	integer
Idx	hoblicode	integer
Idx	talukcode	integer
	villagenamek	varchar(500)
	villagenamee	varchar(500)
	censuscode	varchar(50)
	isurban	boolean
	bhoomitalukcode	integer
	bhoomivillagecode	integer
	bhoomivillagename	varchar(100)
	bhoomidistrictcode	integer
	uportownid	integer
	activeflag	boolean
	inserteddatetime	timestamp DEFAULT CURRENT_TIMESTAMP
	k1k2_flag	smallint DEFAULT 2
Idx	districtcode	integer

Indexes

Type	Name	On
	idx_bhoomivillagemaster_villagecode	villagecode
	idx_bhoomivillagemaster_talukcode	talukcode
	idx_bhoomivillagemaster_hoblicode	hoblicode
	idx_bhoomivillagemaster_districtcode	districtcode

Table bhoomivillagemaster_15feb2025

Idx	Name	Data Type
	villagecode	bigint
	srocode	integer
	hoblicode	integer
	talukcode	integer
	villagenamek	varchar(500)
	villagenamee	varchar(500)

Table bhoomivillagemaster_15feb2025

	censuscode	varchar(50)
	isurban	boolean
	bhoomitalukcode	integer
	bhoomivillagecode	integer
	bhoomivillagename	varchar(100)
	bhoomidistrictcode	integer
	uportownid	integer
	activeflag	boolean
	inserteddatetime	timestamp
	k1k2_flag	smallint
	districtcode	integer

Table bhoomixmllog

Idx	Name	Data Type
* Pk	logid	bigint
	documentid	bigint
* Idx	propertyid	bigint
	inputrtcowners	text
	rtcowners	text
	inputsurveynolist	text
	surveynolist	text
	srocode	decimal
	inserteddatetime	timestamp DEFAULT CURRENT_TIMESTAMP
	k1k2_flag	smallint DEFAULT 2

Indexes

Type	Name	On
	idx_bhoomixmllog	propertyid
Pk	pk_bhoomixmllog	logid

Table blacklistedcitizen

Idx	Name	Data Type
* Pk	citizenid	bigint
	loginname	text
	firstname	text
	middlename	text
	lastname	text
	gender	smallint
	email	text
	phone	bigint
	password	text
	secquestion	smallint
	secanswer	text
	isloggedin	char(1)
	lstupdusr	text
	permanentaddress	varchar(500)
	pin	integer
	pan	varchar(50)
	lstupddt	timestamp

Table blacklistedcitizen

	citizenimagepath	varchar(400)
	invalidlogincount	smallint
	forgotpasswordcount	smallint
	k1k2_flag	smallint
	isinstitution	boolean
	bankid	varchar(15)
	branchid	varchar(15)
	isekycdone	boolean
	isemailverified	boolean
	ismobileverified	boolean
	aadharhash	varchar(100)

Indexes

Type	Name	On
Pk	pk_blacklistedcitizen_citizenid	citizenid

Table blacklistedcitizenloginloginfo

Idx	Name	Data Type
	c_logseqid	bigint
	citizenid	bigint
	publicip	varchar
	localip	varchar
	macaddress	varchar
	location	varchar
	country	varchar
	isactive	boolean
	logindatetime	timestamp
	rowhash	varchar
	prowhash	varchar
	urowhash	varchar
	jwttoken	varchar
	reftoken	varchar
	localport	integer
	remoteport	integer
	ismultilogin	boolean
	logoutdatetime	timestamp

Table book1_part3_court

Idx	Name	Data Type
	certificatesaledate	date
	issuingauthority	varchar(250)
* Pk	applicationnumber	varchar(50)
	challan_number	varchar(50) DEFAULT ''::character varying
	amount_paid	varchar(10) DEFAULT '0'::character varying
	payment_type_id	varchar(10) DEFAULT ''::character varying
	is_stamp_duty_paid	boolean DEFAULT false
	endorsement_date	timestamp

Indexes

Type	Name	On

Table book1_part3_court

Pk	book1_part3_court_pkey	applicationnumber

Table booki_iii_iv_data

Idx	Name	Data Type
	month	varchar(50)
	bookid	integer
	docno	varchar(50)
	natureofdoc	varchar(250)
	marketvalue	decimal
	consideration	decimal
	registrationfees	decimal
	scanningfees	decimal
	fine	decimal
	otherfees	decimal
	govtduty	decimal
	surchargeduty	decimal
	cessduty	decimal
	ddmmyy	varchar(2)
	inserteddatetime	timestamp DEFAULT CURRENT_TIMESTAMP
	k1k2_flag	smallint DEFAULT 2

Table booktypemaster

Idx	Name	Data Type
* Pk	bookid	integer
	booknamekannada	varchar(150)
	booknameenglish	varchar(150)
*	ispublic	boolean
	printablename	varchar(50)
	inserteddatetime	timestamp DEFAULT CURRENT_TIMESTAMP
	k1k2_flag	smallint DEFAULT 2

Indexes

Type	Name	On
Pk	pk_booktypemaster	bookid

Table bucketmaster

Idx	Name	Data Type
* Pk	bucketid	integer
	bucketnamee	varchar(50)
	bucketnamek	varchar(50)
	inserteddate	timestamp DEFAULT CURRENT_TIMESTAMP
	username	varchar(20)
	k1k2_flag	smallint DEFAULT 2

Indexes

Type	Name	On
Pk	pk_bucketmaster_bucketid	bucketid

Table bulk_email_status_log

Idx	Name	Data Type

Table bulk_email_status_log

* Pk	sid	bigint DEFAULT nextval('kaveri.seq_bulk_email_status_log'::regclass)
*	applicationnumber	varchar(100)
*	email	text
	phone	bigint
	isprocessed	boolean
	k1k2_flag	smallint DEFAULT 2
	inserteddatetime	timestamp DEFAULT CURRENT_TIMESTAMP

Indexes

Type	Name	On
Pk	pk_bulk_email_status_log_sid	sid

Table captcha

Idx	Name	Data Type
	id	text
	captchacode	text
	inserteddatetime	timestamp DEFAULT CURRENT_TIMESTAMP

Table cc_applicationdetails

Idx	Name	Data Type
* Pk	ccid	bigint DEFAULT nextval('kaveri.cc_applicationdetails_ccid_seq'::regclass)
	ccnumber	varchar(50)
	ccdate	timestamp
*	userid	bigint
	documenttype	smallint
	kaveridrocode	integer
	kaverisrocode	integer
Idx	documentnumber	varchar(50)
	booktype	smallint
	yearofregistration	varchar(50)
	pagecount	integer
	totalamount	decimal(18,0)
*	isappliedforsignedcopy	boolean
	documentstatusid	smallint
	submittedby	bigint
	submitteddatetime	timestamp
	preparedby	bigint
	prepareddatetime	timestamp
	signedby	bigint
	signeddatetime	timestamp
	appliedsignedcopy	boolean
	comparedby	bigint
	compareddatetime	timestamp
	certificatenumber	varchar(50)
	accepteddatetime	timestamp
	marriagetypeid	smallint
	firmtypeid	smallint
Unq	applicationnumber	varchar(50)

Table cc_applicationdetails

	signedform22	text
	gscno	varchar
	k1k2_flag	smallint DEFAULT 2
	inserteddatetime	timestamp DEFAULT CURRENT_TIMESTAMP
*	isprior2003	boolean DEFAULT false
	refusalremarks	varchar(300)
	isrefused	boolean DEFAULT false
	finalregistrationnumber	varchar(50)
	isquicksearch	boolean DEFAULT false
	reason	varchar(150)
	isappliedbydept	boolean DEFAULT false

Indexes

Type	Name	On
Unq	uk_cc_applicationdetails_applicationnumber	applicationnumber
Pk	pk_cc_applicationdetails	ccid
	cc_applicationdetails_documentnumber_idx_ccnew	documentnumber
	cc_applicationdetails_documentnumber_idx	documentnumber

Table cc_applicationdetails_analysis

Idx	Name	Data Type
* Pk	ccid	bigint
	ccnumber	varchar(50)
	ccdate	timestamp
*	userid	bigint
	documenttype	smallint
	kaveridrocode	integer
	kaverisrocode	integer
	documentnumber	varchar(50)
	booktype	smallint
	yearofregistration	varchar(50)
	pagecount	integer
	totalamount	decimal(18,0)
*	isappliedforsignedcopy	boolean
	documentstatusid	smallint
	submittedby	bigint
	submitteddatetime	timestamp
	preparedby	bigint
	prepareddatetime	timestamp
	signedby	bigint
	signeddatetime	timestamp
	appliedsignedcopy	boolean
	comparedby	bigint
	compareddatetime	timestamp
	certificatenumber	varchar(50)
	accepteddatetime	timestamp
	marriagetypeid	smallint
	inserteddatetime	timestamp DEFAULT CURRENT_TIMESTAMP
	k1k2_flag	smallint DEFAULT 2

Table cc_applicationdetails_analysis

Indexes

Type	Name	On
Pk	pk_cc_applicationdetails_analysis	ccid

Table cc_applicationdetails_dashboard

Idx	Name	Data Type
	ccid	bigint
	ccnumber	varchar(50)
	ccdate	timestamp
	userid	bigint
	documenttype	smallint
	kaveridrocode	integer
	kaverisrocode	integer
	documentnumber	varchar(50)
	booktype	smallint
	yearofregistration	varchar(50)
	pagecount	integer
	totalamount	decimal(18,0)
	isappliedforsignedcopy	boolean
	documentstatusid	smallint
	submittedby	bigint
	submitteddatetime	timestamp
	preparedby	bigint
	prepareddatetime	timestamp
	signedby	bigint
	signeddatetime	timestamp
	appliedsignedcopy	boolean
	comparedby	bigint
	compareddatetime	timestamp
	certificatenumber	varchar(50)
	accepteddatetime	timestamp
	marriagetypeid	smallint
	firmtypeid	smallint
	applicationnumber	varchar(50)
	signedform22	text
	gscno	varchar
	k1k2_flag	smallint
	inserteddatetime	timestamp
	isprior2003	boolean
	refusalremarks	varchar(300)
	isrefused	boolean
	finalregistrationnumber	varchar(50)
	isquicksearch	boolean

Table cc_cscapplicantdetails

Idx	Name	Data Type
* Pk	cscapplicantid	bigint
*	firstname	varchar(50)

Table cc_cscapplicantdetails

	middlename	varchar(50)
	lastname	varchar(50)
*	address	varchar(150)
*	pincode	varchar(6)
*	mobilenumber	varchar(10)
	email	varchar(50)
	uid	varchar(30)
*	ccid	bigint
	operatorid	varchar(200)
	inserteddatetime	timestamp DEFAULT CURRENT_TIMESTAMP
	k1k2_flag	smallint DEFAULT 2

Indexes

Type	Name	On
Pk	pk_cc_cscapplicantdetails	cscapplicantid

Table cc_documents

Idx	Name	Data Type
* Pk	ccdocumentid	bigint DEFAULT nextval('kaveri.ccdocumentid_seq'::regclass)
Idx	ccid	bigint
	cccertificate	text
	inserteddatetime	timestamp DEFAULT CURRENT_TIMESTAMP
	k1k2_flag	smallint DEFAULT 2

Indexes

Type	Name	On
	idx_cc_documents_ccid	ccid
Pk	pk_ccdocumentid_cc_documents	ccdocumentid

Table cc_esignfilepath

Idx	Name	Data Type
* Pk	fileid	bigint
*	ccid	bigint
	pserverpath	varchar(200)
	vserverpath	varchar(200)
	esigndatetime	timestamp
	inserteddatetime	timestamp DEFAULT CURRENT_TIMESTAMP
	k1k2_flag	smallint DEFAULT 2

Indexes

Type	Name	On
Pk	pk_cc_esignfilepath	fileid

Table cc_qrcodedetails

Idx	Name	Data Type
* Pk	qrcodeid	bigint
*	ccdocumentid	bigint
*	qrencryptkey	varchar(200)
	inserteddatetime	timestamp DEFAULT CURRENT_TIMESTAMP
	k1k2_flag	smallint DEFAULT 2

Indexes

Table cc_qrcodedetails

Type	Name	On
Pk	pk_cc_qrcodedetails	qrcodeid

Table cc_remarkdetails

Idx	Name	Data Type
* Pk	remarkid	bigint
	remark	varchar(200)
*	ccid	bigint
*	documentstatusid	smallint
*	userid	bigint
*	documentstatusdatetime	timestamp
	inserteddatetime	timestamp DEFAULT CURRENT_TIMESTAMP
	k1k2_flag	smallint DEFAULT 2

Indexes

Type	Name	On
Pk	pk_cc_remarkdetails	remarkid

Table cc_remarks

Idx	Name	Data Type
*	id	bigint DEFAULT nextval('kaveri.cc_remarks_id_seq'::regclass)
	applicationnumber	varchar
	remarks	text
	userid	bigint
	cc_rejected_remarks	text
	inserteddatetime	timestamp DEFAULT CURRENT_TIMESTAMP

Table cc_requiredfees

Idx	Name	Data Type
* Pk	requiredfeeid	bigint
Idx	ccid	bigint
	feeruleid	smallint
	payableamount	decimal(18,0)
*	ispaid	boolean
	serviceid	smallint
	feedescription	varchar(500)
	inserteddatetime	timestamp DEFAULT CURRENT_TIMESTAMP
	k1k2_flag	smallint DEFAULT 2

Indexes

Type	Name	On
	idx_cc_requiredfees_ccid	ccid
	idx_cc_requiredfees	requiredfeeid
Pk	pk_cc_requiredfees	requiredfeeid

Table cc_signedfilepaths

Idx	Name	Data Type
* Pk	fileid	bigint
*	ccid	bigint
	preparedfserverpath	varchar(200)

Table cc_signedfilepaths

	preparedvserverpath	varchar(200)
	prepareddatetime	timestamp
	comparedfserverpath	varchar(200)
	comparedvserverpath	varchar(200)
	compareddatetime	timestamp
	signedfserverpath	varchar(200)
	signedvserverpath	varchar(200)
	signeddatetime	timestamp
	preparedreferencenumber	varchar(200)
	inserteddatetime	timestamp DEFAULT CURRENT_TIMESTAMP
	k1k2_flag	smallint DEFAULT 2

Indexes

Type	Name	On
Pk	pk_cc_signedfilepaths	fileid

Table checkslipinfo

Idx	Name	Data Type
* Pk	id	integer
	applicationname	varchar(50)
	typeid	integer
	descriptione	varchar(200)
	descriptionk	varchar(200)
	required	boolean
	additionaldesc	varchar(500)
	sevearity	smallint
	isactive	boolean
	checksliptypeid	smallint
	inserteddatetime	timestamp DEFAULT CURRENT_TIMESTAMP
	k1k2_flag	smallint DEFAULT 2

Indexes

Type	Name	On
Pk	pk_checkslipinfo	id

Table citizendashboard

Idx	Name	Data Type
* Pk	id	bigint DEFAULT nextval('kaveri.citizendashboard_id_seq'::regclass)
	applicationsreceived	bigint
	applicationsapproved	bigint
	applicationspending	bigint
	srocode	bigint
	applicationtypeid	integer
	propertytypeid	integer
	averagetime	interval
	mediantime	interval
	mintime	interval
	maxtime	interval
	fromdate	date
	todate	date

Table citizendashboard

*	inserteddatetime	timestamp DEFAULT CURRENT_TIMESTAMP
	male	bigint
	female	bigint
	transgender	bigint
	applicationsreceived_male	bigint
	applicationsreceived_female	bigint
	applicationsreceived_other	bigint
	applicationsreceived_total	bigint
	applicationsapproved_total	bigint

Indexes

Type	Name	On
Pk	pk_dashboard	id

Table citizenloginloginfo

Idx	Name	Data Type
	c_logseqid	bigint DEFAULT nextval('kaveri.citizenlogin'::regclass)
* Idx	citizenid	bigint
*	publicip	varchar
	localip	varchar
	macaddress	varchar
*	location	varchar
*	country	varchar
* Idx	isactive	boolean DEFAULT false
	logindatetime	timestamp DEFAULT now()
	rowhash	varchar
	prowhash	varchar
	urowhash	varchar
	jwttoken	varchar
	reftoken	varchar
	localport	integer
	remoteport	integer
	ismultilogin	boolean DEFAULT false
	logoutdatetime	timestamp

Indexes

Type	Name	On
	idx_citizenloginloginfo_isactive_ccnew	isactive
	idx_citizenloginloginfo_citi_ccnew	citizenid
	idx_citizenloginloginfo_isactive_ccnew1	isactive
	idx_citizenloginloginfo_citi	citizenid
	idx_citizenloginloginfo_isactive	isactive

Table citizenloginloginfo_new

Idx	Name	Data Type
Idx	c_logseqid	bigint DEFAULT nextval('kaveri.citizenlogin_new'::regclass)
* Idx	citizenid	bigint
*	publicip	varchar
*	isactive	boolean DEFAULT false
	logindatetime	timestamp DEFAULT now()

Table citizenloginloginfo_new

*	jwttoken	varchar
	logoutdatetime	timestamp
	issamesession	boolean
	guid	varchar(50)

Indexes

Type	Name	On
	idx_citizenloginloginfo_new_citi_ccnew	citizenid
	idx_citizenloginloginfo_new_c_logseqid_ccnew	c_logseqid
	idx_citizenloginloginfo_new_c_logseqid_ccnew1	c_logseqid
	idx_citizenloginloginfo_new_c_logseqid	c_logseqid
	idx_citizenloginloginfo_new_citi	citizenid

Table citizenloginotp

Idx	Name	Data Type
* Idx	otpid	integer DEFAULT nextval('kaveri.citizenloginotp_otpid_seq'::regclass)
Idx	otpsource	varchar
	otp	smallint
	otptime	timestamp DEFAULT CURRENT_TIMESTAMP
	otpcount	integer
	incorrectotpcnt	integer
	incorrectlogincnt	integer
	inserteddatetime	timestamp DEFAULT CURRENT_TIMESTAMP
	k1k2_flag	smallint DEFAULT 2

Indexes

Type	Name	On
	index_citizenloginotp	otpid, otpsource

Table citizenmaster

Idx	Name	Data Type
* Unq	citizenid	bigint DEFAULT nextval('kaveri.citizenmaster_citizenid_seq'::regclass)
* Unq	loginname	text
*	firstname	text
	middlename	text
*	lastname	text
*	gender	smallint
* Pk	email	text
* Pk	phone	bigint
*	password	text
*	secquestion	smallint
*	secanswer	text
	isloggedin	char(1)
	lstupdusr	text
	permanentaddress	varchar(500)
	pin	integer
	pan	varchar(50)
	lstupddt	timestamp DEFAULT CURRENT_TIMESTAMP
	citizenimagepath	varchar(400)

Table citizenmaster

	invalidlogincount	smallint DEFAULT 0
	forgotpasswordcount	smallint DEFAULT 0
	k1k2_flag	smallint DEFAULT 2
	isinstitution	boolean DEFAULT false
	bankid	varchar(15)
	branchid	varchar(15)
	isekycdone	boolean DEFAULT false
	isemailverified	boolean DEFAULT false
	ismobileverified	boolean DEFAULT true
	aadharhash	varchar(100) DEFAULT NULL::character varying

Indexes

Type	Name	On
Unq	uniq_loginname_citizmstr	loginname
Pk	citizenmaster_pkey	email, phone
Unq	uk_citizenmaster	citizenid
Unq	uk_citizenmaster_loginname	loginname

Table citizenmaster_cd140

Idx	Name	Data Type
	citizenid	bigint
	loginname	text
	firstname	text
	middlename	text
	lastname	text
	gender	smallint
	email	text
	phone	bigint
	password	text
	secquestion	smallint
	secanswer	text
	isloggedin	char(1)
	lstupdusr	text
	permanentaddress	varchar(500)
	pin	integer
	pan	varchar(50)
	lstupddt	timestamp
	citizenimage	varchar(400)
	invalidlogincount	smallint
	forgotpasswordcount	smallint
	k1k2_flag	smallint
	isinstitution	boolean
	bankid	varchar(15)
	branchid	varchar(15)

Table citizenmaster_tmp

Idx	Name	Data Type
*	loginname	text
*	firstname	text

Table citizenmaster_tmp

	middlename	text
*	lastname	text
*	gender	integer
*	email	text
*	phone	bigint
*	password	text
*	secquestion	integer
*	secanswer	text
	permanentaddress	varchar(500)
	invalidlogincount	smallint DEFAULT 0
	forgotpasswordcount	smallint DEFAULT 0
	isinstitution	boolean DEFAULT false
	bankid	varchar(15)
	branchid	varchar(15)

Table citizeotpdetails

Idx	Name	Data Type
* Idx	otpid	integer DEFAULT nextval('kaveri.citizeotpdetails_otpid_seq'::regclass)
Idx	citizenid	bigint
	otp	smallint
	otptime	timestamp DEFAULT CURRENT_TIMESTAMP
	otpcount	integer
	incorrectotpcnt	integer
	inserteddatetime	timestamp DEFAULT CURRENT_TIMESTAMP
	k1k2_flag	smallint DEFAULT 2

Indexes

Type	Name	On
	index_citizeotpdetails	otpid, citizenid

Table company

Idx	Name	Data Type
* Pk	companyid	integer
	description	varchar(100)
	companytypeid	integer

Indexes

Type	Name	On
Pk	pk_company_id	companyid

Table companytype

Idx	Name	Data Type
* Pk	companytypeid	integer
	description	varchar(100)

Indexes

Type	Name	On
Pk	pk_companytype_typeid	companytypeid

Table constructioncostmaster

Idx	Name	Data Type
* Pk	constructionid	decimal(10,0)
*	villagecode	decimal(10,0)
*	constructiontypecode	decimal(18,0)
*	buildingflooreid	integer
*	constructionrate	decimal(18,5)
*	measurementcode	integer
	regionid	integer
	inserteddatetime	timestamp DEFAULT CURRENT_TIMESTAMP
	k1k2_flag	smallint DEFAULT 2

Indexes

Type	Name	On
Pk	pk_constructioncostmstr_constid	constructionid

Table constructioncostmaster_kaveri1

Idx	Name	Data Type
* Pk	constructionid	decimal(10,0)
*	villagecode	decimal(10,0)
*	constructiontypecode	decimal(18,0)
*	buildingflooreid	integer
*	constructionrate	decimal(18,5)
*	measurementcode	integer
	regionid	integer

Indexes

Type	Name	On
Pk	pk_constructioncostmaster	constructionid

Table correctiondetails

Idx	Name	Data Type
* Pk	documentid	bigint
* Pk	correctioncode	integer
* Pk	srocode	integer
	inserteddatetime	timestamp DEFAULT CURRENT_TIMESTAMP
	k1k2_flag	smallint DEFAULT 2

Indexes

Type	Name	On
Pk	pk_correctiondetails	documentid, correctioncode, srocode

Table correctionmaster

Idx	Name	Data Type
* Pk	correctedid	integer
	field	varchar(50)
	inserteddatetime	timestamp DEFAULT CURRENT_TIMESTAMP
	k1k2_flag	smallint DEFAULT 2

Indexes

Type	Name	On
Pk	pk_correctionmaster	correctedid

Table courtorders

Idx	Name	Data Type
Idx	orderid	bigint
* Pk	srocode	integer
	ordernumber	varchar(1000)
	issuingauthority	varchar(1000)
*	issueddate	timestamp
*	description	varchar(5000)
	regactarticle	integer
	dateofcancellation	timestamp
	reasonofcancellation	varchar(1000)
*	iscancelled	boolean
*	isinforce	boolean
	orderentrydatetime	timestamp
	cancellationorderno	varchar(200)
	cancellationdate	timestamp
	cancelledby	integer
	cancellationremarks	varchar(2000)
	username	varchar(50)
* Pk	courtorderid	bigint DEFAULT nextval('kaveri.courtorders_courtorderid_seq'::regclass)
	casetype	varchar(200)
	inserteddatetime	timestamp DEFAULT CURRENT_TIMESTAMP
	k1k2_flag	smallint DEFAULT 2

Indexes

Type	Name	On
Pk	courtorders_pkey	courtorderid, srocode
	courtorders_courtorderid_indx	orderid
	idx_courtorders_srocode_ccnew	srocode
	idx_courtorders_srocode	srocode

Table cropfruitsmaster

Idx	Name	Data Type
* Pk	cropid	integer
	cropnamek	varchar(100)
	cropnamee	varchar(100)
	status	boolean
	croptype	integer
	cropgroup	varchar(100)

Indexes

Type	Name	On
Pk	pk_cropfruitsmaster_cropid	cropid

Table cvcopeningclosing

Idx	Name	Data Type
* Pk	id	bigint
*	srocode	integer
*	districtcode	integer
*	opendate	timestamp
*	closedate	timestamp

Table cvcopeningclosing

	extendedcloserdate	timestamp
	remark	varchar(100)
*	entrydoneby	bigint
*	entrydate	timestamp
*	isenabled	boolean
	disabledby	bigint
	disabledate	timestamp
	isapplicabletoalldistrict	boolean
	isapplicabletoallstate	boolean
	lasteditedby	bigint
	lastediteddate	timestamp
	inserteddatetime	timestamp DEFAULT CURRENT_TIMESTAMP
	k1k2_flag	smallint DEFAULT 2

Indexes

Type	Name	On
Pk	pk_cvcopeningclosing_id	id

Table daily_apps_revenue_scheduler_history

Idx	Name	Data Type
* Pk	scheduler_id	bigint DEFAULT nextval('kaveri.daily_apps_revenue_scheduler_history_seq'::regclass)
*	scheduler_name	varchar
*	scheduler_date	date
*	start_time	timestamp
*	end_time	timestamp
*	is_sucess	boolean
*	k1k2_flag	smallint DEFAULT 2
*	report_date	date
*	inserted_date	timestamp DEFAULT CURRENT_TIMESTAMP
	comment	text

Indexes

Type	Name	On
Pk	daily_apps_revenue_scheduler_history_pk	scheduler_id

Table daily_dashboard_apps_revenue_details

Idx	Name	Data Type
* Pk	id	bigint DEFAULT nextval('kaveri.daily_dashboard_apps_revenue_details_seq'::regclass)
*	report_date	timestamp
*	district_code	bigint
*	district_name	varchar
*	sro_code	bigint
*	sro_name	varchar
*	document_regs	bigint DEFAULT 0
*	document_revenue	bigint DEFAULT 0
*	ec_apps	bigint DEFAULT 0
*	ec_revenue	bigint DEFAULT 0
*	cc_apps	bigint DEFAULT 0

Table daily_dashboard_apps_revenue_details

*	cc_revenue	bigint DEFAULT 0
*	start_time	timestamp
*	end_time	timestamp
*	k1k2_flag	smallint DEFAULT 2

Indexes

Type	Name	On
Pk	daily_dashboard_apps_revenue_details_pk	id

Table dailyreceiptfees

Idx	Name	Data Type
	documentid	bigint
	sroname	varchar(250)
	presentdatetime	timestamp
	presentername	varchar(1000)
	stamparticlename	varchar(100)
	consideration	decimal
	stampduty	decimal
	govtduty	decimal
	stampduty_dd	decimal
	stampduty_others	decimal
	infrastructure	decimal
	corporation	decimal
	muncipal	decimal
	prevtotalstampduty	decimal
	talukboard	decimal
	documentnumber	varchar(500)
	bookid	varchar(150)
	volumename	varchar(50)
	completiondate	timestamp
	returndate	timestamp
	prevtotalregistrationfees	decimal
	registrationfees	decimal
	deficient_registrationfees	decimal
	previousdate	timestamp
	deficient_stampduty	decimal
	copyfees	decimal
	prevtotalcopyfees	decimal
	hindumarriagefee	decimal
	otherfees	decimal
	otherfeesdesc	varchar(50)
	splothermarriagefee	decimal
	prevtotalmarriagefee	decimal
	splmarriagefee	decimal
	prevtotalmutationfee	decimal
	mutationfee	decimal
	exemptiondescription	varchar(2000)
	remarks	varchar(500)
	receiptid	bigint

Table dailyreceiptfees

	inserteddatetime	timestamp DEFAULT CURRENT_TIMESTAMP
	k1k2_flag	smallint DEFAULT 2

Table dataentry_documentmaster

Idx	Name	Data Type
*	dataentryid	bigint DEFAULT nextval('kaveri.dataentryid_seq'::regclass)
	srocode	integer
*	documentid	bigint
	refusalscribe	varchar(400)
	refusalreasons	varchar(500)
	dailyregrefusalsummons	varchar(500)
	dailyregtreasamt	decimal
	dailyregtreasdate	timestamp
	dailyregmutfee	decimal
	dailyregmutfeedate	timestamp
	impdefstamp	decimal
	imppenal	decimal
	impdycomrref	timestamp
	impdycomrret	timestamp
	imppurp	varchar(200)
	imphowdis	varchar(200)
	inx4rem	varchar(100)

Table dec_drordermaster

Idx	Name	Data Type
* Pk	orderid	bigint
	districtcode	integer
	srocode	integer
Idx	documentid	bigint
	ordernumber	varchar(100)
Idx	orderdate	timestamp
	statuscode	integer DEFAULT 0
	userid	bigint
	ipaddress	varchar(50)
*	insertdatetime	timestamp DEFAULT CURRENT_TIMESTAMP
	absolutefilepath	varchar(8000)
	relativepath	varchar(8000)
	filename	varchar(8000)
	isvalid	integer DEFAULT 1
	k1k2_flag	smallint DEFAULT 2
	correctionnote	boolean
	documentrescan	boolean
	rescannoofpages	integer
	rescandocument	varchar(500)
	deoid	bigint
	sroid	bigint
Idx	finalregistrationnumber	varchar(50)

Indexes

Table dec_drordermaster

Type	Name	On
	dec_drordermaster_orderdate_idx	orderdate
	dec_drordermaster_finalreg_idx	finalregistrationnumber
Pk	pk_dec_drordermaster	orderid
	dec_drordermaster_documentid_idx	documentid

Table dec_drpndnote

Idx	Name	Data Type
* Pk	noteid	integer
*	orderid	bigint
	propertyid	bigint
	note_preparedpart	varchar(4000)
	note_enteredpart	varchar(4000)
	userid	bigint
	ipaddress	varchar(50)
*	insertdatetime	timestamp DEFAULT CURRENT_TIMESTAMP
	k1k2_flag	smallint DEFAULT 2

Indexes

Type	Name	On
Pk	pk_dec_pndnote	noteid

Table dec_populatesearchkeystatus

Idx	Name	Data Type
* Pk	attemptid	integer
*	srocode	integer
*	districtcode	integer
	startdatetime	timestamp
	enddatetime	timestamp
*	inserteddatetime	timestamp
	propertyrowstobeinserted	bigint
	propertyrowsinserted	bigint
	partyrowstobeinserted	bigint
	partyrowsinserted	bigint
	iscompleted	integer
	k1k2_flag	smallint DEFAULT 2

Indexes

Type	Name	On
Pk	dec_populatesearchkeystatus_pkey	attemptid

Table declarationmaster

Idx	Name	Data Type
* Pk	declarationid	bigint
	declarationtype	varchar(255)
	marriagetypeid	integer
	inserteddatetime	timestamp DEFAULT CURRENT_TIMESTAMP
	k1k2_flag	smallint DEFAULT 2

Indexes

Type	Name	On

Table declarationmaster

Pk	pk_declarationmaster	declarationid

Table deleted_record_villagemaster

Idx	Name	Data Type
	villagecode	bigint
	srocode	integer
	hoblicode	integer
	censuscode	varchar(50)
	talukcode	integer
	villagenamek	varchar(500)
	villagenamee	varchar(500)
	isurban	boolean
	bhoomitalukcode	integer
	bhoomivillagecode	integer
	bhoomivillagename	varchar(100)
	bhoomidistrictcode	integer
	uportownid	integer
	inserteddatetime	timestamp
	k1k2_flag	smallint

Table departmentaccesslotmaster

Idx	Name	Data Type
* Pk	id	bigint DEFAULT nextval('kaveri.departmentaccesslotmasterid_seq'::regclass)
Idx	srocode	integer
Idx	prelunchstrtime	time
Idx	prelunchendtime	time
Idx	postlunchstrtime	time
Idx	postlunchendtime	time
	additionslotstrtime	time
	additionslotendtime	time
Idx	stepcode	integer
Idx	stepcodedesigntypid	integer
	registrationtype	smallint
	additionslotaproby	bigint
	deptdesignid	bigint
	inserteddatetime	timestamp DEFAULT CURRENT_TIMESTAMP
	k1k2_flag	smallint DEFAULT 2

Indexes

Type	Name	On
Pk	srologininfo_id_pkey	id
	idx_departmentaccesslotmaster_srocode	srocode
	idx_departmentaccesslotmaster_stepcode	stepcode
	idx_departmentaccesslotmaster_stepcodedesigntypid	stepcodedesigntypid
	idx_departmentaccesslotmaster_postlunchstrtime	postlunchstrtime
	idx_departmentaccesslotmaster_prelunchendtime	prelunchendtime
	idx_departmentaccesslotmaster_prelunchstrtime	prelunchstrtime
	idx_departmentaccesslotmaster_postlunchendtime_ccnew	postlunchendtime
	idx_departmentaccesslotmaster_postlunchendtime_ccnew1	postlunchendtime

Table departmentaccesslotmaster

	idx_departmentaccesslotmaster_postlunchendtime	postlunchendtime

Table departmentloginloginfo

Idx	Name	Data Type
* Pk	c_userid	bigint DEFAULT nextval('kaveri.departmentloginlog'::regclass)
* Idx	userid	bigint
*	srocode	integer
	localip	varchar
	localport	integer
	publicip	varchar
	remoteport	integer
	macaddress	varchar
*	location	varchar
*	country	varchar
*	isactive	boolean DEFAULT false
	logindatetime	timestamp DEFAULT now()
	rowhash	varchar
	prowhash	varchar
	urowhash	varchar
	jwttoken	varchar
	reftoken	varchar
	ismultilogin	boolean DEFAULT false
	logoutdatetime	timestamp

Indexes

Type	Name	On
Pk	pk_departmentloginloginfo	c_userid
	idx_departmentloginloginfol_userid_ccnew	userid
	idx_departmentloginloginfol_userid_ccnew1	userid
	idx_departmentloginloginfol_userid	userid

Table departmentloginloginfo_new

Idx	Name	Data Type
* Pk	c_userid	bigint DEFAULT nextval('kaveri.departmentloginlog_new'::regclass)
* Idx	userid	bigint
*	srocode	integer
	publicip	varchar
*	isactive	boolean DEFAULT false
	logindatetime	timestamp DEFAULT now()
	jwttoken	varchar
	logoutdatetime	timestamp
	issamesession	boolean

Indexes

Type	Name	On
Pk	pk_departmentloginloginfo_new	c_userid
	idx_departmentloginloginfol_new_userid	userid

Table departmentuserroles

Idx	Name	Data Type
* Pk	userroleid	bigint DEFAULT nextval('kaveri.departmentuserroles_userroleid_seq'::regclass)
Idx	userid	bigint
Idx	designationid	integer
	updatedby	varchar(50)
	updateddate	timestamp DEFAULT CURRENT_TIMESTAMP
	k1k2_flag	smallint DEFAULT 2
	inserteddatetime	timestamp DEFAULT CURRENT_TIMESTAMP
Idx	mappeduserid	bigint
	mappedsroid	integer
	mappedofficeid	integer

Indexes

Type	Name	On
	idx_departmentuserroles_mappeduserid	mappeduserid
	idx_departmentuserroles_designationid	designationid
	idx_departmentuserroles_userid	userid
	idx_departmentuserroles	userid, mappeduserid, designationid
Pk	departmentuserroles_pkey	userroleid

Table departmentusers

Idx	Name	Data Type
* Pk	userid	bigint DEFAULT nextval('kaveri.deptuserid_seq'::regclass)
*	srocode	integer
* Unq	loginname	text
*	firstname	text
	middlename	text
*	lastname	text
	doj	timestamp
Idx	designationid	integer
Unq	emailid	text
Unq	mobileno	bigint
Idx	serviceflag	boolean
	serviceexpdate	timestamp
*	passwd	text
	usertype	varchar(10)
	periodfrom	timestamp
	periodto	timestamp
	bioauhreq	boolean
	digiverifyreq	boolean
	usrtype	varchar(10)
	crtusr	varchar(10)
	crtdate	timestamp
	joininglocation	varchar(80)
	houseno_per	varchar(20)
	buildingname_per	varchar(80)
	streetname_per	varchar(200)
	statecode_per	bigint
	villagecode_per	bigint

Table departmentusers

	districtcode_per	bigint
	pincode_per	integer
	preferaddressis_per	boolean
	houseno_curr	varchar(20)
	buildingname_curr	varchar(80)
	streetname_curr	varchar(200)
	statecode_curr	bigint
	villagecode_curr	bigint
	districtcode_curr	bigint
	pincode_curr	integer
	emergencycontact	bigint
	uploadphoto	varchar(500)
	pan	varchar(10)
	status	varchar(10)
	lstupdusrid	bigint
	lstupddate	timestamp DEFAULT CURRENT_TIMESTAMP
	k1k2_flag	smallint DEFAULT 2
	officeid	smallint
	kgid	text
	createdby	integer
	employeetypeid	integer
	districtcode	integer
	groupid	integer
	isactive	boolean DEFAULT true
	isdro	boolean DEFAULT false

Indexes

Type	Name	On
	idx_designationid_departmentusers_pkey	designationid
	idx_departmentusers_service	serviceflag
Pk	departmentusers_pkey	userid
Unq	ix_deptuser_loginname	loginname
	idx_departmentusers_userid	userid
Unq	ix_deptuser_emailmobno_ccnew	emailid, mobileno
Unq	ix_deptuser_emailmobno_ccnew1	emailid, mobileno
Unq	ix_deptuser_emailmobno	emailid, mobileno

Table departmentusers_biometrics

Idx	Name	Data Type
*	userid	bigint
	uploadphoto	varchar(500)
	pan	varchar(10)
	status	varchar(10)
	k1k2_flag	smallint
	uploadthumbleft	text
	uploadthumbright	text
	identityprooftype	integer
	idproofnumber	text
	idproofpath	text

Table departmentusers_biometrics

	createdby	integer

Table departmentusers_complete

Idx	Name	Data Type
	userid	bigint
	srocode	integer
	loginname	text
	firstname	text
	middlename	text
	lastname	text
	doj	timestamp
	designationid	integer
	emailid	text
	mobileno	bigint
	serviceflag	boolean
	serviceexpdate	timestamp
	passwd	text
	usertype	varchar(10)
	periodfrom	timestamp
	periodto	timestamp
	bioauhreq	boolean
	digiverifyreq	boolean
	usrtype	varchar(10)
	crtusr	varchar(10)
	crtdate	timestamp
	joininglocation	varchar(80)
	houseno_per	varchar(20)
	buildingname_per	varchar(80)
	streetname_per	varchar(200)
	statecode_per	bigint
	villagecode_per	bigint
	districtcode_per	bigint
	pincode_per	integer
	preferaddressis_per	boolean
	houseno_curr	varchar(20)
	buildingname_curr	varchar(80)
	streetname_curr	varchar(200)
	statecode_curr	bigint
	villagecode_curr	bigint
	districtcode_curr	bigint
	pincode_curr	integer
	emergencycontact	bigint
	uploadphoto	varchar(500)
	pan	varchar(10)
	status	varchar(10)
	lstupdusrid	bigint
	lstupddate	timestamp
	k1k2_flag	smallint

Table departmentusers_complete

	officeid	smallint
	kgid	text
	createdby	integer
	employeetypeid	integer
	districtcode	integer
	groupid	integer

Table departmentusers_deo_service_history

Idx	Name	Data Type
* Pk	uid	bigint DEFAULT nextval('kaveri.departmentusers_deo_serviceid_seq'::regclass)
* Idx	from_userid	bigint
* Idx	from_srocode	integer
Idx	from_designationid	integer
Idx	from_officeid	smallint
	from_firstname	varchar(100)
	from_lastname	varchar(100)
	from_middlename	varchar(100)
	from_phone	varchar(100)
* Idx	to_userid	bigint
* Idx	to_srocode	integer
Idx	to_designationid	integer
Idx	to_officeid	smallint
	to_firstname	varchar(100)
	to_lastname	varchar(100)
	to_middlename	varchar(100)
	to_phone	varchar(100)
	serviceexpdate	timestamp
	updatedby	integer
	servicestartdate	timestamp
Idx	employeetypeid	integer
	istransfer	boolean
	k1k2_flag	smallint DEFAULT 2
	inserteddate	timestamp DEFAULT CURRENT_TIMESTAMP
	from_districtcode	smallint
	to_districtcode	smallint

Indexes

Type	Name	On
Pk	departmentusers_deo_service_history_pkey	uid
	departmentusers_deo_service_history_from_userid_idx	from_userid
	departmentusers_deo_service_history_from_srocode_idx	from_srocode
	departmentusers_deo_service_history_from_designationid_idx	from_designationid
	departmentusers_deo_service_history_from_officeid_idx	from_officeid
	departmentusers_deo_service_history_to_userid_idx	to_userid
	departmentusers_deo_service_history_to_srocode_idx	to_srocode
	departmentusers_deo_service_history_to_designationid_idx	to_designationid
	departmentusers_deo_service_history_to_officeid_idx	to_officeid
	departmentusers_deo_service_history_employeetypeid_idx	employeetypeid

Table departmentusers_service_history

Idx	Name	Data Type
* Pk	serviceid	bigint DEFAULT nextval('kaveri.departmentusers_serviceid_seq'::regclass)
* Idx	userid	bigint
*	srocode	integer
Idx	designationid	integer
	serviceexpdate	timestamp
	k1k2_flag	smallint DEFAULT 2
	officeid	smallint
	updatedby	integer
	servicestartdate	timestamp
	employeetypeid	integer
	isactive	boolean
	inserteddatetime	timestamp DEFAULT CURRENT_TIMESTAMP

Indexes

Type	Name	On
Pk	departmentusers_service_history_pkey	serviceid
	idx_departmentusers_designationid2	designationid
	idx_departmentusers_userid2	userid

Table deps_saved_ddl

Idx	Name	Data Type
* Pk	deps_id	integer DEFAULT nextval('kaveri.deps_saved_ddl_deps_id_seq'::regclass)
	deps_view_schema	name
	deps_view_name	name
	deps_ddl_to_run	text

Indexes

Type	Name	On
Pk	deps_saved_ddl_pkey	deps_id

Table deptmentusergroup

Idx	Name	Data Type
* Pk	groupid	integer DEFAULT nextval('kaveri.groupid_seq'::regclass)
	groupname	text
	groupdesc	text
	isactive	boolean
	createdby	integer
	inserteddatetime	timestamp DEFAULT CURRENT_TIMESTAMP
	k1k2_flag	integer DEFAULT 2

Indexes

Type	Name	On
Pk	pk_deptmentusergroup	groupid
	idx_deptmentusergroup	groupid

Table deptotpdetails

Idx	Name	Data Type
*	otpid	integer DEFAULT nextval('kaveri.deptotpdetails_otpid_seq'::regclass)

Table deptotpdetails

	userid	bigint
	otp	smallint
	otptime	timestamp DEFAULT CURRENT_TIMESTAMP
	otpcount	integer
	incorrectotpcnt	integer
	inserteddatetime	timestamp DEFAULT CURRENT_TIMESTAMP
	k1k2_flag	smallint DEFAULT 2

Table desigmaster

Idx	Name	Data Type
* Pk	designationid	integer DEFAULT nextval('kaveri.designationid_seq'::regclass)
	designame	char(30)
	k1k2_flag	smallint DEFAULT 2
	desigdescription	text
	isactive	boolean DEFAULT false
	inserteddatetime	timestamp DEFAULT CURRENT_TIMESTAMP
	createdby	bigint

Indexes

Type	Name	On
Pk	pk_desigmaster	designationid

Table districtmaster

Idx	Name	Data Type
* Pk	districtcode	integer
*	districtnamee	varchar(75)
*	districtnamek	varchar(150)
	shortnamee	varchar(5)
	shortnamek	varchar(15)
	digcode	integer
	bhoomidistrictcode	integer
	k1k2_flag	smallint DEFAULT 2

Indexes

Type	Name	On
Pk	pk_districtmaster	districtcode

Table districtmaster_prod1

Idx	Name	Data Type
	districtcode	integer
	districtnamee	varchar(75)
	districtnamek	varchar(150)
	shortnamee	varchar(5)
	shortnamek	varchar(15)
	digcode	integer
	bhoomidistrictcode	integer
	k1k2_flag	smallint

Table doc_path_bucket_ref

Idx	Name	Data Type

Table doc_path_bucket_ref

*	doc_id	integer DEFAULT nextval('kaveri.doc_path_bucket_ref_doc_id_seq'::regclass)
Unq	doc_path	text
	bucketname	varchar
	inserteddatetime	timestamp DEFAULT CURRENT_TIMESTAMP

Indexes

Type	Name	On
Unq	uq_doc_path_bucket_ref_doc_path_ccnew	doc_path
Unq	uq_doc_path_bucket_ref_doc_path	doc_path

Table docserialnumbers

Idx	Name	Data Type
*	documenttype	char(10)
	serialno	integer
	inserteddatetime	timestamp DEFAULT CURRENT_TIMESTAMP
	k1k2_flag	smallint DEFAULT 2

Table document_esign

Idx	Name	Data Type
* Pk	doc_guid	varchar(50)
	esign_data	text
	docdate	timestamp DEFAULT CURRENT_TIMESTAMP
	inserteddatetime	timestamp DEFAULT CURRENT_TIMESTAMP
	k1k2_flag	smallint DEFAULT 2

Indexes

Type	Name	On
Unq	pk_doc_guid_document_esign_ccnew	doc_guid
Unq	pk_doc_guid_document_esign_ccnew1	doc_guid
Pk	pk_doc_guid_document_esign	doc_guid

Table document_esign_bck

Idx	Name	Data Type
	doc_guid	varchar(50)
	esign_data	text
	docdate	timestamp
	inserteddatetime	timestamp
	k1k2_flag	smallint

Table document_to_be_included_in_old_method_jslips

Idx	Name	Data Type
* Pk	id	bigint GENERATED ALWAYS AS IDENTITY
*	finalregistrationnumber	varchar(255)
*	srocode	varchar(255)
	sentat	timestamp
	sentfile	varchar(255) DEFAULT NULL::character varying
	created_at	timestamp
	updated_at	timestamp

Indexes

Table document_to_be_included_in_old_method_jslips

Type	Name	On
Unq	document_to_be_included_in_old_method_jslips_pkey_ccnew	id
Pk	document_to_be_included_in_old_method_jslips_pkey	id

Table documentacceslog

Idx	Name	Data Type
*	accessid	bigint DEFAULT nextval('kaveri.documentacceslog_accessid_seq'::regclass)
	documenttype	integer
	districtcode	integer
	srocode	bigint
	documentnumber	bigint
	booktype	integer
	marriagetype	integer
	yearofregistration	varchar(50)
* Idx	citizenid	bigint
	inserteddatetime	timestamp DEFAULT CURRENT_TIMESTAMP
	ipaddress	varchar
	finalregistrationnumber	varchar
	isquicksearch	boolean DEFAULT false

Indexes

Type	Name	On
	idx_documentacceslog_citizenid_ccnew	citizenid
	idx_documentacceslog_citizenid_ccnew1	citizenid
	idx_documentacceslog_citizenid	citizenid

Table documentmaster

Idx	Name	Data Type
* Pk	documentid	bigint
* Pk	srocode	integer
* Idx	bookid	integer
	stamparticlecode	integer
* Idx	regarticlecode	integer
	documentnumber	integer
Idx	finalregistrationnumber	varchar(50)
	presentdatetime	timestamp
	executiondatetime	timestamp
	dateofstamp	timestamp
	stamp1datetime	timestamp
	stamp2datetime	timestamp
	stamp3datetime	timestamp
	stamp4datetime	timestamp
	stamp5datetime	timestamp
	withdrawaldate	timestamp
	pagecount	integer
	index2shera	varchar(250)
	isvisited	boolean
	isfiling	boolean

Table documentmaster

	ispending	boolean
	isscanned	boolean
	isrefused	boolean
	ispaymentofmoney	boolean
	isadjudicated	boolean
	iswithdrawn	boolean
	refusaldate	timestamp
	refusalreason	varchar(250)
	remarksbyuser	varchar(2000)
	remarksbysystem	varchar(250)
	correctionreference	bigint
	olddocreference	varchar(50)
	adjudicationdetails	varchar(2500)
	cdnumber	varchar(50)
	isxmltransferredtobhoomi	boolean DEFAULT false
	uid	integer
	pendingdocumentnumber	varchar(20)
	istransmitted	boolean DEFAULT false
	isphotothumbtransmitted	boolean DEFAULT false
	inserteddatetime	timestamp DEFAULT now()
	initialtransmitted	boolean
	considerationamount	decimal(23,4)
	requiredstampduty	decimal(23,4)
	paidstampduty	decimal(23,4)
	documentstatus	varchar(5)
Unq	applicationnumber	varchar(50)
	verified	boolean DEFAULT false
	issroapproved	varchar(1) DEFAULT 'E'::character varying
	deedattachpath	varchar(200)
	ispaymentdetails	boolean
	isuploaddocuments	boolean
	uploaddocdatetime	timestamp
Idx	registrationdatetime	timestamp
	isregistrationevaluation	boolean
	uploaddocdeedpath	text
	uploaddocannexurepath	text
	docsubmitiondate	timestamp
	lstupddate	timestamp DEFAULT CURRENT_TIMESTAMP
	isregistrationaccepted	boolean
	isprintsummary	boolean
	isprintendorsement	boolean
	isgenerateec	boolean
	isdigitalsigned	boolean
	isregistrationcompleted	boolean
	gscno	varchar(15)
	uploadsummarydocpath	text
	partypaymentdetails	text
	isscancompleted	boolean
	isundervaluation	boolean DEFAULT false

Table documentmaster

	k1k2_flag	smallint DEFAULT 2
	withdrawfilepath	text
	withdrawdocument	varchar(100)
	ackdatetime	timestamp
	ackuser	varchar(100)

Indexes

Type	Name	On
Pk	documentmaster_pkey	documentid, srocode
	documentmaster_bookid_idx	bookid
	ix_nc_finalregnumber	finalregistrationnumber
Unq	documentmaster_multiple	applicationnumber
	documentmaster_regarticlecode_idx	regarticlecode
	documentmaster_registrationdatetime_idx	registrationdatetime
	idx_documentmaster_final_rega	finalregistrationnumber, regarticlecode

Foreign Keys

Type	Name	On
	fk_documentmaster_applicantapplicationdetails (applicationnumber) ref applicantapplicationdetails (applicationnumber)	

Table documentmaster_cd140

Idx	Name	Data Type
	documentid	bigint
	srocode	integer
	bookid	integer
	stamparticlecode	integer
	regarticlecode	integer
	documentnumber	integer
	finalregistrationnumber	varchar(50)
	presentdatetime	timestamp
	executiondatetime	timestamp
	dateofstamp	timestamp
	stamp1datetime	timestamp
	stamp2datetime	timestamp
	stamp3datetime	timestamp
	stamp4datetime	timestamp
	stamp5datetime	timestamp
	withdrawaldate	timestamp
	pagecount	integer
	index2shera	varchar(250)
	isvisited	boolean
	isfiling	boolean
	ispending	boolean
	isscanned	boolean
	isrefused	boolean
	ispaymentofmoney	boolean
	isadjudicated	boolean
	iswithdrawn	boolean
	refusaldate	timestamp
	refusalreason	varchar(250)

Table documentmaster_cd140

remarksbyuser	varchar(2000)
remarksbysystem	varchar(250)
correctionreference	bigint
olddocreference	varchar(50)
adjudicationdetails	varchar(2500)
cdnumber	varchar(50)
isxmltransferredtobhoomi	boolean
uid	integer
pendingdocumentnumber	varchar(20)
istransmitted	boolean
isphotothumbtransmitted	boolean
inserteddatetime	timestamp
initialtransmitted	boolean
considerationamount	decimal(23,4)
requiredstampduty	decimal(23,4)
paidstampduty	decimal(23,4)
documentstatus	varchar(5)
applicationnumber	varchar(50)
verified	boolean
issroapproved	varchar(1)
deedattachpath	varchar(200)
ispaymentdetails	boolean
isuploaddocuments	boolean
uploaddocdatetime	timestamp
registrationdatetime	timestamp
isregistrationevaluation	boolean
uploaddocdeedpath	text
uploaddocannexurepath	text
docsubmitiondate	timestamp
lstupddate	timestamp
isregistrationaccepted	boolean
isprintsummary	boolean
isprintendorsement	boolean
isgenerateec	boolean
isdigitalsigned	boolean
isregistrationcompleted	boolean
gscno	varchar(15)
uploadsummarydocpath	text
partypaymentdetails	text
isscancompleted	boolean
isundervaluation	boolean
k1k2_flag	smallint
withdrawfilepath	text
withdrawdocument	varchar(100)
ackdatetime	timestamp
ackuser	varchar(100)

Table documentmaster_dashboard

Idx	Name	Data Type
	documentid	bigint
	srocode	integer
	bookid	integer
	stamparticlecode	integer
	regarticlecode	integer
	documentnumber	integer
	finalregistrationnumber	varchar(50)
	presentdatetime	timestamp
	executiondatetime	timestamp
	dateofstamp	timestamp
	stamp1datetime	timestamp
	stamp2datetime	timestamp
	stamp3datetime	timestamp
	stamp4datetime	timestamp
	stamp5datetime	timestamp
	withdrawaldate	timestamp
	pagecount	integer
	index2shera	varchar(250)
	isvisited	boolean
	isfiling	boolean
	ispending	boolean
	isscanned	boolean
	isrefused	boolean
	ispaymentofmoney	boolean
	isadjudicated	boolean
	iswithdrawn	boolean
	refusaldate	timestamp
	refusalreason	varchar(250)
	remarksbyuser	varchar(2000)
	remarksbysystem	varchar(250)
	correctionreference	bigint
	olddocreference	varchar(50)
	adjudicationdetails	varchar(2500)
	cdnumber	varchar(50)
	isxmltransferredtobhoomi	boolean
	uid	integer
	pendingdocumentnumber	varchar(20)
	istransmitted	boolean
	isphotothumbtransmitted	boolean
	inserteddatetime	timestamp
	initialtransmitted	boolean
	considerationamount	decimal(23,4)
	requiredstampduty	decimal(23,4)
	paidstampduty	decimal(23,4)
	documentstatus	varchar(5)
	applicationnumber	varchar(50)
	verified	boolean
	issroapproved	varchar(1)

Table documentmaster_dashboard

	deedattachpath	varchar(200)
	ispaymentdetails	boolean
	isuploaddocuments	boolean
	uploaddocdatetime	timestamp
	registrationdatetime	timestamp
	isregistrationevaluation	boolean
	uploaddocdeedpath	text
	uploaddocannexurepath	text
	docsubmitiondate	timestamp
	lstupddate	timestamp
	isregistrationaccepted	boolean
	isprintsummary	boolean
	isprintendorsement	boolean
	isgenerateec	boolean
	isdigitalsigned	boolean
	isregistrationcompleted	boolean
	gscno	varchar(15)
	uploadsummarydocpath	text
	partypaymentdetails	text
	isscancompleted	boolean
	isundervaluation	boolean
	k1k2_flag	smallint
	withdrawfilepath	text
	withdrawdocument	varchar(100)
	ackdatetime	timestamp
	ackuser	varchar(100)

Table documentmaster_dashboard_1

Idx	Name	Data Type
	documentid	bigint
	srocode	integer
	bookid	integer
	stamparticlecode	integer
	regarticlecode	integer
	documentnumber	integer
	finalregistrationnumber	varchar(50)
	presentdatetime	timestamp
	executiondatetime	timestamp
	dateofstamp	timestamp
	stamp1datetime	timestamp
	stamp2datetime	timestamp
	stamp3datetime	timestamp
	stamp4datetime	timestamp
	stamp5datetime	timestamp
	withdrawaldate	timestamp
	pagecount	integer
	index2shera	varchar(250)
	isvisited	boolean

Table documentmaster_dashboard_1	
isfiling	boolean
ispending	boolean
isscanned	boolean
isrefused	boolean
ispaymentofmoney	boolean
isadjudicated	boolean
iswithdrawn	boolean
refusaldate	timestamp
refusalreason	varchar(250)
remarksbyuser	varchar(2000)
remarksbysystem	varchar(250)
correctionreference	bigint
olddocreference	varchar(50)
adjudicationdetails	varchar(2500)
cdnumber	varchar(50)
isxmltransferredtobhoomi	boolean
uid	integer
pendingdocumentnumber	varchar(20)
istransmitted	boolean
isphotothumbtransmitted	boolean
inserteddatetime	timestamp
initialtransmitted	boolean
considerationamount	decimal(23,4)
requiredstampduty	decimal(23,4)
paidstampduty	decimal(23,4)
documentstatus	varchar(5)
applicationnumber	varchar(50)
verified	boolean
issroapproved	varchar(1)
deedattachpath	varchar(200)
ispaymentdetails	boolean
isuploaddocuments	boolean
uploaddocdatetime	timestamp
registrationdatetime	timestamp
isregistrationevaluation	boolean
uploaddocdeedpath	text
uploaddocannexurepath	text
docsubmitiondate	timestamp
lstupddate	timestamp
isregistrationaccepted	boolean
isprintsummary	boolean
isprintendorsement	boolean
isgenerateec	boolean
isdigitalsigned	boolean
isregistrationcompleted	boolean
gscno	varchar(15)
uploadsummarydocpath	text
partypaymentdetails	text
isscancompleted	boolean

Table documentmaster_dashboard_1

	isundervaluation	boolean
	k1k2_flag	smallint
	withdrawfilepath	text
	withdrawdocument	varchar(100)
	ackdatetime	timestamp
	ackuser	varchar(100)

Table documentrescandetails

Idx	Name	Data Type
* Pk	documentid	bigint
* Pk	srocode	integer
	rescanenabledatetime	timestamp
	isfileuploaded	boolean
	absolutefilepath	varchar(500)
	districtcode	integer
	filename	varchar(200)
	isactive	boolean
	insertdatetime	timestamp
	ipaddress	varchar(50)
	ispagecountmodified	boolean
	orderdate	timestamp
	ordernumber	varchar(200)
	pagecount	integer
	userid	bigint
	ismissingdocument	boolean
	k1k2_flag	smallint DEFAULT 2

Indexes

Type	Name	On
Pk	pk_docscandetails	documentid, srocode

Table documentsummary

Idx	Name	Data Type
* Pk	applicationnumber	varchar(100)
	json_value	text

Indexes

Type	Name	On
Pk	pk_documentsummary_applicationnumber	applicationnumber

Table documentsupportdocs

Idx	Name	Data Type
* Pk	documentid	bigint
* Pk	supportdocid	integer
	submitteddate	timestamp
	description	varchar(1000)
*	isrequired	boolean
	issubmitted	boolean
* Pk	srocode	integer
	inserteddatetime	timestamp DEFAULT CURRENT_TIMESTAMP

Table documentsupportdocs

	k1k2_flag	smallint DEFAULT 2

Indexes

Type	Name	On
Pk	pk_documentsupportdocs	documentid, supportdocid, srocode

Table documenttypemaster

Idx	Name	Data Type
* Pk	documenttypeid	integer
	documenttypedesc	varchar(50)
	k1k2_flag	smallint DEFAULT 2

Indexes

Type	Name	On
Pk	pk_documenttypemaster	documenttypeid

Table drc_push_kaveri_response

Idx	Name	Data Type
	txnno	integer
	drcno	text
	finalregistrationno	text
	request	text
	response	text
	inserteddate	timestamp DEFAULT CURRENT_TIMESTAMP

Table dummy_bhoomi

Idx	Name	Data Type
	finalregistrationnumber	varchar(50)

Table dummy_eaasthi

Idx	Name	Data Type
	finalregistrationnumber	varchar(50)

Table dummy_eaasthi_test

Idx	Name	Data Type
	finalregistrationnumber	varchar(50)

Table dummy_eswathu

Idx	Name	Data Type
	finalregistrationnumber	varchar(50)

Table dummy_eswathu_test

Idx	Name	Data Type
	finalregistrationnumber	varchar(50)

Table eaasthipidnumberdetails

Idx	Name	Data Type
* Pk	eaasthipidnumber	bigint
	roadcode	decimal(10,0)

Table eaasthipidnumberdetails

	pidnumber	varchar(50)
	inserteddatetime	timestamp DEFAULT CURRENT_TIMESTAMP
	k1k2_flag	smallint DEFAULT 2

Indexes

Type	Name	On
Pk	eaasthipidnumberdetails_pkey	eaasthipidnumber

Table eaasti_eswatuxmllog

Idx	Name	Data Type
* Pk	logid	bigint
	documentid	bigint
* Idx	propertyid	bigint
	pid	varchar
	xml	text
	srocode	decimal
	inserteddatetime	timestamp DEFAULT CURRENT_TIMESTAMP
	k1k2_flag	smallint DEFAULT 2

Indexes

Type	Name	On
	idx_eaasti_eswatuxmllog_propertyid	propertyid
Pk	eaasti_eswatuxmllog_pkey	logid

Table easthi_eswathu_fileuploaddetails

Idx	Name	Data Type
* Pk	referenceid	bigint DEFAULT nextval('kaveri.referenceid_seq_easthis'::regclass)
	uploaddate	timestamp
	jslipxml	text
	jslipxmlfinal	text
	acknowledgeno	varchar(8000)
Idx	finalregistrationnumber	varchar(50)
	remarks	text
	confirmationsent	boolean
	filepath	varchar(150)
	referencenumber	varchar(100)
	srocode	smallint
	createddate	timestamp
	k1k2_flag	smallint

Indexes

Type	Name	On
Pk	pk_referenceid_easthi_eswathu_fileuploaddetails	referenceid
	idx_easthi_eswathu_fileuploaddetails_finalregistrationnum_ccnew	finalregistrationnumber
	idx_easthi_eswathu_fileuploaddetails_finalregistrationnu_ccnew1	finalregistrationnumber
	idx_easthi_eswathu_fileuploaddetails_finalregistrationnumber	finalregistrationnumber

Table ec_accesslog

Idx	Name	Data Type

Table ec_accesslog

*	logid	bigint DEFAULT nextval('kaveri.ec_accesslog_logid_seq'::regclass)
	citizenid	bigint
	request_body	text
	inserteddatetime	timestamp DEFAULT CURRENT_TIMESTAMP

Table ec_applicationdetails

Idx	Name	Data Type
* Pk	ecid	bigint
	ecnumber	varchar(50)
	certificatenumber	varchar(50)
	ecdate	timestamp
Idx	userid	bigint
	searchfromdate	date
	searchtodate	date
	kaveridrocode	smallint
Idx	kaverisrocode	smallint
	kaverivillagecode	bigint
	kaverihoblicode	integer
	pagecount	integer
	totalamount	decimal(18,0)
	submittedby	bigint
	submitteddatetime	timestamp
	acceptedby	bigint
	acceptedon	timestamp
	documentstatusid	smallint
	preparedby	bigint
	prepareddatetime	timestamp
	signedby	bigint
	signeddatetime	timestamp
	appliedsignedcopy	boolean
	comparedby	bigint
	compareddatetime	timestamp
	eastboundary	varchar(300)
	westboundary	varchar(300)
	northboundary	varchar(300)
	southboundary	varchar(300)
	easttowest	varchar(300)
	northtosouth	varchar(300)
	remarktoreprepareec	varchar(200)
	area	decimal(18,0)
	propertydescription	varchar(10485760)
	measurementunitid	smallint
	hectare	decimal(18,0)
	acre	decimal(18,0)
	gunta	decimal(18,0)
	cents	decimal(18,0)
	partyname	varchar(200)
	isnamesearch	boolean

Table ec_applicationdetails

	ispropertysearch	boolean
	isdocviewable	boolean
Unq	applicationnumber	varchar(50)
	easttowestmeasurement	varchar(18)
	northtosouthmeasurement	varchar(18)
	propertytypeid	integer
	signedform22	text
	gscno	varchar
	k1k2_flag	smallint DEFAULT 2
	inserteddatetime	timestamp DEFAULT CURRENT_TIMESTAMP
	reason	varchar(150)
	isappliedbydept	boolean
	isbefore2004	boolean DEFAULT false
	refusalremarks	varchar(300)
	isrefused	boolean DEFAULT false

Indexes

Type	Name	On
	ec_applicationdetails_kaverisrocode_idx	kaverisrocode
Unq	uk_ec_applicationdetails_applicationnumber	applicationnumber
Pk	pk_ec_applicationdetails	ecid
	idx_ec_applicationdetails_user_ccnew	userid
	idx_ec_applicationdetails_user_ccnew1	userid
	idx_ec_applicationdetails_user	userid

Table ec_applicationdetails_dashboard

Idx	Name	Data Type
	ecid	bigint
	ecnumber	varchar(50)
	certificatenumber	varchar(50)
	ecdate	timestamp
	userid	bigint
	searchfromdate	date
	searchtodate	date
	kaveridrocode	smallint
	kaverisrocode	smallint
	kaverivillagecode	bigint
	kaverihoblicode	integer
	pagecount	integer
	totalamount	decimal(18,0)
	submittedby	bigint
	submitteddatetime	timestamp
	acceptedby	bigint
	acceptedon	timestamp
	documentstatusid	smallint
	preparedby	bigint
	prepareddatetime	timestamp
	signedby	bigint
	signeddatetime	timestamp

Table ec_applicationdetails_dashboard

	appliedsignedcopy	boolean
	comparedby	bigint
	compareddatetime	timestamp
	eastboundary	varchar(300)
	westboundary	varchar(300)
	northboundary	varchar(300)
	southboundary	varchar(300)
	easttowest	varchar(300)
	northtosouth	varchar(300)
	remarktoreprepareec	varchar(200)
	area	decimal(18,0)
	propertydescription	varchar(10485760)
	measurementunitid	smallint
	hectare	decimal(18,0)
	acre	decimal(18,0)
	gunta	decimal(18,0)
	cents	decimal(18,0)
	partyname	varchar(200)
	isnamesearch	boolean
	ispropertysearch	boolean
	isdocviewable	boolean
	applicationnumber	varchar(50)
	easttowestmeasurement	varchar(18)
	northtosouthmeasurement	varchar(18)
	propertytypeid	integer
	signedform22	text
	gscno	varchar
	k1k2_flag	smallint
	inserteddatetime	timestamp
	reason	varchar(150)
	isappliedbydept	boolean
	isbefore2004	boolean
	refusalremarks	varchar(300)
	isrefused	boolean

Table ec_checkedproperties

Idx	Name	Data Type
* Pk	checkedpid	bigint
*	propertyid	bigint
*	regsrocode	integer
*	ecid	bigint
	inserteddatetime	timestamp DEFAULT CURRENT_TIMESTAMP
	k1k2_flag	smallint DEFAULT 2

Indexes

Type	Name	On
Pk	pk_ec_checkedproperties	checkedpid

Table ec_cscapplicantdetails

Idx	Name	Data Type
* Pk	cscapplicantid	bigint
*	firstname	varchar(50)
	middlename	varchar(50)
	lastname	varchar(50)
*	address	varchar(150)
*	pincode	varchar(6)
*	mobilenumber	varchar(10)
	email	varchar(50)
	uid	varchar(30)
*	ecid	bigint
	operatorid	varchar(200)
	inserteddatetime	timestamp DEFAULT CURRENT_TIMESTAMP
	k1k2_flag	smallint DEFAULT 2

Indexes

Type	Name	On
Pk	pk_ec_cscapplicantdetails	cscapplicantid

Table ec_deptreferencecoderequiredfeemapping

Idx	Name	Data Type
* Pk	mappingid	bigint
	deptreferencecode	varchar(18)
	requiredfeeid	bigint
	inserteddatetime	timestamp DEFAULT CURRENT_TIMESTAMP
	k1k2_flag	smallint DEFAULT 2

Indexes

Type	Name	On
Pk	pk_ec_deptreferencecoderequiredfeemapping	mappingid

Table ec_esignfilepath

Idx	Name	Data Type
* Pk	fileid	bigint
*	ecid	bigint
	pserverpath	varchar(200)
	vserverpath	varchar(200)
	esigndatetime	timestamp
	inserteddatetime	timestamp DEFAULT CURRENT_TIMESTAMP
	k1k2_flag	smallint DEFAULT 2

Indexes

Type	Name	On
Pk	pk_ec_esignfilepath	fileid

Table ec_mapped_details_old

Idx	Name	Data Type
Idx	scheduleid	bigint
Idx	villagecode	bigint
Idx	currrentpropertytypeid	integer
Idx	currentnumber	varchar

Table ec_mapped_details_old

Idx	registrationdatetime	timestamp
	orderid	bigint
	k1k2flag	integer

Indexes

Type	Name	On
	idx_scheduleid_jsondata_ccnew	scheduleid
	idx_scheduleid_jsondata_ccnew1	scheduleid
	idx_ecmapped_regdate	registrationdatetime
	idx_scheduleidec	scheduleid
	idx_scheduleidec_currentno	currentnumber
	idx_scheduleidec_currentpropid	currrentpropertytypeid
	idx_scheduleidec_villagecode	villagecode
	idx_scheduleid_jsondata	scheduleid

Table ec_prepared

Idx	Name	Data Type
* Pk	id	bigint DEFAULT nextval('kaveri.ec_prepared_id_seq'::regclass)
	ecid	bigint
	json	text

Indexes

Type	Name	On
Pk	pk_preparedec_id	id

Table ec_propertynumberdetails

Idx	Name	Data Type
* Pk	ecpropertynoid	bigint
Idx	ecid	bigint
Idx	propertynotypeid	integer
	oldpropertynumber	varchar(50)
	newpropertynumber	varchar(50)
	presentpropertydetails	varchar(200)
	inserteddatetime	timestamp DEFAULT CURRENT_TIMESTAMP
	k1k2_flag	smallint DEFAULT 2

Indexes

Type	Name	On
	idx_ec_propertynumberdetails_propertynotypeid	propertynotypeid
	idx_ec_propertynumberdetails_ecid	ecid
	idx_ec_propertynumberdetails	ecid, propertynotypeid
Pk	pk_ec_propertynumberdetails	ecpropertynoid

Table ec_qrcodedetails

Idx	Name	Data Type
* Pk	qrcodeid	bigint
*	ecid	bigint
*	qrencryptkey	varchar(200)
	inserteddatetime	timestamp DEFAULT CURRENT_TIMESTAMP
	k1k2_flag	smallint DEFAULT 2

Indexes

Table ec_qrcodedetails

Type	Name	On
Pk	pk_ec_qrcodedetails	qrcodeid

Table ec_remarkdetails

Idx	Name	Data Type
* Pk	remarkid	bigint
	remark	varchar(200)
* Idx	ecid	bigint
*	documentstatusid	smallint
*	userid	bigint
*	documentstatusdatetime	timestamp
	inserteddatetime	timestamp DEFAULT CURRENT_TIMESTAMP
	k1k2_flag	smallint DEFAULT 2

Indexes

Type	Name	On
	idx_ec_remarkdetails_ecid	ecid
Pk	pk_ec_remarkdetails	remarkid

Table ec_requiredfees

Idx	Name	Data Type
* Pk	requiredfeeid	bigint
Idx	ecid	bigint
Idx	feeruleid	smallint
	payableamount	decimal(18,0)
*	ispaid	boolean
	serviceid	smallint
	feedescription	varchar(500)
	inserteddatetime	timestamp DEFAULT CURRENT_TIMESTAMP
	k1k2_flag	smallint DEFAULT 2

Indexes

Type	Name	On
	idx_ec_ec_requiredfees_ecid	ecid
	idx_ec_ec_requiredfees_fee	feeruleid
Pk	pk_ec_requiredfees	requiredfeeid

Table ec_signedfilepaths

Idx	Name	Data Type
* Pk	fileid	bigint
*	ecid	bigint
	preparedfserverpath	varchar(200)
	preparedvserverpath	varchar(200)
	prepareddatetime	timestamp
	comparedfserverpath	varchar(200)
	comparedvserverpath	varchar(200)
	compareddatetime	timestamp
	signedfserverpath	varchar(200)
	signedvserverpath	varchar(200)
	signeddatetime	timestamp

Table ec_signedfilepaths

	preparedreferencenumber	varchar(200)
	inserteddatetime	timestamp DEFAULT CURRENT_TIMESTAMP
	k1k2_flag	smallint DEFAULT 2

Indexes

Type	Name	On
Pk	pk_ec_signedfilepaths	fileid

Table ec_uncheckedproperties

Idx	Name	Data Type
* Pk	uncheckedpid	bigint
*	propertyid	bigint
*	regsrocode	integer
*	ecid	bigint
	inserteddatetime	timestamp DEFAULT CURRENT_TIMESTAMP
	k1k2_flag	smallint DEFAULT 2

Indexes

Type	Name	On
Pk	pk_ec_uncheckedproperties	uncheckedpid

Table eccertificate

Idx	Name	Data Type
* Pk	certificateid	bigint
*	srocode	integer
*	searchdate	timestamp
*	certificatenumber	varchar(30)
*	certificatedate	timestamp
* Unq	applicationnumber	varchar(50)
*	fromdate	timestamp
*	todate	timestamp
*	isnec	boolean
	searchdescription	varchar(1000)
	uid	integer
	liabilitydetails	varchar(4000)
*	istransmitted	boolean
*	certificatetype	integer
	certificatefile	text
	inserteddatetime	timestamp DEFAULT CURRENT_TIMESTAMP
	k1k2_flag	smallint DEFAULT 2

Indexes

Type	Name	On
Pk	pk_eccertificate	certificateid
Unq	uk_eccertificate_appnumber	applicationnumber

Table ecexemptiondetails

Idx	Name	Data Type
*	exemptioncode	integer
*	applicationid	bigint
*	srocode	integer

Table ecexemptiondetails

*	applicationfees	decimal
*	certificatefees	decimal
	inserteddatetime	timestamp DEFAULT CURRENT_TIMESTAMP
	k1k2_flag	smallint DEFAULT 2

Table ecmisseddata

Idx	Name	Data Type
Idx	finalregistrationnumber	varchar(50)
Idx	applicationnumber	varchar(50)
	registrationdatetime	timestamp

Indexes

Type	Name	On
	idx_appnomissed_ccnew	applicationnumber
	idx_appnomissedfinal_ccnew	finalregistrationnumber
	idx_appnomissed_ccnew1	applicationnumber
	idx_appnomissed	applicationnumber
	idx_appnomissedfinal	finalregistrationnumber

Table ecmisseddata_lastbatch

Idx	Name	Data Type
	finalregistrationnumber	varchar(50)

Table ecmisseddata_nopropnodetails

Idx	Name	Data Type
	finalregistrationnumber	varchar(50)
	applicationnumber	varchar(50)

Table ecname_mapped_details_new

Idx	Name	Data Type
	scheduleid	bigint
	villagecode	bigint
	registrationdatetime	timestamp
	fullname	text
	k1k2_flag	smallint

Table ecnamesearchkeyvalues

Idx	Name	Data Type
* Pk	keyid	bigint
*	documentid	bigint
*	srocode	integer
*	partytypeid	integer
	partyid	bigint
*	firstname	varchar(300)
	middlename	varchar(100)
*	lastname	varchar(350)
	orderid	bigint
*	isactivated	integer DEFAULT 1
	actiontype	char(1) DEFAULT 'I'::bpchar

Table ecnamesearchkeyvalues

	inserteddatetime	timestamp DEFAULT CURRENT_TIMESTAMP
	k1k2_flag	smallint DEFAULT 2

Indexes

Type	Name	On
Pk	pk_ecnamesearchkeyvalues	keyid

Table ecpropertysearchkeyvalues

Idx	Name	Data Type
* Pk	keyid	bigint
	executiondate	timestamp
*	villagecode	bigint
*	propertyid	bigint
	regsrocode	integer
*	srocode	integer
*	documentid	bigint
	newpropertyid	bigint
	newregsrocode	integer
	newsrocode	integer
*	currentpropertytypeid	integer
*	currentnumber	varchar(100)
	oldpropertytypeid	integer
	oldnumber	varchar(75)
	survey_no	integer
	surnoc	varchar(20)
	hissa_no	varchar(30)
	orderid	bigint
*	isactivated	integer DEFAULT 1
	actiontype	char(1) DEFAULT 'I'::bpchar
	inserteddatetime	timestamp DEFAULT CURRENT_TIMESTAMP
	k1k2_flag	smallint DEFAULT 2

Indexes

Type	Name	On
Pk	pk_ecpropertysearchkeyvalues	keyid

Table ecsearchdocumentnodetails

Idx	Name	Data Type
* Pk	ecsearchdocumentid	bigint
*	applicationid	bigint
*	srocode	integer
	bookid	integer
	documentnumber	integer
	registrationyear	varchar(7)
	k1k2_flag	smallint DEFAULT 2
	inserteddatetime	timestamp DEFAULT CURRENT_TIMESTAMP

Indexes

Type	Name	On
Pk	pk_ecsearchdocumentnodetails	ecsearchdocumentid

Table ecsearchpartydetails

Idx	Name	Data Type
* Pk	ecsearchpartyid	bigint
*	applicationid	bigint
*	srocode	integer
	partytypeid	integer
	partyname	varchar(100)
	k1k2_flag	smallint DEFAULT 2
	inserteddatetime	timestamp DEFAULT CURRENT_TIMESTAMP
Indexes		
Type	**Name**	**On**
Pk	pk_ecsearchpartydetails	ecsearchpartyid

Table ecsearchpropertynodetails

Idx	Name	Data Type
* Pk	ecsearchproperty	bigint
*	applicationid	bigint
*	srocode	integer
*	propertynotypeid	integer
	currentpropertynumber	varchar(75)
	oldpropertynumber	varchar(75)
	surveynumber	varchar(10)
	surveychar	varchar(20)
	surveyhissa	varchar(30)
	k1k2_flag	smallint DEFAULT 2
	inserteddatetime	timestamp DEFAULT CURRENT_TIMESTAMP
Indexes		
Type	**Name**	**On**
Pk	pk_ecsearchpropertynodetails	ecsearchproperty

Table eligibleappointmentdatedetails

Idx	Name	Data Type
* Pk	elgappid	bigint
*	elgapplicationnumber	varchar(50)
*	elgdocumenttype	varchar(250)
*	elgappointmentdate	timestamp
* Idx	srocode	integer
* Idx	selectedapplicationnumber	varchar(50)
*	selecteddocumenttype	varchar(250)
*	selectedappointmentdate	timestamp
* Idx	deptuserid	bigint
*	remark	text
	newappointmentdate	timestamp
Idx	inserteddatetime	timestamp DEFAULT CURRENT_TIMESTAMP
Indexes		
Type	**Name**	**On**
Pk	eligibleappointmentdatedetails_pkey	elgappid
	idx_eligibleappointmentdatedetails_inserteddatetime	inserteddatetime
	idx_eligibleappointmentdatedetails_selectedapplicationnumber	selectedapplicationnumber

Table eligibleappointmentdatedetails

	idx_eligibleappointmentdatedetails_deptuserid_ccnew	deptuserid
	idx_eligibleappointmentdatedetails_srocode_ccnew	srocode
	idx_eligibleappointmentdatedetails_deptuserid_ccnew1	deptuserid
	idx_eligibleappointmentdatedetails_srocode_ccnew1	srocode
	idx_eligibleappointmentdatedetails_deptuserid	deptuserid
	idx_eligibleappointmentdatedetails_srocode	srocode

Foreign Keys

Type	Name	On
	fk_eligibleappointmentdatedetails_applicationnumber (elgapplicationnumber) ref applicantapplicationdetails (applicationnumber)	
	fk_eligibleappointmentdatedetails_selapplicationnumber (selectedapplicationnumber) ref applicantapplicationdetails (applicationnumber)	

Table emp_transfer_details

Idx	Name	Data Type
* Pk	transferid	bigint DEFAULT nextval('kaveri.transfer_master_seq'::regclass)
*	empid	bigint
*	designationid	integer
*	currentlocation	varchar(80)
*	transferlocation	varchar(80)
*	from_date	timestamp
*	to_date	timestamp
*	reason	varchar(500)
	transferstatus	varchar(50)
	lastupdateddate	timestamp DEFAULT CURRENT_TIMESTAMP
	username	varchar(50)
	inserteddatetime	timestamp DEFAULT CURRENT_TIMESTAMP
	k1k2_flag	smallint DEFAULT 2

Indexes

Type	Name	On
Pk	pk_transferid_emp_transfer_details	transferid

Table empleavebalance

Idx	Name	Data Type
*	empid	bigint
*	leavetypeid	bigint
*	leaveyear	bigint
*	leaveeligible	bigint
*	leavebalance	bigint
	k1k2_flag	smallint DEFAULT 2

Table empleavedetails

Idx	Name	Data Type
* Pk	empleavedetailsid	bigint DEFAULT nextval('kaveri.empleavedetails_seq'::regclass)
* Idx	empid	bigint
*	leavetypeid	bigint
*	fromdate	timestamp
*	todate	timestamp
*	noofdays	bigint

Table empleavedetails

*	reason	varchar(400)
*	designationid	integer
*	reportingto	varchar(100)
*	reportingperson	varchar(100)
	holidayid	bigint
	leavestatus	varchar(20)
	rejectionreason	varchar(400)
	leaveapplydate	timestamp
	leaveapprovedate	timestamp
	leavemonth	timestamp
	lstupddate	timestamp DEFAULT CURRENT_TIMESTAMP
	lstupdusrid	bigint
	inserteddatetime	timestamp DEFAULT CURRENT_TIMESTAMP
	k1k2_flag	smallint DEFAULT 2

Indexes

Type	Name	On
Pk	pk_empleavedetailsid_empleavedetails	empleavedetailsid
	empleavedetailempid_index	empid
	empleavedetailsoid_index	empleavedetailsid

Table employeetypemaster

Idx	Name	Data Type
* Pk	employeetypeid	integer
	employeetypedesc	text
	inserteddatetime	timestamp DEFAULT CURRENT_TIMESTAMP
	k1k2_flag	smallint DEFAULT 2

Indexes

Type	Name	On
Pk	employeetypemaster_pkey	employeetypeid

Table encryption_key_vault

Idx	Name	Data Type
* Pk	id	integer DEFAULT nextval('kaveri.encryption_key_vault_id_seq'::regclass)
*	key_version	integer
*	encrypted_key	text
*	description	text
*	is_active	boolean DEFAULT true
*	created_on	timestamp DEFAULT CURRENT_TIMESTAMP

Indexes

Type	Name	On
Pk	encryption_key_vault_pkey	id

Table endorsementflowmaster

Idx	Name	Data Type
* Pk	endorsementflowid	integer DEFAULT nextval('kaveri.endorsementflowmaster_endorsementflowid_seq'::regclass)
	endorsmentname	varchar(100)

Table endorsementflowmaster

	endorsmentsubname	varchar(100)
	nature	varchar(50)
	periodicity	varchar(50)
	endorsementdescriptione	text
	endorsementdescriptionk	text
	inserteddatetime	timestamp DEFAULT CURRENT_TIMESTAMP
	k1k2_flag	smallint DEFAULT 2

Indexes

Type	Name	On
Pk	pk_endorsementflowid	endorsementflowid

Table endorsementmaster

Idx	Name	Data Type
* Pk	endorsementid	bigint
	endorsementdescription	varchar(255)
	marriagetypeid	integer
	reasonid	bigint
	inserteddatetime	timestamp DEFAULT CURRENT_TIMESTAMP
	k1k2_flag	smallint DEFAULT 2

Indexes

Type	Name	On
Pk	pk_endorsementmaster	endorsementid

Table exemptmaster

Idx	Name	Data Type
* Pk	srno	integer DEFAULT nextval('kaveri.exemptmaster_srno_seq'::regclass)
*	description	varchar(2000)
*	exemption	varchar(200)
*	forgovfee	boolean
*	forregfee	boolean
*	forcc	boolean
*	forec	boolean
	inserteddatetime	timestamp DEFAULT CURRENT_TIMESTAMP
	k1k2_flag	smallint DEFAULT 2

Indexes

Type	Name	On
Pk	exemptmaster_pkey	srno

Table extent

Idx	Name	Data Type
	extentid	bigint
	extenttype	varchar
	k1k2_flag	smallint DEFAULT 2

Table failed_jobs

Idx	Name	Data Type
* Pk	id	bigint DEFAULT nextval('kaveri.failed_jobs_id_seq'::regclass)

Table failed_jobs

* Unq	uuid	varchar(255)
*	connection	text
* Idx	queue	text
*	payload	text
*	exception	text
*	failed_at	timestamp(22) DEFAULT CURRENT_TIMESTAMP
	inserteddatetime	timestamp DEFAULT CURRENT_TIMESTAMP

Indexes

Type	Name	On
Pk	failed_jobs_pkey	id
	idx_failed_jobs_queue	queue
Unq	uk_failedjob_uuid_ccnew	uuid
Unq	uk_failedjob_uuid_ccnew1	uuid
Unq	uk_failedjob_uuid	uuid

Table fectchdeed

Idx	Name	Data Type
	finalregistrationnumber	varchar

Table feedashboarddetails

Idx	Name	Data Type
Idx	feesname	varchar(250)
Idx	feerulecode	integer
Idx	feesamount	decimal
	lastrefreshdate	timestamp

Indexes

Type	Name	On
	idx_feedashboarddetails_fee	feesname, feerulecode, feesamount

Table feedashboarddetails_new

Idx	Name	Data Type
Idx	feesname	varchar(250)
Idx	srocode	integer
Idx	feerulecode	integer
Idx	feesamount	decimal

Indexes

Type	Name	On
	idx_feedashboarddetails_fee_new	feesname, srocode, feerulecode, feesamount

Table feeruleslabs

Idx	Name	Data Type
* Pk	id	integer
*	feerulecode	integer
*	slabamtfrom	decimal
*	slabamtto	decimal
*	unit	smallint
	maxlimit	decimal
*	value	decimal

Table feeruleslabs

	plusthisamount	decimal
	inserteddatetime	timestamp DEFAULT CURRENT_TIMESTAMP
	k1k2_flag	smallint DEFAULT 2

Indexes

Type	Name	On
Pk	pk_feeruleslabs	id

Table feesrequired

Idx	Name	Data Type	Description
Idx	documentid	bigint	
* Idx	feerulecode	integer	
	isexempted	boolean	
	exemptdescription	varchar(200)	
	isactive	boolean	
	feecalculationstring	varchar(500)	
Idx	srocode	integer	
	isonline	boolean	
	amountrequired	decimal(23,4)	
Idx	applicationnumber	varchar(50)	
Idx	propertyid	bigint	
	lastupdateddate	timestamp	
	exemtype	varchar(50)	
	exemamount	integer	
	exemdocpath	varchar(500)	
	denodocpath	varchar(500)	
	sfdaamountrequired	decimal(23,4)	
Idx	sroamountrequired	decimal(23,4)	
Idx	amountpaid	decimal(23,4)	
	valuatiotypeid	smallint	
	sfdastamprule	integer	
	srostamprule	integer	
	regexemtype	varchar(50)	
	regexemamount	integer	
	paymentstatus	varchar(15)	
	inserteddatetime	timestamp DEFAULT CURRENT_TIMESTAMP	
	k1k2_flag	smallint DEFAULT 2	
	receiptid	bigint	Stores receipt ID that was generated for this fees
	undervaluationamount	decimal(23,4) DEFAULT NULL::numeric	

Indexes

Type	Name	On	Description
	idx_feesrequired_propertyid	propertyid	
	idx_feesrequired_sroamountrequired	sroamountrequired	
	idx_feesrequired_doc	documentid	
	index_feerequired_app	applicationnumber	
	index_feesrequired	documentid, feerulecode, srocode	

Table feesrequired

	index_feesrequired_multiple	applicationnumber, feerulecode, srocode
	idx_feesrequired_fee	feerulecode
	idx_feesrequired_amount	amountpaid

Foreign Keys

Type	Name	On	Description
	fk_feesrequired_applicantapplicationdetails (applicationnumber) ref applicantapplicationdetails (applicationnumber)		

Table feesrequired_cd140

Idx	Name	Data Type
	documentid	bigint
	feerulecode	integer
	isexempted	boolean
	exemptdescription	varchar(200)
	isactive	boolean
	feecalculationstring	varchar(500)
	srocode	integer
	isonline	boolean
	amountrequired	decimal(23,4)
	applicationnumber	varchar(50)
	propertyid	bigint
	lastupdateddate	timestamp
	exemtype	varchar(50)
	exemamount	integer
	exemdocpath	varchar(500)
	denodocpath	varchar(500)
	sfdaamountrequired	decimal(23,4)
	sroamountrequired	decimal(23,4)
	amountpaid	decimal(23,4)
	valuatiotypeid	smallint
	sfdastamprule	integer
	srostamprule	integer
	regexemtype	varchar(50)
	regexemamount	integer
	paymentstatus	varchar(15)
	inserteddatetime	timestamp
	k1k2_flag	smallint
	receiptid	bigint
	undervaluationamount	decimal(23,4)

Table feesrequired_dashboard_1

Idx	Name	Data Type
	documentid	bigint
	feerulecode	integer
	isexempted	boolean
	exemptdescription	varchar(200)
	isactive	boolean

Table feesrequired_dashboard_1

	feecalculationstring	varchar(500)
	srocode	integer
	isonline	boolean
	amountrequired	decimal(23,4)
	applicationnumber	varchar(50)
	propertyid	bigint
	lastupdateddate	timestamp
	exemtype	varchar(50)
	exemamount	integer
	exemdocpath	varchar(500)
	denodocpath	varchar(500)
	sfdaamountrequired	decimal(23,4)
	sroamountrequired	decimal(23,4)
	amountpaid	decimal(23,4)
	valuatiotypeid	smallint
	sfdastamprule	integer
	srostamprule	integer
	regexemtype	varchar(50)
	regexemamount	integer
	paymentstatus	varchar(15)
	inserteddatetime	timestamp
	k1k2_flag	smallint
	receiptid	bigint
	undervaluationamount	decimal(23,4)

Table feesrequired_paymentchk

Idx	Name	Data Type
	documentid	bigint
	feerulecode	integer
	isexempted	boolean
	exemptdescription	varchar(200)
	isactive	boolean
	feecalculationstring	varchar(500)
	srocode	integer
	isonline	boolean
	amountrequired	decimal(23,4)
Idx	applicationnumber	varchar(50)
	propertyid	bigint
	lastupdateddate	timestamp
	exemtype	varchar(50)
	exemamount	integer
	exemdocpath	varchar(500)
	denodocpath	varchar(500)
	sfdaamountrequired	decimal(23,4)
	sroamountrequired	decimal(23,4)
	amountpaid	decimal(23,4)
	valuatiotypeid	smallint
	sfdastamprule	integer

Table feesrequired_paymentchk

	srostamprule	integer
	regexemtype	varchar(50)
	regexemamount	integer
	paymentstatus	varchar(15)
	inserteddatetime	timestamp
	k1k2_flag	smallint
	receiptid	bigint
	undervaluationamount	decimal(23,4)

Indexes

Type	Name	On
	idx_feesrequired_paymentchk	applicationnumber

Table feesrequired_regrepayment

Idx	Name	Data Type
	documentid	bigint
	feerulecode	integer
	isexempted	boolean
	exemptdescription	varchar(200)
	isactive	boolean
	feecalculationstring	varchar(500)
	srocode	integer
	isonline	boolean
	amountrequired	decimal(23,4)
	applicationnumber	varchar(50)
	propertyid	bigint
	lastupdateddate	timestamp
	exemtype	varchar(50)
	exemamount	integer
	exemdocpath	varchar(500)
	denodocpath	varchar(500)
	sfdaamountrequired	decimal(23,4)
	sroamountrequired	decimal(23,4)
	amountpaid	decimal(23,4)
	valuatiotypeid	smallint
	sfdastamprule	integer
	srostamprule	integer
	regexemtype	varchar(50)
	regexemamount	integer
	paymentstatus	varchar(15)
	inserteddatetime	timestamp
	k1k2_flag	smallint
	receiptid	bigint
	undervaluationamount	decimal(23,4)

Table feesresssurcharg

Idx	Name	Data Type
	wrkflowstatusnamee	text
	currentstatus	varchar(5)

Table feesresssurcharg

	applicationnumber	varchar(50)
	stampduty	decimal
	surchagetobecollected	decimal
	surchagecalculated	decimal
	surchage2percentcollected	decimal

Table feesrulemaster

Idx	Name	Data Type	Description
* Pk	feerulecode	integer	
*	regarticlecode	integer	
	sameasarticleid	smallint	
	parentrefid	smallint	
*	haschild	boolean	
*	descriptionk	varchar(250)	
* Idx	descriptione	varchar(250)	
*	isslabs	boolean	
*	unitisamount	boolean	
	unitdescriptionk	varchar(150)	
	unitdescriptione	varchar(150)	
*	unit	double precision	
*	value	double precision	
	minlimit	decimal	
	maxlimit	decimal	
	multipliedby	smallint	
*	isinpercentage	boolean	
*	isfixduty	boolean	
*	isexempted	boolean	
*	isruleactive	boolean	
	stdseqid	integer	
*	isother	boolean	
*	feetype	smallint	
	subrefcode	char(2)	
	ismanualfee	boolean	
	inserteddatetime	timestamp DEFAULT CURRENT_TIMESTAMP	
	k1k2_flag	smallint DEFAULT 2	
	isreceiptreq	boolean DEFAULT true	This flag conveys whether this feerule will be part of receipt or not
	serviceid	integer	

Indexes

Type	Name	On	Description
	idx_feesrulemaster_districtcode	descriptione	
Pk	pk_feesrulemaster	feerulecode	

Table filing_book1

Idx	Name	Data Type
	filing_date	date
	issuingauthority	varchar(300)
*	applicationnumber	varchar(50)
	challan_number	varchar(50) DEFAULT ''::character varying

Table filing_book1

	amount_paid	varchar(10) DEFAULT '0'::character varying
	payment_type_id	varchar(10) DEFAULT ''::character varying
	is_stamp_duty_paid	boolean DEFAULT false
	endorsement_date	timestamp
	book_id	integer
	order_number	varchar(50) DEFAULT ''::character varying
	surety_amount	varchar(10)

Table fingertypemaster

Idx	Name	Data Type
* Pk	fingerid	integer
	description	varchar(100)
*	displayorder	integer
	inserteddatetime	timestamp DEFAULT CURRENT_TIMESTAMP
	k1k2_flag	smallint DEFAULT 2

Indexes

Type	Name	On
Pk	pk_fingertypemaster	fingerid

Table fingerverificationstatusmaster

Idx	Name	Data Type
* Pk	fingerverificationstatusid	smallint
*	fingerverificationstatus	varchar(50)
	inserteddatetime	timestamp DEFAULT CURRENT_TIMESTAMP
	k1k2_flag	smallint DEFAULT 2

Indexes

Type	Name	On
Pk	pk_fingerverificationstatusmaster	fingerverificationstatusid

Table firmamendment

Idx	Name	Data Type
* Pk	amendmentid	decimal
	firmnumber	varchar(50)
	amendmentcount	integer
	firmname	varchar(200)
	firmaddress	varchar(350)
	registrationid	decimal
	amendmentdatetime	timestamp
*	drcode	integer
	k1k2_flag	smallint DEFAULT 2
	inserteddatetime	timestamp DEFAULT CURRENT_TIMESTAMP

Indexes

Type	Name	On
Pk	firmamendment_pkey	amendmentid

Table firmbranches

Idx	Name	Data Type
* Pk	branchid	integer

Table firmbranches

*	registrationid	varchar(50)
	branchaddress	varchar(200)
	branchphone	varchar(50)
	addedon	timestamp
	oldaddress	varchar(200)
	changedate	timestamp
	fax	varchar(50)
	cell	varchar(50)
*	drcode	integer
	k1k2_flag	smallint DEFAULT 2
	inserteddatetime	timestamp DEFAULT CURRENT_TIMESTAMP

Indexes

Type	Name	On
Pk	pk_firmbranches	branchid

Table firmmaster

Idx	Name	Data Type
* Pk	registrationid	decimal
	firmnumber	varchar(50)
*	firmname	varchar(200)
*	firmaddress	varchar(350)
	firmphone	varchar(60)
*	parentref	integer
	hasbranches	boolean
	dateofregistration	timestamp
	supportdocuments	varchar(60)
	durationoffirm	integer
	nameofpresenter	varchar(100)
	designation	varchar(100)
	fees	integer
	amendmentno	integer
	amendmentdesc	varchar(400)
	pages	integer
	remarks	varchar(200)
	oldname	varchar(200)
	printflag	boolean
	receiptid	bigint
	oldaddress	varchar(350)
	atwill	integer
*	firstname	varchar(200)
*	firstaddress	varchar(350)
	nature	integer
	drcode	integer
	firmtype	varchar(10)
	isscanned	integer
	cdnumber	varchar(8)
	oldfirmdate	char(10)
	changedate	timestamp

Table firmmaster

	k1k2_flag	smallint DEFAULT 2
	inserteddatetime	timestamp DEFAULT CURRENT_TIMESTAMP

Indexes

Type	Name	On
Pk	firmmaster_pkey	registrationid

Table firmparty

Idx	Name	Data Type
*	personid	bigint
	firmnumber	varchar(50)
*	registrationid	bigint
	fullname	varchar(500)
	presentaddress	varchar(400)
	permanentaddress	varchar(400)
	occupation	varchar(40)
	dob	timestamp
	sex	char(1)
	age	integer
	memberof	boolean
	phoneno	varchar(40)
	mailaddress	varchar(60)
	dateofjoin	timestamp
	dateofsease	timestamp
	majororminor	integer
*	drcode	integer
	inserteddatetime	timestamp DEFAULT CURRENT_TIMESTAMP
	k1k2_flag	smallint DEFAULT 2

Table firmsakalapending

Idx	Name	Data Type
	gscno	varchar(15)
	applicationnumber	varchar(50)
	webmethod	varchar(50)

Table frm_addressdetails

Idx	Name	Data Type
* Pk	addressid	bigint
	officeid	smallint
	housedoornumber	varchar(20)
	buildingnumber	varchar(20)
	buildingname	varchar(60)
	blockdetails	varchar(100)
	streetsectordetails	varchar(60)
	areadetails	varchar(400)
	town	varchar(60)
	village	varchar(1000)
	subdistrict	varchar(60)
	subdistrictid	smallint

Table frm_addressdetails

	districtid	smallint
	stateid	smallint
	countryid	smallint
	othercountrydetails	varchar(500)
	pin	decimal
	villageid	bigint
	printableaddress	varchar(1000)
	inserteddatetime	timestamp DEFAULT CURRENT_TIMESTAMP
	k1k2_flag	smallint DEFAULT 2

Indexes

Type	Name	On
Pk	frm_addressdetails_pkey	addressid

Table frm_applicationforwarddetails

Idx	Name	Data Type
* Pk	id	bigint
*	officeid	smallint
*	firmid	bigint
*	userid	bigint
	datetime	timestamp
*	forwardedtoroleid	smallint
*	actionid	smallint
*	remarks	varchar(2048)
*	kiosktokenid	bigint
*	forwardedbyroleid	smallint
	resourceid	integer
	k1k2_flag	smallint DEFAULT 2
	inserteddatetime	timestamp DEFAULT CURRENT_TIMESTAMP

Indexes

Type	Name	On
Pk	frm_applicationforwarddetails_pkey	id

Table frm_checkslipsdetails

Idx	Name	Data Type
* Pk	checkslipdetailsid	bigint
*	firmid	bigint
*	checkslipid	smallint
	remarks	varchar(400)
	ischecked	boolean
	userid	bigint
	resourceid	integer
	inserteddatetime	timestamp DEFAULT CURRENT_TIMESTAMP
	k1k2_flag	smallint DEFAULT 2

Indexes

Type	Name	On
Pk	frm_checkslipsdetails_pkey	checkslipdetailsid

Table frm_endorsementdetails

Idx	Name	Data Type
* Pk	endorsementid	bigint
*	firmid	bigint
*	officeid	smallint
*	endorsementtypeid	smallint
*	endorsementnumber	varchar(50)
*	remarks	varchar(1000)
*	dateofendorsement	timestamp
*	userid	bigint
	resourceid	integer
	endorsementfileid	bigint
	k1k2_flag	smallint DEFAULT 2
	inserteddatetime	timestamp DEFAULT CURRENT_TIMESTAMP

Indexes

Type	Name	On
Pk	frm_endorsementdetails_pkey	endorsementid

Table frm_feerequired_paymentmapping

Idx	Name	Data Type
* Pk	id	bigint
*	feerequiredid	bigint
	feespaymentid	bigint
	k1k2_flag	smallint DEFAULT 2

Indexes

Type	Name	On
Pk	frm_feerequired_paymentmapping_pkey	id

Table frm_finaluploadeddocs

Idx	Name	Data Type
* Pk	finaluploadeddocid	bigint
	processmappingid	smallint
*	firmid	bigint
	amendmentid	bigint
	dissolutionid	bigint
*	pages	smallint
*	fileuploaddate	timestamp
	filename	varchar(150)
	filesize	bigint
	fileserverpath	varchar(150)
	checksum	varchar(1)
	uploadedbyuserid	bigint
	uploadedbyresourceid	integer
	crossrefid	bigint
	virtualserverpath	varchar(500)
	isdigitalsign	boolean
	receiptid	bigint
	uploaddoctypeid	smallint
	k1k2_flag	smallint DEFAULT 2

Table frm_finaluploadeddocs

	inserteddatetime	timestamp DEFAULT CURRENT_TIMESTAMP

Indexes

Type	Name	On
Pk	frm_finaluploadeddocs_pkey	finaluploadeddocid

Table frm_firmbranches

Idx	Name	Data Type
* Pk	branchid	bigint
*	applicationid	bigint
	branchaddress	varchar(400)
	branchphone	varchar(11)
*	branchopeningdate	timestamp
*	branchaddeddate	timestamp
*	registrationid	varchar(100)
	addedon	timestamp
	oldaddress	varchar(400)
	changedate	timestamp
	fax	varchar(100)
	cell	varchar(100)
*	drcode	integer
	k1k2_flag	smallint DEFAULT 2
	inserteddatetime	timestamp DEFAULT CURRENT_TIMESTAMP

Indexes

Type	Name	On
Pk	frm_firmbranches_pkey	branchid

Table frm_firmdetails

Idx	Name	Data Type
* Pk	firmid	bigint
*	officeid	smallint
*	kiosktokenid	bigint
*	documentstatusid	smallint
	finalregistrationnumber	varchar(50)
*	serialnumber	bigint
	registrationnumber	bigint
	dateofregistration	timestamp
*	firmname	varchar(500)
*	atwill	boolean
	stdcode	smallint
	phonenumber	varchar(11)
	mobile	varchar(10)
	emaiid	varchar(50)
	pan	varchar(10)
	establishmentdate	timestamp
	durationinmonth	smallint
	hasbranches	boolean
	pages	integer
	remarks	varchar(500)

Table frm_firmdetails

	isold	boolean
	isscanned	boolean
	isdissolved	boolean
	addressid	bigint
	firmnatureid	smallint
*	firmbusinesstypeid	smallint
*	dateofconstitutionoffirm	timestamp
*	applicationdate	timestamp
	userid	bigint
	resourceid	integer
	iskaveri1data	boolean
	kaveri1firmregistrationid	decimal
	isstampdutyalreadypaid	boolean
	k1k2_flag	smallint DEFAULT 2
	inserteddatetime	timestamp DEFAULT CURRENT_TIMESTAMP

Indexes

Type	Name	On
Pk	frm_firmdetails_pkey	firmid

Table frm_firmpaymentdetails

Idx	Name	Data Type
* Pk	paymentid	bigint
*	officeid	smallint
	userid	bigint
	resourceid	integer
	firmid	bigint
	amendmentid	bigint
	dissolutionid	bigint
	partyid	bigint
	firmname	varchar(500)
	k1k2_flag	smallint DEFAULT 2

Indexes

Type	Name	On
Pk	frm_firmpaymentdetails_pkey	paymentid

Table frm_firmprocessforfee

Idx	Name	Data Type
* Pk	id	bigint
*	firmid	bigint
	amendmentid	bigint
	dissolutionid	bigint
*	processid	smallint
*	isfeecalculated	boolean
	k1k2_flag	smallint DEFAULT 2

Indexes

Type	Name	On
Pk	frm_firmprocessforfee_pkey	id

Table frm_firmrefusaldetails

Idx	Name	Data Type
* Pk	refusalid	integer
*	refusalnumber	varchar(100)
*	refusaldate	timestamp
*	remarks	varchar(2048)
*	isrevoked	boolean
*	reasonid	smallint
*	firmid	bigint
	endorsementid	bigint
	k1k2_flag	smallint DEFAULT 2
	inserteddatetime	timestamp DEFAULT CURRENT_TIMESTAMP

Indexes

Type	Name	On
Pk	frm_firmrefusaldetails_pkey	refusalid

Table frm_partnerdetails

Idx	Name	Data Type
* Pk	partnerid	bigint
*	officeid	smallint
	firmid	bigint
	presentertypeid	smallint
*	title	smallint
*	firstname	varchar(150)
	middlename	varchar(150)
	lastname	varchar(150)
*	joiningdate	timestamp
	presentaddressid	bigint
	permanentaddressid	bigint
	dateofbirth	timestamp
	age	smallint
*	genderid	smallint
	professionid	smallint
	maritalstatusid	smallint
*	nationalityid	smallint
*	idproofid	smallint
*	idproofnumber	varchar(20)
	pan	varchar(10)
	epic	varchar(30)
	stdcode	smallint
	phonenumber	varchar(11)
	relativename	varchar(500)
	relationid	smallint
	email	varchar(150)
	ismajor	boolean
	isceased	boolean
	isamendment	boolean
	partnerceaseddate	timestamp
	amendmentid	bigint

Table frm_partnerdetails

*	isactive	boolean
	ispresenter	boolean
	k1k2_flag	smallint DEFAULT 2
	inserteddatetime	timestamp DEFAULT CURRENT_TIMESTAMP

Indexes

Type	Name	On
Pk	frm_partnerdetails_pkey	partnerid

Table frm_supporteddocuments

Idx	Name	Data Type
* Pk	applicationid	bigint
	supportdocumentid	integer
	k1k2_flag	smallint DEFAULT 2

Indexes

Type	Name	On
Pk	frm_supporteddocuments_pkey	applicationid

Table frm_witnessdetails

Idx	Name	Data Type
* Pk	witnessid	bigint
*	officeid	smallint
	firmid	bigint
*	titleid	smallint
*	firstname	varchar(150)
	middlename	varchar(150)
	lastname	varchar(150)
	dateofbirth	timestamp
	age	smallint
*	genderid	smallint
	professionid	smallint
	maritalstatusid	smallint
	pan	varchar(10)
*	idproofid	smallint
*	idproofnumber	varchar(20)
	stdcode	smallint
	phonenumber	varchar(11)
	mobilenumber	varchar(10)
*	addressid	bigint
	inserteddatetime	timestamp DEFAULT CURRENT_TIMESTAMP
	k1k2_flag	smallint DEFAULT 2

Indexes

Type	Name	On
Pk	frm_witnessdetails_pkey	witnessid

Table fruits_data_recv_details

Idx	Name	Data Type
* Pk	requestid	bigint DEFAULT nextval('kaveri.fruits_data_recv_requestid_seq'::regclass)

Table fruits_data_recv_details

* Pk	psrocode	integer
* Unq	referenceno	varchar(50)
*	srocode	integer
*	formiiidata	text
	transxml	text
*	formiiipath	text
*	transxmlpath	varchar(100)
*	aknowledgementno	varchar(50)
*	datareceiveddate	timestamp
	documentid	bigint
	formiiidatasigned	text
	issignedformiiiuploaded	integer
	documentstatuscode	smallint
*	kaigreg_insertdatetime	timestamp DEFAULT CURRENT_TIMESTAMP
	actiondatetime	timestamp
	actionstatuscode	smallint
	istransmitted	integer
	isrejectedtransmitted	integer
Idx	applicationnumber	varchar(50)
	transactiontype	char(1)
	isformiiisrsigned	boolean
	endorsement	text
	k1k2_flag	smallint DEFAULT 2
	inserteddatetime	timestamp DEFAULT CURRENT_TIMESTAMP
	applicationstatus	integer
	isaadharapatra	boolean
	consideration	bigint
	loantype	varchar
	cropid	integer

Indexes

Type	Name	On
	idx_fruits_data_recv_details_applicationnumber	applicationnumber
Pk	pk_fruits_data_recv_details	requestid, psrocode
Unq	unique_referenceno	referenceno

Table function_def

Idx	Name	Data Type
	definition	text

Table function_def_lastet

Idx	Name	Data Type
	proname	name
	pg_get_functiondef	text

Table function_dll

Idx	Name	Data Type
	definition	text

Table functiondef

Idx	Name	Data Type
	proname	name
	pg_get_functiondef	text

Table functionmaster

Idx	Name	Data Type
* Pk	functionid	integer DEFAULT nextval('kaveri.functionid_seq'::regclass)
	functionname	text
Idx	moduleid	integer
Idx	submoduleid	integer
	inserteddatetime	timestamp DEFAULT CURRENT_TIMESTAMP
	createdby	bigint

Indexes

Type	Name	On
Pk	pk_functionmaster	functionid
	idx_functionmaster_functionid	functionid
	idx_functionmaster_moduleid	moduleid
	idx_functionmaster_submoduleid	submoduleid

Table gendermaster

Idx	Name	Data Type
* Pk	genderid	smallint
*	descriptione	varchar(50)
*	descriptionk	varchar(50)
*	descriptionshorte	varchar(50)
*	descriptionshortk	varchar(50)
	crtusr	varchar(10)
	crtdt	timestamp DEFAULT now()
	lstupusr	varchar(10)
	lstupddt	timestamp DEFAULT now()
	k1k2_flag	smallint DEFAULT 2

Indexes

Type	Name	On
Pk	pk_gendermaster	genderid
	idx_gendermaster	genderid

Table graphcnt_dashboad

Idx	Name	Data Type
	applicationtypeid	integer
	applicationtypename	varchar
	cnt_totalapplication	bigint
Idx	srocode	integer
	bookid	integer
	bookname	varchar
Idx	fromdate	date
Idx	todate	date

Indexes

Type	Name	On

Table graphcnt_dashboad

	idx_todate	todate
	idx_fromdate	fromdate
	idx_srocode_ccnew	srocode
	idx_srocode	srocode

Table group_roll_mapping

Idx	Name	Data Type
* Pk	groupid	integer
* Pk	rollid	integer
	inserteddatetime	timestamp DEFAULT CURRENT_TIMESTAMP
	k1k2_flag	integer DEFAULT 2

Indexes

Type	Name	On
Pk	pk_group_roll_mapping	groupid, rollid

Table hoblimaster

Idx	Name	Data Type
* Pk	hoblicode	integer
Idx	talukcode	integer
	hoblinamek	varchar(500)
	hoblinamee	varchar(500)
	shortnamek	varchar(5)
	shortnamee	varchar(5)
	bhoomihoblicode	integer
	bhoomihobliname	varchar(100)
Idx	bhoomitalukcode	integer
	bhoomitalukname	varchar(100)
	bhoomidistrictcode	integer
	k1k2_flag	smallint DEFAULT 2

Indexes

Type	Name	On
Pk	pk_hoblimaster	hoblicode
	idx_hoblimaster	talukcode
	idx_hoblimaster_bhoomitalukcode	bhoomitalukcode

Table hoblimaster_15feb2025

Idx	Name	Data Type
	hoblicode	integer
	talukcode	integer
	hoblinamek	varchar(500)
	hoblinamee	varchar(500)
	shortnamek	varchar(5)
	shortnamee	varchar(5)
	bhoomihoblicode	integer
	bhoomihobliname	varchar(100)
	bhoomitalukcode	integer
	bhoomitalukname	varchar(100)
	bhoomidistrictcode	integer

Table hoblimaster_15feb2025

	k1k2_flag	smallint

Table hoblimaster_prod1

Idx	Name	Data Type
	hoblicode	integer
	talukcode	integer
	hoblinamek	varchar(500)
	hoblinamee	varchar(500)
	shortnamek	varchar(5)
	shortnamee	varchar(5)
	bhoomihoblicode	integer
	bhoomihobliname	varchar(100)
	bhoomitalukcode	integer
	bhoomitalukname	varchar(100)
	bhoomidistrictcode	integer
	k1k2_flag	smallint

Table hoblimaster_prod2

Idx	Name	Data Type
	hoblicode	integer
	talukcode	integer
	hoblinamek	varchar(500)
	hoblinamee	varchar(500)
	shortnamek	varchar(5)
	shortnamee	varchar(5)
	bhoomihoblicode	integer
	bhoomihobliname	varchar(100)
	bhoomitalukcode	integer
	bhoomitalukname	varchar(100)
	bhoomidistrictcode	integer
	k1k2_flag	smallint

Table holidaymaster

Idx	Name	Data Type
* Pk	holidayid	integer DEFAULT nextval('kaveri.holidaymaster_holidayid_seq'::regclass)
*	holidayname	varchar
*	holidaytypeid	bigint
	holidaydate	timestamp
	lstinsddate	timestamp DEFAULT CURRENT_TIMESTAMP
	lstupdusrid	varchar
	k1k2_flag	smallint DEFAULT 2

Indexes

Type	Name	On
Pk	pk_holidaymaster_holidayid	holidayid

Table index_1_data

Idx	Name	Data Type

Table index_1_data

	party1name	varchar(6000)
	party1address	varchar(6000)
	party2name	varchar(6000)
	party2address	varchar(6000)
	villagename	varchar(500)
	executiondate	timestamp
	stamp5datetime	timestamp
	sroname	varchar(250)
	documentid	bigint
	cdnumber	varchar(50)
	finalregistrationnumber	varchar(150)
	propertyid	bigint
	villagecode	bigint
	inserteddatetime	timestamp DEFAULT CURRENT_TIMESTAMP
	k1k2_flag	smallint DEFAULT 2

Table index_fragmented

Idx	Name	Data Type
	tablename	name
	indexname	name
	table_size	text
	index_size	text
	leaf_fragmentation	double precision

Table individualapartmentdetails

Idx	Name	Data Type
* Pk	individualapartmentid	bigint
* Pk	mainapartmentid	bigint
* Pk	srocode	integer
*	individualapartmentno	varchar(75)
*	floorid	integer
*	blockno	varchar(75)
*	eastboundary	varchar(500)
*	westboundary	varchar(500)
*	northboundary	varchar(500)
*	southboundary	varchar(500)
*	superbuiltuparea	decimal(18,0)
*	carpetarea	decimal(18,0)
*	undividedshare	decimal(18,0)
*	unitid	integer
	remarks	varchar(150)
	inserteddatetime	timestamp DEFAULT CURRENT_TIMESTAMP
	k1k2_flag	smallint DEFAULT 2

Indexes

Type	Name	On
Pk	pk_individualapartmentdetails	individualapartmentid, mainapartmentid, srocode

Table integrationdepartment

Idx	Name	Data Type
* Pk	udeptid	integer
	departmentname	varchar(100)
	getdata	boolean
	webserviceaddress	varchar(100)
	registrationarticlesids	varchar(200)
	bookids	varchar(50)
	startdate	timestamp
	status	boolean
	inserteddatetime	timestamp DEFAULT CURRENT_TIMESTAMP
	k1k2_flag	smallint DEFAULT 2
	isactive	boolean DEFAULT true

Indexes

Type	Name	On
Pk	pk_integrationdepartment1	udeptid
	idx_integrationdepartment_udept	udeptid

Table jobs

Idx	Name	Data Type
* Pk	id	bigint DEFAULT nextval('kaveri.jobs_id_seq'::regclass)
* Idx	queue	varchar(255)
*	payload	text
*	attempts	smallint
	reserved_at	integer
*	available_at	integer
*	created_at	integer
	inserteddatetime	timestamp DEFAULT CURRENT_TIMESTAMP

Indexes

Type	Name	On
Pk	jobs_pkey	id
	idx_jobs_queue	queue

Table jslipoldmethodlog

Idx	Name	Data Type
* Pk	refid	integer DEFAULT nextval('kaveri.seq_jslipoldmethodlog_refid'::regclass)
	filename	varchar(500)
	isconfirmationsent	boolean
*	inserteddatetime	timestamp DEFAULT CURRENT_TIMESTAMP
	k1k2_flag	integer DEFAULT 2
	srocode	bigint
	finalregistrationnumbers	text
	filepath	text

Indexes

Type	Name	On
Pk	pk_jslipoldmethodlog_refid	refid

Table jslipstatus

Idx	Name	Data Type
* Pk	filegeneratedid	bigint
	filename	varchar(50)
	filesrnumber	bigint
	filegenerateddate	timestamp
	noofrecords	integer
	noofdocuments	integer
	isreacheddr	boolean
	isreachedsdc	boolean
	documentnumberlist	varchar(2000)
	noofdocregistered	integer
	talukacode	varchar(4)
	additionaldocuments	varchar(2000)
	uploadtime	timestamp
*	istransmitted	boolean
	srocode	smallint
	inserteddatetime	timestamp DEFAULT CURRENT_TIMESTAMP
	k1k2_flag	smallint DEFAULT 2

Indexes

Type	Name	On
Pk	pk_jslipstatus	filegeneratedid

Table k1documentdetails

Idx	Name	Data Type
* Pk	applicationnumber	varchar(50)
	finalregistrationnumber	varchar(50)
*	bookid	integer
	stampduty	decimal(18,4)
*	srocode	integer
	registrationdate	timestamp
	inserteddatetime	timestamp DEFAULT CURRENT_TIMESTAMP
	k1k2_flag	smallint DEFAULT 2
	prevregid	varchar(1000)
	prevarticlecode	integer

Indexes

Type	Name	On
Pk	pk_k1documentdetails_appno	applicationnumber

Table k1jslipdata

Idx	Name	Data Type
	finalregistrationnumber	varchar(255)
	actualdata	text
	modifieddata	text
*	inserteddatetime	timestamp DEFAULT CURRENT_TIMESTAMP
	sentxml	text

Table k1pendingdashboard

Idx	Name	Data Type

Table k1pendingdashboard

* Pk	applicationid	bigint
	applicationnumber	varchar(50)
	pendingnumber	varchar(50)
	pendingsrocode	integer
	statuscode	integer
	citizenid	bigint
	inserteddatetime	timestamp DEFAULT CURRENT_TIMESTAMP
	k1k2_flag	smallint DEFAULT 2
	presentationdate	timestamp
	ordernumber	varchar(255)
	drorderfilepathcitizen	varchar(255)
	drorderfilepath	varchar(255)
	sroid	integer
	documentdetails	varchar(1)
	previousstampdetails	varchar(1)
	previousreceiptdetailspaymentdetails	varchar(1)
	indexvillagedetails	varchar(1)
	boundarydetails	varchar(1)
	valuationdetails	varchar(1)
	scheduledescriptions	varchar(1)
	propertynumberdetails	varchar(1)
	partydetails	varchar(1)
	droid	integer
	orderdate	timestamp
	drremarks	text
	addpropertydetails	varchar(1)

Indexes

Type	Name	On
Pk	k1pendingsudashboard_pkey	applicationid

Table k1pendingregistrationdata

Idx	Name	Data Type
* Pk	pendingregid	integer DEFAULT nextval('kaveri.k1pendingregistrationdata_pendingregid'::regclass)
	srocode	integer
	applicationnumber	varchar(100)
	pendingdocumentnumber	varchar(100)
	pendingdocumentdate	date
	k1responsejson	text
	appointmentscheduled	boolean DEFAULT false

Indexes

Type	Name	On
Pk	pk_k1pendingregistrationdata_pendingregid	pendingregid

Table kaveri1documentcorrection

Idx	Name	Data Type
* Pk	orderid	bigint
	ordernumber	varchar(50)
	propertydata	text

Table kaveri1documentcorrection

	inserteddatetime	timestamp DEFAULT CURRENT_TIMESTAMP
	k1k2_flag	integer DEFAULT 2

Indexes

Type	Name	On
Pk	pk_kaveri1documentcorrection_orderid	orderid

Table khatabdaresptable

Idx	Name	Data Type
* Pk	khatareqid	integer
*	khatadetails	text
*	inserteddatetime	timestamp DEFAULT CURRENT_TIMESTAMP

Indexes

Type	Name	On
Pk	khatabdaresptable_pkey	khatareqid

Table khatadrcresptable

Idx	Name	Data Type
	khatareqid	integer
	khatadetails	text
	inserteddatetime	timestamp

Table khatakhbresptable

Idx	Name	Data Type
* Pk	khatareqid	integer
*	khatadetails	text
*	inserteddatetime	timestamp DEFAULT CURRENT_TIMESTAMP

Indexes

Type	Name	On
Pk	khatakhbresptable_pkey	khatareqid

Table latestfunctiondef

Idx	Name	Data Type
	proname	name
	pg_get_functiondef	text

Table lbpasxml

Idx	Name	Data Type
* Pk	logid	bigint
* Pk	srocode	integer
*	documentid	bigint
*	propertyid	bigint
	inputownerdetails	text
	ownerdetails	text
	verified	boolean
	isuploaded	boolean
	acknumber	bigint
	ackxmldetails	text
	isboundaryimported	boolean

Table lbpasxml

	uploaddatetime	timestamp
	sentxmldetails	text
	sentxmlucdetails	text
	inserteddatetime	timestamp DEFAULT CURRENT_TIMESTAMP
	k1k2_flag	smallint DEFAULT 2

Indexes

Type	Name	On
Pk	pk_lbpasxml	logid, srocode

Table leasetypemaster

Idx	Name	Data Type
* Pk	leasetypeid	integer
*	leasetypenamee	varchar(500)
*	leasetypenamek	varchar(500)
*	parentleaserefrence	integer
*	ismarketvalue	boolean
*	ismovable	integer
	inserteddatetime	timestamp DEFAULT CURRENT_TIMESTAMP
	k1k2_flag	smallint DEFAULT 2

Indexes

Type	Name	On
Pk	leasetypemaster_pkey	leasetypeid

Table leavetypemaster

Idx	Name	Data Type
* Pk	leavetypeid	bigint
*	leavetypename	varchar(30)
*	leavetypeabr	varchar(10)
	k1k2_flag	smallint DEFAULT 2

Indexes

Type	Name	On
Pk	leavetypemaster_pkey	leavetypeid

Table lgd_districtmaster

Idx	Name	Data Type
* Pk	districtcode	integer
* Idx	districtnamee	varchar(75)
	districtnamek	varchar(150)
	shortnamee	varchar(5)
	shortnamek	varchar(15)
*	lgdstatecode	integer
	createddate	timestamp DEFAULT CURRENT_TIMESTAMP
	username	varchar(50)
	k1k2_flag	smallint DEFAULT 2

Indexes

Type	Name	On
	idx_lgd_districtmaster_districtnamee	districtnamee
Pk	pk_lgd_districtmaster_distcode	districtcode

Table lgd_eswath_mapping

Idx	Name	Data Type
	statecode	varchar
	statename	varchar
	districtcode	varchar
	districtname	varchar
	blockcode	varchar
	blockname	varchar
	grampanchayatcode	varchar
	grampanchayatname	varchar
	villagecode	varchar
	villagename	varchar
	lgdvillagecode	varchar

Table lgd_mapping_test

Idx	Name	Data Type
	district_code	varchar
	taluka_code	varchar
	hobli_code	varchar
	village_code	varchar
	district_name_kn	varchar
	district_name	varchar
	taluka_name_kn	varchar
	taluka_name	varchar
	hobli_name_kn	varchar
	hobli_name	varchar
	village_name_kn	varchar
	village_name	varchar
	lgddistcode	varchar
	lgdtalukcode	varchar
	lgdvillagecode	integer
	LGD VILLAGE CODE	integer

Table lgd_statemaster

Idx	Name	Data Type
* Pk	statecode	integer
Idx	statenamee	varchar(75)
	statenamek	varchar(150)
	stateorut	varchar(30)
	stateshortnamee	varchar(75)
	stateshortnamek	varchar(150)
	createddate	timestamp DEFAULT CURRENT_TIMESTAMP
	username	varchar(50)
	k1k2_flag	smallint DEFAULT 2

Indexes

Type	Name	On
Pk	lgd_statemaster_pkey	statecode
	idx_lgdstatemaster_srocodesroname	statecode, statenamee

Table lgd_talukmaster

Idx	Name	Data Type
* Pk	talukcode	integer
* Idx	taluknamee	varchar(150)
	taluknamek	varchar(150)
Idx	lgd_districtcode	integer
	lgd_statecode	integer
	createddate	timestamp DEFAULT CURRENT_TIMESTAMP
	username	varchar(50)
	k1k2_flag	smallint DEFAULT 2

Indexes

Type	Name	On
	idx_lgd_talukmaster_taluk	talukcode, taluknamee
Pk	pk_lgd_talukmaster	talukcode
	idx_lgd_talukmaster_district	lgd_districtcode

Table lgd_test

Idx	Name	Data Type
	village_name	varchar
	lgddistcode	text
	lgdtalukcode	text
	lgd_village_code	text

Table lgd_villagemaster

Idx	Name	Data Type
* Pk	villagecode	bigint
	villagenamek	varchar(500)
	villagenamee	varchar(500)
	statecode	integer
	districtcode	integer
	talukcode	integer
	createddate	timestamp DEFAULT CURRENT_TIMESTAMP
	username	varchar(50)
	k1k2_flag	smallint DEFAULT 2

Indexes

Type	Name	On
Pk	pk_lgd_villagemaster	villagecode

Table liabilitydetails

Idx	Name	Data Type
* Pk	liabilityid	bigint
*	entrydate	timestamp
*	issuedate	timestamp
*	issuedby	varchar(50)
*	amount	decimal
*	ordernumber	varchar(50)
*	liabilitynote	varchar
*	srocode	integer
*	userid	integer

Table liabilitydetails

	drocode	integer
	inserteddatetime	timestamp DEFAULT CURRENT_TIMESTAMP
	k1k2_flag	smallint DEFAULT 2
	isdeleted	boolean DEFAULT false
	liabilityfromdate	timestamp
	liabilityadditionalnote	varchar(500)

Indexes

Type	Name	On
Pk	pk_documentliabilitydetails_1	liabilityid

Table liabilitydetails_new

Idx	Name	Data Type
*	liabilityid	bigint DEFAULT nextval('kaveri.liabilitydetails_new_seq'::regclass)
	finalregistrationnumber	varchar(50)
Idx	propertyid	bigint
	orderdate	timestamp
	ordernumber	varchar(1000)
	issuedby	varchar(50)
	liabilityamount	decimal
	liabilitynote	varchar
	srocode	integer
	userid	integer
	drocode	integer
	iscleared	boolean
	clearedby	varchar(50)
	cleardate	timestamp
	clearnote	varchar
	inserteddatetime	timestamp DEFAULT CURRENT_TIMESTAMP
	k1k2_flag	smallint DEFAULT 2
	challannumber	varchar(255)
	clearorder	varchar(150)

Indexes

Type	Name	On
	idx_propertyind	propertyid

Table liabilitynoteadditionaldetails

Idx	Name	Data Type
* Pk	liabilityid	bigint
*	additionalliabilitynote	varchar(500)
*	entrydate	timestamp
*	userid	integer
	inserteddatetime	timestamp DEFAULT CURRENT_TIMESTAMP
	k1k2_flag	smallint DEFAULT 2

Indexes

Type	Name	On
Pk	pk_liabilitynoteadditionaldetails	liabilityid

Table liabilityonpropertydetails

Idx	Name	Data Type
* Pk	mappingid	bigint
* Pk	srocode1	integer
* Idx	liabilityid	bigint
* Idx	documentid	bigint
* Pk	propertyid	bigint
*	srocode	integer
	ordernumber	varchar(50)
	orderissuedate	timestamp
	note	varchar(1000)
	amount	decimal(23,4)
	inserteddatetime	timestamp DEFAULT CURRENT_TIMESTAMP
	k1k2_flag	smallint DEFAULT 2

Indexes

Type	Name	On
	liabilityonpropertydetails_propertyid_idx	propertyid
	liabilityonpropertydetails_liabilityid_idx	liabilityid
Pk	pk_liabilitypropertymapping	mappingid, srocode1, propertyid
	idx_liabilityonpropertydetails_documentid	documentid

Table liabilitypropertymapped

Idx	Name	Data Type
* Pk	mappedid	bigint
*	liabilityid	bigint
*	documentid	bigint
*	propertyid	bigint
*	ispropertysearched	boolean
*	srocode	integer
	inserteddatetime	timestamp DEFAULT CURRENT_TIMESTAMP
	k1k2_flag	smallint DEFAULT 2

Indexes

Type	Name	On
Pk	pk_liabilitypropertymapped	mappedid

Table loanpurposesmaster

Idx	Name	Data Type
* Pk	loanpurposeid	smallint
*	description	varchar(200)
	descriptionr	varchar(200)
*	isactive	boolean
	inserteddatetime	timestamp DEFAULT CURRENT_TIMESTAMP
	k1k2_flag	smallint DEFAULT 2

Indexes

Type	Name	On
Pk	pk_loanpurposemaster	loanpurposeid

Table mainapartmentdetails

Idx	Name	Data Type

Table mainapartmentdetails

* Pk	mainapartmentid	bigint
* Pk	srocode	integer
	documentid	bigint
	finalregistrationnumber	varchar(50)
*	mainapartmentname	varchar(150)
*	buildername	varchar(150)
	partyid	bigint
*	totalindividualapartments	integer
*	villagecode	bigint
*	eastboundary	varchar(500)
*	westboundary	varchar(500)
*	northboundary	varchar(500)
*	southboundary	varchar(500)
*	streetorroadno	varchar(50)
*	streetorroadname	varchar(150)
*	totalarea	decimal(18,0)
*	unitid	integer
*	townname	varchar(150)
	peth	varchar(150)
	divisionofland	varchar(50)
*	survery_no	integer
*	surnoc_no	varchar(20)
*	hissa_no	varchar(30)
*	isolddeclaration	boolean
	inserteddatetime	timestamp DEFAULT CURRENT_TIMESTAMP
	k1k2_flag	smallint DEFAULT 2

Indexes

Type	Name	On
Pk	pk_mainapartmentdetails	mainapartmentid, srocode

Table mandatorysupportdocuments

Idx	Name	Data Type
* Pk	supportmapid	integer
*	regarticlecode	integer
*	supportdocid	integer
*	isactive	boolean
*	ispartysd	boolean
*	isdocumentsd	boolean
*	isoptional	boolean
	k1k2_flag	smallint DEFAULT 2

Indexes

Type	Name	On
Pk	pk_mandatorysupportdocuments	supportmapid

Table mas_alm_frm_sendmessageconfiguration

Idx	Name	Data Type
* Pk	id	integer
	messagetriggertypeid	integer

Table mas_alm_frm_sendmessageconfiguration

	firmpartner	boolean
	witnesses	boolean
	userid	boolean
	inserteddatetime	timestamp DEFAULT CURRENT_TIMESTAMP
	k1k2_flag	smallint DEFAULT 2

Indexes

Type	Name	On
Pk	pk_mas_alm_frm_sendmessageconfiguration	id

Table mas_ams_accountheads

Idx	Name	Data Type
* Pk	deptpurposeid	smallint
* Idx	serviceid	smallint
	name	varchar(100)
	namer	varchar(100)
Idx	headofaccount	varchar(50)
	treasurynumber	varchar(50)
*	isactive	boolean
	issubpurposeexist	boolean
	subrefcode	varchar(5)
	k1k2_flag	smallint DEFAULT 2

Indexes

Type	Name	On
Pk	pk_deptpurposeid_mas_ams_accountheads	deptpurposeid
	idx_mas_ams_accountheads_head	headofaccount
	idx_mas_ams_accountheads_ser	serviceid

Table mas_ams_accountheadsfeetypesmapping

Idx	Name	Data Type
*	mappingid	smallint
* Idx	deptpurposeid	smallint
* Idx	feeruleid	integer
*	serviceid	smallint
* Idx	isactive	boolean
* Pk	id	bigint DEFAULT nextval('kaveri.mas_ams_accountheadsfeetypesmapping_id_seq'::regclass)
	k1k2_flag	smallint DEFAULT 2

Indexes

Type	Name	On
	idx_mas_ams_accountheadsfeetypesmapping_fee	feeruleid
	idx_mas_ams_accountheadsfeetypesmapping_isact	isactive
Pk	mas_ams_accountheadsfeetypesmapping_pkey	id
	idx_mas_ams_accountheadsfeetypesmapping_dept	deptpurposeid

Table mas_ams_khajaneddocodemapping

Idx	Name	Data Type
	mappingid	integer
	srocode	integer

Table mas_ams_khajaneddocodemapping

	officeid	smallint
	ddocode	varchar(15)

Table mas_ams_khajaneddocodemapping_docdb

Idx	Name	Data Type
	mappingid	integer
	srocode	integer
	officeid	smallint
	ddocode	varchar(15)

Table mas_ctitizenecccfee

Idx	Name	Data Type
* Pk	feeid	integer
	applicationfee	decimal(18,0)
	stampdutyfee	decimal(18,0)
	singlesearchfee	decimal(18,0)
*	feeperpage	decimal(18,0)
	moduleid	smallint
	multiplesearchfee	decimal(18,0)
	inserteddatetime	timestamp DEFAULT CURRENT_TIMESTAMP
	k1k2_flag	smallint DEFAULT 2
Indexes		
Type	Name	On
Pk	pk_mas_ctitizenecccfee	feeid

Table mas_districts

Idx	Name	Data Type
* Pk	districtid	smallint
*	stateid	smallint
*	districtname	varchar(45)
	districtnamer	text
	shortname	varchar(5)
	shortnamer	text
	censuscode	varchar(20)
	isrevenuedistrict	boolean
Idx	kavericode	smallint
	testdate	timestamp
	testdatetime	timestamp
	k1k2_flag	smallint DEFAULT 2
	inserteddatetime	timestamp DEFAULT CURRENT_TIMESTAMP
Indexes		
Type	Name	On
	idx_masdistrict	kavericode
	idx_masdistrict_kavericode	kavericode
Pk	pk_mas_districts	districtid

Table mas_feerules

Idx	Name	Data Type

Table mas_feerules

* Pk	feeruleid	smallint
* Pk	serviceid	smallint
*	description	varchar(500)
*	descriptionr	varchar(500)
*	value	decimal(18,4)
*	isactive	boolean
	displayseqid	integer
	referotherrule	boolean
	additionalvalue	decimal(18,4)
	kaveri1feerulecode	smallint

Indexes

Type	Name	On
Pk	pk_mas_feerules1	feeruleid, serviceid

Table mas_feerules_kaveri1

Idx	Name	Data Type
* Pk	feeruleid	smallint
* Pk	serviceid	smallint
*	description	varchar(500)
*	descriptionr	varchar(500)
*	value	money
*	isactive	smallint
	displayseqid	integer
	referotherrule	smallint
	additionalvalue	money
	kaveri1feerulecode	smallint

Indexes

Type	Name	On
Pk	pk_mas_feerules	feeruleid, serviceid

Table mas_frm_amendmenttypes

Idx	Name	Data Type
* Pk	amendmenttypeid	smallint
*	description	varchar(100)
*	descriptionr	varchar(100)
*	isactive	boolean
	parentid	smallint
	childid	smallint
	inserteddatetime	timestamp DEFAULT CURRENT_TIMESTAMP
	k1k2_flag	smallint DEFAULT 2

Indexes

Type	Name	On
Pk	pk_mas_frm_amendmenttypes	amendmenttypeid

Table mas_frm_applicationtypes

Idx	Name	Data Type
* Pk	applicationtypeid	smallint
*	description	varchar(150)

Table mas_frm_applicationtypes

	descriptionr	varchar(150)
*	isactive	boolean
	inserteddatetime	timestamp DEFAULT CURRENT_TIMESTAMP
	k1k2_flag	smallint DEFAULT 2

Indexes

Type	Name	On
Pk	pk_mas_frm_applicationtypes	applicationtypeid

Table mas_frm_checksliptypeamendmenttypemapping

Idx	Name	Data Type
* Pk	checksliptypeid	smallint
*	amendmenttypeid	smallint
	inserteddatetime	timestamp DEFAULT CURRENT_TIMESTAMP
	k1k2_flag	smallint DEFAULT 2

Indexes

Type	Name	On
Pk	pk_checksliptypeamendmenttypemapping_1	checksliptypeid

Table mas_frm_checksliptypes

Idx	Name	Data Type
* Pk	checksliptypeid	smallint
	description	varchar(2000)
	descriptionr	varchar(2000)
	applicationtypeid	smallint
	inserteddatetime	timestamp DEFAULT CURRENT_TIMESTAMP
	k1k2_flag	smallint DEFAULT 2

Indexes

Type	Name	On
Pk	pk_mas_frm_checksliptypes	checksliptypeid

Table mas_frm_firmbusinesstypes

Idx	Name	Data Type
* Pk	firmbusinesstypeid	smallint
*	description	varchar(300)
	descriptionr	varchar(300)
*	isactive	boolean
	inserteddatetime	timestamp DEFAULT CURRENT_TIMESTAMP
	k1k2_flag	smallint DEFAULT 2

Indexes

Type	Name	On
Pk	pk_mas_frm_businesstype	firmbusinesstypeid

Table mas_frm_firmdissolutiontypes

Idx	Name	Data Type
* Pk	dissolutiontypeid	smallint
*	description	varchar(150)
	descriptionr	varchar(150)
*	isactive	boolean

Table mas_frm_firmdissolutiontypes

	inserteddatetime	timestamp DEFAULT CURRENT_TIMESTAMP
	k1k2_flag	smallint DEFAULT 2

Indexes

Type	Name	On
Pk	pk_mas_frm_firmdissolutiontypes	dissolutiontypeid

Table mas_frm_firmmemberdesignations

Idx	Name	Data Type
* Pk	firmdesignationid	smallint
*	description	varchar(150)
	descriptionr	varchar(150)
*	isgoverningmember	boolean
*	isactive	boolean
	inserteddatetime	timestamp DEFAULT CURRENT_TIMESTAMP
	k1k2_flag	smallint DEFAULT 2

Indexes

Type	Name	On
Pk	pk_mas_frm_firmmemberdesignations	firmdesignationid

Table mas_frm_firmnatures

Idx	Name	Data Type
* Pk	firmnatureid	smallint
*	description	varchar(150)
	descriptionr	varchar(150)
*	isactive	boolean
	inserteddatetime	timestamp DEFAULT CURRENT_TIMESTAMP
	k1k2_flag	smallint DEFAULT 2

Indexes

Type	Name	On
Pk	pk_mas_frm_firmnatures	firmnatureid

Table mas_frm_presentertypes

Idx	Name	Data Type
* Pk	presentertypeid	smallint
*	description	varchar(100)
*	descriptionr	varchar(100)
*	isactive	boolean
	inserteddatetime	timestamp DEFAULT CURRENT_TIMESTAMP
	k1k2_flag	smallint DEFAULT 2

Indexes

Type	Name	On
Pk	pk_mas_frm_presentertpes	presentertypeid

Table mas_frm_refusalreasons

Idx	Name	Data Type
* Pk	reasonid	smallint
*	reason	varchar(400)
	reasonr	varchar(400)

Table mas_frm_refusalreasons

	applicationtypeid	smallint
	inserteddatetime	timestamp DEFAULT CURRENT_TIMESTAMP
	k1k2_flag	smallint DEFAULT 2

Indexes

Type	Name	On
Pk	pk_mas_frm_refusalreasons	reasonid

Table mas_frm_stamparticles

Idx	Name	Data Type
* Pk	stamparticleid	smallint
*	articlename	varchar(200)
	articlenamer	varchar(200)
*	stampactnumber	varchar(50)
*	isactive	boolean
	inserteddatetime	timestamp DEFAULT CURRENT_TIMESTAMP
	k1k2_flag	smallint DEFAULT 2

Indexes

Type	Name	On
Pk	pk_mas_frm_stamparticles	stamparticleid

Table mas_frm_stampcalculationvaluetypes

Idx	Name	Data Type
* Pk	stampcalculationvaluetypeid	smallint
*	description	varchar(100)
	descriptionr	varchar(200)
	displayname	varchar(200)
	displaynamer	varchar(300)
*	isactive	boolean
*	isexternalunit	boolean
	inserteddatetime	timestamp DEFAULT CURRENT_TIMESTAMP
	k1k2_flag	smallint DEFAULT 2

Indexes

Type	Name	On
Pk	pk_mas_frm_stampcalculationvaluetypes	stampcalculationvaluetypeid

Table mas_frm_stamprules

Idx	Name	Data Type
* Pk	stampruleid	integer
*	stampactarticleno	varchar(20)
*	description	varchar(1000)
	descriptionr	varchar(1000)
	displayname	varchar(100)
	displaynamer	varchar(500)
	valuationrequired	boolean
	considerationrequired	boolean
	propertyrequired	boolean
	sharerequired	boolean
	calculationtypeid	smallint

Table mas_frm_stamprules

	isslabs	boolean
	ispercentage	boolean
	isfixed	boolean
	unit	decimal(18,2)
	value	decimal(18,2)
	minlimit	decimal(18,2)
	maxlimit	decimal(18,2)
	plusthisamount	decimal(18,2)
*	stamparticleid	smallint
	considcalculatorreq	boolean
	inserteddatetime	timestamp DEFAULT CURRENT_TIMESTAMP
	k1k2_flag	smallint DEFAULT 2

Indexes

Type	Name	On
Pk	pk_mas_frm_stamprules_1	stampruleid

Table mas_frm_supportdocuments

Idx	Name	Data Type
* Pk	supportdocumentid	smallint
*	description	varchar(100)
*	descriptionr	varchar(100)
*	applicationtypeid	smallint
*	isoptional	boolean
*	isactive	boolean
	inserteddatetime	timestamp DEFAULT CURRENT_TIMESTAMP
	k1k2_flag	smallint DEFAULT 2

Indexes

Type	Name	On
Pk	pk_mas_frm_supportdocuments	supportdocumentid

Table mas_idprooftypes

Idx	Name	Data Type
* Pk	idprooftypeid	smallint
*	description	varchar(50)
	descriptionr	varchar(75)
*	isactive	bit(1)
	k1k2_flag	smallint DEFAULT 2

Indexes

Type	Name	On
Pk	mas_idprooftypes_pkey	idprooftypeid

Table mas_marriagebeforestatus

Idx	Name	Data Type
* Pk	statusid	smallint
	description	varchar(50)
	isactive	boolean
	k1k2_flag	smallint

Indexes

Table mas_marriagebeforestatus

Type	Name	On
Pk	pk_mas_marriagebeforestatus	statusid

Table mas_marriagemode

Idx	Name	Data Type
* Pk	marriagemodeid	integer
* Unq	marriagemode	varchar(50)
Unq	inserteddatetime	timestamp DEFAULT CURRENT_TIMESTAMP
Unq	k1k2_flag	smallint DEFAULT 2

Indexes

Type	Name	On
Pk	pk_mas_marriagemode	marriagemodeid
Unq	marriagetype_marriagemodeid_idx	marriagemodeid, marriagemode, inserteddatetime, k1k2_flag

Table mas_marriagetype

Idx	Name	Data Type
* Pk	marriagetypeid	integer
*	marriagetype	varchar(50)
*	presentmaxvalue	integer
*	marriageregfees	integer
	inserteddatetime	timestamp DEFAULT CURRENT_TIMESTAMP
	k1k2_flag	smallint DEFAULT 2
	shortnamee	varchar(5)

Indexes

Type	Name	On
Pk	pk_marriagetype_mas_marriagetype	marriagetypeid

Table mas_officemaster

Idx	Name	Data Type
* Pk	officeid	smallserial
	officetypeid	smallint
	officename	varchar(150)
	officenamer	varchar(150)
	shortname	varchar(5)
	shortnamer	varchar(50)
	districtid	smallint
	parentofficeid	smallint
Idx	kavericode	smallint
	bhoomicensuscode	smallint
	anywhereregenabled	integer
	officeaddress	varchar(1000)
	landline	varchar(11)
	mobile	varchar(10)
	onlinebookingenabled	integer
	pincode	integer
	govt_order_filepath	text
	ddocode	varchar(20)
	isactive	boolean DEFAULT true

Table mas_officemaster

	inserteddatetime	timestamp DEFAULT CURRENT_TIMESTAMP
	createdby	bigint

Indexes

Type	Name	On
	mas_officemaster_kavericode_idx	kavericode
Pk	pk_mas_officemaster_offceid	officeid
Unq	uk_mas_officemaster	officeid

Table mas_officemaster_docdb

Idx	Name	Data Type
	officeid	smallint
	officetypeid	smallint
	officename	varchar(150)
	officenamer	varchar(150)
	shortname	varchar(5)
	shortnamer	varchar(50)
	districtid	smallint
	parentofficeid	smallint
	kavericode	smallint
	bhoomicensuscode	smallint
	anywhereregenabled	integer
	officeaddress	varchar(1000)
	landline	varchar(11)
	mobile	varchar(10)
	onlinebookingenabled	integer
	pincode	integer
	govt_order_filepath	text
	ddocode	varchar(20)
	isactive	boolean
	inserteddatetime	timestamp
	createdby	bigint

Table mas_officetimings

Idx	Name	Data Type
*	officetimingid	smallint
* Pk	officeid	smallint
*	officeopentime	time
*	officeclosetime	time
	dayid	smallint
	day	varchar(9)
	date	timestamp(26)
*	isdatewise	boolean
*	userid	bigint
*	resourceid	integer
*	isactive	boolean
	inserteddatetime	timestamp DEFAULT CURRENT_TIMESTAMP
	k1k2_flag	smallint DEFAULT 2

Indexes

Table mas_officetimings

Type	Name	On
Pk	pk_mas_officetimings	officeid

Table mas_officetypes

Idx	Name	Data Type
* Pk	officetypeid	smallserial
	officetypedesc	text
	officetypedescr	text
	shortname	text
	shortnamer	text
	k1k2_flag	smallint DEFAULT 2
	officetype	text
	inserteddatetime	timestamp DEFAULT CURRENT_TIMESTAMP
	createdby	bigint

Indexes

Type	Name	On
Pk	pk_mas_officetypes	officetypeid

Table mas_persontype

Idx	Name	Data Type
* Pk	persontypeid	smallserial
*	persontypename	varchar(50)
	inserteddatetime	timestamp DEFAULT CURRENT_TIMESTAMP
	k1k2_flag	smallint DEFAULT 2

Indexes

Type	Name	On
Pk	pk_persontypeid	persontypeid

Table mas_prooftypes

Idx	Name	Data Type
* Pk	prooftypeid	smallint
	prooftype	varchar(50)
	isactive	boolean
	k1k2_flag	smallint

Indexes

Type	Name	On
Pk	pk_prooftypeid	prooftypeid

Table mas_prooftypes_idproof_mapping

Idx	Name	Data Type
*	prooftypeid	smallint
*	idprooftypeid	smallint
	isactive	boolean
	k1k2_flag	smallint

Table mas_registration

Idx	Name	Data Type
* Pk	registrationfee_id	integer

Table mas_registration

	government_circular_no	varchar(300)
	subject	varchar(1000)
	exemption	varchar(200)
	inserteddatetime	timestamp DEFAULT CURRENT_TIMESTAMP
	k1k2_flag	smallint DEFAULT 2

Indexes

Type	Name	On
Pk	pk_mas_registration	registrationfee_id

Table mas_servicemaster

Idx	Name	Data Type
* Pk	serviceid	smallint
	servicename	varchar(300)
	servicenamer	varchar(500)
*	serviceopentime	time
*	serviceclosetime	time
*	isactive	boolean
*	isonline	boolean
	triletter	varchar(10)

Indexes

Type	Name	On
Pk	mas_servicemaster_serviceid	serviceid

Table mas_val_agrilandtypes

Idx	Name	Data Type
* Pk	agrilandtypeid	smallint
	description	varchar(200)
	descriptionr	varchar(200)
	k1k2_flag	smallint DEFAULT 2

Indexes

Type	Name	On
Pk	pk_mas_val_agrilandtypes	agrilandtypeid

Table mas_val_annexurecalculationrules

Idx	Name	Data Type
* Pk	annexureid	smallint
* Pk	displayrulefor	integer
	calculateon	integer
	inserteddatetime	timestamp DEFAULT CURRENT_TIMESTAMP
	k1k2_flag	smallint DEFAULT 2

Indexes

Type	Name	On
Pk	pk_anxrulid_rulefor_mas_val_anexcalculatrules	annexureid, displayrulefor
	idx_mas_val_annexurecalculationrules_annexureid	annexureid, displayrulefor

Table mas_val_annexurerules

Idx	Name	Data Type
* Pk	annexureid	smallint

Table mas_val_annexurerules

*	description	varchar(100)
*	descriptionr	varchar(100)
*	percentage	decimal(15,2)
*	isadditional	boolean
*	onunit	boolean
	group	char(1)
	areastart	decimal(3,1)
	areaend	decimal(3,1)
	inserteddatetime	timestamp DEFAULT CURRENT_TIMESTAMP
	k1k2_flag	smallint DEFAULT 2

Indexes

Type	Name	On
Pk	pk_annexurerules	annexureid
	idx_masvalannexurerules_annexureid	annexureid

Table mas_val_apartmentfloorrates

Idx	Name	Data Type
* Pk	apartmentfloorrateid	smallint
*	floorfrom	smallint
*	floorto	smallint
*	unit	decimal(12,0)
*	value	decimal
*	isfixedduty	boolean
*	ispercentage	boolean
	inserteddatetime	timestamp DEFAULT CURRENT_TIMESTAMP
	k1k2_flag	smallint DEFAULT 2

Indexes

Type	Name	On
Pk	pk_mas_val_apartmentfloorrates	apartmentfloorrateid

Table mas_val_apartmentsamenities

Idx	Name	Data Type
* Pk	amenitiesid	integer DEFAULT nextval('kaveri.mas_val_apartmentsamenities_amenitiesid_seq'::regclass)
	namewithamenities	varchar(200)
	namewithamenitiesr	varchar(200)
	isactive	boolean DEFAULT false
	effectivedate	timestamp
	k1k2_flag	smallint DEFAULT 2
	inserteddatetime	timestamp DEFAULT CURRENT_TIMESTAMP

Indexes

Type	Name	On
Pk	pk_mas_val_apartments	amenitiesid

Table mas_val_apartmentspecialameneties

Idx	Name	Data Type
* Pk	apartmentamenityid	smallint
*	description	varchar(400)

Table mas_val_apartmentspecialameneties

*	descriptionr	varchar(400)
*	isactive	boolean
	inserteddatetime	timestamp DEFAULT CURRENT_TIMESTAMP
	k1k2_flag	smallint DEFAULT 2

Indexes

Type	Name	On
Pk	pk_mas_val_apartmentameneties	apartmentamenityid

Table mas_val_apartmentspecialamenetyrules

Idx	Name	Data Type
* Pk	apartmentamenetyruleid	smallint
*	totalamenities	smallint
*	unit	decimal(12,0)
*	value	decimal
*	isfixed	boolean
*	ispercentage	boolean
	inserteddatetime	timestamp DEFAULT CURRENT_TIMESTAMP
	k1k2_flag	smallint DEFAULT 2

Indexes

Type	Name	On
Pk	pk_mas_val_apartmentamenetyrules	apartmentamenetyruleid

Table mas_val_buildingfloors

Idx	Name	Data Type
* Pk	floorid	smallint
	description	varchar(200)
	descriptionr	varchar(200)
	k1k2_flag	smallint DEFAULT 2

Indexes

Type	Name	On
Pk	pk_mas_val_buildingfloors	floorid

Table mas_val_constructionrates

Idx	Name	Data Type
* Pk	constructionrateid	bigint
* Idx	villageid	bigint
*	constructiontypeid	smallint
* Idx	floorid	smallint
	unitid	integer
*	rate	decimal(15,2)
	k1k2_flag	smallint DEFAULT 2

Indexes

Type	Name	On
	idx_mas_val_constructionrates_villageid	villageid
	idx_mas_val_constructionrates_floorid	floorid
	idx_mas_val_constructionrates	floorid, villageid
Pk	pk_mas_val_constructionrates	constructionrateid

Table mas_val_constructiontypes

Idx	Name	Data Type
* Pk	constructiontypeid	smallint
	description	varchar(200)
	descriptionr	varchar(200)
	isactive	boolean
	groundfloorrate	bigint
	abovefloorrate	bigint
	defaultrates	decimal(18,5)
	measurementcode	smallint
	k1k2_flag	smallint DEFAULT 2

Indexes

Type	Name	On
Pk	pk_mas_val_constructiontypes	constructiontypeid

Table mas_val_flatrates

Idx	Name	Data Type
*	floorid	smallint DEFAULT 1
*	propertytypeid	integer
	unitid	integer
*	rate	decimal(15,2)
	roadid	bigint
	amenitiesid	integer
	effectivedate	timestamp
* Pk	flaterateid	bigint DEFAULT nextval('kaveri.mas_val_flatrates_flaterateid_seq'::regclass)
	apartmentnamewithamenitiese	varchar(500)
	apartmentnamewithamenitiesk	varchar(500)
	propertydescid	smallint
	k1k2_flag	smallint DEFAULT 2
	inserteddatetime	timestamp DEFAULT CURRENT_TIMESTAMP

Indexes

Type	Name	On
Pk	mas_val_flatrates_pkey	flaterateid

Table mas_val_openbuiltrates

Idx	Name	Data Type
* Pk	openbuiltrateid	bigint
	roadid	bigint
*	propertytypeid	integer
	unitid	integer
*	rate	decimal(15,2)
	k1k2_flag	smallint DEFAULT 2

Indexes

Type	Name	On
Pk	pk_mas_val_openbuiltrates	openbuiltrateid

Table mas_val_parkingrates

Idx	Name	Data Type

Table mas_val_parkingrates

* Pk	parkingrateid	smallint
*	parkingtypeid	smallint
*	propvaluefrom	decimal
*	propvalueto	decimal
*	unit	decimal(12,3)
*	value	decimal
*	isfixed	boolean
*	ispercentage	boolean
	k1k2_flag	smallint DEFAULT 2

Indexes

Type	Name	On
Pk	pk_mas_val_parkingrates	parkingrateid

Table mas_val_parkingtypes

Idx	Name	Data Type
* Pk	parkingtypeid	smallint
*	description	varchar(50)
*	descriptionr	varchar(100)
*	isactive	boolean
	k1k2_flag	smallint DEFAULT 2

Indexes

Type	Name	On
Pk	pk_mas_val_parkingtypes	parkingtypeid

Table mas_val_readyreckoner_flats

Idx	Name	Data Type
	rangeid	integer
	vctratefrom	integer
	vctrateto	integer
	flatrate	integer

Table mas_valratedetail

Idx	Name	Data Type
* Pk	valratedetailid	bigint DEFAULT nextval('kaveri.mas_valratedetail_valratedeailid_seq'::regclass)
	valrateheaderid	bigint
Idx	roadcode	bigint
	srocode	bigint
* Idx	propertytypeid	integer
Idx	agrilandtypeid	smallint
	floorid	smallint
	amenitiesid	integer
	unitid	integer
*	rate	decimal(36,2)
	effectivedate	timestamp
	active	boolean
Idx	sfdaid	bigint
	isapproved	boolean

Table mas_valratedetail

	updateddate	timestamp DEFAULT now()
	updatedby	varchar(10)
	remarks	text
	inserteddatetime	timestamp DEFAULT CURRENT_TIMESTAMP
	k1k2_flag	smallint DEFAULT 2

Indexes

Type	Name	On
	idx_mas_valratedetail_agrilandtypeid	agrilandtypeid
	idx_mas_valratedetail_roadcode	roadcode
	idx_mas_valratedetail_sfdaid	sfdaid
	idx_mas_valratedetail_propertytypeid	propertytypeid
Pk	mas_valratedetail_pkey	valratedetailid

Table mas_valratedetail_prod

Idx	Name	Data Type
	valratedetailid	bigint
	valrateheaderid	bigint
	roadcode	bigint
	srocode	bigint
	propertytypeid	integer
	agrilandtypeid	smallint
	floorid	smallint
	amenitiesid	integer
	unitid	integer
	rate	decimal(36,2)
	effectivedate	timestamp
	active	boolean
	sfdaid	bigint
	isapproved	boolean
	updateddate	timestamp
	updatedby	varchar(10)
	remarks	text
	inserteddatetime	timestamp
	k1k2_flag	smallint

Table mas_valrateheader

Idx	Name	Data Type
* Pk	valrateheaderid	bigint DEFAULT nextval('kaveri.mas_valrateheader_valrateheaderid_seq'::regclass)
Idx	srocode	bigint
	effectivedate	timestamp
	active	boolean
Idx	sfdaid	bigint
	isapproved	boolean
	circularpath	text
	circularinfo	text
	updateddate	timestamp DEFAULT now()
	updatedby	varchar(10)

Table mas_valrateheader

	requestdate	timestamp
	inserteddatetime	timestamp DEFAULT CURRENT_TIMESTAMP
	k1k2_flag	smallint DEFAULT 2
	circularyear	integer

Indexes

Type	Name	On
	idx_mas_valrateheader_sfdaid	sfdaid
	idx_mas_valrateheader_srocode	srocode
Pk	mas_valrateheader_pkey	valrateheaderid

Table mas_valuationrates

Idx	Name	Data Type
* Pk	valratedetailid	bigint DEFAULT nextval('kaveri.mas_valuationrates_valratedetailid_seq'::regclass)
Idx	valrateheaderid	bigint
Idx	roadcode	bigint
Idx	srocode	bigint
*	propertytypeid	integer
	agrilandtypeid	smallint
	floorid	smallint
Idx	amenitiesid	integer
	unitid	integer
*	rate	decimal(36,2)
Idx	effectivedate	timestamp
	active	boolean
Idx	sfdaid	bigint
	isapproved	boolean
	updateddate	timestamp DEFAULT now()
	updatedby	varchar(10)
	inserteddatetime	timestamp DEFAULT CURRENT_TIMESTAMP
	k1k2_flag	smallint DEFAULT 2

Indexes

Type	Name	On
	idx_mas_valuationrates_valrateheaderid	valrateheaderid
	idx_mas_valuationrates_sfdaid	sfdaid
	idx_mas_valuationrates_effectivedate	effectivedate
	idx_mas_valuationrates_amenitiesid	amenitiesid
	idx_mas_valuationrates_srocode	srocode
	idx_mas_valuationrates_roadcode	roadcode
Pk	mas_valuationrates_pkey	valratedetailid

Table mas_valuationrates_prod

Idx	Name	Data Type
	valratedetailid	bigint
	valrateheaderid	bigint
	roadcode	bigint
	srocode	bigint
	propertytypeid	integer
	agrilandtypeid	smallint

Table mas_valuationrates_prod

	floorid	smallint
	amenitiesid	integer
	unitid	integer
	rate	decimal(36,2)
	effectivedate	timestamp
	active	boolean
	sfdaid	bigint
	isapproved	boolean
	updateddate	timestamp
	updatedby	varchar(10)
	inserteddatetime	timestamp
	k1k2_flag	smallint

Table measunitmaster

Idx	Name	Data Type
* Pk	unitid	integer
*	descriptionkannada	varchar(50)
*	descriptionenglish	varchar(50)
	inserteddatetime	timestamp DEFAULT CURRENT_TIMESTAMP
	k1k2_flag	smallint DEFAULT 2

Indexes

Type	Name	On
Pk	pk_measunitmaster	unitid

Table measurementmaster

Idx	Name	Data Type
* Pk	measurementcode	integer
*	measurementnamee	varchar(25)
*	measurementnamek	varchar(50)
*	measurementshorte	varchar(25)
*	measurementshortk	varchar(50)
	inserteddatetime	timestamp DEFAULT CURRENT_TIMESTAMP
	k1k2_flag	smallint DEFAULT 2

Indexes

Type	Name	On
Pk	pk_measurementmaster	measurementcode

Table minutebook

Idx	Name	Data Type
* Pk	docid	integer
	documentid	bigint
	registrationno	varchar(50)
*	remarks	char(500)
*	issystem	boolean
*	minutedate	timestamp
	isclosed	boolean
	closuredate	timestamp
* Pk	srocode	integer

Table minutebook

*	details	char(2400)
	k1k2_flag	smallint DEFAULT 2
	inserteddatetime	timestamp DEFAULT CURRENT_TIMESTAMP

Indexes

Type	Name	On
Pk	pk_minutebook	docid, srocode

Table minutebook_data

Idx	Name	Data Type
Idx	docid	bigint
Idx	applicationnumber	varchar(50)
	remarks	varchar(500)
	issystem	boolean
	minutedate	timestamp DEFAULT CURRENT_TIMESTAMP
Idx	srocode	integer
Idx	reasonid	bigint
	remark_comment	text
	inserteddatetime	timestamp DEFAULT CURRENT_TIMESTAMP
	k1k2_flag	smallint DEFAULT 2
	private_remark	text
	dr_order_number	varchar
	dr_order_filepath	varchar
	ispendingdocument	boolean DEFAULT false
	pendingregistrationnumber	text
	isbefore2003	boolean
	depositionstatmentpath	varchar

Indexes

Type	Name	On
	idx_minutebook_data_districtcode	docid
	idx_minutebook_data_srocode_ccnew	srocode
	idx_minutebook_data_reasonid_ccnew	reasonid
	minutebook_data_applicationnumber_idx_ccnew	applicationnumber
	idx_minutebook_data_srocode_ccnew1	srocode
	minutebook_data_applicationnumber_idx_ccnew1	applicationnumber
	idx_minutebook_data_reasonid_ccnew1	reasonid
	idx_minutebook_data_reasonid	reasonid
	idx_minutebook_data_srocode	srocode
	minutebook_data_applicationnumber_idx	applicationnumber

Table modulemaster

Idx	Name	Data Type
* Pk	moduleid	integer DEFAULT nextval('kaveri.moduleid_seq'::regclass)
	modulename	text
	inserteddatetime	timestamp DEFAULT CURRENT_TIMESTAMP
	createdby	integer

Indexes

Type	Name	On
Pk	pk_modulemaster	moduleid

Table modulemaster

	idx_modulemaster_moduleid	moduleid

Table mojanixml

Idx	Name	Data Type
* Pk	logid	bigint
* Pk	srocode	integer
	documentid	bigint
* Idx	propertyid	bigint
	inputsketchdetails	varchar(50)
	receivedxmldetails	text
	receivedencxmldetails	text
	verified	boolean
*	isuploaded	boolean
	uploaddatetime	timestamp
	ackxmldetails	text
	acknumber	text
	sentxmldetails	text
	isfinalregistration	boolean
	inserteddatetime	timestamp DEFAULT CURRENT_TIMESTAMP
	k1k2_flag	smallint DEFAULT 2

Indexes

Type	Name	On
Pk	pk_mojanixml	logid, srocode
	idx_mojanixml_propertyid	propertyid

Table mrg_requiredfees

Idx	Name	Data Type
* Pk	requiredfeeid	bigint
	mrgregistrationid	bigint
	feeruleid	integer
	payableamount	decimal(18,0)
*	ispaid	boolean
	serviceid	integer
	feedescription	varchar(500)
	inserteddatetime	timestamp DEFAULT CURRENT_TIMESTAMP
	k1k2_flag	smallint DEFAULT 2
	applicationnumber	varchar(50)
	receiptid	bigint
	amountpaid	decimal(23,4)
	srocode	integer

Indexes

Type	Name	On
Pk	pk_mrg_requiredfees	requiredfeeid

Foreign Keys

Type	Name	On
	fk_mrg_requiredfees_applicantapplicationdetails (applicationnumber) ref applicantapplicationdetails (applicationnumber)	

Table ngdrs_dashboard_data

Idx	Name	Data Type
* Pk	id	integer GENERATED ALWAYS AS IDENTITY
	no_of_sr_office	integer
	no_of_document_registered	bigint
	no_of_document_submitted	bigint
	no_of_appointment_requested	bigint
	no_of_scan_docs	bigint
	no_of_pending_scan	bigint
	revenue_genereated	decimal
*	date	date

Indexes

Type	Name	On
Pk	pk_dashboard_data_id	id

Table noticemaster

Idx	Name	Data Type
* Pk	noticeid	bigint
	noticeno	varchar(25)
*	noticeissueddate	timestamp
*	bride	integer
*	bridegroom	integer
	fees	integer
	remarks	varchar(200)
	marriagetype	integer
	cdnumber	varchar(50)
	srocode	integer
	pages	integer
	isscanned	integer
	dateofmarriage	timestamp
	issolamenised	boolean
*	istransmitted	boolean
	psrocode	integer
	k1k2_flag	smallint DEFAULT 2
	inserteddatetime	timestamp DEFAULT CURRENT_TIMESTAMP

Indexes

Type	Name	On
Pk	pk_noticemaster	noticeid

Table openbuiltratedetail

Idx	Name	Data Type
*	villagecode	bigint
* Idx	roadcode	bigint
* Idx	propertytypeid	integer
*	rate	decimal(18,5)
*	measurementcode	integer
Idx	effectivedate	timestamp
* Pk	openbuildratecode	bigint DEFAULT nextval('kaveri.openbuiltratedetail_openbuildratecode_seq'::regclass)

Table openbuiltratedetail

	k1k2_flag	smallint DEFAULT 2
	inserteddatetime	timestamp DEFAULT CURRENT_TIMESTAMP
	prevrate	decimal(18,5)
	prevrate2	decimal(18,5)

Indexes

Type	Name	On
	idx_openbuiltratedetail_propertytypeid	propertytypeid
	idx_openbuiltratedetail_roadcode	roadcode
	idx_openbuiltratedetail_prop_roadcode	propertytypeid, roadcode, effectivedate
	idx_openbuiltratedetail	roadcode, propertytypeid
Pk	openbuiltratedetail_pkey	openbuildratecode

Table openbuiltratedetail_prod

Idx	Name	Data Type
	villagecode	bigint
	roadcode	bigint
	propertytypeid	integer
	rate	decimal(18,5)
	measurementcode	integer
	effectivedate	timestamp
	openbuildratecode	bigint
	k1k2_flag	smallint
	inserteddatetime	timestamp
	prevrate	decimal(18,5)
	prevrate2	decimal(18,5)

Table orders

Idx	Name	Data Type
* Pk	orderid	integer
*	ordername	varchar
	quantity	integer
	inserteddatetime	timestamp DEFAULT CURRENT_TIMESTAMP
	k1k2_flag	smallint DEFAULT 2

Indexes

Type	Name	On
Pk	orders_pkey	orderid

Table orgdatajslip

Idx	Name	Data Type
* Pk	mappingid	integer DEFAULT nextval('kaveri.orgdatajslip_mappingid'::regclass)
Idx	partyid	bigint
Idx	documentid	bigint
	propertyid	bigint
	partytypeid	integer
	firstname	varchar(1000)
	mainownerno	bigint
	ownerno	bigint

Table orgdatajslip

	transactextacre	integer
	transactextgunta	integer
	transactextfgunta	decimal(7,5)
Idx	applicationnumber	varchar(50)
	relativename	varchar(300)
	relationship	varchar(100)
	inserteddatetime	timestamp DEFAULT CURRENT_TIMESTAMP

Indexes

Type	Name	On
Pk	pk_orgdatajslip_mappingid	mappingid
	idx_orgdatajslip_applicationnumber	applicationnumber
	idx_orgdatajslip	partyid
	idx_orgdatajslip_docid	documentid

Table otherfeesrequired

Idx	Name	Data Type
	otherfeesid	bigint DEFAULT nextval('kaveri.otherfeesrequired_otherfeesid_seq'::regclass)
	feerulecode	integer
	applicationnumber	varchar(50)
	feerequied	decimal
	receiptid	bigint DEFAULT nextval('kaveri.otherfeesrequired_otherfeesid_seq'::regclass)
Idx	departmentuserid	bigint
	inserteddatetime	timestamp DEFAULT CURRENT_TIMESTAMP
	k1k2_flag	smallint DEFAULT 2

Indexes

Type	Name	On
	otherfeesrequired_departmentuserid_idx	departmentuserid

Table otherreasonmaster

Idx	Name	Data Type
* Pk	reasonid	integer
*	description	varchar(200)
	isactive	boolean
	inserteddatetime	timestamp DEFAULT CURRENT_TIMESTAMP
	k1k2_flag	smallint DEFAULT 2

Indexes

Type	Name	On
Pk	pk_reasonid	reasonid

Table otherreasonremarks

Idx	Name	Data Type
* Pk	id	bigint
Idx	applicationnumber	varchar(50)
	reasonid	integer
	remarks	varchar(400)
	inserteddatetime	timestamp DEFAULT CURRENT_TIMESTAMP

Indexes

Table otherreasonremarks

Type	Name	On
Pk	pk_otherreasonremarks_id	id
	idx_otherreasonremarks_applicationnumber	applicationnumber

Table otherreceiptdetails

Idx	Name	Data Type
* Pk	receiptid	bigint DEFAULT nextval('kaveri.otherrecdetail_receiptid_seq'::regclass)
	partyfirstname	varchar(300)
	partymiddlename	varchar(100)
	partylastname	varchar(100)
	receipttype	varchar(100)
Idx	receiptdate	timestamp
	paymentmode	varchar(20)
	receipttotal	decimal
	paymentdescription	varchar(500)
	ifsccode	varchar(15)
	micrcode	varchar(15)
	ddchallannumber	varchar(50)
	dddate	timestamp
	subpurposedetails	varchar(500)
	inserteddatetime	timestamp DEFAULT CURRENT_TIMESTAMP
	k1k2_flag	smallint DEFAULT 2
	receipttypefromdate	timestamp
	receipttypetodate	timestamp
	financialyears	varchar(100)
	bookdetails	varchar(100)
	ceritificateruletype	varchar(100)
	departmentuserid	varchar(50)

Indexes

Type	Name	On
	otherreceiptdetails_receiptdate_idx	receiptdate
Pk	pk_receiptid_otherreceiptdetails	receiptid

Table otherreceiptdetails_cr0924003000267708

Idx	Name	Data Type
	receiptid	bigint
	partyfirstname	varchar(300)
	partymiddlename	varchar(100)
	partylastname	varchar(100)
	receipttype	varchar(100)
	receiptdate	timestamp
	paymentmode	varchar(20)
	receipttotal	decimal
	paymentdescription	varchar(500)
	ifsccode	varchar(15)
	micrcode	varchar(15)
	ddchallannumber	varchar(50)
	dddate	timestamp

Table otherreceiptdetails_cr0924003000267708

	subpurposedetails	varchar(500)
	inserteddatetime	timestamp
	k1k2_flag	smallint
	receipttypefromdate	timestamp
	receipttypetodate	timestamp
	financialyears	varchar(100)
	bookdetails	varchar(100)
	ceritificateruletype	varchar(100)
	departmentuserid	varchar(50)

Table otherreceiptpartyinfo

Idx	Name	Data Type
* Pk	partyid	bigint
*	drocode	integer
*	documentid	bigint
*	partytypeid	integer
	firstname	varchar(300)
	middlename	varchar(100)
	lastname	varchar(350)
*	address	varchar(300)
	age	varchar(50)
	sex	smallint
*	isexecutor	boolean
*	ispresenter	boolean
	admissiondate	timestamp
	aliasname	varchar(150)
	correctedname	varchar(150)
	relationship	varchar(50)
	relativename	varchar(200)
	epic	varchar(50)
	pan	varchar(50)
	phonenumber	varchar(15)
	availableextacre	integer
	availableextgunta	integer
	availableextfgunta	integer
	bincom	varchar(50)
	category	varchar(120)
	dateofdeath	timestamp
	fingerid	integer
	fingerverificationstatusid	smallint
	ispartofrtc	boolean
	landcode	bigint
	mainownerno	bigint
	ownerno	bigint
	partypoa	varchar(350)
	photopath	varchar(256)
	poaadmission	bigint
	poapresentation	bigint

Table otherreceiptpartyinfo

	primaryseller	boolean
	profession	varchar(100)
	restriction	varchar(1)
	restrictiondescription	varchar(120)
	restrictiontype	varchar(2)
	section88exemption	boolean
	thumbmatchfailedreasonid	integer
	thumbminutiae	varchar(2147)
	thumbpath	varchar(256)
	totalextacre	integer
	totalextgunta	integer
	totalextfgunta	integer
	transactextacre	integer
	transactextgunta	integer
	transactextfgunta	integer
	volumename	varchar(50)
	hasgpa	boolean
	isaua	boolean
	k1k2_flag	smallint DEFAULT 2
	inserteddatetime	timestamp DEFAULT CURRENT_TIMESTAMP

Indexes

Type	Name	On
Pk	otherreceiptpartyinfo_pkey	partyid

Table partyinfo_cd140

Idx	Name	Data Type
	partyid	bigint
	srocode	integer
	documentid	bigint
	partytypeid	integer
	firstname	varchar(300)
	middlename	varchar(300)
	lastname	varchar(350)
	address	varchar(300)
	age	varchar(3)
	sex	smallint
	isexecutor	boolean
	ispresenter	boolean
	admissiondate	timestamp
	aliasname	varchar(150)
	correctedname	varchar(150)
	relationship	varchar(50)
	relativename	varchar(200)
	epic	varchar(50)
	pan	varchar(50)
	phonenumber	varchar(15)
	availableextacre	integer
	availableextgunta	integer

Table partyinfo_cd140

availableextfgunta	decimal(7,5)
bincom	varchar(50)
category	varchar(120)
dateofdeath	timestamp
fingerid	integer
fingerverificationstatusid	smallint
ispartofrtc	boolean
landcode	bigint
mainownerno	bigint
ownerno	bigint
partypoa	varchar(350)
photopath	varchar(256)
poaadmission	bigint
poapresentation	bigint
primaryseller	boolean
profession	varchar(100)
restriction	varchar(1)
restrictiondescription	varchar(120)
restrictiontype	varchar(2)
section88exemption	boolean
thumbmatchfailedreasonid	integer
thumbminutiae	bytea
thumbpath	varchar(256)
totalextacre	integer
totalextgunta	integer
totalextfgunta	decimal(7,5)
transactextacre	integer
transactextgunta	integer
transactextfgunta	decimal(7,5)
volumename	varchar(50)
hasgpa	boolean
isaua	boolean
importedpartyparentid	bigint
salutationid	smallint
isorganization	boolean
organizationid	integer
applicationnumber	varchar(50)
verified	boolean
issroapproved	varchar(1)
districtcode	integer
talukcode	integer
hoblicode	integer
villagecode	bigint
tanno	varchar(50)
yearofincorp	integer
orgpoaauthsignfname	text
orgpoaauthsignmname	text
orgpoaauthsignlname	text
linkpartyid	bigint

Table partyinfo_cd140

	housenumber	text
	pin	integer
	propertyid	bigint
	propertynumber	varchar
	idprooftypeid	smallint
	isconsentwitness	boolean
	isprivateattendance	boolean
	coveringletterno	char(100)
	section88file	char(500)
	isendorseprinted	boolean
	thumbremarks	varchar(200)
	partyidreference	bigint
	inserteddatetime	timestamp
	k1k2_flag	smallint
	ispartyrefused	boolean
	islateapperance	boolean
	isduplicate	boolean
	duplicatepartyid	bigint
	presenternamee	varchar(100)

Table partyinfo_claimaint

Idx	Name	Data Type
	partyid	bigint
	srocode	integer
	documentid	bigint
	partytypeid	integer
	firstname	varchar(300)
	middlename	varchar(100)
	lastname	varchar(350)
	address	varchar(300)
	age	varchar(3)
	sex	smallint
	isexecutor	boolean
	ispresenter	boolean
	admissiondate	timestamp
	aliasname	varchar(150)
	correctedname	varchar(150)
	relationship	varchar(50)
	relativename	varchar(200)
	epic	varchar(50)
	pan	varchar(50)
	phonenumber	varchar(15)
	availableextacre	integer
	availableextgunta	integer
	availableextfgunta	decimal(7,5)
	bincom	varchar(50)
	category	varchar(120)
	dateofdeath	timestamp

Table partyinfo_claimaint

fingerid	integer
fingerverificationstatusid	smallint
ispartofrtc	boolean
landcode	bigint
mainownerno	bigint
ownerno	bigint
partypoa	varchar(350)
photopath	varchar(256)
poaadmission	bigint
poapresentation	bigint
primaryseller	boolean
profession	varchar(100)
restriction	varchar(1)
restrictiondescription	varchar(120)
restrictiontype	varchar(2)
section88exemption	boolean
thumbmatchfailedreasonid	integer
thumbminutiae	bytea
thumbpath	varchar(256)
totalextacre	integer
totalextgunta	integer
totalextfgunta	decimal(7,5)
transactextacre	integer
transactextgunta	integer
transactextfgunta	decimal(7,5)
volumename	varchar(50)
hasgpa	boolean
isaua	boolean
importedpartyparentid	bigint
salutationid	smallint
isorganization	boolean
organizationid	integer
applicationnumber	varchar(50)
verified	boolean
issroapproved	varchar(1)
districtcode	integer
talukcode	integer
hoblicode	integer
villagecode	bigint
tanno	varchar(50)
yearofincorp	integer
orgpoaauthsignfname	text
orgpoaauthsignmname	text
orgpoaauthsignlname	text
linkpartyid	bigint
housenumber	text
pin	integer
propertyid	bigint
propertynumber	varchar

Table partyinfo_claimaint

	idprooftypeid	smallint
	isconsentwitness	boolean
	isprivateattendance	boolean
	coveringletterno	char(100)
	section88file	char(500)
	isendorseprinted	boolean
	thumbremarks	varchar(200)
	partyidreference	bigint
	inserteddatetime	timestamp
	k1k2_flag	smallint
	ispartyrefused	boolean
	islateapperance	boolean
	isduplicate	boolean
	duplicatepartyid	bigint
	presenternamee	varchar(100)

Table partyorganizationinfo

Idx	Name	Data Type
* Pk	organizationid	bigint DEFAULT nextval('kaveri.partyorganizationinfo_organizationid_seq'::regclass)
*	orgname	text
	orgcorrectedname	text
	orgidnumber	text
	panno	varchar(50)
	tinno	varchar(50)
	tanno	varchar(50)
	regaddress	text
	yearofincorp	integer
	documentid	bigint
	srocode	integer
	applicationnumber	varchar(50)
	verified	boolean DEFAULT false
	issroapproved	varchar(1) DEFAULT 'E'::character varying
	inserteddatetime	timestamp DEFAULT CURRENT_TIMESTAMP
	k1k2_flag	smallint DEFAULT 2

Indexes

Type	Name	On
Pk	partyorganizationinfo_pkey	organizationid

Table partyschedules

Idx	Name	Data Type
* Idx	partyscheduleid	bigint DEFAULT nextval('kaveri.partyschedules_partyscheduleid_seq'::regclass)
* Pk	partyid	bigint
* Pk	scheduleid	bigint
* Pk	propertyid	bigint
Idx	applicationnumber	varchar(50)
	isdelete	boolean DEFAULT false

Table partyschedules

	inserteddatetime	timestamp DEFAULT CURRENT_TIMESTAMP
	k1k2_flag	smallint DEFAULT 2

Indexes

Type	Name	On
	idx_partyschedule_partyscheduleid	partyscheduleid, scheduleid
Pk	partyschedules_pkey	scheduleid, propertyid, partyid
	idx_partyschedule_applicationnumber	applicationnumber

Table partyschedules_cd140

Idx	Name	Data Type
	partyscheduleid	bigint
	partyid	bigint
	scheduleid	bigint
	propertyid	bigint
	applicationnumber	varchar(50)
	isdelete	boolean
	inserteddatetime	timestamp
	k1k2_flag	smallint

Table partytypemaster

Idx	Name	Data Type
* Pk	partytypeid	integer
*	descriptioninkannada	varchar(150)
*	descriptioninenglish	varchar(150)
	inserteddatetime	timestamp DEFAULT CURRENT_TIMESTAMP
	k1k2_flag	smallint DEFAULT 2

Indexes

Type	Name	On
Pk	pk_partytypemaster	partytypeid

Table partywitness

Idx	Name	Data Type
* Pk	partyid	bigint
* Pk	witnessid	bigint
	witnessdate	timestamp
* Pk	srocode	integer
	k1k2_flag	smallint DEFAULT 2
	inserteddatetime	timestamp DEFAULT CURRENT_TIMESTAMP

Indexes

Type	Name	On
Pk	pk_partywitness	partyid, witnessid, srocode
	idx_partywitness	partyid
	idx_partywitness_witnes	witnessid

Table paymentmodemaster

Idx	Name	Data Type
* Pk	paymentmodeid	integer
*	descriptionkannada	varchar(75)

Table paymentmodemaster

*	descriptionenglish	varchar(75)
*	ismodeactive	boolean
	minamount	decimal(23,4)
	maxamount	decimal(23,4)
	khajaneremittancedescription	varchar(50)
	inserteddatetime	timestamp DEFAULT CURRENT_TIMESTAMP
	k1k2_flag	smallint DEFAULT 2

Indexes

Type	Name	On
Pk	pk_paymentmodemaster	paymentmodeid

Table pendingreasonmaster

Idx	Name	Data Type
* Pk	pendingreasonid	integer
*	reasoninkannada	varchar(150)
*	reasoninenglish	varchar(150)
	documentstage	varchar(75)
*	severity	integer
	k1k2_flag	smallint DEFAULT 2

Indexes

Type	Name	On
Pk	pk_pendingreasonmaster	pendingreasonid

Table persondetails

Idx	Name	Data Type
* Pk	personid	integer
	salutation	smallint
	firstname	varchar(255)
	middlename	varchar(50)
	lastname	varchar(50)
	mothersalutation	smallint
	motherfirstname	varchar(100)
	mothermiddlename	varchar(100)
	motherlastname	varchar(100)
	fathersalutation	smallint
	fatherfirstname	varchar(100)
	fathermiddlename	varchar(100)
	fatherlastname	varchar(100)
Unq	sex	varchar(1)
	status	varchar(15)
	prehousebuildname	varchar(80)
	prestreetname	varchar(100)
	prestatecode	integer
	predistrictcode	integer
	pretalukacode	integer
	prehoblicode	integer
	precityvillagecode	integer
	prepincode	integer

Table persondetails

	ispresentaddresssameaspermanent	boolean
	perhousebuildname	varchar(80)
	perstreetname	varchar(100)
	perstatecode	integer
	perdistrictcode	integer
	pertalukacode	integer
	perhoblicode	integer
	percityvillagecode	integer
	perpincode	integer
	phoneno	varchar(25)
	email	varchar(100)
	dob	date
	age	integer
	occupation	varchar(50)
	imagefilepath	varchar(500)
	supportdocuments	varchar(50)
	identityproofid	smallint
	identityprooffilepath	varchar(500)
	ageproofid	smallint
	ageprooffilepath	varchar(500)
	addressproofid	smallint
	addressprooffilepath	varchar(500)
	registrationid	bigint
Unq	applicationnumber	varchar(50)
	deathcertificateid	integer
	deathcertificatefilepath	varchar(500)
	divorcecertificateid	integer
	divorcecertificatefilepath	varchar(500)
	inserteddate	timestamp DEFAULT CURRENT_TIMESTAMP
	durationofstayproofpath	varchar(500)
	k1k2_flag	smallint DEFAULT 2
	statusid	smallint
	persontypeid	smallint

Indexes

Type	Name	On
Pk	pk_personid_persondetails	personid
Unq	uq_agesrocdappnumbr_persondetails1	sex, applicationnumber

Foreign Keys

Type	Name	On
	fk_appnumbr_persondetails1 (applicationnumber) ref applicantapplicationdetails (applicationnumber)	

Table persons_additional

Idx	Name	Data Type
* Pk	personiddetail	bigint DEFAULT nextval('kaveri.persons_additional_personiddetail_seq'::regclass)
	personid	bigint
	personname	varchar(200)
	relationshiptype	integer
	inserteddatetime	timestamp DEFAULT CURRENT_TIMESTAMP

Table persons_additional

	k1k2_flag	smallint DEFAULT 2

Indexes

Type	Name	On
Pk	persons_additional_pkey	personiddetail

Table post_office_details

Idx	Name	Data Type
* Pk	postid	integer DEFAULT nextval('kaveri.postid_seq'::regclass)
	designationid	integer
	postdescription	text
	officetypeid	smallint
	officeid	smallint
	supportingdocpath	text
	inserteddatetime	timestamp DEFAULT CURRENT_TIMESTAMP
	createdby	bigint

Indexes

Type	Name	On
Pk	pk_post_office_details	postid
	idx_post_office_details_postid	postid

Table propertybankdetails

Idx	Name	Data Type
* Pk	id	bigint
	propertyid	bigint
	documentid	bigint
	bankid	integer
	branchid	bigint
* Pk	srocode	integer
*	bankcode	varchar(50)
*	bankname	varchar(255)
*	branchcode	varchar(50)
*	branchname	varchar(255)
*	ifcscode	varchar(255)
	isonline	boolean
	loanamount	decimal(23,4)
	inserteddatetime	timestamp DEFAULT CURRENT_TIMESTAMP
	k1k2_flag	smallint DEFAULT 2

Indexes

Type	Name	On
Pk	pk_propertybankdetails	id, srocode

Table propertybuildingusagetypedetails

Idx	Name	Data Type
* Pk	id	bigint
* Pk	srocode	integer
*	propertyid	bigint
*	buildingusagetypeid	integer
	inserteddatetime	timestamp DEFAULT CURRENT_TIMESTAMP

Table propertybuildingusagetypedetails

	k1k2_flag	smallint DEFAULT 2

Indexes

Type	Name	On
Pk	pk_propertybuildingusagetypedetails	id, srocode

Table propertyclassification

Idx	Name	Data Type
* Pk	propertyid	bigint
	urbandeptid	integer
	sellerpartyids	varchar(1000)
	purchaserpartyids	varchar(1000)
* Pk	srocode	integer
	wardid	integer
	k1k2_flag	smallint DEFAULT 2

Indexes

Type	Name	On
Pk	pk_propertyclassification	propertyid, srocode

Table propertyfloornumberdetails

Idx	Name	Data Type
* Pk	id	bigint
* Pk	srocode	integer
*	propertyid	bigint
*	floornumberid	integer
	inserteddatetime	timestamp DEFAULT CURRENT_TIMESTAMP
	k1k2_flag	smallint DEFAULT 2

Indexes

Type	Name	On
Pk	pk_propertyfloornumberdetails	id, srocode

Table propertyfloortypesdetails

Idx	Name	Data Type
* Pk	id	bigint
* Pk	srocode	integer
*	propertyid	bigint
*	floortypeid	integer
	inserteddatetime	timestamp DEFAULT CURRENT_TIMESTAMP
	k1k2_flag	smallint DEFAULT 2

Indexes

Type	Name	On
Pk	pk_propertyfloortypesdetails	id, srocode

Table propertymaster

Idx	Name	Data Type
* Pk	propertyid	bigint
* Idx	documentid	bigint
Idx	villagecode	bigint
* Pk	regsrocode	integer

Table propertymaster

* Idx	srocode	integer
*	totalarea	decimal(20,6)
* Idx	unitid	integer
	northboundary	varchar(500)
	southboundary	varchar(500)
	eastboundary	varchar(500)
	westboundary	varchar(500)
	landmark	varchar(5000)
	marketvalue	decimal
	assessment	varchar(2000)
	sdcalculationstring	varchar(500)
	stampduty	decimal
	transferliabilities	smallint
	consideration	decimal
	additionalduty	decimal
	cessduty	decimal
	govtduty	decimal
	isexempted	boolean
	exemptiondescription	varchar(2000)
* Idx	ismovableproperty	boolean
	sdrefund	decimal
	docmarketvalue	decimal
	valid1	bigint
	isimdemnified	boolean
	restriction	varchar(1)
	restrictiontype	varchar(2)
	restrictiondescription	varchar(120)
	enumber	varchar(20)
	claimingblocknumber	varchar(1)
	retainingblocknumber	varchar(1)
	valuationreport	varchar(4000)
	loanpurposeid	smallint
Idx	applicationnumber	varchar(50)
	verified	boolean DEFAULT false
	issroapproved	varchar(1) DEFAULT 'E'::character varying
Idx	stamparticlecode	integer
Idx	stampruleid	integer
	regarticlecode	integer
Idx	propertytypeid	integer
	noofscanpages	integer
	movablepropertydesc	text
Idx	roadcode	bigint
	wardid	integer
	pidno	bigint
	udeptid	integer
	sfdastamparticlecode	integer
	sfdastampruleid	integer
	sfdanoofscanpages	integer
	srostamparticlecode	integer

Table propertymaster

	srostampruleid	integer
	sronoofscanpages	integer
	sfdamarketvalue	bigint
	sromarketvalue	bigint
	ownedarea	decimal(20,6)
	sfdanatureofdocument	integer
	sronatureofdocument	integer
	denodescription	varchar
	estampdescription	varchar
	adjudescription	varchar
	sroconsideration	decimal
	sfdaconsideration	decimal
	referencepropertyid	bigint
	isbefore2004	boolean
	sfdastampduty	decimal
	srostampduty	decimal
	sfdacessduty	decimal
	srocessduty	decimal
	surcharge	decimal
	sfdasurcharge	decimal
	srosurcharge	decimal
	valuationtypeid	smallint
	inserteddatetime	timestamp DEFAULT CURRENT_TIMESTAMP
	zoneid	integer
	subpropertytypeid	integer
	k1k2_flag	smallint DEFAULT 2
	sroroadcode	bigint
	sfdaroadcode	bigint

Indexes

Type	Name	On
	ix_propertymaster_1	villagecode, ismovableproperty, propertyid, documentid, regsrocode, srocode
	propertymaster_villagecode_idx	villagecode
Pk	propertymaster_pkey	propertyid, regsrocode
	idx_propertymaster_sroc	srocode
	idx_propertymaster_stamp	stamparticlecode
	ix_propertymaster_4	applicationnumber
	propertymaster_documentid_idx	documentid
	propertymaster_ismovableproperty_idx	ismovableproperty
	propertymaster_multiple_3	propertyid, applicationnumber, propertytypeid, srocode, villagecode
	scheduleid_regsrocode_idx	stampruleid
	propertymaster_propertyid_idx	propertyid
	propertymaster_unitid_idx	unitid
	idx_propertymaster_road	roadcode

Table propertymaster_11092023

Idx	Name	Data Type
* Pk	propertyid	bigint

Table propertymaster_11092023

documentid	bigint
villagecode	bigint
regsrocode	integer
srocode	integer
totalarea	decimal(20,6)
unitid	integer
northboundary	varchar(500)
southboundary	varchar(500)
eastboundary	varchar(500)
westboundary	varchar(500)
landmark	varchar(5000)
marketvalue	decimal
assessment	varchar(2000)
sdcalculationstring	varchar(500)
stampduty	decimal
transferliabilities	smallint
consideration	decimal
additionalduty	decimal
cessduty	decimal
govtduty	decimal
isexempted	boolean
exemptiondescription	varchar(2000)
ismovableproperty	boolean
sdrefund	decimal
docmarketvalue	decimal
valid1	bigint
isimdemnified	boolean
restriction	varchar(1)
restrictiontype	varchar(2)
restrictiondescription	varchar(120)
enumber	varchar(20)
claimingblocknumber	varchar(1)
retainingblocknumber	varchar(1)
valuationreport	varchar(4000)
loanpurposeid	smallint
applicationnumber	varchar(50)
verified	boolean
issroapproved	varchar(1)
stamparticlecode	integer
stampruleid	integer
regarticlecode	integer
propertytypeid	integer
noofscanpages	integer
movablepropertydesc	text
roadcode	bigint
wardid	integer
pidno	bigint
udeptid	integer
sfdastamparticlecode	integer

Table propertymaster_11092023

	sfdastampruleid	integer
	sfdanoofscanpages	integer
	srostamparticlecode	integer
	srostampruleid	integer
	sronoofscanpages	integer
	sfdamarketvalue	bigint
	sromarketvalue	bigint
	ownedarea	decimal(20,6)
	sfdanatureofdocument	integer
	sronatureofdocument	integer
	denodescription	varchar
	estampdescription	varchar
	adjudescription	varchar
	sroconsideration	decimal
	sfdaconsideration	decimal
	referencepropertyid	bigint
	isbefore2004	boolean
	sfdastampduty	decimal
	srostampduty	decimal
	sfdacessduty	decimal
	srocessduty	decimal
	surcharge	decimal
	sfdasurcharge	decimal
	srosurcharge	decimal
	valuationtypeid	smallint
	inserteddatetime	timestamp
	zoneid	integer
	subpropertytypeid	integer
	k1k2_flag	smallint
	sroroadcode	bigint
	sfdaroadcode	bigint

Indexes

Type	Name	On
Pk	pk_propertymaster_11_propertyid	propertyid
Unq	uk_propertymaster_11_propertyids	propertyid

Table propertymaster_cd140

Idx	Name	Data Type
	propertyid	bigint
	documentid	bigint
	villagecode	bigint
	regsrocode	integer
	srocode	integer
	totalarea	decimal(20,6)
	unitid	integer
	northboundary	varchar(500)
	southboundary	varchar(500)
	eastboundary	varchar(500)

Table propertymaster_cd140

westboundary	varchar(500)
landmark	varchar(5000)
marketvalue	decimal
assessment	varchar(2000)
sdcalculationstring	varchar(500)
stampduty	decimal
transferliabilities	smallint
consideration	decimal
additionalduty	decimal
cessduty	decimal
govtduty	decimal
isexempted	boolean
exemptiondescription	varchar(2000)
ismovableproperty	boolean
sdrefund	decimal
docmarketvalue	decimal
valid1	bigint
isimdemnified	boolean
restriction	varchar(1)
restrictiontype	varchar(2)
restrictiondescription	varchar(120)
enumber	varchar(20)
claimingblocknumber	varchar(1)
retainingblocknumber	varchar(1)
valuationreport	varchar(4000)
loanpurposeid	smallint
applicationnumber	varchar(50)
verified	boolean
issroapproved	varchar(1)
stamparticlecode	integer
stampruleid	integer
regarticlecode	integer
propertytypeid	integer
noofscanpages	integer
movablepropertydesc	text
roadcode	bigint
wardid	integer
pidno	bigint
udeptid	integer
sfdastamparticlecode	integer
sfdastampruleid	integer
sfdanoofscanpages	integer
srostamparticlecode	integer
srostampruleid	integer
sronoofscanpages	integer
sfdamarketvalue	bigint
sromarketvalue	bigint
ownedarea	decimal(20,6)
sfdanatureofdocument	integer

Table propertymaster_cd140

	sronatureofdocument	integer
	denodescription	varchar
	estampdescription	varchar
	adjudescription	varchar
	sroconsideration	decimal
	sfdaconsideration	decimal
	referencepropertyid	bigint
	isbefore2004	boolean
	sfdastampduty	decimal
	srostampduty	decimal
	sfdacessduty	decimal
	srocessduty	decimal
	surcharge	decimal
	sfdasurcharge	decimal
	srosurcharge	decimal
	valuationtypeid	smallint
	inserteddatetime	timestamp
	zoneid	integer
	subpropertytypeid	integer
	k1k2_flag	smallint
	sroroadcode	bigint
	sfdaroadcode	bigint

Table propertymaster_dashboard_1

Idx	Name	Data Type
	propertyid	bigint
	documentid	bigint
	villagecode	bigint
	regsrocode	integer
	srocode	integer
	totalarea	decimal(20,6)
	unitid	integer
	northboundary	varchar(500)
	southboundary	varchar(500)
	eastboundary	varchar(500)
	westboundary	varchar(500)
	landmark	varchar(5000)
	marketvalue	decimal
	assessment	varchar(2000)
	sdcalculationstring	varchar(500)
	stampduty	decimal
	transferliabilities	smallint
	consideration	decimal
	additionalduty	decimal
	cessduty	decimal
	govtduty	decimal
	isexempted	boolean
	exemptiondescription	varchar(2000)

Table propertymaster_dashboard_1

ismovableproperty	boolean
sdrefund	decimal
docmarketvalue	decimal
valid1	bigint
isimdemnified	boolean
restriction	varchar(1)
restrictiontype	varchar(2)
restrictiondescription	varchar(120)
enumber	varchar(20)
claimingblocknumber	varchar(1)
retainingblocknumber	varchar(1)
valuationreport	varchar(4000)
loanpurposeid	smallint
applicationnumber	varchar(50)
verified	boolean
issroapproved	varchar(1)
stamparticlecode	integer
stampruleid	integer
regarticlecode	integer
propertytypeid	integer
noofscanpages	integer
movablepropertydesc	text
roadcode	bigint
wardid	integer
pidno	bigint
udeptid	integer
sfdastamparticlecode	integer
sfdastampruleid	integer
sfdanoofscanpages	integer
srostamparticlecode	integer
srostampruleid	integer
sronoofscanpages	integer
sfdamarketvalue	bigint
sromarketvalue	bigint
ownedarea	decimal(20,6)
sfdanatureofdocument	integer
sronatureofdocument	integer
denodescription	varchar
estampdescription	varchar
adjudescription	varchar
sroconsideration	decimal
sfdaconsideration	decimal
referencepropertyid	bigint
isbefore2004	boolean
sfdastampduty	decimal
srostampduty	decimal
sfdacessduty	decimal
srocessduty	decimal
surcharge	decimal

Table propertymaster_dashboard_1

	sfdasurcharge	decimal
	srosurcharge	decimal
	valuationtypeid	smallint
	inserteddatetime	timestamp
	zoneid	integer
	subpropertytypeid	integer
	k1k2_flag	smallint
	sroroadcode	bigint
	sfdaroadcode	bigint

Table propertynotypemaster

Idx	Name	Data Type
* Pk	propertytypeid	integer
*	typenamekannada	varchar(75)
*	typenameenglish	varchar(75)
	isactive	integer
	inserteddatetime	timestamp DEFAULT CURRENT_TIMESTAMP
	k1k2_flag	smallint DEFAULT 2

Indexes

Type	Name	On
Pk	pk_propertynotypemaster	propertytypeid

Table propertynumberdetails

Idx	Name	Data Type
* Idx	propertyid	bigint
* Idx	srocode	integer
* Idx	currentpropertytypeid	integer
* Idx	currentnumber	varchar(100)
	oldpropertytypeid	integer
	oldnumber	varchar(75)
Idx	description	varchar(1000)
Idx	survey_no	integer
Idx	surnoc	varchar(20)
Idx	hissa_no	varchar(30)
	inserteddatetime	timestamp DEFAULT CURRENT_TIMESTAMP
	k1k2_flag	smallint DEFAULT 2

Indexes

Type	Name	On
	fki_fk_propertynumberdetails_propertynotypemaster	currentpropertytypeid
	ix_propertynumberdetails	propertyid, srocode, currentnumber, description, survey_no, surnoc, hissa_no
	propertynumberdetails_currentpropertytypeid_idx	currentpropertytypeid
	propertynumberdetails_propertyid_idx	propertyid
	propertynumberdetails_srocode_idx	srocode

Table propertynumberdetails_cd140

Idx	Name	Data Type
	propertyid	bigint

Table propertynumberdetails_cd140

	srocode	integer
	currentpropertytypeid	integer
	currentnumber	varchar(100)
	oldpropertytypeid	integer
	oldnumber	varchar(75)
	description	varchar(1000)
	survey_no	integer
	surnoc	varchar(20)
	hissa_no	varchar(30)
	inserteddatetime	timestamp
	k1k2_flag	smallint

Table propertynumberdetails_space_bck

Idx	Name	Data Type
	propertyid	bigint
	srocode	integer
	currentpropertytypeid	integer
	currentnumber	varchar(100)
	oldpropertytypeid	integer
	oldnumber	varchar(75)
	description	varchar(1000)
	survey_no	integer
	surnoc	varchar(20)
	hissa_no	varchar(30)
	inserteddatetime	timestamp
	k1k2_flag	smallint
	regexp_replace	text

Table propertyrooftypedetails

Idx	Name	Data Type
* Pk	id	bigint
* Pk	srocode	integer
*	propertyid	bigint
*	rooftypeid	integer
	inserteddatetime	timestamp DEFAULT CURRENT_TIMESTAMP
	k1k2_flag	smallint DEFAULT 2

Indexes

Type	Name	On
Pk	pk_propertyrooftypedetails	id, srocode

Table propertyschedules

Idx	Name	Data Type
* Pk	scheduleid	bigint
* Pk	propertyid	bigint
* Pk	srocode	integer
Unq	partyid	bigint
	scheduletype	varchar(6)
*	totalarea	decimal(20,6)

Table propertyschedules

*	unitid	integer
*	description	varchar(5000)
	partyids	varchar(2000)
	aileniatedauthorityid	boolean
	alieniatedorder	varchar(200)
	bhoomisellerpartyids	varchar(2000)
	govtrestricorder	varchar(200)
	govtrestrictionid	boolean
	landcode	bigint
	propertygroup	smallint
	giftshare	decimal(18,2)
	giftsharedetails	varchar(200)
	easttowest	varchar(500)
	northtosouth	varchar(500)
	blockchainpropertyid	varchar(200)
	assignedblockchainpid	varchar(200)
Idx	applicationnumber	varchar(50)
	verified	boolean DEFAULT false
	issroapproved	varchar(1) DEFAULT 'E'::character varying
	eastboundary	varchar(500)
	westboundary	varchar(500)
	northboundary	varchar(500)
	southboundary	varchar(500)
	inserteddatetime	timestamp DEFAULT CURRENT_TIMESTAMP
	k1k2_flag	smallint DEFAULT 2
	electriccompid	varchar(100)
	waterboardid	varchar(100)
	electriccomp	integer
	waterboard	integer

Indexes

Type	Name	On
Pk	propertyschedules_pkey	scheduleid, propertyid, srocode
	idx_propertyschedule_proapp	propertyid, applicationnumber
	idx_propertyschedules_propertyid	propertyid
	idx_propertyschedules_propertyids	applicationnumber
Unq	ix_propertyschedules	srocode, propertyid, scheduleid
Unq	ix_propertyschedules_multiple	propertyid, scheduleid, partyid
	propertyschedules_srocode_idx	srocode

Table propertyschedules_cd140

Idx	Name	Data Type
	scheduleid	bigint
	propertyid	bigint
	srocode	integer
	partyid	bigint
	scheduletype	varchar(6)
	totalarea	decimal(20,6)
	unitid	integer

Table propertyschedules_cd140

	description	varchar(5000)
	partyids	varchar(2000)
	aileniatedauthorityid	boolean
	alieniatedorder	varchar(200)
	bhoomisellerpartyids	varchar(2000)
	govtrestricorder	varchar(200)
	govtrestrictionid	boolean
	landcode	bigint
	propertygroup	smallint
	giftshare	decimal(18,2)
	giftsharedetails	varchar(200)
	easttowest	varchar(500)
	northtosouth	varchar(500)
	blockchainpropertyid	varchar(200)
	assignedblockchainpid	varchar(200)
	applicationnumber	varchar(50)
	verified	boolean
	issroapproved	varchar(1)
	eastboundary	varchar(500)
	westboundary	varchar(500)
	northboundary	varchar(500)
	southboundary	varchar(500)
	inserteddatetime	timestamp
	k1k2_flag	smallint

Table propertytypedescmaster

Idx	Name	Data Type
* Pk	propertytype	integer
	descriptioninkannada	varchar(100)
	descriptioninenglish	varchar(100)
	meaning	varchar(100)
	lstupddate	timestamp DEFAULT CURRENT_TIMESTAMP
	inserteddatetime	timestamp DEFAULT CURRENT_TIMESTAMP
	k1k2_flag	smallint DEFAULT 2

Indexes

Type	Name	On
Pk	pk_propertytypedescmaster	propertytype

Table propertytypemaster

Idx	Name	Data Type
* Pk	propertytypeid	integer
*	propertytypename	varchar(500)
*	propertytypenamek	varchar(500)
	isresidential	boolean
	nodekey	varchar(10)
	considerationrate	double precision
	considerationratewithrefrence	bigint
Idx	refrenceparentpropertyid	bigint

Table propertytypemaster

	groupname	varchar(50)
	description	varchar(100)
	areacaption	varchar(20)
	areacaptionr	varchar(50)
	isagri	boolean
	isopenbuiltraterates	boolean
	isapartment	boolean
	k1k2_flag	smallint DEFAULT 2
	isactive	boolean

Indexes

Type	Name	On
Pk	pk_propertytypemaster_1	propertytypeid
	idx_propertytypemaster	refrenceparentpropertyid

Table propertywoodtypedetails

Idx	Name	Data Type
*	id	bigint
*	srocode	integer
*	propertyid	bigint
*	woodtypeid	integer
	inserteddatetime	timestamp DEFAULT CURRENT_TIMESTAMP
	k1k2_flag	smallint DEFAULT 2

Table queue_service

Idx	Name	Data Type
* Pk	service_id	bigint DEFAULT nextval('kaveri.queue_service_seq'::regclass)
*	service_name	varchar(255)
	description	text
*	inserted_date	timestamp DEFAULT CURRENT_TIMESTAMP

Indexes

Type	Name	On
Pk	queue_service_pk	service_id

Table queues

Idx	Name	Data Type
* Pk	queue_id	bigint DEFAULT nextval('kaveri.queues_seq'::regclass)
*	service_id	bigint
*	isactive	boolean DEFAULT true
*	inserted_date	timestamp DEFAULT CURRENT_TIMESTAMP
	queue_name	varchar(100)

Indexes

Type	Name	On
Pk	queues_pk	queue_id

Table rateagriculturaldetail

Idx	Name	Data Type
* Idx	roadcode	bigint
* Idx	agrilandtypeid	smallint

Table rateagriculturaldetail

* Idx	villagecode	bigint
*	measurementcode	integer
*	rate	decimal(18,5)
Idx	effectivedate	timestamp
* Pk	rateagricode	bigint
	k1k2_flag	smallint DEFAULT 2
	inserteddatetime	timestamp DEFAULT CURRENT_TIMESTAMP
	prevrate	decimal(18,5)
	prevrate2	decimal(18,5)

Indexes

Type	Name	On
	idx_rateagriculturaldetail_ag	agrilandtypeid, roadcode, villagecode, effectivedate
Pk	rateagriculturaldetail_pkey	rateagricode
	idx_rateagriculturaldetail_code	roadcode, villagecode

Table rdpr_document_details

Idx	Name	Data Type
* Pk	id	bigint DEFAULT nextval('kaveri.rdpr_document_details_id_seq'::regclass)
*	uuid	uuid DEFAULT gen_random_uuid()
*	rdpr_document_id	bigint
Idx	application_number	varchar(255)
	finalregistrationnumber	varchar(255)
Idx	property_id	varchar(255)
	claimants	text
	executants	text
	prev_finalregistrationnumber	varchar(255)
	data	text
	status_remarks	varchar(255)
	created_at	timestamp(22)
	updated_at	timestamp(22)
	deleted_at	timestamp(22)
	current_stamparticlecode	text
	current_stamparticlename	text
	currentnumber	text
	inserteddatetime	timestamp DEFAULT CURRENT_TIMESTAMP
	fetch_status	integer

Indexes

Type	Name	On
Pk	rdpr_document_details_pkey	id
	idx_rdprdocdetails_propid	property_id
	idx_rdprdocdetails_appno_ccnew	application_number
	idx_rdprdocdetails_appno_ccnew1	application_number
	idx_rdprdocdetails_appno	application_number

Table rdpr_documents

Idx	Name	Data Type
* Pk	id	bigint DEFAULT nextval('kaveri.rdpr_documents_id_seq'::regclass)

Table rdpr_documents

* Unq	uuid	uuid DEFAULT gen_random_uuid()
Idx	title	varchar(255)
	path	varchar(255)
	uploaded_by	bigint
	created_at	timestamp(22)
	updated_at	timestamp(22)
	deleted_at	timestamp(22)
	inserteddatetime	timestamp DEFAULT CURRENT_TIMESTAMP
	data_imported	integer
	fetch_status	integer

Indexes

Type	Name	On
Pk	rdpr_documents_pkey	id
Unq	uk_rdprdoc_uuid	uuid
	idx_rdpr_documenttitle	title

Table rdprxml

Idx	Name	Data Type
*	logid	bigint
*	srocode	integer
*	documentid	bigint
*	propertyid	bigint
	inputownerdetails	text
	ownerdetails	text
	verified	boolean
*	isuploaded	boolean
	uploaddatetime	timestamp
	eswathureferenceno	varchar(50)
	ackxmldetails	text
	sentxmldetails	text
	sentxmlucdetails	text
	previouspropertyid	bigint
	previoussrocode	smallint
	inserteddatetime	timestamp DEFAULT CURRENT_TIMESTAMP
	k1k2_flag	smallint DEFAULT 2

Table rdprxmltypemapping

Idx	Name	Data Type
* Pk	mappingid	integer
*	regarticlecode	integer
*	typeid	integer
	inserteddatetime	timestamp DEFAULT CURRENT_TIMESTAMP
	k1k2_flag	smallint DEFAULT 2

Indexes

Type	Name	On
Pk	pk_rdprxmltypemapping	mappingid

Table rdprxmltypes

Idx	Name	Data Type
* Pk	typeid	integer
*	description	varchar(150)
	inserteddatetime	timestamp DEFAULT CURRENT_TIMESTAMP
	k1k2_flag	smallint DEFAULT 2

Indexes

Type	Name	On
Pk	pk_rdprxmltypes	typeid

Table reasonmaster

Idx	Name	Data Type
* Pk	reasonid	bigint
	reasontype	varchar(2500)
	wrklflowstatusid	varchar(50)
	inserteddatetime	timestamp DEFAULT CURRENT_TIMESTAMP
	k1k2_flag	smallint DEFAULT 2
	reasontypek	varchar(500)

Indexes

Type	Name	On
Pk	pk_reasonmaster	reasonid

Table reasonmaster_k1

Idx	Name	Data Type
	reasonid	bigint
	reasonid_k1	integer
	reasontype	varchar(2500)
	wrklflowstatusid	varchar(50)
	inserteddatetime	timestamp
	k1k2_flag	smallint
	reasontypek	varchar(500)

Table receiptdetails

Idx	Name	Data Type
*	receiptid	bigint
*	srocode	integer
*	feerulecode	integer
	deptsubpurposeid	integer
	amountpaid	decimal(23,4)
	inserteddatetime	timestamp DEFAULT CURRENT_TIMESTAMP
	k1k2_flag	smallint DEFAULT 2

Table receiptdetails_cd140

Idx	Name	Data Type
	receiptid	bigint
	srocode	integer
	feerulecode	integer
	deptsubpurposeid	integer
	amountpaid	decimal(23,4)

Table receiptdetails_cd140

	inserteddatetime	timestamp
	k1k2_flag	smallint

Table receiptmaster

Idx	Name	Data Type
* Pk	receiptid	bigint
* Idx	documentid	bigint
* Pk	srocode	integer
*	receipttypeid	integer
*	receiptnumber	integer
*	partyid	bigint
* Pk	dateofreceipt	timestamp
*	isprinted	boolean
	printbanner	varchar(75)
	docreturntime	timestamp
Idx	applicationnumber	varchar(75)
	totalamount	decimal(23,4)
	k1k2_flag	smallint DEFAULT 2
	inserteddatetime	timestamp DEFAULT CURRENT_TIMESTAMP

Indexes

Type	Name	On
	receiptmaster_documentid_idx	documentid
	idx_receiptmaster_appno	applicationnumber
Pk	pk_receiptmaster	receiptid, srocode, dateofreceipt

Table receiptmaster_cd140

Idx	Name	Data Type
	receiptid	bigint
	documentid	bigint
	srocode	integer
	receipttypeid	integer
	receiptnumber	integer
	partyid	bigint
	dateofreceipt	timestamp
	isprinted	boolean
	printbanner	varchar(75)
	docreturntime	timestamp
	applicationnumber	varchar(75)
	totalamount	decimal(23,4)
	k1k2_flag	smallint
	inserteddatetime	timestamp

Table receiptpaymentdetails

Idx	Name	Data Type
* Idx	receiptid	bigint
* Idx	srocode	integer
*	paymentmodeid	integer
	description	varchar(250)

Table receiptpaymentdetails

	ddnumber	varchar(20)
	dddate	timestamp
	ifsccodeid	integer
	ifsccode	varchar(20)
	micrcode	decimal(9,0)
	amount	decimal(23,4)
	id	bigint
	inserteddatetime	timestamp DEFAULT CURRENT_TIMESTAMP
	k1k2_flag	smallint DEFAULT 2

Indexes

Type	Name	On
	receiptpaymentdetails_receiptid_idx	receiptid
	receiptpaymentdetails_srocode_idx	srocode
	receiptpaymentdetailss_receiptid_idx	receiptid

Table receiptpaymentdetails_cd140

Idx	Name	Data Type
	receiptid	bigint
	srocode	integer
	paymentmodeid	integer
	description	varchar(250)
	ddnumber	varchar(20)
	dddate	timestamp
	ifsccodeid	integer
	ifsccode	varchar(20)
	micrcode	decimal(9,0)
	amount	decimal(23,4)
	id	bigint
	inserteddatetime	timestamp
	k1k2_flag	smallint

Table receipttypemaster

Idx	Name	Data Type
* Pk	receipttypeid	integer
	descriptionkannada	varchar(75)
	descriptionenglish	varchar(75)
*	isdocreceipt	boolean
	inserteddatetime	timestamp DEFAULT CURRENT_TIMESTAMP
	k1k2_flag	smallint DEFAULT 2

Indexes

Type	Name	On
Pk	pk_receipttypemaster	receipttypeid

Table referencemaster

Idx	Name	Data Type
* Pk	refid	integer DEFAULT nextval('kaveri.referencemaster_refid_seq'::regclass)
Idx	documentid	bigint

Table referencemaster

* Idx	srocode	bigint
	trid	integer
	throughid	integer
*	referencetext	varchar(1000)
	revenueofficerno	varchar(50)
	court_no	varchar(50)
	revenuedate	timestamp
	courtdate	timestamp
	documenttypeid	integer
	registrationid	bigint
	noticeid	bigint
	istransmitted	boolean
	olddocumentid	bigint
	bookid	integer
	year	varchar(10)
	stampduty	decimal(18,4)
	registrationfees	decimal(18,4)
	bankname	varchar(100)
	ddnumber	varchar(50)
	dddate	timestamp
	courtordernumber	integer
	courtorderdate	timestamp
	nameofcourt	varchar(100)
	receiptnumber	varchar(50)
	remiteddate	timestamp
	endorsementdate	timestamp
	partyname	varchar
	documentnumber	integer
	isregisterinnewbifurcatedoffice	boolean
	volumnnumber	integer
	frompagenumber	integer
	topagenumber	integer
	uploadcourtorderpath	varchar(1000)
	lstupddate	timestamp DEFAULT CURRENT_TIMESTAMP
	remittedtypeid	bigint
	oldisregisterinnewbifurcatedoffice	boolean
	k1k2_flag	smallint DEFAULT 2

Indexes

Type	Name	On
Pk	pk_refid_referencemaster	refid
	uniq_docidsrocode_referencemaster	srocode, documentid

Table referencesthroghmaster

Idx	Name	Data Type
* Pk	throghid	integer
*	throghtype	varchar(50)
	inserteddatetime	timestamp DEFAULT CURRENT_TIMESTAMP
	k1k2_flag	smallint DEFAULT 2

Table referencesthroghmaster

Indexes

Type	Name	On
Pk	pk_referencesthroghmaster	throghid

Table referencetransactionmaster

Idx	Name	Data Type
* Pk	trid	integer
*	type	varchar(50)
	k1k2_flag	smallint DEFAULT 2

Indexes

Type	Name	On
Pk	pk_referencetransactionmaster	trid

Table regionmaster

Idx	Name	Data Type
* Pk	regionid	integer
*	regionname	varchar(50)
Idx	isactive	boolean
	inserteddatetime	timestamp DEFAULT CURRENT_TIMESTAMP
	k1k2_flag	smallint DEFAULT 2

Indexes

Type	Name	On
Pk	regionmaster_pkey	regionid
	idx_regionmaster	regionid, isactive

Table regionpvg

Idx	Name	Data Type
* Pk	villagecode	bigint
* Pk	regionid	char(10)
	k1k2_flag	smallint DEFAULT 2

Indexes

Type	Name	On
Pk	pk_villagecode_regionid_regionpvg	villagecode, regionid

Table registrationarticles

Idx	Name	Data Type
* Pk	regarticlecode	integer
*	articlenamek	varchar(250)
*	articlenamee	varchar(250)
	userarticleno	varchar(50)
	bookid	integer
*	getbhoomidata	boolean
	k1k2_flag	smallint DEFAULT 2
	isactive	boolean DEFAULT true

Indexes

Type	Name	On
Pk	pk_registrationarticles	regarticlecode

Table registrationlog

Idx	Name	Data Type
*	logid	bigint DEFAULT nextval('kaveri.registrationlog_logid_seq'::regclass)
*	srocode	integer
*	userid	integer
*	documentid	bigint
*	computername	varchar(100)
*	logdatetime	timestamp
	inserteddatetime	timestamp DEFAULT CURRENT_TIMESTAMP
	k1k2_flag	smallint DEFAULT 2

Table registrationotpdetails

Idx	Name	Data Type
* Pk	id	bigint DEFAULT nextval('kaveri.registrationotpdetails_id_seq'::regclass)
	mobile	bigint
	email	varchar(40)
	mobileotp	integer
	emailotp	integer
*	inserteddatetime	timestamp DEFAULT CURRENT_TIMESTAMP
	k1k2_flag	integer DEFAULT 2
	otpcount	integer

Indexes

Type	Name	On
Pk	registrationotpdetails_pkey	id

Table relationshipmasters

Idx	Name	Data Type
* Pk	id	integer
	relationk	varchar(50)
Unq	relatione	varchar(50)
	mojiniid	smallint
	eaasthiid	smallint
	isactive	smallint
	inserteddatetime	timestamp DEFAULT CURRENT_TIMESTAMP
	k1k2_flag	smallint DEFAULT 2

Indexes

Type	Name	On
Unq	uk_relatione_relationmstr	relatione
Pk	pk_id_relationmstr	id

Table remittedtypemaster

Idx	Name	Data Type
* Pk	remittedtypeid	integer DEFAULT nextval('kaveri.remittedtypemaster_remittedtypeid_seq'::regclass)
	remittedtypedescription	varchar(1000)
	lstupddate	timestamp DEFAULT CURRENT_TIMESTAMP
	k1k2_flag	smallint DEFAULT 2

Indexes

Table remittedtypemaster

Type	Name	On
Pk	remittedtypemaster_pkey	remittedtypeid

Table rescandetails

Idx	Name	Data Type
* Pk	documentid	bigint
* Pk	documenttypeid	integer
	pages	integer
	localpath	varchar(100)
	backuppath	varchar(100)
	filename	varchar(256)
	filesize	bigint
	scandate	timestamp
	starttime	timestamp
	endtime	timestamp
	cdid	integer
	checksum	bigint
*	istransmitted	boolean
	uid	integer
*	isuploaded	boolean
	newcdnumber	varchar(50)
	logdatetime	timestamp
	inserteddatetime	timestamp DEFAULT CURRENT_TIMESTAMP
	k1k2_flag	smallint DEFAULT 2

Indexes

Type	Name	On
Pk	pk_rescandetails	documentid, documenttypeid

Table revised_form_7_statutory

Idx	Name	Data Type
	districtname	varchar
	sroname	varchar
	finalregistrationnumber	varchar
	applicationnumber2	varchar
	presentationdatetime	text
	presenter_name	text
	description_of_document	varchar
	considerationamount	decimal
	marketvalue	bigint
	stampduty	decimal
	cess	decimal
	surcharge_duty_muncipal	decimal
	surcharge_duty_taluk	decimal
	total_duty	decimal
	documentnumber	varchar
	bookid	varchar
	volumenumber	text
	dateofcompletion	text

Table revised_form_7_statutory

	dateofreturn	text
	registrationfees	decimal
	feescopygranted	decimal
	miscfees	decimal
	otherstampduty	decimal
	miscarticlefees	decimal
	total_fees	decimal
	treasury_fees	decimal
	feedate_treasury	text
	dailymutationreceipts	text
	mutationfees	decimal
	mutationfeedate	text
	transmission_of_memorandum	text
	transmission_of_memoranda	text
	total_amount_collected	bigint
	signature_of_register	text
	remarks	text
	copy_of_document	text
	totalcount	bigint

Table revised_form_7_statutory_cc

Idx	Name	Data Type
Idx	applicationnumber	varchar(50)
	dateofpresenter	date
	nameofpresenter	text
	descriptionofdocument	text
	consideration	text
	marketvalue	text
	stampduty	decimal
	cessonduty	text
	muncipal	text
	talukboard	text
	numberinregister	varchar(50)
	book	text
	volumeno	text
	dateofcompletion	date
	dateofreturn	date
	feesforregistrationofdocuments	text
	feesforcopiesgranted	decimal
	scanningfees	text
	otherstampduty	text
	articletableoffees	text
	feesremittedtotreasuryamount	decimal
	feesremittedtotreasurydate	date
	dailymutationreceipts	text
	mutationfeeremittedtotreasurywithdate	text
	copiestowhichdateoffice	text
	memorandatowhichdateoffice	text

Table revised_form_7_statutory_cc

	signatureofregisteringofficer	text
	remarks	text

Indexes

Type	Name	On
	idx_revised_form_7_statutory_cc_appno	applicationnumber

Table revised_form_7_statutory_cc_reg

Idx	Name	Data Type
	districtname	varchar
	sroname	varchar
	finalregistrationnumber	text
	applicationnumber2	varchar
	presentationdatetime	text
	presenter_name	text
	description_of_document	text
	considerationamount	decimal
	marketvalue	decimal
	stampduty	decimal
	cess	decimal
	surcharge_duty_muncipal	decimal
	surcharge_duty_taluk	decimal
	total_duty	decimal
	documentnumber	varchar
	bookid	text
	volumenumber	text
	dateofcompletion	text
	dateofreturn	text
	registrationfees	text
	feescopygranted	decimal
	miscfees	decimal
	otherstampduty	decimal
	miscarticlefees	decimal
	total_fees	decimal
	treasury_fees	decimal
	feedate_treasury	text
	dailymutationreceipts	text
	mutationfees	decimal
	mutationfeedate	text
	transmission_of_memorandum	text
	transmission_of_memoranda	text
	total_amount_collected	bigint
	signature_of_register	text
	remarks	text
	copy_of_document	text
	totalcount	bigint

Table revised_form_7_statutory_doc_reg

Idx	Name	Data Type

Table revised_form_7_statutory_doc_reg

	districtname	varchar
	sroname	varchar
	finalregistrationnumber	varchar
	applicationnumber2	varchar
	presentationdatetime	text
	presenter_name	text
	description_of_document	varchar
	considerationamount	decimal
	marketvalue	bigint
	stampduty	decimal
	cess	decimal
	surcharge_duty_muncipal	decimal
	surcharge_duty_taluk	decimal
	total_duty	decimal
	documentnumber	varchar
	bookid	varchar
	volumenumber	text
	dateofcompletion	text
	dateofreturn	text
	registrationfees	decimal
	feescopygranted	decimal
	miscfees	decimal
	otherstampduty	decimal
	miscarticlefees	decimal
	total_fees	decimal
	treasury_fees	decimal
	feedate_treasury	text
	dailymutationreceipts	text
	mutationfees	decimal
	mutationfeedate	text
	transmission_of_memorandum	text
	transmission_of_memoranda	text
	total_amount_collected	bigint
	signature_of_register	text
	remarks	text
	copy_of_document	text
	totalcount	bigint

Table revised_form_7_statutory_ec

Idx	Name	Data Type
Idx	applicationnumber	varchar(50)
	dateofpresenter	date
	nameofpresenter	text
	descriptionofdocument	text
	consideration	text
	marketvalue	text
	stampduty	text
	cessonduty	text

Table revised_form_7_statutory_ec

	muncipal	text
	talukboard	text
	numberinregister	varchar(50)
	book	text
	volumeno	text
	dateofcompletion	date
	dateofreturn	date
	feesforregistrationofdocuments	text
	feesforcopiesgranted	decimal
	scanningfees	text
	otherstampduty	text
	articletableoffees	text
	feesremittedtotreasuryamount	decimal
	feesremittedtotreasurydate	date
	dailymutationreceipts	text
	mutationfeeremittedtotreasurywithdate	text
	copiestowhichdateoffice	text
	memorandatowhichdateoffice	text
	signatureofregisteringofficer	text
	remarks	text

Indexes

Type	Name	On
	idx_revised_form_7_statutory_ec_appno	applicationnumber

Table revised_form_7_statutory_ec_reg

Idx	Name	Data Type
	districtname	varchar
	sroname	varchar
	finalregistrationnumber	text
	applicationnumber2	varchar
	presentationdatetime	text
	presenter_name	text
	description_of_document	text
	considerationamount	decimal
	marketvalue	decimal
	stampduty	decimal
	cess	decimal
	surcharge_duty_muncipal	decimal
	surcharge_duty_taluk	decimal
	total_duty	decimal
	documentnumber	varchar
	bookid	text
	volumenumber	text
	dateofcompletion	text
	dateofreturn	text
	registrationfees	text
	feescopygranted	decimal
	miscfees	decimal

Table revised_form_7_statutory_ec_reg

	otherstampduty	decimal
	miscarticlefees	decimal
	total_fees	decimal
	treasury_fees	decimal
	feedate_treasury	text
	dailymutationreceipts	text
	mutationfees	decimal
	mutationfeedate	text
	transmission_of_memorandum	text
	transmission_of_memoranda	text
	total_amount_collected	bigint
	signature_of_register	text
	remarks	text
	copy_of_document	text
	totalcount	bigint

Table roadmaster

Idx	Name	Data Type
* Pk	roadcode	bigint
*	roadnamee	varchar(2000)
*	roadnamek	varchar(2000)
* Idx	villagecode	bigint
	roadref	bigint
* Idx	isactive	boolean DEFAULT true
	regionid	integer
	k1k2_flag	smallint DEFAULT 2

Indexes

Type	Name	On
	idx_roadmaster_villagecode	villagecode
Pk	pk_roadmaster1	roadcode
	idx_roadmaster	villagecode, isactive

Table roadmaster_kaveri1

Idx	Name	Data Type
* Pk	roadcode	decimal(10,0)
*	roadnamee	varchar(2000)
*	roadnamek	varchar(2000)
*	villagecode	decimal(10,0)
	roadref	decimal(10,0)
*	isactive	smallint
	regionid	integer

Indexes

Type	Name	On
Pk	pk_roadmaster	roadcode

Table roadmaster_prod

Idx	Name	Data Type
	roadcode	bigint

Table roadmaster_prod

	roadnamee	varchar(2000)
	roadnamek	varchar(2000)
	villagecode	bigint
	roadref	bigint
	isactive	boolean
	regionid	integer
	k1k2_flag	smallint

Table roadmasterdmp

Idx	Name	Data Type
	roadcode	integer
	roadnamee	varchar(128)
	roadnamek	varchar(128)
	villagecode	integer
	roadref	integer
	isactive	boolean
	regionid	integer
	k1k2_flag	integer
	rate	integer
	openbuildratecode	bigint
	flatrateid	bigint

Table role_module_function_mapping

Idx	Name	Data Type
* Pk	rollid	integer
*	moduleid	integer
	submoduleid	integer
Idx	functionid	integer
* Pk	mappigid	integer DEFAULT nextval('kaveri.function_mapping_seq'::regclass)

Indexes

Type	Name	On
Pk	pk_role_module_function_mapping	rollid, mappigid
	idx_role_functionid_module_function_mapping	rollid, functionid
	idx_role_module_function_mapping	rollid

Table rule17filing

Idx	Name	Data Type
* Pk	requestid	integer DEFAULT nextval('kaveri.rule17filing_requestid_seq'::regclass)
*	applicationnumber	varchar(50)
	communicationnumber	varchar(1000)
	srocode	integer
	bookid	integer
*	registrationarticle	integer
	stamparticle	integer
	dateofcommunication	timestamp
	datecreated	timestamp DEFAULT CURRENT_TIMESTAMP
	stampruleid	integer

Table rule17filing

	currentstatus	varchar(5)
	scannedform	varchar
	indexiisummary	varchar
	endorsementdocument	varchar
	courtdocument	varchar
	olddocumentnumber	varchar(50)

Indexes

Type	Name	On
Pk	rule17filing_pkey	requestid

Table rule17filingremarks

Idx	Name	Data Type
* Pk	verificationid	integer DEFAULT nextval('kaveri.rule17filingremarks_verificationid_seq'::regclass)
	applicationnumber	varchar(50)
	propertydetailsremarks_fda	varchar(200)
	propertydetailsverified_fda	boolean
	boundarydetailsremarks_fda	varchar(200)
	boundarydetailsverified_fda	boolean
	scheduledesciptiondetailsremarks_fda	varchar(200)
	scheduledesciptiondetailsverified_fda	boolean
	partydetailsremarks_fda	varchar(200)
	partydetailsverified_fda	boolean
	verificationdatetime_fda	timestamp DEFAULT CURRENT_TIMESTAMP
	propertydetailsremarks_sr	varchar(200)
	propertydetailsverified_sr	boolean
	boundarydetailsremarks_sr	varchar(200)
	boundarydetailsverified_sr	boolean
	scheduledesciptiondetailsremarks_sr	varchar(200)
	scheduledesciptiondetailsverified_sr	boolean
	partydetailsremarks_sr	varchar(200)
	partydetailsverified_sr	boolean
	canpreocesstopaymentremarks_sr	varchar(200)
	canpreocesstopaymentverified_sr	boolean
	verificationdatetime_sr	timestamp DEFAULT CURRENT_TIMESTAMP
	propertydetailsremarks_sda	varchar(200)
	propertydetailsverified_sda	boolean
	boundarydetailsremarks_sda	varchar(200)
	boundarydetailsverified_sda	boolean
	scheduledesciptiondetailsremarks_sda	varchar(200)
	scheduledesciptiondetailsverified_sda	boolean
	partydetailsremarks_sda	varchar(200)
	partydetailsverified_sda	boolean
	canpreocesstopaymentremarks_sda	varchar(200)
	canpreocesstopaymentverified_sda	boolean
	verificationdatetime_sda	timestamp DEFAULT CURRENT_TIMESTAMP
	inserteddatetime	timestamp DEFAULT CURRENT_TIMESTAMP
	k1k2_flag	smallint DEFAULT 2

Indexes

Table rule17filingremarks

Type	Name	On
Pk	rule17filingremarks_pkey	verificationid

Table sakala_department_officecodemaster

Idx	Name	Data Type
* Pk	designoffcode	integer
	officeid	integer
	officename	varchar(250)

Indexes

Type	Name	On
Pk	pk_officecode	designoffcode

Table sakala_marriagepartydetails

Idx	Name	Data Type
* Pk	sakalaid	bigint
*	srocode	integer
*	gscno	varchar
*	registrationid	bigint
*	firstname	varchar(150)
	middlename	varchar(150)
	lastname	varchar(300)
*	address1	varchar(250)
*	address2	varchar(250)
	mobile	varchar(15)
*	servicetype	varchar(3)
	subservicetype	varchar(3)
	enclsubmittedlist	varchar(2000)
*	enclsubmitted	boolean
	marriagetype	integer
	k1k2_flag	smallint DEFAULT 2

Indexes

Type	Name	On
Pk	sakala_marriagepartydetails_pkey	sakalaid

Table sakala_orphan_settle_log

Idx	Name	Data Type
* Pk	sid	bigint DEFAULT nextval('kaveri.sakala_orphan_settle_log_sid'::regclass)
*	gscno	varchar(15)
	srocode	integer
	webmethod	varchar(50)
	isuploaded	boolean
	uploaddatetime	timestamp
	processingcode	integer
	processingstatus	varchar(200)
	recordsinserted	integer
	errordatacount	integer
	inputdataset	varchar(1000)

Table sakala_orphan_settle_log

	transferdatetime	timestamp
	istransmitted	boolean
	isdeliverytransmitted	boolean
	isprocessed	boolean
	k1k2_flag	smallint DEFAULT 2
	inserteddatetime	timestamp DEFAULT CURRENT_TIMESTAMP

Indexes

Type	Name	On
Pk	pk_sakala_orphan_settle_log_sid	sid

Table sakala_partydetails

Idx	Name	Data Type
* Pk	gscno	varchar(15)
*	documentid	bigint
*	srocode	integer
*	firstname	varchar(150)
	middlename	varchar(150)
	lastname	varchar(300)
*	address1	varchar(250)
*	address2	varchar(250)
	mobile	varchar(10)
*	servicetype	varchar(3)
	subservicetype	varchar(3)
	enclsubmittedlist	varchar(200)
*	enclsubmitted	boolean
	referenceno	varchar(50)
	k1k2_flag	smallint DEFAULT 2
	inserteddatetime	timestamp DEFAULT CURRENT_TIMESTAMP

Indexes

Type	Name	On
Pk	pk_gscno_sakala_partydetails	gscno

Table sakala_transactionerrorlog

Idx	Name	Data Type
*	logid	bigint
*	srocode	integer
*	gscno	varchar(15)
*	logdatetime	timestamp
*	description	text
	inserteddatetime	timestamp DEFAULT CURRENT_TIMESTAMP
	k1k2_flag	smallint DEFAULT 2

Table sakala_uploadfiledetails

Idx	Name	Data Type
*	sid	bigint
Idx	gscno	varchar(15)
*	srocode	integer
Idx	webmethod	varchar(50)

Table sakala_uploadfiledetails

*	isuploaded	boolean
	uploaddatetime	timestamp
* Idx	processingcode	integer
	processingstatus	varchar(500)
*	recordsinserted	integer
*	errordatacount	integer
	inputdataset	text
*	transferdatetime	timestamp
	istransmitted	boolean
	isdeliverytransmitted	boolean
	k1k2_flag	smallint DEFAULT 2
	inserteddatetime	timestamp DEFAULT CURRENT_TIMESTAMP
Idx	applicationnumber	varchar(50)

Indexes

Type	Name	On
	idx_gscno	gscno
	idx_status	webmethod
	idx_processingcode	processingcode
	idx_sakala_uploadfiledetails_appno	applicationnumber

Table sakalaservicecodemaster

Idx	Name	Data Type
* Pk	slno	integer
	serviceid	integer
	servicename	varchar(100)
	subserviceid	integer
	subservicename	varchar(100)
	sakalaservicecode	bigint
	isactive	boolean
	inserteddatetime	timestamp
	k1k2_flag	smallint

Indexes

Type	Name	On
Pk	sakalaservicecode_pkey1	slno

Table sakalasubservicecodemaster

Idx	Name	Data Type
* Pk	slno	integer
	sakalaservicecode	bigint
	fromyearduration	bigint
	toyearduration	bigint
	sakalasubservicecode	bigint
	isactive	boolean DEFAULT true
	k1k2_flag	smallint DEFAULT 2
	inserteddatetime	timestamp DEFAULT (CURRENT_DATE)::timestamp without time zone

Indexes

Type	Name	On
Pk	sakalasubservicecodemaster_pkey1	slno

Table salutationmaster

Idx	Name	Data Type
* Pk	salutationid	smallint
*	descriptione	varchar(50)
*	descriptionk	varchar(50)
	isactive	boolean
	k1k2_flag	smallint DEFAULT 2

Indexes

Type	Name	On
Pk	pk_salutationmaster	salutationid

Table scanmaster

Idx	Name	Data Type
* Pk	documentid	bigint
* Pk	srocode	integer
* Pk	documenttypeid	integer
	pages	integer
	localpath	varchar(100)
	backuppath	varchar(100)
	filename	varchar(256)
	filesize	bigint
	scandate	timestamp
	starttime	timestamp
	endtime	timestamp
	cdid	integer
	checksum	bigint
	uid	integer
	isuploaded	boolean
	istransmitted	boolean
	k1k2_flag	smallint DEFAULT 2
	inserteddatetime	timestamp DEFAULT CURRENT_TIMESTAMP

Indexes

Type	Name	On
Pk	pk_docidsrocode_scanmaster	documentid, srocode, documenttypeid

Table scannedfileuploaddetails

Idx	Name	Data Type
*	documentid	bigint
*	srocode	integer
*	scannedfilename	varchar(256)
*	uploadpath	varchar(500)
*	uploaddatetime	timestamp
	rootdirectory	varchar(1500)
*	documenttypeid	integer
	inserteddatetime	timestamp DEFAULT CURRENT_TIMESTAMP
	k1k2_flag	smallint DEFAULT 2

Table scn_frm_scandetails

Idx	Name	Data Type

Table scn_frm_scandetails

* Pk	scanid	bigint
*	officeid	smallint
*	processmappingid	smallint
	firmid	bigint
	amendmentid	bigint
	dissolutionid	bigint
*	scanforwarddate	timestamp
*	pages	smallint
	filename	varchar
	filesize	bigint
	localpath	varchar
	fileserverpath	varchar
	virtualserverpath	varchar
	scandate	timestamp
	starttime	timestamp
	endtime	timestamp
	isuploaded	boolean
	checksum	varchar
	scannedbyuserid	bigint
	scannedbyresourceid	integer
	uploadedbyuserid	bigint
	uploadedbyresourceid	integer
	uploaddatetime	timestamp
	isapproved	boolean
	approveddate	timestamp
	isdigitalsign	boolean
	k1k2_flag	smallint DEFAULT 2
	inserteddatetime	timestamp DEFAULT CURRENT_TIMESTAMP

Indexes

Type	Name	On
Pk	scn_frm_scandetails_pkey	scanid

Table scrutiny_remarks_mapping

Idx	Name	Data Type
*	mapping_id	bigint DEFAULT nextval('kaveri.scrutiny_remarks_mapping_seq'::regclass)
* Idx	stampruleid	bigint
* Idx	remarksid	bigint
*	isactive	boolean DEFAULT true

Indexes

Type	Name	On
	scrutiny_remarks_mapping_stampruleid_idx	stampruleid
	scrutiny_remarks_mapping_remarksid_idx	remarksid

Table scrutinyfeechange

Idx	Name	Data Type
*	id	bigint DEFAULT nextval('kaveri.scruitnyfeechange_id_seq'::regclass)
	feerulecode	integer

Table scrutinyfeechange

Idx	applicationnumber	varchar(50)
	amountrequired	decimal(23,4)
	sroamountrequired	decimal(23,4)
	sfdaamountrequired	decimal(23,4)
	auditoramountrequired	decimal(23,4)
	inserteddatetime	timestamp DEFAULT CURRENT_TIMESTAMP
	propertyid	bigint
	documentid	bigint
	lastupdated	timestamp DEFAULT CURRENT_TIMESTAMP

Indexes

Type	Name	On
	scrutinyfeechange_applicationnumber_idx	applicationnumber

Table scrutinyremarks

Idx	Name	Data Type
* Pk	id	bigint DEFAULT nextval('kaveri.scruitnyremarks_id_seq'::regclass)
Idx	applicationnumber	varchar(50)
Idx	stamparticlecode	bigint
Idx	remarkid	integer
	auditorremarks	text
	inserteddatetime	timestamp DEFAULT CURRENT_TIMESTAMP

Indexes

Type	Name	On
Pk	pk_applicationforscruitnyremarks_ids	id
	scrutinyremarks_applicationnumber_idx	applicationnumber
	scrutinyremarks_stamparticlecode_idx	stamparticlecode
	scrutinyremarks_remarkid_idx	remarkid

Table scrutinyremarksmaster

Idx	Name	Data Type
* Pk	remarkid	bigint DEFAULT nextval('kaveri.scruitnyremarksmaster_remarkid_seq'::regclass)
Idx	remarks_title_id	bigint
	remarkse	varchar(1000)
	remarksk	varchar(1000)
	isactive	boolean
	inserteddatetime	timestamp DEFAULT CURRENT_TIMESTAMP

Indexes

Type	Name	On
Pk	pk_scruitnyremarksmaster_id	remarkid
	scrutinyremarksmaster_remarks_title_id_idx	remarks_title_id

Table scrutinyremarkstitle

Idx	Name	Data Type
* Pk	id	bigint DEFAULT nextval('kaveri.scrutinyremarkstitle_id_seq'::regclass)
	stamparticlecode	integer
	titlek	varchar(1000)
	inserteddatetime	timestamp DEFAULT CURRENT_TIMESTAMP

Table scrutinyremarkstitle

Indexes

Type	Name	On
Pk	pk_scrutinyremarkstitle_id	id

Table securityqstmaster

Idx	Name	Data Type
* Pk	securityqstid	smallint
*	questione	varchar(50)
	questionk	varchar(50)
	crtusr	varchar(10)
	crtdt	timestamp DEFAULT now()
	lstupusr	varchar(10)
	lstupddt	timestamp DEFAULT now()
	k1k2_flag	smallint DEFAULT 2

Indexes

Type	Name	On
Pk	pk_securityqstmaster	securityqstid
	idx_securityqstmaster	securityqstid

Table servicesmaster

Idx	Name	Data Type
* Pk	serviceid	integer
	servicename	varchar(100)
	nomenclature	varchar(3)
	servicenamer	varchar(100)
	serviceopentime	time
	serviceclosetime	time
	dateadded	timestamp
	isactive	boolean
	isonline	boolean
	isotpservice	boolean
	kaveri_ii_serviceid	integer
	k1k2_flag	smallint DEFAULT 2
	inserteddatetime	timestamp DEFAULT CURRENT_TIMESTAMP

Indexes

Type	Name	On
Pk	pk_servicesmaster	serviceid

Table signed_file_upload_details

Idx	Name	Data Type
* Unq	fileid	text
Idx	applicationnumber	varchar
	filepath	text
*	inserteddatetime	timestamp DEFAULT CURRENT_TIMESTAMP

Indexes

Type	Name	On
	idx_signed_file_upload_details_appno	applicationnumber
Unq	uk_file_upload_details_fileidentifier_ccnew	fileid

Table signed_file_upload_details

Unq	uk_file_upload_details_fileidentifier_ccnew1	fileid
Unq	uk_file_upload_details_fileidentifier	fileid

Table skipped_document_numbers

Idx	Name	Data Type
*	id	bigint DEFAULT nextval('kaveri.skipped_document_numbers_id_seq'::regclass)
	srocode	integer
	documentnumber	integer
	bookid	integer
	finyear	varchar(20)
	finalregistrationnumber	varchar(50)
	applicationnumber	varchar(50)
	reason	text
	inserteddatetime	timestamp DEFAULT CURRENT_TIMESTAMP

Table slotconfigurationmaster

Idx	Name	Data Type
* Pk	slotconfigid	integer DEFAULT nextval('kaveri.slotconfigurationmaster_slotconfigid_seq'::regclass)
	srocode	integer
	shiftstarttime	time
	shiftendtime	time
	timetakenforbiometric	integer
	timetakenfor1pgscan	integer
	timetakenforsignature	integer
	timetakenforsrverification	integer
	timetakenbydeo	integer
	timetakenfordigisigning	integer
	timetakenforacknowledgement	integer
	k1k2_flag	smallint DEFAULT 2
	vipwindowstarttime	time
	vipwindowendtime	time
	scrutinywindowstarttime	time
	scrutinywindowendtime	time
	vipapplicationallowedmax	integer

Indexes

Type	Name	On
Pk	slotconfigurationmaster_pkey	slotconfigid

Table slotmaster

Idx	Name	Data Type
* Pk	sltid	bigint DEFAULT nextval('kaveri.slotmaster_sltid_seq'::regclass)
* Unq	srocode	integer
*	serviceid	integer
* Unq	sltdate	date
* Unq	sltstarttime	time
* Unq	sltendtime	time
	sltcapacity	integer DEFAULT 0

Table slotmaster

	sltavlcapacity	integer DEFAULT 0
	sltisactive	boolean DEFAULT true
	isexpress	boolean DEFAULT false
	sltcomments	text
	crtusr	varchar(10)
	crtdt	timestamp DEFAULT CURRENT_TIMESTAMP
	lstupusr	varchar(10)
	lstupddt	timestamp
	k1k2_flag	smallint DEFAULT 2

Indexes

Type	Name	On
Pk	slotmaster_pkey	sltid
Unq	uk_slotmaster	srocode, sltdate, sltstarttime, sltendtime

Table slotsrvcstatusmaster

Idx	Name	Data Type
* Pk	slotsrvcid	integer DEFAULT nextval('kaveri.slotsrvcstatusmaster_slotsrvcid_seq'::regclass)
*	slotsrvcdescription	text

Indexes

Type	Name	On
Pk	pk_slotsrvcstatusmaster	slotsrvcid

Table slottxn

Idx	Name	Data Type
* Pk	sltbookingid	bigint DEFAULT nextval('kaveri.slottxn_sltbookingid_seq'::regclass)
	sltid	integer
*	sltbookedfor	integer
	sltbookedon	timestamp
*	sltbookedby	bigint
*	usrtypeid	integer
	sltservicestatus	integer
	sltreservice	boolean
	applicationnumber	varchar(50)
	appointmenttypeid	integer
	srocode	integer
	sltbookeddate	timestamp
	sltbooktime	text
	lstupddate	timestamp
	oldsltbookingid	bigint
	inserteddatetime	timestamp DEFAULT CURRENT_TIMESTAMP
	k1k2_flag	smallint DEFAULT 2

Indexes

Type	Name	On
Pk	slottxn_pkey	sltbookingid

Table sms_master

Idx	Name	Data Type

Table sms_master

* Pk	sms_id	bigint DEFAULT nextval('kaveri.sms_master_sms_id_seq'::regclass)
*	templateid	varchar(200)
	templatename	varchar(200)
	featurename	varchar(200)
	status	varchar(50)
	eta	varchar(100)
	type	varchar(200)
	header	varchar(200)
	templatemessage	text
	consenttype	varchar(200)
	k1k2_flag	smallint DEFAULT 2

Indexes

Type	Name	On
Pk	sms_master_pkey	sms_id

Table sms_transaction_details

Idx	Name	Data Type
* Pk	transaction_id	bigint DEFAULT nextval('kaveri.sms_transaction_details_transaction_id_seq'::regclass)
	templateid	bigint
	smsmobileto	varchar(50)
	smsmessage	text
	initiatedby	varchar(100)
	requestedon	timestamp
	senton	timestamp
	status	varchar(200)
	isdepartment	boolean
	isotp	boolean
	applicationnumber	varchar(100)
	lastupdated	timestamp DEFAULT CURRENT_TIMESTAMP
	lastupdatedby	varchar(100)
	inserteddatetime	timestamp DEFAULT CURRENT_TIMESTAMP
	k1k2_flag	smallint DEFAULT 2

Indexes

Type	Name	On
Pk	sms_transaction_details_pkey	transaction_id

Table sromaster

Idx	Name	Data Type
* Pk	srocode	integer DEFAULT nextval('kaveri.srocode_seq'::regclass)
Idx	districtcode	integer
	sronamek	varchar(100)
	sronamee	varchar(150)
	shortnamek	varchar(50)
	shortnamee	varchar(15)
*	enableanywherereg	boolean
*	getbhoomidata	boolean

Table sromaster

	registrationdocserial	bigint
	k1k2_flag	smallint DEFAULT 2
	islive	boolean

Indexes

Type	Name	On
	sromaster_districtcode_idx	districtcode
Pk	pk_sromaster	srocode

Table sromaster_prod1

Idx	Name	Data Type
	srocode	integer
	districtcode	integer
	sronamek	varchar(100)
	sronamee	varchar(150)
	shortnamek	varchar(50)
	shortnamee	varchar(15)
	enableanywherereg	boolean
	getbhoomidata	boolean
	registrationdocserial	bigint
	k1k2_flag	smallint
	islive	boolean

Table sroserialmaster

Idx	Name	Data Type
* Pk	srocode	integer
* Pk	bookid	integer
* Pk	finyear	varchar(20)
	pendingserial	bigint DEFAULT 0
	finalserial	bigint DEFAULT 0
	k1k2_flag	smallint DEFAULT 2

Indexes

Type	Name	On
Unq	pk_serialmaster_ccnew	srocode, bookid, finyear
Unq	pk_serialmaster_ccnew1	srocode, bookid, finyear
Pk	pk_serialmaster	srocode, bookid, finyear

Table srowrkingdayexemption

Idx	Name	Data Type
* Pk	id	bigint DEFAULT nextval('kaveri.srowrkingdayexemption_id_seq'::regclass)
	srocode	text
	workedate	timestamp
	isworked	boolean DEFAULT false

Indexes

Type	Name	On
Pk	srowrkingdayexemption_pkey	id

Table stamparticleoptions

Idx	Name	Data Type
* Pk	regarticlecode	integer
*	displaystampdutytab	boolean
*	scanningrequired	boolean
*	displaynoofpages	boolean
*	displaypropertyinfo	boolean
*	displayadmissiontab	boolean
*	displayidentificationtab	boolean
*	valuationrequired	boolean
*	singlesideregister	boolean
*	fixedstampduty	boolean
	considerationworde	varchar(100)
	considerationwordk	varchar(100)
	customregfee	boolean
	loadingmessage	varchar(250)
	inserteddatetime	timestamp DEFAULT CURRENT_TIMESTAMP
	k1k2_flag	smallint DEFAULT 2

Indexes

Type	Name	On
Pk	pk_stamparticleoptions	regarticlecode

Table stamparticles

Idx	Name	Data Type
* Pk	stamparticlecode	integer
*	articlenamek	varchar(200)
*	articlenamee	varchar(100)
	userarticleno	varchar(10)
	inserteddatetime	timestamp DEFAULT CURRENT_TIMESTAMP
	k1k2_flag	smallint DEFAULT 2

Indexes

Type	Name	On
Pk	pk_stamparticles	stamparticlecode

Table stampdetails

Idx	Name	Data Type
* Pk	stampdetailsid	integer
*	documentid	bigint
* Pk	srocode	integer
*	stamptypeid	integer
*	dateofstamp	timestamp
	ddchalnumber	varchar(750)
	ddchaldate	timestamp
	certifiedbyrbi	boolean
	certificationdetails	varchar(250)
	isonline	boolean
	ddnumber	varchar(20)
	ifccodeid	integer
	ifccode	varchar(20)

Table stampdetails

	micrcode	integer
	deptsubpurposeid	integer
	feerulecode	integer
	amount	decimal(23,4)
	areatypeid	integer
	stamppaymentdate	timestamp
	k1k2_flag	smallint DEFAULT 2
	inserteddatetime	timestamp DEFAULT CURRENT_TIMESTAMP

Indexes

Type	Name	On
Pk	pk_stampdetails	stampdetailsid, srocode

Table stampfeerulerelations

Idx	Name	Data Type
Unq	stampruleid	integer
Unq	feerulecode	integer
	inserteddatetime	timestamp DEFAULT CURRENT_TIMESTAMP
	k1k2_flag	smallint DEFAULT 2

Indexes

Type	Name	On
Unq	uk_stamprulefeerulecode	stampruleid, feerulecode

Table stampregrelations

Idx	Name	Data Type
* Pk	regarticlecode	integer
* Pk	stamparticlecode	integer
	inserteddatetime	timestamp DEFAULT CURRENT_TIMESTAMP
	k1k2_flag	smallint DEFAULT 2

Indexes

Type	Name	On
Pk	pk_stampregrelations	regarticlecode, stamparticlecode
	idx_stampregrelations_regarticlecdoe	regarticlecode

Table stamprules

Idx	Name	Data Type
* Pk	stampruleid	integer
* Idx	stamparticlecode	integer
	sameasarticleid	smallint
	parentrefid	smallint
*	haschild	boolean
*	descriptionk	varchar(500)
*	descriptione	varchar(500)
*	isslabs	boolean
*	unitisamount	boolean
	unitdescriptionk	varchar(150)
	unitdescriptione	varchar(150)
*	unit	double precision
*	value	decimal

Table stamprules

	minlimit	decimal
	maxlimit	decimal
	multipliedby	smallint
*	sdcalcon	char(2)
*	isinpercentage	boolean
*	isfixduty	boolean
*	isexempted	boolean
*	isruleactive	boolean
	regvalue	decimal
*	regispercent	boolean
	regmaxlimit	decimal
	regminlimit	decimal
*	regcalconconsideration	char(2)
	othercalcrule	integer
	othercalcon	char(2)
*	isaddonvalue	boolean
	addonvalue	decimal
	addoncaptione	varchar(150)
	addoncaptionk	varchar(150)
*	activefrom	timestamp
	activeto	timestamp
	issurcharge	boolean DEFAULT false
	urbanvalue	decimal DEFAULT 0
	ruralvalue	decimal DEFAULT 0
	issurchargepercentage	boolean DEFAULT false
	iscess	boolean DEFAULT false
	cessvalue	decimal DEFAULT 0
	iscesspercentage	boolean DEFAULT false
	ismarketvaluationdone	boolean
	isparttransactallowed	boolean
	bucketid	integer
	bookid	smallint
	k1k2_flag	smallint DEFAULT 2
	inserteddatetime	timestamp DEFAULT CURRENT_TIMESTAMP
*	isauditrequired	boolean DEFAULT false

Indexes

Type	Name	On
Pk	pk_stamprules	stampruleid
	idx_stamprules	stampruleid
	idx_stamprules_stamp	stamparticlecode

Table stamprules_preprod

Idx	Name	Data Type
	stampruleid	integer
	stamparticlecode	integer
	sameasarticleid	smallint
	parentrefid	smallint
	haschild	boolean

Table stamprules_preprod

	descriptionk	varchar(500)
	descriptione	varchar(500)
	isslabs	boolean
	unitisamount	boolean
	unitdescriptionk	varchar(150)
	unitdescriptione	varchar(150)
	unit	double precision
	value	decimal
	minlimit	decimal
	maxlimit	decimal
	multipliedby	smallint
	sdcalcon	char(2)
	isinpercentage	boolean
	isfixduty	boolean
	isexempted	boolean
	isruleactive	boolean
	regvalue	decimal
	regispercent	boolean
	regmaxlimit	decimal
	regminlimit	decimal
	regcalconconsideration	char(2)
	othercalcrule	integer
	othercalcon	char(2)
	isaddonvalue	boolean
	addonvalue	decimal
	addoncaptione	varchar(150)
	addoncaptionk	varchar(150)
	activefrom	timestamp
	activeto	timestamp
	issurcharge	boolean
	urbanvalue	decimal
	ruralvalue	decimal
	issurchargepercentage	boolean
	iscess	boolean
	cessvalue	decimal
	iscesspercentage	boolean
	ismarketvaluationdone	boolean
	isparttransactallowed	boolean
	bucketid	integer
	bookid	smallint
	k1k2_flag	smallint
	inserteddatetime	timestamp

Table stamprules_temp

Idx	Name	Data Type
	stampruleid	integer
	stamparticlecode	integer
	sameasarticleid	smallint

Table stamprules_temp

	parentrefid	smallint
	haschild	boolean
	descriptionk	varchar(500)
	descriptione	varchar(500)
	isslabs	boolean
	unitisamount	boolean
	unitdescriptionk	varchar(150)
	unitdescriptione	varchar(150)
	unit	double precision
	value	decimal
	minlimit	decimal
	maxlimit	decimal
	multipliedby	smallint
	sdcalcon	char(2)
	isinpercentage	boolean
	isfixduty	boolean
	isexempted	boolean
	isruleactive	boolean
	regvalue	decimal
	regispercent	boolean
	regmaxlimit	decimal
	regminlimit	decimal
	regcalconconsideration	char(2)
	othercalcrule	integer
	othercalcon	char(2)
	isaddonvalue	boolean
	addonvalue	decimal
	addoncaptione	varchar(150)
	addoncaptionk	varchar(150)
	activefrom	timestamp
	activeto	timestamp
	issurcharge	boolean
	urbanvalue	decimal
	ruralvalue	decimal
	issurchargepercentage	boolean
	iscess	boolean
	cessvalue	decimal
	iscesspercentage	boolean
	ismarketvaluationdone	boolean
	isparttransactallowed	boolean
	bucketid	integer
	bookid	smallint
	k1k2_flag	smallint
	inserteddatetime	timestamp

Table stamprulesflag

Idx	Name	Data Type
* Pk	stampruleid	integer

Table stamprulesflag

isagri	boolean
isnonagri	boolean
iswill	boolean
ismiscellaneous	boolean
isorganisationapplicable	boolean
ispoaapplicable	boolean
isminorguardianapplicable	boolean
isexemptionfrompersonalappearanceapplicable	boolean
isprivateattendanceapplicable	boolean
shouldwordpropertyappear	boolean
isownertobeclaimant	boolean
isconsiderationrequired	boolean
isexemptionapplicable	boolean
isdenotationapplicable	boolean
ismultiownerproperty	boolean
is11esketchrequired	boolean
ismutationfee	boolean
ispartytopropertyschd	boolean
isstampduty	boolean
isduplicatesd	boolean
isdeficitsd	boolean
isaffidavitsd	boolean
ispreamptionsd	boolean
iscertifiedcopysd	boolean
isregistrationfee	boolean
isduplicaterf	boolean
isconsentingfee	boolean
ismapfilingfee	boolean
ismemofee	boolean
isservicecharge	boolean
ispvtattendancefee	boolean
isrfus30	boolean
isdelaycondonationfee	boolean
isdelaycondonationfine	boolean
isappealfee	boolean
isdocumentwithdrawalfee	boolean
isholidayrf	boolean
iswilldepositfee	boolean
isfilingoftranslationfee	boolean
issafecustodyfee	boolean
isauthenticationorattestationpoa	boolean
ispershareowner	boolean
ismoneypaidbyowner	boolean
ismoneypaidbybuilder	boolean
isratepermonth	boolean
isnoofyears	boolean
isincrerateperyear	boolean
ispremiumroyaltymoneyadvanced	boolean
isfinalregnumreqd	boolean

Table stamprulesflag

	ispartextentreqd	boolean
	ismultiplescheduleregd	boolean
	ispartyshareregd	boolean
	isregisterable	boolean
	ismov	boolean
	minparty	integer
	minprop	integer
	ispartypropmap	boolean
	ismarketvaluation	boolean
	isconsideration	boolean
	ispresenter	boolean
	isconsentingwitness	boolean
	isidentifyingwitness	boolean
	isprotestapplicationfee	boolean
	xmltypeforeswathu	char(1)
	isconfiscatingagentreqd	boolean
	isprevregddocnoreqd	boolean
	iswillcancellation	boolean
	ispropertysearchreqd	boolean
	ispropertyscheduleapplicable	boolean
	ismultiproperty1consideration	boolean
	isjslipagri	boolean
	isjslipeqvltnonagri	boolean
	isclaimant	smallint
	isexecutant	smallint
	ownertypechange	boolean DEFAULT false
	inserteddatetime	timestamp DEFAULT CURRENT_TIMESTAMP
	k1k2_flag	smallint DEFAULT 2
	issubregistrarallocateapp	boolean
	isnameeditable	boolean DEFAULT false
	propdelete	boolean DEFAULT true
*	isownertabdeletable	boolean DEFAULT false

Indexes

Type	Name	On
Pk	pk_stamprulesflag	stampruleid

Table stamprulesflag_preprod

Idx	Name	Data Type
	stampruleid	integer
	isagri	boolean
	isnonagri	boolean
	iswill	boolean
	ismiscellaneous	boolean
	isorganisationapplicable	boolean
	ispoaapplicable	boolean
	isminorguardianapplicable	boolean
	isexemptionfrompersonalappearanceapplicable	boolean
	isprivateattendanceapplicable	boolean

Table stamprulesflag_preprod

shouldwordpropertyappear	boolean
isownertobeclaimant	boolean
isconsiderationrequired	boolean
isexemptionapplicable	boolean
isdenotationapplicable	boolean
ismultiownerproperty	boolean
is11esketchrequired	boolean
ismutationfee	boolean
ispartytopropertyschd	boolean
isstampduty	boolean
isduplicatesd	boolean
isdeficitsd	boolean
isaffidavitsd	boolean
ispreamptionsd	boolean
iscertifiedcopysd	boolean
isregistrationfee	boolean
isduplicaterf	boolean
isconsentingfee	boolean
ismapfilingfee	boolean
ismemofee	boolean
isservicecharge	boolean
ispvtattendancefee	boolean
isrfus30	boolean
isdelaycondonationfee	boolean
isdelaycondonationfine	boolean
isappealfee	boolean
isdocumentwithdrawalfee	boolean
isholidayrf	boolean
iswilldepositfee	boolean
isfilingoftranslationfee	boolean
issafecustodyfee	boolean
isauthenticationorattestationpoa	boolean
ispershareowner	boolean
ismoneypaidbyowner	boolean
ismoneypaidbybuilder	boolean
isratepermonth	boolean
isnoofyears	boolean
isincrerateperyear	boolean
ispremiumroyaltymoneyadvanced	boolean
isfinalregnumreqd	boolean
ispartextentreqd	boolean
ismultipleschedulereqd	boolean
ispartyshareregd	boolean
isregisterable	boolean
ismov	boolean
minparty	integer
minprop	integer
ispartypropmap	boolean
ismarketvaluation	boolean

Table stamprulesflag_preprod

	isconsideration	boolean
	ispresenter	boolean
	isconsentingwitness	boolean
	isidentifyingwitness	boolean
	isprotestapplicationfee	boolean
	xmltypeforeswathu	char(1)
	isconfiscatingagentreqd	boolean
	isprevregddocnoreqd	boolean
	iswillcancellation	boolean
	ispropertysearchreqd	boolean
	ispropertyscheduleapplicable	boolean
	ismultiproperty1consideration	boolean
	isjslipagri	boolean
	isjslipeqvltnonagri	boolean
	isclaimant	smallint
	isexecutant	smallint
	ownertypechange	boolean
	inserteddatetime	timestamp
	k1k2_flag	smallint
	issubregistrarallocateapp	boolean
	isnameeditable	boolean
	propdelete	boolean
	isownertabdeletable	boolean

Table stamprulesflag_tmp

Idx	Name	Data Type
	stampruleid	integer
	isagri	boolean
	isnonagri	boolean
	iswill	boolean
	ismiscellaneous	boolean
	isorganisationapplicable	boolean
	ispoaapplicable	boolean
	isminorguardianapplicable	boolean
	isexemptionfrompersonalappearanceapplicable	boolean
	isprivateattendanceapplicable	boolean
	shouldwordpropertyappear	boolean
	isownertobeclaimant	boolean
	isconsiderationrequired	boolean
	isexemptionapplicable	boolean
	isdenotationapplicable	boolean
	ismultiownerproperty	boolean
	is11esketchrequired	boolean
	ismutationfee	boolean
	ispartytopropertyschd	boolean
	isstampduty	boolean
	isduplicatesd	boolean
	isdeficitsd	boolean

Table stamprulesflag_tmp

isaffidavitsd	boolean
ispreamptionsd	boolean
iscertifiedcopysd	boolean
isregistrationfee	boolean
isduplicaterf	boolean
isconsentingfee	boolean
ismapfilingfee	boolean
ismemofee	boolean
isservicecharge	boolean
ispvtattendancefee	boolean
isrfus30	boolean
isdelaycondonationfee	boolean
isdelaycondonationfine	boolean
isappealfee	boolean
isdocumentwithdrawalfee	boolean
isholidayrf	boolean
iswilldepositfee	boolean
isfilingoftranslationfee	boolean
issafecustodyfee	boolean
isauthenticationorattestationpoa	boolean
ispershareowner	boolean
ismoneypaidbyowner	boolean
ismoneypaidbybuilder	boolean
isratepermonth	boolean
isnoofyears	boolean
isincrerateperyear	boolean
ispremiumroyaltymoneyadvanced	boolean
isfinalregnumreqd	boolean
ispartextentreqd	boolean
ismultipleschedulereqd	boolean
ispartyshareреqd	boolean
isregisterable	boolean
ismov	boolean
minparty	integer
minprop	integer
ispartypropmap	boolean
ismarketvaluation	boolean
isconsideration	boolean
ispresenter	boolean
isconsentingwitness	boolean
isidentifyingwitness	boolean
isprotestapplicationfee	boolean
xmltypeforeswathu	char(1)
isconfiscatingagentreqd	boolean
isprevregddocnoreqd	boolean
iswillcancellation	boolean
ispropertysearchreqd	boolean
ispropertyscheduleapplicable	boolean
ismultiproperty1consideration	boolean

Table stamprulesflag_tmp

	isjslipagri	boolean
	isjslipeqvltnonagri	boolean
	isclaimant	smallint
	isexecutant	smallint
	ownertypechange	boolean
	inserteddatetime	timestamp
	k1k2_flag	smallint
	issubregistrarallocateapp	boolean
	isnameeditable	boolean
	propdelete	boolean
	isownertabdeletable	boolean

Table stampruleslabs

Idx	Name	Data Type
* Pk	id	integer
Idx	stampruleid	integer
*	slabamtfrom	decimal(23,4)
*	slabamtto	decimal(23,4)
*	unit	decimal(23,4)
	maxlimit	decimal(23,4)
*	value	decimal(23,4)
	plusthisamount	decimal(23,4)
	inserteddatetime	timestamp DEFAULT CURRENT_TIMESTAMP
	k1k2_flag	smallint DEFAULT 2

Indexes

Type	Name	On
Pk	pk_stampruleslabs	id
	idx_stampruleslabs	stampruleid

Table stamprulseminvalue_change

Idx	Name	Data Type
	stampruleid	integer
	stamparticlecode	integer
	sameasarticleid	smallint
	parentrefid	smallint
	haschild	boolean
	descriptionk	varchar(500)
	descriptione	varchar(500)
	isslabs	boolean
	unitisamount	boolean
	unitdescriptionk	varchar(150)
	unitdescriptione	varchar(150)
	unit	double precision
	value	decimal
	minlimit	decimal
	maxlimit	decimal
	multipliedby	smallint
	sdcalcon	char(2)

Table stamprulseminvalue_change

	isinpercentage	boolean
	isfixduty	boolean
	isexempted	boolean
	isruleactive	boolean
	regvalue	decimal
	regispercent	boolean
	regmaxlimit	decimal
	regminlimit	decimal
	regcalconconsideration	char(2)
	othercalcrule	integer
	othercalcon	char(2)
	isaddonvalue	boolean
	addonvalue	decimal
	addoncaptione	varchar(150)
	addoncaptionk	varchar(150)
	activefrom	timestamp
	activeto	timestamp
	issurcharge	boolean
	urbanvalue	decimal
	ruralvalue	decimal
	issurchargepercentage	boolean
	iscess	boolean
	cessvalue	decimal
	iscesspercentage	boolean
	ismarketvaluationdone	boolean
	isparttransactallowed	boolean
	bucketid	integer
	bookid	smallint
	k1k2_flag	smallint
	inserteddatetime	timestamp

Table stampss

Idx	Name	Data Type
	stampruleid	integer
	stamparticlecode	integer
	sameasarticleid	smallint
	parentrefid	smallint
	haschild	boolean
	descriptionk	varchar(500)
	descriptione	varchar(500)
	isslabs	boolean
	unitisamount	boolean
	unitdescriptionk	varchar(150)
	unitdescriptione	varchar(150)
	unit	double precision
	value	decimal
	minlimit	decimal
	maxlimit	decimal

Table stampss

	multipliedby	smallint
	sdcalcon	char(2)
	isinpercentage	boolean
	isfixduty	boolean
	isexempted	boolean
	isruleactive	boolean
	regvalue	decimal
	regispercent	boolean
	regmaxlimit	decimal
	regminlimit	decimal
	regcalconconsideration	char(2)
	othercalcrule	integer
	othercalcon	char(2)
	isaddonvalue	boolean
	addonvalue	decimal
	addoncaptione	varchar(150)
	addoncaptionk	varchar(150)
	activefrom	timestamp
	activeto	timestamp
	issurcharge	boolean
	urbanvalue	decimal
	ruralvalue	decimal
	issurchargepercentage	boolean
	iscess	boolean
	cessvalue	decimal
	iscesspercentage	boolean
	ismarketvaluationdone	boolean
	isparttransactallowed	boolean
	bucketid	integer
	bookid	smallint
	k1k2_flag	smallint
	inserteddatetime	timestamp
	isauditrequired	boolean

Table stamptypemaster

Idx	Name	Data Type
* Pk	stamptypeid	integer
*	nameinkannada	varchar(75)
*	nameinenglish	varchar(75)
*	certificationreqd	boolean
	khajaneremittancedescription	varchar(50)
	inserteddatetime	timestamp DEFAULT CURRENT_TIMESTAMP
	k1k2_flag	smallint DEFAULT 2

Indexes

Type	Name	On
Pk	pk_stamptypemaster	stamptypeid

Table statemaster

Idx	Name	Data Type
* Pk	statecode	integer
	statenamee	varchar(75)
	statenamek	varchar(150)
	stateorut	varchar(30)
	stateshortnamee	varchar(75)
	stateshortnamek	varchar(150)
	k1k2_flag	smallint DEFAULT 2

Indexes

Type	Name	On
Pk	statemaster_pkey	statecode

Table statement

Idx	Name	Data Type
	sroname	varchar(250)
	cmonth	varchar(10)
	cyear	integer
	ctotaldocuments	integer
	ctotalstampduty	decimal
	ctotalregfees	decimal
	pyear	integer
	ptotaldocuments	integer
	ptotalstampduty	decimal
	ptotalregfees	decimal
	inserteddatetime	timestamp DEFAULT CURRENT_TIMESTAMP
	k1k2_flag	smallint DEFAULT 2

Table submodulemaster

Idx	Name	Data Type
* Pk	submoduleid	integer DEFAULT nextval('kaveri.submoduleid_seq'::regclass)
	submodulename	text
	moduleid	integer
	inserteddatetime	timestamp DEFAULT CURRENT_TIMESTAMP
	createdby	bigint

Indexes

Type	Name	On
Pk	pk_submodulemaster	submoduleid
	idx_submodulemaster_submoduleid	submoduleid

Table supportdocumentmaster

Idx	Name	Data Type
* Pk	supportdocid	integer
*	namekannada	varchar(150)
*	nameenglish	varchar(150)
	type	integer
	k1k2_flag	smallint DEFAULT 2

Indexes

Type	Name	On

Table supportdocumentmaster

Pk	pk_supportdocumentmaster	supportdocid

Table supportdocuments

Idx	Name	Data Type
* Pk	suppdocid	integer
*	suppdocnamee	varchar(100)
	suppdocnamek	varchar(100)
*	applicationtype	integer
	inserteddatetime	timestamp DEFAULT CURRENT_TIMESTAMP
	k1k2_flag	smallint DEFAULT 2

Indexes

Type	Name	On
Pk	pk_supportdocuments	suppdocid

Table supportdocumentuploads

Idx	Name	Data Type
*	uploadid	bigint DEFAULT nextval('kaveri.supportdocumentuploads_uploadid_seq'::regclass)
*	documentid	bigint
*	srocode	integer
*	supportdocid	integer
	partyid	bigint
*	uploaddatetime	timestamp
*	supportfilephysicalpath	varchar(1000)
*	supportfilevirtualpath	varchar(1000)
	inserteddatetime	timestamp DEFAULT CURRENT_TIMESTAMP
	k1k2_flag	smallint DEFAULT 2

Table surveynodetails

Idx	Name	Data Type
* Pk	surevynocode	decimal(10,0)
*	categorycode	integer
*	surevynumber	varchar(1500)
*	villagecode	decimal(10,0)
*	roadcode	decimal(10,0)
	surnumber	integer
	surnoc	varchar(200)
	hissano	varchar(200)
	inserteddatetime	timestamp DEFAULT CURRENT_TIMESTAMP
	k1k2_flag	smallint DEFAULT 2

Indexes

Type	Name	On
Pk	pk_surveynodetails_surevynocode	surevynocode

Table t22

Idx	Name	Data Type
	id	integer

Table t6

Idx	Name	Data Type
	id	integer

Table table_def

Idx	Name	Data Type
	relname	name
	tabdef	text

Table table_update_request_logs

Idx	Name	Data Type
* Pk	id	bigint GENERATED BY DEFAULT AS IDENTITY
* Unq	uuid	char(36) DEFAULT gen_random_uuid()
* Idx	table_name	varchar(255)
*	new_values	text
*	existing_values	text
*	where_conditions	text
	request_reason	varchar(255)
*	requested_by	bigint
*	is_approved	smallint DEFAULT '0'::smallint
*	is_rejected	smallint DEFAULT '0'::smallint
*	include_in_audit	smallint DEFAULT '0'::smallint
	approved_rejected_by	bigint
	approved_rejected_reason	varchar(255)
	approved_rejected_at	timestamp
	created_at	timestamp
	updated_at	timestamp
	deleted_at	timestamp
	inserteddatetime	timestamp DEFAULT CURRENT_TIMESTAMP

Indexes

Type	Name	On
Pk	table_update_request_logs_pkey	id
	idx_tableupdatelog	table_name
Unq	uk_tablelog_uuid	uuid

Table tabledef

Idx	Name	Data Type
	relname	name
	tabdef	text

Table talukmaster

Idx	Name	Data Type
* Pk	talukcode	integer
Idx	districtcode	integer
*	taluknamek	varchar(150)
*	taluknamee	varchar(150)
	inserteddatetime	timestamp DEFAULT CURRENT_TIMESTAMP
	k1k2_flag	smallint DEFAULT 2
	unit	char(1)

Table talukmaster

Indexes

Type	Name	On
Pk	pk_talukmaster	talukcode
	idx_talukmaster_districtcode	districtcode

Table talukmaster_prod1

Idx	Name	Data Type
	talukcode	integer
	districtcode	integer
	taluknamek	varchar(150)
	taluknamee	varchar(150)
	inserteddatetime	timestamp
	k1k2_flag	smallint
	unit	char(1)

Table talukmaster_prod2

Idx	Name	Data Type
	talukcode	integer
	districtcode	integer
	taluknamek	varchar(150)
	taluknamee	varchar(150)
	inserteddatetime	timestamp
	k1k2_flag	smallint
	unit	char(1)

Table tbl_book1_part3_remarks

Idx	Name	Data Type
* Pk	verification_id	bigint DEFAULT nextval('kaveri.tbl_book1_part3_remarks_verification_id_seq'::regclass)
	application_no	varchar(50)
	prop_details_remarks_fda	varchar(200)
	prop_details_verify_fda	boolean
	bound_details_remarks_fda	varchar(200)
	bound_details_verify_fda	boolean
	sd_details_remarks_fda	varchar(200)
	sd_details_verify_fda	boolean
	party_details_remarks_fda	varchar(200)
	party_details_verify_fda	boolean
	prop_details_remarks_sro	varchar(200)
	prop_details_verify_sro	boolean
	bound_details_remarks_sro	varchar(200)
	bound_details_verify_sro	boolean
	sd_details_remarks_sro	varchar(200)
	sd_details_verify_sro	boolean
	party_details_remarks_sro	varchar(200)
	party_details_verify_sro	boolean
	reviewed_by	varchar(10)
	property_id	bigint

Table tbl_book1_part3_remarks

Indexes

Type	Name	On
Pk	tbl_book1_part3_remarks_pkey	verification_id

Table temptableforjslip

Idx	Name	Data Type
	finalregistrationnumber	varchar(100)
	confirmationsent	boolean DEFAULT false

Table third_partyintegrationkeys

Idx	Name	Data Type
* Pk	id	integer DEFAULT nextval('kaveri.third_partyintegrationkeys_id_seq'::regclass)
	name	varchar
	apikey	varchar
	hash	text
	citizenid	bigint

Indexes

Type	Name	On
Pk	third_partyintegrationkeys_pkey	id

Table tmp

Idx	Name	Data Type
	gscno	varchar(20)

Table transactionauditlog

Idx	Name	Data Type
* Pk	pid	bigint
	databasename	varchar(50)
	username	varchar(50)
	app_name	varchar(100)
	client_address	inet
	state	varchar(30)
	wait_event	varchar(50)
	blocking_pid	integer[]
	query	text
	backend_type	varchar(50)
	active_since	decimal
	query_start	text

Indexes

Type	Name	On
Pk	pk_transactionauditlog_pid	pid

Table ulbmapping

Idx	Name	Data Type
* Pk	mappingid	integer
* Idx	srocode	integer
*	ulbcode	integer

Table ulbmapping

	inserteddatetime	timestamp DEFAULT CURRENT_TIMESTAMP
	k1k2_flag	smallint DEFAULT 2

Indexes

Type	Name	On
Pk	pk_ulbmapping	mappingid
	idx_ulbmapping	srocode

Table ulbmaster

Idx	Name	Data Type
* Pk	ulbcode	integer
*	ulbname	varchar(200)
	inserteddatetime	timestamp DEFAULT CURRENT_TIMESTAMP
	k1k2_flag	smallint DEFAULT 2

Indexes

Type	Name	On
Pk	pk_ulbmaster	ulbcode

Table ulms_property_importlog

Idx	Name	Data Type
* Pk	logid	bigint DEFAULT nextval('kaveri.ulms_property_importlog_logid_seq'::regclass)
*	propertyid	bigint
	pid	varchar
	json	text
	srocode	decimal
	integrationtype	varchar
	inserteddatetime	timestamp DEFAULT CURRENT_TIMESTAMP
	k1k2_flag	smallint DEFAULT 2

Indexes

Type	Name	On
Pk	ulmspropertyid_pkey	logid

Table upordecisionmaster

Idx	Name	Data Type
* Pk	value	integer
	decision	varchar(100)
	inserteddatetime	timestamp DEFAULT CURRENT_TIMESTAMP
	k1k2_flag	smallint DEFAULT 2

Indexes

Type	Name	On
Pk	upordecisionmaster_pkey	value

Table uporpropertytypemaster

Idx	Name	Data Type
* Pk	propertytypeid	integer
	propertytypenamek	varchar(100)
	propertytypenamee	varchar(100)
	isallow	boolean

Table uporpropertytypemaster

	inserteddatetime	timestamp DEFAULT CURRENT_TIMESTAMP
	k1k2_flag	smallint DEFAULT 2

Indexes

Type	Name	On
Pk	pk__uporpropertytype__729b558b	propertytypeid

Table uporrestrictiontypemaster

Idx	Name	Data Type
* Pk	restrictiontypeid	integer
	restrictiontypenamek	varchar(100)
	restrictiontypenamee	varchar(100)
	decisiontype	integer
	inserteddatetime	timestamp DEFAULT CURRENT_TIMESTAMP
	k1k2_flag	smallint DEFAULT 2

Indexes

Type	Name	On
Pk	uporrestrictiontypemaster_pkey	restrictiontypeid

Table uporxml

Idx	Name	Data Type
* Pk	logid	bigint
*	documentid	bigint
*	propertyid	bigint
	inputownerdetails	text
	ownerdetails	text
	verified	boolean
	isuploaded	boolean
	acknumber	bigint
	ackxmldetails	text
	isboundaryimported	boolean
	uploaddatetime	timestamp
	sentxmldetails	text
*	istransmitted	boolean
	srocode	smallint
	inserteddatetime	timestamp DEFAULT CURRENT_TIMESTAMP
	k1k2_flag	smallint DEFAULT 2

Indexes

Type	Name	On
Pk	pk_uporxml	logid

Table usrtypemst

Idx	Name	Data Type
* Pk	usrtypeid	integer DEFAULT nextval('kaveri.usrtypemst_usrtypeid_seq'::regclass)
*	usrtypedesc	text
	usrtypecode	varchar(5)
	crtusr	varchar(10)
	crtdt	timestamp

Table usrtypemst

	lstupusr	varchar(10)
	lstupddt	timestamp DEFAULT CURRENT_TIMESTAMP

Indexes

Type	Name	On
Pk	usrtypemst_pkey	usrtypeid

Table val_agriculturedetails

Idx	Name	Data Type
* Pk	agriculturedetailsid	bigint DEFAULT nextval('kaveri.val_agriculturedetails_seqid'::regclass)
*	agrilandtypeid	smallint
*	unitid	integer
* Idx	valuationid	bigint
*	verified	boolean
*	agrirateid	bigint
*	rate	decimal(18,2)
*	srocode	integer
*	regsrocode	integer
	inserteddatetime	timestamp DEFAULT CURRENT_TIMESTAMP
	k1k2_flag	smallint DEFAULT 2

Indexes

Type	Name	On
Pk	pk_valagriculturedetails	agriculturedetailsid
	idx_valuation_valuationid	valuationid

Table val_annexuredetails

Idx	Name	Data Type
* Pk	annexuredetailsid	bigint
*	annexureid	smallint
	area	decimal(18,4)
	rate	decimal(15,2)
* Idx	valuationid	bigint
*	verified	boolean
*	srocode	integer
*	regsrocode	integer
	isselected	boolean
	inserteddatetime	timestamp DEFAULT CURRENT_TIMESTAMP
	k1k2_flag	smallint DEFAULT 2

Indexes

Type	Name	On
Pk	pk_valannexcuredetails	annexuredetailsid
	val_annexuredetails_valuationid_idx	valuationid

Table val_apartmentamenitydetails

Idx	Name	Data Type
* Pk	amenetiesdetailsid	bigint DEFAULT nextval('kaveri.val_apartmentamenitydtls_amenetiesdtlsid1_seq'::regclass)
*	apartmentamenetyruleid	smallint

Table val_apartmentamenitydetails

	rate	decimal(18,2)
* Pk	valuationid	bigint
*	verified	boolean
*	srocode	integer
*	regsrocode	integer
	inserteddatetime	timestamp DEFAULT CURRENT_TIMESTAMP
	k1k2_flag	smallint DEFAULT 2

Indexes

Type	Name	On
Pk	pk_amenetiesdetailsid	amenetiesdetailsid, valuationid
	val_apartmentamenitydetails_valuationid_idx	valuationid

Table val_app

Idx	Name	Data Type
	applicationnumber	varchar(100)

Table val_constructionratedetails

Idx	Name	Data Type
* Pk	constructiondetailsid	bigint DEFAULT nextval('kaveri.val_constructionratedtls_constructiondtlsid_seq'::regclass)
*	constructiontypeid	smallint
	gfarea	decimal(18,4)
	agfarea	decimal(18,4)
	rate	decimal(15,2)
*	verified	boolean
* Idx	valuationid	bigint
*	srocode	integer
*	regsrocode	integer
	inserteddatetime	timestamp DEFAULT CURRENT_TIMESTAMP
	k1k2_flag	smallint DEFAULT 2

Indexes

Type	Name	On
	idx_val_constructionratedetails_valuationid	valuationid
Pk	pk_constratdtls_constdtlsid	constructiondetailsid

Table val_flatfloordetails

Idx	Name	Data Type
* Pk	flatfloordetailsid	bigint DEFAULT nextval('kaveri.val_flatfloordetails_flatfloordetailsid_seq'::regclass)
*	apartmentfloorrateid	smallint
	rate	decimal(18,0)
*	verified	boolean
* Idx	valuationid	bigint
*	srocode	integer
*	regsrocode	integer
	inserteddatetime	timestamp DEFAULT CURRENT_TIMESTAMP
	k1k2_flag	smallint DEFAULT 2

Indexes

Table val_flatfloordetails

Type	Name	On
Pk	pk_id_flatflordtls	flatfloordetailsid
	idx_val_annexuredetails_valuationid	valuationid

Table val_flatratedetails

Idx	Name	Data Type
* Pk	flatratedetailsid	bigint DEFAULT nextval('kaveri.val_flatratedetails_flatratedetailsid_seq'::regclass)
*	propertytypeid	integer
*	amenitiesid	integer
*	unitid	integer
	rate	decimal(15,2)
*	flatrateid	integer
*	verified	boolean
*	floorid	smallint
* Idx	valuationid	bigint
*	srocode	integer
*	regsrocode	integer
	inserteddatetime	timestamp DEFAULT CURRENT_TIMESTAMP
	k1k2_flag	smallint DEFAULT 2

Indexes

Type	Name	On
Pk	pk_id_flatratedtls	flatratedetailsid
	val_flatratedetails_valuationid_idx	valuationid

Table val_openbuiltvaluationdetails

Idx	Name	Data Type
* Pk	openbuiltvalid	bigint DEFAULT nextval('kaveri.val_openbuiltvaluationdtls_openbuiltvalid_seq'::regclass)
* Idx	propertytypeid	integer
*	roadid	bigint
*	unitid	integer
*	rate	decimal(15,2)
* Idx	valuationid	bigint
*	verified	boolean
*	openbuiltrateid	bigint
*	srocode	integer
*	regsrocode	integer
	inserteddatetime	timestamp DEFAULT CURRENT_TIMESTAMP
	k1k2_flag	smallint DEFAULT 2

Indexes

Type	Name	On
Pk	pk_id_openbuiltvaldtls	openbuiltvalid
	idx_val_openbuiltvaluationdetails_propertytypeid	propertytypeid
	val_openbuiltvaluationdetails_valuationid_idx	valuationid

Table val_parkingratedetails

Idx	Name	Data Type

Table val_parkingratedetails

* Pk	parkingdetailsid	bigint DEFAULT nextval('kaveri.val_parkingratedetails_parkingdetailsid_seq'::regclass)
*	parkingtypeid	smallint
	totalparkings	integer
	rate	decimal(15,2)
*	verified	boolean
* Idx	valuationid	bigint
*	srocode	integer
*	regsrocode	integer
	inserteddatetime	timestamp DEFAULT CURRENT_TIMESTAMP
	k1k2_flag	smallint DEFAULT 2

Indexes

Type	Name	On
Pk	pk_val_parkingratedetails	parkingdetailsid
	idx_val_parkingdetails_valuationid	valuationid

Table val_userapartmentamenitydetails

Idx	Name	Data Type
* Pk	useramenetiesdetailsid	bigint DEFAULT nextval('kaveri.val_userapartmentamenitydetails_useramenetiesdetailsid_seq'::regclass)
*	apartmentamenityid	smallint
	isselected	boolean DEFAULT false
* Idx	valuationid	bigint
*	verified	boolean
*	srocode	integer
*	regsrocode	integer
	inserteddatetime	timestamp DEFAULT CURRENT_TIMESTAMP
	k1k2_flag	smallint DEFAULT 2

Indexes

Type	Name	On
Pk	pk_valuserapartmentamenitydetails	useramenetiesdetailsid
	idx_val_val_userapartmentamenitydetails_valuationids	valuationid
	val_userapartmentamenitydetails_valuationid_idx	valuationid

Table valdetails_temp

Idx	Name	Data Type
Idx	propertyid	bigint
Idx	valid	bigint
	valuationdate	timestamp
	rn	bigint

Indexes

Type	Name	On
	idx_valdetails_temp	propertyid
	idx_valdetails_temp_valid	valid

Table valuationdetails

Idx	Name	Data Type
* Pk	valid	bigint

Table valuationdetails

*	srocode	integer
* Pk	regsrocode	integer
	villagecode	bigint
	roadcode	integer
	valuationdate	timestamp
Idx	propertytypeid	integer
	totalarea	decimal(18,4)
	unitid	integer
	marketvalue	decimal
	leasetype	integer
	leaseamount	decimal
	northboundary	varchar(50)
	southboundary	varchar(50)
	eastboundary	varchar(50)
	westboundary	varchar(50)
	assessment	varchar(2000)
	regarticlecode	integer
Idx	applicationnumber	varchar(50)
	verified	boolean DEFAULT false
	issroapproved	varchar(1) DEFAULT 'E'::character varying
Idx	propertyid	bigint
	reportdetails	varchar
	inserteddatetime	timestamp DEFAULT CURRENT_TIMESTAMP
	k1k2_flag	smallint DEFAULT 2

Indexes

Type	Name	On
	idx_valuationdetails_propertyid	propertyid
Pk	pk_valdtls_validregsrocd	valid, regsrocode
	idx_valuationdetails_propertyapp	propertytypeid, applicationnumber
	valuationdetails_mulitple	applicationnumber

Table valuationdetails_cd140

Idx	Name	Data Type
	valid	bigint
	srocode	integer
	regsrocode	integer
	villagecode	bigint
	roadcode	integer
	valuationdate	timestamp
	propertytypeid	integer
	totalarea	decimal(18,4)
	unitid	integer
	marketvalue	decimal
	leasetype	integer
	leaseamount	decimal
	northboundary	varchar(50)
	southboundary	varchar(50)
	eastboundary	varchar(50)

Table valuationdetails_cd140

	westboundary	varchar(50)
	assessment	varchar(2000)
	regarticlecode	integer
	applicationnumber	varchar(50)
	verified	boolean
	issroapproved	varchar(1)
	propertyid	bigint
	reportdetails	varchar
	inserteddatetime	timestamp
	k1k2_flag	smallint

Table valuationtypemaster

Idx	Name	Data Type
* Pk	valuatiotypeid	smallint
	valutiontypename	varchar(20)
	lstinsdate	timestamp DEFAULT CURRENT_TIMESTAMP
	k1k2_flag	smallint DEFAULT 2

Indexes

Type	Name	On
Pk	pk_feesrequired_valuatiotypeid	valuatiotypeid

Table viewdef

Idx	Name	Data Type
	viewname	name
	definition	text

Table views_def

Idx	Name	Data Type
	viewname	name
	definition	text

Table villagemaster

Idx	Name	Data Type
* Pk	villagecode	bigint
* Idx	srocode	integer
Idx	hoblicode	integer
	censuscode	varchar(50)
Idx	talukcode	integer
	villagenamek	varchar(500)
	villagenamee	varchar(500)
*	isurban	boolean
	bhoomitalukcode	integer
	bhoomivillagecode	integer
	bhoomivillagename	varchar(100)
	bhoomidistrictcode	integer
	uportownid	integer
	inserteddatetime	timestamp DEFAULT CURRENT_TIMESTAMP
	k1k2_flag	smallint DEFAULT 2

Table villagemaster

	isactive	boolean DEFAULT true

Indexes

Type	Name	On
	villagemaster_talukcode_idx	talukcode
Pk	pk_villagemaster	villagecode
	villagemaster_talukcode_idx_ccnew	talukcode
	idx_villagemaster_ccnew	srocode
	idx_villagemaster_hoblimaster_ccnew	hoblicode
	idx_villagemaster_talukcode_ccnew	villagecode, talukcode, hoblicode
	villagemaster_talukcode_idx_ccnew1	talukcode
	idx_villagemaster_ccnew1	srocode
	idx_villagemaster_hoblimaster_ccnew1	hoblicode
	idx_villagemaster_talukcode	villagecode, talukcode, hoblicode
	idx_villagemaster	srocode
	idx_villagemaster_hoblimaster	hoblicode

Table villagemaster_15feb2025

Idx	Name	Data Type
	villagecode	bigint
	srocode	integer
	hoblicode	integer
	censuscode	varchar(50)
	talukcode	integer
	villagenamek	varchar(500)
	villagenamee	varchar(500)
	isurban	boolean
	bhoomitalukcode	integer
	bhoomivillagecode	integer
	bhoomivillagename	varchar(100)
	bhoomidistrictcode	integer
	uportownid	integer
	inserteddatetime	timestamp
	k1k2_flag	smallint
	isactive	boolean

Table villagemaster_prod

Idx	Name	Data Type
	villagecode	bigint
	srocode	integer
	hoblicode	integer
	censuscode	varchar(50)
	talukcode	integer
	villagenamek	varchar(500)
	villagenamee	varchar(500)
	isurban	boolean
	bhoomitalukcode	integer
	bhoomivillagecode	integer
	bhoomivillagename	varchar(100)

Table villagemaster_prod

	bhoomidistrictcode	integer
	uportownid	integer
	inserteddatetime	timestamp
	k1k2_flag	smallint

Table villagemaster_prod1

Idx	Name	Data Type
	villagecode	bigint
	srocode	integer
	hoblicode	integer
	censuscode	varchar(50)
	talukcode	integer
	villagenamek	varchar(500)
	villagenamee	varchar(500)
	isurban	boolean
	bhoomitalukcode	integer
	bhoomivillagecode	integer
	bhoomivillagename	varchar(100)
	bhoomidistrictcode	integer
	uportownid	integer
	inserteddatetime	timestamp
	k1k2_flag	smallint
	isactive	boolean

Table villagemaster_prod2

Idx	Name	Data Type
	villagecode	bigint
	srocode	integer
	hoblicode	integer
	censuscode	varchar(50)
	talukcode	integer
	villagenamek	varchar(500)
	villagenamee	varchar(500)
	isurban	boolean
	bhoomitalukcode	integer
	bhoomivillagecode	integer
	bhoomivillagename	varchar(100)
	bhoomidistrictcode	integer
	uportownid	integer
	inserteddatetime	timestamp
	k1k2_flag	smallint
	isactive	boolean

Table villageurbanmappeddiffdump

Idx	Name	Data Type
	villagecode	integer
	deptid	integer

Table villageurbanmapping

Idx	Name	Data Type
* Pk	villagecode	integer
* Pk	deptid	integer

Indexes

Type	Name	On
Pk	pk_villageurbanmapping_comp	villagecode, deptid

Table villagewardmapping

Idx	Name	Data Type
* Pk	mappingid	bigint
*	villagecode	bigint
* Idx	wardid	integer
	k1k2_flag	smallint DEFAULT 2
	integrationenabled	boolean DEFAULT false

Indexes

Type	Name	On
Pk	pk_villagewardmapping	mappingid
	idx_villagewardmapping_ccnew	wardid
Unq	pk_villagewardmapping_ccnew	mappingid
Unq	pk_villagewardmapping_ccnew1	mappingid
	idx_villagewardmapping	wardid

Table villagewardmapping_file_data

Idx	Name	Data Type
	srocode	integer
	villagecode	integer
	wardid	integer

Table warddetails

Idx	Name	Data Type
* Pk	wardid	integer
*	wardnumber	varchar(50)
*	integrationenabled	boolean
	inserteddatetime	timestamp DEFAULT CURRENT_TIMESTAMP
	k1k2_flag	smallint DEFAULT 2

Indexes

Type	Name	On
Pk	pk_warddetails	wardid
	idx_warddetails	wardid

Table withdrawapplications

Idx	Name	Data Type
* Pk	id	bigint DEFAULT nextval('kaveri.withdrawapplications_id_seq'::regclass)
	applicationnumber	varchar(50)
	withdrawndate	timestamp
	remarks	varchar(500)
	withdrawdocumentpath	varchar(500)

Table withdrawapplications

Indexes

Type	Name	On
Pk	withdrawapplications_pkey	id

Table witnessinfo

Idx	Name	Data Type
* Pk	witnessid	bigint
Idx	documentid	bigint
	name	varchar(500)
	address	varchar(500)
	sex	integer
	age	varchar(3)
	profession	varchar(150)
	registrationid	bigint
	dateofbirth	timestamp
	status	varchar(15)
	phoneno	varchar(20)
	relation	varchar(50)
	mothername	varchar(50)
	fathersname	varchar(50)
	presentatsolemanization	char(10)
* Pk	srocode	integer
	isonline	boolean
Idx	applicationnumber	varchar(50)
	verified	boolean DEFAULT false
	issroapproved	varchar(1) DEFAULT 'E'::character varying
	statecode	integer
	districtcode	integer
	talukcode	integer
	hoblicode	integer
	villagecode	bigint
	relativename	varchar(200)
	pincode	integer
	middlename	text
	lastname	text
	houseno	text
	iscliment	boolean DEFAULT false
	isexicutent	boolean DEFAULT false
	isendorseprinted	boolean DEFAULT false
	ispresentverification	boolean DEFAULT false
	k1k2_flag	smallint DEFAULT 2
	inserteddatetime	timestamp DEFAULT CURRENT_TIMESTAMP

Indexes

Type	Name	On
Pk	pk_witnessinfo	witnessid, srocode
	idx_witnessinfo	applicationnumber
	idx_witnessinfo_doc	documentid

Table wrkflowmaster

Idx	Name	Data Type
* Pk	wrkflowstatusid	varchar(5)
	wrkflowstatusnamee	text
	wrkflowstatusnamek	text
	wrkflowparntid	varchar(5)
	wrkfloworder	decimal(3,0)
	activeyn	char(1) DEFAULT 'Y'::bpchar
	activefrom	timestamp DEFAULT now()
	activeto	timestamp
	crtusr	varchar(10)
	crtdt	timestamp DEFAULT now()
	lstupusr	varchar(10)
	lstupddt	timestamp DEFAULT now()
	serviceid	bigint
	k1k2_flag	smallint DEFAULT 2

Indexes

Type	Name	On
Pk	pk_wrkflowmaster	wrkflowstatusid
	idx_wrkflowmaster_wrkflow	wrkflowstatusid

Table yearlyleavebalance

Idx	Name	Data Type
*	empid	bigint
*	leavetypeid	bigint
*	leaveyear	bigint
*	outstandingleave	bigint
	k1k2_flag	smallint DEFAULT 2

Table zonemaster

Idx	Name	Data Type
* Pk	zoneid	smallserial
	zonenamee	char(100)
	zonenamek	char(100)
	inserteddatetime	timestamp DEFAULT CURRENT_TIMESTAMP
	k1k2_flag	smallint DEFAULT 2

Indexes

Type	Name	On
Pk	pk_zoneid	zoneid