Entity resolution, step by step

This notebook runs the pipeline that `scripts/resolve.py` runs on a file of any size: the same `er.run.Run`, one step per section, on a small generated population (about 3,700 records) so that every step can be seen. It holds no logic of its own; each section calls the code, then charts what the step did. Every code cell prints its Big-O, filled in with this file's numbers, and its time. The whole notebook runs in about half a minute.

The run never reads the truth (which records are one entity). It exists only because the data is generated, and the notebook reads it to show what each step got right.

1 Setup · 2 Generate · 3 Standardize · 4 Person or company · 5 Fit · 6 Rules · 7 Candidates · 8 Score · 9 Why a pair matches · 10 Threshold · 11 Cluster and evaluate · 12 Increment · 13 How the configuration was chosen · 14 Cost as the file grows

N records, L characters per value, P pairs inside a key's blocks, C candidate pairs, K comparisons, S sampled pairs.

1 · Setup

The chosen pipeline is `config/final.toml`, which `scripts/choose.py` wrote. The demo's population is `config/generator.toml`'s, made smaller. Charts use one colour per meaning: blue for the same entity (or evidence for a match), orange for different entities, red for evidence against.

In [1]:
```
import logging
import math
import shutil
import time
from contextlib import contextmanager
from dataclasses import replace

import matplotlib.pyplot as plt
import numpy as np
import pandas as pd
from matplotlib.ticker import FuncFormatter, PercentFormatter
```

```
from matplotlib_inline.backend_inline import set_matplotlib_formats

from er.candidates import found_by
from er.config import column_name, load_pipeline
from er.evaluate import cluster_metrics, missed_pairs, pair_metrics, predicted_pairs
from er.generate import KindProblems, check, generate, kind_problems, load_reference, load_registry, load_spec
from er.io import table_after
from er.kind import SAYS, kind_review_sheet
from er.match import parameters, scaled_prior, waterfall
from er.cluster import connected_components
from er.run import Run, fill_rates
from er.settings import load_settings, shared_name

logging.disable(logging.WARNING)
S = load_settings()
FINAL = load_pipeline(S.root / "config" / "final.toml", S.standardize, S.chains, S.columns)
SPEC = replace(load_spec(S.root / "config" / "generator.toml")[0], entities=3_000)  # the demo's size
DEMO = S.paths["artifacts"] / "demo"
DEMO.mkdir(parents=True, exist_ok=True)
UID, ENT = S.data.unique_id, S.data.entity_id
L, R = f"{UID}_l", f"{UID}_r"
FIELDS = [f for f in S.columns if f not in ("id", "entity")]  # the logical fields of config/settings.toml [column
s]
pd.set_option("display.max_columns", 30, "display.width", 200)

BLUE, ORANGE, RED, INK, INK2, MUTED, GRID, AXIS, SURFACE = ("#2a78d6", "#eb6834", "#e34948", "#0b0b0b", "#52514e",
                                                            "#898781", "#e1e0d9", "#c3c2b7", "#fcfcfb")
set_matplotlib_formats("svg")
plt.rcParams.update({"figure.facecolor": SURFACE, "axes.facecolor": SURFACE, "savefig.facecolor": SURFACE,
                     "axes.edgecolor": AXIS, "axes.linewidth": 0.8, "axes.labelcolor": INK2, "axes.titlecolor": IN
K,
                     "axes.titlesize": 10, "axes.titleweight": "bold", "axes.titlelocation": "left",
                     "axes.spines.top": False, "axes.spines.right": False, "axes.grid": True, "axes.axisbelow": Tr
ue,
                     "grid.color": GRID, "grid.linewidth": 0.6, "xtick.color": MUTED, "ytick.color": MUTED,
                     "xtick.labelcolor": INK2, "ytick.labelcolor": INK2, "font.size": 9, "lines.linewidth": 2,
                     "legend.frameon": False, "figure.dpi": 100})


@contextmanager
def timed(big_o: str):  # a cell's own work, outside the run's steps
```

```
    t = time.perf_counter()
    yield
    print(f"{big_o} · {time.perf_counter() - t:.2f}s")


def done(run: Run) -> None:  # the step just run: its Big-O with this file's numbers, and its time
    s = run.steps[-1]
    print(f"{s['step']}: {s['big_o']} = {s['filled']} · {s['seconds']:.2f}s")


def same(pairs: pd.DataFrame) -> np.ndarray:  # the truth, read only to show what a step got right
    return pairs[L].map(entity).to_numpy() == pairs[R].map(entity).to_numpy()


def finish(fig) -> None:
    fig.tight_layout()
    plt.show()
```

2 · Generate

A synthetic population built from public reference data: each entity, a person or a company, is written as one or more records with typos, empty fields and life changes (a move, a new phone, a married surname). The truth is kept apart. Below: the entity whose three records differ the most, then how many records each entity has and how often each column is filled. O(E·r) for E entities of r records each.

In [2]:
```
with timed(f"generate: O(E·r) = O({SPEC.entities:,} entities · their records)"):
    g = generate(SPEC, *load_reference(S.paths["reference"]))
    check(SPEC, g)
g.df.to_parquet(DEMO / "records.parquet", index=False)
entity = g.truth.set_index(UID)[ENT]
per_entity = entity.value_counts()
print(f"{len(g.df):,} records · {len(per_entity):,} entities · {(per_entity > 1).mean():.0%} with more than one re
cord")


raw = g.df.set_index(UID)
varied = raw.groupby(entity.reindex(raw.index).to_numpy()).nunique().gt(1).sum(axis=1)  # columns that differ, per
entity
example = varied[per_entity.reindex(varied.index).eq(3)].idxmax()
ex_ids = entity.index[entity == example]
```

```
display(raw.loc[ex_ids].dropna(axis=1, how="all"))

fig, (a, b) = plt.subplots(1, 2, figsize=(10, 3.8), width_ratios=[1, 2])
counts = per_entity.value_counts().sort_index()
a.bar(counts.index.astype(str), counts.to_numpy(), width=0.6, color=BLUE)
a.set(title="Records per entity", xlabel="records", ylabel="entities")
a.grid(axis="x", visible=False)
fill = raw.notna().mean().sort_values()
b.barh(fill.index, fill.to_numpy(), height=0.6, color=BLUE)
b.set(title="Records with the column filled", xlim=(0, 1))
b.grid(axis="y", visible=False)
b.xaxis.set_major_formatter(PercentFormatter(1))
b.tick_params(axis="y", labelsize=7)
finish(fig)
```

```
generate: O(E·r) = O(3,000 entities · their records) · 0.82s
3,758 records · 3,000 entities · 22% with more than one record
```

CONT_ID	PHONE_NUM_4	CIF_ID	FULL_NAME_KANA	O_PERSON_NAME_KANA	POST_CD	POST_CD_KANA	LAST_NAME_KANA	GIVEN_NAME_KANA	BIRTH_DATE	SOURCE_ADDR_CD	ORIGINAL_ADDRESS	ADDRESS_FIVE	ADDRESS_FIVE_KANA	ADDR_CD_KANA	ADDR_CD	STD_ADDRESS	ADDRESS_ONE	ADDRESS_TWO	ADDRESS_THREE
0000000536	4573	6243089361260	ｸﾎﾞ ｳﾝ	ｸﾎﾞ ｳﾝ	8160831	8160831	ｸﾎﾞ	ｳﾝ	19350813	9035229242	春日市大谷９－１８－９	9-18-9	9-18-9	40218009009	40218009009	福岡県春日市大谷9-18-9	福岡県	春日市	大谷
0000001247	9503	8517481989993	ｸﾎﾞｵﾝ	ｸﾎﾞ ｵﾝ	8000301	8000301	ｸﾎﾞ	ｵﾝ	19360813	8037260253	福岡県京都郡苅田町松原町5-27グランドール602	5-27	5-27	40621003000	40621003000	福岡県京都郡苅田町松原町5-27	福岡県	京都郡苅田町	松原町
0000001654	4573	5633639874782	クボウン	クボ ウン	8160831	8160831	クボ	ウン	<NA>	9035229242	<NA>	<NA>	<NA>	40218009009	<NA>	<NA>	<NA>	<NA>	<NA>



3 · Standardize

`load` reads the file in chunks and checks it against `config/pipeline.toml` `[fields]`: the id is mandatory, and at least one of the person and company names is needed. An optional field the file lacks disables only what reads it. It then builds each logical field from `config/settings.toml` `[columns]` (the first filled source wins) and the normalizations the pipeline reads: kana folding, legal forms dropped, addresses cut to the street number. Each record is standardized on its own, so chunks change nothing. O(N·L). Last, the checks `scripts/resolve.py --check` prints: each field's fill rate, the share of filled values that look like the field (`[locale.detect]`), and the share of its most common value, where a placeholder such as `0000` would show.

In [3]:
```
run = Run(FINAL, S)
run.load(DEMO / "records.parquet")
done(run)
print("disabled:", ", ".join(run.disabled) or "nothing: every optional field is in the file")
std = run.con.sql("SELECT * FROM records").df().set_index(UID)
```

```
display(std.loc[ex_ids, [f for f in FIELDS if f in std]])  # the entity above, in logical fields (this file has no flag)
rows = []
for field, chain in [("person_name", "fold"), ("company_name", "company"), ("address", "address")]:
    after = column_name(field, S.chains[chain])
    changed = std.loc[std[field].notna() & (std[field] != std[after]), [field, after]].head(3)
    rows.append(changed.set_axis(["before", "after"], axis=1).assign(field=field, normalization=" → ".join(S.chains[chain])))
display(pd.concat(rows)[["field", "normalization", "before", "after"]])
display(fill_rates(run, FIELDS).set_index("field").round(3))
```

```
load: O(N·L) = O(3,758·L) · 0.10s
disabled: nothing: every optional field is in the file
```

CONT_ID	full_name	person_name	given_name	company_name	any_name	address	address_code	postal_code	prefecture	town_code	city	phone	customer_id	birth_date
0000000536	クボウン	クボウン	ウン	NaN	クホウン	福岡県春日市大谷9-18-9	9035229242	8160831	福岡県	40218009009	春日市	4573	6243089361260	19350813
0000001247	クボオン	クボオン	オン	NaN	クホオン	福岡県京都郡苅田町松原町5-27	8037260253	8000301	福岡県	40621003000	京都郡苅田町	9503	8517481989993	19360813
0000001654	クボウン	クボウン	ウン	NaN	クホウン	NaN	9035229242	8160831	NaN	NaN	NaN	4573	5633639874782	NaN

CONT_ID	field	normalization	before	after
0000000005	person_name	kana_fold	タジツコーダイ	タシツコウタイ
0000000006	person_name	kana_fold	マツザキトモアギ	マツサキトモアキ
0000000008	person_name	kana_fold	ヨネクラギョーシン	ヨネクラキヨウシン
0000000007	company_name	nfkc → strip_legal_form → kana_fold	イスズエンジンセイゾウホッカイドウカブシキガイシャ	イススエンシンセイソウホツカイトウ
0000000013	company_name	nfkc → strip_legal_form → kana_fold	カブシキガイシャグラニツト	クラニツト
0000000017	company_name	nfkc → strip_legal_form → kana_fold	ナルミヤインターナショナル	ナルミヤインタウナシヨナル
0000000002	address	address	神奈川県海老名市門沢橋2-23-5	海老名市門沢橋2-23-5
0000000003	address	address	福島県福島市北町5-30	福島市北町5-30
0000000004	address	address	佐賀県佐賀市12-26	佐賀市12-26

field	filled	looks_right	top_value	flag
full_name	0.759	1.000	0.001	
person_name	0.779	1.000	0.001	
given_name	0.679	1.000	0.004	
company_name	0.175	0.798	0.003	
any_name	0.954	1.000	0.001	
address	0.936	0.788	0.003	
address_code	0.817	1.000	0.002	
postal_code	0.928	1.000	0.002	
prefecture	0.695	1.000	0.115	
town_code	0.715	1.000	0.003	
city	0.675	1.000	0.009	
phone	1.000	1.000	0.001	
customer_id	0.980	1.000	0.001	
birth_date	0.119	0.962	0.004	

4 · Person or company

Each record gets a kind, `er.kind`: 2 company, 1 person, 0 not sure, the codes a person/company flag uses. A legal form written where banks write one (株式会社 in full, カ)〇〇, 〇〇(カ) says company. A name model, logistic regression on the name's character n-grams trained once on public data (real company readings from the registry, and the personas), says where a name leans. With people's answers, a combiner weighs the name's score, the file's own flag, the birth year and the legal form, and a line on each side keeps the sure calls within budget: at most 0.1% of company calls wrong, 1% of person calls. A record where the engine and the flag disagree is held back from matching until a person decides: its name goes to neither side, so it can't be merged with the wrong kind.

Here the population of section 2 gets one name column for every kind, NAME_KANA, and what makes the kinds hard to tell apart (`er.generate.kind_problems`): real company names written as banks write them, company records under their representative's name, sole traders named like a shop, companies with a date in the birth-date column, and a flag that is sometimes wrong. It is loaded twice: without answers, then with people's answers to its review sheet (here, the truth). Below: the review sheet, which says in words why each record is on it; what the answers let the engine decide; and how the name alone scores each kind of record. O(N·L) per load.

In [4]:
```
kg = kind_problems(g, KindProblems(), load_registry(S.paths["reference"]), S.standardize.legal_front, S.standardize.legal_end,
```

```
                    SPEC.kana_confusions, SPEC.branches)
kg.df.to_parquet(DEMO / "kinds.parquet", index=False)
KS = shared_name(S, "NAME_KANA")  # every name field reads NAME_KANA: full_name and person_name where a record lea
ns person, company_name where it leans company
KFINAL = load_pipeline(S.root / "config" / "final.toml", KS.standardize, KS.chains, KS.columns)
case = kg.truth.set_index(UID)["CASE"]
kinds_of = lambda r: r.con.sql(f'SELECT "{UID}", kind_name AS name, kind_flag, birth_date, kind, kind_p, kind_by,
name_p, kind_held FROM records').df()

free = Run(KFINAL, KS)
free.load(DEMO / "kinds.parquet")
done(free)
sheet = kind_review_sheet(free.con, "records", UID, replace(KFINAL.kind, labels_to_draw=600, review_max=150), KS.f
lag_company)
print(f"review sheet: {(sheet['why'] == 'decide').sum():,} records to decide, {(sheet['why'] == 'measure').sum
():,} drawn to measure")
with pd.option_context("display.max_colwidth", 110):  # each row's reason, whole
    display(sheet.groupby("why").head(3)[["why", "reason", "engine_says", "name_says", "flag", "name"]])

sheet["kind"] = np.where(kg.truth.set_index(UID).loc[sheet[UID], "KIND"].eq("company"), 2, 1)  # people's answers:
here, the truth
sheet.to_parquet(DEMO / "kind_answers.parquet")
answered = Run(KFINAL, KS, kind_labels=DEMO / "kind_answers.parquet")
answered.load(DEMO / "kinds.parquet")
done(answered)
c = answered.classifier
line = lambda x, at: at if x <= 1 else "never (no line holds its budget)"
print(f"{c.labels:,} answers, {c.measured:,} of them drawn to measure: company {line(c.line_company, f'at P ≥ {c.l
ine_company:g}')}, "
      f"person {line(c.line_person, f'at P ≤ {1 - c.line_person:.3g}')}; the flag wrong on {c.flag_error:.1%} of t
he answers drawn at random")
after = kinds_of(answered).set_index(UID).join(case.rename("case"))
print(f"held back from matching, the engine and the flag disagreeing: {int(after['kind_held'].sum()):,} records")
display(pd.crosstab(after["case"], after["kind"].map(SAYS)).rename_axis(index="the record is", columns="the engine
says"))

fig, ax = plt.subplots(figsize=(10, 3))
bins = np.linspace(-12, 12, 49)
logodds = np.log(after["name_p"].clip(1e-6, 1 - 1e-6) / (1 - after["name_p"].clip(1e-6, 1 - 1e-6)))
for who, color in (("person", BLUE), ("company", ORANGE), ("representative", RED), ("sole trader", MUTED)):
    ax.hist(logodds[after["case"] == who], bins=bins, histtype="step", linewidth=1.5, color=color, label=who, dens
```


```
ity=True)
ax.axvline(0, color=AXIS, linewidth=0.8)
ax.set(title="What the name alone says, by what the record is", xlabel="log-odds of a company (a legal form: off t
he scale, right)", yticks=[])
ax.legend()
finish(fig)
```

```
load: O(N·L) = O(3,758·L) · 0.10s
review sheet: 150 records to decide, 600 drawn to measure
```

	why	reason	engine_says	name_says	flag	name
0	decide	the engine is sure it is 2 company, the flag says 1: held back from matching until you decide	2 company	2 company (100.0%)	1	ティーアンドピーサクセスマップジャパン(カ
1	decide	the engine is sure it is 2 company, the flag says 1: held back from matching until you decide	2 company	2 company (100.0%)	1	カ)ネイチャー
2	decide	the engine is sure it is 2 company, the flag says 1: held back from matching until you decide	2 company	2 company (100.0%)	1	カ)アールアンドシークリエイティブグループ
150	measure	drawn at random, to measure the flag and the engine	0 not sure	1 person (99.2%)	1	ハマャ　ギエコ
151	measure	drawn at random, to measure the flag and the engine	0 not sure	1 person (100.0%)	1	ヨシタケ　ヒロオ
152	measure	drawn at random, to measure the flag and the engine	0 not sure	1 person (98.5%)	1	フルャケンイチ

```
load: O(N·L) = O(3,758·L) · 0.44s
750 answers, 600 of them drawn to measure: company at P ≥ 0.99, person never (no line holds its budget); the flag wr
ong on 4.5% of the answers drawn at random
held back from matching, the engine and the flag disagreeing: 24 records
```

the engine says the record is	0 not sure	1 person	2 company
company	247	0	507
person	2265	534	0
representative	19	0	12
sole trader	86	88	0



5 · Fit, without labels


Fellegi–Sunter weighs each comparison's agreement level by how much likelier it is for a true match than by chance: log2(m/u) bits. With no labels, λ (the chance two random records match) comes from near-certain rules and their measured recall; u (agreement by chance) from value counts for each comparison's leading exact levels and a random sample of pairs for the rest; m (agreement for true matches) by EM on blocks of equal phones or addresses. The fit uses a fixed-size sample of whole postal areas, so its cost doesn't grow with the file. Then u is measured again on the whole file: how often two records agree by chance depends on how many records there are, and u from the sample would understate the evidence of an agreement on the file. The gate on oversized blocks (section 7) and the scores (section 8) both use these. Below: the bits each level is worth on this file. O(n + S·K + P_em·K) + O(N + S·K).

In [5]:
```
model = run.fit()
done(run)
lam = scaled_prior(model, run.n)
print(f"λ = {lam:.2e} at {run.n:,} records: a pair starts at {math.log2(lam / (1 - lam)):.1f} bits")
params = parameters(run.scoring).dropna(subset=["weight"]).iloc[::-1]

fig, ax = plt.subplots(figsize=(10, 4.4))
ax.barh(params["comparison"] + " · " + params["level"], params["weight"], height=0.6,
        color=np.where(params["weight"] >= 0, BLUE, RED))
```

```
ax.axvline(0, color=AXIS, linewidth=0.8)
ax.set(title="Bits of evidence per comparison level on this file, log2(m/u)", xlabel="bits")
ax.grid(axis="y", visible=False)
ax.tick_params(axis="y", labelsize=7)
finish(fig)
```

```
fit: O(n + S·K + P_em·K) + O(N + S·K) = n = 3,758; u on 3,758 records · 5.51s
λ = 1.47e-04 at 3,758 records: a pair starts at −12.7 bits
```



6 · Rules

Stage 1 is deterministic. An exact rule joins records equal on all its keys; a fuzzy rule needs some keys equal and others close (names within two edits, company names by shared characters, addresses by Jaro–Winkler, a phone one digit off). Before any join, `budget` counts every rule's pairs P = Σ C(k, 2) over its key blocks and stops the run if one is over budget. The first rule in order wins a pair, and a

fuzzy pair is kept only if it touches a record the exact rules left alone. Left: how many true pairs the rules join, clusters included. Right: the true pairs each rule joins itself.

In [6]:
```
plan = run.budget()
done(run)
run.rules()
done(run)
kept = run.con.sql("SELECT * FROM rule_kept").df().assign(true=same)
order = [r.name for st in FINAL.rules.stages for r in st.rules]
stage_of = {r.name: st.name for st in FINAL.rules.stages for r in st.rules}
per_rule = (plan[plan["kind"] == "rule"].set_index("name")[["est_pairs", "largest_block"]].rename(columns={"est_pa
irs": "P"})
            .join(kept.groupby("rule")["true"].agg(joined="size", true="sum")).fillna(0).astype(int).reindex(orde
r))
display(per_rule.rename_axis("rule"))


rule_clusters = run.con.sql("SELECT * FROM rule_clusters").df().set_index(UID)["cluster_id"]
exact_only = connected_components(pd.Series(std.index), kept[kept["stage"] == "exact"], run.db, UID)
m_exact, m_rules = (pair_metrics(c, entity.reindex(c.index)) for c in (exact_only, rule_clusters))
total = m_rules["TP"] + m_rules["FN"]
print(f"the rules join {m_rules['recall']:.1%} of the {total:,} true pairs, with {m_rules['FP']} false")


fig, (a, b) = plt.subplots(1, 2, figsize=(10, 3.4), width_ratios=[1, 1.3])
funnel = pd.Series({"true pairs": total, "joined by the exact rules": m_exact["TP"], "… and the fuzzy rules": m_ru
les["TP"]})[::-1]
a.barh(funnel.index, funnel.to_numpy(), height=0.6, color=BLUE)
for y, v in enumerate(funnel.to_numpy()):
    a.text(v, y, f"  {v / total:.0%}", va="center", color=INK2)
a.set(title="True pairs joined by the rules", xlim=(0, total * 1.15))
a.grid(axis="y", visible=False)
y = np.arange(len(order))[::-1]
for stage, colour in (("exact", BLUE), ("fuzzy", ORANGE)):
    mask = np.array([stage_of[r] == stage for r in order])
    b.barh(y[mask], per_rule["true"].to_numpy()[mask], height=0.6, color=colour, label=f"{stage} rules")
b.set_yticks(y, order, fontsize=7)
b.set(title="True pairs each rule joins (the first rule wins a pair)")
b.grid(axis="y", visible=False)
b.legend(loc="lower right")
finish(fig)
```

```
budget: O(N) = O(3,758) per rule and generator · 0.06s
rules: O(N + Σ P_r·L²) + O(E·d + N) = O(3,758 + 91 pairs) · 0.05s
```

rule	P	largest_block	joined	true
X1_CIF_PERSON_NAME	2	2	2	2
X2_CIF_COMPANY_NAME	0	1	0	0
X3_CIF_PHONE	3	2	2	2
X4_PERSON_NAME_ADDRCD_PHONE	23	2	22	22
X5_COMPANY_NAME_ADDRCD_PHONE	0	1	0	0
F1_NAME~_ADDRCD_PHONE	89	2	44	44
F2_NAME~_ADDRESS~_PHONE	83	3	5	5
F3_NAME~_CIF	14	2	6	6
F4_NAME_ADDRCD_PHONE~	58	3	3	3
F5_COMPANY~_PHONE_POSTAL	107	3	4	4
F6_COMPANY~_ADDRCD_PHONE	89	2	0	0
F7_GIVEN_ADDRCD_PHONE	36	2	3	3

```
the rules join 10.9% of the 855 true pairs, with 0 false
```





7 · Candidates

Stage 2 compares only pairs that some generator lists. A key generator pairs records equal on all its keys; a deletion-key generator pairs names one edit apart (each value and its one-character deletions, within a postal area); a sorted window pairs neighbours in sorted order. Each is one SQL join or window over the records table; their pairs are merged, and pairs inside one rule cluster are dropped. Every key here pairs a share of the records that stays flat as the file grows: a field with a fixed pool of values (the phone's last digits, an address shared by a household) is always combined with another. O(N·L + Σ P_g).


In [7]:
```
report = run.candidates()
done(run)
cands = run.con.sql("SELECT * FROM cands").df().assign(true=same)
targets = missed_pairs(rule_clusters, entity.reindex(rule_clusters.index), UID)  # true pairs the rules left apart
wanted = set(zip(targets[L].astype(str), targets[R].astype(str)))
on_target = np.array([k in wanted for k in zip(cands[L], cands[R])])
report["finds"] = [(found_by(cands, {name}) & on_target).sum() / len(wanted) for name in report["generator"]]
report["different_entity_pairs"] = [(found_by(cands, {name}) & ~cands["true"]).sum() for name in report["generato
r"]]
display(report[["generator", "big_o", "pairs", "finds", "different_entity_pairs", "seconds"]].round(3))
print(f"{len(cands):,} candidate pairs · together they list {on_target.sum() / len(wanted):.1%} of the {len(wante
d):,} true pairs the rules left apart")

fig, (a, b) = plt.subplots(1, 2, figsize=(10, 4.2), sharey=True)
y = np.arange(len(report))[::-1]
a.barh(y, report["pairs"], height=0.6, color=BLUE)
a.set(title="Pairs each generator lists", xscale="log")
b.barh(y, report["finds"], height=0.6, color=BLUE)
b.set(title="Share of the true pairs the rules left apart it finds", xlim=(0, 1))
b.xaxis.set_major_formatter(PercentFormatter(1))
a.set_yticks(y, report["generator"], fontsize=7)
for ax in (a, b):
    ax.grid(axis="y", visible=False)
finish(fig)
```

```
candidates: O(N·L + Σ P_g) = O(3,758·L + 20,977) · 0.12s
```

	generator	big_o	pairs	finds	different_entity_pairs	seconds
0	cif	O(N + P)	4	0.005	0	0.003
1	sn_company_name	O(N log N + N·w)	1961	0.100	1885	0.002
2	phone_prefecture	O(N + P)	131	0.152	15	0.003
3	phone_postal_area	O(N + P)	58	0.073	2	0.003
4	phone_name_initial	O(N + P)	177	0.198	26	0.003
5	sn_person_name	O(N log N + N·w)	8679	0.589	8230	0.002
6	sn_person_name_reversed	O(N log N + N·w)	8664	0.652	8167	0.002
7	person_name	O(N + P)	414	0.521	17	0.003
8	company_name	O(N + P)	61	0.072	6	0.002
9	company_name_deletions	O(N·L + P)	77	0.079	17	0.002
10	person_name_deletions_postal_area	O(N·L + P)	164	0.215	0	0.004
11	given_name_postal	O(N + P)	121	0.159	0	0.003
12	address_phone	O(N + P)	9	0.012	0	0.003
13	address_code_phone	O(N + P)	16	0.021	0	0.002
14	address_name_initial	O(N + P)	81	0.089	13	0.003
15	address_code_name_initial	O(N + P)	137	0.147	25	0.003
16	given_name_address_code	O(N + P)	77	0.101	0	0.002
17	cif_deletions	O(N·L + P)	8	0.010	0	0.007
18	birth_date	O(N + P)	13	0.010	5	0.002
19	given_name_phone	O(N + P)	116	0.152	0	0.003
20	birth_date_deletions_prefecture	O(N·L + P)	9	0.008	3	0.002

18,994 candidate pairs · together they list 87.3% of the 762 true pairs the rules left apart



8 · Score

Every candidate pair gets its weight: the prior plus each comparison's bits, with the u section 5 measured on this file. A pair is accepted at the threshold `scripts/choose.py` chose. O(C·K·L²).


In [8]:

```
run.score()
done(run)
scores = run.con.sql("SELECT * FROM scores").df().assign(same=same)
threshold = run.pipeline.fs.min_match_weight
w = scores["match_weight"]
print(f"{len(scores):,} pairs scored · {(w >= threshold).sum():,} reach {threshold:g} bits, "
      f"{(scores['same'] & (w >= threshold)).sum():,} of them true")

fig, ax = plt.subplots(figsize=(10, 3.4))
```

```
bins = np.arange(math.floor(w.min()), math.ceil(w.max()) + 1)
ax.hist(w[scores["same"]], bins, histtype="step", color=BLUE, linewidth=2, label="same entity")
ax.hist(w[~scores["same"]], bins, histtype="step", color=ORANGE, linewidth=2, label="different entities")
ax.axvline(threshold, color=INK2, linewidth=1)
ax.text(threshold, ax.get_ylim()[1], f" threshold {threshold:g} bits", va="top", color=INK2)
ax.set(title="Weights of the candidate pairs", xlabel="match weight (bits)", ylabel="pairs", yscale="log")
ax.legend(loc="upper right")
finish(fig)
```

```
score: O(C·K·L²) = O(18,994·6·L²) · 0.12s
18,994 pairs scored · 308 reach 8 bits, 308 of them true
```



9 · Why a pair matches

A weight is a sum, so it can be read term by term. Two pairs: the accepted true match closest to the threshold whose names differ, and the rejected pair of different entities closest to it. Each bar is one term: the prior, then the bits of the level each comparison landed in.


In [9]:
```
show = list(FINAL.explain_show)
filled = list(FINAL.explain_filled)
left, right = std.loc[scores[L], show].set_index(scores.index), std.loc[scores[R], show].set_index(scores.index)
```

```
both_filled = (left[filled].notna() & right[filled].notna()).all(axis=1)
differs = (left[filled[0]] != right[filled[0]]).fillna(False)
accepted = w >= threshold
picked = {"Accepted: a true match with a typo": scores[accepted & scores["same"] & both_filled & differs].sort_val
ues(["match_weight", L, R]).head(1),
          "Rejected: different entities": scores[~accepted & ~scores["same"]].sort_values(["match_weight", L, R],
ascending=[False, True, True]).head(1)}

fig, axes = plt.subplots(1, 2, figsize=(10, 3.6), sharey=True)
ends = []
for ax, (title, pair) in zip(axes, picked.items()):
    row = pair.iloc[0]
    display(std.loc[[row[L], row[R]], show])
    bits = waterfall(run.scoring, {c.name: row[f"gamma_{c.name}"] for c in run.pipeline.fs.model.comparisons}, ru
n.n)
    end = bits["bits"].cumsum().to_numpy()
    start = np.concatenate([[0], end[:-1]])
    ends += [*start, *end]
    ax.bar(bits["evidence"], bits["bits"], bottom=start, width=0.6, color=np.where(bits["bits"] >= 0, BLUE, RED))
    ax.plot(len(bits) - 0.5, end[-1], marker="o", markersize=7, color=INK, clip_on=False)
    ax.axhline(threshold, color=INK2, linewidth=1)
    ax.text(-0.4, threshold, f"threshold {threshold:g}", va="bottom", color=INK2)
    ax.axhline(0, color=AXIS, linewidth=0.8)
    ax.set(title=f"{title}: {row['match_weight']:.1f} bits")
    ax.grid(axis="x", visible=False)
axes[0].set(ylabel="running total (bits)", ylim=(min(ends) - 2, max(ends + [threshold]) + 2))
finish(fig)
```

CONT_ID	full_name	company_name	address	phone	customer_id
0000000399	ヤベケイト	NaN	東京都昭島市田中町2-12-24	4505	8766633794722
0000001035	ャベケイド	NaN	東京都港区西新橋1-20-5	4501	1909916302348

CONT_ID	full_name	company_name	address	phone	customer_id
0000001923	サンガジシリナオキ	NaN	茨城県常総市水海道天満町10-8	4162	1305064375017
0000002186	NaN	アサヒアルミサンギョウカブシキガイシャオオサカシテン	茨城県常総市21-14	4162	8324699326995



10 · Threshold


`scripts/choose.py` chose the threshold on cross-validated labelled data: the lowest weight at which no false pair was accepted and the upper bound of the false-merge rate stays under 5%, then one step stricter. A run without labels uses it as it is. Here, with this file's truth: what each weight would accept.

In [10]:
```
with timed(f"O(C·G) = O({len(scores):,} pairs · 25 weights)"):
    grid = np.arange(-4.0, 21.0)
    curve = pd.DataFrame({"weight": grid,
                          "recall": [(scores["same"] & (w >= x)).sum() / len(wanted) for x in grid],
                          "false_pairs": [(~scores["same"] & (w >= x)).sum() for x in grid]})

fig, (a, b) = plt.subplots(1, 2, figsize=(10, 3.2))
a.plot(curve["weight"], curve["recall"], color=BLUE)
a.set(title="Share of the true pairs the rules left apart, accepted", xlabel="threshold (bits)", ylim=(0, 1))
a.yaxis.set_major_formatter(PercentFormatter(1))
b.plot(curve["weight"], curve["false_pairs"], color=ORANGE)
```

```
b.set(title="Pairs of different entities accepted", xlabel="threshold (bits)")
for ax in (a, b):
    ax.axvline(threshold, color=INK2, linewidth=1)
finish(fig)
```

```
O(C·G) = O(18,994 pairs · 25 weights) · 0.00s
```



11 · Cluster and evaluate

The accepted pairs and the rules' pairs are clustered together (connected components, in SQL). Gold gives each record its cluster and what resolved it: a rule, or the model. Without labels, the run also says how many of the model's links it expects to be false: the sum of 1 − match probability over them. Then, with the truth: pairwise recall with its 95% interval, false merges, and the upper bound of the false-merge rate. Below: cluster sizes against true entity sizes, and the largest cluster. Each customer's kind comes from its records: 2 company if any record surely is one, 1 person if no record leans company and one surely is a person, else 0 not sure. This file has no flag and nobody answered, so only a written legal form makes a company (section 4 shows the rest). O(C + E·d + N).

In [11]:
```
run.cluster()
done(run)
shutil.rmtree(DEMO / "run", ignore_errors=True)
run.write(DEMO / "run")
```


```
done(run)
gold = pd.read_parquet(DEMO / "run" / "gold.parquet").set_index(UID)
m = cluster_metrics(gold["cluster_id"], entity.reindex(gold.index))
linked = next(s for s in run.steps if s["step"] == "cluster")
print(f"model links {linked['accepted']:,} · false as the model expects {linked['expected_false']:.2f} · "
      f"false with the truth {(~same(run.con.sql('SELECT * FROM matches').df())).sum()}")
print(f"recall {m['recall']:.1%} ({m['recall_lo']:.1%}–{m['recall_hi']:.1%}) · false merges {m['FP']} "
      f"(rate at most {m['fp_rate_hi']:.2%}) · precision {m['precision']:.2%}")
display(gold["resolved_by"].fillna("(alone)").value_counts().rename_axis("resolved by").to_frame("records"))
print("customers:", " · ".join(f"{n:,} × {SAYS[k]}" for k, n in gold.drop_duplicates("cluster_id")["customer_kin
d"].value_counts().items()))

sizes = lambda ids: ids.value_counts().clip(upper=5).value_counts().reindex(range(1, 6), fill_value=0)
fig, ax = plt.subplots(figsize=(10, 3))
x = np.arange(1, 6)
ax.bar(x - 0.16, sizes(gold["cluster_id"]), width=0.3, color=BLUE, label="clusters found")
ax.bar(x + 0.16, sizes(entity), width=0.3, color=ORANGE, label="true entities")
ax.set_xticks(x, ["1", "2", "3", "4", "5+"])
ax.set(title="Records per cluster, against records per true entity", xlabel="records", yscale="log")
ax.grid(axis="x", visible=False)
ax.legend()
finish(fig)
largest = gold["cluster_id"].value_counts().index[0]
display(std.loc[gold.index[gold["cluster_id"] == largest], show].assign(entity=entity))
```

```
cluster: O(C + E·d + N) = O(18,994 + 300·d + 3,758) · 0.03s
write: O(N + C) = O(3,758 + 300) · 0.02s
model links 300 · false as the model expects 0.28 · false with the truth 0
recall 48.0% (44.6%–51.3%) · false merges 0 (rate at most 0.73%) · precision 100.00%
```

resolved by	records
(alone)	3067
fs	511
F1_NAME~_ADDRCD_PHONE	88
X4_PERSON_NAME_ADDRCD_PHONE	44
F3_NAME~_CIF	11
F2_NAME~_ADDRESS~_PHONE	9
F5_COMPANY~_PHONE_POSTAL	8
F7_GIVEN_ADDRCD_PHONE	6
F4_NAME_ADDRCD_PHONE~	6
X1_CIF_PERSON_NAME	4
X3_CIF_PHONE	4

customers: 2,882 × 0 not sure · 511 × 2 company



CONT_ID	full_name	company_name	address	phone	customer_id	entity
0000000640	コバヤシタツヤ	NaN	埼玉県ふじみ野市上ノ原1-3-21	7543	8480021922415	E001400
0000000998	コバヤシタツヤ	NaN	埼玉県ふじみ野市上ノ原1-3-21	7543	3057483762514	E001400
0000001974	コバヤシタツヤ	NaN	埼玉県ふじみ野市上ノ原1-3-21	4477	8334742939420	E001400
0000002491	コバヤシタツヤ	NaN	埼玉県さいたま市浦和区駒場2-25-10	7543	1663636056484	E001400

12 · Increment

New records only. An increment joins the batch against all the records, rule by rule and generator by generator, scores the pairs that touch it, and merges into the stored clusters, each existing cluster one node. So its cost grows with the batch, not with the file. Here: a full run on 90% of the records with the model fitted above, then the other 10% as an increment, compared with the full run on all of them in section 11. The increment keeps the stored u, except the exact levels, which it counts again: a comparison's sampled u are measured again only once the drift of its exact level exceeds their sampling error, since a new sample would otherwise only redraw the noise. The steps that follow the data (rules, candidates, cluster) follow the batch.


In [12]:
```
batch = np.random.default_rng(0).random(len(g.df)) < 0.1
g.df[~batch].to_parquet(DEMO / "first_90.parquet", index=False)
g.df[batch].to_parquet(DEMO / "new_10.parquet", index=False)
shutil.rmtree(DEMO / "increment", ignore_errors=True)
base = Run(FINAL, S, model=model).full(DEMO / "first_90.parquet", DEMO / "increment")
inc = Run(FINAL, S).increment(DEMO / "new_10.parquet", DEMO / "increment")
for s in inc.steps:
    print(f"increment {s['step']}: {s['big_o']} = {s['filled']} · {s['seconds']:.2f}s")
for name, b in inc.basis.items():  # what the increment did with u, comparison by comparison
    x = b["last_check"]
    se = x["se_bits"] if x["se_bits"] is not None else float("inf")
    print(f"u of {name}: drifted {x['drift_bits']:.3f} bits, sampling error {se:.3f} → {'sampled again' if x['drif
t_bits'] > se else 'kept'}")

after = pd.read_parquet(DEMO / "increment" / "gold.parquet").set_index(UID)["cluster_id"]
new_ids = set(g.df.loc[batch, UID])
old_in = after[~after.index.isin(new_ids)].unique()
joined = after[after.index.isin(new_ids) & after.isin(old_in)]
truth = predicted_pairs(entity)
by_inc, by_full = predicted_pairs(after), predicted_pairs(gold["cluster_id"])
print(f"{batch.sum():,} new records · {len(joined):,} joined an existing cluster · pairs only in the increment: "
      f"{len((by_inc - by_full) & truth)} true, {len((by_inc - by_full) - truth)} false · only in the full run: "
      f"{len((by_full - by_inc) & truth)} true, {len((by_full - by_inc) - truth)} false")

steps = ["load", "budget", "fit", "rules", "candidates", "score", "cluster", "write"]
seconds = lambda r: pd.Series({s["step"]: s["seconds"] for s in r.steps}).reindex(steps, fill_value=0)
fig, ax = plt.subplots(figsize=(10, 3.2))
y = np.arange(len(steps))[::-1]
```

```
ax.barh(y + 0.16, seconds(base), height=0.3, color=BLUE, label=f"full run, {(~batch).sum():,} records (model give
n)")
ax.barh(y - 0.16, seconds(inc), height=0.3, color=ORANGE, label=f"increment, {batch.sum():,} records")
ax.set_yticks(y, steps)
ax.set(title="Seconds per step", xlabel="seconds", xscale="log")
ax.grid(axis="y", visible=False)
ax.legend(loc="lower right")
finish(fig)
```

```
increment load: O(N·L) = O(390·L) · 0.05s
increment fit: O(N + S·K_stale) = O(3,758 + 10,000,000·2) · 4.08s
increment rules: O(|Δ|·Σ b + scan) = O(390 new records) · 0.04s
increment candidates: O(|Δ|·Σ b + scan) = 3,814 pairs touching the batch · 0.10s
increment score: O(C_Δ·K·L²) = O(3,814·6·L²) · 0.08s
increment cluster: O(C_Δ + touched clusters) = 61 accepted · 0.02s
increment write: O(N + C) = O(3,758 + 61) · 0.01s
u of name: drifted 0.063 bits, sampling error 0.017 → sampled again
u of company: drifted 0.072 bits, sampling error 0.126 → kept
u of address: drifted 0.012 bits, sampling error 0.004 → sampled again
u of phone: drifted 0.017 bits, sampling error inf → kept
u of cif: drifted 0.170 bits, sampling error inf → kept
u of birth: drifted 0.336 bits, sampling error inf → kept
390 new records · 73 joined an existing cluster · pairs only in the increment: 6 true, 0 false · only in the full ru
n: 0 true, 0 false
```



13 · How the configuration was chosen

`scripts/choose.py` starts from `config/pipeline.toml` and tries the changes in `config/experiments.py` in order, each on top of the choice so far, on labelled synthetic data. A change is adopted by the decision rule: "better" needs a significant paired gain on the selection set; "cheaper" and "safer", no true pair lost; "chosen" is the owner's call, where no false pair may be added. On validation, all but "chosen" must lose no true pair. Test is scored once, at the end. Its tables are in `reports/choose.md`; read here, not recomputed.

In [13]:
```
text = (S.root / "reports" / "choose.md").read_text(encoding="utf-8")
for stage in ("## Stage 1: rules", "## Stage 2: Fellegi–Sunter"):
    decisions = table_after(text.split(stage, 1)[1], "### Decisions")
    print(stage[3:])
    display(decisions.iloc[:, :8])
print(next(line for line in (S.root / "config" / "final.toml").read_text(encoding="utf-8").splitlines() if line.st
artswith("# Adopted")))
```

```
Stage 1: rules
```

	change	kind	adopted	train_TP_gains	train_TP_losses	train_p	train_FP_added	train_FP_removed
0	fold_levenshtein	better	True	17	4	0.0072	0	0
1	fold_exact	cheaper	False	0	83	0.0	0	0
2	f2_address_exact	cheaper	True	0	0	1.0	0	0
3	f2_address_prefix	cheaper	True	0	0	1.0	0	0
4	optuna_comparators	better	True	33	0	0.0	0	0

Stage 2: Fellegi–Sunter

	change	kind	adopted	cv_TP_gains	cv_TP_losses	cv_p	cv_FP_added	cv_FP_removed
0	no_term_frequency	better	True	12	0	0.0005	0	0
1	exact_keys_only	cheaper	True	0	0	1.0	0	0
2	optuna_suggestion	better	True	1488	1	0.0	0	0
3	u_from_1e6_pairs	cheaper	False	1	8	0.0391	0	0
4	compound_phone_keys	cheaper	True	0	0	1.0	0	0
5	sorted_names_for_tfidf	cheaper	True	1	0	1.0	0	0
6	name_keys	safer	True	1	0	1.0	0	0
7	bounded_address_keys	cheaper	True	0	0	1.0	0	0
8	no_sorted_windows	cheaper	False	0	0	1.0	0	0
9	bridge_rule_clusters	better	False	0	0	1.0	0	0
10	u_from_scored_file	chosen	True	0	60	0.0	0	0
11	u_exact_by_counts	chosen	True	47	5	0.0	0	0
12	cif_one_digit_off	better	True	8	0	0.0078	0	0
13	cif_deletion_key	safer	True	2	0	0.5	0	0
14	graded_address	better	True	124	67	0.0	0	0
15	birth_date	better	True	56	0	0.0	0	0
16	birth_date_key	safer	True	1	0	1.0	0	0
17	given_name_phone_key	safer	True	0	0	1.0	0	0
18	birth_date_deletion_key	safer	True	0	0	1.0	0	0
19	u_near_by_keys	chosen	True	0	2	0.5	0	0
20	fit_u_from_1e6_pairs	cheaper	True	0	0	1.0	0	0
21	company_without_jw_high	cheaper	True	1	0	1.0	0	0
22	name_needed	chosen	True	0	39	0.0	0	0

```
# Adopted: rules fold_levenshtein, f2_address_exact, f2_address_prefix, optuna_comparators; Fellegi–Sunter no_term_f
requency, exact_keys_only, optuna_suggestion, compound_phone_keys, sorted_names_for_tfidf, name_keys, bounded_addres
s_keys, u_from_scored_file, u_exact_by_counts, cif_one_digit_off, cif_deletion_key, graded_address, birth_date, birt
h_date_key, given_name_phone_key, birth_date_deletion_key, u_near_by_keys, fit_u_from_1e6_pairs, company_without_jw_
high, name_needed.
```

14 · Cost as the file grows

Every step's Big-O, for this full run and for the increment, with the numbers filled in. A full run is O(N·L + Σ P + C·K·L² + E·d), plus the fit and the u sample, whose sizes are fixed. When every key's pairs per record stay flat, that is linear in N. An increment of Δ records costs O(|Δ|·(L + Σ b) + C_Δ·K·L²) plus scans of the stored records. Below, measured by `scripts/benchmark.py` (`reports/benchmark.md`): each file resolved in a process of its own, up to a million records.

In [14]:
```
full_steps = pd.DataFrame(run.steps)[["step", "big_o", "filled", "seconds", "peak_memory_gb"]]
inc_steps = pd.DataFrame(inc.steps)[["step", "big_o", "filled", "seconds"]]
display(full_steps, inc_steps)

curve = table_after((S.root / "reports" / "benchmark.md").read_text(encoding="utf-8"), "## Cost")
curve = curve[pd.to_numeric(curve["seconds"], errors="coerce").notna()].astype({"records": int, "seconds": float,
"peak_memory_gb": float})
fig, (a, b) = plt.subplots(1, 2, figsize=(10, 3.2))
for ax, col, title in ((a, "seconds", "Seconds, end to end"), (b, "peak_memory_gb", "Peak memory (GB)")):
    ax.plot(curve["records"], curve[col], color=BLUE, marker="o", markersize=6)
    ax.set(title=title, xlabel="records (log scale)", xscale="log", ylim=(0, curve[col].max() * 1.15))
    ax.xaxis.set_major_formatter(FuncFormatter(lambda x, _: f"{x:,.0f}"))
    last = curve.iloc[-1]
    ax.annotate(f"{last[col]:g} at {last['records']:,}", (last["records"], last[col]), textcoords="offset points",
                xytext=(-8, 8), ha="right", color=INK2)
finish(fig)
```

	step	big_o	filled	seconds	peak_memory_gb
0	load	O(N·L)	O(3,758·L)	0.10	0.51
1	fit	O(n + S·K + P_em·K) + O(N + S·K)	n = 3,758; u on 3,758 records	5.51	0.85
2	budget	O(N)	O(3,758) per rule and generator	0.06	0.86
3	rules	O(N + Σ P_r·L²) + O(E·d + N)	O(3,758 + 91 pairs)	0.05	0.86
4	candidates	O(N·L + Σ P_g)	O(3,758·L + 20,977)	0.12	0.87
5	score	O(C·K·L²)	O(18,994·6·L²)	0.12	0.88
6	cluster	O(C + E·d + N)	O(18,994 + 300·d + 3,758)	0.03	0.89
7	write	O(N + C)	O(3,758 + 300)	0.02	0.89

	step	big_o	filled	seconds
0	load	O(N·L)	O(390·L)	0.05
1	fit	O(N + S·K_stale)	O(3,758 + 10,000,000·2)	4.08
2	rules	O(|Δ|·Σ b + scan)	O(390 new records)	0.04
3	candidates	O(|Δ|·Σ b + scan)	3,814 pairs touching the batch	0.10
4	score	O(C_Δ·K·L²)	O(3,814·6·L²)	0.08
5	cluster	O(C_Δ + touched clusters)	61 accepted	0.02
6	write	O(N + C)	O(3,758 + 61)	0.01

