

MLCC X5R/X7R Series approval sheet



General Specification

■ General introduction:

Ceramic capacitors (or condenser) are widely used in electronic circuitry for coupling, de-coupling and in filters.

These different functions require specific capacitor properties. Ceramic capacitors can be divided into two classes,

● Class 1

In these capacitors dielectric materials are used which have a very high specific resistance, very good Q and linear temperature dependence.

They are used in such applications as oscillators and filters where low losses, capacitance drift compensation and high stability are required.

● Class 2

These capacitors have higher losses and have non-linear characteristics. They are used for coupling and de-coupling.

■ Construction:

The capacitance of a ceramic capacitor depends on the area of the electrodes (A), the thickness of the ceramic dielectric (t) and the dielectric constant of the ceramic material (ϵ_r); and on the number of dielectric layers (n) with multi-layer ceramic capacitors :

$$C = \epsilon_r \times \epsilon_0 \times A/t \times n$$

The standard capacitance unit is the "Farad". A capacitor has capacitance of one farad is when one coulomb charges two parallel conductive plate to one volt potential.

The rated voltage is dependent on the dielectric strength, which is mainly governed by the thickness of the dielectric layer and the ceramic structure. For this reason a reduction of the layer thickness is limited. Figure 1 shows the construction of a multi-layer capacitor.

The electrodes are normally mixed palladium with silver since the electrodes are applied before the ceramic is fired at a temperature where silver would oxidize.

■ Manufacturing of ceramic capacitors

The raw materials are finely milled and carefully mixed. Thereafter the powders are calcined at temperatures between 1100°C and 1300°C to achieve the required chemical composition.

Then, the resultant mass is reground and dopes and/or sintering means are added.

The finely ground material is mixed with a solvent and binding matter. Casting or rolling obtains thin sheets. For multi-layer capacitors electrode material is printed on the sheets and after stacking and pressing of the sheets co-fired with the ceramic compact at temperatures between 1000°C and 1400°C.

The totally enclosed electrodes of a multi-layer capacitor guarantee good life test behavior as well.

■ Operating Voltage

The operating voltage for the capacitors must always be lower than its rated voltage. If an AC voltage is applied, the peak voltage should be lower than the rated voltage of the capacitor. And if both AC and a pulse voltage may be presented, then the sum of the peak should also be lower than the rated voltage of the capacitor chosen.

■ E Standard Number

E 3	1.0								2.2								4.7							
E 6	1.0				1.5				2.2				3.3				4.7				6.8			
E12	1.0		1.2		1.5		1.8		2.2		2.7		3.3		3.9		4.7		5.6		6.8		8.2	
E24	1.0	1.1	1.2	1.3	1.5	1.6	1.8	2.0	2.2	2.4	2.7	3.0	3.3	3.6	3.9	4.3	4.7	5.1	5.6	6.2	6.8	7.5	8.2	9.1

* Non-standard capacitance is available on request.


■ Available Tolerance

T. C.	Capacitance *	Standard Tolerance	Available Tolerance on Request
NP0 (C0G)	Cap < 5pF	C = $\pm 0.25\text{pF}$ D = $\pm 0.5\text{pF}$	B = $\pm 0.1\text{pF}$
	$5\text{pF} \leq \text{Cap} < 10\text{pF}$	D = $\pm 0.5\text{pF}$	B = $\pm 0.1\text{pF}$ C = $\pm 0.25\text{pF}$
	Cap $\geq 10\text{pF}$ E12	J = $\pm 5\%$ K = $\pm 10\%$	F = $\pm 1\%$ G = $\pm 2\%$
X5R X7R	E6	K = $\pm 10\%$ M = $\pm 20\%$	J = $\pm 5\%$
Y5V	E3	Z = -20% to +80%	M = $\pm 20\%$

* Non-standard capacitance is available on request.



Physical Outline




Code	Material Type Elements	Temperature Compensation Class I		High Permittivity Class II	
		NME*	BME*	NME*	BME*
1	Dielectric	TiO ₂	CaZrO ₃	BaTiO ₃	BaTiO ₃
2	Electrode	PdAg	Ni	PdAg	Ni
3	Termination**	Ag	Cu	Ag	Cu
4		Ni			
5		Sn			

* NME (Nobel Metal Electrode), BME (Base Metal Electrode)

** All Darfon's MLCC products are produced under lead-free plating process and in compliance with the lead-free requirement of Green Plan and ROHS.

■ Dimensions



TYPICAL TOLERANCE

SIZE CODE (EIA)	L (Length)	W (Width)	T (Max Thickness)	g (Min)	A (Termination Min/Max)	UNIT
0603 (0201)	0.6+/-0.03 (0.024+/-0.001)	0.3+/-0.03 (0.012+/-0.001)	0.33 (0.013)	0.15 (0.006)	0.10/0.20 (0.004/0.008)	mm (inch)
1005 (0402)	1.0 +/- 0.05 (0.040 +/- 0.002)	0.5 +/- 0.05 (0.020 +/- 0.002)	0.55 (0.022)	0.30 (0.012)	0.10 / 0.30 (0.004 / 0.012)	mm (inch)
1608 (0603)	1.6 +/- 0.10 (0.063 +/- 0.004)	0.8 +/- 0.10 (0.031 +/- 0.004)	0.90 (0.035)	0.50 (0.020)	0.25 / 0.65 (0.010 / 0.026)	mm (inch)
2012 (0805)	2.0 +/- 0.15 (0.079 +/- 0.006)	1.25 +/- 0.20 (0.049 +/- 0.008)	1.45 (0.057)	0.70 (0.028)	0.25 / 0.75 (0.010 / 0.030)	mm (inch)
3216 (1206)	3.2 +/- 0.15 (0.126 +/- 0.006)	1.6 +/- 0.20 (0.063 +/- 0.008)	1.80 (0.069)	1.50 (0.060)	0.25 / 0.75 (0.010 / 0.030)	mm (inch)
3225 (1210)	3.2 +/- 0.20 (0.126 +/- 0.008)	2.5 +/- 0.20 (0.098 +/- 0.008)	2.70 (0.106)	1.50 (0.060)	0.25 / 0.75 (0.010 / 0.030)	mm (inch)

SPECIAL TOLERANCE

SIZE CODE (EIA)	L (Length)	W (Width)	T (Max Thickness)	g (Min)	A (Termination Min/Max)	UNIT
1005* (0402)	1.0 +/- 0.15 (0.040 +/- 0.006)	0.5 +/- 0.15 (0.020 +/- 0.006)	0.65 (0.026)	0.30 (0.012)	0.10 / 0.30 (0.004 / 0.012)	mm (inch)
1608* (0603)	1.6 + 0.15/-0.1 (0.063 +0.006/- 0.004)	0.8 + 0.15/-0.1 (0.031 +0.006/-0.004)	0.95 (0.037)	0.50 (0.020)	0.25 / 0.65 (0.010 / 0.026)	mm (inch)
2012* (0805)	2.0 +/- 0.20 (0.079 +/- 0.008)	1.25 -0.20/+0.30 (0.049 -0.008/+0.012)	1.55 (0.061)	0.70 (0.028)	0.25 / 0.75 (0.010 / 0.030)	mm (inch)
3216* (1206)	3.2 +/- 0.20 (0.126 +/- 0.008)	1.6 -0.20/+0.30 (0.063 -0.008/+0.012)	1.90 (0.075)	1.50 (0.060)	0.25 / 0.75 (0.010 / 0.030)	mm (inch)
3225* (1210)	3.2 +/- 0.30 (0.126 +/- 0.012)	2.5 +/- 0.30 (0.098 +/- 0.012)	2.80 (0.11)	1.50 (0.060)	0.25 / 0.75 (0.010 / 0.030)	mm (inch)

DARFON Part Number

C 1005 NP0 101 J G T S

PRODUCT CODE

C = Capacitor SMD

SIZE in mm (EIA CODE, in inch)

0402(01005)	0603(0201)	1005 (0402)	1608 (0603)	2012 (0805)
3216 (1206)	3225(1210)	4520 (1808)	4532 (1812)	

T. C.

NP0: 0 ± 30ppm/°C	-55°C to +125°C
X7R: ±15%	-55°C to +125°C
X5R: ±15%	-55°C to +85°C
Y5V: +22%/-82%	-30°C to +85°C

CAPACITANCE CODE

Expressed in pico-farads and identified by a three-digit number.

First two digits represent significant figures.

Last digit specifies the number of zeros.

(Use 9 for 1.0 through 9.9pF ; Use 8 for 0.2 through 0.99pF)

(Example: 2.2pF=229 or 0.47pF=478)

TOLERANCE CODE

A: ± 0.05pF	B: ± 0.1pF	C: ± 0.25pF	D: ± 0.5pF	F: ±1%	G: ±2%
J: ±5%	K: ±10%	M: ±20%	Z: +80/-20%		

VOLTAGE CODE

B: 4V	C: 6.3V	D: 10V	E: 16V	F: 25V	N: 35V	G: 50V	H: 100V
J: 200V	K: 250V	L: 500V	M: 630V	P: 1KV	Q: 2KV	R: 3KV	S: 4KV

PACKAGING CODE

T: Paper tape reel Ø180mm (7")
 N: Paper tape reel Ø250mm (10")
 A: Paper tape reel Ø330mm (13")
 B: Bulk, loosed in bag
 W: Special Packing

P: Embossed tape reel Ø180mm (7")
 D: Embossed tape reel Ø250mm (10")
 E: Embossed tape reel Ø330mm (13")
 C: Bulk cassette

Product Type

S: Standard Ceramic Capacitor

Q: High Q/Low ESR

■ Product Range

● NP0 (Class I)

Type		Size				
T.C.	RV	0603 (0201)	1005 (0402)	1608 (0603)	2012 (0805)	3216 (1206)
NPO Class I	16V			2.7nF~3.3nF		12nF~39nF
	25V	0.20pF~100pF	0.20pF~22pF			
	50V	0.20pF~18pF	0.20pF~470pF/1nF	0.20pF~2.2nF	0.50pF~10nF	1.50pF~10nF
	100V		0.20pF~220pF	0.20pF~1nF	0.50pF~3.3nF	1.50pF~4.7nF

● X7R (Class II)

Type		Size					
T.C.	RV	0603 (0201)	1005 (0402)	1608 (0603)	2012 (0805)	3216 (1206)	3225 (1210)
X7R Class II	6.3V				4.7uF~10uF		
	10V	3.3nF/4.7nF/10nF	100pF~100nF	100pF~1uF	1uF/2.2uF/4.7uF/10uF	2.2uF	
	16V		100pF~100nF	100pF~1uF	330nF/470nF/1uF/ 2.2uF	470nF~10uF	10uF
	25V	100pF~2.2nF	100pF~22nF	100pF~1uF	1nF~1uF	220nF~4.7uF	4.7uF/10uF
	50V	100pF~2.2nF	100pF~10nF	100pF~100nF	150pF~470nF	1nF~1uF	
	100V			100pF~10nF	150pF~22nF	1nF~100nF	

● X5R (Class II)

Type		Size					
T.C.	RV	0603 (0201)	1005 (0402)	1608 (0603)	2012 (0805)	3216 (1206)	3225 (1210)
X5R Class II	6.3V	2.2nF~220nF	470nF~4.7uF	2.2uF/ 4.7uF/10uF	4.7uF~22uF	22uF/47uF	47uF/100uF
	10V	2.2nF~100nF	15nF~1uF	220nF~4.7uF	2.2uF~10uF	2.2uF~10uF	22uF
	16V		15nF~1uF	220nF~2.2uF	1uF~10uF	2.2uF~10uF	4.7uF~22uF
	25V		100nF	220nF/1uF	1uF~4.7uF	2.2uF~10uF	4.7uF/ 10uF

● Y5V (Class II)

Type		Size			
T.C.	RV	0603 (0201)	1005 (0402)	1608 (0603)	2012 (0805)
Y5V Class II	6.3V	22nF~100nF	10nF~1uF	10nF~2.2uF	
	10V		10nF~1uF	10nF~2.2uF	
	16V		10nF~220nF	10nF~2.2uF	100nF~2.2uF
	25V		10nF~100nF	10nF~330nF	100nF ~2.2uF
	50V		10nF~33nF	10nF~220nF	100nF~1uF

Note : (1) Other size, capacitance, and voltage are available upon customer's request.

(2) Product range might be extended due to technology improvement or new product released : for up-to-date information, please contact our sales.


(3) Part of Y5V product will be phased out.

■ Packaging

● Tape and Reel Packaging

Tape and reel packaging is currently the most promising system for high-speed production. A typical 180mm (7 inch) diameter reel contains 1,500 to 15,000 capacitors, 250mm (10 inch) contains 10,000 capacitors, and 330mm (13 inch) contains 10,000 to 50,000 capacitors. Three standard sizes are available in taped and reeled package either with paper carrier tapes or embossed tapes.


● Reel Specifications



TAPE WIDTH (mm)	G (mm)	T max. (mm)	D (mm)
8	10.0 +/- 1.5	14.5	180
8	10.0 +/- 1.5	14.5	250
8	10.0 +/- 1.5	14.5	330
12	14.0 +/- 1.5	18.5	180




Paper Tape Specifications



SYMBOL	PRODUCT SIZE CODE										UNIT
	0603 (0201)		1005 (0402)		1608 (0603)		2012 (0805)		3216 (1206)		
	SIZE	TOL.	SIZE	TOL.	SIZE	TOL.	SIZE	TOL.	SIZE	TOL.	
A	0.38	+/- 0.04	0.60	+/- 0.04	1.0	+/- 0.2	1.5	+/- 0.2	1.9	+/- 0.2	mm
B	0.68	+/- 0.04	1.12	+/- 0.04	1.8	+/- 0.2	2.3	+/- 0.2	3.6	+/- 0.2	mm
F	3.50	+/- 0.05	3.50	+/- 0.05	3.5	+/- 0.05	3.5	+/- 0.05	3.5	+/- 0.05	mm
P	2.00	+/- 0.10	2.00	+/- 0.10	4.0	+/- 0.1	4.0	+/- 0.1	4.0	+/- 0.1	mm
W	8.00	+/- 0.20	8.00	+/- 0.20	8.0	+/- 0.2	8.0	+/- 0.2	8.0	+/- 0.2	mm

- Embossed Tape Specifications

4mm and 8mm pitch tape



K_0 : so chosen that the orientation of the component cannot change.

For $W = 8\text{mm}$: $T_2 = 2.5\text{mm}$ max.

For $W = 12\text{mm}$: $T_2 = 4.5\text{mm}$

DIMENSION (mm)	PRODUCT SIZE CODE					TOLERANCE (mm)
	4 mm tape			8 mm tape		
	2012 (0805)	3216 (1206)	3225 (1210)	4520 (1808)	4532 (1812)	
P ₁	4	4	4	8	8	+/- 0.10
P ₀	4	4	4	4	4	+/- 0.10
P ₂	2	2	2	2	2	+/- 0.05
A ₀ nominal clearance*	0.2	0.3	0.3	0.4	0.4	-
B ₀ nominal clearance*	0.2	0.3	0.3	0.4	0.4	-
K ₀ minimum clearance*	0.05	0.05	0.05	0.05	0.05	-
W	8.0	8.0	8.0	12.0	12.0	+/- 0.20
E	1.75	1.75	1.75	1.75	1.75	+/- 0.10
F	3.5	3.5	3.5	5.5	5.5	+/- 0.05
D ₀	1.5	1.5	1.5	1.5	1.5	+0.1/-0.0
D ₁	1 min	1 min	1 min	1.5 min	1.5 min	+0.1/-0.0
T	0.25	0.25	0.25	0.25	0.25	+/- 0.10
T ₁	0.05	0.05	0.05	0.05	0.05	+/- 0.01
T ₂	2.5 max.	2.5 max.	2.5 max.	4.5	4.5	-

* Typical capacitors displace in pocket.


- Thickness and Taping Amount

Thickness			Amount per reel					
			180 mm (7")		250 mm (10")		330 mm (13")	
Code	Spec	Size(EIA)	Paper	Embossed	Paper	Embossed	Paper	Embossed
A	0.30+/-0.03	0603 (0201)	15K					
B	0.50+/-0.05	1005 (0402)	10K				50K	
<u>B</u>	0.50+/-0.15	1005 (0402)	10K				50K	
Q	0.45+/-0.05	1005 (0402)	10K				50K	
C	0.60+/-0.15	2012 (0805)	4K		10K		15K	
		3216(1206)	4K		10K		15K	
Q	0.45+/-0.05	1608(0603)	4K		10K		15K	
D	0.80+/-0.10	1608(0603)	4K		10K		15K	
<u>D</u>	0.80+0.15/ -0.10	1608 (0603)	4K		10K		15K	
E	0.85+/-0.15	2012 (0805)	4K		10K		15K	
		3216 (1206)	4K		10K		15K	
		3225 (1210)		3K				10K
I	0.95+/-0.15	4532 (1812)		1K				
		2012(0805)		3K				
		3216(1206)		3K				
F	1.15+/-0.20	3216 (1206)		3K				10K
		4520 (1808)		3K				
G	1.25 +/-0.20	2012 (0805)		2K/3K				10K
		3216 (1206)		3K				10K
		3225 (1210)		3K				
		4520(1808)		3K				
		4532(1812)		1K				
<u>G</u>	1.25+0.3/-0.2	2012(0805)		2K/3K				10K
		3216(1206)		3K				10K
		3225(1210)		3K				
L	1.60+/-0.20	3216(1206)		2K				
		3225(1210)		2K				
		4520(1808)		2K				
		4532(1812)		1K				
<u>L</u>	1.60+0.30/-0.20	3216(1206)		2K				
		3225(1210)		2K				
		4520(1808)		2K				
		4532(1812)		1K				
N	2.00+/-0.20	3216 (1206)		2K/3K				
		3225 (1210)		2K				
		4520 (1808)		1K				
		4532(1812)		1K				
<u>N</u>	2.00+/-0.30	3225 (1210)		2K				
P	2.50+/-0.20	3225(1210)		500pcs/1K				
<u>P</u>	2.50+/-0.30	3225(1210)		500pcs/1K				

- **Peeling Off Force**

Peeling off force: 0.1N to 1.0N in the direction shown below.

The peeling speed: 300+/-10 mm/min



1. The taped tape on reel is wound clockwise. The sprocket holes are to the right as the tape is pulled toward the user.
2. There are minimum 150 mm as the leader and minimum 40 mm empty tape as the tail be attached to the end of the tape.

X5R, X7R Dielectrics

■ Features

- A monolithic structure ensures high reliability and mechanical strength.
- High capacitance density.
- A wide range of capacitance values in standard case size.
- Suitable for high speed SMT placement on PCBs.
- Ni barrier termination highly resistance to migration.
- Lead-free termination is in compliance with the requirement of green plan and ROHS.

■ Applications

- General electronic equipment.
- Communication equipment.
- Custom Application

■ X5R, X7R Dielectric Characteristics

Capacitance Range	100pF to 100uF					
Size (mm)	0603	1005	1608	2012	3216	3225
(EIA inch)	(0201)	(0402)	(0603)	(0805)	(1206)	(1210)
Test Voltage	1.0 ± 0.2Vrms					
Test Frequency	1.0 ± 0.2KHz					
Capacitance Tolerance	± 10%, ± 20% (± 5% available on request)					
Operating Temperature Range	-55°C to +85°C for X5R -55°C to +125°C for X7R					
Maximum Capacitance Change	± 15 %					
Rated Voltage	6.3, 10, 16, 25, 50, 100 VDC					
Dissipation Factor	Pls refer to DF table on page No. 7					
Insulation Resistance (+25°C, RVDC)	10,000 MΩ min. or 500Ω-F min., whichever is smaller					
Insulation Resistance (Maximum operating temperature, RVDC)	1,000 MΩ min. or 50Ω-F min., whichever is smaller					



Multi-Layer Ceramic Capacitor

C-S2-7-00

Product Range and Thickness

CLASS	Class II																									
TYPE	Standard																									
T.C.	X7R																									
SIZE	0603				1005				1608				2012						3216					3225		
(EIA)	0201				0402				0603				0805						1206					1210		
RV	10V	16V	25V	50V	10V	16V	25V	50V	10V	16V	25V	50V	100V	6.3V	10V	16V	25V	50V	100V	10V	16V	25V	50V	100V	16V	25V
100 p			A	A	B	B	B	B	D	D	D	D	D													
120 p			A	A	B	B	B	B	D	D	D	D	D													
150 p			A	A	B	B	B	B	D	D	D	D	D					C	E	E						
180 p			A	A	B	B	B	B	D	D	D	D	D					C	E	E						
220 p			A	A	B	B	B	B	D	D	D	D	D					C	E	E						
270 p			A	A	B	B	B	B	D	D	D	D	D					C	E	E						
330 p			A	A	B	B	B	B	D	D	D	D	D					C	E	E						
390 p			A	A	B	B	B	B	D	D	D	D	D					C	E	E						
470 p			A	A	B	B	B	B	D	D	D	D	D					C	E	E						
560 p			A	A	B	B	B	B	D	D	D	D	D					C	E	E						
680 p			A	A	B	B	B	B	D	D	D	D	D					C	E	E						
820 p			A	A	B	B	B	B	D	D	D	D	D					C	E	E						
1.0 n			A	A	B	B	B	B	D	D	D	D	D				C	E	C	E	E			E	E	
1.2 n			A	A	B	B	B	B	D	D	D	D	D				C	E	C	E	E			E	E	
1.5 n			A	A	B	B	B	B	D	D	D	D	D				C	E	C	E	E			E	E	
1.8 n			A	A	B	B	B	B	D	D	D	D	D				C	E	C	E	E			E	E	
2.2 n			A	A	B	B	B	B	D	D	D	D	D				C	E	C	E	E			E	E	
2.7 n					B	B	B	B	D	D	D	D	D				C	E	C	E	E			E	E	
3.3 n	A				B	B	B	B	D	D	D	D	D				C	E	C	E	E			E	E	
3.9 n					B	B	B	B	D	D	D	D	D				C	E	C	E	E			E	E	
4.7 n	A				B	B	B	B	D	D	D	D	D				C	E	C	E	E			E	E	
5.6 n					B	B	B	B	D	D	D	D	D				C	E	C	E	E			E	E	
6.8 n					B	B	B	B	D	D	D	D	D				C	E	C	E	E			E	E	
8.2 n					B	B	B	B	D	D	D	D	D				C	E	C	E	E			E	E	
10 n	A				B	B	B	B	D	D	D	D	D				C	E	C	E	E			E	E	
12 n					B	B	B		D	D	D	D					C	E	C	E	E			E	E	
15 n					B	B	B		D	D	D	D					C	E	C	E	E			E	E	
18 n					B	B	B		D	D	D	D					C	E	C	E	E			E	E	
22 n					B	B	B		D	D	D	D					C	E	C	E	E			E	E	
27 n					B	B			D	D	D	D					C	E	C	E				E	E	
33 n					B	B			D	D	D	D*					C	E	C	E				E	E	
39 n					B	B			D	D	D	D*					C	E	C	E				E	E	
47 n					B	B			D	D	D	D*					E	E						E	E	
56 n					B	B			D	D	D	D*					E	E						E	E	
68 n					B	B			D	D	D	D*					E	E						E	E	
82 n					B	B			D	D	D	D*					E	E						E	E	G
100 n					B	B			D	D	D	D*					E	E						E	E	G
120 n																	E	E								
150 n																	E	E								
180 n																	E	E								
220 n									D	D	D*						E	E					I	I		
270 n																										
330 n									D*	D*					G	G	G					I	G			
390 n																										
470 n									D*	D*					G	G	G				G	G	L			
560 n																										
680 n																										
820 n																										
1.0 u									D*	D*	D*				G	G	G				G	G	G	L		
1.2 u																										
1.5 u																										
1.8 u																										
2.2 u															G	G					L	L	L			
2.7 u																										
3.3 u																										
3.9 u																										
4.7 u															G	G						L	L			N
10 u															G							L			N	N

- Non-standard capacitance or thickness is available on request
- * Special length/width tolerance
- The thickness might be changed due to technology improvement.



Multi-Layer Ceramic Capacitor

C-S2-7-00

Product Range and Thickness

CLAS	Class II																						
TYPE	Standard																						
T.C.	X5R																						
SIZE	0603		1005				1608				2012				3216				3225				
(EIA)	0201		0402				0603				0805				1206				1210				
RV	6.3V	10V	6.3V	10V	16V	25V	6.3V	10V	16V	25V	6.3V	10V	16V	25V	6.3V	10V	16V	25V	6.3V	10V	16V	25V	
2.2 n	A	A																					
3.3 n	A	A																					
4.7 n	A	A																					
5.6 n	A	A																					
6.8 n	A	A																					
8.2 n	A	A																					
10 n	A	A																					
15 n				B	B																		
22 n	A	A		B	B																		
33 n				B	B																		
47 n	A	A		B	B																		
56 n				B	B																		
68 n				B	B																		
82 n				B	B																		
100 n	A	A		B	B	B																	
120 n				B	B																		
150 n				B	B																		
180 n				B	B																		
220 n	A			B	B			D	D	D													
270 n																							
330 n								D	D														
390 n																							
470 n			B	B				D	D														
560 n																							
680 n								D	D														
820 n																							
1.0 u			B	B	B			Q	D	D	D			E	G	E	G						
1.5 u																							
1.8 u																							
2.2 u			B					D	D	D			E	G	G		L	L	L				
2.7 u																							
3.3 u																							
3.9 u																							
4.7 u			B*					D	D			G	G	G	G		L	L	L		N	N	
6.8 u																							
10 u								D*				G	G	G			L	L	L		N	N	
22 u												G					L				N	P	
47 u																	L				P		
100 u																					P		

- Non-standard capacitance or thickness is available on request
- * Special length/width tolerance
- The thickness might be changed due to technology improvement.

Thickness Tolerance

Thickness (mm)		Thickness (mm)		Thickness (mm)		Thickness (mm)		Thickness (mm)		Thickness (mm)	
Code	Class	Code	Class	Code	Class	Code	Class	Code	Class	Code	Class
A	0.30+/-0.03	C	0.60+/-0.15	E	0.85+/-0.15	G	1.25 -0.20/+0.30	L	1.60+0.3/-0.20	P	2.50+/-0.20
B	0.50+/-0.05	D	0.80+/-0.10	F	1.15+/-0.20	I	0.95+/-0.15	N	2.00+/-0.20	Q	0.45+/-0.05
B	0.50+/-0.15	D	0.8+0.15/-0.1	G	1.25+/-0.20	L	1.60+/-0.20	N	2.00+/-0.30		

Special Length/Width Tolerance

Size Code(EIA)	1005(0402)	1608(0603)	2012(0805)	3216(1206)	3225(1210)
Length(mm)	1.0 ± 0.15	1.6 ± 0.15	2.0 ± 0.20	3.2 ± 0.20	3.2 ± 0.30
Width(mm)	0.5 ± 0.15	0.8 ± 0.15	1.25 ± 0.30	1.6 ± 0.30	2.5 ± 0.30

Taping Amount

Thickness			Amount per reel					
			180 mm (7")		250 mm (10")		330 mm (13")	
Code	Spec	Size(EIA)	Paper	Embossed	Paper	Embossed	Paper	Embossed
A	0.30+/-0.03	0603 (0201)	15K					
B	0.50+/-0.05	1005 (0402)	10K				50K	
<u>B</u>	0.50+/-0.15	1005 (0402)	10K				50K	
Q	0.45+/-0.05	1005 (0402)	10K				50K	
C	0.60+/-0.15	2012 (0805)	4K		10K		15K	
		3216(1206)	4K		10K		15K	
Q	0.45+/-0.05	1608(0603)	4K		10K		15K	
D	0.80+/-0.10	1608(0603)	4K		10K		15K	
<u>D</u>	0.80+0.15/-0.10	1608 (0603)	4K		10K		15K	
E	0.85+/-0.15	2012 (0805)	4K		10K		15K	
		3216 (1206)	4K		10K		15K	
		3225 (1210)		3K				10K
		4532 (1812)		1K				
I	0.95+/-0.15	2012(0805)		3K				
		3216(1206)		3K				
F	1.15+/-0.20	3216 (1206)		3K				10K
		4520 (1808)		3K				
G	1.25 +/-0.20	2012 (0805)		2K/3K				10K
		3216 (1206)		3K				10K
		3225 (1210)		3K				
		4520(1808)		3K				
		4532(1812)		1K				
<u>G</u>	1.25+0.3/-0.2	2012(0805)		2K/3K				10K
		3216(1206)		3K				10K
		3225(1210)		3K				
L	1.60+/-0.20	3216(1206)		2K				
		3225(1210)		2K				
		4520(1808)		2K				
		4532(1812)		1K				
<u>L</u>	1.60+0.30/-0.20	3216(1206)		2K				
		3225(1210)		2K				
		4520(1808)		2K				
		45321812)		1K				
N	2.00+/-0.20	3216 (1206)		2K/3K				
		3225 (1210)		2K				
		4520 (1808)		1K				
		4532(1812)		1K				
<u>N</u>	2.00+/-0.30	3225 (1210)		2K				
P	2.50+/-0.20	3225(1210)		500pcs/1K				
<u>P</u>	2.50+/-0.30	3225(1210)		500pcs/1K				

■ X5R, X7R Specifications

	Item	Specification			Test Method																												
1	Operating Temperature Range	X7R: -55 to 125 degree C X5R: -55 to 85 degree C			---																												
2	Rated Voltage	6.3VDC, 10VDC, 16VDC, 25VDC, 35VDC, 50VDC, 100VDC,			The rated voltage is defined as the maximum voltage, which may be applied continuously to the capacitor.																												
3	Appearance	No defects or abnormalities.			Visual inspection																												
4	Dimensions	Within the specified dimension.			Using calipers																												
5	Dielectric Strength	No defects or abnormalities.			No failure shall be observed when 250%* of the rated voltage is applied between the terminations for 1 to 5 seconds. The charge and discharge current is less than 50mA.																												
6	Insulation Resistance (I.R.)	Rated Voltage: <500V	To apply rated voltage.	I.R. ≥ 10G or R _i C _R ≥ 500Ω·F (whichever is smaller)	The insulation resistance shall be measured with a DC voltage not exceeding the rated voltage at 25℃ and 75%RH max, and within 1 minute of charging.																												
		Rated Voltage: ≥ 500V	To apply 500V.																														
7	Capacitance	Within the specified tolerance * X7R, X5R at 1000 hours			The capacitance / D.F. shall be measured at 25℃ at the frequency and voltage shown in the tables.																												
8	Q/Dissipation Factor (D.F.)	I. X5R, X7R: See X5R,X7R DF table 3			<table><tr><th>Item</th><th>ClassII (≤ 10 uF)</th><th>ClassII (>10 uF)</th><th>* For item in Table1</th></tr><tr><td>Frequency</td><td>1.0±0.2kHz</td><td>120Hz±24Hz</td><td>1.0±0.2kHz</td></tr><tr><td>Voltage</td><td>1.0±0.2Vrms</td><td>0.5±0.1Vrms</td><td>0.5±0.1Vrms</td></tr></table>	Item	ClassII (≤ 10 uF)	ClassII (>10 uF)	* For item in Table1	Frequency	1.0±0.2kHz	120Hz±24Hz	1.0±0.2kHz	Voltage	1.0±0.2Vrms	0.5±0.1Vrms	0.5±0.1Vrms																
		Item	ClassII (≤ 10 uF)	ClassII (>10 uF)		* For item in Table1																											
		Frequency	1.0±0.2kHz	120Hz±24Hz		1.0±0.2kHz																											
		Voltage	1.0±0.2Vrms	0.5±0.1Vrms		0.5±0.1Vrms																											
Table 1																																	
<table><tr><th>Size</th><th>Thickness</th><th>TC</th><th>RV</th><th>Cap</th></tr><tr><td>0603</td><td>0.3 mm</td><td>X5R</td><td>6.3V</td><td>104</td></tr><tr><td>1005</td><td>0.5 mm</td><td>X5R</td><td>4V/6.3V</td><td>475</td></tr><tr><td>1608</td><td>0.8 mm</td><td>X5R</td><td>4V/6.3V</td><td>106</td></tr></table>	Size	Thickness	TC	RV	Cap	0603	0.3 mm	X5R	6.3V	104	1005	0.5 mm	X5R	4V/6.3V	475	1608	0.8 mm	X5R	4V/6.3V	106													
Size	Thickness	TC	RV	Cap																													
0603	0.3 mm	X5R	6.3V	104																													
1005	0.5 mm	X5R	4V/6.3V	475																													
1608	0.8 mm	X5R	4V/6.3V	106																													
9	Capacitance Temperature Characteristics	Capacitance change X7R/X5R within ±15%			The ranges of capacitance change compared with the 25℃ value over the temperature ranges shall be within the specified ranges.																												
10	Termination Strength	No removal of the terminations or marking defect.			Apply a parallel force of 5N to a PCB mounted sample for 10±1sec. *2N for 0603 (EIA 0201).																												
11	Deflection (Bending Strength)	No cracking or marking defects shall occur at 1mm deflection. Capacitance change: X7R, X5R:within ±12.5%			Solder the capacitor to the test jig (glass epoxy boards) shown in Fig.a using a SAC305(Sn96.5Ag3.0Cu0.5) solder (then let sit for 48±4 hours for X7R X5R and Y5V). Then apply a force in the direction shown in Fig.b. The soldering shall be done with the reflow method and shall be conducted with care so that the soldering is uniform and free of defects such as heat shock.																												
		<div><table><tr><th>Size</th><th>a</th><th>b</th><th>C</th></tr><tr><td>0603</td><td>0.3</td><td>0.9</td><td>0.3</td></tr><tr><td>1005</td><td>0.4</td><td>1.5</td><td>0.5</td></tr><tr><td>1608</td><td>1.0</td><td>3.0</td><td>1.2</td></tr><tr><td>2012</td><td>1.2</td><td>4.0</td><td>1.65</td></tr><tr><td>3216</td><td>2.2</td><td>5.0</td><td>2.0</td></tr><tr><td>4520</td><td>3.5</td><td>7.0</td><td>2.5</td></tr><tr><td>4532</td><td>3.5</td><td>7.0</td><td>3.7</td></tr></table></div>	Size	a	b	C	0603	0.3	0.9	0.3	1005	0.4	1.5	0.5	1608	1.0	3.0	1.2	2012	1.2	4.0	1.65	3216	2.2	5.0	2.0	4520	3.5	7.0	2.5	4532	3.5	7.0
Size	a	b	C																														
0603	0.3	0.9	0.3																														
1005	0.4	1.5	0.5																														
1608	1.0	3.0	1.2																														
2012	1.2	4.0	1.65																														
3216	2.2	5.0	2.0																														
4520	3.5	7.0	2.5																														
4532	3.5	7.0	3.7																														
12	Solderability of Termination	90% of the terminations are to be soldered evenly and continuously.			Immerse the test capacitor into a methanol solution containing rosin for 3 to 5 seconds, preheat it 150 to 180℃ for 2 to 3 minutes and immerse it into Sn-3.0Ag-0.5Cu solder of 245 ± 5℃ for 3±1seconds.																												



Continued from previous page.

	Item	Specification	Test Method
13	Resistance to Soldering Heat	Appearance	No marking defects
		Cap. Change	X7R/X5R within $\pm 7.5\%$
		Q/D.F.	To satisfy the specified initial spec.
		I.R.	I.R. $\geq 10,000\text{M}\Omega$ or $R_1C_R \geq 500\Omega\cdot\text{F}$. (whichever is smaller)
14	Temperature cycle (Thermal shock)	Appearance	No marking defects
		Cap. Change	X7R/X5R within $\pm 7.5\%$
		Q/D.F.	To satisfy the specified initial spec.
		I.R.	I.R. $\geq 10,000\text{M}\Omega$ or $R_1C_R \geq 500\Omega\cdot\text{F}$. (whichever is smaller)
15	Humidity load	Appearance	No marking defects
		Cap. Change	X7R/X5R within $\pm 12.5\%$
		Q/D.F.	X7R 200% max of initial spec. X5R 200% max of initial spec.
		I.R.	I.R. $\geq 500\text{M}\Omega$ or $R_1C_R \geq 25\Omega\cdot\text{F}$. (whichever is smaller) * some of the parts are $R_1C_R \geq 12.5\Omega\cdot\text{F}$, please refer to table 2
16	High temperature load life test	Appearance	No marking defects
		Cap. Change	X7R/X5R within $\pm 12.5\%$
		Q/D.F.	X7R 200% max of initial value X5R 200% max of initial value
		I.R.	More than $1\text{G}\Omega$ or $R_1C_R \geq 50\Omega\cdot\text{F}$ (whichever is less.) * some of the parts are $R_1C_R \geq 25\Omega\cdot\text{F}$, please refer to table 2

Table 2

TC	Product Range
X5R	0603 (EIA 0201): $C > 10\text{ nF}$
	1005 (EIA 0402): $C > 0.1\text{ }\mu\text{F}$
	1608 (EIA 0603): $C \geq 1.0\text{ }\mu\text{F}$
	2012 (EIA 0805): $C \geq 2.2\text{ }\mu\text{F}$
	3216 (EIA 1206): $C \geq 10\text{ }\mu\text{F}$
	3225 (EIA 1210): $C \geq 22\text{ }\mu\text{F}$


■ X5R/X7R DF (tan δ) Table 3

Rated Voltage	Size	Capacitance	D.F Max.	
			X5R	X7R
4V	All	All	15.0%	
6.3V	All	cap ≤ 1.0uF	10.0%	7.5%
	All	cap < 4.7uF	10.0%	10.0%
	All	4.7uF ≤ cap ≤ 100uF	15.0%	15.0%
10V	0603/3216/3225	All	7.5%	5.0%
	0603	100nF ≤ cap	10.0%	
	1005	cap ≤ 100nF	7.5%	5.0%
		100nF < cap < 330nF	7.5%	
		330nF ≤ cap	10.0%	
	1608	cap ≤ 1.0uF	7.5%	5.0%
		cap < 2.2uF	7.5%	
		2.2uF ≤ cap	10.0%	
	2012	cap < 2.2uF	7.5%	5.0%
		2.2uF ≤ cap	10.0%	
	3216	10uF	10.0%	10.0%
	3225	10uF < cap ≤ 22uF	10.0%	10.0%
16V	0603/3216/3225	All	5.0%	5.0%
	1005	cap ≤ 100nF	5.0%	5.0%
		100nF < cap ≤ 220nF	7.5%	
	1608	cap ≤ 470nF	5.0%	5.0%
		470nF < cap < 1.0uF	7.5%	5.0%
		1.0uF ≤ cap	10.0%	10.0%
	2012	cap ≤ 2.2uF	5.0%	5.0%
		2.2uF < cap ≤ 4.7uF	7.5%	
		4.7uF < cap ≤ 10uF	10.0%	
	3216	4.7uF < cap	10.0%	10.0%
	3225	10uF < cap ≤ 22uF	15.0%	
25V	All	All	5.0%	3.5%
		1.0uF ≤ cap	10.0%	
	1608	470nF		10.0%
	3216	1.0uF < cap ≤ 4.7u	5.0%	5.0%
		4.7uF < cap	10.0%	
	3225	4.7uF < cap ≤ 10u	10.0%	
≥ 50V	All	All but below	2.5%	3.0%
	3216/3225	cap ≤ 1.0uF	3.5%	3.5%




Typical Characteristic Curves

- Temperature Coefficient
 - Class 1 (Temperature Compensation series)






- Class 2 (High Dielectric Constant Series)




■ Capacitance Change vs. DC bias Voltage






Impedance vs. Frequency





■ Aging Rate



Application Note

■ Circuit Design

1. Once application and assembly environments have been checked, the capacitor may be used in conformance with the rating and performance, which are provided in both the catalog and the specifications. Exceeding the specifications listed may result in inferior performance. It may also cause a short, open, smoking, or flaming to occur, etc.
2. Please use the capacitors in conformance with the operating temperature provided in both the catalog and the specifications. Be especially cautious not to exceed the maximum temperature. In the situation the maximum temperature set forth in both the catalog and specifications is exceeded, the capacitor's insulation resistance may deteriorate, power may suddenly surge and short-circuit may occur. The loss of capacitance will occur, and may self-heat due to equivalent series resistance when alternating electric current is passed through. As this effect becomes critical in high frequency circuits, please exercise with caution. When using the capacitor in a (self-heating) circuit, please make sure the surface of the capacitor remains under the maximum temperature for usage. Also, please make certain temperature rise remain below 20°C.
3. Please keep voltage under the rated voltage, which is applied to the capacitor. Also, please make certain the peak voltage remains below the rated voltage when AC voltage is super-imposed to the DC voltage. In the situation where AC or pulse voltage is employed, ensure average peak voltage does not exceed the rated voltage. Exceeding the rated voltage provided in both catalog and specifications may lead to defective withstanding voltage or, in worse case situations, may cause the capacitor to burn out.
4. It's is a common phenomenon of high-dielectric products to have a deteriorated amount of static electricity due to the application of DC voltage.

■ Storage

1. The chip capacitors shall be packaged in carrier tapes or bulk cases.
2. Keep storage place temperatures from +5°C to +35°C, humidity from 45 to 70% RH.
3. The storage atmosphere must be free of gas containing sulfur and chlorine. Also, avoid exposing the product to saline moisture. If the product is exposed to such atmospheres, the terminations will oxidize and solderability will be affected.
4. The solderability is assured for 12 months from our final inspection date if the above storage condition is followed.

■ Handling

Chip capacitors should be handled with care to avoid contamination or damage. The use of vacuum pick-up or plastic tweezers is recommended for manual placement. Tape and reeled packages are suitable for automatic pick and placement machine.

■ Flux


1. An excessive amount of flux or too rapid temperature rise can causes solvent burst, solder can generate a large quantity of gas. The gas can spreads small solder particles to cause solder balling effect or bridging problem.
2. Flux containing too high of a percentage of halide may cause corrosion of termination unless sufficient cleaning is applied.
3. Use rosin-type flux. Highly acidic flux (halide content less than 0.2wt%) is not recommended.
4. The water soluble flux causes deteriorated insulation resistance between outer terminations unless sufficiently cleaned.

■ Component Spacing

For wave soldering components, the spacing must be sufficient far apart to prevent bridging or shadowing. This is not so important for reflow process but sufficient space for rework should be considered. The suggested spacing for reflow soldering and wave soldering is 0.5mm and 1.0mm, respectively.

■ Solder Fillet


Too much solder amount may increase solder stress and cause crack risk. Insufficient solder amount may reduce adhesive strength and cause parts falling off PCB. When soldering, confirm that the solder is placed over 0.2mm of the surface of the terminations.



■ Recommended Land Pattern Dimensions

When mounting the capacitor to substrate, it's important to consider carefully that the amount of solder (size of fillet) used has a direct effect upon the capacitor once it's mounted.

1. The greater the amount of solder, the greater the stress to the elements. As this may cause the substrate to break or crack.
2. In the situation where two or more devices are mounted onto a common land separate the device into exclusive pads by using soldering resist.
3. Land width equal to or less than component. It is permissible to reduce land width to 80% of component width.



Size mm (EIA)	L x W (mm)	a (mm)	b (mm)	c (mm)
0603 (0201)	0.6*0.3	0.15 to 0.35	0.2 to 0.3	0.25 to 0.3
1005 (0402)	1.0*0.5	0.3 to 0.5	0.35 to 0.45	0.4 to 0.5
1608 (0603)	1.6*0.8	0.7 to 1.0	0.6 to 0.8	0.7 to 0.8
2012 (0805)	2.0*1.25	1.0 to 1.3	0.7 to 0.9	1.0 to 1.2
3216 (1206)	3.2*1.6	2.1 to 2.5	1.0 to 1.2	1.3 to 1.6
3225 (1210)	3.2*2.5	2.1 to 2.5	1.0 to 1.2	2.0 to 2.5
4520 (1808)	4.5*2.0	3.2 to 3.8	1.2 to 1.4	1.7 to 2.0
4532 (1812)	4.5*3.2	3.2 to 3.8	1.2 to 1.4	2.7 to 3.2




■ **Resin Mold**

If a large amount of resin is used for molding the chip, cracks may occur due to contraction stress during curing. To avoid such cracks, use a low shrinkage resin. The insulation resistance of the chip will degrade due to moisture absorption. Use a low moisture absorption resin. Check carefully that the resin does not generate a decomposition gas or reaction gas during the curing process or during normal storage. Such gases may crack the chip capacitor or damage the device itself.

■ **Soldering Profile for SMT Process with SnPb Solder Paste**

● **Reflow Soldering**




The difference between solder and chip surface should be controlled as following table. The rate of preheat should not exceed 4°C/sec and a target of 2°C/sec is preferred.

Chip Size	3216 and smaller	3225 and above
Preheating	$\Delta T \leq 150^{\circ}\text{C}$	$\Delta T \leq 130^{\circ}\text{C}$




• Wave Soldering



Chip Size	3216 and smaller	3225 and above
Preheating	$\Delta T \leq 150^{\circ}\text{C}$	-

• Soldering Iron




Chip Size	3216 and smaller	3225 and above
Preheating	$\Delta T \leq 190^{\circ}\text{C}$	$\Delta T \leq 130^{\circ}\text{C}$



■ Soldering


• Reflow Soldering for Lead free Termination



The difference between solder and chip surface should be controlled as following table. The rate of preheat should not exceed 4°C/sec and a target of 2°C/sec is preferred.

Chip Size	3216 and smaller	3225 and above
Preheating	$\Delta T \leq 150^{\circ}\text{C}$	$\Delta T \leq 130^{\circ}\text{C}$


• Flow Soldering for Lead free Termination



Chip Size	3216 and smaller	3225 and above
Preheating	$\Delta T \leq 150^{\circ}\text{C}$	-




• Soldering Iron




Chip Size	3216 and smaller	3225 and above
Preheating	$\Delta T \leq 190^{\circ}\text{C}$	$\Delta T \leq 130^{\circ}\text{C}$

■ Chip Layout and Breaking PCB

1. To layout the SMD capacitors for reducing bend stress from board deflection of PCB. The following are examples of good and bad layout.



2. When breaking PCB, the layout should be noted that the mechanical stresses are depending on the position of capacitors. The following example shows recommendation for better design.



■ Aging

The capacitance and dissipation factor of class 2 capacitors decreases with time. It is known as 'aging' that follows a logarithmic law and expressed in terms of an aging constant. Aging is caused by a gradual re-alignment of the crystalline structure of the ceramic. The aging constant is defined as the percentage loss of capacitance at a 'time decade'. The law of capacitance aging is expressed as following equation:

$$C_{t2} = C_{t1} \times (1 - k \times \log_{10}(t_2/t_1))$$


C_{t1} : Capacitance after t_1 hours of start aging.

C_{t2} : Capacitance after t_2 hours of start aging.

k : aging constant (capacitance decrease per decade)

t_1, t_2 : time in hours from start of aging.

A typical curve of aging rate is shown in following figure.



When heating the capacitors above Curie temperature ($130^{\circ}\text{C} \sim 150^{\circ}\text{C}$) the capacitance can be re-new. So capacitance of class 2 capacitors will be complete de-aged by soldering process; subsequently a new aging process begins.

Because of aging, it is specified an age for measurement to meet the prescribed tolerance for class 2 capacitors.

Normally, 1000 hours ($t_2=1000$ hrs) is defined.