Silicon Switching Diode

- For high-speed switching applications
- Series pair configuration



BAV99
BAV99F
BAV99T
BAV99W

BAV99S
BAV99U





Type	Package	Configuration	Marking
BAV99	SOT23	series	A7s
BAV99F*	TSFP-3	series	A7s
BAV99S	SOT363	dual series	A7s
BAV99T	SC75	series	A7s
BAV99U	SC74	dual series	A7s
BAV99W	SOT323	series	A7s

* Preliminary

Maximum Ratings at T_A = 25°C, unless otherwise specified

Parameter	Symbol	Value	Unit
Diode reverse voltage	V_R	80	V
Peak reverse voltage	V_{RM}	85	
Forward current	I_F	200	mA
Non-repetitive peak surge forward current	I_{FSM}		A
t = 1 µs		4.5	
t = 1 ms		1	
t = 1 s, single		0.5	
t = 1 s, double		0.75	
Total power dissipation	P_{tot}		mW
BAV99, $T_S \leq$ 28°C		330	
BAV99F, $T_S \leq$ tbd		250	
BAV99S, $T_S \leq$ 85°C		250	
BAV99T, $T_S \leq$ 104°C		250	
BAV99U, $T_S \leq$ 113°C		250	
BAV99W, $T_S \leq$ 110°C		250	
Junction temperature	T_j	150	°C
Storage temperature	T_{stg}	-65 ... 150	

Thermal Resistance

Parameter	Symbol	Value	Unit
Junction - soldering point[1)]	R_{thJS}		K/W
BAV99		≤ 360	
BAV99F		≤ tbd	
BAV99S		≤ 260	
BAV99T		≤ 185	
BAV99U		≤ 150	
BAV99W		≤ 160	

[1]For calculation of R_{thJA} please refer to Application Note Thermal Resistance

Electrical Characteristics at T_A = 25°C, unless otherwise specified

Parameter	Symbol	Values			Unit
		min.	typ.	max.	
DC Characteristics					
Breakdown voltage $I_{(BR)}$ = 100 µA	$V_{(BR)}$	85	-	-	V
Reverse current	I_R				µA
V_R = 70 V		-	-	0.15	
V_R = 25 V, T_A = 150 °C		-	-	30	
V_R = 70 V, T_A = 150 °C		-	-	50	
Forward voltage	V_F				mV
I_F = 1 mA		-	-	715	
I_F = 10 mA		-	-	855	
I_F = 50 mA		-	-	1000	
I_F = 100 mA		-	-	1200	
I_F = 150 mA		-	-	1250	

Electrical Characteristics at T_A = 25°C, unless otherwise specified

Parameter	Symbol	Values			Unit
		min.	typ.	max.	
AC Characteristics					
Diode capacitance V_R = 0 V, f = 1 MHz	C_T	-	-	1.5	pF
Reverse recovery time I_F = 10 mA, I_R = 10 mA, measured at I_R = 1mA, R_L = 100 Ω	t_{rr}	-	-	4	ns

Test circuit for reverse recovery time



Pulse generator: t_p = 100ns, D = 0.05,
t_r = 0.6ns, R_i = 50Ω

Oscillograph: R = 50, t_r = 0.35ns
$C \leq$ 1pF

Reverse current $I_R = f(T_A)$

V_R = Parameter



Forward Voltage $V_F = f(T_A)$

I_F = Parameter



Forward current $I_F = f(V_F)$

T_A = 25°C



Forward current $I_F = f(T_S)$

BAV99



Forward current $I_F = f(T_S)$
BAV99S



Forward current $I_F = f(T_S)$
BAV99T



Forward current $I_F = f(T_S)$
BAV99U



Forward current $I_F = f(T_S)$
BAV99W



Permissible Puls Load $R_{thJS} = f(t_p)$

BAV99



Permissible Pulse Load

$I_{Fmax}/ I_{FDC} = f(t_p)$

BAV99



Permissible Puls Load $R_{thJS} = f(t_p)$

BAV99S



Permissible Pulse Load

$I_{Fmax}/ I_{FDC} = f(t_p)$

BAV99S



Permissible Puls Load $R_{thJS} = f(t_p)$

BAV99T



Permissible Pulse Load

$I_{Fmax}/ I_{FDC} = f(t_p)$

BAV99T



Permissible Puls Load $R_{thJS} = f(t_p)$

BAV99U



Permissible Pulse Load

$I_{Fmax}/ I_{FDC} = f(t_p)$

BAV99U



Permissible Puls Load $R_{thJS} = f(t_p)$

BAV99W



Permissible Pulse Load

$I_{Fmax}/ I_{FDC} = f(t_p)$

BAV99W



Package Outline



Foot Print



Marking Layout



Example

Packing

Code E6327: Reel ø180 mm = 3.000 Pieces/Reel
Code E6433: Reel ø330 mm = 10.000 Pieces/Reel



Package Outline



Foot Print



Marking Layout



Example

Packing

Code E6327: Reel ø180 mm = 3.000 Pieces/Reel
Code E6433: Reel ø330 mm = 10.000 Pieces/Reel



Package Outline



Foot Print



Marking Layout



Example

Packing

Code E6327: Reel ø180 mm = 3.000 Pieces/Reel
Code E6433: Reel ø330 mm = 10.000 Pieces/Reel



Package Outline



Foot Print



Marking Layout



Example

Packing

Code E6327: Reel ø180 mm = 3.000 Pieces/Reel
Code E6433: Reel ø330 mm = 10.000 Pieces/Reel



Package Outline



Foot Print



Marking Layout



Example

Packing

Code E6327: Reel ø180 mm = 3.000 Pieces/Reel
Code E6433: Reel ø330 mm = 10.000 Pieces/Reel



Package Outline



Foot Print



Marking Layout



Example

Packing

Code E6327: Reel ø180 mm = 3.000 Pieces/Reel
Code E6433: Reel ø330 mm = 10.000 Pieces/Reel



Published by Infineon Technologies AG,
St.-Martin-Strasse 53,
81669 München

Attention please!

The information herein is given to describe certain components and shall not be considered as a guarantee of characteristics.
Terms of delivery and rights to technical change reserved.
We hereby disclaim any and all warranties, including but not limited to warranties of non-infringement, regarding circuits, descriptions and charts stated herein.

Information

For further information on technology, delivery terms and conditions and prices please contact your nearest Infineon Technologies Office (www.Infineon.com).

Warnings

Due to technical requirements components may contain dangerous substances. For information on the types in question please contact your nearest Infineon Technologies Office.
Infineon Technologies Components may only be used in life-support devices or systems with the express written approval of Infineon Technologies, if a failure of such components can reasonably be expected to cause the failure of that life-support device or system, or to affect the safety or effectiveness of that device or system. Life support devices or systems are intended to be implanted in the human body, or to support and/or maintain and sustain and/or protect human life. If they fail, it is reasonable to assume that the health of the user or other persons may be endangered.