Banner appropriate to article type will appear here in typeset article

A spectral theory for turbulent burning velocity across scales

Michael D. Walker[1,2]†, G. V. Nivarti[2], M. E. Mueller[1], R. S. Cant[2], and S. Hochgreb[2]

[1]Department of Mechanical and Aerospace Engineering, Princeton University, Princeton, NJ 08544, USA

[2]Department of Engineering, University of Cambridge, Trumpington Street, Cambridge CB2 1PZ, UK

(Received xx; revised xx; accepted xx)

Damköhler's two hypotheses attribute the enhancement of the turbulent burning velocity s_T over the laminar value s_L to an increase in flame-surface area by eddies larger than the flame thickness δ_L, and to an increase in effective diffusivity by smaller eddies. In intense turbulence, the measured s_T/s_L exceeds the measured area ratio several-fold, an excess that Nivarti *et al.* (*J. Fluid Mech.*, vol. 858, 2019, R1) attributed to a sub-δ_L diffusivity integrated over a model energy spectrum. Here that integral is extended to the whole spectrum and made dimensionally consistent by taking the diffusivity at each wavenumber from the spectral eddy diffusivity of two-point closures. For a model spectrum, the total enhancement reduces to $C\,\mathcal{F}(Re)\,u'/s_L$, where u' is the turbulence intensity, C is a constant and $\mathcal{F}$ is a weak, saturating function of the turbulence Reynolds number Re. The resulting relation $s_T/s_L = [1 + C\,\mathcal{F}(Re)\,u'/s_L]^{1/2}$ recovers Damköhler's linear growth of s_T with u' in weak turbulence and the sublinear 'bending' in strong turbulence, and its sub-δ_L part recovers the $Ka^{1/3}$ scaling of Nivarti *et al.*, where Ka is the Karlovitz number. The relation has the same form as the power-law flame-wrinkling factor of Charlette *et al.* (*Combust. Flame*, vol. 131, 2002, p. 159) with exponent $1/2$, which supports the square-root dependence at large scales. With spectral constants from non-reacting turbulence, the prediction follows 80 measurements from eight datasets spanning four decades of Ka and Re, 71 % of them within a factor of 1.5.

Key words: combustion, turbulent reacting flows, turbulent mixing

1. Introduction

Damköhler (1940) proposed two mechanisms by which turbulence raises the burning velocity of a premixed flame above its laminar value s_L. Eddies larger than the laminar flame thickness δ_L wrinkle the flame without altering its inner structure, so that the turbulent burning velocity

† Email address for correspondence: michael.walker@princeton.edu

Abstract must not spill onto p.2

s_T grows with the flame-surface area,

$$\frac{s_T}{s_L} = \frac{A_T}{A} = 1 + \frac{\Delta A}{A}, \tag{1.1}$$

where A_T is the wrinkled area and A the mean (unwrinkled) area. Eddies smaller than δ_L instead enhance transport within the flame as a diffusive process. Since $s_L \propto D^{1/2}$ for a fixed reaction time (Zel'dovich & Frank-Kamenetskiĭ 1938), an effective turbulent diffusivity $D_T = D + \Delta D$ yields

$$\frac{s_T}{s_L} = \left(\frac{D_T}{D}\right)^{1/2} = \left(1 + \frac{\Delta D}{D}\right)^{1/2}. \tag{1.2}$$

The two hypotheses, (1.1) and (1.2), are conventionally assigned to separate regimes, delineated by the Karlovitz number $Ka \equiv \delta_L^2/\eta^2$, where η is the Kolmogorov scale (Peters 1999, 2000). Throughout, unity Schmidt and Lewis numbers are assumed, so that $\nu = D = s_L\delta_L$, and the Reynolds and Karlovitz numbers are

$$Re \equiv \frac{u'\ell_0}{\nu} = \frac{u'}{s_L}\frac{\ell_0}{\delta_L}, \quad Ka = \left(\frac{u'}{s_L}\right)^{3/2}\left(\frac{\ell_0}{\delta_L}\right)^{-1/2}, \quad \text{such that} \quad \frac{u'}{s_L} = Ka^{1/2}Re^{1/4}, \tag{1.3}$$

with u' the r.m.s. velocity fluctuation and ℓ_0 the integral length scale.

Planar measurements in intense turbulence (Yuen & Gülder 2013; Wabel *et al.* 2017) show that (1.1) fails for $Ka > 1$: the area ratio A_T/A saturates near 4–6 while s_T/s_L continues to rise, reaching nearly 30 (figure 1*b*; see also the reviews of Driscoll *et al.* 2020 and Hochgreb 2023). Direct numerical simulations at $u'/s_L = 35$ show a smaller excess, about 14 % on average, attributed to flame collisions (Poludnenko & Oran 2011; Hicks 2015). Nivarti *et al.* (2019) reconciled s_T and A_T/A by writing $s_T/s_L = (A_T/A)(1 + \Delta D^{>}/D)^{1/2}$ and estimating the sub-δ_L enhancement $\Delta D^{>}$ by summing Prandtl mixing-length diffusivities over the portion of a model energy spectrum with wavenumbers $\kappa > \delta_L^{-1}$. The result, $\Delta D^{>}/D \sim Ka^{2/3}$, accounted for the measured ratio $(s_T/s_L)/(A_T/A) \sim Ka^{1/3}$. Related spectral estimates of small-scale enhancement have been made by Zimont (1979), Ronney & Yakhot (1992) and Gülder (2007), and spectral closures have previously been used for the large-scale regime (Peters 1992; Chaudhuri *et al.* 2011, 2012).

Because area enhancement by large eddies is itself a function of the spectrum, it is natural to ask whether a single spectral sum over all scales can account for s_T in every regime (Walker 2019). Two difficulties must be overcome. First, the scale velocity $u(\kappa) = [2E(\kappa)]^{1/2}$ used by Nivarti *et al.* (2019), where $E(\kappa)$ is the energy spectrum function, has dimensions of $\mathrm{L}^{3/2}\,\mathrm{T}^{-1}$, so the integrand $u(\kappa)/\kappa$ is not a diffusivity and its prefactor is arbitrary. Second, the square root in (1.2) derives from laminar-flame theory, and there is no obvious reason for it to hold at scales where area enhancement contributes significantly to the burning velocity.

This paper resolves both. In § 2, the scale-dependent diffusivity is taken from the spectral eddy diffusivity of two-point closures (Kraichnan 1976; Chollet & Lesieur 1981; Chollet 1984), which fixes its dimensions and prefactor. In § 3, the resulting integral is shown to reduce to a function of u'/s_L and Re alone, and the reduced relation is shown to coincide with the power-law flame-wrinkling factor of Charlette *et al.* (2002*a*) with exponent $1/2$. Section 4 compares the prediction with eight experimental datasets.




Figure 1: (*a*) Experimental conditions on the turbulent combustion regime diagram. (*b*) Burning-velocity ratio s_T/s_L (black) and flame-surface-area ratio A_T/A (blue, with ±20 % uncertainty from Wabel 2017; Yuen 2009; Filatyev *et al.* 2005) against Ka for the datasets where both were measured; for Filatyev *et al.* (2005), A_T/A is the squared ratio of wrinkled to mean flame perimeter, multiplied by a $2/\pi$ consistency factor for comparing slot and round burners. Symbols and data sources are listed in table 1.

2. Formulation

2.1. *Spectral eddy diffusivity*

In two-point closures of isotropic turbulence, the depletion of energy from a mode κ to all modes beyond a cut-off $\kappa_c > \kappa$ is represented by a spectral eddy viscosity (Kraichnan 1976; Chollet & Lesieur 1981; Pope 2000),

$$\nu_e(\kappa|\kappa_c) = \nu_e^+(\kappa/\kappa_c)\left[\frac{E(\kappa_c)}{\kappa_c}\right]^{1/2}, \tag{2.1}$$

where the non-dimensional function ν_e^+, computed with the eddy-damped quasi-normal Markovian closure, is flat for $\kappa \ll \kappa_c$ and rises to a cusp as $\kappa \to \kappa_c$ (Chollet 1984). Chollet (1984) also computed the corresponding eddy diffusivity D_e^+ of a passive scalar, whose ratio to ν_e^+ defines a spectral turbulent Schmidt number $Sc_T = \nu_e^+/D_e^+$. Fits to these curves (figure 2*b*; coefficients in supplementary table S1) give, at the cusp, $\nu_e^+(1) = 0.868$, $Sc_T(1) = 0.462$ and hence $D_e^+(1) = 1.88$.

The factor $[E(\kappa)/\kappa]^{1/2}$ in (2.1) can be written u_κ/κ, where $u_\kappa \equiv [\kappa E(\kappa)]^{1/2}$ is the characteristic velocity of eddies of size κ^{-1}. It is therefore Prandtl's mixing-length product of a velocity and a length at that scale, with the dimensions of a diffusivity. Accordingly, we assign to each wavenumber the scalar eddy diffusivity at the cusp,

$$D_\kappa(\kappa) \equiv D_e^+(1)\left[\frac{E(\kappa)}{\kappa}\right]^{1/2} = D_e^+(1)\,\frac{u_\kappa}{\kappa}, \tag{2.2}$$

that is, the transport exerted by eddies of wavenumber κ on scales just larger than themselves. Equation (2.2) replaces the integrand $[2E(\kappa)]^{1/2}/\kappa$ of Nivarti *et al.* (2019), removing the dimensional inconsistency and taking the prefactor from the closure rather than setting it to unity.

2.2. *Total diffusivity enhancement*

Following Nivarti *et al.* (2019), the contributions of all scales are summed with wavenumber measured in units of the flame wavenumber δ_L^{-1}. Using $D = s_L\delta_L$,

$$\frac{\Delta D}{D} = \frac{1}{D}\int_{\kappa_0}^{\kappa_\eta} D_\kappa \,\mathrm{d}(\kappa\delta_L) = \frac{D_e^+(1)}{s_L}\int_{\kappa_0}^{\kappa_\eta} u_\kappa \,\mathrm{d}\ln\kappa, \tag{2.3}$$

with $\kappa_0 = \ell_0^{-1}$ and $\kappa_\eta = \eta^{-1}$. This weighting is the central modelling assumption of the theory: each logarithmic band of eddies adds a diffusivity $D_e^+ u_\kappa \delta_L$, with the flame thickness as its mixing length. It differs from the classical estimate $\Delta D \propto u'\ell_0$, in which every eddy mixes over its own size (Damköhler 1940). The two can be compared through the flux each band carries across the flame. Let $\Delta\Lambda$ be the change in a progress variable Λ across the flame, so that the molecular flux is $D\Delta\Lambda/\delta_L = s_L\Delta\Lambda$. A band of velocity u_κ can transport at most $u_\kappa\Delta\Lambda$. With mixing length κ^{-1}, its gradient-diffusion flux would be $u_\kappa(\kappa\delta_L)^{-1}\Delta\Lambda$. For eddies smaller than the flame ($\kappa\delta_L > 1$), this is below that bound, and replacing κ^{-1} by δ_L changes only an $O(1)$ constant, because both sums are dominated by $\kappa \approx \delta_L^{-1}$. For eddies larger than the flame, the gradient-diffusion flux exceeds the bound, so their mixing length is capped at δ_L. Each band then carries a flux of order $u_\kappa\Delta\Lambda$, which relative to the molecular flux gives (2.3). The estimate $\Delta D \propto u'\ell_0$ is therefore valid only in Damköhler's limit $\ell_0 < \delta_L$. A further consequence of (2.3) is that δ_L is absent from the enhancement factor, which becomes a ratio of velocities.

For the energy spectrum, we adopt the model of Pope (2000) used by Nivarti *et al.* (2019),

$$E(\kappa) = C\varepsilon^{2/3}\kappa^{-5/3} f_L(\kappa\ell_0) f_\eta(\kappa\eta), \quad f_L = \left[1 + \frac{c_L}{(\kappa\ell_0)^2}\right]^{-(5/3+p_0)/2}, \quad f_\eta = \mathrm{e}^{-\beta\kappa\eta}, \tag{2.4}$$

where ε is the kinetic energy dissipation rate. In units of the laminar flame, with $\hat\kappa \equiv \kappa\delta_L$, the dissipation rate $\varepsilon = 15\nu(u'/\lambda)^2$ with Taylor microscale $\lambda = \ell_0(10/Re)^{1/2}$ (Taylor 1935) becomes $\hat\varepsilon \equiv \varepsilon\delta_L/s_L^3 = (3/2)Ka^2$ (Nivarti *et al.* 2019). The integration limits become $\hat\kappa_0 = Ka^{1/2}Re^{-3/4}$ and $\hat\kappa_\eta = Ka^{1/2}$ (Walker 2019). Substituting (2.4) into (2.3) gives

$$\mathcal{S} \equiv \frac{\Delta D}{D} = C\,Ka^{2/3}\int_{Ka^{1/2}Re^{-3/4}}^{Ka^{1/2}} \hat\kappa^{-4/3}\,\hat f_L^{1/2}\hat f_\eta^{1/2}\,\mathrm{d}\hat\kappa, \qquad C \equiv D_e^+(1)\,C^{1/2}(3/2)^{1/3}, \tag{2.5}$$

where $\hat f_L = [1 + c_L KaRe^{-3/2}\hat\kappa^{-2}]^{-(5/3+p_0)/2}$ and $\hat f_\eta = \exp(-\beta\hat\kappa Ka^{-1/2})$. Compared with Nivarti *et al.* (2019, their equation (2.7)), the exponent of the integrand changes from $-11/6$ to $-4/3$, and the prefactor $(2C)^{1/2}(3/2)^{1/3}$ is replaced by C, which equals 2.64 for $C = 1.5$. Finally, (1.2) is applied over the entire spectrum,

$$\frac{s_T}{s_L} = (1+\mathcal{S})^{1/2}, \tag{2.6}$$

a step justified in § 3.2.

3. Analysis

3.1. *Reduction to two groups*

Equation (2.5) simplifies considerably. Substituting $\hat\kappa = \hat\kappa_0\kappa^*$, where $\kappa^* \equiv \kappa\ell_0$, and using $Ka^{1/2}Re^{1/4} = u'/s_L$ from (1.3), the prefactor $Ka^{2/3}\hat\kappa_0^{-1/3}$ reduces to u'/s_L and the integration

Focus on Fluids articles must not exceed this page length




Figure 2: (*a*) Model energy spectrum (2.4) in flame units for increasing p_0. Wavenumbers below δ_L^{-1} (red) contribute a mixed *Re*–*Ka* dependence to (2.5), and those above δ_L^{-1} (blue) a dependence on *Ka* alone. (*b*) Spectral eddy viscosity ν_e^+, eddy diffusivity D_e^+ and turbulent Schmidt number Sc_T computed by Chollet (1984), the regression for ν_e^+ given by Pope (2000), and those used here.

limits become 1 and $Re^{3/4}$. The enhancement is therefore

$$\mathcal{S} = C\,\frac{u'}{s_L}\,\mathcal{F}(Re), \qquad \mathcal{F}(Re) = \int_1^{Re^{3/4}} \kappa^{*-4/3}\left(1+\frac{c_L}{\kappa^{*2}}\right)^{-(5/3+p_0)/4} \exp\left(-\frac{\beta\kappa^*}{2Re^{3/4}}\right) \mathrm{d}\kappa^*, \tag{3.1}$$

and (2.6) becomes

$$\frac{s_T}{s_L} = \left[1 + C\,\mathcal{F}(Re)\,\frac{u'}{s_L}\right]^{1/2}. \tag{3.2}$$

This is equivalent to $\Delta D = C\,\mathcal{F}(Re)\,u'\delta_L$, an eddy diffusivity with the r.m.s. velocity as its velocity scale and the flame thickness as its mixing length. The burning velocity thus depends on two groups only, u'/s_L and *Re*; the Karlovitz number is not an independent parameter.

The function $\mathcal{F}$ carries the spectral contribution. With $f_L = f_\eta = 1$ (inertial range only), $\mathcal{F} = 3(1 - Re^{-1/4})$. Retaining the dissipation range ($f_L = 1$), $\mathcal{F}$ can be written in terms of the upper incomplete gamma function $\Gamma(s,x)$,

$$\begin{aligned}\mathcal{F} &= (\beta/2)^{1/3} Re^{-1/4}\left[\Gamma(-1/3,\,\beta Re^{-3/4}/2) - \Gamma(-1/3,\,\beta/2)\right] \\ &= 3 - c_\beta Re^{-1/4} + O(Re^{-3/4}),\end{aligned} \tag{3.3}$$

with $c_\beta = (\beta/2)^{1/3}[\Gamma(-1/3,\,\beta/2) - \Gamma(-1/3)] = 5.61$ for $\beta = 5.2$. The energy-containing range reduces the asymptote to $\mathcal{F}_\infty = \int_1^\infty \kappa^{*-4/3}(1 + c_L\kappa^{*-2})^{-(5/3+p_0)/4}\,\mathrm{d}\kappa^*$, which equals 2.56, 2.24 and 2.05 for $p_0 = 0$, 2 and 4 ($c_L = 6.78$). For $p_0 = 0$, $\mathcal{F} = 0.98$, 1.60 and 2.00 at $Re = 10^2$, 10^3 and 10^4. Since $\mathcal{F}$ approaches its asymptote as $Re^{-1/4}$, the Reynolds-number dependence persists up to the highest laboratory Reynolds numbers, but it is weak (figure 3*a*). The dissipation range lowers $\mathcal{F}$ more than the energy-containing range for $Re \lesssim 10^3$, and less for larger *Re*.

Three limits of (3.2) connect it with earlier results.

(i) *Weak turbulence*, $C\,\mathcal{F}\,u'/s_L \ll 1$: $s_T/s_L \approx 1 + \frac{1}{2}C\,\mathcal{F}\,u'/s_L$. This is Damköhler's linear scaling $s_T - s_L \propto u'$, which he derived from (1.1) by taking the area increase proportional to u'/s_L.

(ii) *Strong turbulence*, $C\,\mathcal{F}\,u'/s_L \gg 1$: $s_T/s_L \approx (C\,\mathcal{F}\,u'/s_L)^{1/2}$, i.e. $s_T/s_L \propto Ka^{1/4}Re^{1/8}$




Figure 3: (*a*) The function $\mathcal{F}(Re)$ of (3.1) for $p_0 = 0$, 2 and 4, with the inertial-range result $3(1 - Re^{-1/4})$ and the form (3.3) with $f_L = 1$; short lines at the right mark $\mathcal{F}_\infty$, and shading spans the Re of the measurements. (*b*) Measured s_T/s_L (black) and A_T/A (blue) against the prediction (3.2). Dashed line, equality; dotted lines, a factor of 1.5 either side. Symbols as in table 1.

at fixed $\mathcal{F}$. The transition between (i) and (ii) is the 'bending' of s_T with increasing u' (Bradley 1992; Lipatnikov & Chomiak 2002). It arises here without any quenching mechanism, from the square root in (2.6) alone. For comparison, taking $\Delta D \propto u'\ell_0$ in (1.2) gives $s_T/s_L \propto Re^{1/2}$ (Damköhler 1940; Chaudhuri *et al.* 2011); Chaudhuri *et al.* (2012) found the same scaling in expanding flames with the mean flame radius in place of ℓ_0. The difference lies in the mixing length: ℓ_0 in that estimate, δ_L in (2.3).

(iii) *Sub-flame scales.* The part of (2.5) with $\hat{\kappa} > 1$, for which $\hat{f}_L \approx 1$ when $\ell_0 \gg \delta_L$, is

$$\begin{aligned} \mathcal{S}^> &= C(\beta/2)^{1/3} Ka^{1/2} \left[\Gamma(-1/3,\, \beta Ka^{-1/2}/2) - \Gamma(-1/3,\, \beta/2)\right] \\ &= 3CKa^{2/3} - c_\beta C Ka^{1/2} + O(Ka^{1/6}), \end{aligned} \tag{3.4}$$

which retains the leading-order $Ka^{2/3}$ scaling of Nivarti *et al.* (2019) and hence their $(s_T/s_L)/(A_T/A) \sim Ka^{1/3}$, now with a dimensionally consistent integrand. In the inertial range, the remaining large-scale part is $\mathcal{S}^< \approx 3C(u'/s_L - Ka^{2/3})$, so that $\mathcal{S}^</\mathcal{S}^> \approx (\ell_0/\delta_L)^{1/3} - 1$. Eddies larger than the flame therefore dominate once $\ell_0/\delta_L \gtrsim 8$. The total, however, is a smooth function of u'/s_L and Re in which δ_L plays no distinct role, so a division of turbulence into 'large' and 'small' scales at δ_L is not needed to predict s_T.

3.2. *Equivalence with power-law flame wrinkling*

Charlette *et al.* (2002*a*) modelled the unresolved wrinkling of a flame in a large-eddy simulation with filter width Δ as a power law between an outer cut-off Δ and an inner cut-off η_c,

$$\Xi_\Delta = \left(1 + \frac{\Delta}{\eta_c}\right)^{\beta_w}, \qquad \frac{\Delta}{\eta_c} = \Gamma_\Delta \frac{u'_\Delta}{s_L} \quad \longrightarrow \quad \Xi_\Delta = \left(1 + \Gamma_\Delta \frac{u'_\Delta}{s_L}\right)^{\beta_w}. \tag{3.5}$$

Here η_c follows from an equilibrium between the production of surface by sub-filter strain, $\Gamma_\Delta u'_\Delta/\Delta$, and its destruction by propagation, s_L/η_c. The efficiency function Γ_Δ is a spectral superposition of the straining by all eddies smaller than Δ (Meneveau & Poinsot 1991; Colin *et al.* 2000). Evaluated at $\Delta = \ell_0$, the limit noted by Charlette *et al.* (2002*a*), where $\Xi_{\ell_0} = s_T/s_L$, and with $\beta_w = 1/2$, (3.5) is identical to (3.2) with $\Gamma_{\ell_0} \equiv C\,\mathcal{F}(Re)$.

Equation (3.2) can therefore be read in two ways: as Damköhler's second hypothesis

	Dataset	Configuration	ϕ [-]	u'/s_L [-]	ℓ_0/δ_L [-]	$\overline{\Lambda}$ [-]	n
△	Michigan (Wabel *et al.* 2017)	piloted Bunsen, 21.6 mm	0.75	5.2–163	17–114	0.5	18
▷	Michigan (Filatyev *et al.* 2005)	piloted slot, 25.4 mm	1.0	0.68–4.8	8.9–37	0.5	7
○	Toronto (Yuen & Gülder 2013)	piloted Bunsen, 11.2 mm	0.6–1.0	3.2–24	1.6–3.8	0.5	8
◁	Toronto (Tamadonfar & G. 2014)	piloted Bunsen, 11.1 mm	0.7–1.0	1.8–12	13–40	0.5	16
▽	Tohoku (Kobayashi *et al.* 1996)	piloted Bunsen, 20 mm	0.9	0.29–1.4	19–42	0.5	4
□	Aachen (Plessing *et al.* 2000)	low-swirl, 50.8 mm	0.7	3.5–19	43	0.5	6
◇	Ottawa (Smallwood *et al.* 1995)	Bunsen, 25 mm	0.7–1.0	0.62–2.4	33–141	0.05	6
⬠	Damköhler (1940)	Bunsen, 1.4–2.7 mm	–	0–5.8	11–21	–	15

Table 1: Datasets, with the symbols used in figures 1, 3 and 4. All are methane–air flames at 0.1 MPa and about 300 K except those of Damköhler (1940) (propane–butane–oxygen). Here ϕ is the equivalence ratio, $\overline{\Lambda}$ the mean progress variable of the isosurface defining s_T, and n the number of points.

with a spectral eddy diffusivity, or as his first hypothesis with a power-law wrinkling of exponent $1/2$ and a spectrally derived efficiency. The burning velocity cannot distinguish between them. Charlette *et al.* (2002*a*) chose $\beta_w = 0.5$ from comparisons with measured s_T, and their dynamic procedure (Charlette *et al.* 2002*b*) returned local exponents concentrated between 0.5 and 0.6 (supplementary figure S1). They also argued that the fractal value $\beta_w = 1/3$, required to recover Damköhler's large-u' limit $s_T \propto u'$, is unlikely to be reached in practice. The square root in (2.6) is thus consistent with the observed behaviour of large-scale wrinkling, which resolves the second difficulty raised in § 1. The equivalence concerns the consumption rate rather than the area itself. The sub-δ_L contribution (3.4) acts through transport within the flame (Nivarti *et al.* 2019) and is not expected to appear in a measured A_T/A.

4. Comparison with experiments

Table 1 lists the experiments, which span $0.02 < Ka < 310$ and $10 < Re < 2{\times}10^4$ (figure 1*a*). For uniformity, s_T is the global consumption speed on the $\overline{\Lambda} = 0.5$ isosurface wherever the source reports it (supplementary section S2), and Re and Ka are evaluated from the tabulated u'/s_L and ℓ_0/δ_L using (1.3). The spectral constants are those of non-reacting turbulence: $C = 1.5$, $\beta = 5.2$ and $c_L = 6.78$ (Pope 2000), with $D_e^+(1) = 1.88$ from Chollet (1984), so that $C = 2.64$. We take $p_0 = 0$, a spectrum that is flat at low wavenumbers, which gave the best agreement in the comparisons of Walker (2019); $p_0 = 2$ and 4 lower the predictions by medians of 12 % and 20 % over the present data. Apart from this choice, no constant is adjusted to the data.

Figure 3(*b*) compares (3.2) with the measurements. Over a more than twenty-fold range of s_T/s_L, 71 % of the 80 points lie within a factor of 1.5 of the prediction, and the r.m.s. logarithmic deviation is 0.38. The two high-Ka datasets are captured best. For Michigan (Wabel *et al.* 2017), at $3 < Ka < 310$ and Re up to 2×10^4, the geometric-mean ratio of measurement to prediction is 1.06 with an r.m.s. logarithmic deviation of 0.21; Toronto (Yuen & Gülder 2013) has the same mean ratio with a deviation of 0.20. These are the conditions under which A_T/A (blue symbols) falls furthest below s_T/s_L, and the prediction tracks s_T rather than the area. The remaining datasets show systematic offsets: the low-Ka Bunsen flames of Tohoku, Ottawa and Michigan (2005) lie above the prediction by factors of 1.4–1.8, the low-swirl flames of Aachen by a factor of 2, and the Toronto data of Tamadonfar




Figure 4: (*a*) Measured s_T/s_L against u'/s_L, with (3.2) at three Reynolds numbers; thick grey lines show the weak- and strong-turbulence limits at $Re = 10^3$. (*b*) Contours of (3.2) in the (Re, Ka) plane, labelled with the predicted s_T/s_L; symbols are coloured by the measured s_T/s_L on the same scale. Symbols as in table 1.

& Gülder (2014) at 0.8 times the prediction. Offsets of this size are comparable to the effect of the isosurface choice alone, which changes the reported s_T by up to a factor of two in the Toronto data (Yuen & Gülder 2013). They are also comparable to the known sensitivity of s_T to flame configuration (Driscoll 2008; Verma & Lipatnikov 2016). There is, however, a weak trend with Ka: points with $Ka \leqslant 1$ lie above the prediction by a factor of 1.3 on average, whereas those with $Ka > 1$ are unbiased (mean ratios of 1.00 for $1 < Ka \leqslant 10$ and 1.07 for $Ka > 10$). One candidate for the low-Ka excess is hydrodynamic (Darrieus–Landau) instability, which adds wrinkling when u'/s_L is small (Chaudhuri *et al.* 2011) and is absent from the present formulation.

Figure 4(*a*) shows the data against u'/s_L. The prediction passes from the linear growth of limit (i) to the square-root growth of limit (ii) near $u'/s_L \approx 1/(\mathcal{C}\mathcal{F})$, which is 0.2–0.4 for $10^2 \leqslant Re \leqslant 10^4$. The data follow this bending over three decades of u'/s_L, and the spread in $\mathcal{F}(Re)$ between $Re = 10^2$ and 10^4 accounts for part of their scatter at fixed u'/s_L. Figure 4(*b*) maps the prediction over the regime landscape. At $Re \gtrsim 10^3$, where $\mathcal{F}$ is nearly constant, the contours approach lines of constant u'/s_L, $Ka \propto Re^{-1/2}$. At lower Re, the decrease of $\mathcal{F}$ steepens them, and there s_T becomes sensitive to Re at fixed u'/s_L. The measured values (symbol colour) increase across the plane in the same direction as the contours, from the low-Re, low-u'/s_L corner to the high-Re, high-Ka Michigan flames. Supplementary figure S3 shows the same measurements as $(s_T/s_L)/Ka$ against Re.

5. Conclusions

The diffusive enhancement of the burning velocity proposed by Nivarti *et al.* (2019) for sub-flame eddies has been extended to the whole turbulence spectrum and made dimensionally consistent. Its scale-dependent diffusivity is taken from the spectral eddy diffusivity of two-point closures. For a model spectrum, the total enhancement reduces to $\mathcal{C}\,\mathcal{F}(Re)\,u'/s_L$, with $\mathcal{F}$ a weak, saturating function of the Reynolds number. The resulting burning velocity, (3.2), recovers three established results: Damköhler's linear law in weak turbulence, the bending of s_T in strong turbulence, and the $Ka^{1/3}$ excess of s_T/s_L over A_T/A at high Karlovitz number. With spectral constants from non-reacting turbulence, it follows eight datasets over four decades of Ka and Re, mostly to within a factor of 1.5. The same expression is the power-law wrinkling factor of Charlette *et al.* (2002*a*) with exponent 1/2, so area enhancement by large

eddies and diffusive enhancement by small eddies need not be treated as distinct mechanisms when predicting s_T.

Two implications follow. First, evaluated at a filter scale Δ with the sub-filter intensity u'_Δ and Reynolds number Re_Δ, (3.2) provides a sub-filter wrinkling factor of the form (3.5) whose efficiency function, $C\mathcal{F}(Re_\Delta)$, follows from the spectrum rather than from a fit to combustion data. Second, the remaining differences between datasets may be explained by the quantities the theory neglects: anisotropy of the approaching flow and the effect of heat release on its spectrum, differences in the definitions of s_T and δ_L, and differential diffusion, stretch and quenching. Measurements of the turbulence spectrum upstream of the flame, and simulations at matching u'/s_L and Re in different configurations, would test whether the dependence on these two groups alone is complete.

Supplementary data. Supplementary material is available at https://doi.org/ ....

Acknowledgements. The authors thank Dr Aaron Skiba for helping interpret the experimental data. The authors thank Professors Denis Veynante, Peter Davidson, Andy Aspden and Matthew Juniper for helpful discussions and critical feedback.

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the U.S. Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the U.S. Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the U.S. Government or any agency thereof.

Funding. This material is based upon work supported by the U.S. Department of Energy, Office of Science, Office of Advanced Scientific Computing Research, Department of Energy Computational Science Graduate Fellowship under Award Number DE-SC0024386. M.D.W. was further supported by the Churchill Scholarship from the Winston Churchill Foundation of the United States. G.V.N. acknowledges the funding support of EPSRC grant EP/P022286/1.

Declaration of interests. The authors report no conflict of interest.

Data availability statement. The data that support the findings of this study are openly available on GitHub at https://github.com/mw6136/spectral.

Author ORCIDs. M. D. Walker, https://orcid.org/0000-0002-4765-6539; G. V. Nivarti, https://orcid.org/0000-0002-8326-1147; M. E. Mueller, https://orcid.org/0000-0002-5699-1275; R. S. Cant, https://orcid.org/0000-0003-1851-6665; S. Hochgreb, https://orcid.org/0000-0001-7192-4786

Author contributions. M. D. Walker: Writing – original draft, Validation, Software, Methodology, Investigation, Data Curation. G. V. Nivarti: Methodology, Investigation, Conceptualization, Writing – review & editing. M. E. Mueller: Writing – review & editing, Supervision. R. S. Cant: Methodology, Investigation, Writing – review & editing, Supervision. S. Hochgreb: Conceptualization, Writing – review & editing, Supervision.

REFERENCES

Bradley, D. 1992 How fast can we burn? *Symp. (Int.) Combust.* **24** (1), 247–262.

Charlette, F., Meneveau, C. & Veynante, D. 2002*a* A power-law flame wrinkling model for LES of premixed turbulent combustion Part I: non-dynamic formulation and initial tests. *Combust. Flame* **131** (1), 159–180.

Charlette, F., Meneveau, C. & Veynante, D. 2002*b* A power-law flame wrinkling model for LES of premixed turbulent combustion Part II: dynamic formulation. *Combust. Flame* **131** (1), 181–197.

Chaudhuri, S., Akkerman, V. & Law, C. K. 2011 Spectral formulation of turbulent flame speed with consideration of hydrodynamic instability. *Phys. Rev. E* **84** (2), 026322.

Chaudhuri, S., Wu, F., Zhu, D. & Law, C. K. 2012 Flame speed and self-similar propagation of expanding turbulent premixed flames. *Phys. Rev. Lett.* **108** (4), 044503.

Chollet, J.-P. 1984 Two-point closure used for a sub-grid scale model in large eddy simulations. In *4th Symposium on Turbulent Shear Flows* (ed. L. J. S. Bradbury, F. Durst, B. E. Launder, F. W. Schmidt & J. H. Whitelaw), pp. 62–72. Springer Berlin Heidelberg.

Chollet, J.-P. & Lesieur, M. 1981 Parameterization of small scales of three-dimensional isotropic turbulence utilizing spectral closures. *J. Atmos. Sci.* **38** (12), 2747–2757.

Colin, O., Ducros, F., Veynante, D. & Poinsot, T. 2000 A thickened flame model for large eddy simulations of turbulent premixed combustion. *Phys. Fluids* **12** (7), 1843–1863.

Damköhler, G. 1940 Der Einfluss der Turbulenz auf die Flammengeschwindigkeit in Gasgemischen. *Z. Elektrochem. Angew. Phys. Chem.* **46** (11), 601–652, (English translation: The effect of turbulence on the flame velocity in gas mixtures, NACA TM 1112, 1947).

Driscoll, J. F. 2008 Turbulent premixed combustion: Flamelet structure and its effect on turbulent burning velocities. *Prog. Energy Combust. Sci.* **34** (1), 91–134.

Driscoll, J. F., Chen, J. H., Skiba, A. W., Carter, C. D., Hawkes, E. R. & Wang, H. 2020 Premixed flames subjected to extreme turbulence: Some questions and recent answers. *Prog. Energy Combust. Sci.* **76**, 100802.

Filatyev, S. A., Driscoll, J. F., Carter, C. D. & Donbar, J. M. 2005 Measured properties of turbulent premixed flames for model assessment, including burning velocities, stretch rates, and surface densities. *Combust. Flame* **141** (1), 1–21.

Gülder, Ö. L. 2007 Contribution of small scale turbulence to burning velocity of flamelets in the thin reaction zone regime. *Proc. Combust. Inst.* **31** (1), 1369–1375.

Hicks, E. P. 2015 Rayleigh–Taylor unstable flames—fast or faster? *Astrophys. J.* **803** (2), 72.

Hochgreb, S. 2023 How fast can we burn, 2.0. *Proc. Combust. Inst.* **39** (2), 2077–2105.

Kobayashi, H., Tamura, T., Maruta, K., Niioka, T. & Williams, F. A. 1996 Burning velocity of turbulent premixed flames in a high-pressure environment. *Symp. (Int.) Combust.* **26** (1), 389–396.

Kraichnan, R. H. 1976 Eddy viscosity in two and three dimensions. *J. Atmos. Sci.* **33** (8), 1521–1536.

Lipatnikov, A. N. & Chomiak, J. 2002 Turbulent flame speed and thickness: phenomenology, evaluation, and application in multi-dimensional simulations. *Prog. Energy Combust. Sci.* **28** (1), 1–74.

Meneveau, C. & Poinsot, T. 1991 Stretching and quenching of flamelets in premixed turbulent combustion. *Combust. Flame* **86** (4), 311–332.

Nivarti, G. V., Cant, R. S. & Hochgreb, S. 2019 Reconciling turbulent burning velocity with flame surface area in small-scale turbulence. *J. Fluid Mech.* **858**, R1.

Peters, N. 1992 A spectral closure for premixed turbulent combustion in the flamelet regime. *J. Fluid Mech.* **242**, 611–629.

Peters, N. 1999 The turbulent burning velocity for large-scale and small-scale turbulence. *J. Fluid Mech.* **384**, 107–132.

Peters, N. 2000 *Turbulent Combustion*. Cambridge University Press.

Plessing, T., Kortschik, C., Peters, N., Mansour, M. S. & Cheng, R. K. 2000 Measurements of the turbulent burning velocity and the structure of premixed flames on a low-swirl burner. *Proc. Combust. Inst.* **28** (1), 359–366.

Poludnenko, A. Y. & Oran, E. S. 2011 The interaction of high-speed turbulence with flames: Turbulent flame speed. *Combust. Flame* **158** (2), 301–326.

Pope, S. B. 2000 *Turbulent Flows*. Cambridge University Press.

Ronney, P. D. & Yakhot, V. 1992 Flame broadening effects on premixed turbulent flame speed. *Combust. Sci. Technol.* **86** (1–6), 31–43.

Smallwood, G. J., Gülder, Ö. L., Snelling, D. R., Deschamps, B. M. & Gökalp, I. 1995 Characterization of flame front surfaces in turbulent premixed methane/air combustion. *Combust. Flame* **101** (4), 461–470.

Tamadonfar, P. & Gülder, Ö. L. 2014 Flame brush characteristics and burning velocities of premixed turbulent methane/air Bunsen flames. *Combust. Flame* **161** (12), 3154–3165.

Taylor, G. I. 1935 Statistical theory of turbulence. *Proc. R. Soc. Lond. A* **151** (873), 421–444.

Verma, S. & Lipatnikov, A. N. 2016 Does sensitivity of measured scaling exponents for turbulent burning velocity to flame configuration prove lack of generality of notion of turbulent burning velocity? *Combust. Flame* **173**, 77–88.

Wabel, T. M. 2017 An experimental investigation of premixed combustion in extreme turbulence. PhD thesis, University of Michigan (USA).

Rapids articles must not exceed this page length

Wabel, T. M., Skiba, A. W. & Driscoll, J. F. 2017 Turbulent burning velocity measurements: Extended to extreme levels of turbulence. *Proc. Combust. Inst.* **36** (2), 1801–1808.

Walker, M. D. 2019 A review of turbulent burning velocity and a spectral theory for turbulent flame propagation. Master's thesis, Churchill College, University of Cambridge (UK).

Yuen, F. T. C. 2009 Experimental investigation of the dynamics and structure of lean-premixed turbulent combustion. PhD thesis, University of Toronto (Canada).

Yuen, F. T. C. & Gülder, Ö. L. 2013 Turbulent premixed flame front dynamics and implications for limits of flamelet hypothesis. *Proc. Combust. Inst.* **34** (1), 1393–1400.

Zel'dovich, Ya. B. & Frank-Kamenetskiĭ, D. A. 1938 Teoriĭa teplovogo rasprostraneniĭa plameni. *Zh. Fiz. Khim.* **12**, 100–105, (English translation: A theory of thermal flame propagation, In "Selected Works of Yakov Borisovich Zel'dovich, Volume I", Princeton University Press, 1992).

Zimont, V. L. 1979 Theory of turbulent combustion of a homogeneous fuel mixture at high Reynolds numbers. *Combust. Explos. Shock Waves* **15** (3), 305–311.