




ANTLR - Introduction


(ANother Tool for Language Recognition)

Vertalerbouw HC4

VB HC4

Original design: Theo Ruys
University of Twente
Department of Computer Science
Formal Methods & Tools

Arend Rensink
kamer: Zilverling 5090
telefoon: 4862
email: rensink@cs.utwente.nl



© Theo Ruys, Arend Rensink

What have you seen last time?

- AST implementation
 - Construction during parsing
- Scoping
 - Blocks
 - Symbol tables
- Type checking
 - Type rules
 - Visitor pattern


VB HC 2

2


© Theo Ruys, Arend Rensink

Overview of Lecture 4

www.antlr.org




- Introduction
- ANTLR 3.4 by Example
 - Calc – a simple calculator language
- Some ANTLR grammar patterns

VB HC 4

ANTLR - Introduction

3


© Theo Ruys, Arend Rensink

ANTLR – Introduction (1)

www.antlr.org

- ANTLR
 - input: language descriptions using EBNF grammar
 - output: recognizer for the language
- ANTLR can build recognizers for three kinds of input:
 - character streams (i.e. by generating a scanner)
 - token streams (i.e. by generating a parser)
 - node streams (i.e. by generating a tree walker)

ANTLR uses the same syntax for all its recognizer descriptions.

VB HC 4

ANTLR - Introduction

4

© Theo Ruys, Arend Rensink www.antlr.org

ANTLR – Introduction (2)


- ANTLR generates (predictive) LL(k) or LL(*) recognizers
 - Computes **first**, **follow** and **lookahead sets**
 - Verifies syntax conditions (e.g. LL(k) test)
 - Generated scanner/lexer is a predictive recursive-descent recognizer and not a finite automaton.
- Terminology
 - lexer** = scanner, lexical analyser, tokenizer
 - parser** = syntactical analyser
 - tree parser** = tree walker
- Other well-known compiler generators
 - scanners**: lex/flex, JFlex
 - parsers**: yacc/Bison, JCup, javaCC, sableCC, SLADE

VB HC 4 ANTLR - Introduction 5

© Theo Ruys, Arend Rensink www.antlr.org


ANTLR – Introduction (3)

- Material** on ANTLR:
 - See ANTLR's website.
 - There is a **wealth of information on ANTLR**. Unfortunately, the documentation is not very well structured and might be overwhelming for beginners.
Spend some time browsing the documentation to get an overview of what is available.
 - Yahoo group**: **antlr-interest** (also as mailing-list)
Active community: quite some traffic!
- Book**:
Terence Parr.
The Definitive ANTLR Reference.
Pragmatic Bookshelf, 2007.



PDF freely available

VB HC 4 ANTLR - Introduction 6



© Theo Ruys, Arend Rensink www.antlr.org

ANTLR – input file structure

```

[?type] grammar FooBar;
options {
    // options for entire grammar file
}

tokens {
    // extra token definitions
}

@header {
    // will be copied to the generated Java file(s)
}

@rulecatch {
    // error handling: how to deal with exceptions?
}

@members {
    // also: @lexer::header and @lexer::members
    // optional class definitions: instance variables, methods
}

rulename : all rules for FooBar
  
```

***.g**

gtype may be empty or tree.

A single .g file can specify a Lexer + Parser, or a TreeParser.

e.g. imports

also: @lexer::header and @lexer::members

optional class definitions: instance variables, methods

all rules for FooBar

VB HC 4 ANTLR - Introduction 8

© Theo Ruys, Arend Rensink

ANTLR – rule structure

ANTLR generates a *recursive descent* recognizer: for each *rule*, ANTLR will generate a Java *method*.

```

rulename [args] returns [T val]
{
  options { local options }
  : alternative1
  | alternative2
  | ...
  | alternativen
  ;

```

optional, used for *passing information around*

An **alternative** is an EBNF expression containing:

- rule names
- TOKENs
- EBNF operators
- Java code in braces

+ optional code sections to insert at start of end of method

```

@init { ... }
@after { ... }

```

EBNF operators

A B	A or B
A*	zero or more A's
A+	one or more A's
A?	an optional A

When using EBNF operators in ANTLR: use parentheses to enclose more than one symbol..

Example

```

expr : operand (PLUS operand)*
      ;
operand : LPAREN expr RPAREN
        | NUMBER
        ;

```

VB HC 4 ANTLR - Introduction 9

© Theo Ruys, Arend Rensink

Running ANTLR

- ANTLR is a Java program:
 - `java org.antlr.Tool file.g`
 - may contain specifications for a lexer and parser, or a treewalker
 - The ANTLR **jar**-file should be in the **CLASSPATH** of course.
- By default Java generates **.java** files which have to be compiled to an **Java application**.
- There also exist several **ANTLR GUI Development Environments**:
 - ANTLRv3 IDE** (for Eclipse)
 - <http://antlr3ide.sourceforge.net/>
 - ANTLRWorks**
 - <http://www.antlr.org/works/>

VB HC 4 ANTLR - Introduction 10

© Theo Ruys, Arend Rensink

Calc – Language (1)

Will be extended upon in the laboratory of week 3 and 4

- Calc**: simple calculator language
 - declarations**
 - only integer variables
 - must all come before statements
 - statements**
 - assignment to variables
 - printing of expressions

```

// ex1.calc
var n: integer;
var x: integer;
n := 2+4-1;
x := n+3+7;
print(x);

```

VB HC 4 ANTLR - Introduction 11

© Theo Ruys, Arend Rensink

Calc – Language (2)

```

// ex1.calc
var n: integer;
var x: integer;
n := 2+4-1;
x := n+3+7;
print(x);

```

- EBNF for Calc**

program	::= declarations statements EOF
declarations	::= (declaration SEMICOLON)*
declaration	::= VAR IDENTIFIER COLON type
statements	::= (statement SEMICOLON)+
statement	::= assignment printStatement
assignment	::= lvalue BECOMES expr
printStatement	::= PRINT LPAREN expr RPAREN
lvalue	::= IDENTIFIER
expr	::= operand ((PLUS MINUS) operand)*
operand	::= IDENTIFIER NUMBER LPAREN expr RPAREN
type	::= INTEGER

All terminals are written as **UPPERCASE** symbols.

VB HC 4 ANTLR - Introduction 12

© Theo Ruys, Arend Rensink

Calc compiler – overview

- We let ANTLR generate four **recognizers**:
 - CalcLexer** (extends *Lexer*)
 - translates a stream of characters to stream of tokens
 - CalcParser** (extends *Parser*)
 - translates a stream of tokens to an stream of tree nodes
 - CalcChecker** (extends *TreeParser*)
 - reads the stream of tree nodes (i.e. the AST) and checks whether the context constraints are obeyed
 - CalcInterpreter** (extends *TreeParser*)
 - reads the stream of tree nodes (i.e. the AST) and executes the program

VB HC 4 ANTLR - Introduction 13

© Theo Ruys, Arend Rensink

ANTLR - Parser & Lexer

- A **lexer** and **parser** are closely **related**. A lexer generates tokens which are consumed by a parser.
- In ANTLR 3.x, the lexer and parser can be combined elegantly into a **single grammar specification**.
 - ANTLR takes care of **splitting** the two specifications.

Literals (i.e. character strings) are enclosed in **single quotes** (e.g. `'bar'`).

Lexer non-terminals (i.e. token names) always start with an **UPPERCASE** letter.

Parser non-terminals always start with an **lowercase** letter.

VB HC 4 ANTLR - Introduction 14

© Theo Ruys, Arend Rensink

Calc – Parser & Lexer (1)

```

grammar Calc;

options {
    k = 1;
    language = Java;
    output = AST;
}

tokens {
    PLUS      = '+' ;
    MINUS     = '-' ;
    BECOMES   = ':' ;
    COLON     = ':' ;
    SEMICOLON = ';' ;
    LPAREN    = '(' ;
    RPAREN    = ')' ;

    // keywords
    PROGRAM   = 'program' ;
    VAR       = 'var' ;
    PRINT     = 'print' ;
    INTEGER   = 'integer' ;
}
  
```

This is a **combined specification** (not prefixed by lexer, parser or tree).

amount of **lookahead**, disables LL(*)

Target language is **Java**.

build an **AST**

token definitions (literals)

tokens always start with an **uppercase letter** and specify the text for a token

VB HC 4 ANTLR - Introduction 15

© Theo Ruys, Arend Rensink

Calc – Parser & Lexer (3)

```

IDENTIFIER : LETTER (LETTER | DIGIT)* ;
NUMBER     : DIGIT+ ;
COMMENT    : '/*' .* '\n' { $channel=HIDDEN ; } ;
WS         : (' ' | '\t' | '\f' | '\r' | '\n')+ { $channel=HIDDEN ; } ;

fragment DIGIT : ('0'..'9') ;
fragment LOWER : ('a'..'z') ;
fragment UPPER : ('A'..'Z') ;
fragment LETTER : LOWER | UPPER ;
  
```

lexer specific rules

`" .* "` matches everything except the character that follows it (i.e. `'\n'`).

There are **multiple token channels**. The parser reads from the **DEFAULT** channel. By setting a token's channel to **HIDDEN** it will be **ignored** by the parser.

shorthand for (the complete) `'a' | 'b' | 'c' | ... | 'y' | 'z'`

fragment lexer rules can be used by other lexer rules, but **do not** return tokens by themselves

VB HC 4 ANTLR - Introduction 16

© Theo Ruys, Arend Rensink

Calc – Parser & Lexer (2)

First **only recognising**, no AST construction yet.

parser specific rules

```

program : declarations statements EOF
;
declarations : (declaration SEMICOLON)*
;
statements : (statement SEMICOLON)+
;
declaration : VAR IDENTIFIER COLON type
;
statement : assignment
;
; print
;
assignment : lvalue BECOMES expr
;
;
print : PRINT LPAREN expr RPAREN
;
;
lvalue : IDENTIFIER
;
;
expr : operand ((PLUS | MINUS) operand)*
;
;
operand : IDENTIFIER
;
; NUMBER
;
; LPAREN expr RPAREN
;
;
type : INTEGER
;

```

special "end-of-file" token

parser rules start with a lowercase letter

```

// ex1.calc
var n: integer;
var x: integer;
n := 2+4-1;
x := n+3+7;
print(x);

```

In this example, all tokens are explicitly named (as UPPERCASE tokens). It is also possible to use **literals** in the parser specification.

For example:

```

print : 'print' '(' expr ')'
expr : operand (('+' | '-') operand)*

```

VB HC 4 ANTLR - Introduction 17

© Theo Ruys, Arend Rensink

Calc – Parser & Lexer (4)

The Parser does not only **recognize** the language, it should also **build the AST**.

parser building the AST

```

program : declarations statements EOF
;
; -> ^(PROGRAM declarations statements)
;
declarations : (declaration SEMICOLON!)*
;
statements : (statement SEMICOLON!)+
;
declaration : VAR^ IDENTIFIER COLON! type
;
statement : assignment
;
; print
;
assignment : lvalue BECOMES^ expr
;
;
print : PRINT^ LPAREN! expr RPAREN!
;
;
lvalue : IDENTIFIER
;
;
expr : operand ((PLUS^ | MINUS^ ) operand)*
;
;
operand : IDENTIFIER
;
; NUMBER
;
; LPAREN! expr RPAREN!
;
;
type : INTEGER
;

```

Imaginary token used as the root node.

Annotations for building AST nodes	
T^	make T the root of this (sub)rule
T!	discard T
-> ^(...)	tree construction for a rule

For example:

```

VAR^ IDENTIFIER COLON! type
= ^ (VAR IDENTIFIER type)
=
  VAR
  /  \
ID   type
ID   type

```

due to rule of operand this builds:

```

^ (PLUS expr expr)

```

first child, next sibling notation

VB HC 4 ANTLR - Introduction 18

© Theo Ruys, Arend Rensink

AST Tree (Example)

```

// ex1.calc
var n: integer;
var x: integer;
n := 2+4-1;
x := n+3+7;
print(x);

```

```

program : decls stats EOF
;
; -> ^(PROGRAM decls stats);
;
decls : (decl SEMICOLON!)*
;
stats : (stat SEMICOLON!)+
;
decl : VAR^ ID COLON! type ;
;
stat : assign | print ;
;
assign : lvalue BECOMES^ expr ;
;
lvalue : ID ;
;
print : PRINT^ LPAREN! expr RPAREN! ;
;
expr : ID ;
;
oper : ((PLUS^ | MINUS^ ) oper)* ;
;
ID : ID | NUM | LPAREN! expr RPAREN! ;
;
type : INT ;

```

ID = IDENTIFIER
INT = INTEGER

VB HC 4 ANTLR - Introduction 19

© Theo Ruys, Arend Rensink

Calc - generated Java files

DEMO

```

Calc.g
grammar Calc;

```

ANTLR

CalcLexer.java
CalcParser.java
Calc.tokens

Contains for each rule **r**, a class **r_return**, which results in many **CalcParser\$.class** files.

VB HC 4 ANTLR - Introduction 20

© Theo Ruys, Arend Rensink

Calc – visualizing the AST (1)

```

public static void main(String[] args) {
    CalcLexer lexer = new CalcLexer(
        new ANTLRInputStream(System.in));
    CommonTokenStream tokens = new CommonTokenStream(lexer);
    CalcParser parser = new CalcParser(tokens);

    Call the start symbol to start parsing.
    CalcParser program_return result = parser.program();
    CommonTree tree = (CommonTree) result.getTree();

    // show S-Expression representation of the AST
    String s = tree.toStringTree();
    System.out.println(s);

    // print the AST as DOT specification
    DOTTreeGenerator gen = new DOTTreeGenerator();
    StringTemplate st = gen.toDOT(tree);
    System.out.println(st);
}

```

A **lexer** gets an ANTLR stream as input.

The **parser** gets the lexer's output tokens.

.dot files can be visualized using the **GraphViz** program: <http://www.graphviz.org/>

DOTTreeGenerator is defined in package **org.antlr.stringtemplate**

VB HC 4 ANTLR - Introduction 21

© Theo Ruys, Arend Rensink

Calc – visualizing the AST (2)

```

// ex1.calc
var n: integer;
var x: integer;
n := 2+4-1;
x := n+3+7;
print(x);

```

```

[nor@joy]$ java Calc -no_interpreter -ast < ex1.calc
PROGRAM (var n integer) (var x integer) (n (- (+ 2 4) 1)) (x (+ (+ n 3) 7)) (print x)
[nor@joy]$

```

via **tree.toStringTree()**

via **DOTTreeGenerator** and **GraphViz**

VB HC 4 ANTLR - Introduction 22

© Theo Ruys, Arend Rensink

Calc Parser – Java code (1)

```

public class CalcParser extends Parser {
    ...
    public final program_return program() throws RecognitionException {
        program_return retval = new program_return();
        ...
        try {
            // Calc.g:44:9: declarations statements EOF
            {
                pushFollow(FOLLOW_declarations_in_program412);
                declarations1=declarations();
                _fsp--;

                stream_declarations.add(declarations1.getTree());
                pushFollow(FOLLOW_statements_in_program414);
                statements2=statements();
                _fsp--;

                stream_statements.add(statements2.getTree());
                EOF3=(Token)input.LT(1);
                match(input,EOF,FOLLOW_EOF_in_program416);
                stream_EOF.add(EOF3);
                ...
            }
        } catch (RecognitionException re) {
            reportError(re);
            recover(input,re);
        }
        ...
        return retval;
    }
}

```

Most code that builds the AST is omitted!

```

program
: declarations statements EOF!
;

```

VB HC 4 ANTLR - Introduction 23

© Theo Ruys, Arend Rensink

Calc Parser – Java code (2)

```

public final declarations_return declarations() throws RecognitionException {
    declarations_return retval = new declarations_return();
    ...
    try {
        ...
        loop1:
        do {
            int alt1=2;
            int LA1_0 = input.LA(1);

            if ( (LA1_0==VAR) )
                alt1=1;

            switch (alt1) {
                case 1 :
                    {
                        pushFollow(FOLLOW_declaration_in_declarations463);
                        declaration4=declaration();
                        ...
                        match(input,SEMICOLON,FOLLOW_SEMICOLON_in_declarations465);
                    }
                    break;
                default :
                    break loop1;
            }
        } while (true);
    } catch (RecognitionException re) {
        reportError(re);
        recover(input,re);
    }
    ...
    return retval;
}

```

LA(1) - current lookahead Token.

```

declarations
: (declaration SEMICOLON!)*
;

```

VB HC 4 ANTLR - Introduction 24

© Theo Ruys, Arend Rensink

Calc – Tree walker

```

program : decls stats EOF -> ^(PROGRAM decls stats);
decls  : (decl SEMICOLON)*;
stats  : (stat SEMICOLON)*;
decl   : VAR IDENTIFIER COLON type;
stat   : assign | print;
assign : lvalue BECOMES expr;
print  : PRINT LPAREN! expr RPAREN!;
lvalue : ID;
expr   : operand ((PLUS | MINUS) operand)*;
operand : ID | NUM | LPAREN! expr RPAREN!;
type   : INT;

```

tree grammar CalcTreeWalker;

```

options {
    tokenVocab = Calc;
    ASTLabelType = CommonTree;
}

program : ^(PROGRAM (declaration | statement)+);

declaration : ^(VAR IDENTIFIER type);

statement : ^(BECOMES IDENTIFIER expr)
          | ^(PRINT expr);

expr : operand
     | ^(PLUS expr expr)
     | ^(MINUS expr expr);

operand : IDENTIFIER | NUMBER;
type : INTEGER;

```

This is a specification of a tree walker.

Import tokens from Calc.tokens.

The AST nodes are of type CommonTree.

The AST has a root node PROGRAM with many (declaration or statement) children.

Match a tree whose root is a PLUS token with two children that match the expr rule.

This tree walker does not do anything (yet). Note the conciseness of the grammar and the correspondence with the "abstract syntax" of the language Calc.

VB HC 4 ANTLR - Introduction 25

© Theo Ruys, Arend Rensink

Calc – Checker (1)

```

tree grammar CalcChecker;

options {
    tokenVocab = Calc;
    ASTLabelType = CommonTree;
}

@header {
    import java.util.Set;
    import java.util.HashSet;
}

@rulecatch {
    catch (RecognitionException e) {
        throw e;
    }
}

@members {
    private Set<String> idset = new HashSet<String>();
    public boolean isDeclared(String s) {
        return idset.contains(s);
    }
    public void declare(String s) {
        idset.add(s);
    }
}

```

CalcChecker checks the context rules of the language:

- each identifier can be declared only once
- identifiers that are used must have been declared.

@header: code block which is copied verbatim to the beginning of CalcChecker.java.

@rulecatch: specify your own error handler. Here: no error handler; exceptions are propagated to the method calling this checker.

@members: code block which is copied verbatim to the class definition of CalcChecker.java.

The Calc language uses a monolithic block structure. For checking the scope rules we can use a Set.

The methods isDeclared and declare become methods of the class CalcChecker.

VB HC 4 ANTLR - Introduction 26

© Theo Ruys, Arend Rensink

Calc – Checker (2)

```

program : ^(PROGRAM (declaration | statement)+);

declaration : (VAR id=IDENTIFIER type)
             { if (!isDeclared($id.getText()))
               throw new CalcException($id.getText() + " is already declared");
             }
             else declare($id.getText());

statement : (BECOMES id=IDENTIFIER expr)
           { if (!isDeclared($id.text))
             throw new CalcException($id.text + " is used but not declared");
           }
           | (PRINT expr);

```

With name=NODE we can refer to the AST node using name ...

... and get its String representation.

Within Java code, the ANTLR variables are (usually) prefixed with \$.

Java code block which is copied verbatim to the parse method of 'declaration' in CalcChecker.java.

... or use the attribute text.

CalcException is a user-defined Exception (subclass of org.antlr.runtime.RecognitionException) to express some problem in the input.

VB HC 4 ANTLR - Introduction 27

© Theo Ruys, Arend Rensink

Calc – Interpreter (1)

```

// ex1.calc
var n: integer;
var x: integer;
n := 2+4-1;
x := n+3+7;
print(x);

```

PROGRAM

```

graph TD
    PROGRAM --> VAR1[VAR]
    PROGRAM --> BECOMES1[BECOMES]
    PROGRAM --> BECOMES2[BECOMES]
    PROGRAM --> PRINT[PRINT]
    VAR1 --> ID1[ID]
    VAR1 --> INT1[INT]
    ID1 --> n[n]
    INT1 --> 0[0]
    BECOMES1 --> ID2[ID]
    BECOMES1 --> MINUS1[MINUS]
    ID2 --> x[x]
    MINUS1 --> PLUS1[PLUS]
    MINUS1 --> 5[5]
    PLUS1 --> ID3[ID]
    PLUS1 --> NUMBER1[NUMBER]
    ID3 --> n[n]
    NUMBER1 --> 1[1]
    PLUS1 --> 6[6]
    PLUS1 --> 4[4]
    BECOMES2 --> ID4[ID]
    BECOMES2 --> PLUS2[PLUS]
    ID4 --> x[x]
    PLUS2 --> ID5[ID]
    PLUS2 --> NUMBER2[NUMBER]
    ID5 --> n[n]
    NUMBER2 --> 7[7]
    PLUS2 --> 8[8]
    PLUS2 --> 3[3]
    PRINT --> ID6[ID]
    ID6 --> x[x]

```

Idea of Interpreter:

- depth-first, left-to-right traversal of AST.
- use Map for storing values of variables
- compute expressions bottom up

VB HC 4 ANTLR - Introduction 28

© Theo Ruys, Arend Rensink

Calc – Interpreter (2)

The structure of the tree grammar *CalcInterpreter* is the same as for *CalcChecker*

```
tree grammar CalcInterpreter;
options {
    tokenVocab = Calc;
    ASTLabelType = CommonTree;
}
@header {
    import java.util.Map;
    import java.util.HashMap;
}
@members {
    Map<String,Integer> store = new HashMap<String,Integer>();
}
program      : ^(PROGRAM (declaration | statement)+);
declaration  : ^(VAR id=IDENTIFIER type)
               { store.put($id.text, 0); };
...

```

Idea of Interpreter:

- depth-first, left-to-right traversal of AST.
- use **Map** for storing values of variables
- compute expressions bottom up

To store the values of the variables.

Initialized on 0.

VB HC 4 ANTLR - Introduction 29

© Theo Ruys, Arend Rensink

Calc – Interpreter (2)

```
statement
: ^(BECOMES id=IDENTIFIER v=expr)
  { store.put($id.text, $v); }
| ^(PRINT v=expr)
  { System.out.println("" + $v); }
;

expr returns [int val = 0]
: z=operand { val = z; }
| ^(PLUS x=expr y=expr) { val = x + y; }
| ^(MINUS x=expr y=expr) { val = x - y; }
;

operand returns [int val = 0]
: id=IDENTIFIER { val = store.get($id.text); }
| n=NUMBER { val = Integer.parseInt($n.text); }
;

```

The rule *expr* returns a value.

The value returned by *expr* is put into the store for *id*.

ANTLR deduces from the context the types of the variables: *id* is a *CommonTree*, *v* is an *int*.

A rule can return a value: **ruleName returns [T x]**
The type of the return value is **T** and the value returned is the value of **x** at the end of the rule.

Note that it is also possible to pass arguments to a rule.

Get the value of **IDENTIFIER** out of the store.

Parse the string representation of the **NUMBER**.

VB HC 4 ANTLR - Introduction 30

© Theo Ruys, Arend Rensink

Calc – driver

```
public static void main(String[] args) {
    CalcLexer lex = new CalcLexer(
        new ANTLRInputStream(System.in));
    CommonTokenStream tokens = new CommonTokenStream(lex);
    CalcParser parser = new CalcParser(tokens);

    Call the start symbol to start parsing.
    CalcParser.program_result result = parser.program();
    CommonTree tree = (CommonTree) result.getTree();

    CommonTreeNodeStream nodes1 = new CommonTreeNodeStream(tree);
    CalcChecker checker = new CalcChecker(nodes1);
    checker.program();

    CommonTreeNodeStream nodes2 = new CommonTreeNodeStream(tree);
    CalcInterpreter interpreter = new CalcInterpreter(nodes2);
    interpreter.program();
}

```

lexer

parser

checker


inter-
preter

A *lexer* gets an ANTLR stream as input.

The *parser* gets the lexer's output tokens.

The recognition methods may all throw **Exceptions** (e.g. *RecognitionException*, *TokenStreamException*); These have to be caught in *main*-method. See *Calc.java*.

VB HC 4 ANTLR - Introduction 31



© Theo Ruys, Arend Rensink

Advantages ANTLR

- With ANTLR you can specify your compiler and let ANTLR do the hard work of generating the compiler.
But the generated Java code is similar to what you would write manually: it is possible (and easy!) to read and debug Java files generated by ANTLR.
- The syntax for specifying scanners, parsers and tree walkers is the same.
- ANTLR can generate recognizers for many programming languages (e.g. Java, C#, Python, (Objective) C, etc.)
- ANTLR is well supported and has an active user community.

VB HC 4 ANTLR - Introduction 33

© Theo Ruys, Arend Rensink

Some ANTLR Tips

- left associative
- right associative
- operator precedence
- dangling-else


Second lecture on ANTLR will discuss some more advanced ANTLR Tips and Techniques.

VB HC 4 ANTLR - Introduction 34

© Theo Ruys, Arend Rensink

Left associative

- Left associative operator \otimes :
 $a \otimes b \otimes c \equiv (a \otimes b) \otimes c$
- Production rule:
 $E ::= E \otimes T \mid T$
 which can be written (by eliminating left recursion) as
 $E ::= X Y$
 $X ::= T$
 $Y ::= \otimes T Y \mid \text{empty}$
- or using EBNF:
 $E ::= T (\otimes T)^*$




VB HC 4 ANTLR - Introduction 35

© Theo Ruys, Arend Rensink

Right associative

- Right associative operator \otimes :
 $a \otimes b \otimes c \equiv a \otimes (b \otimes c)$
- Production rule:
 $E ::= T \otimes E \mid T$
 which can be written (using left factorisation) as
 $E ::= T X$
 $X ::= \otimes E$
 $\mid \text{empty}$
- or using EBNF:
 $E ::= T (\otimes E)^?$



VB HC 4 ANTLR - Introduction 36

© Theo Ruys, Arend Rensink

Operator Precedence (1)

- Consider the following example
 $a + b * c - d$
- which should be parsed as
 $(a + (b * c)) - d$
- This means that the operator $*$ has **precedence** over the operators $+$ and $-$. This can be reflected in the grammar by making sure that $*$ is 'closer to the operands' than $+$ and $-$.

```

expr1 : expr2 ((PLUS^ | MINUS^) expr2)*
expr2 : operand (TIMES^ operand)*
operand : IDENTIFIER
  
```

VB HC 4 ANTLR - Introduction 37

© Theo Ruys, Arend Rensink

Operator Precedence (2)

$a + b * c - d$

```

expr1 : expr2 ((PLUS^ | MINUS^) expr2)*
expr2 : operand (TIMES^ operand)*
operand : IDENTIFIER
  
```

parse tree:

constructed AST:

VB HC 4 ANTLR - Introduction 38

© Theo Ruys, Arend Rensink

Greedy (1)

- Consider the classic if-then-else **ambiguity** (i.e., **dangling else**)

```

stat : 'if' expr 'then' stat ('else' stat)?
      | ... ;
  
```

e.g. `if b1 then if b2 then s1 else s2`

Two possible parse trees:

VB HC 4 ANTLR - Introduction 39

© Theo Ruys, Arend Rensink

Greedy (2)

- So this ambiguity (which statement should the "else" be attached to) results in a **parser nondeterminism**. ANTLR warns you:

```

warning(200): Foo.g:12:33: Decision can match input
such as "'else'" using multiple alternatives: 1, 2
As a result, alternative(s) 2 were disabled for that
input
  
```

- If you make it clear to ANTLR that you want the subrule to match **greedily**, ANTLR will not generate the warning.

```

stat : 'if' expr 'then' stat
      (options {greedy=true;} : 'else' stat)?
      | ... ;
  
```

VB HC 4 ANTLR - Introduction 40