

MR Image Synthesis BlochGAN

MIA

2021



Fat-saturated image generation from multi-contrast MRIs using generative adversarial networks with Bloch equation-based autoencoder regularization



Sewon Kim^a, Hanbyol Jang^a, Seokjun Hong^a, Yeong Sang Hong^{b,c}, Won C. Bae^{d,e},
Sungjun Kim^{b,c,**}, Dosik Hwang^{a,b,*}

^a School of Electrical and Electronic Engineering, Yonsei University, 50, Yonsei-ro, Seodaemun-gu, Seoul 03722, Republic of Korea

^b Center for Clinical Imaging Data Science Center, Research Institute of Radiological Science, Department of Radiology, Yonsei University College of Medicine, 50-1, Yonsei-ro, Seodaemun-gu, Seoul 03722, Republic of Korea

^c Department of Radiology, Gangnam Severance Hospital, 211, Eonju-ro, Gangnam-gu, Seoul 06273, Republic of Korea

^d Department of Radiology, Veterans Affairs San Diego Healthcare System, 3350 La Jolla Village Drive, San Diego, CA 92161-0114, USA

^e Department of Radiology, University of California-San Diego, La Jolla, CA 92093-0997, USA

ARTICLE INFO

Article history:

Received 15 December 2020

Revised 18 July 2021

Accepted 23 July 2021

Available online 30 July 2021

MSC:

41A05

41A10

65D05

65D17

Keywords:

Magnetic resonance image
Image synthesis

ABSTRACT

Obtaining multiple series of magnetic resonance (MR) images with different contrasts is useful for accurate diagnosis of human spinal conditions. However, this can be time consuming and a burden on both the patient and the hospital. We propose a Bloch equation-based autoencoder regularization generative adversarial network (BlochGAN) to generate a fat saturation T2-weighted (T2 FS) image from T1-weighted (T1-w) and T2-weighted (T2-w) images of human spine. To achieve this, our approach was to utilize the relationship between the contrasts using Bloch equation since it is a fundamental principle of MR physics and serves as a physical basis of each contrast. BlochGAN properly generated the target-contrast images using the autoencoder regularization based on the Bloch equation to identify the physical basis of the contrasts. BlochGAN consists of four sub-networks: an encoder, a decoder, a generator, and a discriminator. The encoder extracts features from the multi-contrast input images, and the generator creates target T2 FS images using the features extracted from the encoder. The discriminator assists network learning by providing adversarial loss, and the decoder reconstructs the input multi-contrast images and regularizes the learning process by providing reconstruction loss. The discriminator and the decoder are only used

MR Image Synthesis

BlochGAN

Background & Goal

▶ Background

- Because MRI has a relatively long scanning time per pulse sequence, acquiring FS images in addition to T1-w and T2-w images is burdensome for both patients and hospitals
- Existing deep learning-based models do not consider physical information (Bloch equation)

▶ Goal

- Aimed to acquire T2 FS images from T1-w and T2-w images
- BlochGAN applies Autoencoder Regularization based on the Bloch Equation to produce more physically consistent synthetic results

MR Image Synthesis

BlochGAN

Bloch Equation

- An equation that describes the process (time evolution) in which the magnetization of hydrogen nuclei (protons) returns to its original state when RF pulses are turned on and off.




Fig 1. Polarization & Excitation & Relaxation

$$S = S_0 \left(1 - \exp \left(-\frac{TR}{T_1} \right) \right) \exp \left(-\frac{TE}{T_2} \right)$$

Eq 1. Bloch equation representing the signal obtained by the spin echo pulse sequence

MR Image Synthesis BlochGAN

Network Architecture




Fig 2. Overall of BlochGAN

MR Image Synthesis

BlochGAN

Network Architecture

▶ Encoder

- Receives multi-contrast images as network inputs and extracts the features

▶ Decoder

- Generates MR parameter maps from the features of the encoder
- Restores synthetic input multi-contrast images with the Bloch equation functions

▶ Generator

- Receives features from the encoder and generates synthetic T2 FS images

▶ Discriminator

- Distinguishes images generated by the generator from the acquired T2 FS image

MR Image Synthesis

BlochGAN

Network Architecture

▶ Haar Wavelet Decomposition & Reconstruction

- Used as a down- and up-sampling layer, to preserve detail information
- Low frequency data generated from wavelet decomposition: delivered to the next layer as layer input
- High frequency: delivered to the decoder and the generator at the same resolution for wavelet reconstruction




Fig 3. Example of Haar Wavelet Decomposition

MR Image Synthesis

BlochGAN

Loss Functions

► Bloch equation-based generative adversarial network

- Receives multi-contrast images as network inputs and extracts the features
- Regularization help the encoder avoid overfitting and learn efficient feature extraction during training

$$\hat{y} = Ge(En(\mathbf{x}))$$

Eq 2. Synthetic T2 FS images

$$\mathcal{L}_{l1} = \frac{1}{w \times h} \sum_i^w \sum_j^h |y_{i,j} - Ge(En(\mathbf{x}))_{i,j}|,$$

$$\mathcal{L}_{vgg} = \frac{1}{n_k \times w_k \times h_k} \times \sum_c^{n_k} \sum_i^{w_k} \sum_j^{h_k} |VGG_k(y)_{c,i,j} - VGG_k(Ge(En(\mathbf{x})))_{c,i,j}|$$

Eq 3. Pixel-wise loss & Perceptual loss

$$\mathcal{L}_{adv} = \frac{1}{2} \mathbb{E}_{\mathbf{x}} [(D(\mathbf{x}, Ge(En(\mathbf{x}))) - 1)^2]$$

Eq 4. Adversarial loss of the BlochGAN

$$\mathcal{L}_R = \frac{1}{w \times h \times 2} \sum_i^w \sum_j^h \sum_k^2 |\mathbf{x}_{i,j,k} - B(De(En(\mathbf{x})))_{i,j,k}|$$

$$B(\mathbf{t}; \mathbf{TR}, \mathbf{TE}) = t_3 (1 - \exp^{-\frac{\mathbf{TR}}{t_1}}) \exp^{-\frac{\mathbf{TE}}{t_2}},$$

Eq 5. Regularization function used in BlochGAN

MR Image Synthesis BlochGAN

Results




Fig 4. Compared the synthetic T2 FS images generated by various methods




Fig 5. Quantitative Evaluation results of the proposed method and other methods

MR Image Synthesis BlochGAN

Ablation Study




Fig 6. Comparison between the generated T2 FS images by BlochGAN(NAE), BlochGAN(AE), BlochGAN




Fig 7. Images generated by BlochGAN(NW), BlochGAN

MR Image Synthesis

BlochGAN

Implications & Limitations

► Implications

- First attempt to train the network in medical image synthesis using a Bloch Equation

► Limitations

- Because of a hardware limitation, BlochGAN were carried out for 2D data, rather than 3D data
- BlochGAN still needs further validation to apply to more complex pulse sequences and diverse anatomies