

Image Style Transfer

NST

Definition

▶ Image-to-Image Translation

- Transformation between different domains.
- shared features : content, domain-specific features : style

▶ Style Transfer

- Preserving the content of an image while applying the style of a reference image.

▶ Recent Trend

- Both fields have evolved toward disentangling content and style for more flexible and controllable generation.



Image Style Transfer NST

CVPR

2016



This CVPR paper is the Open Access version, provided by the Computer Vision Foundation.
Except for this watermark, it is identical to the version available on IEEE Xplore.

Image Style Transfer Using Convolutional Neural Networks

Leon A. Gatys

Centre for Integrative Neuroscience, University of Tübingen, Germany
Bernstein Center for Computational Neuroscience, Tübingen, Germany
Graduate School of Neural Information Processing, University of Tübingen, Germany
leon.gatys@bethgelab.org

Alexander S. Ecker

Centre for Integrative Neuroscience, University of Tübingen, Germany
Bernstein Center for Computational Neuroscience, Tübingen, Germany
Max Planck Institute for Biological Cybernetics, Tübingen, Germany
Baylor College of Medicine, Houston, TX, USA

Matthias Bethge

Centre for Integrative Neuroscience, University of Tübingen, Germany
Bernstein Center for Computational Neuroscience, Tübingen, Germany
Max Planck Institute for Biological Cybernetics, Tübingen, Germany

Abstract

Rendering the semantic content of an image in different styles is a difficult image processing task. Arguably, a major limiting factor for previous approaches has been the lack of image representations that explicitly represent semantic information and, thus, allow to separate image content from style. Here we use image representations derived from Convolutional Neural Networks optimised for object recognition, which make high level image information explicit. We introduce A Neural Algorithm of Artistic Style that can sep-

there exist a large range of powerful non-parametric algorithms that can synthesise photorealistic natural textures by resampling the pixels of a given source texture [7, 30, 8, 20]. Most previous texture transfer algorithms rely on these non-parametric methods for texture synthesis while using different ways to preserve the structure of the target image. For instance, Efros and Freeman introduce a correspondence map that includes features of the target image such as image intensity to constrain the texture synthesis procedure [8]. Hertzman et al. use image analogies to transfer the texture from an already stylised image onto a target image[13].

Image Style Transfer NST

Background & Goal

▶ Previous research limitation

- Separate content from style in natural images is still a difficult problem

▶ Goal

- Separate the content and style of the image and apply a new style



Fig 1. Style transfer results

Image Style Transfer NST

Network Architecture

▶ VGG Network

- Basis of the 19 layers VGG network




Fig 2. VGG19 architecture

Image Style Transfer NST

Feature Representations





Fig 3. Image representations in a CNN

Image Style Transfer NST

Feature Representations



Content representations

- The higher layers (conv4_2) of a pre-trained VGG network capture high-level content that represents the semantic meaning of an image.

Fig 3. Image representations in a CNN

Image Style Transfer NST

Feature Representations




Fig 3. Image representations in a CNN

Style representations

- Style is the overall texture, color distribution, and pattern of the image.
- Expressed as a relationship between entire channels (features), not individual pixels
=> Gram matrix

$$\mathbf{F} \in \mathbb{R}^{C \times H \times W} \quad \mathbf{F}_{\text{flat}} \in \mathbb{R}^{C \times (H \times W)}$$


$$\mathbf{G} = \mathbf{F}_{\text{flat}} \mathbf{F}_{\text{flat}}^T \in \mathbb{R}^{C \times C}$$

$$G_{ij} = \sum_k F_{ik} F_{jk}$$

- Gram matrix calculates the correlations between various feature maps while disregarding spatial information

Image Style Transfer NST

Feature Representations




Style representations

- The lower layers (conv1_1) of a pre-trained VGG network capture fine-grained texture patterns and colors, while the higher layers (conv4_1, conv5_1) represent more abstract style properties such as global patterns.

Fig 3. Image representations in a CNN

Image Style Transfer NST

Loss Functions



Content loss

$$\mathcal{L}_{content}(\vec{p}, \vec{x}, l) = \frac{1}{2} \sum_{i,j} (F_{ij}^l - P_{ij}^l)^2$$


- \vec{p}, \vec{x} : Original & Generate image
- P^l, F^l : Feature representations in layer l
- $F_{i,j}^l$: Activation of the i^{th} filter at position j in layer l

Eq1. Content loss

Fig 4. Style transfer Algorithm

Image Style Transfer NST

Loss Functions



Style loss

$$E_L = \sum (G^L - A^L)^2 \quad G^l_{ij} = \sum_k F^l_{ik} F^l_{jk}$$

$$\mathcal{L}_{style}(\vec{a}, \vec{x}) = \sum_{l=0}^L w_l E_l$$

- \vec{a}, \vec{x}, w_l : Original, Generate image, weight factor
- A^l, G^l : Gram Matrix in layer l
- $G^l_{i,j}$: Inner between the vectorized feature maps

Eq2. Style loss

Fig 4. Style transfer Algorithm

Image Style Transfer NST

Loss Functions




Fig 4. Style transfer Algorithm

Transfer

- Perform gradient descent on a white noise image
- Synthesis a new image that simultaneously matches the content representation of \vec{p} and the style representation of \vec{a}

$$\mathcal{L}_{total}(\vec{p}, \vec{a}, \vec{x}) = \alpha \mathcal{L}_{content}(\vec{p}, \vec{x}) + \beta \mathcal{L}_{style}(\vec{a}, \vec{x})$$

Eq 3. Total loss function

Image Style Transfer NST

Experiment Results



Fig 5. Images that combine the content of a photograph with the style

Image Style Transfer

NST

Experiment Results

► Why are content and style entangled in the synthesized image?

- VGG Network was not originally trained by separating content and style.
- Content and style are mixed in the feature map extracted from VGG.
- Gram matrix captures texture and global statistics but is agnostic to spatial information.
- Interpret and utilize the features extracted by a pre-trained VGG network in a meaningful way.

Image Style Transfer

NST

Experiment Results

► Why are content and style entangled in the synthesized image?

- VGG Network was not originally trained by separating content and style.
- Content and style are mixed in the feature map extracted from VGG.
- Gram matrix captures texture and global statistics but is agnostic to spatial information.
- Interpret and utilize the features extracted by a pre-trained VGG network in a meaningful way.

► Recent Trend

- To better disentangle content and style
- Adaptive Instance Normalization (AdaIN) separate style information through normalization techniques.
- Disentangled representation learning, content and style are explicitly separated into different latent spaces.

Image Style Transfer NST

Additional Experiments

► Trade-off between content and style matching

- A linear combination between the loss functions for content and style
- Strong emphasis on style: produces a texturized version of the style image
- Strong emphasis on content: produces an image with only little stylization



$$\mathcal{L}_{\text{total}}(\vec{p}, \vec{a}, \vec{x}) = \alpha \mathcal{L}_{\text{content}}(\vec{p}, \vec{x}) + \beta \mathcal{L}_{\text{style}}(\vec{a}, \vec{x})$$



Fig 6. Images generated by α/β ratio

Image Style Transfer NST

Additional Experiments

► Effect of different layers



Fig 7. The effect of matching the content representation in different layers of the network.

Image Style Transfer NST

Additional Experiments

► Initialization of gradient descent



Fig 8. Results for initialization image

Image Style Transfer

NST

Implications & Limitations

► Implications

- To achieve style transfer between arbitrary images using feature representations extracted from Convolutional Neural Network

► Limitations

- Optimization-based approach => Not suitable for real-time processing
- Difficulty in separating content and style