

CSCE 629

Cyber Attack

Covering Tracks
and


Hiding



Dr. Barry Mullins
AFIT/ENG
Bldg 642
Room 209
255-3636 x7979


Computer and Network Hacker Exploits

- ❑ Step 1: Reconnaissance
- ❑ Step 2: Scanning
- ❑ Step 3: Gaining Access
 - ❖ Application and Operating System Attacks
 - ❖ Network Attacks
 - ❖ Denial of Service Attacks
- ❑ Step 4: Maintaining Access
- ❑ Step 5: Covering Tracks and Hiding
 - ❖ Altering Event Logs
 - ❖ Covert Channels




Attackers' Modus Operandi

- ❑ Some attackers want to draw attention to their cause
 - ❖ Defacing website
 - Attacker's presence is obvious immediately



Attackers' Modus Operandi

- ❑ Most attackers prefer more clandestine operations
- ❑ Prefer to maintain access for long period of time
- ❑ In order to hide the attacker's presence, the attacker
 - ❖ Installs rootkits 
 - ❖ Modifies logs to remove evidence of
 - Gaining access to the machine
 - Elevating privileges
 - Installing a rootkit
 - ❖ Creates hidden files
 - ❖ Establishes covert channels

Event Logs in Windows

- Windows event logs are stored in
 - ❖ Win XP → `C:\Windows\System32\Config`
 - `AppEvent.evt` - Application-oriented events
 - `SecEvent.evt` - Security events
 - `SysEvent.evt` - System events (readable by all users)
 - ❖ Win 7, 10 → `C:\Windows\System32\winevt\Logs`
 - `Application.evtx` - Application-oriented events
 - `Security.evtx` - Security events
 - `System.evtx` - System events (readable by all users)
- Files are stored as binary information and are not directly editable
 - ❖ Files are write-locked on a running Windows system

Viewing and Clearing Event Logs

The screenshot shows the Windows Computer Management console. In the left-hand tree view, the 'Event Viewer' icon under 'System Tools' is highlighted with a red rectangle. The main pane displays a list of security events. The first event is selected, and its details are shown in the bottom pane. The 'Actions' pane on the right also has the 'Clear Log...' option highlighted with a red rectangle.

Keywords	Date and Time	Source	Event ID	Task Category
Audit Succ...	2/18/2016 7:51:48 AM	Microsoft Windo...	4672	Special Logon
Audit Succ...	2/18/2016 7:51:48 AM	Microsoft Windo...	4624	Logon
Audit Succ...	2/18/2016 7:51:46 AM	Microsoft Windo...	4672	Special Logon
Audit Succ...	2/18/2016 7:51:46 AM	Microsoft Windo...	4624	Logon
Audit Succ...	2/18/2016 7:51:46 AM	Microsoft Windo...	4672	Special Logon
Audit Succ...	2/18/2016 7:51:46 AM	Microsoft Windo...	4624	Logon
Audit Succ...	2/18/2016 7:01:46 AM	Microsoft Windo...	4634	Logoff
Audit Succ...	2/18/2016 7:01:46 AM	Microsoft Windo...	4624	Logon
Audit Succ...	2/18/2016 7:01:46 AM	Microsoft Windo...	4672	Special Logon
Audit Succ...	2/18/2016 5:41:20 AM	Microsoft Windo...	4634	Logoff
Audit Succ...	2/18/2016 5:41:20 AM	Microsoft Windo...	4624	Logon
Audit Succ...	2/18/2016 5:41:20 AM	Microsoft Windo...	4672	Special Logon
Audit Succ...	2/18/2016 5:41:20 AM	Microsoft Windo...	4648	Logon
Audit Succ...	2/18/2016 5:11:48 AM	Microsoft Windo...	4634	Logoff
Audit Succ...	2/18/2016 5:11:48 AM	Microsoft Windo...	4624	Logon
Audit Succ...	2/18/2016 5:11:48 AM	Microsoft Windo...	4672	Special Logon
Audit Succ...	2/18/2016 5:11:48 AM	Microsoft Windo...	4648	Logon
Audit Succ...	2/18/2016 5:11:47 AM	Microsoft Windo...	4739	Authenticatio...

Event 4672, Microsoft Windows security auditing.

General Details

Special privileges assigned to new logon.

Subject:

Log Name: Security
Source: Microsoft Windows security
Event ID: 4672
Level: Information
Logged: 2/18/2016 7:51:48 AM
Task Category: Special Logon
Keywords: Audit Success

Actions

Security

Open Saved Log...
Create Custom View...
Import Custom View...
Clear Log...
Filter Current Log...
Properties
Find...
Save All Events As...
Attach a Task To this L...
View
Refresh
Help
Event 4672, Microsoft Wind...
Event Properties
Attach Task To This Eve...
Copy
Save Selected Events...
Refresh
Help

"Attacking" Event Logs Windows 7-10

- ❑ Attacker with admin privileges can "clear" the log files

```
C:\>wevtutil cl security
```

Computer Management Before					
File Action View Help					
Computer Management (Local)					
System Tools					
Task Scheduler					
Event Viewer					
Custom Views					
Windows Logs					
Application					
Security					
Setup					
System					
Forwarded Event					
Applications and Se					
Subscriptions					
Shared Folders					
Local Users and Groups					
Performance					
Keywords	Date and Time	Source	Event ID	Task Category	
Audit Succ...	2/18/2016 7:51:48 AM	Microsoft Windo...	4672	Special Logon	
Audit Succ...	2/18/2016 7:51:48 AM	Microsoft Windo...	4624	Logon	
Audit Succ...	2/18/2016 7:51:46 AM	Microsoft Windo...	4672	Special Logon	
Audit Succ...	2/18/2016 7:51:46 AM	Microsoft Windo...	4624	Logon	
Audit Succ...	2/18/2016 7:51:46 AM	Microsoft Windo...	4672	Special Logon	
Audit Succ...	2/18/2016 7:51:46 AM	Microsoft Windo...	4624	Logon	
Audit Succ...	2/18/2016 7:01:46 AM	Microsoft Windo...	4634	Logoff	
Audit Succ...	2/18/2016 7:01:46 AM	Microsoft Windo...	4624	Logon	
Audit Succ...	2/18/2016 7:01:46 AM	Microsoft Windo...	4672	Special Logon	
Audit Succ...	2/18/2016 5:41:20 AM	Microsoft Windo...	4634	Logoff	
Audit Succ...	2/18/2016 5:41:20 AM	Microsoft Windo...	4624	Logon	
Audit Succ...	2/18/2016 5:41:20 AM	Microsoft Windo...	4672	Special Logon	
Audit Succ...	2/18/2016 5:41:20 AM	Microsoft Windo...	4648	Logon	
Audit Succ...	2/18/2016 5:11:48 AM	Microsoft Windo...	4634	Logoff	

"Attacking" Event Logs Windows 7-10

- ❑ Attacker with admin privileges can "clear" the log files

```
C:\>wevtutil cl security
```

Computer Management **After**

File Action View Help

Computer Management (Local)

- System Tools
 - Task Scheduler
 - Event Viewer
 - Custom Views
 - Windows Logs
 - Application
 - Security
 - Setup
 - System
 - Forwarded Events
 - Applications and Services Logs
 - Subscriptions
 - Shared Folders
 - Local Users and Groups
 - Performance
 - Device Manager
 - Storage
 - Disk Management
 - Services and Applications

Keywords	Date and Time	Source	Event ID	Task Category
Audit Succ...	2/18/2016 8:15:41 AM	Eventlog	1102	Log clear

"Attacking" Event Logs Pre-Windows 7

- ❑ Clears the event log (Security, System or Application)
 - ❖ Windows NT 4.0 / 2000 / XP / 2003 / Vista
- ❑ Can also clear logs on a remote computer
- ❑ ntsecurity.nu/toolbox/clearlogs/

```
ClearLogs 1.0 - (c) 2002, Arne Vidstrom (arne.vidstrom@ntsecurity.nu)
               - http://ntsecurity.nu/toolbox/clearlogs/

Usage: clearlogs [\\computername] [-app / -sec / -sys]

       -app = application log
       -sec = security log
       -sys = system log


C:\Documents and Settings\bmullins\My Documents>clearlogs -sys

ClearLogs 1.0 - (c) 2002, Arne Vidstrom (arne.vidstrom@ntsecurity.nu)
               - http://ntsecurity.nu/toolbox/clearlogs/


Success: The log has been cleared

C:\Documents and Settings\bmullins\My Documents>
```

Before Running clearlogs -sys



After Running `clearlogs -sys`



Linux/Unix System Logs - ASCII



- ❑ **Locations** of main log file in `/etc/rsyslog.conf`
 - ❖ `/var/log/auth.log` → Authentication logs
 - ❖ `/var/log/messages` → boot messages / system messages
- ❑ Service logs
 - ❖ `/var/log/httpd/error_log`
 - ❖ `/var/log/httpd/access_log`
- ❑ Log files usually in ASCII
 - ❖ Edit using text editor
 - ❖ Use Perl or Python script if file is large

Accounting Files in Linux/Unix - Binary

- ❑ `utmp`: Currently logged in users `/var/run/utmp`
- ❑ `wtmp`: Past user logins `/var/log/wtmp`
- ❑ `lastlog`: Login name, port and last login time for each user
 - ❖ `/var/log/lastlog`
- ❑ Can only be edited using specialized tools:
 - ❖ `Last Door Log Wiper`
 - Wipes specific entries in arbitrary log files
 - If root, will also execute arbitrary commands without logging
 - ❖ `remove`
 - Changes last login time, location, and status by editing `lastlog`
 - Removes entries from `utmp`, `wtmp`, and `lastlog`
 - ❖ Numerous others including `RopeADope`, `Linux Log Eraser`, `wtmped`, `marry`, `cloak`, `logwedit`, `zapper`
 - ❖ www.packetstormsecurity.org/UNIX/penetration/log-wipers

Don't Forget Linux Shell History

- ❑ List of the most recent N commands stored in `~/.bash_history`
 - ❖ N=500 by default in bash
 - ❖ Written in ASCII and can be edited by hand with permissions of the user or root
- ❑ Attackers also delete or edit their shell history files
 - ❖ Attackers remove suspicious commands
 - ❖ Some even add commands to implicate some other user in the attack (divert attention)



Editing Shell History - A Problem

- ❑ Shell history is written when the shell is exited
- ❑ When editing shell history, the command used to invoke the editor is placed in the shell history file
- ❑ Attacker could edit the file, exit the shell, start another shell, edit the history file again to remove it...
 - ❖ ... but it will be added again!
 - ❖ Chicken and egg problem
- ❑ Solutions
 - ❖ 1) Kill the shell, so that it cannot write the most recent shell history, including the command used to edit it
 - # `kill -9 [pid_of_the_shell_process]`
 - ❖ 2) Change environment variable HISTSIZE (for bash) to zero
 - # `export HISTSIZE=0`

Creating Hidden Files and Directories in Unix

□ Easiest (and effective) way to hide files is to simply name them something like ". " or ".. "

❖ There's a space after those periods

□ Name a file "... " or even " " (That's a space!)

□ Could also append a period "." to the beginning of the filename

❖ These files are not displayed by the `ls` command

❖ `ls -a` will display all files

□ For example:

```
# ls
```

```
test.txt  files
```

```
# ls -a
```

```
.  ..  .mystuff
```

```
test.txt  files
```

```
# echo hideme > ".. "
```

```
# ls -a
```

```
.  ..  ..  .mystuff  test.txt  files
```

```
[root@lislx421jlt ~]# echo hello > ". "
```

```
[root@lislx421jlt ~]# ls -al
```

```
total 5036
```

```
drwxr-x--- 33 root root 4096 2008-02-28 13:28 .
```

```
-rw-r--r--  1 root root    6 2008-02-28 13:28 .
```



```
drwxr-xr-x 23 root root 4096 2008-02-22 11:49 ..
```

```
-rw-----  1 root root 1175 2007-08-28 14:30 anaconda
```


File

File

Creating Hidden Files in Windows



Hiding Files Behind Other Files

- ❑ Can append two or more files together
- ❑ `copy /b cover.jpg + secret.txt hidden.jpg`
- ❑ Appends `secret.txt` to the end of `cover.jpg` and names the new file `hidden.jpg`
- ❑  Can view `hidden.jpg` in an image viewer but if you open `hidden.jpg` in a text editor (e.g., notepad or notepad++) you will see the contents of `secret.txt` at the end


Hiding Files in NTFS Alternate Data Streams (ADS)

- Attacker's files can be hidden in a stream behind normal files or directories on the system
 - ❖ Such as .txt files, notepad.exe or word.exe (or anything else!)
- If system is running NTFS (New Technology File System), ADS is supported
 - ❖ ADS created to provide compatibility with the Macintosh Hierarchical File System which stored files in two parts—data and resource (how to use the data part)

Hiding Files in NTFS

Alternate Data Streams (ADS)

- ❑ Multiple streams can be attached to each file or directory



Hiding Files in NTFS Alternate Data Streams (ADS)

- Legit uses of ADS
 - ❖ Metadata about file
 - ❖ Encryption information
 - ❖ Backup, maintenance, information on files and directories
 - ❖ Extended information about file activity
 - ❖ IE, Edge, Chrome and other browsers will add an ADS named Zone.Identifier to a file downloaded with info about the source
 - Some browsers even add other details about the file downloaded like source and referrer URLs

Hiding Files in NTFS

- ❑ Use the type command built into Windows

```
type stuff.txt > notepad.exe:anyfile.txt
```

- ❑ Pull file from stream and print to screen

```
more < notepad.exe:anyfile.txt
```

- ❑ Can also save to file

```
more < notepad.exe:anyfile.txt > newfile.txt
```

- ❑ Can even execute an ADS (Windows XP)

```
type evil.exe > good.txt:evil.exe
```

```
start .\good.txt:evil.exe
```

Example: Hiding Video Files in NTFS

```
G:\ADS>echo This is a visible file > visible.txt
```

```
G:\ADS>dir
```

```
Volume in drive G is Data
```

```
Volume Serial Number is 70F4-AF07
```

```
Directory of G:\ADS
```

```
09/10/2018  09:59 AM    <DIR>          .
09/10/2018  09:59 AM    <DIR>          ..
05/27/2015  08:23 AM                313,064 hidden.mp4
09/10/2018  09:59 AM                25 visible.txt
           2 File(s)                313,089 bytes
           2 Dir(s)  1,288,046,288,896 bytes free
```

Example: Hiding Video Files in NTFS

```
G:\ADS>type hidden.mp4 > visible.txt:hidden.mp4
```


```
G:\ADS>dir /r
Volume in drive G is Data
Volume Serial Number is 70F4-AF07
```

Directory of G:\ADS

```
09/10/2018  09:59 AM    <DIR>          .
09/10/2018  09:59 AM    <DIR>          ..
05/27/2015  08:23 AM                313,064 hidden.mp4
                                26 hidden.mp4:Zone.Identifier:$DATA
09/10/2018  10:00 AM                25 visible.txt
                                313,064 visible.txt:hidden.mp4:$DATA
                2 File(s)          313,089 bytes
                2 Dir(s)  1,288,046,104,576 bytes free
```

As of Vista, `dir /r` will display (not delete) ADSs


```
G:\ADS>"c:\Program Files (x86)\Windows Media Player\wmplayer.exe" g:\ads\visible.txt:hidden.mp4
```



Can even play the hidden video


Alternate Data Streams in NTFS

- The hidden file in the stream will follow the other file around through normal copying between **NTFS** partitions
- Most, if not all, Internet protocols do **NOT** support ADS
 - ❖ The stream is removed during the copy



Tools To Detect And Remove Streams

- ❑ LADS (List ADS) - command line - scans entire drive or given directory and lists the names and size of all ADSs it finds
- ❑ ADS Scanner 2 - www.pointstone.com/products/ADS-Scanner/



Computer and Network Hacker Exploits

- ❑ Step 1: Reconnaissance
- ❑ Step 2: Scanning
- ❑ Step 3: Gaining Access
 - ❖ Application and Operating System Attacks
 - ❖ Network Attacks
 - ❖ Denial of Service Attacks
- ❑ Step 4: Maintaining Access
- ❑ Step 5: Covering Tracks and Hiding
 - ❖ Altering Event Logs
 - ❖ Covert Channels



Covert Channels - It Can Be Quite Easy

- ❑ Terrorist Bob purposely corrupts a file signature (magic numbers)
- ❑ Sends to terrorist Chuck who reverses the process
- ❑ Anyone intercepting the file will see it is corrupt and disregard



Bob



Chuck


Tunneling and Covert Channels

- ❑ Attackers need a way to communicate with their evil programs
- ❑ You can carry any protocol on top of any other protocol
 - ❖ First protocol is encapsulated inside packets of second protocol
 - Network only sees second “outer” protocol
 - FTP over SSH
 - IP inside of IP
 - VPNs




Tunneling and Covert Channels

- ❑ Covert channels require
 - ❖ Server on the victim machine
 - ❖ Client on the attacker's machine
- ❑ Attacker wants to hide the fact that he is moving data or issuing commands to the victim



Covert Channels Using ICMP: Loki

- ❑ Pronounced "Low Key" - and it's covert... Get it?
- ❑ Tunnels shell sessions over innocuous-looking protocols
 - ❖ ICMP (looks like ping)
 - ❖ UDP port 53 (looks like DNS queries and responses)
- ❑ Think of it as a telnet over ICMP (ping)
- ❑ Offers a command shell on the victim machine to attacker




Covert Channels Using ICMP: Loki

- ❑ Can also encrypt traffic
- ❑ Code at www.phrack.org/issues.html?issue=51&id=6
- ❑ Very effective for covert sessions
 - ❖ ICMP messages do not require an open port
 - ❖ Only trace of the Loki daemon is a root-level process and ICMP packets going back and forth
 - ❖ What if ICMP is blocked...



Covert Channels Using HTTP: Reverse WWW Shell

- ❑ Get a command shell on a machine behind a firewall
- ❑ Requires the attacker to place a server on an internal host



Covert Channels Using HTTP: Reverse WWW Shell


- ❑ At certain time intervals (e.g., 60 sec), the server "surfs" out to pick up commands
- ❑ Looks like an HTTP "GET" going out to the Internet
- ❑ Shell runs on internal host with input from external system!
- ❑ Attacker has to wait the 60 seconds before command is executed
 - ❖ Attacker could shorten this interval but not too short
 - Shorter intervals may be noticed as something suspicious
- ❑ freeworld.thc.org/releases.php

Covert Channels Using TCP/IP Headers


- ❑ Creates a covert channel using **unused fields** in TCP or IP header
- ❑ Covert_TCP is a Linux tool that implements a covert channel using either the TCP or IP header
- ❑ Designed to transfer ASCII files in
 - ❖ IP Identification field
 - ❖ TCP Sequence Number field
 - ❖ TCP Acknowledgement Number field
- ❑ Client and server are the same executable
 - ❖ Client sets up TCP connection and sends packets (no payload)
- ❑ Sends one byte per packet
- ❑ https://github.com/cudeso/security-tools/blob/master/networktools/covert/covert_tcp.c

Covert_TCP Modes

□ IP ID Mode




□ TCP Seq # Mode



Covert TCP Bounce Mode

- TCP Ack Mode (also known as "bounce" mode)
 - ❖ ISN_A needs to be one less than ASCII char to be transmitted
 - Send "L" (0x4C) if you want the server to recv "M" (0x4D)




Passive Covert Channels

- ❑ Most covert channels generate their own packets hiding the data inside those packets
 - ❖ Covert_TCP, Loki, ICMP tunnel, etc.
- ❑ Passive covert channels use **existing** packets inserting their data inside
- ❑ Technique implemented in Nushu
 - ❖ Named after a secret language created by Chinese women centuries ago
 - ❖ Characters disguised as decorative marks or as part of artwork




Passive Covert Channels in Action


- ❑ Send data inside of SYN packets by tweaking ISNa to include data
- ❑ Strip data off while its on its way to destination using a gateway controlled by the attacker and running Nushu server
- ❑ Works on Linux



Substituting ISNA




Dealing with ACKs



Nushu - Data Format

- Format for the **initial sequence number (ISN)** in the SYN packet
 - ❖ Can only carry 3 bytes per **new** TCP connection
 - ❖ Still a “reasonable” data channel if someone is surfing the web
- Interesting anomaly
 - ❖ Local tcpdump of packets have different sequence numbers than network-sniffed packets!



of actual data bytes sent in this packet:
00: no data (control packet)
01: b0 is valid
10: b0 & b1 are valid
11: b0, b1 & b2 are valid

Covert Channels Using Steganography

- **Steganography**
 - ❖ From the Greek word *steganos* meaning "covered"
 - ❖ the Greek word *graphie* meaning "writing"
- Steganography is the process of hiding a secret message within an ordinary message and extracting it at its destination
- Although information can be hidden in almost any type of file, multimedia files are the most common carriers
- Digital images are good candidates for carriers
 - ❖ Commonly used -- not suspicious
 - ❖ Easily transported
 - ❖ Compression errors (noise) can mask errors introduced by payload
 - ❖ Anyone else viewing or listening to the file will fail to know it contains hidden/encrypted data

Steganography Uses

- Legitimate uses
 - ❖ Watermarking for copyright protection
 - ❖ Tagging images

- Illegitimate uses
 - ❖ Espionage
 - ❖ Concealing evidence
 - ❖ Covert communication

Accused Russian spies in N.J. used high-tech art of steganography to write, pass messages



By [Steve Strunsky](#) | NJ Advance Media for NJ.com

[Email the author](#) | [Follow on Twitter](#)

on June 28, 2010 at 9:35 PM, updated June 28, 2010 at 9:36 PM

Print

Email

MOST READ

http://www.nj.com/news/index.ssf/2010/06/accused_russian_spies_in_nj_us.html

Steganography Example

- Picture of the cat is embedded in the picture of the tree
 - ❖ Do you see the cat in the tree?



Steganography vs. Cryptography

- ❑ Crypto - Observer can see there is a message but cannot read it
- ❑ Stego - Observer doesn't even know the message exists
- ❑ **Steganography** deals with the concealment of a message, not the encryption of it
- ❑ **Steganalysis** → Identifying the **existence** of a hidden message
 - ❖ Not extracting the message

Steganography - Hiding Techniques

- ❑ Append information to a file
- ❑ Hide in unused portions of file header (PE header) or Code Cave
- ❑ Disperse hidden message/file throughout the file using algorithm
 - ❖ Modification of LSB (Least Significant Bit)
 - ❖ Many other techniques!
- ❑ Can be as simple as un-cropping a image



StegHide - One Tool... of many

- ❑ Supports (JPG, BMP, WAV, AU)
 - ❖ Linux (Kali: `apt install steghide`) or Windows XP
 - ❖ steghide.sourceforge.net/index.php

carrier_image.jpg



secret.txt



Steganography - StegHide Embedding

```
# steghide embed -cf carrier-image.jpg -ef secret.txt  
-sf stegofile.jpg
```

Enter passphrase:

Re-Enter passphrase:

```
embedding "secret.txt" in "carrier-image.jpg"... done  
writing stego file "stegofile.jpg"... done
```

carrier_image.jpg



secret.txt



Steganography - StegHide Detecting

```
# steghide info stegofile.jpg
```

```
"stegofile.jpg":
```

```
  format: jpeg
```

```
  capacity: 1.9 KB
```

```
Try to get information about embedded data ? (y/n) 
```



```
Enter passphrase:
```

```
  embedded file "secret.txt":
```

```
    size: 23.0 Byte
```

```
    encrypted: rijndael-128, cbc
```

```
    compressed: yes
```

Steganography - StegHide Extracting

```
# steghide extract -xf out.txt -sf stegofile.jpg
```

```
Enter passphrase:
```

```
wrote extracted data to "out.txt".
```