

# Malware Analysis and Threat Intelligence Report – Oski Stealer Lab

Analyst Name: Mduduzi William Radebe  
Role: SOC Analyst Tier 1 (Practice Lab)  
Date: 01 February 2026  
Platform: CyberDefenders – Oski Lab  
Tools Used: VirusTotal, ANY.RUN (public report)

## 1. Executive Summary

This report documents the analysis of a suspected malware incident involving a malicious PowerPoint (PPT) file identified within a corporate environment. The investigation was conducted as part of a SOC Analyst Tier 1 practice lab on CyberDefenders.

The objective of the investigation was to analyze sandbox intelligence and threat behavior to determine how the malware operated, identify its command and control infrastructure, understand its credential theft mechanisms, and map its behavior to the MITRE ATT&CK framework.

The malware analyzed was identified as **Oski Stealer**, an information-stealing malware designed to collect credentials and sensitive user data, exfiltrate the data to a remote server, and then remove itself to evade detection.

## 2. Incident Scenario Overview

An accountant received an email titled “Urgent New Order” containing an attached invoice in PowerPoint format. Upon opening the attachment, false order information was displayed. Shortly afterward, the company’s SIEM generated an alert indicating the download of a potentially malicious file.

Initial investigation suggested that the PPT file was responsible for triggering malicious activity. Network and sandbox analysis were initiated to determine the scope and behavior of the threat.

## 3. Scope and Objectives

The objectives of this investigation were to:

- Determine the malware creation time
- Identify the Command and Control (C2) server
- Analyze post-infection behavior
- Identify credential theft techniques
- Extract encryption configuration details
- Identify self-deletion and defense evasion behavior
- Map malware behavior to MITRE ATT&CK tactics and techniques

## **4. Tools and Methodology**

### **4.1 Tools Used**

VirusTotal

Used to analyze malware behavior, contacted URLs, HTTP requests, and execution behavior when direct sandbox access was unavailable.

ANY.RUN (Public Report)

Used to analyze runtime behavior, configuration data, child processes, MITRE ATT&CK mappings, and malware execution flow.

### **4.2 Methodology (Beginner SOC Analyst Approach)**

As a beginner SOC Analyst Tier 1, the investigation followed a structured and repeatable methodology:

1. Understand the incident context and alert
2. Review sandbox behavior reports
3. Identify indicators of compromise (IOCs)
4. Analyze network communication and downloaded files
5. Examine execution and child processes
6. Map observed behavior to MITRE ATT&CK
7. Document findings clearly and objectively

This approach mirrors real-world SOC triage and investigation workflows.

## **5. Detailed Analysis and Findings**

### **Q1. Malware Creation Time**

Method:

The malware creation timestamp was identified by reviewing the file metadata and sandbox analysis provided in VirusTotal and ANY.RUN reports.

Finding:

The malware creation time was identified from the sandbox metadata associated with the sample.

Conclusion:

The creation time provides insight into the malware's origin and helps determine whether it is part of a recent campaign or reused payload.

## Q2. Command and Control (C2) Server

Method:

Using VirusTotal, the "Relations" and "Behavior" sections were reviewed, focusing on contacted URLs and HTTP requests made by the malware.

Finding:

The malware communicated with the following IP address:

171.22.28.221

This IP was observed serving malicious payloads and acting as the Command and Control server.

Conclusion:

The identified IP represents the attacker-controlled infrastructure used to manage infected systems and receive stolen data.

## Q3. First Library Requested Post-Infection

Method:

The VirusTotal Behavior tab was examined under HTTP Requests to identify the first file downloaded after execution.

Finding:

The malware issued the following HTTP request:

GET <http://171.22.28.221/9e226a84ec50246d/sqlite3.dll>

Conclusion:

The first library requested post-infection was **sqlite3.dll**, which is commonly used by stealers to store harvested credentials and browser data locally before exfiltration.

#### **Q4. RC4 Key Used for Decryption**

Method:

Since a private ANY.RUN account was unavailable, a public ANY.RUN report was reviewed. The malware configuration section was examined for encryption details.

Finding:

The RC4 key used to decrypt base64-encoded strings was:

5329514621441247975720749009

Conclusion:

This key is used by the malware to decrypt embedded configuration data and evade static analysis.

#### **Q5. MITRE ATT&CK Technique for Password Theft**

Method:

The MITRE ATT&CK section of the ANY.RUN report was reviewed, focusing on credential access techniques.

Finding:

The primary MITRE ATT&CK technique used for password theft is:

T1555 – Credentials from Password Stores

Mapped Tactic:

Credential Access

Conclusion:

The malware targets stored credentials from browsers and system password stores to steal user authentication data.

#### **Q6. Directory Targeted for DLL Deletion**

Method:

Child processes in the ANY.RUN report were analyzed, specifically command-line execution via cmd.exe.

Observed Command:

"C:\Windows\System32\cmd.exe" /c timeout /t 5 & del /f /q

"C:\Users\admin\AppData\Local\Temp\VPN.exe" & del "C:\ProgramData\*.dll" & exit

Finding:

The malware deletes all DLL files located in:

C:\ProgramData\

Conclusion:

Deleting DLLs in this directory disrupts security tools and system stability, contributing to defense evasion.

## **Q7. Time Before Malware Self-Deletion**

Method:

The command-line execution was reviewed for delay mechanisms.

Observed Command:

timeout /t 5

Finding:

The malware waits 5 seconds before deleting itself.

Conclusion:

The malware self-deletes 5 seconds after completing data exfiltration, indicating anti-forensic behavior.

## **6. MITRE ATT&CK Mapping Summary**

Initial Access

Execution

Defense Evasion

Credential Access

Command and Control

Exfiltration

Primary Techniques Observed:

- T1555 Credentials from Password Stores
- Command-line execution via cmd.exe
- Network-based C2 communication
- Self-deletion and artifact removal

## **7. Indicators of Compromise (IOCs)**

IP Address:

171.22.28.221

Downloaded File:  
sqlite3.dll

Malware Executable:  
VPN.exe

Targeted Directory:  
C:\ProgramData\

## 8. Impact Assessment

The malware was capable of:

- Stealing stored credentials
- Communicating with an external C2 server
- Exfiltrating sensitive data
- Deleting forensic artifacts
- Evading detection through delayed execution and self-removal

If left undetected, this threat could result in credential compromise, data loss, and lateral movement within the network.

## 9. Mitigation and Recommendations

Immediate Actions:

- Block the C2 IP address at firewall and proxy levels
- Isolate affected endpoints
- Reset compromised credentials
- Scan systems for residual artifacts

Preventive Measures:

- Implement email attachment filtering
- Disable macros in Office documents
- Enforce endpoint detection and response (EDR)
- Monitor outbound network traffic
- Conduct user awareness training

## 10. Conclusion

This investigation successfully identified and analyzed an Oski Stealer malware infection using sandbox intelligence and threat analysis tools. The findings demonstrate a complete malware lifecycle including initial execution, credential theft, command and control communication, data exfiltration, and defense evasion.

This lab reflects the responsibilities and analytical workflow expected of a SOC Analyst Tier 1 and serves as practical proof of hands-on incident analysis capability.

## Screenshots

Network Communication

HTTP Requests

+

GET http://171.22.28.221/9e226a84ec50246d/sqlite3.dll 200

+

POST http://171.22.28.221/5c06c05b7b34e8e6.php

+

GET http://171.22.28.221/9e226a84ec50246d/sqlite3.dll

Basic properties

MD5

I2c1842c3ccafe7408c23abf292ee3d9

SHA-1

4b1a84cc11a8b1e290a18a4222a49526eeadd10

SHA-256

a040a0af8697e30506218103074c7d6ea77a84ba3ac1ee5efae20f15630a19bb

Vhash

0350365d15101523007cenz1fz

Authentihash

64232d71f5775257fc17860be8a2c063382d6a06a7ba20b86f017e425ed37cc1

Imphash

915313f9ba3d4f8e9e467fb8242a50c

Rich PE header hash

047f7fa4d51f65c29f5c9cb30b066cb

SSDEEP

6144:sMHkITkt3eaAuvuOosMVhCHCEs2qwVZKmATfrdHcn5IoT MperwCC5EQrZHK

TLSH

T13D647E4393F17C60E5364B329E2EC2E8761EF5604E59776A2329BA2F08B05F2D673711

File type

Win32 EXE executable windows win32 pe peexe

Magjc

PE32 executable (GUI) Intel 80386, for MS Windows

TrID

Win32 Executable MS Visual C++ (generic) (52.5%) Win64 Executable (generic) (17.7%) Win16 NE executable (generic) (8.4%) Win32 Executable (generic) (7.5%) ...

DetectItEasy

PE32 Compiler: EP:Microsoft Visual C/C++ (2008-2010) [EXE32] Compiler: Microsoft Visual C/C++ (16.00.30319) [LTCG/C++] Linker: Microsoft Linker (10.00.30319)...

Magika

PEBIN

File size

311.50 KB (318976 bytes)

History

Creation Time

2022-09-28 17:40:46 UTC

First Seen In The Wild

2023-09-23 22:33:33 UTC

First Submission

2023-09-23 22:02:55 UTC

Last Submission

2025-09-29 02:35:54 UTC

Last Analysis


2026-01-28 17:47:27 UTC

Contacted URLs (2)

Scanned	Detections	Status	URL
2026-01-26	11 / 94	-	http://171.22.28.221/5c06c05b7b34e8e6.php
2025-06-23	11 / 97	-	http://171.22.28.221/9e226a84ec50246d/sqlite3.dll






Contacted Domains (5)

Domain	Detections	Contacted	Registration
--------	------------	-----------	--------------





**VPN.exe**  
MD5: 12C1842C3C3CAFE7408C23EBF292EE3D9  
Start: 24.09.2023, 01:17    Total time: 60 s  
stealc stealer loader oski


Win7 32bit


Indicators:      

Tracker: [Loader](#), [Stealc](#), [Stealer](#)

 Get sample

 IOC


 MalConf

 Restart

Text report

Graph

ATT&CK

 Tools ▾

Export ▾






CPU

RAM

Processes 3    Actions 0    beta

Filter by PID or name Only important

3484 VPN.exe PE CFG DMP

      stealc 28k 2k 303

2780 cmd.exe /c timeout /t 5 & del /f /q "C:\Users\admin\AppData\Local\Temp\VPN.exe" & del "C:\ProgramData\\*.dll" & exit

Process details ID 3484 Malicious

**Danger 9**

T1070.004 File Deletion (1)

- Starts CMD.EXE for self-deleting

Loads dropped or rewritten executable

T1555.003 Credentials from Web Browsers (1)

- Steals credentials from Web Browsers

T1552.001 Credentials In Files (3)






- Steals credentials from Web Browsers
- Steals credentials
- Actions looks like stealing of personal data

STEAL C detected by memory dumps

Processes 3    Actions 0    beta

Filter by PID or name Only important

3484 VPN.exe PE CFG DMP

      stealc 28k 2k 303

2780 cmd.exe /c timeout /t 5 & del /f /q "C:\Users\admin\AppData\Local\Temp\VPN.exe" & del "C:\ProgramData\\*.dll" & exit

Process details ID 2780 No verdict

cmd.exe AI

6.1.7601.17514 (win7sp1\_rtm.101119-1850)  
Windows Command Processor

Username: admin

Start: +29031ms

Command line AI

'C:\Windows\system32\cmd.exe' /c timeout /t 5 & del /f /q "C:\Users\admin\AppData\Local\Temp\VPN.exe" & del "C:\ProgramData\\*.dll" & exit

More Info

Hide all

**Warning 1**

T1059.003 Windows Command Shell (1)

- Uses TIMEOUT.EXE to delay execution



Malware configuration

☒ Add for printing

▲

Stealc

(PID) Process	(3484) VPN.exe
C2	http://171.22.28.221/5c06c05b7b34e8e6.php
Keys	▼
RC4	5329514621441247975720749009
Strings (298)	▼
	" & del "C:\ProgramData\*.dll" & exit
	%08X%04IX%lu
	%APPDATA%
	%DESKTOP%
	%DOCUMENTS%
	%LOCALAPPDATA%
	%PROGRAMFILES%