

Action Archive

for BigFix Platform

Installation Guide

Version	1.1.4
Document Revision	May 18, 2026
Archive Server	Ubuntu Server 22.04 / 24.04 LTS
Audit Agent	BigFix Root Server (Windows)
Author	Mike Consuegra

Legal Notices and Trademarks

Third-Party Trademarks and Proprietary Rights

This document references products, product names, brand names, and trademarks that are the property of their respective owners. References are made solely for descriptive and identification purposes, to accurately describe the systems and environments with which Action Archive for BigFix Platform is designed to operate. No sponsorship, affiliation, endorsement, or approval by any third-party trademark holder is implied or should be inferred.

Product / Mark	Owner	Nature of Reference in This Document
HCL BigFix®, BigFix®, BigFix Platform™	HCLSoftware	Action Archive is designed to integrate with HCL BigFix via its published REST API and Session Relevance interface. All references to BigFix, BigFix Platform, and related product names are made solely to identify the platform with which this software operates. No claim of ownership, partnership, or endorsement by HCL Software is made or implied.
IBM®	International Business Machines Corporation	Any references to IBM pertain to the historical evolution of the BigFix platform while owned by IBM and do not imply any current relationship with IBM.
PostgreSQL®	The PostgreSQL Global Development Group	PostgreSQL is an open-source relational database management system. No affiliation with or endorsement by the PostgreSQL Global Development Group is implied.
Ubuntu®, Canonical®	Canonical Ltd.	Referenced as the operating system platform on which Action Archive is deployed. No affiliation with or endorsement by Canonical Ltd. is implied.
Nginx™	F5, Inc.	Referenced as the reverse proxy component in the Action Archive deployment architecture. No affiliation with or endorsement by F5, Inc. is implied.
Python™	Python Software Foundation	Referenced as the programming language and runtime used to build the Action Archive application. No affiliation with or endorsement by the Python Software Foundation is implied.
Windows®, Microsoft®	Microsoft Corporation	Referenced in the context of the Audit Agent component, which runs as a Windows Scheduled Task on the BigFix Root Server host. No affiliation with or endorsement by Microsoft Corporation is implied.

General Disclaimer

All trademarks, registered trademarks, service marks, and product names referenced in this document are the property of their respective owners and are used herein for identification purposes only. The use of any such mark does not imply any relationship between the author of this document or the Action Archive software and the holder of the respective mark, nor does it constitute an endorsement of this document or software by any trademark holder.

Action Archive for BigFix Platform is an independent tool and is not an official product of HCLSoftware, IBM, or any other third party named in this document. It is not affiliated with, certified by, or supported by HCLSoftware or any other referenced vendor. Use of HCL BigFix requires a valid license from HCLSoftware, obtained independently of this software.

® indicates a registered trademark. ™ indicates a trademark. All other product names and company names mentioned in this document may be trademarks or registered trademarks of their respective holders.

Table of Contents

1. What's Included.....	5
2. Architecture Overview.....	6
Data Flow.....	6
3. Prerequisites.....	7
Archive Server (Ubuntu).....	7
BigFix Root Server (Windows): Audit Agent.....	7
BigFix Operator Account.....	7
4. Part 1: Archive Server Installation (Ubuntu).....	8
Step 1: Copy the Archive Package.....	8
Step 2: Extract the Package.....	8
Step 3: Run the Installer.....	9
Step 4: Enter Admin Account Details.....	10
Step 5: Enter BigFix Connection Details.....	10
Step 6: SSL Certificate Configuration.....	11
Step 7: Performance Tuning.....	11
Step 7: Installation Completes.....	12
5. Part 2: First Login and Configuration.....	13
Step 1: Open the Archive Server's Web UI.....	13
Step 2: Log In.....	13
Step 3: Configure/Verify BigFix Connection.....	14
Step 4: Run Your First Collection.....	15
Step 5: Browse Archived Actions.....	15
Step 6: Generate an API Key and Download the Audit Agent (Optional).....	17
6. Part 3: Audit Agent Installation (Windows).....	18
Step 1: Install Python (if not already installed).....	18
Step 2: Transfer the Audit Agent Package.....	18
Step 3: Run the Installer.....	18
Step 4: Enter Configuration.....	19
Step 5: Test the Connection.....	19
Step 6: Install.....	20
Step 7: Confirm the Scheduled Task.....	20
7. Verification.....	21
Archive Server.....	21
1. Verify the service is running:.....	21
2. Check the health endpoint:.....	21
3. Web UI and data:.....	21
Audit Agent (Windows).....	21
8. Troubleshooting.....	22
Archive Server.....	22
Audit Agent (Windows).....	22
Log File Locations.....	23
9. Managing the Application.....	24
Service Management (Ubuntu).....	24
Database Backup (from Web UI).....	24
Audit Agent Management (Windows).....	25

Uninstalling the Audit Agent.....	25
-----------------------------------	----

1. What's Included

The installation package includes a single file:

File	Size	Purpose	Install On
action-archive-latest.tar.gz	~8 MB	Archive Server application + installer	Ubuntu Server

Note: The single installation file also contains the audit agent installer. The Audit Agent is optional but recommended. Without it, actions deleted from BigFix before they are collected will not be visible in the archive.

2. Architecture Overview

The diagram below illustrates how the components interact across your environment.




Figure 1: Action Archive System Architecture

Data Flow

- **Collection Service:** The Archive Server polls the BigFix REST API on a schedule to collect expired and stopped actions. It can also be configured to mark collected actions as 'deleted' in the console for BigFix's cleanup process to remove from the database during a cleanup run.
- **Audit Agent:** Monitors server_audit.log on the BigFix Root Server and reports any action deletions to the Archive API via HTTPS.
- **Web UI:** Users access the archive through any web browser over HTTPS (port 443).

3. Prerequisites

Archive Server (Ubuntu)

Requirement	Details
Operating System	Ubuntu Server 22.04 LTS or 24.04 LTS (amd64)
Access	Root or sudo access
CPU	2 vCPU minimum, 4 vCPU recommended (x86-64 / amd64)
RAM	Minimum 4 GB
Disk	Minimum 20 GB free
Network	Internet access during installation (for apt packages)
Network	Must be able to reach the BigFix Root Server REST API
Ports	443 (HTTPS) must be accessible to users

Note: The installer will automatically install and configure PostgreSQL, Nginx, Python, and all dependencies. You do not need to pre-install anything beyond the base Ubuntu Server.

BigFix Root Server (Windows): Audit Agent

Requirement	Details
Operating System	Windows Server 2016+
Python	Python 3.8 or later (download from python.org)
PowerShell	5.1+ (included with Windows)
Network	Must be able to reach the Archive Server over HTTPS

BigFix Operator Account

The Archive Server requires a BigFix operator account to collect actions. This account must be a Master Operator (MO) to retrieve complete action data including targets and status.

Important: Master Operator is the only role that provides complete access to all action data via the BigFix REST API. A non-MO operator will result in incomplete collections. It is recommended to create a dedicated service account for this purpose. The same requirement applies whether the installer is configured for Password or API Token authentication.

4. Part 1: Archive Server Installation (Ubuntu)

Step 1: Copy the Archive Package

Copy action-archive-latest.tar.gz to your Ubuntu server (e.g., /tmp folder):

Step 2: Extract the Package

```
ssh user@your-server
cd /tmp
tar -xzf action-archive-latest.tar.gz
cd action-archive
```

You should see the following files after extraction:

```
action-archive/
  app/                # Application code
  static/             # Web frontend files
  agent/              # Bundled Audit Agent installer (Windows)
  install.sh          # Automated installer
  schema.sql          # Database schema
  requirements.txt
  README.md
  LICENSE
```


Step 3: Run the Installer

```
sudo bash install.sh
```

The installer will display a banner and perform a pre-flight check to ensure all packages it needs for a successful installation are present. If any are not present, it will offer to install via apt install.

```
=====
Action Archive for BigFix Platform - Installer
Version 1.1.4
=====

[20:33:42] === Pre-flight Checks ===
Detected: Ubuntu 24.04 (noble)

[20:33:42] === Prerequisite Check ===
Found: curl
Found: python3
Found: openssl
Found: free
Found: lsblk
Found: nproc
Found: useradd
All prerequisites satisfied.
Memory: 7942MB available
Disk: 11146MB free on /opt
```

Note: If an existing Action Archive installation is detected on this server, the installer presents an Upgrade / Reinstall / Cancel prompt. Upgrade (the default) preserves all configuration, credentials, and archived data and only refreshes the application files. Reinstall performs a fresh install and wipes existing data. Use with caution. This prompt does not appear on a first-time install.

```
=====
Action Archive for BigFix Platform - Installer
Version 1.1.3
=====

[20:44:15] === Pre-flight Checks ===
Detected: Ubuntu 24.04 (noble)
Memory: 7942MB available
Disk: 10380MB free on /opt

WARNING: Action Archive for BigFix Platform is already installed (version: 1.1.2). This installer is version 1.1.3.

1) Upgrade -- Replace application code only. Preserves the .env
             file (BigFix credentials, encryption keys, all
             in-app settings), the SSL certificate, the admin
             password, and the database. Recommended.

2) Reinstall -- Start fresh. Prompts for new BigFix and admin
                credentials, regenerates .env, regenerates the
                self-signed SSL cert, and resets the admin
                password. The database itself (archived actions,
                users, audit log) is preserved either way.

3) Cancel

Choose [1, 2, or 3, default 1]:
```

Step 4: Enter Admin Account Details

The installer will prompt you for the initial administrator account:

- **Admin username:** The username you will use to log into the web UI (e.g., admin)
- **Admin password:** Must meet complexity requirements (minimum 8 characters, uppercase, lowercase, number, special character)
- **Admin email:** Email address for notifications and password resets. This value is optional during the install, but should be set later in the Web interface to enable admin self-service password reset and email notifications.

Step 5: Enter BigFix Connection Details

Next, the installer prompts for BigFix server connection information:

- **BigFix Server URL:** The hostname or IP of your BigFix Root Server (e.g., https://bigfix-server)
- **BigFix Server Port:** REST API port (default: 52311)
- **BigFix Authentication Method:** Choose Password (default) or API Token. API Token is new in v1.1.0 and uses BigFix's native REST API token authentication (Authorization: Bearer header).
- **If Password:** enter the BigFix Operator Username (a Master Operator service account) and Password when prompted. **If API Token:** paste the token value when prompted (paste carefully; the token is encrypted at rest and cannot be retrieved later).

Tip: To mint a BigFix API token, sign in to the BigFix Console as the operator, open Tools → Manage Tokens, and create a new token. The operator must retain the REST API permission. See the Administrator Guide for details.

```
BigFix server URL (e.g., https://bigfix.company.com): https://bfrootsvr
BigFix server port [52311]:

BigFix authentication method:
  password - Operator username and password (works on all BigFix versions)
  token    - API token (BigFix 11.0.6+ only)
Authentication method (password/token) [password]:
BigFix operator username: admin
BigFix operator password: *****
Confirm BigFix operator password: *****

Testing BigFix connection to https://bfrootsvr:52311 ...
BigFix connection verified (HTTP 200).
```

Note: The installer will test the connection and display an error if it's unable to connect to the Root Server.

Step 6: SSL Certificate Configuration

The installer will ask about SSL certificates:

- **Option 1:** Generate a self-signed certificate (recommended for testing/internal use)
- **Option 2:** Provide paths to an existing certificate and key

For most installations, choose the self-signed option.

--- SSL Certificate ---

A self-signed certificate will be generated by default.
Use existing certificate? (y/N) [N]:

Step 7: Performance Tuning

The installer will auto detect the host's hardware specs and make a recommendation about tuning the database and kernel :

- **PostgreSQL:** The installer will make recommendations about tuning PostgreSQL for performance
- **Kernel Virtual Memory:** The installer will recommend a memory management setting

It is recommended to accept the tuning parameters for better application performance.

```
[20:38:33] === PostgreSQL Performance Tuning ===  
  
Detected hardware:  
Total RAM:      7942 MB (~8 GB)  
CPU cores:      1  
PG storage:     SSD  
  
Recommended PostgreSQL settings for this server:  
shared_buffers      = 1985MB  
effective_cache_size = 4765MB  
work_mem            = 16MB  
maintenance_work_mem = 256MB  
random_page_cost    = 1.1  
effective_io_concurrency = 200  
max_worker_processes = 1  
max_parallel_workers = 1  
max_parallel_workers_per_gather = 1  
max_parallel_maintenance_workers = 1  
wal_buffers         = 16MB  
checkpoint_completion_target = 0.9  
  
Plus kernel: vm.swappiness = 10  
  
Apply these PostgreSQL tuning settings now? [Y/n]: y
```

Step 7: Installation Completes

The installer will perform the following steps automatically:

- Install system packages (PostgreSQL, Nginx, Python, Node.js)
- Create the application user and directories
- Set up the Python virtual environment and install dependencies
- Initialize the database with the schema
- Configure Nginx as a reverse proxy with SSL
- Create and start the systemd service

When complete, you will see a success message with the URL to access the application.

```
=====
Installation Complete! (v1.1.4)
=====

Access the application:
URL:      https://192.168.0.42
Username: admin
Password: (as configured during install)

Service management:
Start:    sudo systemctl start bigfix-archive
Stop:     sudo systemctl stop bigfix-archive
Restart:  sudo systemctl restart bigfix-archive
Status:   sudo systemctl status bigfix-archive
Logs:     sudo journalctl -u bigfix-archive -f

Important paths:
App:      /opt/bigfix-archive/
Config:   /opt/bigfix-archive/config/.env
Backups:  /opt/bigfix-archive/backups/
Logs:     journalctl -u bigfix-archive

Note: You are using a self-signed SSL certificate.
Your browser will show a security warning on first visit.
You can replace it via System Settings > Certificates in the web UI.
```

5. Part 2: First Login and Configuration

Step 1: Open the Archive Server's Web UI


Open a web browser and navigate to the Archive Server URL:

```
https://your-server-ip
```

Note: If using a self-signed certificate, your browser will show a security warning.

Step 2: Log In

Enter the admin username and password you created during installation.

The image shows a dark-themed login interface for 'ACTION ARCHIVE FOR BIGFIX PLATFORM'. It features two input fields for 'USERNAME' and 'PASSWORD'. Below these is a checkbox labeled 'Remember me'. A yellow 'LOGIN' button is positioned below the checkbox, and a 'Forgot Password?' link is located at the bottom of the form area.

ACTION ARCHIVE
FOR BIGFIX PLATFORM


USERNAME

PASSWORD

☐ Remember me

LOGIN


[Forgot Password?](#)



The dashboard should display the counters showing “0” for all statistics

Step 3: Configure/Verify BigFix Connection

Navigate to Administration > System Settings > Connections to verify the BigFix server connection is correct. Click Test Connection to confirm the Archive can reach your BigFix REST API.



Step 4: Run Your First Collection

- Go to the Dashboard and click the **Run Collection** button to run an immediate collection

The screenshot shows the 'ACTION ARCHIVE FOR BIGFIX PLATFORM' dashboard. At the top, it says 'Welcome, Administrator' with 'MY ACCOUNT' and 'LOGOUT' buttons. The 'DASHBOARD' tab is selected. Four large digital displays show: '1,796 TOTAL ACTIONS', '457 TOTAL TARGETS', '1,740 SINGLE ACTIONS', and '56 MULTI-ACTION GROUPS'. Below these is a 'RECENT COLLECTIONS' section with a table and a 'RUN COLLECTION' button highlighted by a red arrow.

STARTED	STATUS	TYPE	STARTED BY	ACTIONS	DURATION	PROGRESS
4/5/2026, 3:59 PM	COMPLETED	MANUAL	admin	1796	45s	-

Step 5: Browse Archived Actions

After the first collection completes, navigate to the Actions tab to see your archived actions.

The screenshot shows the 'ACTION ARCHIVE FOR BIGFIX PLATFORM' dashboard with the 'ACTIONS' tab selected. It displays 'ARCHIVED ACTIONS' and 'DELETED BEFORE ARCHIVED' sections. A search bar and filters are at the top. Below is a table of archived actions.

ID	NAME	SITE	ISSUER	TYPE	STATUS	ISSUED	ARCHIVED	TARGETS	ACTIONS
2319	POLICY - Deploy and Run Security Checklist RedHat ...	Master Operator Site	admin	SINGLE	STOPPED	1/14/2019, 1:06 PM	4/5/2026, 4:00 PM	2	VIEW
2969	Configure File Checksums Collection (MD5/SHA-256)	IBM Endpoint Manager for Software Use Analysis	admin	SINGLE	STOPPED	2/1/2019, 10:47 AM	4/5/2026, 4:00 PM	Dynamic	VIEW
4411	Deploy ComplianceWhitelist File	Manage_Windows_Admin	admin	SINGLE	STOPPED	3/19/2019, 10:47 AM	4/5/2026, 4:00 PM	Dynamic	VIEW
4478	Deploy: 7-Zip	Corporate Utilities	admin	SINGLE	STOPPED	4/1/2019, 12:31 PM	4/5/2026, 4:00 PM	1	VIEW
4479	Deploy Speccy v1.32	Corporate Utilities	admin	SINGLE	STOPPED	4/1/2019, 12:33 PM	4/5/2026, 4:00 PM	1	VIEW
4480	Slack Desktop	Corporate Utilities	admin	SINGLE	STOPPED	4/1/2019, 12:35 PM	4/5/2026, 4:00 PM	1	VIEW
4483	TightVNC v2.8	ActionSite	admin	SINGLE	STOPPED	4/1/2019, 12:50 PM	4/5/2026, 4:00 PM	1	VIEW
4494	MobaXterm v11.1	ActionSite	admin	SINGLE	STOPPED	4/1/2019, 2:53 PM	4/5/2026, 4:00 PM	1	VIEW
4811	Change '...RelaySelect_Automatic' Setting	Master Operator Site	admin	SINGLE	STOPPED	6/3/2019, 10:16 AM	4/5/2026, 4:00 PM	3	VIEW

Click the 'View' button on an action to view the action's details.

DEPLOY: 7-ZIP

ACTION INFORMATION

ACTION ID

18927

TYPE

SINGLE

STATUS

EXPIRED

SITE

Corporate Utilities

ISSUER

mconsuegra

ARCHIVED

4/5/2026, 4:00 PM

ACTION TIMELINE

ISSUED

4/1/2026, 6:04 PM

TARGET SUMMARY

1 TOTAL

1 COMPLETED

0 FAILED

0 PENDING

0 NOT RELEVANT

0 NOT REPORTED

RELEVANCE

((if(name of operating system starts with "Win") then free space of drive of client > 2876172 else if ((mac of it) of operating system) then free space of filesystem of folder (pathname of client) > 2876172 else free space of filesystem of client > 2876172)) AND (version of client >= "8.2")) AND (windows of operating system AND (if(name of operating system starts with "Win") then platform id of operating system != 3 else true))

ACTION SCRIPT

//Download all specified files
begin prefetch block
 add prefetch item name=A2183901F65B6789494AB712C54B6202A56CA5A0 size=1438086
 sha1=a2183901f65b6789494ab712c54b6202a56ca5a0 size=1438086
 url=SWDProtocol://127.0.0.1:52311/uploads/A2183901F65B6789494AB712C54B6202A56CA5A0/7z1805-x64.exe.bfswd sha256=c1e42d8b76a80ea1890ad080e69a04c75a5f2c0484bdcd838dc8fa008dd4a84c
end prefetch block

parameter "baseFolder" = "__Download/"

//Move files into subfolders and unescape file names
move "__Download/A2183901F65B6789494AB712C54B6202A56CA5A0" "{parameter "baseFolder"}7z1805-x64.exe"

// Log setup

TARGET COMPUTERS (1)

Export Targets

COMPUTER	STATUS	STARTED	COMPLETED
ADR00T2016	COMPLETED	4/1/2026, 6:08 PM	4/1/2026, 6:08 PM

BIGFIX CONSOLE ACTIONS

Delete from BigFix Console

Marks this action as deleted in BigFix (does not remove from this archive)

Step 6: Generate an API Key and Download the Audit Agent (Optional)

If you plan to install the Audit Agent (Part 3), both the API key and the agent installer package are obtained from the same panel of the web UI. No internet access is required. The agent installer is served from local disk on the Archive Server.

- Navigate to Administration > System Settings > API Keys
- Click Generate New Key
- Enter a name (e.g., "BigFix Audit Agent")
- Click Generate Key

Copy the generated key value immediately (it will not be shown again) and save it somewhere safe; you will paste it into the agent's installer in Part 3.

On the same API Keys panel, click Download Audit Agent to save action-archive-audit-agent-latest.zip to your local machine. You will transfer this file to the BigFix Root Server in Part 3.

The screenshot shows the 'ACTION ARCHIVE FOR BIGFIX PLATFORM' web interface. The top navigation bar includes 'DASHBOARD', 'ACTIONS', and 'ADMINISTRATION'. The 'ADMINISTRATION' section is active, showing 'USER MANAGEMENT', 'SYSTEM SETTINGS', and 'LOGS'. The 'SYSTEM SETTINGS' section is highlighted, and the 'API KEYS' panel is displayed. The panel includes a 'GENERATE NEW KEY' button and a 'DOWNLOAD AUDIT AGENT' button. Below these buttons is a table of API keys.

NAME	KEY PREFIX	CREATED	LAST USED	STATUS	ACTIONS
BigFixAuditAgent-April2026	aa-8b5f317...	4/7/2026	4/13/2026, 4:30:35 PM	ACTIVE	REVOKE
BigFix Audit Agent	aa-235358c...	4/5/2026	4/5/2026, 5:25:16 PM	REVOKED	REACTIVATE

Important: Copy the displayed key immediately. It will only be shown once and cannot be retrieved later.

6. Part 3: Audit Agent Installation (Windows)

The Audit Agent is installed on the BigFix Root Server (Windows). It monitors the BigFix server_audit.log file for action deletions and reports them to the Archive Server.

Step 1: Install Python (if not already installed)

- Download Python 3.8 or later from python.org
- Run the installer

IMPORTANT: Check the box "Add python.exe to PATH" on the first installer screen.

Step 2: Transfer the Audit Agent Package


Transfer action-archive-audit-agent-latest.zip (downloaded in Part 2, Step 6) to the BigFix Root Server and extract it. You can place it anywhere (e.g., C:\Temp\ or the Desktop). If you did not download the agent in Part 2, sign in to the Archive web UI now and download it from Administration → System Settings → API Keys → Download Audit Agent.

Step 3: Run the Installer

- Navigate to the extracted folder
- **Double-click** Install.bat

Note: If prompted by Windows SmartScreen or UAC, click "Run Anyway" / "Yes" to allow the installer to run. The installer requires Administrator privileges to create the scheduled task.

The installer GUI will appear:



Step 4: Enter Configuration

Fill in the following fields in the installer:

Field	Value	Notes
Archive Server URL	<code>https://your-archive-server-ip</code>	Must include <code>https://</code>
API Key	The key generated in Part 2, Step 6	Paste the full key starting with <code>aa-</code>
Install Directory	<code>C:\BigFix\audit_agent</code>	Default is fine for most environments
BigFix Server Dir	Auto-detected	Only change if BigFix is installed to a non-default location
Schedule Interval	Every hour	Configurable

Step 5: Test the Connection

Click Test Connection to verify the Archive Server URL and API Key are correct.

If the connection fails, verify:

- The Archive Server URL is correct and reachable from this server
- The API key was copied correctly (starts with `aa-`)
- The API key was generated on the Archive Server you are connecting to (keys are server-specific)


Step 6: Install

Click the Install button. The installer will perform the following steps:

- Create the install directory
- Copy agent scripts
- Generate config.ini with your settings
- Install the Python requests library
- Test the API connection
- Create a Windows Scheduled Task
- Run a historical scan of ALL server_audit.log files to catch past deletions
- Set the position marker for ongoing monitoring

Step 7: Confirm the Scheduled Task

Open Windows Task Scheduler and verify the task BigFix-ActionArchive-AuditAgent exists and is enabled.



7. Verification

After completing both installations, verify everything is working correctly.

Archive Server

1. Verify the service is running:

```
sudo systemctl status bigfix-archive
```

Should show active (running).

2. Check the health endpoint:

```
curl -sk https://localhost/api/health | python3 -m json.tool
```

Should return "status": "healthy" with all checks passing.

3. Web UI and data:

- Open <https://your-server-ip> in a browser and confirm you can log in
- Navigate to the Actions tab; it should show archived actions after a collection run

Audit Agent (Windows)

- **Scheduled task:** Open Task Scheduler and confirm BigFix-ActionArchive-AuditAgent is present
- **Agent log:** Check C:\BigFix\audit_agent\agent.log for successful runs
- **API Key activity:** In the Archive web UI, go to Settings > API Keys and verify the "Last Used" timestamp has updated
- **Deleted actions:** If any actions have been deleted from BigFix, they should appear in the Archive. You can test by deleting a test action from the BigFix Console, waiting for the next agent run, and checking the Archive.

8. Troubleshooting

Archive Server

Symptom	Likely Cause	Solution
Service fails to start	Configuration error	<code>sudo journalctl -u bigfix-archive -n 50</code>
"502 Bad Gateway" in browser	App not running or Nginx misconfigured	Verify service: <code>sudo systemctl status bigfix-archive</code>
Collection returns 0 actions	Operator is probably not a Master Operator	Verify MO status in BigFix Console
SSL certificate warning	Self-signed certificate in use	Expected for self-signed certs; proceed past the warning
Cannot reach BigFix server	Network or firewall issue	Verify: <code>curl -sk https://bigfix-server:52311</code>
Database connection error	PostgreSQL not running	<code>sudo systemctl status postgresql</code>

Audit Agent (Windows)

Symptom	Likely Cause	Solution
requests library not installed	pip failed during install	Run: <code>pip install requests</code> manually
Connection test fails	SSL or network issue	Verify Archive URL is reachable by opening it in a browser
API key rejected	Key mismatch or wrong server	Generate a new key on the correct Archive server
Agent runs but finds nothing	No deletions since last scan	Normal behavior: agent only reports new deletions
"Access denied" on scheduled task	Not running as Administrator	Right-click Install.bat > Run as Administrator
Historical scan found 0 deletions	No actions have been deleted	Normal if no one has deleted actions from BigFix

Log File Locations

Component	Log Location
Archive Server application	sudo journalctl -u bigfix-archive
Archive Server Nginx	/var/log/nginx/bigfix-archive-error.log
Audit Agent installer	install.log (in the extracted folder)
Audit Agent runtime	C:\BigFix\audit_agent\agent.log

9. Managing the Application

Service Management (Ubuntu)

```
# Check status
sudo systemctl status bigfix-archive

# Restart the service
sudo systemctl restart bigfix-archive


# Stop the service
sudo systemctl stop bigfix-archive

# View recent logs
sudo journalctl -u bigfix-archive -n 100


# Follow logs in real-time
sudo journalctl -u bigfix-archive -f
```

Database Backup (from Web UI)

- Navigate to Administration > System Settings > Backup & Restore
- Click Create Backup



- Download the backup file for off-site storage



Audit Agent Management (Windows)

```
# View task status
Get-ScheduledTask -TaskName "BigFix-ActionArchive-AuditAgent"

# Run manually
Start-ScheduledTask -TaskName "BigFix-ActionArchive-AuditAgent"

# Disable temporarily
Disable-ScheduledTask -TaskName "BigFix-ActionArchive-AuditAgent"

# Re-enable
Enable-ScheduledTask -TaskName "BigFix-ActionArchive-AuditAgent"
```

Uninstalling the Audit Agent

Use the installer GUI: double-click Install.bat, then click the Uninstall button. This removes the scheduled task and all agent files.