

QUICK START GUIDE

New to Agent Monitor? You do not need to read the full Installation Guide to get started. This single page takes you from the distribution files to a monitored environment. Each step is covered in depth in the Installation Guide if you want more detail, and day-to-day operation is covered in the Administrator Guide.

1. Install the Dashboard. Copy the server package to a dedicated Ubuntu Server 24.04 (or later) host, extract it, and run the installer as root. Answer the prompts: admin account, database user, SSL certificate, and the address agents will use to reach this server.

2. Log In and Connect BigFix (*optional-Not needed for agent monitoring*). Browse to the dashboard over HTTPS and log in. Click Administration > System Settings > Connections, enter your BigFix Root Server URL and Master Operator credentials, and capture the BES Root CA.

3. Generate the Deployment Charter. On the Agent Builds page, generate and download dashboard.charter. Placed beside an installer, it configures the agent completely: dashboard address, enrollment key, and encryption anchor.

4. Create Your Signing Certificate. In WINDOWS AGENT SIGNING on the Agent Builds page, click GENERATE. Store the downloaded .pfx and its passphrase securely (it signs every future release, and the server never keeps it), then click Download CA. Have your own certificate? Use it instead.

5. Sign the Windows Agent. Click SIGN on the Windows build row, upload the .pfx with its passphrase, then download the signed zip. Linux agents need no signing; their integrity is verified through build attestation.

6. Include the CA Certificate with the Agent. Place agent-signing-ca.crt (from Step 4) alongside the installer files. During installation the agent verifies it is signed by that certificate and trusts it automatically, so endpoints do not report CHAIN INVALID. For centrally managed trust, distribute the CA through Group Policy or a Fixlet instead.

7. Deploy the Agents. Stage the signed Windows zip, the Linux bundle, and the charter on your BigFix server and deploy with the installation Fixlet, or extract a bundle on an endpoint with the charter beside the installer and run it silently. (Steps 7 and 8 can be part of a BigFix Baseline in this order)

8. Verify. Within minutes each endpoint appears on the Endpoints page as HEALTHY with no integrity badge beside it. Done.