

15213 - Recitation 2 - Datalab

Introduction

In this activity you will review the material on integers, binary, and floating-point necessary for datalab. This activity was based on material developed by Professor Saturnino Garcia of the University of San Diego. It is used here with permission.

Each activity is designed to be solved in groups and take approximately 10 minutes.

Activity 1: Bit-level and Logical

1. De Morgan's Law enables one to distribute negation over AND and OR. Given the following expression, complete the following table to verify for the 4-bit inputs. $\sim(x \& y) == (\sim x) \mid (\sim y)$

x	y	$\sim(x \& y)$	$(\sim x) \mid (\sim y)$
0xF	0x1	0b1110	0xE
0x5	0x7	0b1010	0xA
0x3	0xC	0b1111	0xF

This section will explore logical operations. These operations contrast with bit-level in that they treat the entire value as a single element. In other languages, the type of these values would be termed, "bool" or "boolean". C does not have any such type. Instead, the value of 0 is false and all other values are true.

The three operators are AND (&&), OR (||), and NOT (!). "!" is commonly termed "bang".

2. Evaluate the following expression: $(0x3 \&\& 0xC) == (0x3 \& 0xC)$ **0x1** \neq **0x0**
3. Test whether $(!!X) == X$ holds across different values of X. Do the same for bitwise complement.

X	!X	!!X	~X	~~X
-1	0	1	0	-1
0	1	0	-1	0
1	0	1	-2	1
2	0	1	-3	2

Activity 2: Shifts, Negation and Conditional

1. Suppose we right shift the value of "-2" by 1. What value do we expect? **-2 / 2 = -1**

2. With 4-bit integers, what is the binary for -2? After right shifting by 1, what value(s) might we have? **0b1110 >> 1 = 0b1111**
3. Fill in the following table, assuming you only have 4 bits to represent the 2s complement integer.

x	x in binary	-x in binary
1	0001	1111
2	0010	1110
7	0111	1001
-8	1000	-

4. Find an algorithm for computing the expression $(cond) ? t : f$, which equals t if $cond$ is 1 and f if $cond$ is 0. Assume $cond$ will either be 1 or 0.

```
int conditional(int cond, int t, int f) {
    /* Compute a mask that equals 0x00000000 or
    0xFFFFFFFF depending on the value of cond */

    int mask = _____(cond<<31)>>31_____;;

    /* Use the mask to toggle between returning t or returning f */

    return ____ (mask "and" t) "or" (~mask "and" f) ____;
}
```

Activity 4: Divide and Conquer (Bit Parity)

Let's determine whether a number has an even number of 1-bits or an odd number. You can use any operator allowed in datalab. Return a 0 if there's an even number and 1 if odd. Using 1 op, you can

return the parity of a 1-bit number. `int bitParity1bit(int x) {return x;}`

1. How about if there are two bits in the input? (4 ops max)

```
int bitParity2bit(int x)
{
    int bit1 = __0b01 & x_____;
    int bit2 = ___0b01 & (x >> 1)_____;
    return ___bit1_____ ^ ___bit2_____ ;
}
```

2. How about if there are four bits? (8 ops max)

```
int bitParity4bit(int x)
{
    int mask = ___0b0101_____;

    int halfParity = ____ (mask & x) ^ (mask & (x >> 1))_____;

    int mask2 = ___0b0011_____;

    return ___ (mask2 & halfParity)_____ ^ ___ (mask2 & (halfParity >> 2))_____ ;
}
```

3. How about if there are eight bits? (12 ops max)

```
int bitParity8bit(int x)
{
    int mask = ___0b01010101_____;

    int quarterParity = ____ (mask & x) ^ (mask & (x >> 1))_____;

    int mask2 = ___0b00110011_____;

    int halfParity = ___ (mask2 & quarterParity) ^ (mask2 & (quarterParity >> 2))_____;

    int mask3 = ___0b00001111_____;

    return __ (mask3 & halfParity)_____ ^ ____ (mask3 & (halfParity >> 4))_____ ;
}
```

Activity 5: Divide and Conquer (Bit Count)

Let's count how many bits are set in a number. For each challenge, you can use any allowed operator allowed in the integer problems in datalab. Using 1 op, return the number of bits set in a 1-bit number. `int bitCount1bit(int x) {return x;}`

1. How about if there are two bits in the input? (4 ops max)

```
int bitCount2bit(int x)
{
    int bit1 = __0b01 & x_____;
    int bit2 = ____0b01 & (x >> 1)_____;
    return ____bit1____ + ____bit2____ ;
}
```

2. How about if there are four bits? (8 ops max)

```
int bitCount4bit(int x)
{
    int mask = ____0b0101_____;

    int halfSum = ____ (mask & x) + (mask & (x >> 1)) ____;

    int mask2 = ____0b0011_____;

    return ___ (mask2 & halfSum) _____ + ___ (mask2 & (halfSum >> 2)) _____ ;
}
```

3. How about if there are eight bits? (12 ops max)

```
int bitCount8bit(int x)
{
    int mask = ____0b01010101_____;

    int quarterSum = ____ (mask & x) + (mask & (x >> 1)) ____;

    int mask2 = ___0b00110011_____;

    int halfSum = ___ (mask2 & quarterSum) + (mask2 & (quarterSum >> 2)) _____;

    int mask3 = ____0b00001111_____;

    return __ (mask3 & halfSum) _____ + ____ (mask3 & (halfSum >> 4)) _____ ;
}
```