

GNU Make Cheat Sheet

RULES

Short rules can be written as below

```
target(s): [prerequisites] [; shell-command(s)]
```

```
target(s): [prerequisites]  
          [shell-command]
```

```
%.class: %.java; javac $<
```

A target pattern is composed of a “%” between a prefix and a suffix, either or both of which may be empty.

MACROS/VARIABLES

Values assigned to variables with **=** are expanded when used (like a reference) while values assigned with **:=** are expanded at declaration time. **\$(myvar)** returns the stored value and **\$(call myvar)** executes the value (like a function).

\$\$	The name of the target.
\$\$%	The target member name, when the target is an archive member.
\$<	The name of the first (or only) prerequisite.
\$?	Space separated list of all prerequisites newer than the target.
\$^ \$+	Space separated list of all prerequisites. \$^ omits duplicate prerequisites, while \$+ retains them and preserves their order.
\$*	The stem with which an implicit rule matches.
\$(•D) \$(•F)	The path and the file name of a macro. For instance \$(@D) returns the directory-part of @@ .

INCLUDES

For large projects use several makefiles and use the command **include** to call them within your ‘master’ makefile. Use **-include Makefile(s)** if you don’t want **make** to abort when the included Makefiles are missing. The minus sign generally forces **make** to ignore errors.

FUNCTIONS

```
$(subst from,to,text)  
$(patsubst pattern,replacement,text)  
$(strip string)  
$(findstring find,in)  
$(filter pattern_1 pattern_2...,text)  
$(filter-out pattern_1 pattern_2...,text)  
$(sort list)  
$(dir names...)  
$(notdir names...)  
$(realpath names...)
```

```
$(suffix names...)  
$(basename names...)  
$(addsuffix suffix,names...)  
$(addprefix prefix,names...)  
$(join list_1,list_2)  
$(word n,text)  
$(words text)  
$(wordlist i,j,text)  
$(firstword names...)  
$(wildcard pattern...)  
$(error text...)  
$(warning text...)  
$(shell command)  
$(origin variable)
```

```
$(foreach var,words,text)  
$(call var,param,param,...)
```

Replaces each occurrence of **from** in **text** by **to**

Replaces words matching **pattern** with **replacement** in **text**.

Removes excess whitespace characters from **string**.

Search **in** for an occurrence of **find**.

Selects words in **text** that match one of the **pattern** words.

Selects words in **text** that do not match any of the **pattern** words.

Sorts the words in **list** lexicographically, removing duplicates.

Extracts the directory-part of each file name in **names**.

Extracts the non-directory part of each file name in **names**.

Returns an absolute name (does not contain “.”, “..” or symlinks) for each file name in **names**.

Extracts the suffix (everything starting with the last period) of each file name in **names**.

Extracts all but the suffix of each file name in **names**.

Appends **suffix** to each word in **names**.

Prepends **prefix** to each word in **names**.

Join two parallel lists of words.

Extracts the **nth** word of **text**.

Counts the number of words in **text**.

Returns the list of words in **text** from **i** to **j**.

Extracts the first word in **names**.

Returns the file names matching (a shell file name) **pattern** (not a “%” pattern).

When the function is evaluated a fatal error with the message **text** is generated.

When the function is evaluated a warning with the message **text** is generated.

Execute a shell command and return its output.

Describes where **variable** came from. Do not use “\$” or parentheses around **variable** unless you want the name not to be constant and provide a variable reference.

Evaluate **text** with **var** bound to each word in **words**, and concatenate the results.

Evaluate **var** replacing any references to **\$(1)**, **\$(2)** with the first, second, etc. **param** values.

SPECIAL BUILT-IN TARGET NAMES

- .PHONY** prerequisites of a **.PHONY** target are never considered to be up to date.
- .INTERMEDIATE** the targets which **.INTERMEDIATE** depends on are treated as intermediate files and they are deleted once no longer needed for a rule.
- .SECONDARY** the targets which **.SECONDARY** depends on are treated as intermediate files but they are not automatically deleted.
- .PRECIOUS** like **.SECONDARY**, and files will not be deleted if **make** is aborted.
- .IGNORE** errors encountered while executing recipes for the prerequisites of **.IGNORE** are ignored.
- .EXPORT_ALL_VARIABLES** allows variables exported in parent Makefile to be available to rules in child processes. It uses no prerequisites.