

Sedeo 2.0 API Documentation

Models

Model Name	Description
<code>atlascloud/sedeo-2.0</code>	State-of-the-art video generation with native audio, multimodal reference, video editing, and web search
<code>atlascloud/sedeo-2.0-fast</code>	Fast video generation with native audio, optimized for speed and cost efficiency

Capabilities

Both models share a single unified endpoint, but differ in supported modes:

Capability	sideo- 2.0	sideo- 2.0-fast	Description
Text-to-video	✓	✓	Generate video from text prompt
Image-to-video (first frame)	✓	✓	First frame image + optional text prompt
Image-to-video (first & last frame)	✓	✓	First frame + last frame images + optional text prompt
Multimodal reference (image)	✓	✓	Reference images (1-9) + optional text prompt
Multimodal reference (video)	✓	✓	Reference videos (0-3) + optional text prompt
Multimodal reference (combined)	✓	✓	Images + videos + audio combinations
Video editing	✓	✓	Edit existing videos using reference inputs
Video extension	✓	✓	Extend videos using reference inputs
Audio generation	✓	✓	Synchronized audio generation (enabled by default)
Web search	✓	✗	Use web search tool to enhance text-to-video generation
Draft mode	✗	✗	Generate lower-quality draft videos for preview

Pricing

Token-based postpaid billing. Amount is computed from actual `completion_tokens` at task completion

completion.

Base rates (list price):

Model	Without Video Input	With Video Input
atlascloud/sedeo-2.0	\$10.0000 / Mtokens	\$6.0870 / Mtokens
atlascloud/sedeo-2.0-fast	\$8.0435 / Mtokens	\$4.7826 / Mtokens

Account-specific discounts may apply, reducing the effective rate. The final charge is:

amount = completion_tokens / 1,000,000 × token_rate × effective_discount

Video input is detected automatically from the request body (presence of video_url content type), which switches to the lower token_rate_with_video.

Token consumption formula: tokens ≈ (width × height × 24 × duration) / 1024

Reference: a typical 5s 720p 16:9 video consumes approximately 108,000 tokens.

Authentication

All requests require authentication via one of:

- **API Key:** Authorization: Bearer apikey-{key}

Endpoints

Create Video Generation Task

POST https://api.atlascloud.ai/api/v1/model/sedeo/tasks

Creates an asynchronous video generation task. The request body is forwarded to the upstream provider as-is (only the model field is replaced with the upstream model ID).

Request Body

```
{
  "model": "atlascloud/sedeo-2.0",
  "content": [
    {
      "type": "text",
```

```
      "text": "A cat walking on the beach at sunset"
    }
  ],
  "resolution": "720p",
  "ratio": "16:9",
  "duration": 5,
  "generate_audio": true,
  "watermark": false
}
```

Parameters

Parameter	Type	Required	Default	Description
model	string	Yes	-	Model name: atlascloud/sedeo-2.0 or atlascloud/sedeo-2.0-fast
content	object[]	Yes	-	Array of content objects defining the input (see Content Types)
resolution	string	No	720p	Video resolution: 480p or 720p
ratio	string	No	adaptive	Aspect ratio: 16:9, 4:3, 1:1, 3:4, 9:16, 21:9, or adaptive
duration	integer	No	5	Video duration in seconds. sedeo-2.0: [4, 15]; sedeo-2.0-fast: [4, 12]. Set to -1 for model to choose
generate_audio	boolean	No	true	Whether to generate synchronized audio
watermark	boolean	No	false	Whether to add a watermark to the generated video
tools	object[]	No	-	Tool configuration, e.g., [{"type": "web_search"}]. Only supported for text-to-video (atlascloud/sedeo-2.0 only)

Content Types

Text (type: "text")

Text prompt describing the desired video. Supports Chinese and English.

```
{
  "type": "text",
  "text": "A serene mountain landscape with flowing rivers"
}
```

```
}

```

Recommended length: Chinese < 500 characters, English < 1000 words.

Image (type: "image_url")

Image input via URL, Base64 encoding, or Asset ID (asset://<ASSET_ID>).

```
{
  "type": "image_url",
  "image_url": {
    "url": "https://example.com/image.jpg"
  },
  "role": "first_frame"
}
```

Role	Description
first_frame (or omit)	Use as the first frame of the video
last_frame	Use as the last frame (requires a first_frame image)
reference_image	Use as a reference image for multimodal generation

Image requirements: jpeg/png/webp/bmp/tiff/gif, aspect ratio (0.4, 2.5) exclusive, dimensions (300, 6000)px exclusive, max 30MB per image, max 64MB request body. Up to 9 reference images.

Video (type: "video_url")

Video input via URL or Asset ID. Supported by both atlascloud/sedeo-2.0 and atlascloud/sedeo-2.0-fast.

```
{
  "type": "video_url",
  "video_url": {
    "url": "https://example.com/video.mp4"
  }
}
```

```

    },
    "role": "reference_video"
  }

```

Video requirements: mp4/mov, 480p or 720p, aspect ratio [0.4, 2.5] inclusive, dimensions [300, 6000]px inclusive, pixel count [409,600, 927,408], duration [2, 15]s, max 3 reference videos (total <= 15s), max 50MB, FPS [24, 60].

Audio (`type: "audio_url"`)

Audio input via URL, Base64 encoding, or Asset ID. Cannot be used alone — must include at least 1 reference video or image.

```

{
  "type": "audio_url",
  "audio_url": {
    "url": "https://example.com/audio.wav"
  },
  "role": "reference_audio"
}

```

Audio requirements: wav/mp3, duration [2, 15]s, max 3 reference audio clips (total <= 15s), max 15MB per clip, max 64MB request body.

Supported Content Combinations

- Text only
- Text (optional) + image(s)
- Text (optional) + video(s)
- Text (optional) + image(s) + audio
- Text (optional) + image(s) + video(s)
- Text (optional) + video(s) + audio
- Text (optional) + image(s) + video(s) + audio

Response

```

{
  "code": 200,
  "message": "",
  "data": {
    "id": "a1b2c3d4e5f6...",
    "type": "reference_video",
    "url": "https://example.com/video.mp4",
    "duration": 10,
    "width": 1280,
    "height": 720,
    "fps": 30,
    "aspect_ratio": 1.78,
    "pixel_count": 921600,
    "file_size": 50000000
  }
}

```

```
  "model": "atlascloud/sedeo-2.0",
  "status": "processing",
  "outputs": [],
  "urls": {
    "get": "https://api.atlascloud.ai/api/v1/model/sedeo/tasks/a1b2c3d4e5f6..."
  },
  "created_at": "2026-03-24T10:00:00Z"
}
```

Get Task Status

```
GET https://api.atlascloud.ai/api/v1/model/sedeo/tasks/{id}
```

Polls the status of a video generation task. For in-progress tasks, the endpoint queries the upstream provider for the latest status. For terminal tasks (completed/failed/timeout), it returns the cached result.

Path Parameters

Parameter	Type	Description
<code>id</code>	string	Task ID returned from the create endpoint

Response — Processing

```
{
  "code": 200,
  "message": "",
  "data": {
    "id": "a1b2c3d4e5f6...",
    "model": "atlascloud/sedeo-2.0",
    "status": "processing",
    "outputs": [],
    "urls": {
      "get": "https://api.atlascloud.ai/api/v1/model/sedeo/tasks/a1b2c3d4e5f6..."
    },
    "created_at": "2026-03-24T10:00:00Z"
  }
}
```

Response — Completed

```
{
  "code": 200,
  "message": "",
  "data": {
    "id": "a1b2c3d4e5f6...",
    "model": "atlascloud/sedeo-2.0",
    "status": "completed",
    "outputs": [
      "https://example.com/generated-video.mp4",
      "https://example.com/last-frame.png"
    ],
    "urls": {
      "get": "https://api.atlascloud.ai/api/v1/model/sedeo/tasks/a1b2c3d4e5f6..."
    },
    "created_at": "2026-03-24T10:00:00Z",
    "duration": 5,
    "ratio": "16:9",
    "resolution": "720p",
    "seed": 780,
    "framespersecond": 24,
    "completion_tokens": 108900,
    "total_tokens": 108900,
    "usage": {
      "completion_tokens": 108900,
      "total_tokens": 108900,
      "tool_usage": {
        "web_search": 0
      }
    }
  }
}
```

Response — Failed

```
{
  "code": 500,
  "message": "generation failed",
  "data": {
    "id": "a1b2c3d4e5f6...",
  }
}
```



```
    "model": "atlascloud/sedeo-2.0",
    "status": "failed",
    "outputs": [],
    "error": "content moderation failed",
    "error_code": 1013001,
    "urls": {
      "get": "https://api.atlascloud.ai/api/v1/model/sedeo/tasks/a1b2c3d4e5f6..."
    },
    "created_at": "2026-03-24T10:00:00Z"
  }
}
```

Task Statuses

Status	Description
processing	Task is queued or being generated
completed	Video generation succeeded. Outputs contain video URL(s) and last frame
failed	Task failed (content moderation, invalid input, provider error, etc.)
timeout	Task exceeded the maximum processing time

Upstream status mapping: The upstream provider uses `running` → our `processing`, `succeeded` → our `completed`. The `timeout` status is added by the proxy layer.

Resolution / Aspect Ratio Pixel Values

Resolution	16:9	4:3	1:1	3:4	9:16	21:9
480p	864x496	752x560	640x640	560x752	496x864	992x432
720p	1280x720	1112x834	960x960	834x1112	720x1280	1470x630

Adaptive Ratio Behavior

When `ratio` is set to `adaptive` (default):

- **Text-to-video:** Model chooses the best ratio based on the prompt
- **First frame / first+last frame:** Matches the first frame image aspect ratio

- **Multimodal reference:** The model judges intent from the prompt — if the intent is first-frame generation, video editing, or video extension, the ratio matches the primary image/video; otherwise, it uses the first media file's aspect ratio (video takes priority over image)

Rate Limits

Limit	Value
Requests per minute (RPM)	600
Max concurrency	10

Workflow

1. **Create** a video generation task via `POST /model/sedeo/tasks`
2. **Poll** the task status via `GET /model/sedeo/tasks/{id}` until `status` is terminal
3. **Download** the generated video from `outputs[0]` within 24 hours (URLs are temporary)

Examples

Text-to-Video

```
curl -X POST https://api.atlascloud.ai/api/v1/model/sedeo/tasks \
-H "Authorization: Bearer apikey-YOUR_KEY" \
-H "Content-Type: application/json" \
-d '{
  "model": "atlascloud/sedeo-2.0",
  "content": [
    {"type": "text", "text": "A golden retriever playing fetch on a sunny
beach"}
  ],
  "resolution": "720p",
  "ratio": "16:9",
  "duration": 5,
  "generate_audio": true
}'
```

Image-to-Video (First Frame)

```
curl -X POST https://api.atlascloud.ai/api/v1/model/sedeo/tasks \
-H "Authorization: Bearer apikey-YOUR_KEY" \
-H "Content-Type: application/json" \
-d '{
  "model": "atlascloud/sedeo-2.0",
  "content": [
    {"type": "text", "text": "The scene comes alive with gentle motion"},
    {"type": "image_url", "image_url": {"url":
"https://example.com/photo.jpg"}, "role": "first_frame"}
  ],
  "duration": 5
}'
```

Image-to-Video (First & Last Frame)

```
curl -X POST https://api.atlascloud.ai/api/v1/model/sedeo/tasks \
-H "Authorization: Bearer apikey-YOUR_KEY" \
-H "Content-Type: application/json" \
-d '{
  "model": "atlascloud/sedeo-2.0",
  "content": [
    {"type": "text", "text": "Smooth transition between two scenes"},
    {"type": "image_url", "image_url": {"url":
"https://example.com/start.jpg"}, "role": "first_frame"},
    {"type": "image_url", "image_url": {"url": "https://example.com/end.jpg"},
"role": "last_frame"}
  ],
  "duration": 5
}'
```

Multimodal Reference (Image + Video + Audio)

```
curl -X POST https://api.atlascloud.ai/api/v1/model/sedeo/tasks \
-H "Authorization: Bearer apikey-YOUR_KEY" \
-H "Content-Type: application/json" \
-d '{
  "model": "atlascloud/sedeo-2.0",
  "content": [
    {"type": "text", "text": "A person dancing gracefully"},
    {"type": "image_url", "image_url": {"url":
"https://example.com/reference.jpg"}, "role": "reference_image"},
    {"type": "video_url", "video_url": {"url":
"https://example.com/dance.mp4"}, "role": "reference_video"},
    {"type": "audio_url", "audio_url": {"url":
"https://example.com/music.mp3"}, "role": "reference_audio"}
  ],
  "duration": 10
}'
```

With Web Search (atlascloud/sedeo-2.0 only, text-to-video only)

```
curl -X POST https://api.atlascloud.ai/api/v1/model/sedeo/tasks \
-H "Authorization: Bearer apikey-YOUR_KEY" \
-H "Content-Type: application/json" \
-d '{
  "model": "atlascloud/sedeo-2.0",
  "content": [
    {"type": "text", "text": "The Eiffel Tower lit up at night during the 2024
Olympics"}
  ],
  "tools": [{"type": "web_search"}],
  "duration": 5
}'
```

```
}'
```

Poll Task Status

```
curl https://api.atlascloud.ai/api/v1/model/sedeo/tasks/a1b2c3d4e5f6... \
-H "Authorization: Bearer apikey-YOUR_KEY"
```

Using the Fast Model

```
curl -X POST https://api.atlascloud.ai/api/v1/model/sedeo/tasks \
-H "Authorization: Bearer apikey-YOUR_KEY" \
-H "Content-Type: application/json" \
-d '{
  "model": "atlascloud/sedeo-2.0-fast",
  "content": [
    {"type": "text", "text": "A timelapse of clouds moving over mountains"}
  ],
  "resolution": "720p",
  "duration": 5
}'
```

Notes

- Output video URLs are temporary and expire after 24 hours — download promptly
- The `outputs` array typically contains the video URL as the first element and the last frame image as the second
- The alternative polling endpoint `GET /api/v1/model/prediction/{id}` also works for Sedeo tasks
- Parameters `service_tier`, `frames`, and `camera_fixed` are not supported by Sedeo 2.0 models
- Generated audio is always mono, regardless of the input audio channel count
- The upstream provider also exposes a task list endpoint (`GET /tasks?page_num=&page_size=&filter.status=&filter.task_ids=&filter.model=`); this is not currently proxied

- When web search is enabled, the response includes `usage.tool_usage.web_search` (integer) indicating how many searches were performed (0 = no search triggered)
- Request body size must not exceed 64 MB; avoid Base64 encoding for large files