### NONLINEAR ANALYSIS TO QUANTIFY MOVEMENT VARIABILITY IN HUMAN-HUMANOID INTERACTION

by

#### MIGUEL XOCHICALE

A thesis submitted to The University of Birmingham for the degree of DOCTOR OF PHILOSOPHY

> School of Engineering College of Engineering and Physical Sciences The University of Birmingham 20 May 2019

#### Abstract

Nonlinear analysis can be applied to investigate the dynamics of time-ordered data. Such dynamics relate to sensorimotor variability in the context of human-humanoid interaction. Hence, this dissertation not only explores questions such as how to quantify movement variability or which methods of nonlinear analysis are appropriate to quantify movement variability but also how methods of nonlinear analysis are affected by real-world time series data (e.g. non-stationary, data length size, sensor sources or noise). Methods are explored to determine embedding parameters, reconstructed state spaces, recurrence plots and recurrence quantification analysis. Additionally, this thesis presents three dimensional surface plots of recurrence quantification analysis with which to consider the variation of embedded parameters and recurrence thresholds. These show that three dimensional surface plots of Shannon entropy might be a suitable approach to understand the dynamics of real-world time series data. This thesis opens new avenues of applications in human-humanoid interaction where humanoid robots can be pre-programmed with nonlinear analysis algorithms to evaluate, for instance, the improvement of movement performances, to quantify and provide feedback of skill learning or to quantify movement adaptations and pathologies.



#### Acknowledgements

I would like to acknowledge to both the Mexican National Council of Science and Technology and the University of Birmingham that funded my curiosity-driven PhD degree. To Professor Chris Baber for supervising my scientific endeavours and who wisely loosed the leash in any of my explorations so as to take me back at the right time to write up this thesis. To Professor Martin J Russell who, in the first year of my PhD, helped with his acute comments and critics to make a better use of the language of mathematics. To Mourad Oussalah who kindly dedicate his time to discuss my research interests and our collaboration with three peer-reiview conference papers. I would also like to thank to Dr. Dolores Columba Perez Flores for her valuable comments that help me to have a better insight on nonlinear analysis, and to Constantino Antonio Garcia Martinez for developing the nonlinearTseries R package that was of significant help to accelerate the results of this thesis. Last but not least, many thanks to Patricia Herterich, from Library Services of the University of Birmingham, who helped me to find the first published phd dissertations in 1901 and e-thesis in 2011 which allow me to state that this thesis is the first Open Access PhD thesis at the University of Birmingham.

> Miguel Xochicale Birmingham, UK May 2019

| Li | st of | figure    | s   | XV |  |  |
|----|-------|-----------|---|----|--|--|
| 1  | Intr  | roduction |   |    |  |  |
|    | 1.1   | Backg     | round   | 1  |  |  |
|    | 1.2   | Mover     | nent variability                                    | 3  |  |  |
|    |       | 1.2.1     | Modelling human movement variability                | 4  |  |  |
|    |       | 1.2.2     | Movement variability in human-humanoid interaction  | 9  |  |  |
|    | 1.3   | Resear    | rch questions                                       | 13 |  |  |
|    | 1.4   | Outlin    | ne of the thesis                                    | 15 |  |  |
|    | 1.5   | Public    | eations   | 17 |  |  |
|    | 1.6   | Open      | access PhD thesis                                   | 18 |  |  |
| 2  | Qua   | antifyii  | ng Movement Variability                             | 19 |  |  |
|    | 2.1   | Introd    | luction   | 19 |  |  |
|    | 2.2   | Funda     | mentals of time-series analysis                     | 19 |  |  |
|    |       | 2.2.1     | Linear and non-linear systems                       | 20 |  |  |
|    |       | 2.2.2     | Stationary and non-stationary signals               | 20 |  |  |
|    |       | 2.2.3     | Deterministic and stochastic systems                | 20 |  |  |
|    |       | 2.2.4     | Deterministic-chaotic time series                   | 21 |  |  |
|    | 2.3   | Quant     | ifving movement variability with nonlinear analysis | 21 |  |  |

|   |     | 2.3.1   | What to quantify in movement variability?                       | 23 |
|---|-----|---------|---|----|
|   |     | 2.3.2   | Which methods of nonlinear analysis are appropriate to quantify |    |
|   |     |         | movement variability?   | 24 |
|   | 2.4 | Nonlin  | near analysis with real-world data                              | 27 |
|   |     | 2.4.1   | Non-stationarity  | 28 |
|   |     | 2.4.2   | Data length   | 29 |
|   |     | 2.4.3   | Sampling rate   | 30 |
|   |     | 2.4.4   | Noise   | 30 |
|   | 2.5 | Final   | remarks   | 32 |
| 3 | Nor | ılinear | Analysis  | 33 |
|   | 3.1 | Introd  | luction   | 33 |
|   | 3.2 | State   | Space Reconstruction Theorem                                    | 34 |
|   | 3.3 | Unifor  | rm Time-Delay Embedding (UTDE)                                  | 35 |
|   | 3.4 | Estima  | ation of Embedding Parameters                                   | 37 |
|   |     | 3.4.1   | False Nearest Neighbours (FNN)                                  | 39 |
|   |     | 3.4.2   | Average Mutual Information (AMI)                                | 42 |
|   |     | 3.4.3   | Overall minimum embedding parameters                            | 44 |
|   | 3.5 | Recon   | structed State Space with UTDE                                  | 45 |
|   | 3.6 | Recur   | rence Plots (RP)  | 45 |
|   |     | 3.6.1   | Structures of Recurrence Plots                                  | 47 |
|   | 3.7 | Recur   | rence Quantifications Analysis (RQA)                            | 49 |
|   |     | 3.7.1   | Measures of RP based on the recurrence density                  | 49 |
|   |     | 3.7.2   | Measures of RP based on diagonal lines                          | 49 |
|   |     | 3.7.3   | Some weaknesses and strengths of RP and RQA                     | 50 |
|   |     | 3.7.4   | 3D surface plots of RQA   | 51 |
|   | 3.8 | Final : | remarks   | 54 |

| 4 | Exp | erime    | nts                                  | 55 |
|---|-----|----------|--------------------------------------|----|
|   | 4.1 | Aims     |                                      | 55 |
|   | 4.2 | Partic   | ipants                               | 56 |
|   |     | 4.2.1    | Human-image imitation activities     | 56 |
|   |     | 4.2.2    | Human-humanoid imitation activities  | 56 |
|   | 4.3 | Equip    | ment                                 | 57 |
|   | 4.4 | Ethics   | 3                                    | 57 |
|   | 4.5 | Exper    | iments                               | 57 |
|   |     | 4.5.1    | Human-image imitation activities     | 57 |
|   |     | 4.5.2    | Human-humanoid imitation activities  | 59 |
|   | 4.6 | Proces   | ssing of time series                 | 62 |
|   |     | 4.6.1    | Raw time-series                      | 62 |
|   |     | 4.6.2    | Postprocessing time-series           | 64 |
|   |     | 4.6.3    | Window size of time-series           | 64 |
|   |     | 4.6.4    | Normalization of time-series         | 65 |
|   |     | 4.6.5    | Smoothing time-series                | 65 |
| 5 | Qua | antifyir | ng Human-Image Imitation Activities  | 67 |
|   | 5.1 | Introd   | luction                              | 67 |
|   | 5.2 | Time     | series                               | 68 |
|   | 5.3 | Minim    | num Embedding Parameters             | 71 |
|   |     | 5.3.1    | Average minimum embedding parameters | 73 |
|   | 5.4 | Recon    | structed state spaces with UTDE      | 73 |
|   | 5.5 | Recur    | rences Plots                         | 79 |
|   | 5.6 | Recur    | rence Quantification Analysis        | 85 |
|   | 5.7 | Weakr    | nesses and strengths of RQA          | 89 |
|   |     | 5.7.1    | Sensors and activities               | 91 |

|                  |      | 5.7.2   | Window size  | . 97  |
|------------------|------|---------|--|-------|
|                  |      | 5.7.3   | Smoothness   | . 97  |
|                  |      | 5.7.4   | Participants   | . 100 |
|                  |      | 5.7.5   | Final remarks  | . 102 |
| 6                | Qua  | ntifyii | ng Human-Humanoid Imitation Activities                     | 103   |
|                  | 6.1  | Introd  | luction  | . 103 |
|                  | 6.2  | Time    | series   | . 104 |
|                  | 6.3  | Minim   | num Embedding Parameters                                   | . 107 |
|                  |      | 6.3.1   | Average minimum embedding parameters                       | . 109 |
|                  | 6.4  | Recon   | structed state spaces with UTDE                            | . 109 |
|                  | 6.5  | Recur   | rences Plots   | . 113 |
|                  | 6.6  | Recur   | rence Quantification Analysis                              | . 116 |
|                  | 6.7  | Weakı   | nesses and strengths of RQA                                | . 119 |
|                  |      | 6.7.1   | Sensors and activities                                     | . 121 |
|                  |      | 6.7.2   | Window size  | . 121 |
|                  |      | 6.7.3   | Smoothness   | . 125 |
|                  |      | 6.7.4   | Participants   | . 125 |
|                  |      | 6.7.5   | Final remarks  | . 128 |
| 7                | Con  | clusio  | ns and future work   | 129   |
|                  | 7.1  | Concl   | usions   | . 129 |
|                  | 7.2  | Future  | e work   | . 132 |
| $\mathbf{A}_{]}$ | ppen | dix A   | Examples of Uniform Time-Delay Embedding                   | 139   |
|                  | A.1  | 20 san  | nple length vector.  | . 139 |
|                  | Δ 2  | Timo    | series for horizontal movement of a triavial accelerometer | 1/1   |

| Appen | dix B Equipment                                  | 145 |
|-------|--|-----|
| B.1   | NeMEMsi IMU sensors                              | 145 |
|       | B.1.1 Issues with IMUs                           | 147 |
| B.2   | Time-series preprocessing                        | 148 |
|       | B.2.1 Organising Data in Multidimensional Arrays | 148 |
|       | B.2.2 Data Synchronisation                       | 148 |
|       | B.2.3 Time Alignment                             | 149 |
| В.3   | NAO – humanoid robot                             | 150 |
| Appen | dix C Experiment Design                          | 151 |
| C.1   | Experiment Check List                            | 151 |
| C.2   | Information Sheet                                | 151 |
| Appen | dix D Additional Results for HII experiment      | 157 |
| D.1   | Time Series                                      | 157 |
| D.2   | Embedding parameters                             | 164 |
|       | D.2.1 Minimum dimension embedding values         | 164 |
|       | D.2.2 Minimum delay embedding values             | 169 |
| D.3   | RSSs   | 174 |
| D.4   | RPs  | 183 |
| D.5   | RQAs   | 188 |
|       | D.5.1 REC values                                 | 188 |
|       | D.5.2 DET values                                 | 191 |
|       | D.5.3 RATIO values                               | 194 |
|       | D.5.4 ENTR values                                | 197 |
| Appen | dix E Additional results for HHI experiment      | 201 |
| E 1   | Time Series                                      | 201 |

| E.2    | Embed  | dding parameters                   | . 208 |
|--------|--------|------------------------------------|-------|
|        | E.2.1  | Minimum dimension embedding values | . 208 |
|        | E.2.2  | Minimum delay embedding values     | . 211 |
| E.3    | RSSs   |                                    | . 214 |
| E.4    | RPs    |                                    | . 219 |
| E.5    | RQAs   |                                    | . 224 |
|        | E.5.1  | REC values                         | . 224 |
|        | E.5.2  | DET values                         | . 225 |
|        | E.5.3  | RATIO values                       | . 227 |
|        | E.5.4  | ENTR values                        | . 228 |
| Appen  | dix F  | Open Access Code and Data          | 231   |
| F.1    | Code a | and data organisation              | . 231 |
| F.2    | How re | esults can be replicated           | . 232 |
| Refere | nces   |                                    | 233   |

# List of figures

| 1.1 | Thesis outline  | 16 |
|-----|---|----|
| 3.1 | State space reconstruction methodology                        | 36 |
| 3.2 | Uniform time-delay embedding                                  | 38 |
| 3.3 | Minimum dimension embedding values with Cao's method          | 41 |
| 3.4 | Minimum delay embedding values with AMI's method              | 43 |
| 3.5 | Recurrence Plots  | 47 |
| 3.6 | Patterns in Recurrence Plots                                  | 48 |
| 3.7 | 3D surface plots  | 53 |
| 4.1 | Human-image imitation (HII) activities                        | 59 |
| 4.2 | Time series for horizontal and vertical arm movements         | 60 |
| 4.3 | Human-humanoid imitation activities                           | 61 |
| 4.4 | Time series duration of horizontal and vertical arm movements | 63 |
| 5.1 | Time series for horizontal arm movements                      | 69 |
| 5.2 | Time series for vertical arm movements                        | 70 |
| 5.3 | Box plots for minimum embedding dimensions                    | 72 |
| 5.4 | Box plots for 1st minimum AMI                                 | 72 |
| 5.5 | RSSs for horizontal arm movements (no beat)                   | 75 |
| 5.6 | RSSs for horizontal arm movements (with beat)                 | 76 |

#### List of figures

| 5.7  | RSSs for vertical arm movements (no beat)   | 77  |
|------|---|-----|
| 5.8  | RSSs for vertical arm movements (with beat)                                       | 78  |
| 5.9  | RPs for horizontal arm movements (no beat)  | 81  |
| 5.10 | RPs for horizontal arm movements (with beat)                                      | 82  |
| 5.11 | RPs for vertical arm movements (no beat)  | 83  |
| 5.12 | RPs for vertical arm movements (with beat) $\dots \dots \dots$                    | 84  |
| 5.13 | Box plots of RQA values for horizontal arm movements                              | 87  |
| 5.14 | Box plots for RQA values for vertical arm movements                               | 88  |
| 5.15 | 3D surface plots of RQA metrics   | 90  |
| 5.16 | $3\mathrm{D}$ surface plots of RQA metrics for horizontal arm movements with HS01 | 93  |
| 5.17 | $3\mathrm{D}$ surface plots of RQA metrics for horizontal arm movements with HS02 | 94  |
| 5.18 | $3\mathrm{D}$ surface plots of RQA metrics for vertical arm movements with HS01   | 95  |
| 5.19 | 3D surface plots of RQA metrics for vertical arm movements with $HS02$            | 96  |
| 5.20 | 3D surface plots of RQA metrics for different window lengths                      | 98  |
| 5.21 | 3D surface plots of RQA metrics with three levels of smoothness                   | 99  |
| 5.22 | 3D surface plots of RQA metrics with four participants                            | 101 |
| 6.1  | Time series for horizontal arm movements  | .05 |
| 6.2  | Time series for vertical arm movements  | .06 |
| 6.3  | Box plots of minimum embedding parameters   | .08 |
| 6.4  | RSSs for horizontal arm movements   | 11  |
| 6.5  | RSSs for vertical arm movements   | .12 |
| 6.6  | RPs for horizontal arm movements  | .14 |
| 6.7  | RPs for vertical arm movements  | .15 |
| 6.8  | Box plots for RQA values  | .18 |
| 6.9  | 3D surface plots for RQA metrics  | 20  |
| 6.10 | 3D surface plots of RQA metrics for HS01 sensor                                   | 22  |

| 6.11 3D surface plots of RQA metrics for RS01 sensor                                  | 23         |
|---|------------|
| 6.12 3D surface plots of RQAs metrics with four window lengths                        | 24         |
| $6.13~3 \mathrm{D}$ surface plots of RQA metrics with three levels of smoothness $12$ | 26         |
| 6.14 3D surface plots of RQA metrics with three participants                          | 27         |
| A.1 Examples of time series with an IMU   | 3          |
| B.1 Inertial Measurament Sensor   | Ł7         |
| B.2 NAO, humanoid robot from SoftBank   | 0          |
| C.1 Experiment Check List   | 52         |
| C.2 Participant Information Sheet (p. 1/4)  | 3          |
| C.3 Participant Information Sheet (p. 2/4)  | 4          |
| C.4 Participant Information Sheet (p. 3/4)  | 5          |
| C.5 Participant Information Sheet (p. 4/4)  | 6          |
| D.1 Time series for horizontal arm movements (sg0)                                    | 8          |
| D.2 Time series for horizontal arm movements (sg1)                                    | 9          |
| D.3 Time series for horizontal arm movements (sg2)                                    | 0          |
| D.4 Time series for vertical arm movements (sg0)                                      | <b>3</b> 1 |
| D.5 Time series for vertical arm movements (sg1)                                      | 52         |
| D.6 Time series for vertical arm movements (sg2)                                      | 3          |
| D.7 Minimum embedding dimensions for horizontal arm movements (no beat) 16            | i5         |
| D.8 Minimum embedding dimensions for horizontal arm movements (with                   |            |
| beat)   | 6          |
| D.9 Minimum embedding dimensions for vertical arm movements (no beat) 16              | <b>i</b> 7 |
| D.10 Minimum embedding dimensions for vertical arm movements (with beat) 16           | 8          |
| $\mathrm{D.11}$ First minimum AMI values for horizontal arm movements (no beat) 17    | 0'         |
| D 12 First minimum AMI values for horizontal arm movements (with heat) 17             | 71         |

#### List of figures

| D.13 First minimum AMI values for vertical arm movements (no beat) 172                   |
|--|
| $\rm D.14\;First\;minimum\;AMI\;values\;for\;vertical\;arm\;movements\;(with\;beat)$ 173 |
| D.15 RSSs for horizontal normal arm movements (no beat) 175                              |
| D.16 RSSs for horizontal normal arm movements (with beat) 176                            |
| D.17 RSSs for horizontal faster arm movements (no beat) 177                              |
| D.18 RSSs for horizontal faster arm movements (with beat)                                |
| D.19 RSSs for vertical normal arm movements (no beat) 179                                |
| D.20 RSSs for vertical normal arm movements (with beat)                                  |
| D.21 RSSs for vertical faster arm movements (no beat)                                    |
| D.22 RSSs for vertical faster arm movements (with beat)                                  |
| D.23 RPs for horizontal normal arm movements   |
| D.24 RPs for horizontal faster arm movements   |
| D.25 RPs for vertical normal arm movements   |
| D.26 RPs for vertical faster arm movements   |
| D.27 REC values for horizontal arm movements   |
| D.28 REC values for vertical arm movements   |
| D.29 DET values for horizontal arm movements   |
| D.30 DET values for vertical arm movements   |
| D.31 RATIO values for horizontal arm movements   |
| D.32 RATIO values for vertical arm movements   |
| D.33 ENTR values for horizontal arm movements  |
| D.34 ENTR values for vertical arm movements  |
| E.1 Time series for horizontal arm movements (sg0)                                       |
| E.2 Time series for horizontal arm movements (sg1) 203                                   |
| E.3 Time series for horizontal arm movements (sg2)                                       |
| E.4 Time series for vertical arm movements (sg0)   |

| E.5 Time series for vertical arm movements (sg1)                 |
|--|
| E.6 Time series for vertical arm movements (sg2)                 |
| E.7 Minimum embedding dimensions for horizontal arm movements 20 |
| E.8 Minimum embedding dimensions for vertical arm movements 21   |
| E.9 First minimum AMI values for horizontal arm movements        |
| E.10 First minimum AMI values for vertical arm movements         |
| E.11 RSSs for horizontal normal arm movements                    |
| E.12 RSSs for horizontal faster arm movements                    |
| E.13 RSSs for vertical normal arm movements                      |
| E.14 RSSs for vertical faster arm movements                      |
| E.15 RPs for horizontal normal arm movements                     |
| E.16 RPs for horizontal faster arm movements                     |
| E.17 RPs for vertical normal arm movements                       |
| E.18 RPs for vertical faster arm movements                       |
| E.19 REC values for horizontal arm movements                     |
| E.20 REC values for vertical arm movements                       |
| E.21 DET values for horizontal arm movements                     |
| E.22 DET values for vertical arm movements                       |
| E.23 RATIO values for horizontal arm movements                   |
| E.24 RATIO values for vertical arm movement                      |
| E.25 ENTR values for horizontal arm movements                    |
| E.26 ENTR values for vertical arm movements                      |